



KGT METAL MESH FILTER



ABOUT

The KGT Wire Mesh Metal Filter cartridge has a rigid pore structure enabling removal of particles at higher differential pressures with consistent efficiency.

Apart from the wide chemical compatibility, the filters are suitable for either gas or liquid having a high dirt holding capacity.

The KGT Wire Mesh Metal Filter cartridge is available in SS304/SS316 and SS316L.

ADVANTAGES

- Due to wide range to media selection, a variety of liquids from acids to alkalis; from seawater to process water; and in gases from air to fuel gas to hot exhaust gases.
- Standard dimensions of 2.5" outer diameter and 1" internal diameter ensures fitment in most standard housings with varied length availability. (Other dimensions are available on request)
- Available in 10 / 20 / 30 / 40 / 60 inches length. (Other lengths available on request.)
- Solid internal core ensures optimal strength and withstanding of differential pressure.

DIFFERENTIAL PRESSURE DATA

For Normal Flow from Outside to Inside for liquids compatible with the filter media, the maximum differential pressure is 1.5 bard (22 psid) @ 75°C.

APPLICATIONS

Corrosive Fluids

Steam

Amine, Glycol

Thermic Fluids

High Temperature applications in liquids and gases





KGT METAL MESH FILTER

PART NUMBERING GUIDE

Filter Element Part Number : KGT - ● - ■ - M - ▲ - ◆

Short Code	Description	Short Code	Description
010	1 μ m	020	2 μ m
030	3 μ m	050	5 μ m
100	10 μ m	200	20 μ m
300	30 μ m	400	40 μ m
500	50 μ m	700	70 μ m
1000	100 μ m	2000	200 μ m

(Other Removal Ratings are available as per requirements)

Short Code	Description
	Length (inches)
10	10
20	20
30	30
40	40
60	60



Short Code	Filter Media	Short Code	Filter
	Material Of Construction		Fitment Style
SS	SS304	7	Size 226 double O-rings, flat top
SST	SS316	0	Double Open end with Gaskets
		3	SOE with NPT Threads

KLENGAS TECH LLP

6, Anurag, Rajaji Path, Ramnagar, Dombivli, Mumbai, 421201, Maharashtra, India
 ☎ +91 251 2420878 📠 +91 9166 593 315 ✉ solutions@klengas.com