TCPServer.py

```
import socket

try:
    # Create server socket
    server = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    server.bind(("localhost", 5000))
    server.listen(1)
    print("Server is waiting for client...")

    # Accept client connection
    conn, addr = server.accept()
    print("Client connected!")

    # Receive message from client
    message = conn.recv(1024).decode()
    print("Client:", message)

    # Send response to client
    conn.sendall(b"Hello from Server!")

    # Close connections
    conn.close()
    server.close()

except Exception as e:
    print(e)
```

TCPClient.py

```
import socket

try:
    # Connect to server
    client = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    client.connect(("localhost", 5000))
    print("Connected to server!")

    # Send message to server
    client.sendall(b"Hello Server!\n")

    # Receive response from server
    response = client.recv(1024).decode()
    print("Server:", response)

    # Close connection
    client.close()

except Exception as e:
    print(e)
```

UDPServer.py

```
import socket

# Create UDP socket
server_socket = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)

# Set server address
server_address = ("127.0.0.1", 8080)

# Bind socket
server_socket.bind(server_address)

print("UDP Server started on port 8080...")
print("Waiting for client message...")

# Receive message from client
buffer, client_address = server_socket.recvfrom(1024)
print("Message from client:", buffer.decode())

# Send response
response = "Hello from UDP Server!"
server_socket.sendto(response.encode(), client_address)
print("Response sent to client.")

# Close socket
server_socket.close()
```

UDPClient.py

```
import socket

# Create UDP socket
client_socket = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)

# Server address
server_address = ("127.0.0.1", 8080)

# Message to send
message = "Hello from UDP Client!"

# Send message to server
client_socket.sendto(message.encode(), server_address)
print("Message sent to server:", message)

# Receive response from server
buffer, address = client_socket.recvfrom(1024)
print("Response from server:", buffer.decode())

# Close socket
client_socket.close()
```