FastAPI

From Fundamentals to Production

A Practical Backend Development Guide

A complete learning resource compiled from the substantive FastAPI teaching in our learning session.

Compiled from our complete FastAPI learning session

Table of Contents

Table of Contents 2

Backend & HTTP Foundations 6

1.1 What a backend API does . . . 6

1.2 HTTP methods . . . 6

1.3 REST and resources . . . 6

1.4 JSON . . . 7

1.5 Status codes . . . 7

Python Foundations Used Heavily in FastAPI 8

2.1 Comprehensions . . . 8

2.2 map, filter, lambda and pipelines . . . 8

2.3 sorted(key=...) and enumerate() . . . 8

2.4 Type hints and generics . . . 8

2.5 Protocol versus Java interfaces . . . 9

Pydantic: Data Models and Validation 10

3.1 BaseModel, defaults, and optional fields . . . 10

3.2 Field constraints . . . 10

3.3 EmailStr and richer validation . . . 10

3.4 Nested/list models . . . 10

3.5 model_dump() and ** . . . 10

3.6 Request schemas versus response schemas . . . 11

Async Python and Concurrency 12

4.1 async def and await . . . 12

4.2 Blocking versus non-blocking . . . 12

4.3 Concurrency versus parallelism . . . 12

4.4 asyncio.gather() . . . 12

HTTP Clients and External APIs with HTTPX 13

5.1 Requests, params, JSON and headers . . . 13

5.2 AsyncClient and raise_for_status() . . . 13

5.3 Timeouts . . . 13

5.4 Retries, backoff, and idempotency . . . 13

FastAPI Routes, Parameters, OpenAPI and Project Structure 15

6.1 First route . . . 15

6.2 Path, query and body parameters . . . 15

6.3 APIRouter . . . 15
6.4 OpenAPI, /docs and /redoc . . . 15
6.5 response_model . . . 16
6.6 Project structure and Uvicorn . . . 16
Dependency Injection with Depends **17**
7.1 The basic idea . . . 17
7.2 Database session dependency . . . 17
7.3 Nested dependencies . . . 17
Errors, Validation, Logging and Middleware **19**
8.1 HTTPException . . . 19
8.2 Validation and 422 . . . 19
8.3 Global exception handlers . . . 19
8.4 Middleware . . . 19
8.5 Middleware versus exception handlers . . . 20
8.6 Logging . . . 20
Authentication and Authorization **21**
9.1 OAuth2PasswordBearer . . . 21
9.2 JWT verification . . . 21
9.3 Roles and permissions . . . 21
9.4 401 versus 403 . . . 21
9.5 Password hashing . . . 21
9.6 Access and refresh tokens . . . 21
9.7 Security as dependency composition . . . 22
Database Architecture: Router → Service → Repository **23**
10.1 Router responsibilities . . . 23
10.2 Service responsibilities . . . 23
10.3 Repository responsibilities . . . 23
10.4 Session lifecycle . . . 23
10.5 Transactions . . . 24
SQLAlchemy 2.x: Models and Queries **25**
11.1 Declarative model . . . 25
11.2 select(), execute(), scalars() . . . 25
11.3 scalar_one_or_none() . . . 25
11.4 PostgreSQL connection setup . . . 25
11.5 Async SQLAlchemy . . . 25

Relationships, Foreign Keys, Joins, Loading and N+1 **26**

12.1 One-to-many . . . 26

12.2 Creating related objects . . . 26

12.3 SQL joins . . . 26

12.4 SQLAlchemy joins . . . 26

12.5 Lazy loading and N+1 . . . 26

12.6 Eager loading . . . 27

Alembic and Database Migrations **28**

13.1 Why migrations exist . . . 28

13.2 Typical workflow . . . 28

13.3 Migration history . . . 28

Testing FastAPI Applications **29**

14.1 Unit tests versus API tests . . . 29

14.2 TestClient . . . 29

14.3 Validation tests . . . 29

14.4 Authentication and authorization tests . . . 29

14.5 Dependency overrides . . . 29

Debugging Lessons from the Learning Project **30**

15.1 psycopg2 single-parameter tuples . . . 30

15.2 index 0 is falsy . . . 30

15.3 Response model mismatch . . . 30

15.4 SQLAlchemy/ORM versus in-memory assumptions . . . 30

15.5 Logging that appears to disappear . . . 30

End-to-End Architecture and Production Thinking **31**

16.1 Request lifecycle . . . 31

16.2 Security lifecycle . . . 31

16.3 External service lifecycle . . . 31

16.4 Production concerns . . . 31

16.5 Docker/deployment mental model . . . 32

Final Reference and Mental Checklists **33**

17.1 Core patterns . . . 33

17.2 Pydantic . . . 33

17.3 SQLAlchemy . . . 33

17.4 HTTPX . . . 33

17.5 Testing . . . 33

17.6 New-endpoint checklist 33

Java / Spring Boot Translation Guide **35**

Chapter 1

Backend & HTTP Foundations

FastAPI sits on top of HTTP. A good backend developer therefore needs a mental model of requests, responses, resources, JSON, methods, and status codes before framework-specific features become meaningful.

1.1 What a backend API does

A backend receives a request from a browser, mobile app, another service, or an API client. It interprets the request, performs application logic, reads or changes data, and returns a response. FastAPI gives us a concise way to describe that HTTP interface while also providing validation, dependency injection, serialization, and OpenAPI generation.



Typical request path

1.2 HTTP methods

GET normally retrieves a representation, POST commonly creates a resource or triggers an operation, PUT replaces a representation, PATCH partially updates it, and DELETE removes it. These are semantic conventions, not direct translations to database commands.

- GET → read
- POST → create
- PUT → replace/update
- PATCH → partial update
- DELETE → delete

> Remember HTTP method is not a database command
>
> The method communicates intended semantics. The application still decides what work the endpoint performs.

1.3 REST and resources

REST is a style of designing network APIs around resources and their representations. The goal is a predictable interface rather than a collection of arbitrary command-like URLs.

```
GET    /posts
GET    /posts/42
POST   /posts
PUT    /posts/42
DELETE /posts/42
```

1.4 JSON

JSON is a common representation for API data. FastAPI can parse incoming JSON into Pydantic models and serialize Python data into JSON responses.

```
{
  "title": "Learning FastAPI",
  "content": "Build APIs step by step",
  "published": true
}
```

1.5 Status codes

Status codes are part of the API contract. Clients use them to distinguish success, validation problems, authentication failures, missing resources, and server errors.

- 200 OK
- 201 Created
- 204 No Content
- 400 Bad Request
- 401 Missing/invalid authentication
- 403 Authenticated but forbidden
- 404 Resource not found
- 422 Validation failure commonly produced by FastAPI/Pydantic
- 500 Unexpected server failure

> **Common Mistake Returning an error with HTTP 200**
>
> Returning "Not Found!" with status 200 makes the client interpret failure as success. Prefer an explicit HTTPException with 404 when the resource is missing.

Chapter 2

Python Foundations Used Heavily in FastAPI

Several Python features repeatedly appeared in the course because they make backend code compact and expressive.

2.1 Comprehensions

List, set, and dictionary comprehensions express iterate/filter/transform operations concisely.

```
names = ["alice", "bob", "carol"]

upper_names = [name.upper() for name in names]
long_names = [name for name in names if len(name) > 3]
name_lengths = {name: len(name) for name in names}
```

2.2 map, filter, lambda and pipelines

Functions are first-class values in Python. map() transforms, filter() selects, and lambda creates a small anonymous function. Comprehensions are often clearer for simple cases, but understanding these tools helps when reading existing code.

```
numbers = [1, 2, 3, 4, 5]

doubled = list(map(lambda x: x * 2, numbers))
evens = list(filter(lambda x: x % 2 == 0, numbers))

# Often clearer:
doubled = [x * 2 for x in numbers]
evens = [x for x in numbers if x % 2 == 0]
```

2.3 sorted(key=...) and enumerate()

```
users = [{"name":"Alice","age":35},{"name":"Bob","age":28}]
users_by_age = sorted(users, key=lambda user: user["age"])

for index, post in enumerate(posts):
    print(index, post)
```

2.4 Type hints and generics

Type hints describe intended types and improve editor support and static analysis. They do not by themselves perform runtime validation.

```
from typing import Optional

def get_users() -> list[str]:
    return ["alice", "bob"]

def find_user(user_id: int) -> Optional[str]:
    return None
```

2.5 Protocol versus Java interfaces

Protocol expresses structural typing: an object is compatible when it provides the required members. Java interfaces are nominally implemented. This makes Protocol useful for dependency abstractions without forcing inheritance.

```
from typing import Protocol

class UserRepository(Protocol):
    def find_by_username(self, username: str):
        ...

def authenticate(repo: UserRepository, username: str):
    return repo.find_by_username(username)
```

> **Important Static checking versus runtime validation**
>
> mypy/Pyright inspect code statically. Pydantic validates actual values at runtime. FastAPI uses Pydantic to establish a runtime boundary between untrusted request data and application logic.

Chapter 3

Pydantic: Data Models and Validation

Pydantic is the data-contract layer used heavily by FastAPI. It turns Python type declarations into runtime validation and serialization rules.

3.1 BaseModel, defaults, and optional fields

```
from pydantic import BaseModel

class PostCreate(BaseModel):
    title: str
    content: str
    published: bool = True
    rating: int | None = None
```

Required fields have no default. A default value makes a field optional from the client perspective. A union such as int | None means the value may be an integer or None.

3.2 Field constraints

```
from pydantic import BaseModel, Field

class UserCreate(BaseModel):
    username: str = Field(min_length=3, max_length=50)
    age: int = Field(ge=18)
```

3.3 EmailStr and richer validation

```
from pydantic import BaseModel, EmailStr

class UserCreate(BaseModel):
    email: EmailStr
```

Pydantic also supports validators and nested models when validation needs to express more than primitive constraints.

3.4 Nested/list models

```
class Address(BaseModel):
    city: str
    country: str

class UserCreate(BaseModel):
    name: str
    addresses: list[Address]
```

3.5 model_dump() and **

```
post_data = post.model_dump()
new_post = models.Post(**post_data)
```

model_dump() converts a Pydantic model to a Python dictionary. The ** operator unpacks that dictionary into keyword arguments. Conceptually, {"title":"Hello","content":"World"} becomes Post(title="Hello", content="World").

3.6 Request schemas versus response schemas

A create request should not necessarily contain database-generated fields. A response may expose id and created_at even though the client never submits them. Separate schemas make the API contract safer and clearer.

```
class PostCreate(BaseModel):
    title: str
    content: str

class PostResponse(BaseModel):
    model_config = ConfigDict(from_attributes=True)

    id: int
    title: str
    content: str
```

> **Remember Pydantic model ≠ SQLAlchemy model**
>
> Pydantic describes data crossing an application boundary. SQLAlchemy models describe persistence. They are complementary, not interchangeable.

Chapter 4

Async Python and Concurrency

Async programming matters because backend applications frequently wait for I/O. The goal is to let the event loop work on other tasks while one operation is waiting.

4.1 async def and await

```
async def get_data():
    result = await some_io_operation()
    return result
```

async def defines a coroutine function. await suspends that coroutine until the awaited operation completes, allowing other tasks to make progress.

4.2 Blocking versus non-blocking

```
import asyncio
import time

async def good():
    await asyncio.sleep(1)

async def bad():
    time.sleep(1)
```

> **Common Mistake Blocking inside an async path**
>
> An async function is not automatically non-blocking. A synchronous database driver, blocking HTTP client, or CPU-heavy operation can still block the event loop.

4.3 Concurrency versus parallelism

Concurrency means tasks can make progress during overlapping periods. Parallelism means work literally executes at the same time, usually on multiple CPU cores. Asyncio primarily helps with I/O-bound concurrency; it is not a magic solution for CPU-heavy work.

4.4 asyncio.gather()

```
results = await asyncio.gather(
    fetch_user(),
    fetch_posts(),
    fetch_permissions(),
)
```

When independent operations can run concurrently, gather can reduce total waiting time compared with sequential awaits.

Chapter 5

HTTP Clients and External APIs with HTTPX

A FastAPI application may itself call other APIs. HTTPX gives the application synchronous and asynchronous HTTP clients.

5.1 Requests, params, JSON and headers

```
import httpx

response = httpx.get(
    "https://example.com/users",
    params={"page": 1},
    headers={"Accept": "application/json"},
)

print(response.status_code)
data = response.json()
```

5.2 AsyncClient and raise_for_status()

```
async with httpx.AsyncClient() as client:
    response = await client.get(
        "https://example.com/users",
        params={"page": 1},
    )

response.raise_for_status()
data = response.json()
```

params becomes the query string. headers become HTTP headers. response.json() parses JSON. raise_for_status() raises for 4xx/5xx responses so callers do not silently treat an error response as successful data.

5.3 Timeouts

```
timeout = httpx.Timeout(10.0)

async with httpx.AsyncClient(timeout=timeout) as client:
    response = await client.get(url)
```

A timeout prevents a dependency from waiting forever and consuming application capacity.

5.4 Retries, backoff, and idempotency

Retries are appropriate only for failures likely to be transient and operations whose side effects can safely be repeated. A retry policy should consider method idempotency, status/exception type, maximum attempts, and backoff.

```
attempt = 0
while attempt < max_attempts:
    try:
        response = await call_remote_service()
        response.raise_for_status()
        break
    except TransientError:
        attempt += 1
```

```
        await asyncio.sleep(backoff(attempt))
```

Best Practice Treat external services as unreliable

Use explicit timeouts, sensible retry policies, clear error handling, and useful logs. Never assume a network call will always succeed quickly.

Chapter 6

FastAPI Routes, Parameters, OpenAPI and Project Structure

FastAPI turns Python functions into HTTP endpoints. Type annotations and Pydantic models let the framework infer and document much of the API contract.

6.1 First route

```
from fastapi import FastAPI

app = FastAPI()

@app.get("/")
async def root():
    return {"message": "Hello World!"}
```

6.2 Path, query and body parameters

```
@app.get("/posts/{post_id}")
def get_post(post_id: int, published: bool | None = None):
    ...

@app.post("/posts")
def create_post(post: PostCreate):
    ...
```

A value appearing in the path is a path parameter. A normal typed scalar parameter is commonly interpreted as a query parameter. A Pydantic model parameter is commonly parsed from the JSON body.

6.3 APIRouter

```
from fastapi import APIRouter

router = APIRouter(prefix="/posts", tags=["Posts"])

@router.get("/")
def get_posts():
    ...

@router.post("/")
def create_post(post: PostCreate):
    ...

from .routers import post
app.include_router(post.router)
```

Routers organize endpoints by feature. Prefixes and tags reduce repetition and improve OpenAPI documentation.

6.4 OpenAPI, /docs and /redoc

FastAPI generates an OpenAPI schema from the routes, parameters, models, dependencies, and response declarations. Swagger UI is normally available at /docs and ReDoc at /redoc. The documentation is therefore connected directly to the code contract rather than being maintained separately.

6.5 response_model

```
@app.get("/posts/{post_id}", response_model=PostResponse)
def get_post(post_id: int):
    return db_post
```

The response model documents, validates, and serializes the declared response shape. It also helps prevent accidental leakage of internal fields.

6.6 Project structure and Uvicorn

```
app/
├── main.py
├── database.py
├── models.py
├── schemas.py
├── routers/
│   ├── post.py
│   ├── user.py
│   └── auth.py
└── ...

python -m uvicorn app.main:app --reload
```

Uvicorn uses module:attribute. If the FastAPI instance is app inside app/main.py, app.main:app is the natural import path.

Chapter 7

Dependency Injection with Depends

FastAPI dependency injection makes common infrastructure and security logic reusable and keeps endpoints focused on their actual work.

7.1 The basic idea

```
from fastapi import Depends

def get_current_user():
    ...

@app.get("/me")
def read_me(user = Depends(get_current_user)):
    return user
```

Pass the dependency function itself to Depends; do not call it. FastAPI controls when it runs and injects its result.

7.2 Database session dependency

```
def get_db():
    db = SessionLocal()
    try:
        yield db
    finally:
        db.close()

@app.get("/posts")
def get_posts(db: Session = Depends(get_db)):
    ...
```

FastAPI executes setup, yields the session to the request, then resumes the dependency so the finally block closes it.

7.3 Nested dependencies

```
oauth2_scheme = OAuth2PasswordBearer(tokenUrl="/login")

def get_current_user(token: str = Depends(oauth2_scheme)):
    return verify_token_and_load_user(token)

def require_admin(user = Depends(get_current_user)):
    if "admin" not in user.roles:
        raise HTTPException(status_code=403, detail="Forbidden")
    return user
```

Dependencies form a graph. An authorization dependency can depend on current-user authentication, which can depend on token extraction.



Dependency lifecycle

Chapter 8

Errors, Validation, Logging and Middleware

A production API needs consistent failure behavior and observability. FastAPI provides explicit mechanisms for request validation, HTTP exceptions, global exception handlers, middleware, and integration with Python logging.

8.1 HTTPException

```
if post is None:
    raise HTTPException(
        status_code=404,
        detail="Post not found",
    )
```

Raising HTTPException stops normal endpoint processing and produces an HTTP error response.

8.2 Validation and 422

FastAPI validates path/query/body inputs before endpoint logic when their declarations require it. Pydantic validation failures therefore commonly appear as 422 responses.

8.3 Global exception handlers


```
@app.exception_handler(MyDomainError)
async def domain_error_handler(request: Request, exc: MyDomainError):
    return JSONResponse(
        status_code=400,
        content={"detail": str(exc)},
    )
```

This is conceptually similar to Spring @RestControllerAdvice and @ExceptionHandler: an application exception is translated into a consistent HTTP response.

8.4 Middleware

```
@app.middleware("http")
async def log_requests(request: Request, call_next):
    response = await call_next(request)
    return response
```

Middleware wraps HTTP processing and can run code before and after the downstream application. It is useful for request logging, timing, request IDs, CORS, and other broad HTTP concerns.



Middleware wraps request processing

8.5 Middleware versus exception handlers

Middleware is about cross-cutting HTTP behavior. Exception handlers are about converting specific exceptions into HTTP responses. Business rules and resource authorization generally belong in dependencies/services rather than global middleware.

8.6 Logging

```
import logging
logger = logging.getLogger(__name__)

logger.info("Creating post")
logger.warning("Remote service is slow")

try:
    ...
except Exception:
    logger.exception("Unexpected failure")
```

logger.exception() records the exception and traceback. With an ASGI server such as Uvicorn, application logging also interacts with server logging configuration, so missing logs should be debugged by checking levels, handlers, propagation, and server configuration.

Chapter 9

Authentication and Authorization

Authentication answers “Who are you?” Authorization answers “What are you allowed to do?” Keeping those concepts separate is the foundation of secure API design.

9.1 OAuth2PasswordBearer

```
from fastapi.security import OAuth2PasswordBearer

oauth2_scheme = OAuth2PasswordBearer(tokenUrl="/login")

def get_current_user(token: str = Depends(oauth2_scheme)):
    ...
```

OAuth2PasswordBearer extracts the bearer token and contributes a security scheme to OpenAPI. It does not itself verify a JWT signature or claims.

9.2 JWT verification

A JWT can contain claims such as subject, expiration, issuer, audience, and application-specific information. Authentication logic must verify the signature and the relevant claims before treating the caller as authenticated.

```
def get_current_user(token: str = Depends(oauth2_scheme)):
    payload = verify_jwt(token)
    user_id = payload["sub"]
    return load_user(user_id)
```

9.3 Roles and permissions

Roles group capabilities, such as admin or manager. Permissions are more granular, such as post:delete. Either model can be valid; the authorization decision should ultimately answer whether the identity may perform the concrete action on the concrete resource.

9.4 401 versus 403

- 401 means valid authentication is missing or invalid.
- 403 means identity is established but access is forbidden.

> **Remember Authentication first, authorization second**
>
> Never use a role check as a substitute for validating the caller’s credentials.

9.5 Password hashing

Passwords should never be stored as plaintext. Password-hashing algorithms make guessing expensive; the stored value is a hash and login verifies a submitted password against it.

9.6 Access and refresh tokens

Access tokens are normally short-lived credentials used to call APIs. Refresh tokens can be longer-lived and used to obtain new access tokens. Separate lifetimes reduce exposure while preserving a usable session.

9.7 Security as dependency composition

```
def get_current_user(token: str = Depends(oauth2_scheme)):
    ...

def require_permission(user = Depends(get_current_user)):
    ...

@router.delete("/posts/{post_id}")
def delete_post(post_id: int, user = Depends(require_permission)):
    ...
```




Security dependency chain

Chapter 10

Database Architecture: Router → Service → Repository

The course used a layered mental model to separate HTTP concerns from business rules and persistence. The goal is clear responsibility, not ceremony.



A practical layered backend

10.1 Router responsibilities

Routers handle HTTP-specific concerns: path/query/body parameters, response models, status codes, and request-facing dependencies. They should not become a dumping ground for complicated business rules.

10.2 Service responsibilities

Services represent application use cases and business rules. A service can coordinate multiple repositories, external API calls, authorization decisions, and transaction boundaries.

10.3 Repository responsibilities

A repository is a persistence-oriented abstraction. It can hide query details from the service when that abstraction genuinely improves maintainability. For a small project, a formal repository layer is optional.

10.4 Session lifecycle

```
def get_db():
    db = SessionLocal()
    try:
        yield db
    finally:
        db.close()

# endpoint
def create_user(user_data: UserCreate, db: Session = Depends(get_db)):
    user = User(**user_data.model_dump())
    db.add(user)
    db.commit()
    db.refresh(user)
    return user
```

For a Java developer, SQLAlchemy Session is a useful conceptual analogue to a JPA persistence context/EntityManager.

10.5 Transactions

```
with db.begin():
    db.add(user)
    db.add(post)
```

A transaction groups related operations so they succeed or fail together. The boundary should normally correspond to a meaningful business operation.

Chapter 11

SQLAlchemy 2.x: Models and Queries

Modern SQLAlchemy uses explicit SQL expression objects such as select(). Understanding the result API is essential for writing predictable repository code.

11.1 Declarative model

```
from sqlalchemy.orm import DeclarativeBase, Mapped, mapped_column

class Base(DeclarativeBase):
    pass

class User(Base):
    __tablename__ = "users"

    id: Mapped[int] = mapped_column(primary_key=True)
    username: Mapped[str]
```

11.2 select(), execute(), scalars()

```
stmt = select(User)
result = db.execute(stmt)
users = result.scalars().all()
```

select(User) builds the statement. execute runs it. scalars extracts User objects from result rows. all collects them.

11.3 scalar_one_or_none()

```
stmt = select(User).where(User.username == username)
user = db.execute(stmt).scalar_one_or_none()
```

This communicates the expectation of zero or one matching result. Multiple matches indicate an unexpected data/query condition instead of silently selecting an arbitrary row.

11.4 PostgreSQL connection setup

```
DATABASE_URL = "postgresql+psycopg2://postgres:postgres@localhost/fastapi"

engine = create_engine(DATABASE_URL)
SessionLocal = sessionmaker(bind=engine)
```

11.5 Async SQLAlchemy

```
from sqlalchemy.ext.asyncio import AsyncSession

async def get_user(db: AsyncSession, user_id: int):
    result = await db.execute(
        select(User).where(User.id == user_id)
    )
    return result.scalar_one_or_none()
```

Async database access requires an async-capable driver/session and explicit awaits. Making the route async does not turn a synchronous database driver into an asynchronous one.

Chapter 12

Relationships, Foreign Keys, Joins, Loading and N+1

Relational data becomes practical when database relationships and object-level relationships are understood together.

12.1 One-to-many

```
class User(Base):
    __tablename__ = "users"
    id: Mapped[int] = mapped_column(primary_key=True)
    posts = relationship("Post", back_populates="owner")

class Post(Base):
    __tablename__ = "posts"
    id: Mapped[int] = mapped_column(primary_key=True)
    owner_id: Mapped[int] = mapped_column(ForeignKey("users.id"), nullable=False)
    owner = relationship("User", back_populates="posts")
```

The foreign key belongs on the many side. A user can own many posts; each post has one owner.

12.2 Creating related objects

```
new_post = models.Post(
    **post.model_dump(),
    owner_id=user_id,
)
db.add(new_post)
db.commit()
db.refresh(new_post)
```

12.3 SQL joins

```
SELECT *
FROM posts p
INNER JOIN users u
    ON p.owner_id = u.id;
```

The ON clause states how rows are related. Omitting the relationship condition can produce a Cartesian product.

12.4 SQLAlchemy joins

```
stmt = (
    select(Post)
    .join(Post.owner)
    .where(User.username == username)
)
posts = db.execute(stmt).scalars().all()
```

12.5 Lazy loading and N+1

Lazy loading can issue another query when a relationship is accessed. If one query loads N users and then each user's posts causes another query, the application performs 1 + N database round trips. This is the N+1 problem.



The N+1 pattern

12.6 Eager loading

```
from sqlalchemy.orm import selectinload

stmt = select(User).options(selectinload(User.posts))
users = db.execute(stmt).scalars().all()

stmt = select(User).options(joinedload(User.profile))
```

selectinload often works well for collections by fetching related rows in a separate efficient query. joinedload uses a join. The correct strategy depends on relationship shape and how much data the endpoint actually needs.

> **Best Practice Choose loading deliberately**
>
> Avoid both accidental N+1 queries and indiscriminate eager loading. Measure query shape and load only what the use case needs.

Chapter 13

Alembic and Database Migrations

Schema evolution is part of application delivery. Alembic gives SQLAlchemy projects versioned migrations, similar in purpose to Flyway or Liquibase in Java.

13.1 Why migrations exist

Changing a SQLAlchemy model changes Python code, not existing databases. If a users table needs a new email column, the schema must be changed in a controlled way across development, test, and production. A migration records that transition.

13.2 Typical workflow

```
alembic init alembic

alembic revision --autogenerate -m "add email to users"

alembic upgrade head
```

> **Important** Review autogenerated migrations
>
> Autogenerate produces a candidate migration. It cannot perfectly understand intent, especially for renames, data transformations, constraints, and destructive changes. Review the migration before applying it.

13.3 Migration history

Migration files live in source control and let an environment move through known schema versions. This makes database evolution repeatable instead of dependent on manual edits.



Application code and schema evolution

Chapter 14

Testing FastAPI Applications

Testing was treated as an API contract problem as well as a unit-testing problem. FastAPI makes HTTP-level testing straightforward.

14.1 Unit tests versus API tests

Unit tests isolate business behavior. API tests exercise routing, parsing, validation, dependencies, authentication, authorization, and response serialization. The distinction is similar to focused JUnit tests versus controller/API tests with MockMvc.

14.2 TestClient

```
from fastapi.testclient import TestClient

client = TestClient(app)

def test_read_root():
    response = client.get("/")
    assert response.status_code == 200
    assert response.json() == {"message": "Hello World!"}
```

14.3 Validation tests

```
def test_create_post_rejects_invalid_payload():
    response = client.post("/posts", json={"title": 123})
    assert response.status_code in (400, 422)
```

Tests should assert the application's actual contract. The important idea is that invalid input is rejected at the boundary rather than causing a confusing downstream error.

14.4 Authentication and authorization tests

Test missing/invalid credentials, valid credentials, and authenticated users without required permissions. Both the identity boundary and access-control boundary deserve tests.

14.5 Dependency overrides

```
app.dependency_overrides[get_current_user] = lambda: fake_user
try:
    response = client.get("/admin")
finally:
    app.dependency_overrides.clear()
```

Dependency overrides make it possible to replace real databases, external services, or authentication dependencies during tests.

Chapter 15

Debugging Lessons from the Learning Project

The course included concrete bugs that are valuable because they expose small language/framework details that are easy to overlook.

15.1 psycopg2 single-parameter tuples

```
# Wrong: parentheses alone do not create a tuple
cursor.execute("SELECT * FROM posts WHERE id = %s", (id))

# Correct
cursor.execute("SELECT * FROM posts WHERE id = %s", (id,))
```

The comma creates the one-element tuple. This is a Python syntax detail, not a database-specific rule.

15.2 index 0 is falsy

```
# Wrong if 0 is a valid index
if not index:
    ...

# Correct
if index is None:
    ...
```

Zero is falsy. Explicitly compare with None when None means “missing”.

15.3 Response model mismatch

A PUT endpoint can fail response validation if it declares a response model containing id and created_at but returns a create model that does not contain them. The fix is to return the correct persisted object or response schema, not to remove validation.

15.4 SQLAlchemy/ORM versus in-memory assumptions

Once a project moves from an in-memory list to a database, code that assumes list indexes, immediate mutation, or Python-only object state may no longer describe what the database actually contains. Query the database and use explicit transaction/session behavior.

15.5 Logging that appears to disappear

If logging.basicConfig(level=logging.INFO) appears ineffective under Uvicorn, inspect the server’s logging setup and logger hierarchy. Prefer module-level loggers and verify that the effective level and handlers permit the message through.

Chapter 16

End-to-End Architecture and Production Thinking

The separate concepts now fit together into one request lifecycle. The goal is a mental model that helps diagnose new code rather than memorizing framework APIs.

16.1 Request lifecycle



Typical layered request flow


A request enters through HTTP. FastAPI matches the route, parses and validates inputs, resolves dependencies, and calls application logic. The service applies business rules. SQLAlchemy performs persistence work. The response object is validated/serialized according to the response model and returned as JSON.

16.2 Security lifecycle



Authentication establishes identity; authorization evaluates access

16.3 External service lifecycle



Remote API calls should have explicit boundaries

16.4 Production concerns

- Configuration should come from environment/configuration rather than hard-coded secrets.

- Database schema changes should be versioned with migrations.
- External calls should have timeouts and carefully designed retries.
- Logs should contain enough context to diagnose failures without exposing secrets.
- Authentication and authorization should be tested as part of the API contract.
- Queries should be reviewed for N+1 behavior and unnecessary round trips.
- Transactions should have deliberate boundaries.
- Response models should prevent accidental data exposure.

16.5 Docker/deployment mental model

Containerization packages an application and its runtime environment so the application can be started consistently across environments. A Docker daemon is the local service responsible for building/running containers; if Docker commands fail because the daemon is unavailable, that is an infrastructure/runtime problem rather than a FastAPI route bug. The application itself should still be designed independently of the local container tooling.

Chapter 17

Final Reference and Mental Checklists

Use this chapter for review after studying the detailed explanations above.

17.1 Core patterns

```
from fastapi import Depends, FastAPI, HTTPException
from fastapi.security import OAuth2PasswordBearer

app = FastAPI()
oauth2_scheme = OAuth2PasswordBearer(tokenUrl="/login")

@app.get("/posts/{post_id}", response_model=PostResponse)
def get_post(post_id: int, db: Session = Depends(get_db)):
    post = ...
    if post is None:
        raise HTTPException(status_code=404, detail="Post not found")
    return post
```

17.2 Pydantic

```
class PostCreate(BaseModel):
    title: str
    content: str
    published: bool = True

class PostResponse(BaseModel):
    model_config = ConfigDict(from_attributes=True)
    id: int
    title: str
    content: str
```

17.3 SQLAlchemy

```
stmt = select(User).where(User.username == username)
user = db.execute(stmt).scalar_one_or_none()

stmt = select(User).options(selectinload(User.posts))
users = db.execute(stmt).scalars().all()
```

17.4 HTTPX

```
async with httpx.AsyncClient(timeout=10.0) as client:
    response = await client.get(url, params=params, headers=headers)
    response.raise_for_status()
    data = response.json()
```

17.5 Testing

```
client = TestClient(app)

def test_get_post():
    response = client.get("/posts/1")
    assert response.status_code == 200
```

17.6 New-endpoint checklist

- HTTP: What method and resource does this endpoint represent?
- Input: What comes from path, query, headers, and body?

- Validation: What Pydantic constraints apply?
- Security: Who is the caller and what may they do?
- Business logic: What belongs in the service?
- Persistence: What query and transaction are required?
- Performance: Could this create N+1 queries?
- External calls: Are timeouts/retries defined?
- Response: What schema and status code should be returned?
- Observability: What should be logged?
- Testing: What success, validation, auth, authorization and failure cases matter?

> **Remember FastAPI is the framework; the architecture is yours**
>
> FastAPI supplies routing, validation, dependency injection, OpenAPI, and an ASGI foundation. A production backend still requires deliberate business boundaries, persistence design, security, observability, testing, and operational discipline.

Appendix

Java / Spring Boot Translation Guide

Because the learning process used existing Java/Spring knowledge as a bridge, these mappings can help transfer the mental model without pretending the frameworks are identical.

FastAPI / Python	Java / Spring Boot	Mental model
FastAPI route decorator	@GetMapping / @PostMapping	HTTP endpoint declaration
Pydantic BaseModel	DTO + Bean Validation	API data contract + runtime validation
Depends(...)	Spring dependency injection	Framework supplies dependencies
SQLAlchemy Session	EntityManager / persistence context	Database interaction context
SQLAlchemy model	JPA entity	Persistence mapping
Alembic	Flyway / Liquibase	Versioned schema migrations
HTTPException	ResponseStatusException	HTTP error response
exception_handler	@RestControllerAdvice / @ExceptionHandler	Exception → response
APIRouter	Controller organization	Feature-level endpoint grouping
JWT verification	Spring Security JWT decoder	Token validation
TestClient	MockMvc-style API testing	Exercise HTTP boundary
async/await	Async/reactive concepts (not identical)	Non-blocking I/O

End of guide