# Decentralized Cultural Archives: Preserving Persian Heritage on Censorship-Resistant Infrastructure

## Content-Addressed Storage and Incentive Design for the Pars Network

Cyrus Pahlavi, Pars Teamresearch@pars.id

February 2026

**Abstract**

We present ParsArchive, a decentralized cultural preservation system for Persian heritage built on censorship-resistant infrastructure. ParsArchive combines content-addressed storage (IPFS and Arweave) with rich preservation metadata, community-driven curation, tiered access control, and economic incentives for translation and annotation. The system preserves six categories of Persian cultural material: literary works, historical documents, audiovisual recordings, oral histories, calligraphic art, and scholarly works. We design a metadata schema based on Dublin Core with Persian-specific extensions for script variants, dialectal provenance, and cultural context. Access control employs attribute-based encryption enabling nuanced permissions: some materials are fully public, others restricted to verified community members, and sensitive materials (e.g., documenting human rights violations) available only to authorized researchers. We introduce a translation bounty mechanism that incentivizes multilingual access to archived materials. The system currently holds 2.4 million objects totaling 18 TB across 340 archive nodes in 22 countries, with measured retrieval latency of 2.1 seconds at the 95th percentile and proven resistance to targeted takedown attempts in simulation.

# 1 Introduction

Cultural preservation is an existential concern for diaspora communities. The Persian cultural heritage—encompassing one of the world's oldest continuous literary traditions [Yarshater, 1988]—faces multiple threats: physical destruction through conflict and natural disaster, digital censorship by governments that restrict access to cultural materials deemed subversive [Anderson and Murdoch, 2013], and gradual loss as diaspora generations lose connection to their heritage [Naficy, 1993].

Centralized digital archives (Internet Archive, Google Books, national libraries) provide valuable preservation but are vulnerable to takedown requests, sanctions-related access restrictions, and organizational failure. The Internet Archive's legal challenges [Hachette v. Internet Archive, 2023] and the loss of numerous smaller Persian cultural websites demonstrate the fragility of centralized approaches.

## 1.1 Scope of Persian Cultural Heritage

The materials requiring preservation span millennia:

Table 1: Persian Cultural Heritage Categories

| Category | Est. Items | Period | Examples |
|---|---|---|---|
| Classical literature | 50,000+ | 900–1900 CE | Shahnameh, Divan-e Hafez |
| Modern literature | 200,000+ | 1900–present | Novels, poetry, short stories |
| Historical documents | 100,000+ | 500 BCE–present | Royal decrees, treaties |
| Audiovisual | 500,000+ | 1900–present | Films, music, broadcasts |
| Oral histories | 50,000+ | 1900–present | Interviews, testimonies |
| Calligraphy/art | 100,000+ | 700–present | Manuscripts, miniatures |
| Scholarly works | 300,000+ | 800–present | Scientific, philosophical |

## 1.2 Contributions

(i) **Hybrid Storage Architecture:** A tiered storage system using IPFS for frequently accessed content and Arweave for permanent archival, with Pars Network nodes providing a censorship-resistant caching layer.

(ii) **Persian Metadata Schema:** Extensions to Dublin Core for Persian-specific bibliographic needs including script variants, dialectal provenance, ezafe-aware title indexing, and cultural context annotations.

(iii) **Attribute-Based Access Control:** Fine-grained permissions using ciphertext-policy attribute-based encryption (CP-ABE) enabling context-dependent access without centralized authorization.

(iv) **Translation Bounty System:** An economic mechanism incentivizing community translation of archived materials into diaspora host languages.

(v) **Provenance and Integrity:** Merkle-tree based provenance tracking ensuring archived materials are authentic and unmodified.

# 2 Related Work

## 2.1 Digital Preservation

The OAIS reference model [ISO 14721, 2012] defines the standard framework for digital preservation systems. The Library of Congress Digital Preservation Program [Library of Congress, 2023] and the Internet Archive [Kahle, 1996] demonstrate centralized approaches at scale. LOCKSS (Lots of Copies Keep Stuff Safe) [Reich and Rosenthal, 2001] pioneers decentralized preservation using peer-to-peer replication among libraries.

## 2.2 Decentralized Storage

IPFS [Benet, 2014] provides content-addressed storage with peer-to-peer distribution. Filecoin [Protocol Labs, 2017] adds economic incentives for persistent storage. Arweave [Williams et al., 2019] offers permanent storage through a novel "blockweave" data structure with a one-time payment model. Ceramic Network [Ceramic, 2021] provides mutable document streams on IPFS.

## 2.3 Cultural Heritage Digitization

UNESCO's Memory of the World program [UNESCO, 2023] and Europeana [Europeana, 2023] represent institutional approaches to cultural digitization. Community-driven projects like Project Gutenberg [Hart, 1992] demonstrate the potential of volunteer effort. The Afghan Digital Library [NYU, 2020] provides a precedent for conflict-zone cultural preservation.

# 3 Storage Architecture

## 3.1 Tiered Storage

ParsArchive uses a three-tier storage architecture:

**Definition 1** (Storage Tiers).

- ***Tier 1 (Hot):*** *Pars Network archive nodes. Content replicated across $r = 5$ geographically diverse nodes. Provides low-latency retrieval. Funded by ASHA staking rewards.*
- ***Tier 2 (Warm):*** *IPFS network with Filecoin persistence deals. Content-addressed and globally accessible. Storage paid through periodic deal renewals.*
- ***Tier 3 (Cold):*** *Arweave permanent storage. One-time payment for provably permanent storage. Used for materials deemed permanently valuable by community curation.*

**Algorithm 1** Object Ingestion Pipeline

**Require:** Cultural object $O$ (content + metadata), submitter $S$
**Ensure:** Object archived across storage tiers

**Phase 1: Validation**
$hash \leftarrow \mathcal{H}(\mathsf{Serialize}(O.content))$
Verify $O$ not already in archive (dedup by hash)
Validate metadata schema compliance
Check submitter permissions ($S$ has valid Pars ID)
**Phase 2: Processing**
Extract text via OCR if applicable
Generate thumbnails/previews
Normalize metadata (Section 4)
Apply access control policy (Section 5)
**Phase 3: Storage**
Pin to Tier 1 (Pars archive nodes): $\mathsf{ParsPin}(O, r = 5)$
Add to IPFS with Filecoin deal: $\mathsf{FilDeal}(O, duration = 3\text{yr})$
**if** $O.tier3_eligible$ **then** ▷ Community curated
    Upload to Arweave: $\mathsf{ArweaveStore}(O)$
**end if**
**Phase 4: Indexing**
Index in search system with full-text and metadata search
Register in provenance chain
Emit $\mathsf{ObjectArchived}(O.hash, S, \mathsf{now}())$

### 3.2 Replication Strategy

Table 2: Replication Parameters by Content Type

| Content Type | Tier 1 (Pars) | Tier 2 (IPFS) | Tier 3 (AR) | Total | Durability |
|---|---|---|---|---|---|
| Classical literature | 7 | 3 | 1 | 11 | 99.9999% |
| Modern literature | 5 | 3 | Optional | 8+ | 99.999% |
| AV recordings | 5 | 2 | Optional | 7+ | 99.999% |
| Oral histories | 7 | 3 | 1 | 11 | 99.9999% |
| Scholarly works | 5 | 3 | Optional | 8+ | 99.999% |
| Sensitive materials | 5 | 0 | 0 | 5 | 99.99% |

Sensitive materials (human rights documentation, political dissident works) are stored only on Tier 1 with access control, as IPFS and Arweave storage could expose content to adversaries.

### 3.3 Censorship Resistance

**Theorem 1** (Takedown Resistance)**.** *For an object with $r$ replicas distributed across $k$ jurisdictions, the probability of successful takedown by a single-jurisdiction adversary is bounded by:*

$$P(takedown) \leq \left(\frac{n_j}{N}\right)^{\lceil r/2 \rceil + 1} \tag{1}$$

*where $n_j$ is the number of nodes in the adversary's jurisdiction and $N$ is the total node count.*

*Proof.* A takedown requires removing the object from at least $\lceil r/2 \rceil + 1$ replicas (to exceed the retrieval threshold). Each replica is uniformly distributed across nodes. The probability that a

specific replica is in the adversary's jurisdiction is $n_j/N$. The probability that $\lceil r/2 \rceil + 1$ or more replicas are in the adversary's jurisdiction follows from the binomial distribution, bounded by the stated expression. □

With $r = 7$, $k = 22$ jurisdictions, and the largest jurisdiction hosting 15% of nodes:

$$P(\text{takedown}) \leq 0.15^4 = 5.06 \times 10^{-4} \tag{2}$$

# 4 Metadata Schema

## 4.1 Persian Dublin Core Extensions

We extend Dublin Core [DCMI, 2020] with Persian-specific elements:

Table 3: Persian Metadata Extensions

| Field | Type | Description |
|---|---|---|
| `pars:script` | Enum | nastaliq, naskh, shekasteh, latin |
| `pars:dialect` | Enum | iranian, dari, tajiki, mixed |
| `pars:era` | String | Hijri-Shamsi, Hijri-Qamari, Gregorian |
| `pars:originalScript` | URI | Reference to original manuscript scan |
| `pars:ezafeTitle` | String | Title with explicit ezafe marking |
| `pars:translitTitle` | String | Romanized title |
| `pars:culturalContext` | Text | Cultural significance annotation |
| `pars:oralSource` | Object | Speaker, location, recording method |
| `pars:calligraphyStyle` | Enum | nastaliq, sols, naskh, etc. |
| `pars:preservationUrgency` | Enum | critical, high, medium, low |
| `pars:accessSensitivity` | Enum | public, community, restricted, sealed |
| `pars:diasporaRelevance` | Float | 0.0–1.0 diaspora relevance score |

## 4.2 Provenance Tracking

Each archived object maintains a provenance chain recording its history:

**Algorithm 2** Provenance Chain Update

**Require:** Object $O$, action $a$, actor $A$
**Ensure:** Provenance chain extended

```
prev_hash ← O.provenance[last].hash
entry ← {
    action : a,                                  ▷ ingest, annotate, translate, curate, access
    actor : A.did,
    timestamp : now(),
    details : ActionDetails(a),
    prev : prev_hash
}
entry.hash ← H(Serialize(entry))
entry.signature ← Sign(A.sk, entry.hash)
O.provenance.append(entry)
```

# 5 Access Control

## 5.1 Attribute-Based Encryption

ParsArchive uses ciphertext-policy attribute-based encryption (CP-ABE) [Bethencourt et al., 2007] for fine-grained access control:

**Definition 2** (Access Policy)**.** *An access policy $\mathcal{P}$ is a boolean formula over attributes. Attributes include:*

- `community_member`*: Has verified Pars identity.*
- `researcher`*: Has academic affiliation attestation.*
- `diaspora_{region}`*: Located in specific diaspora region.*
- `language_{lang}`*: Speaks specified language.*
- `contributor`*: Has contributed to the archive.*
- `elder`*: Recognized community elder (reputation $\geq$ threshold).*

Example policies:

- Public domain literature: `TRUE` (no encryption, fully public).
- Community-only content: `community_member`.
- Sensitive oral history: `researcher` $\wedge$ (`community_member` $\vee$ `contributor`).
- Sealed testimony: `researcher` $\wedge$ `elder` $\wedge$ $\neg$`diaspora_iran`.

**Algorithm 3** CP-ABE Encryption for Archive Object

**Require:** Content $C$, access policy $\mathcal{P}$, ABE master public key $mpk$
**Ensure:** Encrypted content $\hat{C}$ accessible only to users with matching attributes

```
k ← Random(32)                                  ▷ Symmetric content key
Ĉ_sym ← AES256GCM.Enc(k, C)                     ▷ Encrypt content
k̂ ← CPABE.Enc(mpk, P, k)                        ▷ Encrypt key under policy
return (Ĉ_sym, k̂, P)
```

## 5.2 Decentralized Key Management

The ABE master key is distributed across the Pars Network's governance committee using threshold secret sharing:

- Master key is split into $n = 7$ shares with threshold $t = 4$.
- Key shares are held by Guardian Council members.
- Attribute keys are issued by any $t$ guardians collectively.
- Key revocation uses epoch-based re-keying (quarterly).

# 6 Translation Bounty System

## 6.1 Mechanism Design

The translation bounty system incentivizes community members to translate archived materials:

**Algorithm 4** Translation Bounty Workflow

**Require:** Archived object $O$, target language $L$, bounty amount $B$ ASHA
**Ensure:** Translation produced and verified

**Phase 1: Bounty Creation**
Community member or governance creates bounty for $(O, L)$
$B$ ASHA locked in bounty escrow
Bounty published with deadline $T$
**Phase 2: Translation Submission**
Translator $T_1$ submits translation $tr_1$
Quality score: $q_1 \leftarrow \mathsf{AutoScore}(tr_1, O)$ ▷ ParsLM quality assessment
**if** $q_1 < q_{\min}$ **then**
    Reject and allow resubmission
**end if**
**Phase 3: Peer Review**
$k = 3$ bilingual reviewers independently score translation
$score \leftarrow \mathsf{MedianScore}(r_1, r_2, r_3)$
**Phase 4: Payment**
**if** $score \geq \theta_{\text{accept}}$ **then**
    Pay $B$ to translator, $B_r$ to each reviewer from bounty pool
    Archive translation with provenance link to original
**else**
    Allow revision or reassign bounty
**end if**

## 6.2 Bounty Pricing

Table 4: Translation Bounty Base Rates

| Content Type | Per Word (ASHA) | Complexity | Reviewer Rate | Typical Total |
|---|---|---|---|---|
| Modern prose | 0.05 | Low | 0.01/word | 600 ASHA/10K word |
| Poetry | 0.15 | High | 0.03/word | 1,800 ASHA/10K wor |
| Academic | 0.10 | Medium | 0.02/word | 1,200 ASHA/10K wor |
| Legal/historical | 0.12 | Medium-High | 0.025/word | 1,450 ASHA/10K wor |
| Oral history (transcript) | 0.08 | Medium | 0.02/word | 1,000 ASHA/10K wor |

## 6.3 Quality Assurance

Translation quality is assessed through three mechanisms:

1. **Automated scoring:** ParsLM evaluates fluency, adequacy, and consistency using reference-free quality estimation.
2. **Peer review:** Bilingual community members rate accuracy and cultural appropriateness.
3. **Community feedback:** Post-publication ratings from users who access the translation.

Translator reputation is updated based on review scores and community feedback, affecting future bounty eligibility and rates.

# 7 Community Curation

## 7.1 Curation DAO

Material selection for permanent archival (Tier 3) is governed by a specialized curation DAO:

**Algorithm 5** Curation Process

**Require:** Candidate object $O$ for Tier 3 promotion
**Ensure:** Community decision on permanent archival

```
Curator C nominates O with justification
C stakes 50 ASHA as curation bond
Assessment period (7 days):
    Domain experts (literature, history, art) review
    Community members comment and signal support
Curation vote (3 days):
    Quadratic voting among veASHA holders
    Category-specific experts have 2× weight
if Vote passes (>60% support, >5% quorum) then
    Approve Tier 3 storage
    Fund Arweave upload from archive treasury
    Return curation bond + 10 ASHA reward
else
    Object remains at Tier 1+2
    Return curation bond (no reward)
end if
```

## 7.2 Curation Categories

Table 5: Curation Criteria by Category

| Category | Primary Criteria | Expert Panel | Threshold |
|---|---|---|---|
| Classical literature | Literary significance, rarity | 3 scholars | 60% |
| Modern literature | Cultural impact, risk of loss | 3 critics | 60% |
| Historical documents | Historical value, authenticity | 3 historians | 70% |
| Audiovisual | Cultural significance, quality | 3 archivists | 60% |
| Oral histories | Witness importance, uniqueness | 3 scholars | 50% |
| Calligraphy/art | Artistic value, provenance | 3 art experts | 70% |

# 8 Search and Discovery

## 8.1 Multilingual Search

ParsArchive provides search across all archived materials in Persian (all dialects), English, German, French, and Turkish:

**Algorithm 6** Cross-Lingual Search

**Require:** Query $q$ in language $L_q$, user attributes $A$
**Ensure:** Ranked results accessible to user

```
q_norm ← ParsNormalize(q) if L_q is Persian
q_embed ← ParsLMEmbed(q)                                  ▷ Cross-lingual embedding
candidates ← ANN_Search(q_embed, k = 100)
results ← ∅
for O ∈ candidates do
    if CheckAccess(A, O.policy) then
        score ← Relevance(q_embed, O.embed) · Quality(O)
        results.add((O, score))
    end if
end for
return Sort(results)[: 20]
```

### 8.2 Collection Browsing

Curated collections organized by theme, period, and cultural significance:

Table 6: Featured Collections

| Collection | Objects | Languages | Access |
|---|---|---|---|
| Classical Poetry Canon | 12,400 | 4 | Public |
| 20th Century Iranian Cinema | 3,200 | 2 | Community |
| Persian Calligraphy Masters | 8,700 | 1 | Public |
| Oral Histories of Revolution | 4,100 | 2 | Restricted |
| Diaspora Literary Voices | 6,800 | 6 | Public |
| Scientific Heritage | 15,200 | 3 | Public |
| Women's Movement Archive | 2,900 | 3 | Community |
| Music Traditions | 7,400 | 2 | Public |

## 9 Evaluation

### 9.1 Archive Statistics

Table 7: Current Archive Statistics

| Metric | Value | Growth/month |
|---|---|---|
| Total objects | 2,400,000 | +45,000 |
| Total storage | 18 TB | +800 GB |
| Archive nodes | 340 | +12 |
| Countries | 22 | +1 |
| Unique contributors | 4,200 | +180 |
| Translations | 28,000 | +1,200 |
| Active bounties | 450 | – |
| Tier 3 (permanent) | 89,000 | +2,800 |

### 9.2 Retrieval Performance

Table 8: Content Retrieval Latency (seconds)

| Content Type | Size | P50 | P90 | P95 | P99 |
|---|---|---|---|---|---|
| Text document | 50 KB | 0.3 | 0.8 | 1.2 | 2.4 |
| Image (calligraphy) | 5 MB | 0.8 | 1.6 | 2.1 | 4.2 |
| Audio recording | 50 MB | 2.1 | 4.8 | 6.2 | 12.0 |
| Video (SD) | 500 MB | 8.4 | 18.0 | 24.0 | 45.0 |
| Full book (PDF) | 20 MB | 1.2 | 2.8 | 3.6 | 7.2 |

### 9.3 Censorship Resistance Evaluation

We simulated targeted takedown attacks against specific archived materials:

Table 9: Takedown Resistance Simulation Results

| Attack Scope | Nodes Compromised | Content Available | Recovery Time |
|---|---|---|---|
| Single jurisdiction | 12% of nodes | 100% | 0 (no impact) |
| Two jurisdictions | 25% of nodes | 100% | 0 (no impact) |
| Three jurisdictions | 38% of nodes | 99.8% | <1 hour |
| Global CDN takedown | IPFS gateways | 100% (Tier 1) | 0 |
| Coordinated (5 countries) | 52% of nodes | 97.2% | <4 hours |

### 9.4 Translation Bounty Effectiveness

Table 10: Translation Bounty Program Results (12 months)

| Language Pair | Bounties | Completed | Avg Quality | Avg Cost | Avg Time |
|---|---|---|---|---|---|
| Persian → English | 320 | 285 | 4.2/5 | 480 ASHA | 8 days |
| Persian → German | 180 | 142 | 4.0/5 | 520 ASHA | 11 days |
| Persian → French | 120 | 98 | 4.1/5 | 500 ASHA | 10 days |
| Persian → Turkish | 85 | 72 | 3.9/5 | 420 ASHA | 7 days |
| Dari → Persian | 60 | 55 | 4.4/5 | 280 ASHA | 5 days |
| Tajiki → Persian | 40 | 34 | 4.3/5 | 300 ASHA | 6 days |

### 9.5 Comparison with Existing Archives

Table 11: Comparison with Cultural Archive Systems

| Feature | ParsArchive | Internet Archive | Arweave | LOCKSS | Europeana |
|---|---|---|---|---|---|
| Decentralized | Yes | No | Yes | Partial | No |
| Censorship-resistant | Yes | No | Yes | Partial | No |
| Persian-optimized | Yes | No | No | No | No |
| Access control | CP-ABE | Basic | No | IP-based | Basic |
| Translation incentives | Yes | No | No | No | Partial |
| Community curation | Yes | No | No | Library-led | Curated |
| Permanent storage | Arweave tier | At risk | Yes | Replicated | Institutional |
| Search (Persian) | Optimized | Basic | No | No | Basic |

## 10 Integrity Verification

### 10.1 Merkle DAG Verification

Every archived object is stored as a Merkle DAG with content-addressed nodes. Verification proceeds bottom-up:

**Algorithm 7** Content Integrity Verification

**Require:** Object CID $c$, retrieved content $C$, Merkle DAG $D$
**Ensure:** Content matches claimed CID

```
Parse D into nodes {n_1, ..., n_k}
for each leaf node n_i do
    h_i ← H(n_i.data)
    Verify h_i = n_i.claimed_hash
end for
for each internal node n_j (bottom-up) do
    h_j ← H(n_j.children_hashes || n_j.metadata)
    Verify h_j = n_j.claimed_hash
end for
Verify root hash = c
return VALID if all checks pass
```

**Theorem 2** (Tamper Detection)**.** *Any modification to archived content is detected with probability* $1 - 2^{-256}$ *under the collision resistance of SHA-256.*

*Proof.* Content integrity relies on the collision resistance of SHA-256 used in CIDv1 computation. For any content $C$ and tampered content $C' \neq C$, finding $\mathcal{H}(C) = \mathcal{H}(C')$ requires $O(2^{128})$ operations (birthday bound). The Merkle DAG structure ensures that modifying any leaf propagates hash changes to the root, requiring the adversary to find a collision at the root level. The root CID is recorded on the Pars blockchain, which provides Byzantine fault tolerance for $f < n/3$ validators. Therefore, successful tampering requires both a SHA-256 collision and corruption of the blockchain record, an event with negligible probability. □

### 10.2 Cross-Tier Consistency

Objects stored across multiple tiers must maintain consistency. We verify this periodically:

**Algorithm 8** Cross-Tier Consistency Check

**Require:** Object $O$ stored on tiers $\{T_1, T_2, T_3\}$
**Ensure:** All tier copies are consistent

```
for each tier pair (T_i, T_j) do
    h_i ← FetchHash(O, T_i)
    h_j ← FetchHash(O, T_j)
    if h_i ≠ h_j then
        Flag inconsistency
        Initiate repair from authoritative tier (Arweave if available)
    end if
end for
Report consistency status to provenance chain
```

Consistency checks run weekly on a random 10% sample and monthly on the full archive. Over 18 months of operation, 23 inconsistencies were detected (all caused by transient IPFS pinning failures), with 100% successful repair from Arweave or peer Pars nodes.

# 11 Economic Sustainability

## 11.1 Storage Cost Model

Long-term archive sustainability requires predictable economics:

Table 12: Annual Storage Cost Projections (per TB)

| **Tier** | **Year 1** | **Year 3** | **Year 5** | **Year 10** |
|---|---|---|---|---|
| Pars nodes (ASHA rewards) | 240 ASHA | 180 ASHA | 140 ASHA | 100 ASHA |
| IPFS/Filecoin deals | \$180 | \$120 | \$80 | \$50 |
| Arweave (one-time) | \$5,200 | – | – | – |

The ParsArchive endowment fund receives 5% of annual ASHA staking rewards from the archive treasury allocation. At current network parameters, this sustains approximately 2 TB of new permanent archival per year. Community governance can adjust this allocation through DAO proposals.

## 11.2 Contributor Incentives

Table 13: Contributor Reward Structure

| **Role** | **Activity** | **Reward (ASHA)** | **Frequency** |
|---|---|---|---|
| Node operator | Storage & bandwidth | 50–200/month | Monthly |
| Digitizer | Physical → digital | 5–20/object | Per object |
| Metadata editor | Cataloguing | 2–8/object | Per object |
| Translator | Translation bounty | Per bounty | Per task |
| Reviewer | Quality review | 15% of bounty | Per review |
| Curator | Curation nomination | 10 (if accepted) | Per nomination |

## 12 Limitations and Future Work

1. **Copyright:** Many modern Persian works are under copyright. We are developing a fair-use framework for diaspora educational access and working with rights holders on licensing agreements.
2. **Digitization:** Many physical materials have not been digitized. Partnerships with diaspora cultural organizations for digitization programs are being established.
3. **Quality:** OCR quality for Persian scripts, particularly Nastaliq, remains imperfect. We are training specialized OCR models on the archived calligraphy dataset.
4. **Sustainability:** Long-term storage costs require ongoing funding. The ASHA tokenomics must sustain archive operations as emission decreases.
5. **Oral Histories:** Recording and archiving oral histories from aging first-generation diaspora members is time-sensitive. An accelerated collection program is planned.
6. **Cross-Archive Federation:** Interoperability with Kurdish, Armenian, and Afghan cultural archives would strengthen the shared cultural heritage of the region. A federation protocol based on shared metadata standards is under design.
7. **AI-Assisted Curation:** Fine-tuned Persian language and vision models for automated metadata extraction, period classification, and script identification will reduce manual curation burden.

## 13 Conclusion

ParsArchive provides censorship-resistant infrastructure for preserving Persian cultural heritage, combining decentralized storage, community curation, and economic incentives for translation and annotation. By distributing archived materials across 340 nodes in 22 countries with proven resistance to jurisdictional takedown attempts, ParsArchive ensures that Persian cultural heritage remains accessible to the diaspora regardless of political circumstances. The translation bounty system bridges the language gap between archived materials and diaspora host-country languages, making cultural heritage actively accessible rather than merely preserved.

## References

Anderson, C. and Murdoch, S. J. The dimming of the internet: Detecting throttling as a mechanism of censorship in Iran. *arXiv preprint arXiv:1306.4361*, 2013.

Benet, J. IPFS – Content addressed, versioned, P2P file system. *arXiv preprint arXiv:1407.3561*, 2014.

Bethencourt, J., Sahai, A., and Waters, B. Ciphertext-policy attribute-based encryption. In *IEEE S&P*, pages 321–334, 2007.

Ceramic Network. Ceramic Protocol Specification. Technical documentation, 2021.

Dublin Core Metadata Initiative. DCMI Metadata Terms. `https://www.dublincore.org/specifications/dublin-core/dcmi-terms/`, 2020.

Europeana Foundation. Europeana: Digital cultural heritage. `https://www.europeana.eu`, 2023.

Hachette Book Group v. Internet Archive. *No. 20-cv-4160 (S.D.N.Y. 2023)*, 2023.

Hart, M. Project Gutenberg. `https://www.gutenberg.org`, 1992.

ISO. Space data and information transfer systems – Open archival information system (OAIS) – Reference model. ISO 14721:2012, 2012.

Kahle, B. Preserving the internet. *Scientific American*, 276(3):82–83, 1997.

Library of Congress. Digital Preservation. `https://www.digitalpreservation.gov`, 2023.

Naficy, H. *The Making of Exile Cultures: Iranian Television in Los Angeles*. University of Minnesota Press, 1993.

NYU Libraries. Afghan Digital Library. `https://afghanistandl.nyu.edu`, 2020.

Protocol Labs. Filecoin: A decentralized storage network. *Filecoin Whitepaper*, 2017.

Reich, V. and Rosenthal, D. S. LOCKSS: A permanent web publishing and access system. *D-Lib Magazine*, 7(6), 2001.

UNESCO. Memory of the World Programme. `https://en.unesco.org/programme/mow`, 2023.

Williams, S., Diordiiev, V., Berman, L., et al. Arweave: A protocol for economically sustainable information permanence. *Arweave Yellowpaper*, 2019.

Yarshater, E., editor. *Persian Literature*. SUNY Press, 1988.

Sahai, A. and Waters, B. Fuzzy identity-based encryption. In *EUROCRYPT*, pages 457–473, 2005.

Goyal, V., Pandey, O., Sahai, A., and Waters, B. Attribute-based encryption for fine-grained access control of encrypted data. In *CCS*, pages 89–98, 2006.

Merkle, R. C. A digital signature based on a conventional encryption function. In *CRYPTO*, pages 369–378, 1987.

Maymounkov, P. and Mazières, D. Kademlia: A peer-to-peer information system based on the XOR metric. In *IPTPS*, pages 53–65, 2002.

Reed, I. S. and Solomon, G. Polynomial codes over certain finite fields. *Journal of the Society for Industrial and Applied Mathematics*, 8(2):300–304, 1960.

Langley, A., Riddoch, A., Wilk, A., et al. The QUIC transport protocol: Design and internet-scale deployment. In *ACM SIGCOMM*, pages 183–196, 2017.

Bernstein, D. J. Curve25519: New Diffie-Hellman speed records. In *PKC 2006*, pages 207–228, 2006.