



[Unit 1 Linear Classifiers and Course](#) > [Generalizations \(2 weeks\)](#)

[Lecture 2. Linear Classifier and](#) > [Perceptron](#)

> 5. The Perceptron Algorithm

Audit Access Expires May 11, 2020

You lose all access to this course, including your progress, on May 11, 2020.

Upgrade by Mar 25, 2020 to get unlimited access to the course as long as it exists on the site. [Upgrade now](#)

5. The Perceptron Algorithm

The Perceptron Algorithm

**Video**

[Download video file](#)

Transcripts

[Download SubRip \(.srt\) file](#)

[Download Text \(.txt\) file](#)

Perceptron Concept Questions 1

1/1 point (graded)

Remember that the Perceptron Algorithm (without offset) is stated as the following:

Perceptron $\left(\{ (x^{(i)}, y^{(i)}), i = 1, \dots, n \}, T \right) :$

initialize $\theta = 0$ (vector);

for $t = 1, \dots, T$ do

for $i = 1, \dots, n$ do

if $y^{(i)} (\theta \cdot x^{(i)}) \leq 0$ then
 update $\theta = \theta + y^{(i)} x^{(i)}$

What does the Perceptron algorithm take as inputs among the following? Choose all those apply.

☒ Training set

☒ T - the number of times the algorithm iterates through the whole training set

☐ Test set

☐ θ

☐ θ_0



Solution:

The perceptron algorithm takes T and the training set as input, and aims to learn the optimal " θ ", " θ_0 "

Submit

You have used 1 of 2 attempts

i Answers are displayed within the problem

Perceptron Update 1

1/1 point (graded)

Now consider the Perceptron algorithm with Offset. Whenever there is a "mistake" (or equivalently, whenever $y^{(i)} (\theta \cdot x^{(i)} + \theta_0) \leq 0$ i.e. when the label y^i and $h(x)$ do not match), perceptron updates

$$\theta \text{ with } \theta + y^{(i)} x^{(i)}$$

and

$$\theta_0 \text{ with } \theta_0 + y^{(i)}.$$

More formally, the Perceptron Algorithm with Offset is defined as follows:

Perceptron $\left(\{ (x^{(i)}, y^{(i)}), i = 1, \dots, n \}, T \right) :$

initialize $\theta = 0$ (vector); $\theta_0 = 0$ (scalar)

for $t = 1, \dots, T$ do

for $i = 1, \dots, n$ do

if $y^{(i)} (\theta \cdot x^{(i)} + \theta_0) \leq 0$ then

update $\theta = \theta + y^{(i)} x^{(i)}$

$$\text{update } \theta_0 = \theta_0 + y^{(i)}$$

In the next set of problems, we will try to understand why such an update is a reasonable one.

When a mistake is spotted, do the updated values of θ and θ_0 provide a better prediction? In other words, is

$$y^{(i)} ((\theta + y^{(i)} x^{(i)}) \cdot x^{(i)} + \theta_0 + y^{(i)})$$

always greater than or equal to

$$y^{(i)} (\theta \cdot x^{(i)} + \theta_0)$$

☐ Yes, because $\theta + y^{(i)} x^{(i)}$ is always larger than θ

☒ Yes, because $(y^{(i)})^2 \|x^{(i)}\|^2 + (y^{(i)})^2 \geq 0$

☐ No, because $(y^{(i)})^2 \|x^{(i)}\|^2 - (y^{(i)})^2 \leq 0$

☐ No, because $\theta + y^{(i)} x^{(i)}$ is always larger than θ



Solution:

Comparing the two terms,

$$y^{(i)} ((\theta + y^{(i)} x^{(i)}) \cdot x^{(i)} + \theta_0 + y^{(i)}) - y^{(i)} (\theta \cdot x^{(i)} + \theta_0) = (y^{(i)})^2 \|x^{(i)}\|^2 + (y^{(i)})^2 = (y^{(i)})^2 (\|x^{(i)}\|^2 + 1) > 0$$

the first is always greater than the latter. Considering that our goal is to minimize the training error, the update always makes the training error decrease, which is desirable.

Submit

You have used 1 of 2 attempts

i Answers are displayed within the problem

Perceptron Update 2

0 points possible (ungraded)

For a given example i , we defined the training error as 1 if $y^{(i)} (\theta \cdot x^{(i)} + \theta_0) \leq 0$, and 0 otherwise:

$$\varepsilon_i(\theta, \theta_0) = \mathbb{I}[y^{(i)} (\theta \cdot x^{(i)} + \theta_0) \leq 0]$$

Say we have a linear classifier given by θ, θ_0 . After the perceptron update using example i , the training error $\varepsilon_i(\theta, \theta_0)$ for

that example can (select all those apply):

☐ Increase

☒ Stay the same

☒ Decrease


Solution:

From the previous problem, we saw that $y^i (\theta \cdot x + \theta_0)$ increases after the perceptron update. Thus $[y^i (\theta \cdot x + \theta_0) \leq 0]$ becomes zero or stays 1.

You have used 2 of 2 attempts

Answers are displayed within the problem

Discussion

Topic: Unit 1 Linear Classifiers and Generalizations (2 weeks):Lecture 2. Linear Classifier and Perceptron / 5. The Perceptron Algorithm

[Add a Post](#)

Show all posts

by recent activity

- [Recitation 2](#)
 Many of the questions below will be addressed in the recitation video coming out next week!
 Pinned Staff 2
- [Lecture Question](#)
 Dear Staff, Hello, can you please explain to me the following, how did the professor get the update ? I don't understand how did he move from $y_i(\theta \cdot x_i + \theta_0)$ to $y_i(\theta \cdot x_i + \theta_0) + \eta y_i(\theta \cdot x_i + \theta_0)$...
 3
- [Deadline missed, can I still earn a certificate?](#)
 If I missed the deadline for completing some homework/exercise, can I still earn the course certificate by completing them before May 12, 2020? Th...
 2
- [error in video](#)
 I believe that there is an error in the video. It claims that after the first execution of the loop, if the new value for theta is used in the check for a mat...
 3
- [How to choose an appropriate value?](#)
 1
- [Error on i-th example after the update](#)
 3
- [Perceptron algorithm with non-binary features](#)
 Hello, I have a question. Is it a requirement for the perceptron algorithm that every element of the feature vector be binary —either 0 or 1—? Woul...
 2
- [Success of algorithm for linearly separable sets](#)
 Nice proof for those that are interested <http://www.cs.columbia.edu/~mccollins/courses/6998-2012/notes/perc.converge.pdf> Uses a definition of $x \cdot t$...
 1
- [What about noise?](#)
 I'm new to machine learning, but it is true that Perceptron Algorithm might get stuck in a loop if any of the training data was wrong? If, for example, ...
 2

<div><div>?</div><div>Perceptron Update 2</div></div> <div>I am confused about this question. In the answer choice, I see something related to "change. However, what I have understood from the question i...</div>	8
<div><div><input checked="" type="checkbox"/></div><div>Question regarding the step for weights update</div></div>	2
<div><div>?</div><div>Need clarification/help on when it is considered an error when the label and classifier meet the condition (video @ 2:28).</div></div> <div>In the video (2:28), it has $y_i(\theta x_i + \theta_0) \leq 0$. The lecture says that if the result is either 0 or Negative, then it is conside...</div>	2
<div><div>●</div><div>glitch in course progress. Where is Question 18?</div></div>	

Learn About Verified Certificates

© All Rights Reserved