



[Unit 1 Linear Classifiers and Course](#) > [Generalizations \(2 weeks\)](#)

> [Homework 2](#) > 3. Perceptron Updates

Audit Access Expires May 11, 2020

You lose all access to this course, including your progress, on May 11, 2020. Upgrade by Mar 25, 2020 to get unlimited access to the course as long as it exists on the site. [Upgrade now](#)

3. Perceptron Updates

In this problem, we will try to understand the convergence of perceptron algorithm and its relation to the ordering of the training samples for the following simple example.

Consider a set of $n = d$ labeled d —dimensional feature vectors, $\{(x^{(t)}, y^{(t)}), t = 1, \dots, d\}$ defined as follows:

$$x_i^{(t)} = \cos(\pi t) \quad \text{if } i = t \quad (3.7)$$

$$x_i^{(t)} = 0 \quad \text{otherwise,} \quad (3.8)$$

Recall the no-offset perceptron algorithm, and assume that $\theta \cdot x = 0$ is treated as a mistake, regardless of label. Assume that in all of the following problems, we initialize $\theta = 0$ and when we refer to the perceptron algorithm we only consider the no-offset variant of it.

Working out Perceptron Algorithm

3/3 points (graded)

Consider the $d = 2$ case. Let $y^{(1)} = 1, y^{(2)} = 1$. Assume that the feature vector $x^{(1)}$ is presented to the perceptron algorithm before $x^{(2)}$.

For this particular assignment of labels, work out the perceptron algorithm until convergence.

Let $\hat{\theta}$ be the resulting θ value after convergence. Note that for $d = 2$, $\hat{\theta}$ would be a two-dimensional vector. Let's denote the first and second components of $\hat{\theta}$ by $\hat{\theta}_1$ and $\hat{\theta}_2$ respectively.

Please enter the total number of updates made to θ by perceptron algorithm:

✓ Answer: 2

Please enter the numerical value of $\hat{\theta}_1$:

✓ Answer: -1

Please enter the numerical value of $\hat{\theta}_2$:

✓ Answer: 1

Solution:

The first iteration of perceptron with data point $(x^{(i)}, y^{(i)})$ will be a mistake due to our initialization of $\theta^{(0)} = \bar{0}$. The first update sets $\theta^{(1)} = y^{(i)} x^{(i)} = x^{(i)}$. The second iteration of perceptron with data point $(x^{(j)}, y^{(j)})$ will also yield a mistake since

$$\theta^{(1)} \cdot x^{(j)} = x^{(i)} \cdot x^{(j)} = 0$$

. Thus, for the $d = 2$ example, after 2 updates $\theta^{(2)} = x^{(i)} + x^{(j)}$. We now check whether the second pass yields mistakes

$$\begin{aligned}y^{(i)} \theta^{(2)} \cdot x^{(i)} &= y^{(i)} (y^{(i)} x^{(i)} + y^{(j)} x^{(j)}) \cdot x^{(i)} \\&= \|x^{(i)}\|^2 + x^{(i)} \cdot x^{(j)} \\&= \|x^{(i)}\|^2 + 0 \\&> 0\end{aligned}$$

so the first point is classified correctly. Similarly, the second point is also classified correctly.

Therefore, it only takes two updates to classify the $d = 2$ dataset and θ converges to $\hat{\theta} = \begin{bmatrix} -1 \\ 1 \end{bmatrix}$

You have used 1 of 3 attempts

i Answers are displayed within the problem

General Case - Number of updates

1/1 point (graded)

Now consider any $d > 0$.

For the specific dataset we are considering, please choose the correct answer from the options below:

- ☒ Perceptron algorithm will make exactly d updates to θ regardless of the order and labelings of the feature vectors
- ☐ Perceptron algorithm will make at least d updates to θ with the exact number of updates depending on the ordering of the feature vectors presented to it
- ☐ Perceptron algorithm will make at least d updates to θ with the exact number of updates depending on the ordering of the feature vectors presented to it and their labeling
- ☐ Perceptron algorithm will make at most d updates to θ with the exact number of updates depending on the ordering of the feature vectors presented to it and their labeling



Solution:

Using the intuition that we gained from the $d = 2$ case, we notice that upon the first pass of the data points, every $\theta \cdot x^{(i)} = 0$ for all i . In other words, each data point we consider in sequence lies on the current boundary. Since each point starts as a mistake, there are $\geq d$ updates. Now it remains to be shown that after d updates, all points are classified correctly. After the i th update, we add $y^{(i)} x^{(i)}$ to $\theta^{(i-1)}$. After d updates,

$$\theta^{(d)} = \sum_{i=1}^d y^{(i)} x^{(i)}$$

We check whether $y^{(t)} \theta^{(d)} \cdot x^{(t)} > 0$ for all t to ensure there are no mistakes. Notice that the only non-zero term of the dot product occurs when $i = t$. Thus,

$$y^{(t)} \theta^{(d)} \cdot x^{(t)} = (y^{(t)})^2 \|x^{(t)}\|^2 > 0$$

for all $t = 1, 2, \dots, d$. Therefore, the perceptron algorithm will make exactly d updates regardless of the order and the labelings of the feature vectors.

You have used 1 of 3 attempts

i Answers are displayed within the problem

Sketching convergence

1/1 point (graded)

Consider the case with $d = 3$. Also assume that all the feature vectors are positively labelled. Let P denote the plane through the three points in a 3-d space whose vector representations are given by the feature vectors $x^{(1)}, x^{(2)}, x^{(3)}$.

Let $\hat{\theta}$ denote the value of θ after perceptron algorithm converges for this example. Let v denote the vector connecting the origin and $\hat{\theta}$. Which of the following options is true regarding the vector represented by $\hat{\theta}$.

☐ v is parallel to the plane P

☐ v is perpendicular to the plane P and pointing away from it

☒ v is perpendicular to the plane P and pointing towards it

☐ $\hat{\theta}$ lies on the plane P



Solution:

Note that from the previous problem

$$\hat{\theta} = \sum_{i=1}^d y^{(i)} x^{(i)}$$

Evaluating the above expression, for the current example gives,

$$\hat{\theta} = \begin{bmatrix} -1 \\ 1 \\ -1 \end{bmatrix}$$

The equation of the plane is given by:

$$\begin{vmatrix} x & -1 & 0 \\ y - 1 & -1 & -1 \\ z & 0 & -1 \end{vmatrix} = 0$$

That is,

$$x - y + z = -1$$

Or equivalently,

$$\begin{pmatrix} x \\ y \\ z \end{pmatrix} \cdot \begin{pmatrix} -1 \\ 1 \\ -1 \end{pmatrix} = 1$$

Hence, v is perpendicular to P and pointing towards it.

Submit

You have used 2 of 3 attempts

i Answers are displayed within the problem

Discussion

[Hide Discussion](#)

Topic: Unit 1 Linear Classifiers and Generalizations (2 weeks);Homework 2 / 3. Perceptron Updates

[Add a Post](#)

Show all posts

by recent activity

- | | |
|---|---|
| ? <u>General Case - Number of updates</u> | 6 |
| <u>Hello, I don't think we did prove this result, did we ? we did prove that k number of iterations ...</u> | |
| 💬 <u>Why is this so hard?</u> | 2 |
| <u>Is it only me? It seems like I cannot solve the homework just based on the knowledge I have g...</u> | |
| ? <u><staff> Bug question general case</u> | 2 |
| <u>There must be a bug because I submit the right solution as you can see from the question on...</u> | |
| ? <u>General case, number of updates; what happens for negative labels?</u> | 1 |
| <u>Something interesting happens when all labels are negative. I think that the question 2 assu...</u> | |
| ? <u>Any hint on how to define feature vectors (x1 and x2) for the perceptron updates?</u> | 9 |
| <u>We are given the labels, d but, I'm still trying to figure out how to interpret what feature vecto...</u> | |
| ? <u>Result is interesting. What is an intuition behind this result?</u> | 2 |
| <u>Result looks amazing to me. I wonder if there is some intuition behind it.</u> | |
| 💬 <u>[STAFF] What do you recommend, as a graph tool, for point 3 in page 3?</u> | 5 |
| <u>I'm asking this because I took a lot to correctly visualize this geometrically, and I'd like a grap...</u> | |
| 💬 <u>Typo on Section 3: Sketching Convergence</u> | 3 |
| <u>I think there is a typo in the following sentence in section 3: `Let v denote the vector connecti...</u> | |
| 💬 <u>Missed point 2 in page 3 due to a silly bug!!!!</u> | 2 |
| <u>Please! Don't be like me! Check all the times you need your academic-purpose-only impleme...</u> | |

💬	Sketching convergence	2
?	What is index i? What is index i?	3
?	[STAFF] What is i? I don't understand the question, $i=1 \dots n$?	2

[Learn About Verified Certificates](#)

© All Rights Reserved