



[Course](#) > [Unit 3 Neural networks \(2.5 weeks\)](#) > [Project 3: Digit recognition \(Part 2\)](#) >
9. Convolutional Neural Networks

Audit Access Expires May 11, 2020

You lose all access to this course, including your progress, on May 11, 2020.

9. Convolutional Neural Networks

Next, we are going to apply convolutional neural networks to the same task. These networks have demonstrated great performance on many deep learning tasks, especially in computer vision.

You will be working in the files `part2-mnist/nnet_cnn.py` and `part2-mnist/train_utils.py` in this problem

Convolutional Neural Networks

3.0/3.0 points (graded)

We provide skeleton code `part2-mnist/nnet_cnn.py` which includes examples of some (**not all**) of the new layers you will need in this part. Using the [PyTorch Documentation](#), complete the code to implement a convolutional neural network with following layers in order:

- A convolutional layer with 32 filters of size 3×3
- A ReLU nonlinearity
- A max pooling layer with size 2×2
- A convolutional layer with 64 filters of size 3×3

- A ReLU nonlinearity
- A max pooling layer with size 2×2
- A flatten layer
- A fully connected layer with 128 neurons
- A dropout layer with drop probability 0.5
- A fully-connected layer with 10 neurons

Note: We are not using a softmax layer because it is already present in the loss: PyTorch's `nn.CrossEntropyLoss` combines `nn.LogSoftMax` with `nn.NLLLoss`.

Without GPU acceleration, you will likely find that this network takes quite a long time to train. For that reason, we don't expect you to actually train this network until convergence. Implementing the layers and verifying that you get approximately 93% **training accuracy** and 98% **validation accuracy** after one training epoch (this should take less than 10 minutes) is enough for this project. If you are curious, you can let the model train longer; if implemented correctly, your model should achieve >99% **test accuracy** after 10 epochs of training. If you have access to a CUDA compatible GPU, you could even try configuring PyTorch to use your GPU.

After you successfully implement the above architecture, copy+paste your model code into the codebox below for grading.

Grader note:: If you get a NameError "Flatten" not found, make sure to unindent your code.

Available Functions: You have access to the `torch.nn` module as `nn` and to the `Flatten` layer as `Flatten`; No need to import anything.

```
model = nn.Sequential(  
    nn.Conv2d(1, 32, (3, 3)),  
    nn.ReLU(),  
    nn.MaxPool2d((2, 2)),  
    nn.Conv2d(32, 64, (3, 3)),  
    nn.ReLU(),  
    nn.MaxPool2d((2, 2)),  
    Flatten(),  
    nn.Linear(1600, 128),  
)
```

```
10 nn.Dropout(0.5),  
11 nn.Linear(128, 10),  
12 )
```

Press ESC then TAB or click outside of the code editor to exit

Correct

```
model = nn.Sequential(  
    nn.Conv2d(1, 32, (3, 3)),  
    nn.ReLU(),  
    nn.MaxPool2d((2, 2)),  
    nn.Conv2d(32, 64, (3, 3)),  
    nn.ReLU(),  
    nn.MaxPool2d((2, 2)),  
    Flatten(),  
    nn.Linear(1600, 128),  
    nn.Dropout(0.5),  
    nn.Linear(128, 10),  
)
```

Test results

CORRECT

[See full output](#)

[See full output](#)

Submit

You have used 4 of 25 attempts

i Answers are displayed within the problem

Discussion

Hide Discussion

Topic: Unit 3 Neural networks (2.5 weeks):Project 3: Digit recognition (Part 2) / 9. Convolutional Neural Networks

Add a Post

Show all posts

by recent activity

?	Allow to submit answer for no credit	2
	I completed half of the project and unfortunately didn't have time to finish it, but I was wond...	
💬	The 2nd maxpool operation	5
	- A convolutional layer with 32 filters of size 3x3 - (28 -> 26) - A max pooling layer with size 2x...	
?	RuntimeError	1
	I was testing the solution code, but got runtime error as the message showed below. Does an...	
💬	ReLU before max pooling	3
	What is the effect of ReLU before max pooling? It is like applying max(max(0,x)), this might ze...	
💬	pytorch 1.4 has nn.Flatten	2
	Please consider as an update for the next version.	
💬	Issue with compute_accuracy	3
	Keep getting a ValueError, 'File "/.part2-mnist/train_utils.py", line 32, in compute_accuracy ret...	
💬	I have no words	2
	So, we had no lecture about pytorch, and, since I couldn't start the project before today, I hav...	
?	Error on compute_accuracy while running the code	1
	Not sure if this is supposed to be the case. When I run the code (no change to the code), I get...	
💬	Tip for size of tensor	6 new_
	In the forward method of the Flatten class in train_utils.py, it might be helpful to put, print(in...	
?	Input size for "nn.Linear(in_features, out_features, bias=True)"	15 new_
	Hello! How are you? I can not realize what is the size for the in_features in the nn.Linear() fun...	
💬	Flatten error/indent	7 new_
	Hi, I keep getting the error below. I tried different indents, but nothing seems to work... Work...	
💬	Stride for Max Pooling	2
	Does 2 x 2 Max pooling imply that the strides are 2,2 along the horizontal and vertical directi...	
✓	[Staff] Is it a coincident that the "batch_size" appears in the input for "Flatten"	6
	Dear TA. I am using @soup PI method to check the dimension of the "Flatten" Then I found t...	

