



[Unit 1 Linear Classifiers and](#)
[Course](#) > [Generalizations \(2 weeks\)](#)

> [Homework 2](#) > 1. Linear Support Vector Machines

Audit Access Expires May 11, 2020

You lose all access to this course, including your progress, on May 11, 2020.

Upgrade by Mar 25, 2020 to get unlimited access to the course as long as it exists on the site. [Upgrade now](#)

1. Linear Support Vector Machines

In this problem, we will investigate minimizing the training objective for a Support Vector Machine (with margin loss).

The training objective for the Support Vector Machine (with margin loss) can be seen as optimizing a balance between the average hinge loss over the examples and a regularization term that tries to keep the parameters small (increase the margin). This balance is set by the regularization parameter $\lambda > 0$. Here we only consider the case without the offset parameter θ_0 (setting it to zero) so that the training objective is given by

$$\left[\frac{1}{n} \sum_{i=1}^n \text{Loss}_h(y^{(i)} \theta \cdot x^{(i)}) \right] + \frac{\lambda}{2} \|\theta\|^2 = \frac{1}{n} \sum_{i=1}^n \left[\text{Loss}_h(y^{(i)} \theta \cdot x^{(i)}) + \frac{\lambda}{2} \|\theta\|^2 \right] \quad (3.3)$$

where the hinge loss is given by

$$\text{Loss}_h(y(\theta \cdot x)) = \max\{0, 1 - y(\theta \cdot x)\}$$

$$\hat{\theta} = \text{Argmin}_{\theta} [\text{Loss}_h(y \theta \cdot x) + \frac{\lambda}{2} \|\theta\|^2] \quad (3.4)$$

Note: For all of the exercises on this page, assume that $n = 1$ where n is the number of

training examples and $x = x^{(1)}$ and $y = y^{(1)}$.

Minimizing Loss - Case 1

1/1 point (graded)

In this question, suppose that $\text{Loss}_h(y(\hat{\theta} \cdot x)) > 0$. Under this hypothesis, solve for optimisation problem and express $\hat{\theta}$ in terms of x , y and λ

$y \cdot x / \lambda$



Answer: $x \cdot y / \lambda$

$\frac{y \cdot x}{\lambda}$

STANDARD NOTATION

Solution:

$$\hat{\theta} = \text{Argmin}_{\theta} [\text{Loss}_h(y \theta \cdot x) + \frac{\lambda}{2} \|\theta\|^2]$$

The above loss can be minimized by solving for the following equation

$$0 = \nabla_{\theta} [\text{Loss}_h(y(\theta \cdot x))] + \nabla_{\theta} \left[\frac{\lambda}{2} \|\theta\|^2 \right]$$

Given that

$$\text{Loss}_h(y(\hat{\theta} \cdot x)) > 0$$

$$\text{Loss}_h(y(\hat{\theta} \cdot x)) = \max\{0, 1 - y(\theta \cdot x)\}$$

$$\text{Loss}_h(y(\hat{\theta} \cdot x)) = 1 - y(\theta \cdot x)$$

$$\nabla_{\theta} [\text{Loss}_h(y(\theta \cdot x))] = -yx$$

Plugging this back in the previous equation, we get:

$$0 = \lambda \hat{\theta} - yx$$

$$\hat{\theta} = \frac{1}{\lambda} yx$$

Submit

You have used 1 of 3 attempts

i Answers are displayed within the problem

Minimizing Loss - Numerical Example (1)

2/2 points (graded)

Consider minimizing the above objective function for the following numerical example:

$$\lambda = 0.5, y = 1, x = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

Note that this is a classification problem where points lie on a two dimensional space. Hence $\hat{\theta}$ would be a two dimensional vector.

Let $\hat{\theta} = [\hat{\theta}_1, \hat{\theta}_2]$, where $\hat{\theta}_1, \hat{\theta}_2$ are the first and second components of $\hat{\theta}$ respectively.

Solve for $\hat{\theta}_1, \hat{\theta}_2$.

Hint: For the above example, show that $\text{Loss}_h(y(\hat{\theta} \cdot x)) \leq 0$

$\hat{\theta}_1 =$

✓ Answer: 1.0

$\hat{\theta}_2 =$

0

✓ Answer: 0.0

Solution:

First note that for this example $Loss_h(y(\theta \cdot x)) \leq 0$.

To show this we use proof by contradiction.

Suppose $Loss_h(y(\theta \cdot x)) > 0$:

From the previous problem, we know that under this condition, $\hat{\theta} = \frac{yx}{\lambda}$

For this example, $\hat{\theta} = \begin{bmatrix} 2 \\ 0 \end{bmatrix}$.

For this value of $\hat{\theta}$, we see that $1 - (y(\theta \cdot x)) = 1 - 2 = -1 < 0$ contradicting our original assumption.

Hence, $Loss_h(y(\theta \cdot x)) \leq 0$, which implies that $y(\theta \cdot x) \geq 1$.

We are left with minimizing $\frac{\lambda}{2} \|\theta\|^2$ under the constraint $y(\theta \cdot x) \geq 1$.

The geometry of the problem implies that in fact, $y(\theta \cdot x) = 1$.

That is, $1 - (\hat{\theta}_1 * 1 + \hat{\theta}_2 * 0) = 0$ implying that $\hat{\theta}_1 = 1$.

Then, to minimize $\|\theta\|$, $\hat{\theta}_2 = 0$.

Therefore $\hat{\theta} = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$.

In fact, we can show that $\hat{\theta} = \frac{x}{y\|x\|^2}$. Looking back at the previous question, the solution of the optimization is then necessarily of the form $\hat{\theta} = \eta yx$ for some real $\eta > 0$.

Submit

You have used 2 of 3 attempts

❗ Answers are displayed within the problem

Minimizing Loss - Numerical Example (2)

1.0/1 point (graded)

Now, let $\hat{\theta} = \hat{\theta}(\lambda)$ be the solution as a function of λ .

For what value of $\|x\|^2$, the training example (x, y) will be misclassified by $\hat{\theta}(\lambda)$?

$$\|x\|^2 = 0$$



Answer: 0

Solution:

For a point to be considered misclassified

$$y\hat{\theta} \cdot x \leq 0$$

The above condition implies that the hinge loss is greater than zero. From above problems, we know that under this condition,

$$\hat{\theta} = \frac{yx}{\lambda}$$

$$y\hat{\theta} \cdot x = \frac{y^2\|x\|^2}{\lambda} \leq 0$$

All terms of the product are non-negative, making it impossible to be < 0 . But if $\|x\| = 0$, the product can be 0.

Hence $\|x\|^2 = 0$

Submit

You have used 2 of 3 attempts

i Answers are displayed within the problem

Discussion


Add a Post

Hide Discussion


Topic: Unit 1 Linear Classifiers and Generalizations (2 weeks); Homework 2 / 1. Linear Support Vector Machines

Show all posts


by recent activity

- 
[Two homeworks in one week is strange.](#)


I had to go to a different country for 10 days, and I didn't have much access to the internet, so I missed...

2
- 
[Minimizing Loss - Numerical Example \(1\) vs. Case 1 \[staff\]](#)


Not clear about what happens here. I gave the correct answer in Case 1, tried to apply the same reaso...

7
- 
[Norm \$x^2\$](#)


Numerical or with lambda?

2
- 
[What`s theta_hat?](#)


Can anyone help me understand what theta_hat is? I probably missed it in the lectures...

4
- 
[minimizing case 1_theta not accepted in answer](#)


I am so confused. From the lectures it appears that argmin of theta_hat, is a derivative of the loss funct...

3
- 
[Minimizing Loss - Numerical Example \(1\)](#)


8 new_

11
- 
[Minimizing Loss - Numerical Example \(2\): need a hint](#)


18 new_

25
- 
[Numerical Example 1](#)


After having spent some time on this question, I thought I could give a quick hint to anyone struggling (...)


7
- 
[Need Help, Clarification, Anything.\(Numerical Example 2\)](#)

I'm absolutely stuck on this question for over 3,4 hours. I think I understand the role of lambda and th...


11
- 
[suggestion](#)

I'd like to suggest that you abolish the word "above". E.g. instead of saying "the above example" or "the...

4
- 
[\[Cace 1\] theta instaead of theta_hat](#)

4
- 
[optimizing perceptron](#)

FYI, I come from a Computer Science background. given this version of the perceptron algorithm with ...

1
- 
[A recitation should have been included to review constrained and unconstrained loss minimization concepts.](#)

12 new_

Just wanted to share that I was going really fine up till this homework and suddenly got dejected and d...

Learn About Verified Certificates

© All Rights Reserved