



[Unit 1 Linear Classifiers and Course](#) > [Generalizations \(2 weeks\)](#)

> [Homework 1](#) > 1. Perceptron Mistakes

Audit Access Expires May 11, 2020

You lose all access to this course, including your progress, on May 11, 2020. Upgrade by Mar 25, 2020 to get unlimited access to the course as long as it exists on the site. [Upgrade now](#)

1. Perceptron Mistakes

In this problem, we will investigate the perceptron algorithm with different iteration ordering.

Consider applying the perceptron algorithm **through the origin** based on a small training set containing three points:

$$x^{(1)} = [-1, -1],$$

$$y^{(1)} = 1$$

$$x^{(2)} = [1, 0],$$

$$y^{(2)} = -1$$

$$x^{(3)} = [-1, 1.5],$$

$$y^{(3)} = 1$$

Given that the algorithm starts with $\theta^{(0)} = 0$, the first point that the algorithm sees is always considered a mistake. The algorithm starts with some data point and then cycles through the data (in order) until it makes no further mistakes.

1. (a)

4.0/4 points (graded)

How many mistakes does the algorithm make until convergence if the algorithm

starts with data point $x^{(1)}$? How many mistakes does the algorithm make if it starts with data point $x^{(2)}$?

Also provide the progression of the separating plane as the algorithm cycles in the following **list format**: $[[\theta_1^{(1)}, \theta_2^{(1)}], \dots, [\theta_1^{(N)}, \theta_2^{(N)}]]$, where the superscript denotes different θ as the separating plane progresses. For example, if θ progress from $[0, 0]$ (initialization) to $[1, 2]$ to $[3, -2]$, you should enter $[[1, 2], [3, -2]]$

Please enter the **number of mistakes** of Perceptron algorithm if the algorithm starts with $x^{(1)}$.

✓ Answer: 2

Please enter the **progression of the separating hyperplane (θ , in the list format described above)** of Perceptron algorithm if the algorithm starts with $x^{(1)}$.

()

✓ Answer: $[[-1, -1], [-2, 0.5]]$

Please enter the **number of mistakes** of Perceptron algorithm if the algorithm starts with $x^{(2)}$.

✓ Answer: 1

Please enter the **progression of the separating hyperplane (θ , in the list format described above)** of Perceptron algorithm if the algorithm starts with $x^{(2)}$.

✓ Answer: $[[-1, 0]]$

Solution:

- If the algorithm starts with $x^{(1)}$, then it will encounter two errors: $x^{(1)}$ and $x^{(3)}$.
- Since $[0, 0] \cdot x^{(1)} = 0$, the result is not greater than 0.

- It would induce an update $\theta^{(1)} = \theta^{(0)} + y^{(1)}x^{(1)} = [-1, -1]$.
- Then $\theta^{(1)} \cdot x^{(2)} < 0$, so there is no mistakes.
- Finally, $\theta^{(1)} \cdot x^{(3)} < 0$, which incur an error and would induce an update $\theta^{(2)} = \theta^{(1)} + y^{(3)}x^{(3)}$.
- Afterwards, there should be no mistakes.
- If the algorithm starts with $x^{(2)}$, then it will only encounter one error: $x^{(2)}$. The derivation is similar to the above analysis.
- The progression of the separating hyperplane reflects the updated hyperplane after encountering errors.

You have used 1 of 3 attempts

 Answers are displayed within the problem

1. (b)

1/1 point (graded)

In part (a), what are the factors that affect the number of mistakes made by the algorithm?

Note: Only choose factors that were changed in part (a), **not** all factors that can affect the number of mistakes

(Choose all that apply.)



Iteration order



Maximum margin between positive and negative data points



Maximum norm of data points

**Solution:**

- Only the iteration order is changed in part (a).

Submit

You have used 1 of 3 attempts

i Answers are displayed within the problem

1. (c)

4.0/4 points (graded)

Now assume that $x^{(3)} = [-1, 10]$. How many mistakes does the algorithm make until convergence if cycling starts with data point $x^{(1)}$?

Also provide the progression of the separating plane as the algorithm cycles in the following **list format**: $[[\theta_1^{(1)}, \theta_2^{(1)}], \dots, [\theta_1^{(N)}, \theta_2^{(N)}]]$, where the superscript denotes different θ as the separating plane progresses. For example, if θ progress from $[0, 0]$ (initialization) to $[1, 2]$ to $[3, -2]$, you should enter $[[1, 2], [3, -2]]$

Please enter the **number of mistakes** of Perceptron algorithm if the algorithm starts with $x^{(1)}$.

6

✓ Answer: 6

Please enter the **progression of the separating hyperplane (θ , in a list format described above)** of Perceptron algorithm if the algorithm starts with $x^{(1)}$.

[[-1,-1], [-2,9], [-3,8], [-4,7], [-

✓ Answer: [[-1, -1],[-2, 9],[-3,8],[-4,7],[-5,6],[-6,5]]

Please enter the **number of mistakes** of Perceptron algorithm if the algorithm starts with $x^{(2)}$.

✓ Answer: 1

Please enter the **progression of the separating hyperplane (θ , in the list format described above)** of Perceptron algorithm if the algorithm starts with $x^{(2)}$.

✓ Answer: $[-1, 0]$ **Solution:**

- The derivation is similar to part (a).
- If the algorithm starts with $x^{(1)}$, then it will encounter one error for $x^{(1)}$, one error for $x^{(3)}$, and then 4 errors for $x^{(1)}$.
- If the algorithm starts with $x^{(2)}$, then it will only encounter one error: $x^{(2)}$.
- The progression of the separating hyperplane reflects the updated hyperplane after encountering errors.

You have used 1 of 3 attempts

i Answers are displayed within the problem

1. (d)

1/1 point (graded)

For a fixed iteration order, what are the factors that affect the number of mistakes made by the algorithm between part (a) and part (c)?

Note: Only choose factors that were changed between part (a) and part (c), **not** all factors that can affect the number of mistakes

(Choose all that apply.)



Iteration order



Maximum margin between positive and negative data points



Maximum norm of data points

**Solution:**

- The maximum norm of data points cause part (c) to make more mistakes.

Submit

You have used 3 of 3 attempts



Answers are displayed within the problem

1. (e) (Optional)

0 points possible (ungraded)

In 1962, Novikoff has proven the following theorem.

Assume:

- There exists θ^* such that $\frac{y^{(i)}(\theta^* x^{(i)})}{\|\theta^*\|} \geq \gamma$ for all $i = 1, \dots, n$ and some $\gamma > 0$
- All the examples are bounded $\|x^{(i)}\| \leq R, i = 1, \dots, n$

Then the number k of updates made by the perceptron algorithm is bounded by $\frac{R^2}{\gamma^2}$.

(Note that the first condition implies that the data is linearly separable)

For proof, refer to theorem 1 of [this paper](#). Based on this theorem, what are the factors that constitute the bound on the number of mistakes made by the algorithm?

(Choose all that apply.)

☐

Iteration order

☒

Maximum margin between positive and negative data points

☒

Maximum norm of data points

☐

Average norm of data points



Solution:

- Iteration order would affect relative convergence speed, but does not constitute the bound in this theorem.
- The maximum margin and the maximum norm of data points constitute the bounds in the maximum number of mistakes.
- We can always scale an easy dataset to achieve the same average norm of data points with the same number of mistakes.

Submit

You have used 1 of 3 attempts

i Answers are displayed within the problem

1. (f) (Optional)

0 points possible (ungraded)

Now we want to establish an adversarial procedure to maximize the number of mistakes the perceptron algorithm makes. What are possible solutions? You should consider a general dataset instead of part (a) and part (c). (Choose all that apply.)



Exhaustive search the worst ordering



Dynamic Programming the worst ordering



Greedy select the data point with the maximum norm

**Solution:**

- There are only finitely possible iteration orders, since the algorithm can converge in finite adjustments. As a direct result, exhaustive search can always find the worst ordering.
- Given any prior mistakes made by the algorithm, we know that the maximum number of mistakes should be prior mistakes plus maximum future mistakes. Hence, optimal substructure exist and dynamic programming can be applied.
- Choosing the data point with maximum norm does not maximize the number of mistakes. For instance, take example from part (c) and adjust $x^{(2)}$ to be $[100000, 0]$ to get a counter example.

Submit

You have used 3 of 3 attempts

 Answers are displayed within the problem

Discussion

[Hide Discussion](#)

Topic: Unit 1 Linear Classifiers and Generalizations (2 weeks):Homework 1 / 1. Perceptron Mistakes

[Add a Post](#)[Show all posts](#)[by recent activity](#)

💬	<u>Detailed Solutions</u>	3
	<u>Can we get detailed solutions? The solutions provided are still very confusing.</u>	
✓	<u>Stupid question: if I find a mistake with perceptron in one case, and I update theta, do I need to redo the calculation</u>	4
	<u>do I need to redo the calculation for the same case with the new theta? And check until I get i...</u>	
💬	<u>[To STAFF] - Impossible to enter the answers as matrix in 1a) and 1c)</u>	62
	<u>In 1a) and 1c) I enter the matrix as indicated i.e [[number,number],[number,number]] but I g...</u>	
💬	<u>[STAFF] Need extension by 2 days</u>	1
	<u>Hello Staff, My work has been crazy last 2 weeks, can you please extend deadline for Unit1's "...</u>	
💬	<u>[STAFF].problem with question 1(c)</u>	4
	<u>Question 1(c) is not showing up for me. This is the error message that I'm getting "Could not f...</u>	
💬	<u>What should be the value of T?</u>	1
	<u>I randomly selected T as 20. What determines the value of T in the algorithm?</u>	
💬	<u>Hint. I think coding the solution would be the best approach because it is quite easy to get a wrong solution.</u>	5
	<u>I tried by hand and failed many times</u>	
💬	<u>Clarification on ordering when starting with x2</u>	4
?	<u>Not able to submit 1c due to an issue with submission</u>	14
	<u>Is there an issue with 1c. I am not able to submit it. It is exepcting a matrix is what I get, but I...</u>	
?	<u>The equation that we're optimizing?</u>	5
	<u>Thoroughly confused with '1a' here... 1. All the other articles / examples / papers that I read o...</u>	
✓	<u>Number of iterations in 1A</u>	2
	<u>Greetings! I didn't get it for how many times should I use perceptron algorithm. I can cycle th...</u>	
💬	<u>[STAFF].please hint for solution of "Expected answer to be a matrix, but input is a matrix of incorrect shape"</u>	14
	<u>Tried everything I could come up with for the matrix is not accepted by the grading system. P...</u>	

[Learn About Verified Certificates](#)

© All Rights Reserved