RuseTect study notes

Generated by `research/build_notes.py` from `research/out/*.json`.

1. What RuseTect is

RuseTect scores bank payments for money laundering and mule activity, and screens scam messages, before money moves. It is one Rust program (`rusetect-server`) that serves an HTTP API and web pages, plus a research pipeline in `research/` that measures every claim. The models are gradient-boosted trees trained on synthetic bank data (IBM AMLworld), because real labelled bank transfers are not public.

2. How one payment is scored

1. **Features.** 31 causal account-history features from earlier payments only: amounts, timing, fan-in and fan-out, new payee, pass-through ratio, 24 hour velocity. The state is then updated.
2. **L1 gate.** A small XGBoost (30 trees). Low scores exit as safe.
3. **L2.** The mean of an XGBoost (400 trees) and a LightGBM (600 trees).
4. **Pair window.** A 24 hour noisy-OR of recent risks: $1 - \prod(1 - r_i)$. It catches one sum split into parts.
5. **Hardening.** risk = max(calibrated cascade risk, calibrated format-free model pooled over all payment datasets). A launderer cannot lower it by changing the payment format.
6. **Bands.** Verify, hold, block, with thresholds set to an alert budget on validation data.
7. **Reasons.** TreeSHAP contributions of the model that set the risk, only for flagged payments.

3. Metrics you must know

Metric	Meaning	Used here?
PR-AUC	Area under precision against recall. With rare positives it shows how many alerts are real.	Main metric
ROC-AUC	Chance a random fraud scores above a random genuine payment. 0.5 is random.	Across datasets
Precision / recall	Share of alerts that are fraud / share of fraud that is alerted.	Per band
ECE	Expected calibration error: gap between predicted risk and observed rate.	Calibration
MAE	Mean absolute error of a numeric prediction: average of $\lvert y - \hat{y} \rvert$.	No: fraud is yes/no
RMSE	Square root of the mean squared error; punishes large errors more than MAE.	No
R^2	Share of the variance of a numeric target the model explains (1 = perfect, 0 = predicting the mean).	No
Brier score	MSE of predicted probabilities against 0/1 outcomes; the classification cousin of MSE.	Could be, for calibration

4. Key results (HI-Small test)

Score	PR-AUC	PR-AUC, format attack	Block recall / precision
Cascade alone	0.710	0.004	65.3% / 63.7%
Served, hardened	0.720	0.687	69.7% / 60.4%

The full test window has 1,015,669 payments and 1,797 laundering. Without the last eight days (a simulation tail with 36% of test laundering) the cascade scores 0.581: the honest headline.

5. Robustness: what an attacker can do

Block recall on the HI-Small demo window when the launderer changes their own payments (research/out/evasion_suite.json):

Attack	Cascade	Hardened	Hardened + pair window
base	37%	37%	37%
cheque	0%	2%	2%
amount_minus10	20%	13%	13%
amount_jitter	12%	7%	7%
delay_6h	2%	1%	1%
split4_spread	1%	1%	14%
split4_new_payees	0%	0%	0%
cheque_split4	0%	0%	0%

The payer window was tested under its own rule and not adopted.

6. Generalisation

ROC-AUC on each dataset's last 20% in time, served models trained on HI-Small (research/out/hardened_transfer.json):

Dataset	Cascade	Hardened
HI-Small (in domain)	0.983	0.991
LI-Small (in domain: the served models also trained on LI-Small)	0.943	0.977
HI-Medium	0.961	0.990
LI-Medium	0.900	0.975
HI-Large	0.952	0.947
LI-Large	0.875	0.866
SAML-D	0.565	0.998
AMLgentex Sweden difficult	0.521	0.674
BankSim (cards)	0.934	0.995
Sparkov (cards)	0.469	0.988
PaySim (mobile wallets)	0.360	0.896
IEEE-CIS (real card-not-present fraud labels)	0.433	0.597
TabFormer (cards)	0.635	0.833

Pooled second opinion adopted. Lesson: synthetic generators differ; a new bank must label some of its own data (docs/PILOT.md).

6a. MAE, RMSE and R^2 of the risk score

Computed against the 0/1 label on the HI-Small test part (1,015,669 payments). For a yes/no target these measure calibration: $RMSE^2$ is the Brier score and R^2 is the Brier skill score (research/out/regression_metrics.json).

Score	MAE	RMSE	R^2
Served risk (calibrated)	0.0017	0.0271	0.585
Cascade, uncalibrated	0.0128	0.0580	-0.905
Always the base rate	0.0035	0.0420	0.000

6b. Real against synthetic training data

Tested on IEEE-CIS (real card fraud), last 20% in time. The arm was chosen on validation: **real only** (research/out/real_vs_synthetic.json).

Trained on	PR-AUC	ROC-AUC	F1	FPR
real only	0.100	0.738	0.165	0.0425
synthetic only	0.039	0.514	0.066	0.0873
hybrid	0.052	0.572	0.087	0.0640

Synthetic card data does not stand in for real card data.

7. Why these choices

- **Rust serves, Python trains.** Per-payment code needs speed and one binary; training needs mature libraries.
- **Trees, not neural networks.** Tabular data, rare positives, exact explanations; no evidence a GNN wins here.
- **Chronological splits.** Fraud drifts; a random split leaks the future.
- **Pre-registered rules.** Each change is adopted only if a rule written before reading test data passes.
- **Isotonic calibration.** Puts two models on one probability scale without assuming a shape.
- **Fail closed.** No keys and no demo flag: the server does not start.

8. Quiz (answers in grey)

1. **Which file is the entry point of the API server?**

   crates/rusetect-server/src/main.rs (api/rusetect.rs on Vercel).

2. **Name the three stages a payment passes before banding.**

   Features, the L1 XGBoost gate, the L2 XGBoost + LightGBM mean; then the window and hardening.

3. **Why is PR-AUC preferred over accuracy here?**

   Fraud is about 0.1% of payments, so 99.9% accuracy is possible by approving everything.

4. **What does the hardened risk protect against?**

   A launderer switching payment format, which the cascade over-relies on.

5. **What is a noisy-OR?**

   1 minus the product of (1 minus each risk): the chance at least one part is bad if parts were independent.

6. **Why are thresholds fitted on validation only?**

   Fitting on test would report an optimistic number that a bank would never see.

7. **Is MAE a sensible metric for RuseTect? Why?**

   No: MAE measures numeric prediction error; fraud is a yes/no label, so ranking and calibration metrics are used.

8. **What does $R^2 = 0$ mean?**

   The model is no better than always predicting the average of the target.

9. **Why are explanations computed only for flagged payments?**

   TreeSHAP was most of the scoring time and approved payments show no reasons.

10. **What stops a misconfigured deployment from using demo keys?**

    check_config: without RUSETECT_ANALYST_KEYS the server needs RUSETECT_DEMO=1 explicitly.

11. **What is the biggest remaining weakness?**

    All payment data is synthetic; real performance is unknown until a shadow pilot on a bank's data.

12. **Which training data won on real card fraud, and how was it chosen?**

    Real only (IEEE-CIS), picked on validation PR-AUC before the test part was read.

13. **Which attack is still hardest?**

    Changes that keep each payment small and new, such as splitting over new mule accounts and delaying.