

NUMPY - CODING Q&A

BY - SHUBHAM WADEKAR

Copyright © Shubham Wadekar. All rights reserved.

This material is for personal use only. No part may be copied, shared, resold, or published without written permission. Unauthorized distribution is strictly prohibited and may result in action.

For permissions or licensing, contact: [shubham.p.wadekar@gmail.com]

Disclaimer: This content is for educational purposes. Accuracy is attempted but not guaranteed. No job outcome is promised.

NUMPY CODING QUESTIONS FOR DATA ENGINEERS

1. Create a 2D array and find the sum of all elements.

Scenario:

You have a 2D array. Calculate the sum of all its elements.

Logic:

- Use `np.sum()` to calculate the sum.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
total_sum = np.sum(arr)
print(total_sum)
```

2. Find the mean of each row in a 2D array.

Scenario:

You have a 2D array. Calculate the mean of each row.

Logic:

- Use `np.mean()` with `axis=1`.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
row_means = np.mean(arr, axis=1)
print(row_means)
```

3. Find the maximum value in each column of a 2D array.

Scenario:

You have a 2D array. Find the maximum value in each column.

Logic:

- Use `np.max()` with `axis=0`.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
col_max = np.max(arr, axis=0)
print(col_max)
```

4. Reshape a 1D array into a 2D array.

Scenario:

You have a 1D array. Reshape it into a 2D array of shape (2, 3).

Logic:

- Use `np.reshape()`.

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5, 6])
reshaped_arr = arr.reshape(2, 3)
print(reshaped_arr)
```

5. Flatten a 2D array into a 1D array.

Scenario:

You have a 2D array. Flatten it into a 1D array.

Logic:

- Use `.flatten()`.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
flattened_arr = arr.flatten()
print(flattened_arr)
```

6. Concatenate two 1D arrays.

Scenario:

You have two 1D arrays. Concatenate them.

Logic:

- Use `np.concatenate()`.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
concatenated_arr = np.concatenate((arr1, arr2))
print(concatenated_arr)
```

7. Stack two 1D arrays vertically.

Scenario:

You have two 1D arrays. Stack them vertically.

Logic:

- Use `np.vstack()`.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
stacked_arr = np.vstack((arr1, arr2))
print(stacked_arr)
```

8. Stack two 1D arrays horizontally.

Scenario:

You have two 1D arrays. Stack them horizontally.

Logic:

- Use `np.hstack()`.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
stacked_arr = np.hstack((arr1, arr2))
print(stacked_arr)
```

9. Split a 1D array into 3 equal parts.

Scenario:

You have a 1D array. Split it into 3 equal parts.

Logic:

- Use `np.split()`.

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5, 6])
split_arr = np.split(arr, 3)
print(split_arr)
```

10. Find the indices of non-zero elements in an array.

Scenario:

You have an array. Find the indices of non-zero elements.

Logic:

- Use `np.nonzero()`.

Program:

```
import numpy as np
arr = np.array([0, 1, 0, 2, 3])
nonzero_indices = np.nonzero(arr)
print(nonzero_indices)
```

11. Create a 3D array and find the sum along a specific axis.

Scenario:

You have a 3D array. Calculate the sum along the second axis.

Logic:

- Use `np.sum()` with `axis=1`.

Program:

```
import numpy as np
arr = np.array([[[1, 2], [3, 4]], [[5, 6], [7, 8]]])
sum_axis_1 = np.sum(arr, axis=1)
print(sum_axis_1)
```

12. Perform matrix multiplication on two 2D arrays.

Scenario:

You have two 2D arrays. Perform matrix multiplication.

Logic:

- Use `np.dot()` or `@`.

Program:

```
import numpy as np
arr1 = np.array([[1, 2], [3, 4]])
arr2 = np.array([[5, 6], [7, 8]])
result = np.dot(arr1, arr2)
print(result)
```

13. Find the determinant of a 2D array.

Scenario:

You have a 2D array. Calculate its determinant.

Logic:

- Use `np.linalg.det()`.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
determinant = np.linalg.det(arr)
print(determinant)
```

14. Find the inverse of a 2D array.

Scenario:

You have a 2D array. Calculate its inverse.

Logic:

- Use `np.linalg.inv()`.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
inverse = np.linalg.inv(arr)
```

15. Solve a system of linear equations.

Scenario:

You have a system of linear equations. Solve it using NumPy.

Logic:

- Use `np.linalg.solve()`.

Program:

```
import numpy as np
A = np.array([[3, 1], [1, 2]])
b = np.array([9, 8])
solution = np.linalg.solve(A, b)
print(solution)
```

16. Find the eigenvalues and eigenvectors of a 2D array.

Scenario:

You have a 2D array. Find its eigenvalues and eigenvectors.

Logic:

- Use `np.linalg.eig()`.

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
eigenvalues, eigenvectors = np.linalg.eig(arr)
print(eigenvalues, eigenvectors)
```

17. Perform element-wise multiplication of two arrays.

Scenario:

You have two arrays. Perform element-wise multiplication.

Logic:

- Use `*` operator.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
result = arr1 * arr2
print(result)
```

18. Perform element-wise division of two arrays.

Scenario:

You have two arrays. Perform element-wise division.

Logic:

- Use `/` operator.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
result = arr1 / arr2
print(result)
```

19. Find the dot product of two 1D arrays.

Scenario:

You have two 1D arrays. Calculate their dot product.

Logic:

- Use `np.dot()`.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
dot_product = np.dot(arr1, arr2)
print(dot_product)
```

20. Find the cross product of two 1D arrays.

Scenario:

You have two 1D arrays. Calculate their cross product.

Logic:

- Use `np.cross()`.

Program:

```
import numpy as np
arr1 = np.array([1, 2, 3])
arr2 = np.array([4, 5, 6])
cross_product = np.cross(arr1, arr2)
print(cross_product)
```

21. Normalize an array to a range of 0 to 1.

Scenario:

You have an array. Normalize its values to a range of 0 to 1.

Logic:

- Use $(arr - \min) / (\max - \min)$.

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
normalized_arr = (arr - np.min(arr)) / (np.max(arr) - np.min(arr))
print(normalized_arr)
```


22. Calculate the cumulative sum of an array.

Scenario:

You have an array. Calculate its cumulative sum.

Logic:

- Use np.cumsum().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
cumulative_sum = np.cumsum(arr)
print(cumulative_sum)
```

23. Calculate the cumulative product of an array.

Scenario:

You have an array. Calculate its cumulative product.

Logic:

- Use np.cumprod().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
cumulative_product = np.cumprod(arr)
print(cumulative_product)
```

24. Find the unique elements in an array.

Scenario:

You have an array. Find its unique elements.

Logic:

- Use np.unique().

Program:

```
import numpy as np
arr = np.array([1, 2, 2, 3, 3, 3])
unique_elements = np.unique(arr)
print(unique_elements)
```

25. Sort an array along a specific axis.

Scenario:

You have a 2D array. Sort it along the second axis.

Logic:

- Use `np.sort()` with `axis=1`.

Program:

```
import numpy as np
arr = np.array([[3, 1], [2, 4]])
sorted_arr = np.sort(arr, axis=1)
print(sorted_arr)
```

26. Find the indices that would sort an array.

Scenario:

You have an array. Find the indices that would sort it.

Logic:

- Use `np.argsort()`.

Program:

```
import numpy as np
arr = np.array([3, 1, 2])
sorted_indices = np.argsort(arr)
print(sorted_indices)
```

27. Reverse an array.

Scenario:

You have an array. Reverse its elements.

Logic:

- Use slicing `[::-1]`.

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
reversed_arr = arr[::-1]
print(reversed_arr)
```

28. Find the index of the maximum value in an array.

Scenario:

You have an array. Find the index of the maximum value.

Logic:

- Use np.argmax().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
max_index = np.argmax(arr)
print(max_index)
```

29. Find the index of the minimum value in an array.

Scenario:

You have an array. Find the index of the minimum value.

Logic:

- Use np.argmin().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
min_index = np.argmin(arr)
print(min_index)
```

30. Replace all occurrences of a value in an array.

Scenario:

You have an array. Replace all occurrences of a value (e.g., 2) with another value (e.g., 10).

Logic:

- Use np.where().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 2, 5])
replaced_arr = np.where(arr == 2, 10, arr)
print(replaced_arr)
```

31. Find the median of an array.

Scenario:

You have an array. Calculate its median.

Logic:

- Use np.median().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
median = np.median(arr)
print(median)
```

32. Calculate the standard deviation of an array.

Scenario:

You have an array. Calculate its standard deviation.

Logic:

- Use np.std().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
std_dev = np.std(arr)
print(std_dev)
```

33. Calculate the variance of an array.

Scenario:

You have an array. Calculate its variance.

Logic:

- Use np.var().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
variance = np.var(arr)
print(variance)
```

34. Find the percentile of an array.

Scenario:

You have an array. Find the 75th percentile.

Logic:

- Use np.percentile().

Program:

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
percentile_75 = np.percentile(arr, 75)
print(percentile_75)
```

35. Generate a random array and shuffle it.

Scenario:

You need to generate a random array and shuffle its elements.

Logic:

- Use np.random.rand() and np.random.shuffle().

Program:

```
import numpy as np
arr = np.random.rand(5)
np.random.shuffle(arr)
print(arr)
```

36. Generate a random array with a specific shape.

Scenario:

You need to generate a random array of shape (3, 3).

Logic:

- Use np.random.rand().

Program:

```
import numpy as np
arr = np.random.rand(3, 3)
print(arr)
```

37. Generate a random integer array within a range.

Scenario:

You need to generate a random integer array with values between 1 and 10.

Logic:

- Use `np.random.randint()`.

Program:

```
import numpy as np
arr = np.random.randint(1, 10, size=(3, 3))
print(arr)
```

38. Create an identity matrix.

Scenario:

You need to create a 3x3 identity matrix.

Logic:

- Use `np.eye()`.

Program:

```
import numpy as np
identity_matrix = np.eye(3)
print(identity_matrix)
```

39. Create a diagonal matrix from a 1D array.

Scenario:

You have a 1D array. Create a diagonal matrix from it.

Logic:

- Use `np.diag()`.

Program:

```
import numpy as np
arr = np.array([1, 2, 3])
diagonal_matrix = np.diag(arr)
print(diagonal_matrix)
```

40. Extract the diagonal elements of a 2D array.

Scenario:

You have a 2D array. Extract its diagonal elements.

Logic:

- Use np.diag().

Program:

```
import numpy as np
arr = np.array([[1, 2], [3, 4]])
diagonal_elements = np.diag(arr)
print(diagonal_elements)
```