Introducing Google Al Edge Portal (https://ai.google.dev/edge/ai-edge-portal): Benchmark Edge Al at scale.

Sign-up

(https://docs.google.com/forms/d/e/1FAIpQLSfTcGPycQve8TLAsfH46pBIXBZe9FrgJAClwbF7DeL1LgVn4Q/viewform)

to request access during private preview.

Pose landmark detection guide

The MediaPipe Pose Landmarker task lets you detect landmarks of human bodies in an image or video. You can use this task to identify key body locations, analyze posture, and categorize movements. This task uses machine learning (ML) models that work with single images or video. The task outputs body pose landmarks in image coordinates and in 3-dimensional world coordinates.



<u>Try it!</u> → (https://mediapipe-studio.webapps.google.com/demo/pose_landmarker)

Get Started

Start using this task by following the implementation guide for your target platform. These platform-specific guides walk you through a basic implementation of this task, including a recommended model, and code example with recommended configuration options:

- Android Code example
 - (https://github.com/google-ai-edge/mediapipe-samples/tree/main/examples/pose_landmarker/android)
 - <u>Guide</u> (https://ai.google.dev/edge/mediapipe/solutions/vision/pose_landmarker/android)
- Python Code example
 - (https://colab.sandbox.google.com/github/googlesamples/mediapipe/blob/main/examples/pose_land marker/python/%5BMediaPipe_Python_Tasks%5D_Pose_Landmarker.ipynb)
 - Guide (https://ai.google.dev/edge/mediapipe/solutions/vision/pose_landmarker/python)
- **Web** <u>Code example</u> (https://codepen.io/mediapipe-preview/pen/abRLMxN) <u>Guide</u> (https://ai.google.dev/edge/mediapipe/solutions/vision/pose_landmarker/web_js)

Task details

This section describes the capabilities, inputs, outputs, and configuration options of this task.

Features

- **Input image processing** Processing includes image rotation, resizing, normalization, and color space conversion.
- Score threshold Filter results based on prediction scores.

Task inputs	Task outputs
The Pose Landmarker accepts an input of one of the following data types:	The Pose Landmarker outputs the following results:
Still imagesDecoded video framesLive video feed	 Pose landmarks in normalized image coordinates Pose landmarks in world coordinates Optional: a segmentation mask for the pose.

Configurations options

This task has the following configuration options:

Description	Value Range	Defaul Value
Sets the running mode for the task. There are three modes:	{IMAGE, VIDEO. LIVE_	IMAGE
IMAGE: The mode for single image inputs.	STREAM}	
VIDEO: The mode for decoded frames of a video.		
LIVE_STREAM: The mode for a livestream of input data, such as from a camera. In this mode, resultListener must be called to set up a listener to receive results asynchronously.		
The maximum number of poses that can be detected by the Pose Landmarker.	Integer > 0	1
The minimum confidence score for the pose detection to be considered successful.	Float [0.0, 1.0]	0.5
	Sets the running mode for the task. There are three modes: IMAGE: The mode for single image inputs. VIDEO: The mode for decoded frames of a video. LIVE_STREAM: The mode for a livestream of input data, such as from a camera. In this mode, resultListener must be called to set up a listener to receive results asynchronously. The maximum number of poses that can be detected by the Pose Landmarker. The minimum confidence score for the pose detection to be	Sets the running mode for the task. There are three modes: {IMAGE, VIDEO, LIVE_IMAGE: The mode for single image inputs. STREAM} VIDEO: The mode for decoded frames of a video. LIVE_STREAM: The mode for a livestream of input data, such as from a camera. In this mode, resultListener must be called to set up a listener to receive results asynchronously. The maximum number of poses that can be detected by the Integer > 0 Pose Landmarker. The minimum confidence score for the pose detection to be Float [0.0,

Option Name	Description	Value Range	Default Value
min_pose_ presence_ confidence	The minimum confidence score of pose presence score in the pose landmark detection.	Float [0.0, 1.0]	0.5
min_tracking_ confidence	The minimum confidence score for the pose tracking to be considered successful.	Float [0.0, 1.0]	0.5
output_ segmentation_ masks	Whether Pose Landmarker outputs a segmentation mask for the detected pose.	Boolean	False
result_callback	Sets the result listener to receive the landmarker results asynchronously when Pose Landmarker is in the live stream mode. Can only be used when running mode is set to LIVE_STREAM	Result Listener	N/A

Models

The Pose Landmarker uses a series of models to predict pose landmarks. The first model detects the presence of human bodies within an image frame, and the second model locates landmarks on the bodies.

The following models are packaged together into a downloadable model bundle:

- Pose detection model: detects the presence of bodies with a few key pose landmarks.
- **Pose landmarker model**: adds a complete mapping of the pose. The model outputs an estimate of 33 3-dimensional pose landmarks.

This bundle uses a convolutional neural network similar to MobileNetV2
(https://arxiv.org/pdf/1801.04381.pdf) and is optimized for on-device, real-time fitness applications.
This variant of the BlazePose (https://arxiv.org/pdf/2006.10204.pdf) model uses GHUM
(https://openaccess.thecvf.com/content_CVPR_2020/papers/Xu_GHUM__GHUML_Generative_3D_Human_Sh ape_and_Articulated_Pose_CVPR_2020_paper.pdf)


, a 3D human shape modeling pipeline, to estimate the full 3D body pose of an individual in images or videos.

Attention: This MediaPipe Solutions Preview is an early release. <u>Learn more</u> (/edge/mediapipe/solutions/about#notice).

Model bundle	Input shap	Dat e typ:
Pose landmarker (lite) (https://storage.googleapis.com/mediapipe- models/pose_landmarker/pose_landmarker_lite/float16/latest/pose_landmarker_lite.task)		floa 16 x r:
Pose landmarker (Full) (https://storage.googleapis.com/mediapipe-models/pose_landmarker/pose_landmarker_full/float16/latest/pose_landmarker_full.task)	Pose detector: 224 x 224 x 3 Pose landmarker 256 x 256 x 3	r:
Pose landmarker (Heavy) (https://storage.googleapis.com/mediapipe- models/pose_landmarker/pose_landmarker_heavy/float16/latest/pose_landmarker_heavy.tasl	Pose detector: k)224 x 224 x 3 Pose landmarke 256 x 256 x	r:

Pose landmarker model

The pose landmarker model tracks 33 body landmark locations, representing the approximate location of the following body parts:



- 0 nose
- 1 left eye (inner)
- 2 left eye
- 3 left eye (outer)
- 4 right eye (inner)
- 5 right eye
- 6 right eye (outer)
- 7 left ear
- 8 right ear
- 9 mouth (left)
- 10 mouth (right)
- 11 left shoulder
- 12 right shoulder
- 13 left elbow

- 14 right elbow
- 15 left wrist
- 16 right wrist
- 17 left pinky
- 18 right pinky
- 19 left index
- 20 right index
- 21 left thumb
- 22 right thumb
- 23 left hip
- 24 right hip
- 25 left knee
- 26 right knee
- 27 left ankle
- 28 right ankle
- 29 left heel
- 30 right heel
- 31 left foot index
- 32 right foot index

The model output contains both normalized coordinates (Landmarks) and world coordinates (WorldLandmarks) for each landmark.

Except as otherwise noted, the content of this page is licensed under the <u>Creative Commons Attribution 4.0 License</u> (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the <u>Apache 2.0 License</u> (https://www.apache.org/licenses/LICENSE-2.0). For details, see the <u>Google Developers Site Policies</u> (https://developers.google.com/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated 2025-01-13 UTC.