

```

1  /** 125 - Numbering Paths:
2  Given the Number of roads m. Then the next m lines, each will contain two integer u and v,
3  indicating there is a one way road from city u to city v. You have to determine the number
4  of different routes between each city to all the city. City are numbered from 0
5  to largest all max(u,v). Consider four city are connected by the following one-way streets:
6  0-->1, 0-->2, 1-->2, 2-->3.
7  There is one route from intersection 0 to 1, two routes from 0 to 2 (the routes are 0-->1-->2
8  and 0-->2), one route from 0 to 3, one route from 1 to 2, one route from 1 to 3, one route from
9  2 to 3, and no other routes. It is possible that an infinite number of different routes
10 to exist for two cities. For example if we added a road 3-->2 in the list, then there is
11 still only one route from 0 to 1, but there are infinitely many different routes from 0 to 2.
12 Because the street from 2 to 3 and back to 2 can be repeated yielding a different sequence of
13 streets and hence a different route. Thus the route 0-->2-->3-->2-->3-->2 is a different
14 route than 0-->2-->3-->2.
15 For each test case, a square matrix of the number of different routes from city j to city k
16 is printed. If the matrix is denoted M, then M[j][k] is the number of different routes
17 from city j to city k. If there are an infinite number of different paths between
18 two city a '-1' should be printed.
19 */
20 vector<int>ed[105]; int n,m,way[105][105];
21 void floydWarshall(){
22     for(int k=0; k<=n; k++){
23         for(int i=0; i<=n; i++){
24             for(int j=0; j<=n; j++){
25                 if(way[i][k]!=0 && way[k][j]!=0){
26                     way[i][j] += way[i][k]*way[k][j];
27                 }
28             }
29         }
30     }
31
32     for(int k=0; k<=n; k++){
33         if(way[k][k]!=0) { // have a cycle
34             for(int i=0; i<=n; i++){
35                 for(int j=0; j<=n; j++){
36                     if(way[i][k]!=0 && way[k][j]!=0) {
37                         way[i][j] = -1;
38                     }
39                 }
40             }
41         }
42     }
43 }
44 int main(){
45     int ks=0;
46     while(scanf("%d",&m)==1){
47         n=0; memset(way,0,sizeof(way));
48         for(int i=1; i<=m; i++){
49             int u,v; scanf("%d%d",&u,&v);
50             n = max(n,max(u,v));
51             ed[u].push_back(v);
52             way[u][v]=1;
53         }
54
55         floydWarshall();
56
57         printf("matrix for city %d\n",ks++);
58         for(int i=0; i<=n; i++){
59             for(int j=0; j<=n; j++){
60                 if(j==0)printf("%d",way[i][j]);
61                 else printf(" %d",way[i][j]);
62             }
63             printf("\n");
64         }
65         for(int i=0; i<=n; i++)ed[i].clear();
66     }
67 }

```