



# TECHNOTHERM INDUSTRIES LLP

103, Yamini Industrial Estate No. 2, Bhoidapada, Vasai (East),

Dist. Palghar - 401 210. Maharashtra, India

Tel: +91 99209 70209 Email: [thermojacket@yahoo.com](mailto:thermojacket@yahoo.com)

---

## TECHNICAL DATA SHEET

### **THERMO-FLEX™**

### **Self-Limiting Self-Regulating Heating Cable (SLSR)**

#### **1. Product Overview**

**THERMO-FLEX** Heating Cable is engineered for reliable freeze protection and process temperature maintenance. Its PTC/FEP core automatically adjusts heat output relative to surface temperature, ensuring energy savings and safe operation.

#### **2. Electrical Specifications**

| <u>Parameter</u>       | <u>Specification</u> |
|------------------------|----------------------|
| Rated Voltage          | 220–230 V AC         |
| Output Power @ 10°C    | 12 W/m               |
| Maximum Circuit Length | 100 m                |

#### **3. Construction Detail**

| <u>Component</u>   | <u>Material / Specification</u>      |
|--------------------|--------------------------------------|
| Bus Wires          | Tinned Copper, 7 × 0.4mm             |
| Heating Core       | <b>PTC Self-Regulating</b> Conductor |
| Primary Insulation | Polyolefin                           |
| Metallic Shield    | Al-Mg Alloy                          |
| Outer Jacket       | Polyolefin                           |
| Cable Dimensions   | <b>9.8 mm × 4.7 mm (W × H)</b>       |

#### **4. Temperature Ratings**

| <u>Parameter</u>                 | <u>Value</u> |
|----------------------------------|--------------|
| Minimum Installation Temperature | –40°C        |
| Maximum Tolerance Temperature    | 105°C        |
| Maximum Maintain Temperature     | 65°C± 5°C    |



# TECHNOTHERM INDUSTRIES LLP

103, Yamini Industrial Estate No. 2, Bhoidapada, Vasai (East),

Dist. Palghar - 401 210. Maharashtra, India

Tel: +91 99209 70209 Email: [thermojacket@yahoo.com](mailto:thermojacket@yahoo.com)

---

## 5. Key Features

- Self-regulating technology: prevents overheating
- Energy-efficient power adjustment
- Cut-to-length flexibility during installation
- Durable moisture-resistant jacket
- Rugged Al-Mg metallic shield for enhanced grounding
- Suitable for harsh environments

## 6. Applications

- Industrial & commercial pipe freeze protection
- Temperature maintenance systems
- Roof/gutter de-icing
- Pipe, Tank and vessel heating
- Fire protection & sprinkler lines

## 7. Ordering Information

| Model                         | Voltage   | Output Power | Jacket     | Maximum Length |
|-------------------------------|-----------|--------------|------------|----------------|
| <b><i>THERMO-FLEX</i></b> 12W | 220–230 V | 12W/m        | Polyolefin | 100 m          |

## 8. Safety & Compliance

- Designed for harsh outdoor and industrial environments
- Compatible with standard circuit protection devices
- Follow installation guidelines and electrical standards