



TECHNOTHERM INDUSTRIES LLP

103, Yamini Industrial Estate No. 2, Bhoidapada, Vasai (East),

Dist. Palghar - 401 210. Maharashtra, India

Tel: +91 99209 70209 Email: thermojacket@yahoo.com

TECHNICAL DATA SHEET

HERMO-FLEX™

Self-Limiting Self-Regulating Heating Cable (SLSR)

1. Product Overview

HERMO-FLEX Heating Cable is engineered for reliable freeze protection and process temperature maintenance. Its PTC/FEP core automatically adjusts heat output relative to surface temperature, ensuring energy savings and safe operation.

2. Electrical Specifications

Parameter	Specification
Rated Voltage	220-230 V AC
Output Power @ 10°C	25 W/m
Maximum Circuit Length	100 m

3. Construction Detail

Component	Material / Specification
Bus Wires	Tinned Copper, 7 × 0.4mm
Heating Core	PTC Self-Regulating Conductor
Primary Insulation	Polyolefin
Metallic Shield	Al-Mg Alloy Braid
Outer Jacket	Polyolefin
Cable Dimensions	9.8 mm × 4.9 mm (W × H)



4. Temperature Ratings

Parameter	Value
Minimum Installation Temperature	-40°C
Maximum Tolerance Temperature	105°C
Maximum Maintain Temperature	65°C



TECHNOTHERM INDUSTRIES LLP

103, Yamini Industrial Estate No. 2, Bhoidapada, Vasai (East),

Dist. Palghar - 401 210. Maharashtra, India

Tel: +91 99209 70209 Email: thermojacket@yahoo.com

5. Key Features

- Self-regulating technology: prevents overheating
- Energy-efficient power adjustment
- Cut-to-length flexibility during installation
- Durable moisture-resistant jacket
- Rugged Al-Mg metallic shield for enhanced grounding
- Suitable for harsh environments

6. Applications

- Industrial & commercial pipe freeze protection
- Temperature maintenance systems
- Roof/gutter de-icing
- Pipe, Tank and vessel heating
- Fire protection & sprinkler lines

7. Ordering Information

Model	Voltage	Output Power	Jacket	Maximum Length
THERMO-FLEX 25W	220–230 V	25 W/m	Polyolefin	100 m

8. Safety & Compliance

- Designed for harsh outdoor and industrial environments
- Compatible with standard circuit protection devices
- Follow installation guidelines and electrical standards

