```
import pandas as pd
import numpy as np
import torch
import torch.nn as nn
import torch.optim as optim
from sklearn.preprocessing import MinMaxScaler, OneHotEncoder
from sklearn.compose import ColumnTransformer
from google.colab import drive, files
```

```
# Mount Google Drive
from google.colab import drive
drive.mount('/content/drive', force_remount = True)
```

```
Mounted at /content/drive
```

```
import matplotlib.pyplot as plt
import seaborn as sns
```

```
file_path = '/content/drive/My Drive/Upgrad MS Dataset'

# 3. Read the 4th sheet (index 3)
df = pd.read_csv(f'{file_path}/batsmen_final_data.csv')
```

```
print(df)
```

```
436              132.45               1880           34.96           75
437              146.66               1151           24.67           55
438              147.57               7088           41.70          124
```

```
..                      ...                             ...                  ...
435                       2                               3                   26
436                       0                              11                   34
437                       1                               4                   34
438                      24                              36                   31
439                       0                               2                   29

    Capped or Uncapped  Last Auction Price Sold (in Crs)  Unnamed: 16  \
0               Capped                             21.00          NaN
1               Capped                             16.35          NaN
2               Capped                             16.35          NaN
3               Capped                             16.35          NaN
4               Capped                             26.75          NaN
..                 ...                               ...          ...
435             Capped                             10.15          NaN
436           Uncapped                              5.49          NaN
437             Capped                              4.79          NaN
438             Capped                              1.69          NaN
439           Uncapped                              2.81          NaN

    Auction_Value_Category
0               High Value
1               High Value
2               High Value
3               High Value
4               High Value
..                     ...
435             High Value
436             High Value
437             High Value
438              Mid Value
439              Mid Value

[440 rows x 18 columns]
```

```
df['Last Auction Price Sold (in Crs)'].mean()
```

```
np.float64(4.80075)
```

```
print(df['Capped or Uncapped'].value_counts())
```

```
Capped or Uncapped
Capped      342
Uncapped     98
Name: count, dtype: int64
```

```
print(df['Country'].value_counts())
```

```
Country
India           168
England          88
Australia        47
Afghanistan      26
New Zealand      23
```

```
Sri Lanka        20
South Africa     18
West Indies      10
Bangladesh        8
Zimbabwe          8
Ireland           7
USA               7
Netherlands       5
Nepal             5
Name: count, dtype: int64
```

```
print(df_scrambled['No of Fours'].value_counts())
```

```
No of Fours
113    6
94     5
18     5
107    5
171    5
      ..
261    1
971    1
313    1
578    1
360    1
Name: count, Length: 280, dtype: int64
```

```
print(df_scrambled)
```

```
437      Player_259  International        India  Batsman              128.95
438      Player_346  International    Australia  Batsman              197.16
439       Player_13  International      England  Batsman              133.96

     Batsmen Total Runs  Batting Average  No of Sixes  No of Fours  \
0                  1749            29.25          107          206
1                   908            27.80           51           76
2                 10115            31.08          171          492
3                  4430            27.37           99          444
4                  3082            30.13          196          219
..                  ...              ...          ...          ...
435                3266            30.56          123          313
436                6036            42.13          137          578
437                3347            27.54           79          360
438                 866            34.68           39           94
439                1932            27.68           83          171
```

```
436         3631                          2076                      11
437         2688                          1386                       1
438          344                           136                       2
439         1454                           480                       1

     No of Half Centuries Scored  Age of the Player Capped or Uncapped  \
0                             11                 25             Capped
1                              6                 22           Uncapped
2                             33                 35             Capped
3                             25                 34             Capped
4                             10                 39           Uncapped
..                           ...                ...                ...
435                           23                 35             Capped
436                           58                 33             Capped
437                           17                 32             Capped
438                            3                 26             Capped
439                           11                 27             Capped

     Last Auction Price Sold (in Crs)  Unnamed: 16 Auction_Value_Category
0                               15.08          NaN             High Value
1                                0.00          NaN              Low Value
2                                1.49          NaN              Mid Value
3                                0.73          NaN              Low Value
4                                8.12          NaN             High Value
..                                ...          ...                    ...
435                              7.37          NaN             High Value
436                              3.85          NaN              Mid Value
437                              2.42          NaN              Mid Value
438                             10.15          NaN             High Value
439                              1.65          NaN              Mid Value

[440 rows x 18 columns]
```

```
df_scrambled.drop(['Unnamed: 16'],axis = 1,inplace = True)
```

# Task

The user wants to perform an Exploratory Data Analysis (EDA) on the `df_scrambled` DataFrame, which includes displaying basic information, analyzing the distribution of numerical and categorical features, examining relationships between features and the target variable ('Last Auction Price Sold (in Crs)'), and visualizing correlations.

To achieve this, I will execute the following steps:

1. **Initial Data Overview**: Display `df_scrambled.info()`, `df_scrambled.describe()`, and `df_scrambled.head()`.
2. **Target Variable Distribution**: Plot a histogram and KDE for 'Last Auction Price Sold (in Crs)'.

3. **Numerical Features Distribution**: Generate histograms and box plots for all other numerical features.
4. **Categorical Features Distribution**: Create countplots for the categorical features.
5. **Bivariate Analysis (Numerical vs. Target)**: Generate scatter plots of numerical features against the target variable.
6. **Bivariate Analysis (Categorical vs. Target)**: Create box plots of the target variable grouped by categorical features.
7. **Correlation Heatmap**: Compute and visualize the correlation matrix for all numerical features.
8. **Final Task**: Summarize the findings.

I will now write and execute the Python code for these steps.

```
# Initial Data Overview
print("--- Initial Data Overview ---")
print("\nDataFrame Info:")
df_scrambled.info()

print("\nDataFrame Description:")
print(df_scrambled.describe())

print("\nDataFrame Head:")
print(df_scrambled.head())

# Target Variable Distribution
target_variable = 'Last Auction Price Sold (in Crs)'
plt.figure(figsize=(10, 6))
sns.histplot(df_scrambled[target_variable], kde=True, color='skyblue')
plt.title(f'Distribution of {target_variable}')
plt.xlabel(target_variable)
plt.ylabel('Frequency')
plt.grid(True, linestyle='--', alpha=0.6)
plt.legend([f'KDE for {target_variable}'])
plt.tight_layout()
plt.savefig('target_distribution_scrambled.png')
plt.show()

# Numerical Features Distribution
numerical_cols = df_scrambled.select_dtypes(include=np.number).columns.tolist()
numerical_cols.remove(target_variable) # Exclude target variable from this analysis

print("\n--- Numerical Features Distribution ---")
```

```
for col in numerical_cols:
    plt.figure(figsize=(15, 6))

    # Histogram
    plt.subplot(1, 2, 1)
    sns.histplot(df_scrambled[col], kde=True, color='lightcoral')
    plt.title(f'Distribution of {col}')
    plt.xlabel(col)
    plt.ylabel('Frequency')
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.legend([f'KDE for {col}'])


    # Box plot
    plt.subplot(1, 2, 2)
    sns.boxplot(y=df_scrambled[col], color='lightgreen')
    plt.title(f'Box Plot of {col}')
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)

    plt.tight_layout()
    plt.savefig(f'numerical_distribution_{col}.png')
    plt.show()

# Categorical Features Distribution
categorical_cols = ['Category', 'Country', 'Role', 'Auction_Value_Category', 'Capp

print("\n--- Categorical Features Distribution ---")
for col in categorical_cols:
    plt.figure(figsize=(12, 7))
    sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().inde
    plt.title(f'Distribution of {col}')
    plt.xlabel('Count')
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'categorical_distribution_{col}.png')
    plt.show()

# Bivariate Analysis (Numerical vs. Target)
print("\n--- Bivariate Analysis (Numerical vs. Target) ---")
for col in numerical_cols:
    plt.figure(figsize=(10, 6))
```

```
    sns.scatterplot(x=df_scrambled[col], y=df_scrambled[target_variable], color='pu
    plt.title(f'{col} vs. {target_variable}')
    plt.xlabel(col)
    plt.ylabel(target_variable)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'bivariate_numerical_{col}.png')
    plt.show()

# Bivariate Analysis (Categorical vs. Target)
print("\n--- Bivariate Analysis (Categorical vs. Target) ---")
for col in categorical_cols:
    plt.figure(figsize=(12, 7))
    sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='cool
    plt.title(f'{target_variable} vs. {col}')
    plt.xlabel(target_variable)
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'bivariate_categorical_{col}.png')
    plt.show()

# Correlation Heatmap
print("\n--- Correlation Heatmap ---")
correlation_matrix = df_scrambled[numerical_cols + [target_variable]].corr()
plt.figure(figsize=(14, 10))
sns.heatmap(correlation_matrix, annot=True, cmap='coolwarm', fmt=".2f", linewidths=
plt.title('Correlation Matrix of Numerical Features')
plt.tight_layout()
plt.savefig('correlation_heatmap_scrambled.png')
plt.show()
```

## Initial Data Overview

### Subtask:

Display the basic information (`info()`), descriptive statistics (`describe()`), and the first few rows (`head()`) of the `df_scrambled` DataFrame to get a preliminary understanding of its structure, data types, and value ranges.

**Reasoning**: The subtask requires displaying basic information, descriptive statistics, and the first few rows of the `df_scrambled` DataFrame. I will generate a code block that uses `info()`, `describe()`, and `head()` methods along with descriptive headers.

```
print('--- Initial Data Overview ---')
print('\nDataFrame Info:')
df_scrambled.info()
print('\nDataFrame Description:')
print(df_scrambled.describe())
print('\nDataFrame Head:')
print(df_scrambled.head())
```

```
3                           802                       2
4                           613                       1

   No of Half Centuries Scored  Age of the Player Capped or Uncapped  \
0                           11                 25             Capped
1                            6                 22           Uncapped
2                           33                 35             Capped
3                           25                 34             Capped
4                           10                 39           Uncapped

   Last Auction Price Sold (in Crs) Auction_Value_Category
0                             15.08             High Value
1                              0.00              Low Value
2                              1.49              Mid Value
3                              0.73              Low Value
4                              8.12             High Value
```

**Reasoning**: To understand the distribution of the target variable, 'Last Auction Price Sold (in Crs)', I will generate a histogram with a Kernel Density Estimate (KDE) plot. This will visually represent its spread, central tendency, and any skewness.

```
target_variable = 'Last Auction Price Sold (in Crs)'
plt.figure(figsize=(10, 6))
sns.histplot(df_scrambled[target_variable], kde=True, color='skyblue')
plt.title(f'Distribution of {target_variable}')
plt.xlabel(target_variable)
plt.ylabel('Frequency')
plt.grid(True, linestyle='--', alpha=0.6)
plt.legend([f'KDE for {target_variable}'])
plt.tight_layout()
plt.savefig('target_distribution_scrambled.png')
plt.show()
```




**Reasoning**: To analyze the distribution of other numerical features, I will generate histograms with KDE and box plots for each numerical column in `df_scrambled`, excluding the target variable. This will help identify their spread, central tendency, and presence of outliers.

```
numerical_cols = df_scrambled.select_dtypes(include=np.number).columns.tolist()
target_variable = 'Last Auction Price Sold (in Crs)' # Ensure target_variable i
numerical_cols.remove(target_variable) # Exclude target variable from this anal

print("--- Numerical Features Distribution ---")
for col in numerical_cols:
    plt.figure(figsize=(15, 6))

    # Histogram
    plt.subplot(1, 2, 1)
    sns.histplot(df_scrambled[col], kde=True, color='lightcoral')
    plt.title(f'Distribution of {col}')
    plt.xlabel(col)
    plt.ylabel('Frequency')
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.legend([f'KDE for {col}'])


    # Box plot
    plt.subplot(1, 2, 2)
    sns.boxplot(y=df_scrambled[col], color='lightgreen')
    plt.title(f'Box Plot of {col}')
    plt.ylabel(col)
```

```
plt.grid(True, linestyle='--', alpha=0.6)

plt.tight_layout()
plt.savefig(f'numerical_distribution_{col}.png')
plt.show()
```


Frequency
Batting Strike Rate
Batting Strike Rate


Distribution of Batsmen Total Runs
KDE for Batsmen Total Runs
Frequency
Batsmen Total Runs
Box Plot of Batsmen Total Runs
Batsmen Total Runs


Distribution of Batting Average
KDE for Batting Average
Frequency
Batting Average
Box Plot of Batting Average
Batting Average


Distribution of No of Sixes
KDE for No of Sixes
Frequency
No of Sixes
Box Plot of No of Sixes
No of Sixes


Distribution of No of Fours
KDE for No of Fours
Frequency
No of Fours


Box Plot of No of Fours
No of Fours


Distribution of Balls Faced
KDE for Balls Faced
Frequency
Balls Faced


Box Plot of Balls Faced
Balls Faced


Distribution of Total career dot balls played
KDE for Total career dot balls played
Frequency
Total career dot balls played


Box Plot of Total career dot balls played
Total career dot balls played


Distribution of No of Centuries Scored
KDE for No of Centuries Scored
Frequency
No of Centuries Scored


Box Plot of No of Centuries Scored
No of Centuries Scored


Distribution of No of Half Centuries Scored
KDE for No of Half Centuries Scored


Box Plot of No of Half Centuries Scored

**Reasoning**: To analyze the distribution of categorical features, I will generate countplots for each categorical column. This will help in understanding the frequency of each category within these features.




```
categorical_cols = ['Category', 'Country', 'Role', 'Auction_Value_Category',

print("--- Categorical Features Distribution ---")
for col in categorical_cols:
    plt.figure(figsize=(12, 7))
    sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts(
    plt.title(f'Distribution of {col}')
    plt.xlabel('Count')
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'categorical_distribution_{col}.png')
    plt.show()
```



```
Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().in
```




```
/tmp/ipykernel_562/2302480829.py:6: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().in
```




```
/tmp/ipykernel_562/2302480829.py:6: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().in
```




```
/tmp/ipykernel_562/2302480829.py:6: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().in
```




```
/tmp/ipykernel_562/2302480829.py:6: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().in
```



**Reasoning**: The previous code block generated a FutureWarning because `palette` was used without explicitly assigning a `hue` argument in `sns.countplot`. To fix this and comply with the suggested change, I will explicitly set `hue` to the `col` variable and `legend=False`.

```
categorical_cols = ['Category', 'Country', 'Role', 'Auction_Value_Category', 'C

print("--- Categorical Features Distribution ---")
for col in categorical_cols:
    plt.figure(figsize=(12, 7))
    sns.countplot(y=df_scrambled[col], order=df_scrambled[col].value_counts().i
    plt.title(f'Distribution of {col}')
    plt.xlabel('Count')
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'categorical_distribution_{col}.png')
    plt.show()
```










**Reasoning**: To perform bivariate analysis for numerical features against the target variable, I will generate scatter plots for each numerical column in `df_scrambled` against 'Last Auction Price Sold (in Crs)'. This will help visualize potential linear or non-linear relationships.

```
print("\n--- Bivariate Analysis (Numerical vs. Target) ---")
for col in numerical_cols:
    plt.figure(figsize=(10, 6))
    sns.scatterplot(x=df_scrambled[col], y=df_scrambled[target_variable], color
```

```
plt.title(f'{col} vs. {target_variable}')
plt.xlabel(col)
plt.ylabel(target_variable)
plt.grid(True, linestyle='--', alpha=0.6)
plt.tight_layout()
plt.savefig(f'bivariate_numerical_{col}.png')
plt.show()
```







Last Auction Price Sold (in Crs)
Batting Strike Rate

Batsmen Total Runs vs. Last Auction Price Sold (in Crs)
Last Auction Price Sold (in Crs)
Batsmen Total Runs


Batting Average vs. Last Auction Price Sold (in Crs)


Last
Batting Average


No of Sixes vs. Last Auction Price Sold (in Crs)
Last Auction Price Sold (in Crs)
No of Sixes


No of Fours vs. Last Auction Price Sold (in Crs)
Last Auction Price Sold (in Crs)
No of Fours


Balls Faced vs. Last Auction Price Sold (in Crs)
Crs)










No of Half Centuries Scored vs. Last Auction Price Sold (in Crs)

**Reasoning**: To perform bivariate analysis for categorical features against the target variable, I will generate box plots for each categorical column against 'Last Auction Price Sold (in Crs)'. This will help visualize the distribution of the target variable across different categories.

```
print("\n--- Bivariate Analysis (Categorical vs. Target) ---")
for col in categorical_cols:
    plt.figure(figsize=(12, 7))
    sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='
    plt.title(f'{target_variable} vs. {col}')
    plt.xlabel(target_variable)
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'bivariate_categorical_{col}.png')
    plt.show()
```



```
/tmp/ipykernel_562/136314451.py:4: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='c
```




```
/tmp/ipykernel_562/136314451.py:4: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='c
```




```
/tmp/ipykernel_562/136314451.py:4: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in
```

```
sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='c
```




```
/tmp/ipykernel_562/136314451.py:4: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='c
```




```
/tmp/ipykernel_562/136314451.py:4: FutureWarning:

Passing `palette` without assigning `hue` is deprecated and will be removed in

  sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], palette='c
```






**Reasoning**: The previous code block generated a `FutureWarning` because `palette` was used in `sns.boxplot` without explicitly assigning a `hue` argument. To address this warning and follow the suggested fix, I will assign the `y` variable to `hue` and set `legend=False`.

```
print("\n--- Bivariate Analysis (Categorical vs. Target) ---")
for col in categorical_cols:
    plt.figure(figsize=(12, 7))
    sns.boxplot(x=df_scrambled[target_variable], y=df_scrambled[col], hue=df_sc
    plt.title(f'{target_variable} vs. {col}')
    plt.xlabel(target_variable)
    plt.ylabel(col)
    plt.grid(True, linestyle='--', alpha=0.6)
    plt.tight_layout()
    plt.savefig(f'bivariate_categorical_{col}.png')
    plt.show()
```







Last Auction Price Sold (in Crs) vs. Role

**Reasoning**: To analyze the relationships between all numerical features, including the target variable, I will compute and visualize the correlation matrix using a heatmap. This will help identify highly correlated features.

```
print("\n--- Correlation Heatmap ---")
correlation_matrix = df_scrambled[numerical_cols + [target_variable]].corr()
plt.figure(figsize=(14, 10))
sns.heatmap(correlation_matrix, annot=True, cmap='coolwarm', fmt=".2f", linewic
plt.title('Correlation Matrix of Numerical Features')
```

```
plt.tight_layout()
plt.savefig('correlation_heatmap_scrambled.png')
plt.show()
```

```
--- Correlation Heatmap ---
```




# Summary of EDA Findings

Based on the comprehensive Exploratory Data Analysis performed on the `df_scrambled` DataFrame, here's a summary of the key observations:

## 1. Initial Data Overview:

- The DataFrame `df_scrambled` contains 440 entries and 17 columns.
- There are no missing values in any of the columns, indicating a clean dataset in terms of completeness.
- Data types are appropriate, with `float64` for numerical values like 'Batting Strike Rate' and 'Last Auction Price Sold (in Crs)', `int64` for count-based features, `object` for categorical text, and `category` for 'Auction_Value_Category'.
- The descriptive statistics reveal wide ranges for many numerical features (e.g., 'Batsmen Total Runs', 'No of Sixes', 'No of Fours'), suggesting potential outliers or

highly varied player performances.

## 2. Target Variable Distribution ('Last Auction Price Sold (in Crs)'):

- The distribution of 'Last Auction Price Sold (in Crs)' is heavily skewed to the right, indicating that most players have lower auction prices, with a few players fetching exceptionally high prices.
- The KDE plot confirms this positive skewness, showing a long tail towards higher values.

## 3. Numerical Features Distribution:

- Many numerical features like 'Batsmen Total Runs', 'No of Sixes', 'No of Fours', 'Balls Faced', 'Total career dot balls played', 'No of Centuries Scored', and 'No of Half Centuries Scored' also exhibit right-skewed distributions, similar to the target variable. This implies a large number of players with lower stats and a smaller group of high-performing players.
- 'Batting Strike Rate' and 'Batting Average' generally show more symmetric distributions, though 'Batting Average' has some outliers at higher values.
- 'Age of the Player' appears somewhat normally distributed but with a range that suggests both young prospects and veteran players.
- Box plots consistently show a significant number of outliers for most performance-related metrics, further emphasizing the disparity in player statistics.

## 4. Categorical Features Distribution:

- **Category**: The majority of players are 'International', with a smaller proportion being 'Domestic'.
- **Country**: India has the highest number of players, followed by England and Australia, reflecting common demographics in cricket leagues.
- **Role**: All players are listed as 'Batsman', which is consistent with the dataset's focus.
- **Auction_Value_Category**: There's a distribution across 'Low Value', 'Mid Value', and 'High Value', reflecting the segmentation performed earlier.
- **Capped or Uncapped**: A higher number of players are 'Capped' (experienced international players) compared to 'Uncapped' players.

## 5. Bivariate Analysis (Numerical vs. Target):

- **Strong positive correlations** are observed between 'Last Auction Price Sold (in Crs)' and several performance metrics such as 'Batsmen Total Runs', 'No of Sixes', 'No of Fours', 'Balls Faced', 'Total career dot balls played', 'No of Centuries Scored',

and 'No of Half Centuries Scored'. This suggests that higher performing players generally command higher auction prices.
- 'Batting Strike Rate' and 'Batting Average' show a weaker, but still positive, correlation with the target variable.
- 'Age of the Player' exhibits a relatively scattered relationship, indicating that while experience might play a role, it's not the sole determinant of price.

### 6. Bivariate Analysis (Categorical vs. Target):

- **Category**: 'International' players tend to have significantly higher auction prices than 'Domestic' players, as expected due to their higher profile and experience.
- **Country**: Players from top cricketing nations like India, England, and Australia generally have higher average auction prices, although there is variation within each country.
- **Role**: Since all players are batsmen, this feature does not differentiate auction prices within this dataset.
- **Auction_Value_Category**: This feature, being derived from the target variable, shows clear distinctions in auction prices across its categories.
- **Capped or Uncapped**: 'Capped' players generally have substantially higher auction prices compared to 'Uncapped' players, highlighting the premium on international experience.

### 7. Correlation Heatmap:

- The heatmap confirms strong positive correlations among most performance-related numerical features themselves (e.g., 'Batsmen Total Runs' with 'No of Sixes', 'No of Fours', 'Balls Faced'). This is logical as these metrics are often inter-related aspects of a player's career performance.
- 'Last Auction Price Sold (in Crs)' shows its strongest positive correlations with metrics like 'Batsmen Total Runs', 'No of Sixes', 'No of Fours', indicating these are significant drivers of auction price.

## Summary of EDA Findings

Based on the comprehensive Exploratory Data Analysis performed on the `df_scrambled` DataFrame, here's a summary of the key observations:

### 1. Initial Data Overview:

- The DataFrame `df_scrambled` contains 440 entries and 17 columns.

- There are no missing values in any of the columns, indicating a clean dataset in terms of completeness.
- Data types are appropriate, with `float64` for numerical values like 'Batting Strike Rate' and 'Last Auction Price Sold (in Crs)', `int64` for count-based features, `object` for categorical text, and `category` for 'Auction_Value_Category'.
- The descriptive statistics reveal wide ranges for many numerical features (e.g., 'Batsmen Total Runs', 'No of Sixes', 'No of Fours'), suggesting potential outliers or highly varied player performances.

## 2. Target Variable Distribution ('Last Auction Price Sold (in Crs)'):

- The distribution of 'Last Auction Price Sold (in Crs)' is heavily skewed to the right, indicating that most players have lower auction prices, with a few players fetching exceptionally high prices.
- The KDE plot confirms this positive skewness, showing a long tail towards higher values.

## 3. Numerical Features Distribution:

- Many numerical features like 'Batsmen Total Runs', 'No of Sixes', 'No of Fours', 'Balls Faced', 'Total career dot balls played', 'No of Centuries Scored', and 'No of Half Centuries Scored' also exhibit right-skewed distributions, similar to the target variable. This implies a large number of players with lower stats and a smaller group of high-performing players.
- 'Batting Strike Rate' and 'Batting Average' generally show more symmetric distributions, though 'Batting Average' has some outliers at higher values.
- 'Age of the Player' appears somewhat normally distributed but with a range that suggests both young prospects and veteran players.
- Box plots consistently show a significant number of outliers for most performance-related metrics, further emphasizing the disparity in player statistics.

## 4. Categorical Features Distribution:

- **Category**: The majority of players are 'International', with a smaller proportion being 'Domestic'.
- **Country**: India has the highest number of players, followed by England and Australia, reflecting common demographics in cricket leagues.
- **Role**: All players are listed as 'Batsman', which is consistent with the dataset's focus.
- **Auction_Value_Category**: There's a distribution across 'Low Value', 'Mid Value', and 'High Value', reflecting the segmentation performed earlier.

- **Capped or Uncapped**: A higher number of players are 'Capped' (experienced international players) compared to 'Uncapped' players.

## 5. Bivariate Analysis (Numerical vs. Target):

- **Strong positive correlations** are observed between 'Last Auction Price Sold (in Crs)' and several performance metrics such as 'Batsmen Total Runs', 'No of Sixes', 'No of Fours', 'Balls Faced', 'Total career dot balls played', 'No of Centuries Scored', and 'No of Half Centuries Scored'. This suggests that higher performing players generally command higher auction prices.
- 'Batting Strike Rate' and 'Batting Average' show a weaker, but still positive, correlation with the target variable.
- 'Age of the Player' exhibits a relatively scattered relationship, indicating that while experience might play a role, it's not the sole determinant of price.

## 6. Bivariate Analysis (Categorical vs. Target):

- **Category**: 'International' players tend to have significantly higher auction prices than 'Domestic' players, as expected due to their higher profile and experience.
- **Country**: Players from top cricketing nations like India, England, and Australia generally have higher average auction prices, although there is variation within each country.
- **Role**: Since all players are batsmen, this feature does not differentiate auction prices within this dataset.
- **Auction_Value_Category**: This feature, being derived from the target variable, shows clear distinctions in auction prices across its categories.
- **Capped or Uncapped**: 'Capped' players generally have substantially higher auction prices compared to 'Uncapped' players, highlighting the premium on international experience.

## 7. Correlation Heatmap:

- The heatmap confirms strong positive correlations among most performance-related numerical features themselves (e.g., 'Batsmen Total Runs' with 'No of Sixes', 'No of Fours', 'Balls Faced'). This is logical as these metrics are often inter-related aspects of a player's career performance.
- 'Last Auction Price Sold (in Crs)' shows its strongest positive correlations with metrics like 'Batsmen Total Runs', 'No of Sixes', 'No of Fours', indicating these are significant drivers of auction price.

# Final Task

## Subtask:

Summarize the key findings and insights derived from the complete Exploratory Data Analysis of the `df_scrambled` DataFrame, now including the new `Auction_Value_Category`, and its relationships with 'Last Auction Price Sold (in Crs)'.

# Summary:

## Q&A

The subtask aimed to summarize the key findings and insights derived from the Exploratory Data Analysis (EDA) of the `df_scrambled` DataFrame, including the `Auction_Value_Category`, and its relationships with 'Last Auction Price Sold (in Crs)'.

## Data Analysis Key Findings

- **Data Completeness and Structure**: The `df_scrambled` DataFrame contains 440 entries and 17 columns with no missing values, indicating a clean dataset. Data types are appropriate for their respective features.
- **Target Variable Distribution**: The 'Last Auction Price Sold (in Crs)' exhibits a heavily right-skewed distribution, meaning most players have lower auction prices, while a few command exceptionally high values.
- **Numerical Features Distribution**: Most performance-related numerical features such as 'Batsmen Total Runs', 'No of Sixes', and 'No of Fours' also show right-skewed distributions, with a significant presence of outliers. 'Batting Strike Rate' and 'Batting Average' are more symmetrically distributed, while 'Age of the Player' is somewhat normally distributed.
- **Categorical Features Distribution**:
    - The majority of players are categorized as 'International'.
    - India has the highest representation among countries.
    - All players in the dataset are 'Batsman'.
    - There are more 'Capped' (experienced international) players than 'Uncapped' players.
- **Strong Positive Bivariate Relationships (Numerical)**: 'Last Auction Price Sold (in Crs)' shows strong positive correlations with key performance metrics such as

'Batsmen Total Runs', 'No of Sixes', 'No of Fours', 'Balls Faced', 'Total career dot balls played', 'No of Centuries Scored', and 'No of Half Centuries Scored'.

- **Significant Bivariate Relationships (Categorical)**:
  - 'International' players tend to achieve significantly higher auction prices compared to 'Domestic' players.
  - 'Capped' players also command substantially higher auction prices than 'Uncapped' players, underscoring the value of international experience.
  - Players from prominent cricketing nations like India, England, and Australia generally have higher average auction prices.
- **Correlation Heatmap Confirmation**: The heatmap reinforced the strong positive correlations observed between 'Last Auction Price Sold (in Crs)' and performance metrics like 'Batsmen Total Runs', 'No of Sixes', and 'No of Fours', suggesting these are major drivers of auction price.

### Insights or Next Steps

- The heavily skewed distribution of the target variable and several numerical features suggests that data transformations (e.g., log transformation) might be beneficial before building predictive models to improve model performance and address outlier impact.
- Given the strong relationships identified, a predictive model for 'Last Auction Price Sold (in Crs)' should prioritize features related to player performance statistics (e.g., total runs, boundaries, centuries) and player profile (e.g., 'Category', 'Capped or Uncapped', 'Country').

# Task

Prepare data for SMOTE by separating the `df_scrambled` DataFrame into features (X) and target (y), with 'Auction_Value_Category' as the target. Exclude 'Player' and 'Last Auction Price Sold (in Crs)' from the features.

# Prepare Data for SMOTE

### Subtask:

Separate the `df_scrambled` DataFrame into features (X) and target (y). The target variable will be 'Auction_Value_Category'. Exclude 'Player', 'Last Auction Price Sold (in Crs)', and 'Unnamed: 16' (if it exists) from the features.

**Reasoning**: To separate the data into features (X) and target (y) as specified, I will first extract the 'Auction_Value_Category' column for 'y'. Then, I will create 'X' by dropping the 'Player', 'Last Auction Price Sold (in Crs)', 'Auction_Value_Category', and conditionally 'Unnamed: 16' columns from the original DataFrame. Finally, I will print the shapes and heads of X and y to confirm the separation.

```
y = df_scrambled['Auction_Value_Category']

columns_to_drop = ['Player', 'Last Auction Price Sold (in Crs)', 'Auction_Value

if 'Unnamed: 16' in df_scrambled.columns:
    columns_to_drop.append('Unnamed: 16')

X = df_scrambled.drop(columns=columns_to_drop)

print("Shape of X:", X.shape)
print("Shape of y:", y.shape)
print("\nX Head:\n", X.head())
print("\ny Head:\n", y.head())
```

```
Shape of X: (440, 14)
Shape of y: (440,)

X Head:
         Category      Country     Role  Batting Strike Rate  \
0  International        India  Batsman               165.02
1  International  Netherlands  Batsman               144.80
2  International    Australia  Batsman               147.69
3  International     Zimbabwe  Batsman               132.97
4       Domestic        India  Batsman               134.68

   Batsmen Total Runs  Batting Average  No of Sixes  No of Fours  Balls Faced  \
0               1749            29.25          107          206         1258
1                908            27.80           51           76          627
2              10115            31.08          171          492         4674
3               4430            27.37           99          444         3423
4               3082            30.13          196          219         2238

   Total career dot balls played  No of Centuries Scored  \
0                            529                       2
1                            259                       1
2                           1388                       8
3                            802                       2
4                            613                       1

   No of Half Centuries Scored  Age of the Player Capped or Uncapped
0                           11                 25            Capped
1                            6                 22          Uncapped
2                           33                 35            Capped
3                           25                 34            Capped
```

```
4                           10                  39           Uncapped

y Head:
 0    High Value
1     Low Value
2     Mid Value
3     Low Value
4    High Value
Name: Auction_Value_Category, dtype: category
Categories (3, object): ['Low Value' < 'Mid Value' < 'High Value']
```

## Preprocess Features for SMOTE

### Subtask:

Apply Min-Max scaling to numerical features and One-Hot Encoding to categorical features using a `ColumnTransformer`. This prepares the data for SMOTE, which requires numerical input.

**Reasoning**: To prepare the data for SMOTE, which requires numerical input, I will apply Min-Max scaling to numerical features and One-Hot Encoding to categorical features using a `ColumnTransformer` as per the instructions. This involves identifying the column types, creating appropriate transformers, and then fitting and transforming the `X` DataFrame.

```
numerical_cols_X = X.select_dtypes(include=np.number).columns.tolist()
categorical_cols_X = X.select_dtypes(include='object').columns.tolist()

# Create a Min-Max Scaler for numerical features
scaler = MinMaxScaler()

# Create a One-Hot Encoder for categorical features
encoder = OneHotEncoder(handle_unknown='ignore', sparse_output=False)

# Create a ColumnTransformer
preprocessor = ColumnTransformer(
    transformers=[
        ('num', scaler, numerical_cols_X),
        ('cat', encoder, categorical_cols_X)
    ],
    remainder='passthrough' # Keep other columns (if any) as they are
)

# Fit and transform the X DataFrame
X_preprocessed = preprocessor.fit_transform(X)
```

```
print("Shape of X_preprocessed:", X_preprocessed.shape)
print("First 5 rows of X_preprocessed:\n", X_preprocessed[:5])
```

```
Shape of X_preprocessed: (440, 29)
First 5 rows of X_preprocessed:
 [[0.45494851 0.01979661 0.13933958 0.06793651 0.0197543  0.02987219
  0.04263334 0.02325581 0.0237069  0.28205128 0.         1.
  0.         0.         0.         0.         1.         0.
  0.         0.         0.         0.         0.         0.
  0.         0.         1.         1.         0.        ]
 [0.31035469 0.00987471 0.12751733 0.03238095 0.00697789 0.01451004
  0.01951888 0.01162791 0.01293103 0.20512821 0.         1.
  0.         0.         0.         0.         0.         0.
  0.         1.         0.         0.         0.         0.
  0.         0.         1.         0.         1.        ]
 [0.33102117 0.1184965  0.15426009 0.10857143 0.04786241 0.11303713
  0.11617156 0.09302326 0.07112069 0.53846154 0.         1.
  0.         1.         0.         0.         0.         0.
  0.         0.         0.         0.         0.         0.
  0.         0.         1.         1.         0.        ]
 [0.22575801 0.05142635 0.12401141 0.06285714 0.04314496 0.08258065
  0.06600462 0.02325581 0.05387931 0.51282051 0.         1.
  0.         0.         0.         0.         0.         0.
  0.         0.         0.         0.         0.         0.
  0.         1.         1.         1.         0.        ]
 [0.23798627 0.03552299 0.14651447 0.12444444 0.02103194 0.05373098
  0.0498245  0.01162791 0.02155172 0.64102564 1.         0.
  0.         0.         0.         0.         1.         0.
  0.         0.         0.         0.         0.         0.
  0.         0.         1.         0.         1.        ]]
```

## Apply SMOTE for Class Balancing

### Subtask:

Apply the Synthetic Minority Over-sampling Technique (SMOTE) to the preprocessed features (`X_preprocessed`) and the 'Auction_Value_Category' target (`y`). This will balance the distribution of the price categories.

**Reasoning**: To apply SMOTE for class balancing, I will import SMOTE, instantiate it, and then use its `fit_resample` method on the preprocessed features and target. Finally, I will print the shapes and value counts to verify the balancing.

```
from imblearn.over_sampling import SMOTE

# Instantiate SMOTE
smote = SMOTE(random_state=42)
```

```
# Apply SMOTE to the preprocessed features and target
X_resampled, y_resampled = smote.fit_resample(X_preprocessed, y)

print("Shape of X_resampled:", X_resampled.shape)
print("Shape of y_resampled:", y_resampled.shape)

print("\nValue counts of y_resampled after SMOTE:")
print(y_resampled.value_counts())
```

```
Shape of X_resampled: (441, 29)
Shape of y_resampled: (441,)

Value counts of y_resampled after SMOTE:
Auction_Value_Category
Low Value     147
Mid Value     147
High Value    147
Name: count, dtype: int64
```

## Reconstruct Oversampled DataFrame

### Subtask:

Convert the SMOTE-generated numerical arrays back into a Pandas DataFrame, ensuring that the feature names are correctly assigned. The target variable will also be included.

**Reasoning**: To reconstruct the oversampled data into a Pandas DataFrame, I will first obtain the feature names from the preprocessor (both numerical and one-hot encoded categorical), then create a new DataFrame from the `X_resampled` array, and finally add the `y_resampled` target column.

```
numerical_features_after_preprocessing = numerical_cols_X
categorical_features_after_preprocessing = preprocessor.named_transformers_['ca

# Combine all feature names in the correct order
all_feature_names = list(numerical_features_after_preprocessing) + list(categor

# Create the DataFrame from X_resampled with the combined feature names
df_resampled = pd.DataFrame(X_resampled, columns=all_feature_names)

# Add the y_resampled Series as a new column to df_resampled
df_resampled['Auction_Value_Category'] = y_resampled
```

```
print("Shape of df_resampled:", df_resampled.shape)
print("\nFirst 5 rows of df_resampled:\n", df_resampled.head())
```

```
Shape of df_resampled: (441, 30)

First 5 rows of df_resampled:
    Batting Strike Rate  Batsmen Total Runs  Batting Average  No of Sixes  \
0             0.454949            0.019797         0.139340     0.067937
1             0.310355            0.009875         0.127517     0.032381
2             0.331021            0.118496         0.154260     0.108571
3             0.225758            0.051426         0.124011     0.062857
4             0.237986            0.035523         0.146514     0.124444

   No of Fours  Balls Faced  Total career dot balls played  \
0     0.019754     0.029872                       0.042633
1     0.006978     0.014510                       0.019519
2     0.047862     0.113037                       0.116172
3     0.043145     0.082581                       0.066005
4     0.021032     0.053731                       0.049825

   No of Centuries Scored  No of Half Centuries Scored  Age of the Player  \
0                0.023256                     0.023707           0.282051
1                0.011628                     0.012931           0.205128
2                0.093023                     0.071121           0.538462
3                0.023256                     0.053879           0.512821
4                0.011628                     0.021552           0.641026

   ...  Country_New Zealand  Country_South Africa  Country_Sri Lanka  \
0  ...                  0.0                   0.0                0.0
1  ...                  0.0                   0.0                0.0
2  ...                  0.0                   0.0                0.0
3  ...                  0.0                   0.0                0.0
4  ...                  0.0                   0.0                0.0

   Country_USA  Country_West Indies  Country_Zimbabwe  Role_Batsman  \
0          0.0                  0.0               0.0           1.0
1          0.0                  0.0               0.0           1.0
2          0.0                  0.0               0.0           1.0
3          0.0                  0.0               1.0           1.0
4          0.0                  0.0               0.0           1.0

   Capped or Uncapped_Capped  Capped or Uncapped_Uncapped  \
0                        1.0                          0.0
1                        0.0                          1.0
2                        1.0                          0.0
3                        1.0                          0.0
4                        0.0                          1.0

   Auction_Value_Category
0             High Value
1              Low Value
2              Mid Value
3              Low Value
4             High Value

[5 rows x 30 columns]
```

## Split Data into Training, Validation, and Testing Sets

### Subtask:

Divide the oversampled dataset into training, validation, and testing sets with a 70%, 20%, and 10% split, respectively. This will be done using `train_test_split` with a fixed `random_state` for reproducibility.

**Reasoning**: To divide the `df_resampled` DataFrame into training, validation, and testing sets with the specified ratios (70%, 20%, 10%), I will use `train_test_split` twice. First, to separate the training set from the combined validation/test set, and then to split the combined validation/test set into individual validation and test sets. I will also ensure to stratify the splits to maintain the class distribution and print the shapes of the resulting sets.

```
from sklearn.model_selection import train_test_split

# Separate features (X) and target (y) from df_resampled
X = df_resampled.drop('Auction_Value_Category', axis=1)
y = df_resampled['Auction_Value_Category']

# 1. First split: 70% train, 30% temp (validation + test)
X_train, X_temp, y_train, y_temp = train_test_split(
    X, y, test_size=0.3, random_state=42, stratify=y
)

# 2. Second split: split temp into 20% validation and 10% test
# Calculate the test_size for the second split: 10% of original / 30% of origir
X_val, X_test, y_val, y_test = train_test_split(
    X_temp, y_temp, test_size=(1/3), random_state=42, stratify=y_temp
)

# Print the shapes of the resulting sets
print("Shape of X_train:", X_train.shape)
print("Shape of y_train:", y_train.shape)
print("Shape of X_val:", X_val.shape)
print("Shape of y_val:", y_val.shape)
print("Shape of X_test:", X_test.shape)
print("Shape of y_test:", y_test.shape)

print("\nValue counts of y_train:")
print(y_train.value_counts())
print("\nValue counts of y_val:")
print(y_val.value_counts())
```

```
print("\nValue counts of y_test:")
print(y_test.value_counts())
```

```
Shape of X_train: (308, 29)
Shape of y_train: (308,)
Shape of X_val: (88, 29)
Shape of y_val: (88,)
Shape of X_test: (45, 29)
Shape of y_test: (45,)

Value counts of y_train:
Auction_Value_Category
Low Value     103
High Value    103
Mid Value     102
Name: count, dtype: int64

Value counts of y_val:
Auction_Value_Category
Mid Value     30
Low Value     29
High Value    29
Name: count, dtype: int64

Value counts of y_test:
Auction_Value_Category
Low Value     15
Mid Value     15
High Value    15
Name: count, dtype: int64
```

# Train Classification Model

## Subtask:

Train a suitable classification model (e.g., RandomForestClassifier) on the training data using the 'Auction_Value_Category' as the target variable.

**Reasoning**: To train a classification model, I will import `RandomForestClassifier`, instantiate it with a specified `random_state`, and then fit the model to the `X_train` and `y_train` datasets.

```
from sklearn.ensemble import RandomForestClassifier

# Instantiate a RandomForestClassifier object
model = RandomForestClassifier(random_state=42)

# Train the model
model.fit(X_train, y_train)
```

```
print("RandomForestClassifier model trained successfully.")
```

```
RandomForestClassifier model trained successfully.
```

# Evaluate Classification Model

## Subtask:

Evaluate the trained classification model on the validation and test sets. Calculate and report accuracy, precision, recall, and F1-score to assess performance and determine if the 85-90% accuracy target is met.

**Reasoning**: To evaluate the trained classification model, I will import the required metrics from `sklearn.metrics`, make predictions on the validation and test sets, and then calculate and report the accuracy, precision, recall, and F1-score for each set, along with a full classification report.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

print("--- Model Evaluation on Validation Set ---")
# Make predictions on the validation set
y_pred_val = model.predict(X_val)

# Calculate metrics for validation set
accuracy_val = accuracy_score(y_val, y_pred_val)
precision_val = precision_score(y_val, y_pred_val, average='weighted')
recall_val = recall_score(y_val, y_pred_val, average='weighted')
f1_val = f1_score(y_val, y_pred_val, average='weighted')

print(f"Validation Accuracy: {accuracy_val:.4f}")
print(f"Validation Precision (weighted): {precision_val:.4f}")
print(f"Validation Recall (weighted): {recall_val:.4f}")
print(f"Validation F1-Score (weighted): {f1_val:.4f}")
print("\nValidation Classification Report:\n", classification_report(y_val, y_p

print("\n--- Model Evaluation on Test Set ---")
# Make predictions on the test set
y_pred_test = model.predict(X_test)

# Calculate metrics for test set
accuracy_test = accuracy_score(y_test, y_pred_test)
precision_test = precision_score(y_test, y_pred_test, average='weighted')
recall_test = recall_score(y_test, y_pred_test, average='weighted')
f1_test = f1_score(y_test, y_pred_test, average='weighted')
```

```
print(f"Test Accuracy: {accuracy_test:.4f}")
print(f"Test Precision (weighted): {precision_test:.4f}")
print(f"Test Recall (weighted): {recall_test:.4f}")
print(f"Test F1-Score (weighted): {f1_test:.4f}")
print("\nTest Classification Report:\n", classification_report(y_test, y_pred_t

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment ---")
if target_min_accuracy <= accuracy_val <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val:.4f}) is within the target range
else:
    print(f"Validation Accuracy ({accuracy_val:.4f}) is NOT within the target r

if target_min_accuracy <= accuracy_test <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test:.4f}) is within the target range of {
else:
    print(f"Test Accuracy ({accuracy_test:.4f}) is NOT within the target range
```

```
--- Model Evaluation on Validation Set ---
Validation Accuracy: 0.6364
Validation Precision (weighted): 0.6533
Validation Recall (weighted): 0.6364
Validation F1-Score (weighted): 0.6316

Validation Classification Report:
               precision    recall  f1-score   support

  High Value       0.68      0.86      0.76        29
   Low Value       0.79      0.52      0.62        29
   Mid Value       0.50      0.53      0.52        30

    accuracy                           0.64        88
   macro avg       0.66      0.64      0.63        88
weighted avg       0.65      0.64      0.63        88


--- Model Evaluation on Test Set ---
Test Accuracy: 0.7111
Test Precision (weighted): 0.7095
Test Recall (weighted): 0.7111
Test F1-Score (weighted): 0.6943

Test Classification Report:
               precision    recall  f1-score   support

  High Value       0.71      1.00      0.83        15
   Low Value       0.71      0.67      0.69        15
   Mid Value       0.70      0.47      0.56        15

    accuracy                           0.71        45
   macro avg       0.71      0.71      0.69        45
```

```
weighted avg       0.71      0.71      0.69        45


--- Accuracy Target Assessment ---
Validation Accuracy (0.6364) is NOT within the target range of 85.0% - 90.0%
Test Accuracy (0.7111) is NOT within the target range of 85.0% - 90.0%
```

# Final Task

## Subtask:

Summarize the entire process, including the impact of SMOTE, model performance against the target accuracy, and insights from the classification task.

# Summary:

## Data Analysis Key Findings

- **Data Preparation and Preprocessing**: The initial `df_scrambled` DataFrame was successfully separated into features (X) and target (y), with 'Auction_Value_Category' as the target. Features 'Player', 'Last Auction Price Sold (in Crs)', and 'Auction_Value_Category' were excluded from X. Numerical features were scaled using Min-Max Scaler, and categorical features were One-Hot Encoded, resulting in a preprocessed feature set `X_preprocessed` with a shape of (440, 29).
- **Impact of SMOTE**: The Synthetic Minority Over-sampling Technique (SMOTE) was applied to the preprocessed data, effectively balancing the class distribution of the 'Auction_Value_Category'. Before SMOTE, the class distribution was imbalanced. After SMOTE, each of the three categories ('Low Value', 'Mid Value', 'High Value') contained exactly 147 instances, leading to a total of 441 samples in the resampled dataset.
- **Data Splitting**: The oversampled dataset (`df_resampled` with 441 rows and 30 columns) was split into training, validation, and testing sets with a 70%, 20%, and 10% distribution, respectively, while maintaining stratified class proportions across all sets.
    - Training set: 308 samples
    - Validation set: 88 samples
    - Test set: 45 samples

- **Model Training**: A `RandomForestClassifier` model was successfully trained on the preprocessed and resampled training data (`X_train`, `y_train`).
- **Model Performance (Validation Set)**:
  - Accuracy: 0.6364 (63.64%)
  - Precision (weighted): 0.6533
  - Recall (weighted): 0.6364
  - F1-Score (weighted): 0.6316
  - The model showed varying performance across classes, with 'High Value' having a recall of 0.86, while 'Low Value' and 'Mid Value' had lower recalls (0.52 and 0.53, respectively).
- **Model Performance (Test Set)**:
  - Accuracy: 0.7111 (71.11%)
  - Precision (weighted): 0.7095
  - Recall (weighted): 0.7111
  - F1-Score (weighted): 0.6943
  - Similar to the validation set, 'High Value' demonstrated a high recall of 1.00 on the test set, whereas 'Mid Value' had the lowest recall at 0.47.
- **Accuracy Target Assessment**: The target accuracy range for the model was 85-90%.
  - The validation accuracy of 63.64% did not meet the target range.
  - The test accuracy of 71.11% also did not meet the target range.

### Insights or Next Steps

- The current RandomForestClassifier model does not meet the target accuracy of 85-90%. Further model optimization, hyperparameter tuning, or exploring more advanced classification algorithms (e.g., Gradient Boosting, Neural Networks) is required to improve performance.
- Investigate the classification report further, especially the lower recall for 'Low Value' and 'Mid Value' categories. This might suggest these categories are harder to distinguish, and feature engineering or collecting more data specific to these categories could be beneficial.

## Task

**Plan:**

- **Re-apply SMOTE with Custom Ratios**: Apply SMOTE again to the preprocessed features (X_preprocessed) and target (y), but this time using a `sampling_strategy` dictionary to achieve the requested sample counts: 'High Value' (500), 'Mid Value' (350), and 'Low Value' (250). Display the new value counts after resampling.
- **Reconstruct Oversampled DataFrame with New Ratios**: Convert the newly SMOTE-generated numerical arrays (X_resampled, y_resampled) back into a Pandas DataFrame (`df_resampled`), ensuring that the feature names are correctly assigned. The updated target variable ('Auction_Value_Category') will also be included. Display the head and shape of the new `df_resampled`.
- **Re-split Data into Training, Validation, and Testing Sets**: Divide the newly reconstructed `df_resampled` into training, validation, and testing sets with a 70%, 20%, and 10% split, respectively. This will be done using `train_test_split` with a fixed `random_state` for reproducibility and stratification to maintain class proportions. Display the shapes and value counts of the resulting sets.
- **Train and Evaluate Logistic Regression Classifier**: Initialize, train, and make predictions with a `LogisticRegression` model on the new training data (X_train, y_train). Evaluate its performance on the validation (X_val, y_val) and test (X_test, y_test) sets by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report.
- **Train and Evaluate Random Forest Classifier**: Initialize, train, and make predictions with a `RandomForestClassifier` model on the new training data (X_train, y_train). Evaluate its performance on the validation (X_val, y_val) and test (X_test, y_test) sets by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report.
- **Train and Evaluate Decision Tree Classifier**: Initialize, train, and make predictions with a `DecisionTreeClassifier` model on the new training data (X_train, y_train). Evaluate its performance on the validation (X_val, y_val) and test (X_test, y_test) sets by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report.
- **Train and Evaluate Multi-layer Perceptron (MLP) Classifier**: Initialize, train, and make predictions with a `MLPClassifier` (as a general neural network model) on the new training data (X_train, y_train). Evaluate its performance on the validation (X_val, y_val) and test (X_test, y_test) sets by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report.
- **Compare All Models and Assess Target Accuracy**: Consolidate and compare the performance metrics (accuracy, precision, recall, F1-score) of all trained

classification models (Logistic Regression, Random Forest Classifier, Decision Tree Classifier, MLP Classifier). Assess whether any model meets the target accuracy range of 85-90% on both validation and test sets.

- **Final Task**: Summarize the entire process, including the specific SMOTE ratios used, the performance of each model, and whether the target accuracy was achieved by any model, providing insights into the strengths and weaknesses of each approach.

**Task:** Re-apply SMOTE to the preprocessed features (X_preprocessed) and the original target variable ('Auction_Value_Category' from `df_scrambled`), using a custom sampling strategy: 'High Value' (500 samples), 'Mid Value' (350 samples), and 'Low Value' (250 samples). Then, display the value counts of the resampled target variable.

## Re-apply SMOTE with Custom Ratios

### Subtask:

Apply SMOTE again to the preprocessed features (X_preprocessed) and target (y), but this time using a `sampling_strategy` dictionary to achieve the requested sample counts: 'High Value' (500), 'Mid Value' (350), and 'Low Value' (250). Display the new value counts after resampling.

**Reasoning**: To apply SMOTE with custom ratios, I will define the sampling strategy as a dictionary, instantiate SMOTE with this strategy, and then fit-resample the preprocessed features and original target variable. Finally, I will print the value counts of the resampled target to verify the new distribution.

**Reasoning**: The error `ValueError: Found input variables with inconsistent numbers of samples: [440, 441]` indicates that the `X_preprocessed` and `y` variables passed to SMOTE have different numbers of samples. This happened because `y` was overwritten with the target from the previously oversampled DataFrame (`df_resampled`). To fix this, I need to use the original target variable from `df_scrambled` which has the same number of samples as `X_preprocessed`.

```
from imblearn.over_sampling import SMOTE

# Define the custom sampling strategy
sampling_strategy = {
    'High Value': 500,
    'Mid Value': 350,
```

```
    'Low Value': 250
}

# Instantiate SMOTE with the custom sampling strategy
smote_custom = SMOTE(sampling_strategy=sampling_strategy, random_state=42)

# Get the original target variable from df_scrambled (before any previous SMOTE
original_y = df_scrambled['Auction_Value_Category']

# Apply SMOTE to the preprocessed features and original target
X_resampled_custom, y_resampled_custom = smote_custom.fit_resample(X_preprocess

print("Shape of X_resampled_custom:", X_resampled_custom.shape)
print("Shape of y_resampled_custom:", y_resampled_custom.shape)

print("\nValue counts of y_resampled_custom after SMOTE with custom ratios:")
print(y_resampled_custom.value_counts())
```

```
Shape of X_resampled_custom: (1100, 29)
Shape of y_resampled_custom: (1100,)

Value counts of y_resampled_custom after SMOTE with custom ratios:
Auction_Value_Category
High Value    500
Mid Value     350
Low Value     250
Name: count, dtype: int64
```

**Reasoning**: To reconstruct the oversampled data into a Pandas DataFrame, I will first obtain the feature names from the preprocessor (both numerical and one-hot encoded categorical), then create a new DataFrame from the `X_resampled_custom` array, and finally add the `y_resampled_custom` target column.

```
numerical_features_after_preprocessing = numerical_cols_X
categorical_features_after_preprocessing = preprocessor.named_transformers_['ca

# Combine all feature names in the correct order
all_feature_names_custom = list(numerical_features_after_preprocessing) + list(

# Create the DataFrame from X_resampled_custom with the combined feature names
df_resampled_custom = pd.DataFrame(X_resampled_custom, columns=all_feature_name

# Add the y_resampled_custom Series as a new column to df_resampled_custom
df_resampled_custom['Auction_Value_Category'] = y_resampled_custom

print("Shape of df_resampled_custom:", df_resampled_custom.shape)
print("\nFirst 5 rows of df_resampled_custom:\n", df_resampled_custom.head())
```

```
Shape of df_resampled_custom: (1100, 30)
```

```
First 5 rows of df_resampled_custom:
    Batting Strike Rate  Batsmen Total Runs  Batting Average  No of Sixes  \
0             0.454949            0.019797         0.139340     0.067937
1             0.310355            0.009875         0.127517     0.032381
2             0.331021            0.118496         0.154260     0.108571
3             0.225758            0.051426         0.124011     0.062857
4             0.237986            0.035523         0.146514     0.124444

   No of Fours  Balls Faced  Total career dot balls played  \
0     0.019754     0.029872                       0.042633
1     0.006978     0.014510                       0.019519
2     0.047862     0.113037                       0.116172
3     0.043145     0.082581                       0.066005
4     0.021032     0.053731                       0.049825

   No of Centuries Scored  No of Half Centuries Scored  Age of the Player  \
0                0.023256                     0.023707           0.282051
1                0.011628                     0.012931           0.205128
2                0.093023                     0.071121           0.538462
3                0.023256                     0.053879           0.512821
4                0.011628                     0.021552           0.641026

   ...  Country_New Zealand  Country_South Africa  Country_Sri Lanka  \
0  ...                  0.0                   0.0                0.0
1  ...                  0.0                   0.0                0.0
2  ...                  0.0                   0.0                0.0
3  ...                  0.0                   0.0                0.0
4  ...                  0.0                   0.0                0.0

   Country_USA  Country_West Indies  Country_Zimbabwe  Role_Batsman  \
0          0.0                  0.0               0.0           1.0
1          0.0                  0.0               0.0           1.0
2          0.0                  0.0               0.0           1.0
3          0.0                  0.0               1.0           1.0
4          0.0                  0.0               0.0           1.0

   Capped or Uncapped_Capped  Capped or Uncapped_Uncapped  \
0                        1.0                          0.0
1                        0.0                          1.0
2                        1.0                          0.0
3                        1.0                          0.0
4                        0.0                          1.0

   Auction_Value_Category
0             High Value
1              Low Value
2              Mid Value
3              Low Value
4             High Value

[5 rows x 30 columns]
```

**Reasoning**: To divide the `df_resampled_custom` DataFrame into training, validation, and testing sets with the specified ratios (70%, 20%, 10%), I will use

`train_test_split` twice. First, to separate the training set from the combined validation/test set, and then to split the combined validation/test set into individual validation and test sets. I will ensure to stratify the splits to maintain the class distribution and print the shapes and value counts of the resulting sets.

```
from sklearn.model_selection import train_test_split

# Separate features (X) and target (y) from df_resampled_custom
X_custom = df_resampled_custom.drop('Auction_Value_Category', axis=1)
y_custom = df_resampled_custom['Auction_Value_Category']

# 1. First split: 70% train, 30% temp (validation + test)
X_train, X_temp, y_train, y_temp = train_test_split(
    X_custom, y_custom, test_size=0.3, random_state=42, stratify=y_custom
)

# 2. Second split: split temp into 20% validation and 10% test
# Calculate the test_size for the second split: 10% of original / 30% of origir
X_val, X_test, y_val, y_test = train_test_split(
    X_temp, y_temp, test_size=(1/3), random_state=42, stratify=y_temp
)

# Print the shapes of the resulting sets
print("Shape of X_train:", X_train.shape)
print("Shape of y_train:", y_train.shape)
print("Shape of X_val:", X_val.shape)
print("Shape of y_val:", y_val.shape)
print("Shape of X_test:", X_test.shape)
print("Shape of y_test:", y_test.shape)

print("\nValue counts of y_train:")
print(y_train.value_counts())
print("\nValue counts of y_val:")
print(y_val.value_counts())
print("\nValue counts of y_test:")
print(y_test.value_counts())
```

```
Shape of X_train: (770, 29)
Shape of y_train: (770,)
Shape of X_val: (220, 29)
Shape of y_val: (220,)
Shape of X_test: (110, 29)
Shape of y_test: (110,)

Value counts of y_train:
Auction_Value_Category
High Value    350
Mid Value     245
Low Value     175
Name: count, dtype: int64
```

```
Value counts of y_val:
Auction_Value_Category
High Value    100
Mid Value      70
Low Value      50
Name: count, dtype: int64

Value counts of y_test:
Auction_Value_Category
High Value    50
Mid Value     35
Low Value     25
Name: count, dtype: int64
```

**Reasoning**: To train a Logistic Regression model, I will import the `LogisticRegression` class, instantiate it with `random_state=42`, and then fit the model to the `X_train` and `y_train` datasets.

```
from sklearn.linear_model import LogisticRegression

# Instantiate a LogisticRegression object
log_reg_model = LogisticRegression(random_state=42, max_iter=1000) # Increas

# Train the model
log_reg_model.fit(X_train, y_train)

print("LogisticRegression model trained successfully.")
```

```
LogisticRegression model trained successfully.
```

**Reasoning**: To evaluate the trained Logistic Regression model, I will make predictions on the validation and test sets, then calculate and print the accuracy, precision, recall, and F1-score for each, along with a classification report, and finally assess if the target accuracy is met.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f

print("--- Model Evaluation (Logistic Regression) on Validation Set ---")
# Make predictions on the validation set
y_pred_val_lr = log_reg_model.predict(X_val)

# Calculate metrics for validation set
accuracy_val_lr = accuracy_score(y_val, y_pred_val_lr)
precision_val_lr = precision_score(y_val, y_pred_val_lr, average='weighted',
recall_val_lr = recall_score(y_val, y_pred_val_lr, average='weighted', zero_
f1_val_lr = f1_score(y_val, y_pred_val_lr, average='weighted', zero_division

print(f"Validation Accuracy (Logistic Regression): {accuracy_val_lr:.4f}")
```

```
print(f"Validation Precision (weighted): {precision_val_lr:.4f}")
print(f"Validation Recall (weighted): {recall_val_lr:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_lr:.4f}")
print("\nValidation Classification Report (Logistic Regression):\n", classif

print("\n--- Model Evaluation (Logistic Regression) on Test Set ---")
# Make predictions on the test set
y_pred_test_lr = log_reg_model.predict(X_test)

# Calculate metrics for test set
accuracy_test_lr = accuracy_score(y_test, y_pred_test_lr)
precision_test_lr = precision_score(y_test, y_pred_test_lr, average='weighte
recall_test_lr = recall_score(y_test, y_pred_test_lr, average='weighted', ze
f1_test_lr = f1_score(y_test, y_pred_test_lr, average='weighted', zero_divis

print(f"Test Accuracy (Logistic Regression): {accuracy_test_lr:.4f}")
print(f"Test Precision (weighted): {precision_test_lr:.4f}")
print(f"Test Recall (weighted): {recall_test_lr:.4f}")
print(f"Test F1-Score (weighted): {f1_test_lr:.4f}")
print("\nTest Classification Report (Logistic Regression):\n", classificatio

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (Logistic Regression) ---")
if target_min_accuracy <= accuracy_val_lr <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_lr:.4f}) is within the target
else:
    print(f"Validation Accuracy ({accuracy_val_lr:.4f}) is NOT within the ta

if target_min_accuracy <= accuracy_test_lr <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_lr:.4f}) is within the target rang
else:
    print(f"Test Accuracy ({accuracy_test_lr:.4f}) is NOT within the target
```

```
--- Model Evaluation (Logistic Regression) on Validation Set ---
Validation Accuracy (Logistic Regression): 0.6909
Validation Precision (weighted): 0.7121
Validation Recall (weighted): 0.6909
Validation F1-Score (weighted): 0.6972

Validation Classification Report (Logistic Regression):
               precision    recall  f1-score   support

  High Value       0.81      0.76      0.78       100
   Low Value       0.80      0.64      0.71        50
   Mid Value       0.51      0.63      0.56        70

    accuracy                           0.69       220
   macro avg       0.71      0.68      0.69       220
weighted avg       0.71      0.69      0.70       220
```

```
--- Model Evaluation (Logistic Regression) on Test Set ---
Test Accuracy (Logistic Regression): 0.6273
Test Precision (weighted): 0.6415
Test Recall (weighted): 0.6273
Test F1-Score (weighted): 0.6319

Test Classification Report (Logistic Regression):
               precision    recall  f1-score   support

  High Value       0.78      0.72      0.75        50
   Low Value       0.59      0.52      0.55        25
   Mid Value       0.48      0.57      0.52        35

    accuracy                           0.63       110
   macro avg       0.62      0.60      0.61       110
weighted avg       0.64      0.63      0.63       110


--- Accuracy Target Assessment (Logistic Regression) ---
Validation Accuracy (0.6909) is NOT within the target range of 85.0% - 90.0%
Test Accuracy (0.6273) is NOT within the target range of 85.0% - 90.0%
```

**Reasoning**: To train a RandomForestClassifier, I will import the `RandomForestClassifier` class, instantiate it with `random_state=42`, and then fit the model to the `X_train` and `y_train` datasets.

```
from sklearn.ensemble import RandomForestClassifier

# Instantiate a RandomForestClassifier object
rf_model = RandomForestClassifier(random_state=42)

# Train the model
rf_model.fit(X_train, y_train)

print("RandomForestClassifier model trained successfully.")
```

```
RandomForestClassifier model trained successfully.
```

**Reasoning**: To evaluate the trained RandomForestClassifier model, I will make predictions on the validation and test sets, then calculate and print the accuracy, precision, recall, and F1-score for each, along with a classification report, and finally assess if the target accuracy is met.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

print("-- Model Evaluation (RandomForestClassifier) on Validation Set ---")
# Make predictions on the validation set
y_pred_val_rf = rf_model.predict(X_val)
```

```
# Calculate metrics for validation set
accuracy_val_rf = accuracy_score(y_val, y_pred_val_rf)
precision_val_rf = precision_score(y_val, y_pred_val_rf, average='weighted', ze
recall_val_rf = recall_score(y_val, y_pred_val_rf, average='weighted', zero_div
f1_val_rf = f1_score(y_val, y_pred_val_rf, average='weighted', zero_division=0)

print(f"Validation Accuracy (RandomForestClassifier): {accuracy_val_rf:.4f}")
print(f"Validation Precision (weighted): {precision_val_rf:.4f}")
print(f"Validation Recall (weighted): {recall_val_rf:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_rf:.4f}")
print("\nValidation Classification Report (RandomForestClassifier):\n", classif

print("\n--- Model Evaluation (RandomForestClassifier) on Test Set ---")
# Make predictions on the test set
y_pred_test_rf = rf_model.predict(X_test)

# Calculate metrics for test set
accuracy_test_rf = accuracy_score(y_test, y_pred_test_rf)
precision_test_rf = precision_score(y_test, y_pred_test_rf, average='weighted',
recall_test_rf = recall_score(y_test, y_pred_test_rf, average='weighted', zero_
f1_test_rf = f1_score(y_test, y_pred_test_rf, average='weighted', zero_divisior

print(f"Test Accuracy (RandomForestClassifier): {accuracy_test_rf:.4f}")
print(f"Test Precision (weighted): {precision_test_rf:.4f}")
print(f"Test Recall (weighted): {recall_test_rf:.4f}")
print(f"Test F1-Score (weighted): {f1_test_rf:.4f}")
print("\nTest Classification Report (RandomForestClassifier):\n", classificatic

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (RandomForestClassifier) ---")
if target_min_accuracy <= accuracy_val_rf <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_rf:.4f}) is within the target ra
else:
    print(f"Validation Accuracy ({accuracy_val_rf:.4f}) is NOT within the targe

if target_min_accuracy <= accuracy_test_rf <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_rf:.4f}) is within the target range c
else:
    print(f"Test Accuracy ({accuracy_test_rf:.4f}) is NOT within the target rar
```

```
-- Model Evaluation (RandomForestClassifier) on Validation Set ---
Validation Accuracy (RandomForestClassifier): 0.9000
Validation Precision (weighted): 0.8990
Validation Recall (weighted): 0.9000
Validation F1-Score (weighted): 0.8989

Validation Classification Report (RandomForestClassifier):
               precision    recall  f1-score   support
```

```
  High Value       0.94      0.98      0.96       100
   Low Value       0.84      0.86      0.85        50
   Mid Value       0.88      0.81      0.84        70

    accuracy                           0.90       220
   macro avg       0.89      0.88      0.89       220
weighted avg       0.90      0.90      0.90       220


--- Model Evaluation (RandomForestClassifier) on Test Set ---
Test Accuracy (RandomForestClassifier): 0.8909
Test Precision (weighted): 0.8909
Test Recall (weighted): 0.8909
Test F1-Score (weighted): 0.8890

Test Classification Report (RandomForestClassifier):
               precision    recall  f1-score   support

  High Value       0.89      0.98      0.93        50
   Low Value       0.91      0.84      0.88        25
   Mid Value       0.88      0.80      0.84        35

    accuracy                           0.89       110
   macro avg       0.89      0.87      0.88       110
weighted avg       0.89      0.89      0.89       110


--- Accuracy Target Assessment (RandomForestClassifier) ---
Validation Accuracy (0.9000) is within the target range of 85.0% - 90.0%
Test Accuracy (0.8909) is within the target range of 85.0% - 90.0%
```

**Reasoning**: To train a Decision Tree Classifier, I will import the `DecisionTreeClassifier` class, instantiate it with `random_state=42`, and then fit the model to the `X_train` and `y_train` datasets.

```
from sklearn.tree import DecisionTreeClassifier

# Instantiate a DecisionTreeClassifier object
dt_model = DecisionTreeClassifier(random_state=42)

# Train the model
dt_model.fit(X_train, y_train)

print("DecisionTreeClassifier model trained successfully.")
```

```
DecisionTreeClassifier model trained successfully.
```

**Reasoning**: To evaluate the trained Decision Tree Classifier model, I will make predictions on the validation and test sets, then calculate and print the accuracy,

precision, recall, and F1-score for each, along with a classification report, and finally assess if the target accuracy is met.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

print("--- Model Evaluation (DecisionTreeClassifier) on Validation Set ---")
# Make predictions on the validation set
y_pred_val_dt = dt_model.predict(X_val)

# Calculate metrics for validation set
accuracy_val_dt = accuracy_score(y_val, y_pred_val_dt)
precision_val_dt = precision_score(y_val, y_pred_val_dt, average='weighted', ze
recall_val_dt = recall_score(y_val, y_pred_val_dt, average='weighted', zero_div
f1_val_dt = f1_score(y_val, y_pred_val_dt, average='weighted', zero_division=0)

print(f"Validation Accuracy (DecisionTreeClassifier): {accuracy_val_dt:.4f}")
print(f"Validation Precision (weighted): {precision_val_dt:.4f}")
print(f"Validation Recall (weighted): {recall_val_dt:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_dt:.4f}")
print("\nValidation Classification Report (DecisionTreeClassifier):\n", classif

print("\n--- Model Evaluation (DecisionTreeClassifier) on Test Set ---")
# Make predictions on the test set
y_pred_test_dt = dt_model.predict(X_test)

# Calculate metrics for test set
accuracy_test_dt = accuracy_score(y_test, y_pred_test_dt)
precision_test_dt = precision_score(y_test, y_pred_test_dt, average='weighted',
recall_test_dt = recall_score(y_test, y_pred_test_dt, average='weighted', zero_
f1_test_dt = f1_score(y_test, y_pred_test_dt, average='weighted', zero_divisior

print(f"Test Accuracy (DecisionTreeClassifier): {accuracy_test_dt:.4f}")
print(f"Test Precision (weighted): {precision_test_dt:.4f}")
print(f"Test Recall (weighted): {recall_test_dt:.4f}")
print(f"Test F1-Score (weighted): {f1_test_dt:.4f}")
print("\nTest Classification Report (DecisionTreeClassifier):\n", classificatic

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (DecisionTreeClassifier) ---")
if target_min_accuracy <= accuracy_val_dt <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_dt:.4f}) is within the target ra
else:
    print(f"Validation Accuracy ({accuracy_val_dt:.4f}) is NOT within the targe

if target_min_accuracy <= accuracy_test_dt <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_dt:.4f}) is within the target range c
else:
```

```
    print(f"Test Accuracy ({accuracy_test_dt:.4f}) is NOT within the target rar
```

```
--- Model Evaluation (DecisionTreeClassifier) on Validation Set ---
Validation Accuracy (DecisionTreeClassifier): 0.8500
Validation Precision (weighted): 0.8490
Validation Recall (weighted): 0.8500
Validation F1-Score (weighted): 0.8484

Validation Classification Report (DecisionTreeClassifier):
               precision    recall  f1-score   support

  High Value       0.88      0.94      0.91       100
   Low Value       0.87      0.78      0.82        50
   Mid Value       0.79      0.77      0.78        70

    accuracy                           0.85       220
   macro avg       0.85      0.83      0.84       220
weighted avg       0.85      0.85      0.85       220


--- Model Evaluation (DecisionTreeClassifier) on Test Set ---
Test Accuracy (DecisionTreeClassifier): 0.8000
Test Precision (weighted): 0.8128
Test Recall (weighted): 0.8000
Test F1-Score (weighted): 0.8008

Test Classification Report (DecisionTreeClassifier):
               precision    recall  f1-score   support

  High Value       0.86      0.86      0.86        50
   Low Value       0.66      0.84      0.74        25
   Mid Value       0.86      0.69      0.76        35

    accuracy                           0.80       110
   macro avg       0.79      0.80      0.79       110
weighted avg       0.81      0.80      0.80       110


--- Accuracy Target Assessment (DecisionTreeClassifier) ---
Validation Accuracy (0.8500) is within the target range of 85.0% - 90.0%
Test Accuracy (0.8000) is NOT within the target range of 85.0% - 90.0%
```

**Reasoning**: To train a Multi-layer Perceptron (MLP) Classifier, I will import the `MLPClassifier` class, instantiate it with `random_state=42`, and then fit the model to the `X_train` and `y_train` datasets. I will also increase `max_iter` and enable `early_stopping` for better convergence and to prevent overfitting.

**Reasoning**: The `TypeError` in `MLPClassifier.fit()`, specifically `ufunc 'isnan' not supported for the input types`, often occurs when the input data (features) contains non-numeric types or mixed types that are not compatible with NumPy's

mathematical operations during validation (due to `early_stopping=True`). Although the features were preprocessed, they were reassembled into Pandas DataFrames (`X_train`, `X_val`, `X_test`). To ensure `MLPClassifier` receives purely numerical input, I will explicitly convert `X_train` and `X_val` to NumPy arrays of float type before fitting the model.

**Reasoning**: The `TypeError` occurs because `MLPClassifier` with `early_stopping=True` expects purely numerical input for both training and validation sets. Although `X_train` was cast during the fit call, `X_val` (used internally for early stopping) was not. To fix this, I will explicitly convert both `X_train` and `X_val` to NumPy arrays of `np.float32` type before fitting the model, ensuring all inputs are uniformly numerical.

**Reasoning**: The `TypeError` in `MLPClassifier.fit()` with `early_stopping=True` often arises when the target variable `y_train` is a categorical Pandas Series, even if the features are numeric. `MLPClassifier` internally handles validation split and expects numerical labels for the target. To resolve this, I will explicitly convert `y_train` (and its corresponding validation split) into numerical labels using `LabelEncoder` before fitting the `MLPClassifier`.

```
from sklearn.neural_network import MLPClassifier
from sklearn.preprocessing import LabelEncoder
import numpy as np

# Instantiate an MLPClassifier object
mlp_model = MLPClassifier(random_state=42, max_iter=1000, early_stopping=True)

# Convert DataFrames to NumPy arrays of float type for both training and valida
X_train_np = X_train.astype(np.float32)
X_val_np = X_val.astype(np.float32)

# Encode the target variable to numerical labels
label_encoder = LabelEncoder()
y_train_encoded = label_encoder.fit_transform(y_train)

# Train the model using the NumPy arrays for X and encoded y
mlp_model.fit(X_train_np, y_train_encoded)

print("MLPClassifier model trained successfully.")
```

```
MLPClassifier model trained successfully.
```

**Reasoning**: To evaluate the trained MLPClassifier model, I will make predictions on the validation and test sets, converting the target variables to encoded numerical labels for comparison. Then, I will calculate and print the accuracy, precision, recall, and F1-score for each, along with a classification report, and finally assess if the target accuracy is met.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

print("--- Model Evaluation (MLPClassifier) on Validation Set ---")
# Make predictions on the validation set
y_pred_val_mlp_encoded = mlp_model.predict(X_val_np) # Use X_val_np

# Convert y_val to encoded labels for comparison
y_val_encoded = label_encoder.transform(y_val)

# Calculate metrics for validation set
accuracy_val_mlp = accuracy_score(y_val_encoded, y_pred_val_mlp_encoded)
precision_val_mlp = precision_score(y_val_encoded, y_pred_val_mlp_encoded, aver
recall_val_mlp = recall_score(y_val_encoded, y_pred_val_mlp_encoded, average='w
f1_val_mlp = f1_score(y_val_encoded, y_pred_val_mlp_encoded, average='weighted'

print(f"Validation Accuracy (MLPClassifier): {accuracy_val_mlp:.4f}")
print(f"Validation Precision (weighted): {precision_val_mlp:.4f}")
print(f"Validation Recall (weighted): {recall_val_mlp:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_mlp:.4f}")
print("\nValidation Classification Report (MLPClassifier):\n", classification_r

print("\n--- Model Evaluation (MLPClassifier) on Test Set ---")
# Convert X_test to numpy array for prediction
X_test_np = X_test.astype(np.float32)
# Make predictions on the test set
y_pred_test_mlp_encoded = mlp_model.predict(X_test_np)

# Convert y_test to encoded labels for comparison
y_test_encoded = label_encoder.transform(y_test)

# Calculate metrics for test set
accuracy_test_mlp = accuracy_score(y_test_encoded, y_pred_test_mlp_encoded)
precision_test_mlp = precision_score(y_test_encoded, y_pred_test_mlp_encoded, a
recall_test_mlp = recall_score(y_test_encoded, y_pred_test_mlp_encoded, average
f1_test_mlp = f1_score(y_test_encoded, y_pred_test_mlp_encoded, average='weight

print(f"Test Accuracy (MLPClassifier): {accuracy_test_mlp:.4f}")
print(f"Test Precision (weighted): {precision_test_mlp:.4f}")
print(f"Test Recall (weighted): {recall_test_mlp:.4f}")
print(f"Test F1-Score (weighted): {f1_test_mlp:.4f}")
print("\nTest Classification Report (MLPClassifier):\n", classification_report(
```

```
# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (MLPClassifier) ---")
if target_min_accuracy <= accuracy_val_mlp <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_mlp:.4f}) is within the target r
else:
    print(f"Validation Accuracy ({accuracy_val_mlp:.4f}) is NOT within the targ

if target_min_accuracy <= accuracy_test_mlp <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_mlp:.4f}) is within the target range
else:
    print(f"Test Accuracy ({accuracy_test_mlp:.4f}) is NOT within the target ra
```

```
--- Model Evaluation (MLPClassifier) on Validation Set ---
Validation Accuracy (MLPClassifier): 0.6818
Validation Precision (weighted): 0.6990
Validation Recall (weighted): 0.6818
Validation F1-Score (weighted): 0.6822

Validation Classification Report (MLPClassifier):
               precision    recall  f1-score   support

  High Value       0.72      0.80      0.76       100
   Low Value       0.88      0.58      0.70        50
   Mid Value       0.54      0.59      0.56        70

    accuracy                           0.68       220
   macro avg       0.71      0.66      0.67       220
weighted avg       0.70      0.68      0.68       220


--- Model Evaluation (MLPClassifier) on Test Set ---
Test Accuracy (MLPClassifier): 0.6545
Test Precision (weighted): 0.6633
Test Recall (weighted): 0.6545
Test F1-Score (weighted): 0.6457

Test Classification Report (MLPClassifier):
               precision    recall  f1-score   support

  High Value       0.68      0.84      0.75        50
   Low Value       0.80      0.48      0.60        25
   Mid Value       0.55      0.51      0.53        35

    accuracy                           0.65       110
   macro avg       0.67      0.61      0.63       110
weighted avg       0.66      0.65      0.65       110


--- Accuracy Target Assessment (MLPClassifier) ---
Validation Accuracy (0.6818) is NOT within the target range of 85.0% - 90.0%
Test Accuracy (0.6545) is NOT within the target range of 85.0% - 90.0%
```

**Reasoning**: To compare all models and assess target accuracy, I will collect the performance metrics (accuracy, precision, recall, F1-score) for each trained model on both validation and test sets. I will store these metrics in a dictionary and then print them, along with an assessment against the target accuracy range.

```
model_performance = {
    "Logistic Regression": {
        "Validation": {
            "Accuracy": accuracy_val_lr,
            "Precision": precision_val_lr,
            "Recall": recall_val_lr,
            "F1-Score": f1_val_lr
        },
        "Test": {
            "Accuracy": accuracy_test_lr,
            "Precision": precision_test_lr,
            "Recall": recall_test_lr,
            "F1-Score": f1_test_lr
        }
    },
    "Random Forest": {
        "Validation": {
            "Accuracy": accuracy_val_rf,
            "Precision": precision_val_rf,
            "Recall": recall_val_rf,
            "F1-Score": f1_val_rf
        },
        "Test": {
            "Accuracy": accuracy_test_rf,
            "Precision": precision_test_rf,
            "Recall": recall_test_rf,
            "F1-Score": f1_test_rf
        }
    },
    "Decision Tree": {
        "Validation": {
            "Accuracy": accuracy_val_dt,
            "Precision": precision_val_dt,
            "Recall": recall_val_dt,
            "F1-Score": f1_val_dt
        },
        "Test": {
            "Accuracy": accuracy_test_dt,
            "Precision": precision_test_dt,
            "Recall": recall_test_dt,
            "F1-Score": f1_test_dt
        }
    },
```

```
        "MLP Classifier": {
            "Validation": {
                "Accuracy": accuracy_val_mlp,
                "Precision": precision_val_mlp,
                "Recall": recall_val_mlp,
                "F1-Score": f1_val_mlp
            },
            "Test": {
                "Accuracy": accuracy_test_mlp,
                "Precision": precision_test_mlp,
                "Recall": recall_test_mlp,
                "F1-Score": f1_test_mlp
            }
        }
    }

    print("--- Comparison of Model Performance ---")
    for model_name, metrics in model_performance.items():
        print(f"\nModel: {model_name}")
        for dataset, scores in metrics.items():
            print(f"  {dataset} Set:")
            for metric, value in scores.items():
                print(f"    {metric}: {value:.4f}")

    print("\n--- Overall Accuracy Target Assessment (85-90%) ---")
    for model_name, metrics in model_performance.items():
        val_acc = metrics["Validation"]["Accuracy"]
        test_acc = metrics["Test"]["Accuracy"]

        val_status = "within" if target_min_accuracy <= val_acc <= target_max_accur
        test_status = "within" if target_min_accuracy <= test_acc <= target_max_acc

        print(f"\n{model_name}:")
        print(f"  Validation Accuracy ({val_acc:.4f}) is {val_status} the target ra
        print(f"  Test Accuracy ({test_acc:.4f}) is {test_status} the target range.
```

```
    Accuracy: 0.6273
    Precision: 0.6415
    Recall: 0.6273
    F1-Score: 0.6319
```

```
    Recall: 0.8909
    F1-Score: 0.8890

Model: Decision Tree
  Validation Set:
    Accuracy: 0.8500
    Precision: 0.8490
    Recall: 0.8500
    F1-Score: 0.8484
  Test Set:
    Accuracy: 0.8000
    Precision: 0.8128
    Recall: 0.8000
    F1-Score: 0.8008

Model: MLP Classifier
  Validation Set:
    Accuracy: 0.6818
    Precision: 0.6990
    Recall: 0.6818
    F1-Score: 0.6822
  Test Set:
    Accuracy: 0.6545
    Precision: 0.6633
    Recall: 0.6545
    F1-Score: 0.6457

--- Overall Accuracy Target Assessment (85-90%) ---

Logistic Regression:
  Validation Accuracy (0.6909) is NOT within the target range.
  Test Accuracy (0.6273) is NOT within the target range.

Random Forest:
  Validation Accuracy (0.9000) is within the target range.
  Test Accuracy (0.8909) is within the target range.

Decision Tree:
  Validation Accuracy (0.8500) is within the target range.
  Test Accuracy (0.8000) is NOT within the target range.

MLP Classifier:
  Validation Accuracy (0.6818) is NOT within the target range.
  Test Accuracy (0.6545) is NOT within the target range.
```

# Final Task

## Subtask:

Summarize the entire process, including the specific SMOTE ratios used, the performance of each model, and whether the target accuracy was achieved by any model, providing insights into the strengths and weaknesses of each approach.

# Summary:

## Q&A

- **What specific SMOTE ratios were used?** SMOTE was applied with a custom sampling strategy to balance the target classes: 'High Value' (500 samples), 'Mid Value' (350 samples), and 'Low Value' (250 samples).
- **What was the performance of each model?**
  - **Logistic Regression:** Validation Accuracy: 69.09%, Test Accuracy: 62.73%.
  - **Random Forest Classifier:** Validation Accuracy: 90.00%, Test Accuracy: 89.09%.
  - **Decision Tree Classifier:** Validation Accuracy: 85.00%, Test Accuracy: 80.00%.
  - **MLP Classifier:** Validation Accuracy: 68.18%, Test Accuracy: 65.45%.
- **Did any model achieve the target accuracy (85-90%)?** Yes, only the Random Forest Classifier achieved the target accuracy range of 85-90% on both the validation (90.00%) and test (89.09%) sets.

## Data Analysis Key Findings

- SMOTE was successfully re-applied with custom ratios: 'High Value' at 500 samples, 'Mid Value' at 350 samples, and 'Low Value' at 250 samples, resulting in a balanced dataset of 1100 samples.
- The Random Forest Classifier exhibited the best performance, achieving an accuracy of 90.00% on the validation set and 89.09% on the test set, successfully meeting the target accuracy range of 85-90%.
- The Decision Tree Classifier showed promising validation accuracy (85.00%) but its test accuracy (80.00%) fell below the target, indicating potential overfitting or less robust generalization.
- Logistic Regression and MLP Classifier performed significantly worse, with test accuracies of 62.73% and 65.45% respectively, failing to meet the target accuracy.
- The MLP Classifier required explicit data type conversion (to `np.float32`) and target variable encoding (using `LabelEncoder`) to resolve a `TypeError` during training, highlighting its sensitivity to input data format.

## Insights or Next Steps

- The Random Forest Classifier is the most suitable model for this classification task given its robust performance and consistent adherence to the target accuracy

range. Further hyperparameter tuning for this model could potentially yield even better or more stable results.
- For models like the Decision Tree, exploring techniques such as pruning or ensemble methods (beyond Random Forest) could improve generalization and prevent overfitting observed in the decline from validation to test accuracy.

# Task

Perform hyperparameter tuning for Logistic Regression, RandomForestClassifier, DecisionTreeClassifier, and MLPClassifier models using GridSearchCV or RandomizedSearchCV with cross-validation on the training data. Then, train each model with its best hyperparameters, evaluate their performance on validation and test sets (reporting accuracy, precision, recall, and F1-score with classification reports), and finally compare all tuned models to identify the best-performing one and assess if any achieve a target accuracy between 85% and 90%.

# Define Parameter Grids for Tuning

## Subtask:

Define appropriate hyperparameter grids for Logistic Regression, RandomForestClassifier, DecisionTreeClassifier, and MLPClassifier. These grids will specify the range of parameters to be searched during tuning.

**Reasoning**: To define the hyperparameter grids for each classifier as specified, I will create four dictionaries: `param_grid_lr`, `param_grid_rf`, `param_grid_dt`, and `param_grid_mlp`, populating them with the given parameters and their values.

```
param_grid_lr = {
    'C': [0.1, 1, 10],
    'penalty': ['l2'],
    'solver': ['liblinear', 'saga']
}

param_grid_rf = {
    'n_estimators': [100, 200],
    'max_features': ['sqrt', 'log2'],
    'max_depth': [10, 20, None],
    'min_samples_split': [2, 5],
    'min_samples_leaf': [1, 2]
}
```

```
}

param_grid_dt = {
    'max_depth': [5, 10, None],
    'min_samples_split': [2, 5],
    'min_samples_leaf': [1, 2],
    'criterion': ['gini', 'entropy']
}

param_grid_mlp = {
    'hidden_layer_sizes': [(50,), (100, 50)],
    'activation': ['relu', 'tanh'],
    'solver': ['adam'],
    'alpha': [0.0001, 0.001],
    'learning_rate': ['adaptive']
}

print("--- Hyperparameter Grids Defined ---")
print("\nLogistic Regression Grid:", param_grid_lr)
print("\nRandom Forest Grid:", param_grid_rf)
print("\nDecision Tree Grid:", param_grid_dt)
print("\nMLP Classifier Grid:", param_grid_mlp)
```

```
--- Hyperparameter Grids Defined ---

Logistic Regression Grid: {'C': [0.1, 1, 10], 'penalty': ['l2'], 'solver': ['lib

Random Forest Grid: {'n_estimators': [100, 200], 'max_features': ['sqrt', 'log2'

Decision Tree Grid: {'max_depth': [5, 10, None], 'min_samples_split': [2, 5], 'm

MLP Classifier Grid: {'hidden_layer_sizes': [(50,), (100, 50)], 'activation': ['
```

## Hyperparameter Tuning for Logistic Regression

### Subtask:

Perform hyperparameter tuning for the `LogisticRegression` model using `GridSearchCV` with cross-validation on the training data (`X_train`, `y_train`). Use the `param_grid_lr` defined previously. After tuning, print the best parameters and the best cross-validation score.

**Reasoning**: To perform hyperparameter tuning for the Logistic Regression model, I will use `GridSearchCV` with the predefined `param_grid_lr`. I will fit it to the training data (`X_train`, `y_train`), using the `LabelEncoder` to transform `y_train` into numerical

labels as required by `LogisticRegression`. Finally, I will print the best parameters and the best cross-validation score found by the grid search.

```
from sklearn.model_selection import GridSearchCV
from sklearn.linear_model import LogisticRegression

print("--- Starting Hyperparameter Tuning for Logistic Regression ---")

# Instantiate the Logistic Regression model
log_reg = LogisticRegression(random_state=42, max_iter=1000)

# Create the GridSearchCV object
grid_search_lr = GridSearchCV(
    estimator=log_reg,
    param_grid=param_grid_lr,
    cv=5, # 5-fold cross-validation
    scoring='accuracy', # Use accuracy as the scoring metric
    n_jobs=-1, # Use all available CPU cores
    verbose=1 # Display progress
)

# Encode y_train for GridSearchCV as LogisticRegression expects numerical label
y_train_encoded = label_encoder.transform(y_train)

# Fit GridSearchCV to the training data
grid_search_lr.fit(X_train, y_train_encoded)

print("\nBest Parameters for Logistic Regression:", grid_search_lr.best_params_
print("Best Cross-validation Score for Logistic Regression:", grid_search_lr.be
```

```
--- Starting Hyperparameter Tuning for Logistic Regression ---
Fitting 5 folds for each of 6 candidates, totalling 30 fits

Best Parameters for Logistic Regression: {'C': 10, 'penalty': 'l2', 'solver': 'l
Best Cross-validation Score for Logistic Regression: 0.6870129870129871
```

## Hyperparameter Tuning for RandomForestClassifier

### Subtask:

Perform hyperparameter tuning for the `RandomForestClassifier` model using `GridSearchCV` with cross-validation on the training data (`X_train`, `y_train`). Use the `param_grid_rf` defined previously. After tuning, print the best parameters and the best cross-validation score.

**Reasoning**: To perform hyperparameter tuning for the RandomForestClassifier model, I will use `GridSearchCV` with the predefined `param_grid_rf`. I will fit it to the training data (`X_train`, `y_train_encoded`), using the already encoded `y_train` from the previous step. Finally, I will print the best parameters and the best cross-validation score found by the grid search.

```
from sklearn.ensemble import RandomForestClassifier

print("--- Starting Hyperparameter Tuning for RandomForestClassifier ---")

# Instantiate the RandomForestClassifier model
rf_classifier = RandomForestClassifier(random_state=42)

# Create the GridSearchCV object
grid_search_rf = GridSearchCV(
    estimator=rf_classifier,
    param_grid=param_grid_rf,
    cv=5, # 5-fold cross-validation
    scoring='accuracy', # Use accuracy as the scoring metric
    n_jobs=-1, # Use all available CPU cores
    verbose=1 # Display progress
)

# Fit GridSearchCV to the training data (using already encoded y_train)
grid_search_rf.fit(X_train, y_train_encoded)

print("\nBest Parameters for RandomForestClassifier:", grid_search_rf.best_para
print("Best Cross-validation Score for RandomForestClassifier:", grid_search_rf
```

```
--- Starting Hyperparameter Tuning for RandomForestClassifier ---
Fitting 5 folds for each of 48 candidates, totalling 240 fits

Best Parameters for RandomForestClassifier: {'max_depth': 20, 'max_features': 's
Best Cross-validation Score for RandomForestClassifier: 0.8584415584415584
```

## Hyperparameter Tuning for DecisionTreeClassifier

### Subtask:

Perform hyperparameter tuning for the `DecisionTreeClassifier` model using `GridSearchCV` with cross-validation on the training data (`X_train`, `y_train`). Use the `param_grid_dt` defined previously. After tuning, print the best parameters and the best cross-validation score.

**Reasoning**: To perform hyperparameter tuning for the DecisionTreeClassifier model, I will use `GridSearchCV` with the predefined `param_grid_dt`. I will fit it to the training data (`X_train`, `y_train_encoded`), using the already encoded `y_train` from the previous steps. Finally, I will print the best parameters and the best cross-validation score found by the grid search.

```
from sklearn.tree import DecisionTreeClassifier

print("--- Starting Hyperparameter Tuning for DecisionTreeClassifier ---")

# Instantiate the DecisionTreeClassifier model
dt_classifier = DecisionTreeClassifier(random_state=42)

# Create the GridSearchCV object
grid_search_dt = GridSearchCV(
    estimator=dt_classifier,
    param_grid=param_grid_dt,
    cv=5, # 5-fold cross-validation
    scoring='accuracy', # Use accuracy as the scoring metric
    n_jobs=-1, # Use all available CPU cores
    verbose=1 # Display progress
)

# Fit GridSearchCV to the training data (using already encoded y_train)
grid_search_dt.fit(X_train, y_train_encoded)

print("\nBest Parameters for DecisionTreeClassifier:", grid_search_dt.best_p
print("Best Cross-validation Score for DecisionTreeClassifier:", grid_search
```

```
--- Starting Hyperparameter Tuning for DecisionTreeClassifier ---
Fitting 5 folds for each of 24 candidates, totalling 120 fits

Best Parameters for DecisionTreeClassifier: {'criterion': 'gini', 'max_depth': N
Best Cross-validation Score for DecisionTreeClassifier: 0.7935064935064935
```

```
import pandas as pd

# Create a copy of X_test to add actual and predicted labels
predictions_df = X_test.copy()

# Decode y_test_encoded back to original labels and add to the DataFrame
predictions_df['Actual_Auction_Value'] = label_encoder.inverse_transform(y_test

# Get and decode predictions from each tuned model and add to the DataFrame
predictions_df['Predicted_LR'] = label_encoder.inverse_transform(best_log_reg_m
predictions_df['Predicted_RF'] = label_encoder.inverse_transform(best_rf_model.
predictions_df['Predicted_DT'] = label_encoder.inverse_transform(best_dt_model.
predictions_df['Predicted_MLP'] = label_encoder.inverse_transform(best_mlp_mode
```

```
predictions_df['Predicted_Bagging'] = label_encoder.inverse_transform(best_bagg
predictions_df['Predicted_AdaBoost'] = label_encoder.inverse_transform(best_ada

# Display the head of the new DataFrame
print("DataFrame with Actual vs. Predicted Labels for all Models (first 5 rows)
print(predictions_df.head())
```

```
DataFrame with Actual vs. Predicted Labels for all Models (first 5 rows):

      Batting Strike Rate  Batsmen Total Runs  Batting Average  No of Sixes  \
1084             0.698642            0.003379         0.154629     0.012016
581              0.352049            0.034234         0.152852     0.090896
1062             0.321014            0.024374         0.110961     0.071433
272              0.189645            0.015561         0.115614     0.039365
982              0.391922            0.021771         0.096868     0.081091

      No of Fours  Balls Faced  Total career dot balls played  \
1084     0.003549     0.003292                       0.002814
581      0.043682     0.045036                       0.053216
1062     0.018306     0.034810                       0.043521
272      0.010614     0.025393                       0.029621
982      0.015896     0.031645                       0.038208

      No of Centuries Scored  No of Half Centuries Scored  Age of the Player  \
1084                0.006582                     0.002155           0.215288
581                 0.002063                     0.034100           0.363524
1062                0.011628                     0.036107           0.333333
272                 0.011628                     0.017241           0.333333
982                 0.023256                     0.021495           0.205128

      ...  Role_Batsman  Capped or Uncapped_Capped  \
1084  ...           1.0                        0.0
581   ...           1.0                        1.0
1062  ...           1.0                        1.0
272   ...           1.0                        1.0
982   ...           1.0                        1.0

      Capped or Uncapped_Uncapped  Actual_Auction_Value  Predicted_LR  \
1084                          1.0             Mid Value    High Value
581                           0.0            High Value    High Value
1062                          0.0             Mid Value     Mid Value
272                           0.0             Low Value     Low Value
982                           0.0             Mid Value     Mid Value

      Predicted_RF  Predicted_DT  Predicted_MLP  Predicted_Bagging  \
1084     Mid Value    High Value     High Value         High Value
581     High Value     Low Value     High Value         High Value
1062     Mid Value     Mid Value      Low Value          Mid Value
272      Low Value     Low Value      Mid Value          Low Value
982      Mid Value     Mid Value     High Value          Mid Value

      Predicted_AdaBoost
1084         High Value
581          High Value
1062          Mid Value
```

```
272            Low Value
982            Mid Value

[5 rows x 36 columns]
```

# Hyperparameter Tuning for Multi-layer Perceptron (MLP) Classifier

## Subtask:

Perform hyperparameter tuning for the `MLPClassifier` model using `GridSearchCV` with cross-validation on the training data (`X_train`, `y_train`). Use the `param_grid_mlp` defined previously. After tuning, print the best parameters and the best cross-validation score. Remember to handle data type conversions for `MLPClassifier` as needed.

**Reasoning**: To perform hyperparameter tuning for the MLPClassifier model, I will use `GridSearchCV` with the predefined `param_grid_mlp`. I will ensure that `X_train` is converted to a NumPy array of float type and `y_train` is encoded to numerical labels as `MLPClassifier` requires. Finally, I will print the best parameters and the best cross-validation score found by the grid search.

```
from sklearn.neural_network import MLPClassifier

print("--- Starting Hyperparameter Tuning for MLPClassifier ---")

# Instantiate the MLPClassifier model
mlp_classifier = MLPClassifier(random_state=42, max_iter=1000, early_stopping=T

# Create the GridSearchCV object
grid_search_mlp = GridSearchCV(
    estimator=mlp_classifier,
    param_grid=param_grid_mlp,
    cv=5, # 5-fold cross-validation
    scoring='accuracy', # Use accuracy as the scoring metric
    n_jobs=-1, # Use all available CPU cores
    verbose=1 # Display progress
)

# Fit GridSearchCV to the training data (using already encoded y_train and X_tr
# Ensure X_train is converted to numpy array of float type for MLPClassifier
grid_search_mlp.fit(X_train_np, y_train_encoded)
```

```
print("\nBest Parameters for MLPClassifier:", grid_search_mlp.best_params_)
print("Best Cross-validation Score for MLPClassifier:", grid_search_mlp.best_sc
```

```
--- Starting Hyperparameter Tuning for MLPClassifier ---
Fitting 5 folds for each of 8 candidates, totalling 40 fits

Best Parameters for MLPClassifier: {'activation': 'relu', 'alpha': 0.0001, 'hidd
Best Cross-validation Score for MLPClassifier: 0.6506493506493507
```

## Train and Evaluate Tuned Logistic Regression Classifier

### Subtask:

Train a `LogisticRegression` model using the best hyperparameters found from `grid_search_lr`. Then, make predictions on the validation (`X_val`, `y_val`) and test (`X_test`, `y_test`) sets. Evaluate its performance by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report, and assess if the target accuracy is met.

**Reasoning**: To evaluate the tuned Logistic Regression model, I will retrieve the best estimator from `grid_search_lr`, make predictions on the validation and test sets, encode the true target values, then calculate and print the required performance metrics (accuracy, precision, recall, F1-score, and classification report) for both sets, and finally assess against the target accuracy.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

# Get the best Logistic Regression model
best_log_reg_model = grid_search_lr.best_estimator_

print("--- Model Evaluation (Tuned Logistic Regression) on Validation Set ---")
# Make predictions on the validation set
y_pred_val_lr_tuned = best_log_reg_model.predict(X_val)

# Convert y_val to encoded labels for comparison (if not already done)
y_val_encoded = label_encoder.transform(y_val)

# Calculate metrics for validation set
accuracy_val_lr_tuned = accuracy_score(y_val_encoded, y_pred_val_lr_tuned)
precision_val_lr_tuned = precision_score(y_val_encoded, y_pred_val_lr_tuned, av
recall_val_lr_tuned = recall_score(y_val_encoded, y_pred_val_lr_tuned, average=
f1_val_lr_tuned = f1_score(y_val_encoded, y_pred_val_lr_tuned, average='weighte

print(f"Validation Accuracy (Tuned Logistic Regression): {accuracy_val_lr_tunec
```

```
print(f"Validation Precision (weighted): {precision_val_lr_tuned:.4f}")
print(f"Validation Recall (weighted): {recall_val_lr_tuned:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_lr_tuned:.4f}")
print("\nValidation Classification Report (Tuned Logistic Regression):\n", clas

print("\n--- Model Evaluation (Tuned Logistic Regression) on Test Set ---")
# Make predictions on the test set
y_pred_test_lr_tuned = best_log_reg_model.predict(X_test)

# Convert y_test to encoded labels for comparison
y_test_encoded = label_encoder.transform(y_test)

# Calculate metrics for test set
accuracy_test_lr_tuned = accuracy_score(y_test_encoded, y_pred_test_lr_tuned)
precision_test_lr_tuned = precision_score(y_test_encoded, y_pred_test_lr_tuned,
recall_test_lr_tuned = recall_score(y_test_encoded, y_pred_test_lr_tuned, avera
f1_test_lr_tuned = f1_score(y_test_encoded, y_pred_test_lr_tuned, average='weig

print(f"Test Accuracy (Tuned Logistic Regression): {accuracy_test_lr_tuned:.4f}
print(f"Test Precision (weighted): {precision_test_lr_tuned:.4f}")
print(f"Test Recall (weighted): {recall_test_lr_tuned:.4f}")
print(f"Test F1-Score (weighted): {f1_test_lr_tuned:.4f}")
print("\nTest Classification Report (Tuned Logistic Regression):\n", classifica

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (Tuned Logistic Regression) ---")
if target_min_accuracy <= accuracy_val_lr_tuned <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_lr_tuned:.4f}) is within the tar
else:
    print(f"Validation Accuracy ({accuracy_val_lr_tuned:.4f}) is NOT within the

if target_min_accuracy <= accuracy_test_lr_tuned <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_lr_tuned:.4f}) is within the target r
else:
    print(f"Test Accuracy ({accuracy_test_lr_tuned:.4f}) is NOT within the targ
```

```
--- Model Evaluation (Tuned Logistic Regression) on Validation Set ---
Validation Accuracy (Tuned Logistic Regression): 0.6955
Validation Precision (weighted): 0.6987
Validation Recall (weighted): 0.6955
Validation F1-Score (weighted): 0.6967

Validation Classification Report (Tuned Logistic Regression):
               precision    recall  f1-score   support

  High Value       0.80      0.80      0.80       100
   Low Value       0.72      0.66      0.69        50
   Mid Value       0.54      0.57      0.56        70
```

```
    accuracy                           0.70       220
   macro avg       0.69      0.68      0.68       220
weighted avg       0.70      0.70      0.70       220


--- Model Evaluation (Tuned Logistic Regression) on Test Set ---
Test Accuracy (Tuned Logistic Regression): 0.7000
Test Precision (weighted): 0.7015
Test Recall (weighted): 0.7000
Test F1-Score (weighted): 0.7004

Test Classification Report (Tuned Logistic Regression):
               precision    recall  f1-score   support

  High Value       0.82      0.82      0.82        50
   Low Value       0.65      0.60      0.62        25
   Mid Value       0.57      0.60      0.58        35

    accuracy                           0.70       110
   macro avg       0.68      0.67      0.68       110
weighted avg       0.70      0.70      0.70       110


--- Accuracy Target Assessment (Tuned Logistic Regression) ---
Validation Accuracy (0.6955) is NOT within the target range of 85.0% - 90.0%
Test Accuracy (0.7000) is NOT within the target range of 85.0% - 90.0%
```

## Train and Evaluate Tuned Random Forest Classifier

### Subtask:

Train a `RandomForestClassifier` model using the best hyperparameters found from `grid_search_rf`. Then, make predictions on the validation (`X_val`, `y_val`) and test (`X_test`, `y_test`) sets. Evaluate its performance by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report, and assess if the target accuracy is met.

**Reasoning**: To evaluate the tuned Random Forest Classifier model, I will retrieve the best estimator from `grid_search_rf`, make predictions on the validation and test sets, encode the true target values, then calculate and print the required performance metrics (accuracy, precision, recall, F1-score, and classification report) for both sets, and finally assess against the target accuracy.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f

# Get the best Random Forest model
best_rf_model = grid_search_rf.best_estimator_
```

```
print("--- Model Evaluation (Tuned RandomForestClassifier) on Validation Set
# Make predictions on the validation set
y_pred_val_rf_tuned = best_rf_model.predict(X_val)

# y_val is already encoded to y_val_encoded in the previous step if necessar
# If y_val was not encoded for LR, encode it here. Assuming y_val_encoded is
# If not, add: y_val_encoded = label_encoder.transform(y_val)

# Calculate metrics for validation set
accuracy_val_rf_tuned = accuracy_score(y_val_encoded, y_pred_val_rf_tuned)
precision_val_rf_tuned = precision_score(y_val_encoded, y_pred_val_rf_tuned,
recall_val_rf_tuned = recall_score(y_val_encoded, y_pred_val_rf_tuned, avera
f1_val_rf_tuned = f1_score(y_val_encoded, y_pred_val_rf_tuned, average='weig

print(f"Validation Accuracy (Tuned RandomForestClassifier): {accuracy_val_rf
print(f"Validation Precision (weighted): {precision_val_rf_tuned:.4f}")
print(f"Validation Recall (weighted): {recall_val_rf_tuned:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_rf_tuned:.4f}")
print("\nValidation Classification Report (Tuned RandomForestClassifier):\n"

print("\n--- Model Evaluation (Tuned RandomForestClassifier) on Test Set ---
# Make predictions on the test set
y_pred_test_rf_tuned = best_rf_model.predict(X_test)

# y_test is already encoded to y_test_encoded in the previous step if necess
# If y_test was not encoded for LR, encode it here. Assuming y_test_encoded
# If not, add: y_test_encoded = label_encoder.transform(y_test)

# Calculate metrics for test set
accuracy_test_rf_tuned = accuracy_score(y_test_encoded, y_pred_test_rf_tuned
precision_test_rf_tuned = precision_score(y_test_encoded, y_pred_test_rf_tun
recall_test_rf_tuned = recall_score(y_test_encoded, y_pred_test_rf_tuned, av
f1_test_rf_tuned = f1_score(y_test_encoded, y_pred_test_rf_tuned, average='w

print(f"Test Accuracy (Tuned RandomForestClassifier): {accuracy_test_rf_tune
print(f"Test Precision (weighted): {precision_test_rf_tuned:.4f}")
print(f"Test Recall (weighted): {recall_test_rf_tuned:.4f}")
print(f"Test F1-Score (weighted): {f1_test_rf_tuned:.4f}")
print("\nTest Classification Report (Tuned RandomForestClassifier):\n", clas

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (Tuned RandomForestClassifier) ---")
if target_min_accuracy <= accuracy_val_rf_tuned <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_rf_tuned:.4f}) is within the
else:
    print(f"Validation Accuracy ({accuracy_val_rf_tuned:.4f}) is NOT within

if target_min_accuracy <= accuracy_test_rf_tuned <= target_max_accuracy:
```

```
    print(f"Test Accuracy ({accuracy_test_rf_tuned:.4f}) is within the targe
else:
    print(f"Test Accuracy ({accuracy_test_rf_tuned:.4f}) is NOT within the t
```

```
--- Model Evaluation (Tuned RandomForestClassifier) on Validation Set ---
Validation Accuracy (Tuned RandomForestClassifier): 0.9000
Validation Precision (weighted): 0.8990
Validation Recall (weighted): 0.9000
Validation F1-Score (weighted): 0.8989

Validation Classification Report (Tuned RandomForestClassifier):
               precision    recall  f1-score   support

  High Value       0.94      0.98      0.96       100
   Low Value       0.84      0.86      0.85        50
   Mid Value       0.88      0.81      0.84        70

    accuracy                           0.90       220
   macro avg       0.89      0.88      0.89       220
weighted avg       0.90      0.90      0.90       220


--- Model Evaluation (Tuned RandomForestClassifier) on Test Set ---
Test Accuracy (Tuned RandomForestClassifier): 0.8818
Test Precision (weighted): 0.8809
Test Recall (weighted): 0.8818
Test F1-Score (weighted): 0.8794

Test Classification Report (Tuned RandomForestClassifier):
               precision    recall  f1-score   support

  High Value       0.89      0.98      0.93        50
   Low Value       0.88      0.84      0.86        25
   Mid Value       0.87      0.77      0.82        35

    accuracy                           0.88       110
   macro avg       0.88      0.86      0.87       110
weighted avg       0.88      0.88      0.88       110


--- Accuracy Target Assessment (Tuned RandomForestClassifier) ---
Validation Accuracy (0.9000) is within the target range of 85.0% - 90.0%
Test Accuracy (0.8818) is within the target range of 85.0% - 90.0%
```

# Train and Evaluate Tuned Decision Tree Classifier

## Subtask:

Train a `DecisionTreeClassifier` model using the best hyperparameters found from `grid_search_dt`. Then, make predictions on the validation (`X_val`, `y_val`) and test (`X_test`, `y_test`) sets. Evaluate its performance by calculating and reporting

accuracy, precision, recall, and F1-score, along with a classification report, and assess if the target accuracy is met.

## Train and Evaluate Tuned Decision Tree Classifier

### Subtask:

Train a `DecisionTreeClassifier` model using the best hyperparameters found from `grid_search_dt`. Then, make predictions on the validation (`X_val`, `y_val`) and test (`X_test`, `y_test`) sets. Evaluate its performance by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report, and assess if the target accuracy is met.

**Reasoning**: To evaluate the tuned Decision Tree Classifier model, I will retrieve the best estimator from `grid_search_dt`, make predictions on the validation and test sets, ensure the true target values are encoded, then calculate and print the required performance metrics (accuracy, precision, recall, F1-score, and classification report) for both sets, and finally assess against the target accuracy.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

# Get the best Decision Tree model
best_dt_model = grid_search_dt.best_estimator_

print("--- Model Evaluation (Tuned DecisionTreeClassifier) on Validation Set --
# Make predictions on the validation set
y_pred_val_dt_tuned = best_dt_model.predict(X_val)

# y_val is already encoded to y_val_encoded from previous steps

# Calculate metrics for validation set
accuracy_val_dt_tuned = accuracy_score(y_val_encoded, y_pred_val_dt_tuned)
precision_val_dt_tuned = precision_score(y_val_encoded, y_pred_val_dt_tuned, av
recall_val_dt_tuned = recall_score(y_val_encoded, y_pred_val_dt_tuned, average=
f1_val_dt_tuned = f1_score(y_val_encoded, y_pred_val_dt_tuned, average='weighte

print(f"Validation Accuracy (Tuned DecisionTreeClassifier): {accuracy_val_dt_tu
print(f"Validation Precision (weighted): {precision_val_dt_tuned:.4f}")
print(f"Validation Recall (weighted): {recall_val_dt_tuned:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_dt_tuned:.4f}")
print("\nValidation Classification Report (Tuned DecisionTreeClassifier):\n", c

print("\n--- Model Evaluation (Tuned DecisionTreeClassifier) on Test Set ---")
# Make predictions on the test set
```

```
y_pred_test_dt_tuned = best_dt_model.predict(X_test)

# y_test is already encoded to y_test_encoded from previous steps

# Calculate metrics for test set
accuracy_test_dt_tuned = accuracy_score(y_test_encoded, y_pred_test_dt_tuned)
precision_test_dt_tuned = precision_score(y_test_encoded, y_pred_test_dt_tuned,
recall_test_dt_tuned = recall_score(y_test_encoded, y_pred_test_dt_tuned, avera
f1_test_dt_tuned = f1_score(y_test_encoded, y_pred_test_dt_tuned, average='weig

print(f"Test Accuracy (Tuned DecisionTreeClassifier): {accuracy_test_dt_tuned:.
print(f"Test Precision (weighted): {precision_test_dt_tuned:.4f}")
print(f"Test Recall (weighted): {recall_test_dt_tuned:.4f}")
print(f"Test F1-Score (weighted): {f1_test_dt_tuned:.4f}")
print("\nTest Classification Report (Tuned DecisionTreeClassifier):\n", classif

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (Tuned DecisionTreeClassifier) ---")
if target_min_accuracy <= accuracy_val_dt_tuned <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_dt_tuned:.4f}) is within the tar
else:
    print(f"Validation Accuracy ({accuracy_val_dt_tuned:.4f}) is NOT within the

if target_min_accuracy <= accuracy_test_dt_tuned <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_dt_tuned:.4f}) is within the target r
else:
    print(f"Test Accuracy ({accuracy_test_dt_tuned:.4f}) is NOT within the targ
```

```
--- Model Evaluation (Tuned DecisionTreeClassifier) on Validation Set ---
Validation Accuracy (Tuned DecisionTreeClassifier): 0.8500
Validation Precision (weighted): 0.8490
Validation Recall (weighted): 0.8500
Validation F1-Score (weighted): 0.8484

Validation Classification Report (Tuned DecisionTreeClassifier):
               precision    recall  f1-score   support

  High Value       0.88      0.94      0.91       100
   Low Value       0.87      0.78      0.82        50
   Mid Value       0.79      0.77      0.78        70

    accuracy                           0.85       220
   macro avg       0.85      0.83      0.84       220
weighted avg       0.85      0.85      0.85       220


--- Model Evaluation (Tuned DecisionTreeClassifier) on Test Set ---
Test Accuracy (Tuned DecisionTreeClassifier): 0.8000
Test Precision (weighted): 0.8128
Test Recall (weighted): 0.8000
```

```
Test F1-Score (weighted): 0.8008

Test Classification Report (Tuned DecisionTreeClassifier):
               precision    recall  f1-score   support

  High Value       0.86      0.86      0.86        50
   Low Value       0.66      0.84      0.74        25
   Mid Value       0.86      0.69      0.76        35

    accuracy                           0.80       110
   macro avg       0.79      0.80      0.79       110
weighted avg       0.81      0.80      0.80       110


--- Accuracy Target Assessment (Tuned DecisionTreeClassifier) ---
Validation Accuracy (0.8500) is within the target range of 85.0% - 90.0%
Test Accuracy (0.8000) is NOT within the target range of 85.0% - 90.0%
```

## Train and Evaluate Tuned MLP Classifier

### Subtask:

Train an `MLPClassifier` model using the best hyperparameters found from `grid_search_mlp`. Then, make predictions on the validation (`X_val`, `y_val`) and test (`X_test`, `y_test`) sets. Evaluate its performance by calculating and reporting accuracy, precision, recall, and F1-score, along with a classification report, and assess if the target accuracy is met. Ensure proper handling of data types and target encoding for evaluation.

**Reasoning**: To evaluate the trained MLPClassifier model, I will retrieve the best estimator, make predictions on the validation and test sets, convert the target variables to encoded numerical labels for comparison, then calculate and print the required performance metrics (accuracy, precision, recall, F1-score, and classification report) for both sets, and finally assess against the target accuracy.

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_s

# Get the best MLPClassifier model
best_mlp_model = grid_search_mlp.best_estimator_

print("--- Model Evaluation (Tuned MLPClassifier) on Validation Set ---")
# Convert X_val to numpy array for prediction
X_val_np = X_val.astype(np.float32)
# Make predictions on the validation set
y_pred_val_mlp_tuned = best_mlp_model.predict(X_val_np)
```

```
# Convert y_val to encoded labels for comparison
y_val_encoded = label_encoder.transform(y_val)

# Calculate metrics for validation set
accuracy_val_mlp_tuned = accuracy_score(y_val_encoded, y_pred_val_mlp_tuned)
precision_val_mlp_tuned = precision_score(y_val_encoded, y_pred_val_mlp_tuned,
recall_val_mlp_tuned = recall_score(y_val_encoded, y_pred_val_mlp_tuned, averag
f1_val_mlp_tuned = f1_score(y_val_encoded, y_pred_val_mlp_tuned, average='weigh

print(f"Validation Accuracy (Tuned MLPClassifier): {accuracy_val_mlp_tuned:.4f}
print(f"Validation Precision (weighted): {precision_val_mlp_tuned:.4f}")
print(f"Validation Recall (weighted): {recall_val_mlp_tuned:.4f}")
print(f"Validation F1-Score (weighted): {f1_val_mlp_tuned:.4f}")
print("\nValidation Classification Report (Tuned MLPClassifier):\n", classifica

print("\n--- Model Evaluation (Tuned MLPClassifier) on Test Set ---")
# Convert X_test to numpy array for prediction
X_test_np = X_test.astype(np.float32)
# Make predictions on the test set
y_pred_test_mlp_tuned = best_mlp_model.predict(X_test_np)

# Convert y_test to encoded labels for comparison
y_test_encoded = label_encoder.transform(y_test)

# Calculate metrics for test set
accuracy_test_mlp_tuned = accuracy_score(y_test_encoded, y_pred_test_mlp_tuned)
precision_test_mlp_tuned = precision_score(y_test_encoded, y_pred_test_mlp_tune
recall_test_mlp_tuned = recall_score(y_test_encoded, y_pred_test_mlp_tuned, ave
f1_test_mlp_tuned = f1_score(y_test_encoded, y_pred_test_mlp_tuned, average='we

print(f"Test Accuracy (Tuned MLPClassifier): {accuracy_test_mlp_tuned:.4f}")
print(f"Test Precision (weighted): {precision_test_mlp_tuned:.4f}")
print(f"Test Recall (weighted): {recall_test_mlp_tuned:.4f}")
print(f"Test F1-Score (weighted): {f1_test_mlp_tuned:.4f}")
print("\nTest Classification Report (Tuned MLPClassifier):\n", classification_r

# Assess against target accuracy
target_min_accuracy = 0.85
target_max_accuracy = 0.90

print("\n--- Accuracy Target Assessment (Tuned MLPClassifier) ---")
if target_min_accuracy <= accuracy_val_mlp_tuned <= target_max_accuracy:
    print(f"Validation Accuracy ({accuracy_val_mlp_tuned:.4f}) is within the ta
else:
    print(f"Validation Accuracy ({accuracy_val_mlp_tuned:.4f}) is NOT within th

if target_min_accuracy <= accuracy_test_mlp_tuned <= target_max_accuracy:
    print(f"Test Accuracy ({accuracy_test_mlp_tuned:.4f}) is within the target
else:
    print(f"Test Accuracy ({accuracy_test_mlp_tuned:.4f}) is NOT within the tar
```

```
--- Model Evaluation (Tuned MLPClassifier) on Validation Set ---
Validation Accuracy (Tuned MLPClassifier): 0.7273
Validation Precision (weighted): 0.7238
Validation Recall (weighted): 0.7273
Validation F1-Score (weighted): 0.7226

Validation Classification Report (Tuned MLPClassifier):
               precision    recall  f1-score   support

  High Value       0.79      0.89      0.84       100
   Low Value       0.78      0.64      0.70        50
   Mid Value       0.58      0.56      0.57        70

    accuracy                           0.73       220
   macro avg       0.72      0.70      0.70       220
weighted avg       0.72      0.73      0.72       220


--- Model Evaluation (Tuned MLPClassifier) on Test Set ---
Test Accuracy (Tuned MLPClassifier): 0.6636
Test Precision (weighted): 0.6624
Test Recall (weighted): 0.6636
Test F1-Score (weighted): 0.6605

Test Classification Report (Tuned MLPClassifier):
               precision    recall  f1-score   support

  High Value       0.73      0.80      0.76        50
   Low Value       0.70      0.56      0.62        25
   Mid Value       0.54      0.54      0.54        35

    accuracy                           0.66       110
   macro avg       0.66      0.63      0.64       110
weighted avg       0.66      0.66      0.66       110


--- Accuracy Target Assessment (Tuned MLPClassifier) ---
Validation Accuracy (0.7273) is NOT within the target range of 85.0% - 90.0%
Test Accuracy (0.6636) is NOT within the target range of 85.0% - 90.0%
```

# Final Task

## Subtask:

Summarize the entire process, including the specific SMOTE ratios used, the performance of each model, and whether the target accuracy was achieved by any model, providing insights into the strengths and weaknesses of each approach.

# Final Task

### Subtask:

Summarize the entire process, including the specific SMOTE ratios used, the performance of each model, and whether the target accuracy was achieved by any model, providing insights into the strengths and weaknesses of each approach.

## Final Task

### Subtask:

Summarize the entire process, including the specific SMOTE ratios used, the performance of each model, and whether the target accuracy was achieved by any model, providing insights into the strengths and weaknesses of each approach.

## Summary:

### Q&A

- **What specific SMOTE ratios were used?** SMOTE was applied with a custom sampling strategy to balance the target classes: 'High Value' (500 samples), 'Mid Value' (350 samples), and 'Low Value' (250 samples).
- **What was the performance of each model after tuning?**
  - **Tuned Logistic Regression:** Validation Accuracy: 69.55%, Test Accuracy: 70.00%.
  - **Tuned Random Forest Classifier:** Validation Accuracy: 90.00%, Test Accuracy: 88.18%.
  - **Tuned Decision Tree Classifier:** Validation Accuracy: 85.00%, Test Accuracy: 80.00%.
  - **Tuned MLP Classifier:** Validation Accuracy: 72.73%, Test Accuracy: 66.36%.
- **Did any model achieve the target accuracy (85-90%)?** Yes, only the **Tuned Random Forest Classifier** achieved the target accuracy range of 85-90% on both the validation (90.00%) and test (88.18%) sets.

### Data Analysis Key Findings

- **SMOTE Custom Ratios**: SMOTE was successfully re-applied with the custom ratios: 'High Value' (500 samples), 'Mid Value' (350 samples), and 'Low Value' (250

samples). This resulted in a larger and more balanced dataset of 1100 samples, which was then split into training (770), validation (220), and test (110) sets.

- **Hyperparameter Tuning Impact**: Grid Search Cross-Validation was effectively used to find optimal hyperparameters for all four models.
- **Model Performance Comparison (Tuned Models)**:
    - **Tuned Random Forest Classifier**: Emerged as the best-performing model, achieving an impressive 90.00% accuracy on the validation set and 88.18% on the test set. This consistently placed it within the target accuracy range, demonstrating strong generalization capabilities.
    - **Tuned Decision Tree Classifier**: Showed a validation accuracy of 85.00%, meeting the lower bound of the target. However, its test accuracy dropped to 80.00%, suggesting some overfitting or less robust performance on unseen data compared to Random Forest.
    - **Tuned Logistic Regression**: Improved slightly from its initial performance but still remained well below the target, with validation accuracy at 69.55% and test accuracy at 70.00%.
    - **Tuned MLP Classifier**: Also showed some improvement over its untuned version, reaching 72.73% validation accuracy and 66.36% test accuracy, but still fell short of the target.

## Insights or Next Steps

- The **Tuned Random Forest Classifier** is the most robust and suitable model for this classification task, as it consistently met the target accuracy on both validation and test sets after hyperparameter tuning.
- The performance gap between the validation and test sets for the Decision Tree Classifier indicates that even with tuning, it might struggle with generalization, suggesting ensemble methods like Random Forest are inherently more stable for this dataset.
- Logistic Regression and MLP Classifier's performance, even after tuning, suggests that these models might not be complex enough to capture the underlying patterns in the data, or that more extensive tuning/different architectures would be needed for the MLP.
- Further steps could involve: evaluating the best Random Forest model with more advanced metrics (e.g., ROC AUC, confusion matrix), performing feature importance analysis with the Random Forest model to identify key drivers of auction price categories, or exploring other advanced ensemble methods or deep learning architectures to potentially push performance even higher.

# Compare All Tuned Models and Assess Target Accuracy

## Subtask:

Consolidate and compare the performance metrics (accuracy, precision, recall, F1-score) of all tuned classification models (Logistic Regression, Random Forest Classifier, Decision Tree Classifier, MLP Classifier). Assess whether any tuned model meets the target accuracy range of 85-90% on both validation and test sets.

# Final Task

## Subtask:

Summarize the entire process of hyperparameter tuning, including the specific tuning strategies, the performance of each tuned model, and whether the target accuracy was achieved by any model. Identify the best-performing model among all candidates and provide insights into the strengths and weaknesses of each approach.

# Summary:

## Q&A

- **What specific SMOTE ratios were used?** SMOTE was applied with a custom sampling strategy to balance the target classes: 'High Value' (500 samples), 'Mid Value' (350 samples), and 'Low Value' (250 samples). This resulted in a larger and more balanced dataset of 1100 samples, which was then split into training (770), validation (220), and test (110) sets.
- **What was the performance of each model after tuning?**
    - **Tuned Logistic Regression:** Validation Accuracy: 69.55%, Test Accuracy: 70.00%.
    - **Tuned Random Forest Classifier:** Validation Accuracy: 90.00%, Test Accuracy: 88.18%.
    - **Tuned Decision Tree Classifier:** Validation Accuracy: 85.00%, Test Accuracy: 80.00%.
    - **Tuned MLP Classifier:** Validation Accuracy: 72.73%, Test Accuracy: 66.36%.
- **Did any model achieve the target accuracy (85-90%)?** Yes, only the **Tuned Random Forest Classifier** achieved the target accuracy range of 85-90% on both

the validation (90.00%) and test (88.18%) sets.

### Data Analysis Key Findings

- **SMOTE Custom Ratios**: SMOTE was reapplied with custom ratios: 'High Value' (500 samples), 'Mid Value' (350 samples), and 'Low Value' (250 samples), leading to a balanced dataset of 1100 samples.
- **Hyperparameter Tuning Strategy**: GridSearchCV with 5-fold cross-validation and 'accuracy' scoring was used for all models (Logistic Regression, RandomForestClassifier, DecisionTreeClassifier, and MLPClassifier) to find optimal hyperparameters.
- **Tuned Random Forest Classifier**: This model was the best performer, achieving 90.00% accuracy on the validation set and 88.18% accuracy on the test set, successfully meeting the target accuracy range of 85-90% on both sets.
- **Tuned Decision Tree Classifier**: Achieved 85.00% accuracy on the validation set, meeting the lower bound of the target. However, its test accuracy dropped to 80.00%, indicating potential overfitting or less robust generalization.
- **Other Models Performance**: Tuned Logistic Regression (validation accuracy: 69.55%, test accuracy: 70.00%) and Tuned MLP Classifier (validation accuracy: 72.73%, test accuracy: 66.36%) did not meet the target accuracy range after tuning.

### Insights or Next Steps

- The **Tuned Random Forest Classifier** is the most robust and suitable model for this classification task, consistently meeting the target accuracy on both validation and test sets.
- The performance gap between validation and test sets for the Decision Tree Classifier suggests it may not generalize as well as ensemble methods like Random Forest, even after tuning.
- The relatively lower performance of Logistic Regression and MLP Classifier, despite tuning, suggests these models might be too simple or require more extensive architectural search/tuning to capture the complexity of the data.
- Further steps could involve performing feature importance analysis using the best Random Forest model to understand key predictors, or exploring other advanced ensemble methods to potentially enhance performance.

## Task

# Define Parameter Grids for New Ensemble Models

## Subtask:

Define appropriate hyperparameter grids for `BaggingClassifier` and `AdaBoostClassifier`. These grids will specify the range of parameters to be searched during tuning for these ensemble methods.

# Define Parameter Grids for New Ensemble Models

## Subtask:

Define appropriate hyperparameter grids for BaggingClassifier and AdaBoostClassifier. These grids will specify the range of parameters to be searched during tuning for these ensemble methods.

**Reasoning**: To define the hyperparameter grids for BaggingClassifier and AdaBoostClassifier as specified, I will create two dictionaries, `param_grid_bagging` and `param_grid_adaboost`, populating them with the given parameters and their values. I will also import `DecisionTreeClassifier` for the `base_estimator` in `param_grid_adaboost`.

```
from sklearn.tree import DecisionTreeClassifier

param_grid_bagging = {
    'n_estimators': [10, 50, 100],
    'max_samples': [0.5, 0.7, 1.0],
    'max_features': [0.5, 0.7, 1.0]
}

param_grid_adaboost = {
    'n_estimators': [50, 100, 200],
    'learning_rate': [0.01, 0.1, 1.0],
    'base_estimator': [DecisionTreeClassifier(max_depth=1, random_state=42)]
}

print("--- Hyperparameter Grids Defined ---")
print("\nBaggingClassifier Grid:", param_grid_bagging)
print("\nAdaBoostClassifier Grid:", param_grid_adaboost)
```

```
--- Hyperparameter Grids Defined ---

BaggingClassifier Grid: {'n_estimators': [10, 50, 100], 'max_samples': [0.5, 0.7
```

```
AdaBoostClassifier Grid: {'n_estimators': [50, 100, 200], 'learning_rate': [0.01
```

**Reasoning**: To perform hyperparameter tuning for the BaggingClassifier model, I will use `GridSearchCV` with the predefined `param_grid_bagging`. I will fit it to the training data (`X_train`, `y_train_encoded`), using the already encoded `y_train` from previous steps. Finally, I will print the best parameters and the best cross-validation score found by the grid search.

```
from sklearn.ensemble import BaggingClassifier

print("--- Starting Hyperparameter Tuning for BaggingClassifier ---")

# Instantiate the BaggingClassifier model
bagging_classifier = BaggingClassifier(random_state=42)

# Create the GridSearchCV object
grid_search_bagging = GridSearchCV(
    estimator=bagging_classifier,
    param_grid=param_grid_bagging,
    cv=5, # 5-fold cross-validation
    scoring='accuracy', # Use accuracy as the scoring metric
    n_jobs=-1, # Use all available CPU cores
    verbose=1 # Display progress
)

# Fit GridSearchCV to the training data (using already encoded y_train)
grid_search_bagging.fit(X_train, y_train_encoded)

print("\nBest Parameters for BaggingClassifier:", grid_search_bagging.best_para
print("Best Cross-validation Score for BaggingClassifier:", grid_search_bagging
```

```
--- Starting Hyperparameter Tuning for BaggingClassifier ---
Fitting 5 folds for each of 27 candidates, totalling 135 fits

Best Parameters for BaggingClassifier: {'max_features': 1.0, 'max_samples': 1.0,
Best Cross-validation Score for BaggingClassifier: 0.8649350649350648
```

**Reasoning**: To perform hyperparameter tuning for the AdaBoostClassifier model, I will use `GridSearchCV` with the predefined `param_grid_adaboost`. I will fit it to the training data (`X_train`, `y_train_encoded`), using the already encoded `y_train` from previous steps. Finally, I will print the best parameters and the best cross-validation score found by the grid search.

```
from sklearn.ensemble import AdaBoostClassifier
```