

# LA\_mnist

September 15, 2021

```
[ ]: import numpy as np
import matplotlib.pyplot as plt
import random
from tensorflow.keras.datasets import mnist
import argparse
```

```
[ ]: class KMeans():
    def __init__(
        self,
        x_train,
        y_train,
        num_clusters=3,
        max_iter=100,
        tol=1e-4,
        seed: str = None,
    ):
        """
        Initialize KMeans object.
        Arguments:
            dataset: numpy array of shape (n_samples, n_features)
            k: number of clusters
            max_iter: maximum number of iterations
            tol: tolerance for convergence
            seed: initial cluster centroids choice ['random', 'cluster']
        """
        self.dataset = x_train
        self.targets = y_train

        self.k = num_clusters
        self.max_iter = max_iter
        self.tol = tol

        self.num_features = x_train.shape[1]
        self.num_samples = x_train.shape[0]
        self.losses = []

        if seed == "random":
```

```

        self.centroids = np.random.uniform(
            size=(self.k, self.num_features))
elif seed == "cluster":
    if (self.k > self.num_samples): # hack for large k
        self.centroids = np.copy(self.dataset[np.random.choice(
            self.num_samples, self.k, replace=True)])
    else:
        self.centroids = np.copy(self.dataset[np.random.choice(
            self.num_samples, self.k, replace=False)])
else:
    raise ValueError("seed must be in ['random', 'cluster']")
# store old centroids for convergence check
self.old_centroids = np.copy(self.centroids)
# store cluster assignment indexes
self.cluster_labels = np.zeros(self.num_samples, dtype=int)

def converged(self):
    """
    Checks if the kmeans algorithm has converged.
    The algorithm has converged if the centroids have not changed by a h.p
    →tolerance
    Returns:
        bool: True if converged, False otherwise
    """
    return np.all(np.linalg.norm(self.centroids - self.old_centroids,
    →ord=2, axis=1) < self.tol)

def assign_clusters(self):
    """
    Assigns each sample to a cluster.
    """
    for i in range(self.num_samples):
        self.cluster_labels[i] = np.argmin(
            np.linalg.norm(self.dataset[i]-self.centroids, ord=2, axis=1))

def get_centroid_labels(self):
    """
    Computes the label class for each centroid by finding the maximum freq
    →of a label in a cluster.
    Returns:
        numpy array of shape (k,)
    """
    centroid_labels = np.zeros(self.k)
    for i in range(self.k):
        count = np.bincount(self.targets[self.cluster_labels == i])
        if len(count) > 0:
            centroid_labels[i] = np.argmax(count)

```

```

        return centroid_labels

def fit(self, verbose=False, plot=False):
    """
    Runs the KMeans algorithm.
    Args:
        verbose (bool, optional): Parameter to print every iteration result.
        → Defaults to False.
        plot (bool, optional): Parameter to plot J_clust vs Iterations.
        → Defaults to False.
    """
    for i in range(self.max_iter):
        self.assign_clusters()
        self.update_centroids()
        loss = self.calc_loss()
        self.losses.append(loss)
        if verbose:
            print(f"Iteration {i+1} Loss: {loss}")
            print("-----")
        if self.converged():
            print(f"{loss}")
            break
        self.old_centroids = np.copy(self.centroids)
    if plot:
        self.plot_loss()

def plot_loss(self):
    """
    Plots the loss vs iterations.
    """
    plt.plot(self.losses)
    plt.xlabel("Iterations")
    plt.ylabel("Loss")
    plt.show()

def calc_loss(self):
    """
    Calculates the J_clust loss value
    Returns:
        float: J_clust loss value
    """
    loss = np.mean(np.square(np.linalg.norm(
        self.dataset - self.centroids[self.cluster_labels], ord=2,
        →axis=1)), axis=0)
    return loss

def update_centroids(self):

```

```

        """
        Updates the centroids by finding the mean of each cluster.
        Note:
            If a cluster is empty, the centroid is set to a random point in the
        ↪ dataset.
        """
        for i in range(self.k):
            alloted = self.dataset[self.cluster_labels == i]
            if len(alloted) > 0:
                self.centroids[i] = np.mean(alloted, axis=0)
            else:
                self.centroids[i] = np.zeros(self.num_features)

    def predict(self, x):
        """
        Predicts the label for a given sample. by finding out in which cluster
        ↪ it belongs and the cluster label
        Args:
            x (numpy array): samples to predict label for
        Returns:
            numpy array of shape (n_samples,)
        """
        labels = np.zeros(x.shape[0], dtype=int)
        for i in range(x.shape[0]):
            labels[i] = np.argmin(
                np.linalg.norm(x[i]-self.centroids, ord=2, axis=1))
        return self.get_centroid_labels()[labels]

```

```

[ ]: def seed_everything(seed):
    """
    Util function to seed numpy and random
    Args:
        seed (int)
    """
    random.seed(seed)
    np.random.seed(seed)

```

```

[ ]: def load_data():
    """
    Loads the mnist dataset and returns train and test dataset
    """
    (x_train, y_train), (x_test, y_test) = mnist.load_data()

    # normalize training and test data
    x_train = x_train / 255
    x_test = x_test / 255
    x_train = x_train.reshape(x_train.shape[0], -1)

```

```

x_test = x_test.reshape(x_test.shape[0], -1)

digits = []
targets = []
for i in range(10):
    images = x_train[y_train == i]
    digits.append(images[np.random.choice(
        len(images), 100, replace=False)])
    targets.append(np.full((100,), i))

x_train = np.vstack(digits)
y_train = np.hstack(targets)

# shuffle the data
permutation = np.random.permutation(x_train.shape[0])
x_train = x_train[permutation]
y_train = y_train[permutation]

test_indices = np.random.choice(x_test.shape[0], 50)
x_test = x_test[test_indices]
y_test = y_test[test_indices]
return (x_train, y_train), (x_test, y_test)

```

```

[ ]: def plot_centroids(kmeans, centroids):
    """
    Plots the centroids of the KMeans algorithm.
    Args:
        kmeans (KMeans): KMeans object
        centroids (numpy array): centroids of the KMeans object
    """
    centroid_images = np.copy(centroids.reshape(kmeans.k, 28, 28))
    centroid_images = centroid_images * 255

    centroid_labels = kmeans.get_centroid_labels()

    fig = plt.figure(figsize=(20, 20))
    nrows = 5
    ncols = kmeans.k // nrows + kmeans.k % nrows
    for i in range(kmeans.k):
        fig.add_subplot(nrows, ncols, i+1)
        plt.imshow(centroid_images[i], cmap="gray")
        plt.title(f"Label: {centroid_labels[i]}", fontsize=15)
        plt.axis("off")
    plt.show()

```

```

[ ]: def main(num_clusters, max_iter, seed, tol, verbose):
    """

```

```

Utility function to run the KMeans algorithm and plot the centroids.
"""

# load the mnist data
(x_train, y_train), (x_test, y_test) = load_data()
# create a kmeans instance
kmeans = KMeans(x_train, y_train,
                 num_clusters= num_clusters,
                 max_iter=max_iter,
                 tol=tol,
                 seed=seed)

kmeans.fit(verbose=verbose, plot=True) # train the model
# predict the labels from input labels and centroids
predictions = kmeans.predict(x_test)
print(f"Accuracy: {np.mean(predictions == y_test)}") # print the accuracy
plot_centroids(kmeans, kmeans.centroids) # plot the centroids

```

```
[ ]: seed_everything(72)
```

```
[ ]: main(num_clusters=20, max_iter=1000, seed='cluster',tol=1e-6,verbose=False)
```

```
[ ]: main(num_clusters=20, max_iter=100, seed='random',tol=1e-6,verbose=False)
```

```
[ ]: def plot_jclust(max_iter, seed,tol,verbose):
      k = np.arange(start=5, stop=21, step=1, dtype=int)
      (x_train, y_train), (x_test, y_test) = load_data()
      # create a kmeans instance
      jclust = []
      for num_cluster in k:
          kmeans = KMeans(x_train, y_train,
                           num_clusters=num_cluster,
                           max_iter=max_iter,
                           tol=tol,
                           seed=seed)
          kmeans.fit(verbose=verbose) # train the model
          jclust.append(kmeans.calc_loss())

      plt.plot(k, jclust)
      plt.xlabel("Number of Clusters")
      plt.ylabel("J-Clustering Loss")
      plt.show()

```

```
[ ]: plot_jclust(max_iter=1000, seed='cluster',tol=1e-6,verbose=False)
```

```
[ ]: plot_jclust(max_iter=1000, seed='random',tol=1e-6,verbose=False)
```