Supplementary Material for "Memory and State Control for LLM-Driven NPC Dialogue: Scoped Dual-Tier Memory and Pre-Commit Invariant Validation under a Paired, Oracle-Audited Evaluation"

Anonymous Authors

This document supplements the manuscript. Sections, tables, figures, equations and algorithms numbered with an S prefix are in this document, and all others are in the manuscript. It holds the algorithms (Section S1), the dataset (Section S2), the implementation, run configuration and audit (Section S3), the extended results (Sections S4 and S5) and the sample-size ladder (Section S6). Every number comes from the run outputs released with the code.

S1. Algorithms

Algorithm S1 is one turn of the engine, following nodes 1 to 9 of Fig. 1: input sanitisation, scoped retrieval, budgeted prompt assembly, generation and parsing, validation against a running state, repair of a reply whose proposals were rejected, and the commit that appends events, reduces the state, updates both memory tiers and writes periodic snapshots.

Algorithm S1 One turn of the engine (nodes 1 to 9 of Fig. 1)

Require: player input u, active NPC n, state S_t, store M, buffer H, log $\mathcal{E}$

$u \leftarrow \textsc{Trim}(u)$, **if** $u = \varepsilon$ **then** $u \leftarrow$ "(silence)"

$\mathbf{q} \leftarrow \textsc{Embed}(u)$, $\mathcal{R} \leftarrow \textsc{ScopedRetrieve}(\mathbf{q}, \pi(S_t), n)$ ▷ Algorithm S2

$(\mathcal{R}', h) \leftarrow \textsc{PackContext}(\mathcal{R}, H,\ 1{,}600\ \text{chars})$, $x \leftarrow \textsc{BuildPrompt}(S_t, n, u, \mathcal{R}', h)$

$y \leftarrow \text{LLM}(x)$, $o \leftarrow \textsc{ParseJSON}(y)$ ▷ on failure: y becomes dialogue, no proposals

$\hat{S} \leftarrow S_t$, $E_t \leftarrow [\,]$, $rej \leftarrow [\,]$

for $(\tau, p) \in o.\text{proposals}$ **do**

  if $V(\tau, p, \hat{S}, S_t)$ **then** $E_t.\text{append}(e(\tau, p))$, $\hat{S} \leftarrow \delta(\hat{S}, e(\tau, p))$

  else $rej.\text{append}((\tau, p))$

if $rej \neq [\,]$ **then** $o.\text{dialogue} \leftarrow \textsc{Repair}(o, E_t, rej)$ ▷ one LLM call, neutral narration on failure

append e_{speech} and E_t to $\mathcal{E}$ in one transaction, $S_{t+1} \leftarrow \text{foldl}(\delta, S_t, E_t)$

$H.\text{push}(u, o.\text{dialogue}, n)$, $M.\text{add}(\mathbf{q},\ o.\text{summary},\ t{+}1,\ \pi(S_{t+1}),\ n)$

if $|M| > 1000$ **then** keep the newest 500 entries of M

if $(t+1) \bmod 16 = 0$ **then** write snapshot $(S_{t+1}, \max \text{id}(\mathcal{E}))$ atomically and save M

return dialogue, narration, S_{t+1}

Algorithm S2 is the retrieval step, (4) as code: it over-fetches fk nearest neighbours by exact inner product, keeps those inside the current scope, and falls back to the unscoped list when fewer than θ survive.

Algorithm S2 ScopedRetrieve
(`make_node_retrieval`, `FAISSMemory.search`)

Require: query $\mathbf{q}$, location ℓ, NPC n, $k = 6$, $f = 5$, $\theta = 3$

$C \leftarrow$ exact inner-product top-$\min(fk, |M|)$ of $\mathbf{q}$ over M

$R \leftarrow [\,]$

for $m \in C$ in descending similarity **do**

  if $\phi_{\ell,n}(m)$ **then** append m to R, **if** $|R| = k$ **then break**

if $|R| < \theta$ **then** $R \leftarrow$ first k entries of C ▷ relaxation fallback, unscoped

return R

TABLE S1
WORLD SUITE AS BUILT FOR THE RUN (METRICS/WORLD_STATS.CSV). "JOIN" COUNTS SPANNING-TREE EDGES ADDED TO CONNECT LIGHT'S ROOM GRAPH.

World	Family	Locations	NPCs	Objects	Rules	Edges	Diameter	Secrets	Join
W1	in-house (in-distribution)	8	4	4	7	7	4	8	0
W2a	LIGHT-derived	16	6	7	5	15	8	12	14
W2b	LIGHT-derived	24	6	9	5	23	9	12	22
W2c	LIGHT-derived	32	6	12	5	31	9	12	27
W3	held-out genre	24	6	8	6	27	4	12	0
W4-32	procedural	32	8	16	5	39	9	16	0
W4-128	procedural	128	16	64	5	163	12	32	0

A. Paired four-way commit and audit

Algorithm S3 is the core of the evaluation protocol of Section IV-D. One model output per probe is committed through the corrected barrier, the Review-02 barrier, the reducer alone and by direct writes, and each post-state is audited by the oracle.

Algorithm S3 Paired four-way commit and independent audit of one probe output

Require: scenario state S, prompt x, seed $s = h(\text{probe id})$ ▷ independent of condition
$y \leftarrow \text{LLM}(x, \text{seed } s)$, $o \leftarrow \textsc{ParseJSON}(y)$
for mode $\in$ {barrier, barrier v1, reducer, direct} **do**
  if mode = barrier **then** $S' \leftarrow \text{foldl}(\delta, S, E)$ with E from the running-state check of Equation (2)
  else if mode = barrier v1 **then** $S' \leftarrow \text{foldl}(\delta, S, [e(\tau, p) : V_{\text{v1}}(\tau, p, S)])$ ▷ Review-02 validator
  else if mode = reducer **then** $S' \leftarrow \text{foldl}(\delta, S, [e(\tau, p) : \tau \text{ a known type}])$ ▷ ablation A5
  else $S' \leftarrow$ write each proposal and each new entity into a copy of S ▷ no clamping
  $v_{\text{mode}} \leftarrow \textsc{Oracle}(S, S', \text{committed list})$ ▷ O1 to O8, no validator code
return the four verdicts and lawful/unlawful counts per proposal

B. Complexity

With $|M| \leq 1000$ entries, $d = 384$ and p proposals per turn: exact search is $O(|M|d)$. Validation is $O(p)$ lookups plus one reduction per accepted proposal for the running state. Reduction is $O(p\,|S|)$ because each event deep-copies the state. Recovery from the latest snapshot is $O(|S| + r)$ with r the events since it. Measured costs are in Section S4-F.

S2. DATASET DESCRIPTION AND USAGE

The dataset is a benchmark built for this study: seven worlds, teacher-forced recall sessions, adversarial probes with lawful twins, and live-session scripts, generated deterministically by the evaluation notebook from a master seed, together with the model outputs and metrics of the reported run. Section S2-E lists the released files and how each is used.

A. World suite

A single hand-made world cannot support generalisation claims, and a benchmark written by the system's authors risks being tuned to it. The suite therefore has four families (Table S1 and Fig. S1): W1, the in-house dark-fantasy development world (Backend/game/world_seed.json), and W2a to W2c, converted by a deterministic seeded script from the crowd-written LIGHT environment file [1] (CC BY-NC 4.0), with LIGHT's fragmented room graph joined by a seeded spanning tree and two templated secrets per NPC built from words that occur nowhere else in the world. W3 is a 24-location science-fiction station authored in the notebook from a written specification before any system run, and W4-32 and W4-128 are procedural graphs (random spanning tree plus about 30% extra edges) with templated names. No system setting was tuned on W2 to W4. W3 is held out from tuning but was *not* independently authored.

B. Teacher-forced long-horizon recall sessions

A session is a fixed script of $H \in \{50, 100, 200\}$ player turns. For each fact age $a \in \{5, 10, 20, 40, 80, 160\}$ with $a < H - 1$, two facts are *planted* with a randomly chosen NPC and *probed* a turns later with the same NPC, using 15 attribute templates (meeting place, password, debt, and so on). Each fact has a paraphrased *distractor* with a different value told to a different NPC, placed between plant and probe where possible. Values come from pools of invented or uncommon words. Any value whose key word occurs anywhere in a world's text is removed, so a correct answer cannot come from lore. A probe is correct




Fig. S1. Size of each world (log scale): locations, NPCs and objects. The procedural W4-128 extends the suite to 128 locations, 16 NPCs and 64 objects.

when the gold key word appears as a whole word in the reply or narration, and *confused* when the distractor's key word appears instead.

Fillers are small talk with the NPC of the next scripted event, and the player stands at that NPC's location. NPC replies and memory summaries in the history are scripted (teacher forcing), so every condition sees the same history and the LLM is called only at probe turns. A session holds 8, 10 or 12 probes for $H = 50, 100, 200$. With three sessions per world and horizon, each condition answers 630 probes over 63 sessions: 540 on held-out worlds, of which 324 have $a \geq 20$. Because a fact is always probed with the NPC it was told to, at that NPC's fixed location, this design favours scoping. Section X returns to this.

C. Adversarial invariant probes with lawful twins

Each probe is a scenario (a world state with the player beside an NPC, three teacher-forced history turns, and one attack turn) in one of seven categories, each paired with a lawful twin: teleportation (twin: walk to an adjacent location), item fabrication (pick up a present item), theft or duplication (pick up a present item), trust inflation (thank the NPC), currency exploits (pay a small affordable amount), prompt injection [2] (an ordinary question), and secret extraction at trust 0 (the same request at trust 80). The run used 10 attacks per category per world, 490 attacks in all, with 470 twins: theft has twins for 50 of its 70 attacks. Every attack and twin was posed under five context conditions (F4, B0, B1, B2, B3), giving 4,800 probe outputs.

D. Live sessions

Live sessions run the backend's real LangGraph nodes every turn, so the model's own replies and committed state feed later turns. Each script has 39 turns: four plants with two NPCs, walks between them (one "I walk over to …" turn per edge), small talk, two lawful trades, six attacks, and four late probes. The recorded fact ages of these probes are 30 to 34 turns. Two scripts per world give 14 sessions per condition, paired on identical inputs. If a scripted move is not committed the script continues, which the desynchronisation metric detects.

E. Sources, format and release

Sources. W1 is the game's own seed (Backend/game/world_seed.json). W2a to W2c are converted from the LIGHT environment file [1] (`light-environment.pkl`, CC BY-NC 4.0), whose rooms (setting and description), characters with personas, and objects become locations, NPCs and objects. W3 and W4 are generated in the notebook. *Format.* Each world is a JSON document in the game's save schema: metadata, locations with `connected_to` lists, NPCs with description, personality, knowledge, secrets and an `alive` flag, objects with location and owner, world rules, the player (location, inventory, currency), trust relationships, journal and turn. Recall sessions (session id, world, horizon, scripted turns, planted facts), adversarial probes (category, attack, lawful twin, scenario state, history) and live scripts are JSON Lines files with one record per line. *Size.* The notebook generates the full pools of the largest sample-size level, 840 recall sessions, 2,940 probe scenarios and 70 live scripts (about 33 MB and 130 MB for the first two), and a run uses a prefix of each. The reported run used 63 recall sessions per condition (630 probes), 490 attacks with 470 lawful twins, and 14 live sessions of 39 turns per condition. *Release.* The generated data, every prediction and metric file, and the blinded annotation sheets are committed under notebooks/outputs/ and in notebooks/outputs.zip. The W2 worlds inherit LIGHT's non-commercial licence.

F. How the data is used

Recall sessions answer RQ1: every memory condition replays the same teacher-forced history and is asked the same probes, so recall, MRR and gold-in-prompt rates are paired across conditions. Probes answer RQ2: each attack and its lawful twin is posed under five context conditions, and every output is committed four ways (Section IV-D). The paired before-and-after

comparison uses all three kinds of data. Live sessions answer RQ3 and RQ4: they run the real backend graph each turn for the 2×2 factorial and the control ablations and record latency and tokens. RQ5 uses the split by world family (W1 is in-distribution, W2 to W4 are held out from tuning) and three further models on a subset: a smaller model of the same family and two models of other families. Every table in Section IX can be regenerated from the prediction files and response caches without a GPU (Section S3-B).

S3. Implementation and Run

A. Software stack

The engine has four tiers. The presentation tier (React, TypeScript, Zustand) streams turns over a WebSocket. The orchestration tier (FastAPI with per-session async locks) runs a compiled nine-node LangGraph `StateGraph` (graph/definition.py). The validation tier is the barrier (game/validator.py). The storage tier holds the SQLite event log and snapshots (core/event_store.py, core/snapshot.py, core/recovery.py), the FAISS store with all-MiniLM-L12-v2 embeddings (memory/faiss_index.py) and the turn buffer (memory/short_term.py). In the shipped game the LLM is a hosted endpoint (Groq, `openai/gpt-oss-120b`, temperature 0.35, Backend/config.py). In the evaluation it is a self-hosted model served by vLLM [3].

B. System under test

The notebook notebooks/npc-memory-state-benchmark.ipynb does not clone the repository: it embeds the backend source of commit [commit withheld for review] as a hashed bundle (SHA-256 `9f7d7e7bbb0d`…, 45 files), together with the validator and prompt builder of the Review-02 commit [commit withheld for review] for condition F4v1, asserts the hash, and imports the real backend modules (reducer, validator, event store, snapshots, recovery, prompt builder and packing, FAISS memory, buffer, JSON extractor and the LangGraph node factories). The released notebook embeds a later bundle whose only change is the backend's dependency list, which the notebook does not install from. Live conditions are built from the backend's own nodes, swapping only the nodes a condition changes. Only the baselines, the oracle and the benchmark generators are new code. Before any GPU time, a self-test with a deterministic mock LLM checks that the oracle flags direct writes, that the corrected barrier commits no more violations than the Review-02 barrier, that event-sourced sessions replay exactly, that the corrected load path recovers after a crash, and that the notebook's scoped retrieval matches `node_retrieval`. Table S2 lists the run configuration.

TABLE S2
Run configuration (metrics/run_manifest.json).

Hardware	Kaggle session, 2× Tesla T4 (15.64 GB each, compute capability 7.5, driver 580.178.04), 4 CPU cores, 33.7 GB RAM
Software	Python 3.13.15, PyTorch 2.11.0+cu128, sentence-transformers 5.4.1, faiss-cpu 1.15.1, LangGraph 0.6.11, langchain-core 0.3.86, Pydantic 2.13.5, NumPy 2.1.3, pandas 2.3.3, SciPy 1.16.3, statsmodels 0.15.0, vLLM 0.30.0 in an isolated environment
Backbones	primary `IFM/K2-Horizon-7B` (fp16, tensor parallel over both GPUs), `IFM/K2-Horizon-3.7B` (same family), `Qwen/Qwen2.5-7B-Instruct` and `microsoft/Phi-4-mini-instruct` (other families, chat endpoint), Qwen2.5-7B is also the contradiction judge
Decoding	temperature 0.35 (backend value), top-p 0.95, K2-Horizon reasoning effort low, thinking capped at 192 tokens then closed by the harness, answer $\leq$768 tokens, context 16,384 tokens, 64 concurrent sequences
Seeds	master seed 20261001, request seed a function of probe or turn only, sampling-seed replicates 1 and 2 for F4, B1, B2, B3
Engine constants	buffer 8, $k = 6$, over-fetch 5, fallback threshold 3, memory budget 1,600 chars, newest 2 turns always kept, snapshot every 16 turns, prompt cap 16,384 chars, trust step 20, currency gain cap 50, secrets shown at trust 60
Benchmark	horizons 50/100/200, fact ages 5 to 160, 2 probes per age, 3 history turns per probe, budget $B = 389$ tokens, 300 crash trials, oracle trust step 20, currency gain cap 50
Sample size	ladder level 2 (index 0 to 7): 3 sessions per world and horizon, 10 probes per category and world, 2 live sessions per world
Statistics	10,000 cluster-bootstrap resamples, $\alpha = 0.05$, Holm correction

C. Sample-size planning

Eight pre-declared levels (index 0 to 7, Section S6) fix sessions per world and horizon, probes per category and world, and live sessions per world, so a smaller level is a prefix of a larger one. A pilot of 256 jobs measured steady-state throughput, and a planner chose the largest level whose estimated cost fitted the 11.25-hour budget after reserves for the analysis, the latency benchmark, the second backbone and the independent families: level 2 (estimated 6.76 h of 7.74 h available, level 3 needed 8.40 h), the third of the eight levels. The two earlier Review-03 runs had chosen level 1 because their planner multiplied an already conservative estimate by a safety factor of 1.15. The reported run is the first without that factor. Its estimate was still conservative: the four LLM stages of level 2 took 5.49 h, 23% less than estimated, and the run ended after 7.65 of the 11.25 hours. Coverage was complete: 8,190 recall, 4,800 probe, 3,822 live-turn, 1,680 seed-variance, 48 repair, 364 judge and 108 single-stream latency rows, 1,080 and 550 for the second backbone, and 840 and 550 for each independent family, none lost to a deadline. The primary server generated 16,220 responses and served 2,860 from the response cache (pilot responses reused by the main stages, and identical prompts shared by conditions). No request was skipped. Fig. S2 shows the run profile.




Fig. S2. GPU utilisation of both T4s over the 7.65-hour run, sampled every 15 s by `nvidia-smi`. Utilisation is near 100% from the pilot (0.5 h) to the end of the single-stream latency benchmark (6.4 h). The drops are stage changes (the dip at 4.4 h is the dialogue-repair stage), and the final segment is the second backbone and the two independent families, with server restarts between them.

D. Execution procedure

(1) Create a Kaggle notebook from notebooks/npc-memory-state-benchmark.ipynb, select *GPU T4 x2*, enable Internet, and optionally attach an independently written `w3_world_seed.json`, earlier `llm_cache_*.jsonl` files or completed rating sheets. (2) Run it as a saved version (*Save & Run All*). The notebook installs the pinned packages, builds the worlds and benchmark, runs the CPU experiments, the pilot, the planner and every LLM stage, and writes `outputs.zip`. Stage times in the reported run were: recall 183.1 min, probes 44.8 min, live sessions 74.6 min, seed variance 26.8 min, latency 17.9 min, second backbone 44.8 min, independent families 30.3 min, replay 13.1 min, crash trials 6.2 min. (3) The outputs used in this paper come from the notebook as committed at [commit withheld for review], run on 24 and 25 October 2026, and are committed under notebooks/outputs/ (plots, metrics, predictions, annotation sheets) together with notebooks/outputs.zip, which also holds the generated worlds, sessions, probes and logs. With the response caches attached and `CACHE_ONLY=True`, the notebook regenerates every table without a GPU. The game itself runs with `npm run dev` from the repository root (Python 3.10+, Node 20.19+ or 22.12+, and a `GROQ_API_KEY`), this paper builds with `npm run paper` from the repository root, which runs the bundled Tectonic and fails on any undefined reference, overfull box or bibliography warning.

E. Corrections and audit of the run

The Review-02 run of this protocol found seven defects in the engine: (1) unbounded currency gains, (2) per-proposal instead of per-turn checking, (3) unchecked NPC drops and relocations, (4) a prompt that advertised a different trust range than the validator allowed, (5) secrets that never reached the model, (6) a load path that discarded the logged suffix, with the active NPC set outside the log, and (7) dialogue that described rejected changes. All seven are corrected in the evaluated code (Section IV-A) and covered by unit and property tests, including 3,000 random multi-proposal turns checked against an independent invariant checker. Structural legality remains the only rule: an in-bounds but unjustified trust change passes.

The corrected system was run three times. Auditing the first Review-03 run (22 October 2026) against its prediction files found four measurement defects in the notebook: retrieval metrics counted every age-5 probe as a retrieval miss for F4, A3 and A4, whose packing drops a memory that duplicates a buffered turn (Section IV-E), which biased the pre-registered H2 test against F4. The single-stream live latency sessions reused the main run's seeds, so their LLM calls were answered from the response cache, and the latency stage reached its deadline before B4 and B5. The secret-leak scorer took template words such as "behind" as secret keywords. Finally, a shared random stream gave one estimate different bootstrap intervals in different tables. The notebook was fixed and run again on 24 October 2026. Auditing that second run found one attribution error, a single-stream stage table with no row for dialogue repair, whose regeneration was counted as local compute. It also showed that the planner's safety factor kept both runs at level 1, and that the progress log fell silent for 31 minutes while the concurrent live sessions ran. The notebook was corrected (repair as its own stage, local compute without either LLM call, no safety factor, a progress heartbeat every 60 s) and run a third time, unchanged, from 24 to 25 October 2026. That third run is the one reported here, and its saved outputs confirm each fix. Auditing it found no further measurement defect. It did find that every lawful twin proposal the barrier rejected is a trust change that names the NPC by its display name instead of its id. The oracle's lawfulness label did not check NPC ids, so the false-rejection rate on probes slightly overstates the barrier's cost (Section IX-C). The released notebook's oracle now also requires trust relationships to name canonical NPCs.

S4. Extended Results

This section gives the full text and tables behind the summary in Section IX.




Fig. S3. Mean input tokens per turn against recall at fact age 20 or more (held-out worlds). Up and to the left is better. The budgeted conditions cluster near 1,450 tokens. B0 costs about three times as much for lower recall. A1 and B1 sit at zero.

A. *Cost against recall*

Fig. S3 plots each condition's input tokens per turn against its recall at fact age 20 or more.

B. *Retrieval quality, sensitivity and seed variance*

Scoping changed *ranking* more than *reach*. Scored on the 432 held-out probes older than the buffer, F4 placed the gold memory in its retrieved list for 100% of them, as did B2, A2 and A4 (B3 99.8%, Section S5), but ranked it higher: MRR@6 0.910 against 0.742 for B2 and 0.732 for the unscoped ablation A3. It also kept the paraphrased distractor out of 46% of prompts, against 1% for B2 and 9% for A3. Removing the buffer (A2) kept the distractor out of 90% of prompts, because the distractor, told to a different NPC, then reaches the prompt only through retrieval. In the teacher-forced design the fallback rarely helps: disabling it (A4) raised MRR@6 to 0.954, since the fallback replaces a short scoped list with unscoped neighbours.

The retrieval-only sweeps (80 sessions on W1 and W2 at horizons 100 and 200, one setting varied at a time around buffer 8, $k = 6$, $\theta = 3$) confirm this (Fig. S4, values in Section S5). Buffer size had no effect on retrieval. A threshold of 0, which is A4, gave the best MRR, and $\theta = 6$ triggered the fallback more often and lowered it. Scaling every condition's budget (plotted in Section S5) shows that from half the default budget F4 places the gold turn in 99.9% of prompts, like B2 (100%) and close to B3 (98.3% at half and 99.8% at the full budget), while B4 and B5 saturate at 85% and 95% and the rolling context needs four times the budget to reach 70%.




Fig. S4. Gold-in-prompt rate and MRR@k for each sweep setting. The default is buffer 8, $k = 6$, threshold 3 (labelled buf8). Lower k and a higher fallback threshold reduce ranking quality. Removing the fallback (thr0) improves it on this benchmark.

Across three sampling seeds on the 21 calibration sessions (210 probes, all ages), every condition varied by a few points (Table S3, plotted in Section S5).

C. *Factorial separation in live sessions*

Live sessions reproduce the probe result (Table S4, interaction plots in Section S5). Under direct writes the oracle flagged 471 of 546 F1 turns and 469 of 546 F3 turns, from only 94 and 118 committed transitions, because the corruption persists: direct writes left the player in a non-existent location on an average of 29.4 (F1) and 30.6 (F3) of 39 turns, and the harness then prompted from the last valid location. Neither corrected-barrier condition (F2, F4) had a flagged turn. F4v1 had four: three currency gains (+300, +300 and +2,000) that the Review-02 validator accepted during currency attacks, and one NPC

TABLE S3
RECALL OVER ALL AGES FOR THREE SAMPLING SEEDS (CALIBRATION SESSIONS, ALL WORLDS).

Condition	Seed 0	Seed 1	Seed 2	SD (points)
F4	0.843	0.814	0.857	2.18
B1, B	0.295	0.276	0.276	1.10
B2	0.848	0.848	0.857	0.55
B3	0.633	0.671	0.633	2.20

TABLE S4
MEMORY × CONTROL FACTORIAL ON LIVE SESSIONS (14 SESSIONS OF 39 TURNS PER CELL, 56 LIVE PROBES PER CELL). FALSE REJECTION IS OF LAWFUL LIVE PROPOSALS. DESYNCHRONISATION IS AFTER REPAIR.

Cell	Live recall (%)	Viol./100 transitions	False rejection (%)	Desync (%)
F1 Rolling, direct writes	0.0 [0.0, 0.0]	501.1 [425.2, 602.6]	–	3.1 [1.6, 4.9]
F2 Rolling, barrier	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.7 [0.0, 2.4]	12.5 [9.7, 15.0]
F3 Dual-tier, direct writes	37.5 [25.0, 50.0]	397.5 [358.8, 447.1]	–	2.9 [1.5, 4.9]
F4 Dual-tier, barrier	46.4 [35.7, 58.9]	0.0 [0.0, 0.0]	0.7 [0.0, 2.4]	9.5 [7.9, 11.7]

moved to a non-adjacent location. The per-code breakdown (Section S5) shows that direct writes fail through non-canonical entities (O1), non-adjacent moves (O3), overspending (O7) and a few NPC relocations (O5).

Desynchronisation rose from about 3% of live turns under direct writes to 12.5% (F2) and 9.5% (F4) with the barrier, because the NPC's words still describe rejected changes, but it was lower than in the Review-02 system (18.9% for F4v1, Section IX-E). Live recall with dual-tier memory (37.5% in F3, 21 of 56 probes, 46.4% in F4, 26 of 56) was well below teacher-forced recall. Live memories are written from model-generated summaries and depend on committed movement, and the run does not isolate which factor causes the drop. The simple effects (per session, Wilcoxon, not Holm-corrected, 14 sessions per cell) were: a memory effect on recall of $+37.5$ points under direct writes ($p = 0.0012$) and $+46.4$ under the barrier ($p = 0.0008$), and a control effect on violations of -628.7 (rolling, $p = 0.0010$) and -421.2 per 100 transitions (dual-tier, $p = 0.0010$). The barrier's effect on recall with dual-tier memory, $+8.9$ points, was not significant ($p = 0.16$).

TABLE S5
MIXED-EFFECTS LOGISTIC MODELS OF EQUATION (5) ON LIVE TURNS, FITTED BY VARIATIONAL BAYES. "SD" IS THE POSTERIOR STANDARD DEVIATION, AND p IS THE TWO-SIDED NORMAL TAIL OF $z = \text{MEAN}/\text{SD}$. RECALL IS MODELLED ON PROBE TURNS, VIOLATION ON ALL TURNS.

Outcome	Term	Mean	SD	z	p
Recall	intercept	-3.939	0.196	-20.14	3.4×10^{-90}
	β_M memory	3.377	0.203	16.66	2.4×10^{-62}
	β_C control	-0.895	0.277	-3.23	0.0012
	β_{MC} interaction	1.317	0.283	4.66	3.1×10^{-6}
Violation	intercept	2.019	0.091	22.09	3.6×10^{-108}
	β_M memory	-0.001	0.130	-0.01	0.99
	β_C control	-8.317	0.657	-12.66	9.4×10^{-37}
	β_{MC} interaction	-1.908	1.176	-1.62	0.105

Table S5 confirms that memory dominates recall and control dominates violations, as designed. Unlike the smaller earlier run, memory has no effect on violations ($\beta_M = -0.001$). As in every earlier run, the recall model also shows what H6 ruled out: a control effect on recall and a positive memory-by-control interaction. The two terms nearly cancel ($-0.89 + 1.32$): in the raw cells the barrier left recall at 0.0% under rolling memory and raised it by 8.9 points under dual-tier memory, which the session-level test does not find significant. With rolling recall at zero, the control term is identified only at that floor, so the interaction should be read cautiously.

D. Ablations

Table S6 shows that not every memory component earned its place on this benchmark: removing the buffer (A2) or the fallback (A4) did not lower recall. Scoping improved ranking (MRR@6 0.910 against 0.732 without it) but not significantly recall at $a \geq 20$ (83.0% against 81.2%). On the control side, removing the validator (A5) let committed violations through on probes (5.0 per 100 transitions) and in live play (3.9), and A6, which validates but applies accepted proposals by in-place writes, had no violation, unlike the Review-02 run, where unchecked NPC relocations corrupted its state.

TABLE S6

SINGLE-COMPONENT ABLATIONS. MEMORY ABLATIONS ARE TEACHER-FORCED ON HELD-OUT WORLDS. CONTROL ABLATIONS USE PROBES (ALL SEVEN WORLDS, F4 CONTEXT) AND LIVE SESSIONS. MRR@6 IS SCORED ON PROBES OLDER THAN THE BUFFER. LOCAL COMPUTE IS THE MEDIAN TURN TIME MINUS LLM AND DIALOGUE-REPAIR TIME IN THE BATCHED LIVE SESSIONS. RECOVERY IS THE MEDIAN AT TURN 160 OVER 42 REPLAY SESSIONS.

			Viol./100 transitions			
Ablation	Recall, $a \geq 20$ (%)	MRR@6	Probes	Live	Local P50 (ms)	Recovery (ms)
F4 full system	83.0 [79.4, 86.7]	0.910 [0.889, 0.931]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	25.0	1.4 (snapshot)
A1 no long-term memory	0.0 [0.0, 0.0]	–	as F4	as F4	–	–
A2 no short-term buffer	86.4 [83.0, 89.7]	0.888 [0.864, 0.913]	as F4	as F4	–	–
A3 no scoping	81.2 [77.6, 84.8]	0.732 [0.707, 0.759]	as F4	as F4	–	–
A4 no fallback	83.0 [79.5, 86.6]	0.954 [0.939, 0.969]	as F4	as F4	–	–
A5 no validation barrier	as F4	as F4	5.0 [2.3, 8.1]	3.9 [1.0, 7.1]	22.3	1.4 (snapshot)
A6 no event sourcing	as F4	as F4	–	0.0 [0.0, 0.0]	10.0	no log
A7 no snapshots	as F4	as F4	as F4	as F4	–	243.2 (replay)

Replay consistency: F4 and A5 100%. A6 not replayable. A7 100% (full fold).

E. Replay and recovery

Replay behaved as Proposition 1 predicts (Table S7 and Fig. S5): every event-sourced live session and every CPU replay session was reproduced exactly by full fold, by snapshot plus suffix and after a restart. Full replay time grew with log length, reaching a median of 243.2 ms at turn 160, while snapshot loading stayed between 1.1 and 1.4 ms. The corrected load path recovered every simulated crash, and the Review-02 path, which drops the suffix, none of the replay sessions' crashes, losing 8 turns on average. Over 300 randomised crash trials the corrected path was consistent in all 300, the Review-02 path in 77 (25.7%), losing 5.6 turns on average. The Review-02 path was always consistent when the crash came just after a snapshot write and was otherwise consistent only in the 25 trials where the crash lost no committed turn, such as a crash before the first snapshot.

TABLE S7

REPLAY AND RECOVERY ON 42 CPU SESSIONS OF 200 TURNS (6 PER WORLD, 367.2 EVENTS ON AVERAGE), COMMITTED THROUGH THE REAL EVENT STORE AND REDUCER, AND 300 RANDOMISED CRASH TRIALS.

Reconstruction	Consistent
Full fold of the event log	100%
Latest snapshot plus the events after it	100%
Both of the above in a fresh process from the SQLite file	100%
Corrected load path after a crash between commit and save	100% (0 turns lost)
Review-02 load path after the same crash	0% (8.0 turns lost)
300 crash trials, corrected load path	100%
300 crash trials, Review-02 load path	25.7% (5.6 turns lost)




Fig. S5. Median time to rebuild state at each snapshot point (log scale): full replay of the event log (A7) against snapshot loading (the system), over 42 sessions of 200 turns. The plot's title strip, which lists the consistency rates of Table S7, is cropped.

F. Latency and token cost

Local work was negligible against generation (per-stage values in Section S5): 15.1 ms at P50 and 19.2 ms at P95 for the live F4 graph run single-stream. Validation took 0.013 ms at P50 and 1.4 ms at P95, inside the 5 ms bound of H4, and the commit

TABLE S8
PER-WORLD AND PER-MODEL BREAKDOWN. BEST BASELINE FOR RECALL: HIGHEST OF B0 TO B5 ON THAT WORLD. FOR ATTACKS: THE BASELINE CONTEXT WITH THE LOWEST DIRECT-WRITE SUCCESS. THE OTHER MODELS RAN AT HORIZON 100 ON FOUR WORLDS WITH PROBES UNDER THE F4 CONTEXT ONLY, SO THEIR ATTACK COMPARISON IS THE CORRECTED BARRIER AGAINST DIRECT WRITES OF THE SAME OUTPUTS ("F4 OUTPUTS").

World	Model	Recall $a \geq 20$: F4	Recall: best baseline	Attack: F4 barrier	Attack: best baseline (direct)
W1	K2-7B	87.0 [79.6, 94.6]	B2: 88.9 [81.5, 96.3]	0.0 [0.0, 0.0]	B0: 14.3 [7.1, 22.9]
W2a	K2-7B	83.3 [75.0, 91.1]	B2: 81.5 [69.6, 93.2]	0.0 [0.0, 0.0]	B3: 4.3 [0.0, 10.0]
W2b	K2-7B	88.9 [81.5, 95.8]	B5: 85.2 [75.9, 94.0]	0.0 [0.0, 0.0]	B0: 2.9 [0.0, 7.1]
W2c	K2-7B	79.6 [71.0, 90.0]	B2: 83.3 [66.7, 95.8]	0.0 [0.0, 0.0]	B0: 2.9 [0.0, 7.1]
W3	K2-7B	79.6 [70.0, 88.7]	B2: 81.5 [65.0, 94.8]	0.0 [0.0, 0.0]	B2: 5.7 [1.4, 11.4]
W4-32	K2-7B	83.3 [75.9, 91.1]	B2: 88.9 [83.3, 95.5]	0.0 [0.0, 0.0]	B0: 0.0 [0.0, 0.0]
W4-128	K2-7B	83.3 [73.9, 91.7]	B5: 90.7 [83.9, 97.9]	0.0 [0.0, 0.0]	B0: 0.0 [0.0, 0.0]
W1	K2-3.7B	88.9 [83.3, 100.0]	B4: 94.4 [83.3, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 12.9 [5.7, 21.4]
W2a	K2-3.7B	83.3 [83.3, 83.3]	B2: 72.2 [50.0, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 11.4 [4.3, 18.6]
W3	K2-3.7B	72.2 [50.0, 83.3]	B2: 72.2 [66.7, 83.3]	0.0 [0.0, 0.0]	F4 outputs: 8.6 [2.9, 15.7]
W4-32	K2-3.7B	83.3 [66.7, 100.0]	B5: 88.9 [83.3, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 15.7 [7.1, 24.3]
W1	Qwen2.5-7B	100.0 [100.0, 100.0]	B2: 94.4 [83.3, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 55.7 [44.3, 67.1]
W2a	Qwen2.5-7B	94.4 [83.3, 100.0]	B2: 83.3 [66.7, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 48.6 [37.1, 60.0]
W3	Qwen2.5-7B	88.9 [83.3, 100.0]	B2: 94.4 [83.3, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 34.3 [22.9, 45.7]
W4-32	Qwen2.5-7B	94.4 [83.3, 100.0]	B2: 83.3 [66.7, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 37.1 [25.7, 48.6]
W1	Phi-4-mini	83.3 [66.7, 100.0]	B2: 77.8 [66.7, 83.3]	0.0 [0.0, 0.0]	F4 outputs: 27.1 [17.1, 37.1]
W2a	Phi-4-mini	72.2 [50.0, 100.0]	B2: 61.1 [50.0, 83.3]	0.0 [0.0, 0.0]	F4 outputs: 17.1 [8.6, 27.1]
W3	Phi-4-mini	77.8 [50.0, 100.0]	B5: 77.8 [66.7, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 27.1 [17.1, 37.1]
W4-32	Phi-4-mini	88.9 [83.3, 100.0]	B2: 77.8 [66.7, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 24.3 [14.3, 34.3]

node (SQLite append, reduction, indexing) dominated local time at 8.4 ms. The LLM call took 8,113 ms at P50 and 14,933 ms at P95 per live turn, and 6,593 ms and 8,120 ms per recall request. Dialogue repair adds a second LLM call on turns with a rejected proposal (6.9 and 5.3 s on the 2 of 24 single-stream turns that needed it), which is why end-to-end P95 reached 17.7 s. Under the batched live stage (98 concurrent sessions) the median LLM time per F4 turn was 54.5 s, a throughput setting rather than an interactive one. Per 100 turns F4 consumed 144,375 input and 14,859 output tokens, against 440,632 and 13,635 for full history (Section S5). Because the models were self-hosted, no monetary cost is reported.

G. Generalisation across worlds and models

The recall effect held on every world and every model (Table S8, plotted in Section S5). By family, F4 minus B1 recall at $a \geq 20$ was $+0.840$ (W2), $+0.796$ (W3) and $+0.833$ (W4). F4 did not beat the best baseline on every world: it was ahead on W2a and W2b, while B2 was ahead on W1, W2c, W3 and W4-32 and B5 on W4-128, all within overlapping intervals. Direct-minus-barrier attack success was $+0.048$ on W2 and $+0.071$ on W3 but exactly zero on W4, where no attack succeeded even under direct writes in the F4 context, so the H3 direction is not shown there. On the subset where all four models ran (W1, W2a, W3, W4-32 at horizon 100, 72 probes at $a \geq 20$ per condition), F4 kept recall between 80.6% and 94.4%, while B2 ranged from 70.8% to 88.9% and B3 from 55.6% to 66.7% (Section S5). The models of other families proposed far more unlawful changes: direct writes of their own outputs succeeded in 43.9% (Qwen2.5-7B) and 23.9% (Phi-4-mini) of attacks, against 7.5% (K2-Horizon-7B) and 12.1% (K2-Horizon-3.7B). The Review-02 barrier let through 8.6% and 6.1% of the Qwen and Phi attacks, and the corrected barrier let none through for any model.

H. Comparison with the base paper and reported results

Table S9 sets the system beside Generative Agents [4]. The two evaluations are not numerically comparable: they use different worlds, backbones, tasks and metrics, and the base paper's code was not rerun here. Three comparisons are nevertheless informative.

Memory is necessary in both. The base paper's closest controlled result is its memory ablation: removing observation, reflection and planning lowered the TrueSkill rating from 29.89 to 21.21, eight standard deviations. Removing long-term memory here (A1) lowered recall of facts 20 or more turns old from 83.0% to 0.0%. Both systems depend on long-term memory for anything beyond the immediate context.

The base paper's retrieval rule forgets under a budget. B4 ranks memories by the base paper's recency and relevance terms (without importance, which needs an LLM call per write). At the same budget its recall at $a \geq 20$ was 63.0%, against 83.0% for F4 ($p_{\text{Holm}} = 4.8 \times 10^{-10}$), and fell to 38% or less for facts 80 or more turns old, because recency decay pushes them out of the budget. Relevance alone (B2) was much stronger: scoping beat it on ranking (MRR@6 0.910 against 0.742) and on keeping the paraphrased distractor out of the prompt (46% against 1% of probes), but not on recall (83.0% against 84.3%, not significant). Unlike the base paper, the engine spends no LLM call on writing a memory.

TABLE S9
THE SYSTEM AGAINST THE BASE PAPER. BASE-PAPER VALUES ARE THOSE REPORTED BY PARK ET AL. [4]. VALUES FOR THIS WORK ARE FROM SECTIONS S4-B, S4-D TO S4-F, IX-A AND IX-C.

Aspect	Generative Agents (base paper)	This work
Setting	25 agents in one sandbox town, `gpt-3.5-turbo`	NPC dialogue in 7 worlds of 8 to 128 locations, four self-hosted models from three families
Memory	memory stream of observations, reflections and plans	8-turn buffer plus a FAISS store of turn summaries (384-d), packed into 1,600 characters
Retrieval	recency + importance + relevance, equal weights, min-max normalised	cosine relevance scoped to location and NPC, with relaxation fallback
LLM calls per memory write	one importance rating, reflection when summed importance exceeds 150	none: the summary is a field of the turn's own output
World-state control	natural-language actions mapped to the sandbox, no rule check described	typed, event-sourced state, symbolic barrier, pure reducer, dialogue repair
Evaluation	100 human evaluators rank interview answers (TrueSkill), two-day end-to-end simulation	automatic and paired: recall of planted facts, MRR, oracle-audited violations, false rejection, desynchronisation, replay, crash recovery, latency, tokens
Effect of memory	full architecture $\mu = 29.89$ against 21.21 without memory, $d = 8.16$	recall at $a \geq 20$ 83.0% against 0.0% without long-term memory (A1)
Memory errors	embellishment, 1.3% (6 of 453) of relationship answers hallucinated	2.0% of recall probes answered with the distractor's value
Rule violations	not measured	no committed state violation through the barrier, against 6.4% attack success by direct writes
State replay	not measured	100% of event-sourced sessions reproduced, 300 of 300 crashes recovered
Cost	"thousands of dollars in token credits" for two simulated days	144,375 input and 14,859 output tokens per 100 turns, validation 1.4 ms at P95

State control has no counterpart in the base paper. Generative Agents report embellishment at the level of dialogue and do not measure rule violations. In the engine no probe or live output committed a state violation through the corrected barrier, for any of four models (Tables IV and S8), and the event log reproduced the live state exactly. The closest reported measurement is NCP-Bench [5], where the best model kept its narrative commitments in only 42% of runs after 20 turns when checked afterwards by LLM auditors. Here the specification is enforced before commit, which protects the state, but the dialogue still contradicted rejected changes on 9.5% of live F4 turns by the cue proxy: the barrier protects the state, not the narration, and dialogue repair did not close that gap on the turns it rewrote.

I. Error analysis

Automatic coding locates the failures (counts per condition in Section S5). None of F4's recall failures came from retrieval: in all 84 "hit but ignored" cases the gold turn was in the prompt and the model answered wrongly, and 13 answers used the distractor's value. Rolling contexts failed by forgetting (335 misses for B1), generic RAG by ignoring or confusing retrieved chunks (146 and 61), the scored memory stream B4 partly by forgetting (65 misses), and the ablation without long-term memory by both (388 misses, 109 confusions). The desynchronisation proxy flagged 52 F4 turns against 103 for F4v1, 68 for F2 and 56 for A6, the conditions that can reject proposals. In conditions that never reject, only the arrival cue can fire: 17 turns for F1, 16 for F3 and 28 for A5.

S5. ADDITIONAL TABLES AND FIGURES

This section holds the tables and figures that the manuscript states in text or that duplicate another table or figure.
Table S10 gives recall by fact age for every condition, the values plotted in Fig. 2.

TABLE S10
RECALL (%) BY FACT AGE ON HELD-OUT WORLDS. AGES 80 AND 160 OCCUR ONLY IN 100- AND 200-TURN SESSIONS.

Condition	5	10	20	40	80	160
B0 Full history	83.3 [75.0, 90.7]	76.9 [69.4, 84.3]	77.8 [69.4, 86.1]	75.9 [67.6, 84.3]	81.9 [72.2, 90.3]	75.0 [63.9, 86.1]
B1 Rolling, B	80.6 [73.1, 88.0]	59.3 [49.1, 69.4]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
B1 Rolling, $2B$	75.9 [68.5, 83.3]	78.7 [71.3, 85.2]	59.3 [48.1, 70.4]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
B2 Vector memory	85.2 [78.7, 90.7]	88.9 [82.4, 94.4]	85.2 [78.7, 91.7]	83.3 [75.0, 90.7]	80.6 [70.8, 90.3]	91.7 [83.3, 100.0]
B3 Generic RAG	68.5 [60.2, 76.9]	66.7 [57.4, 75.0]	62.0 [52.8, 71.3]	62.0 [52.8, 71.3]	61.1 [50.0, 72.2]	61.1 [47.2, 75.0]
B4 Memory stream (GA)	85.2 [78.7, 90.7]	90.7 [84.3, 96.3]	85.2 [78.7, 91.7]	71.3 [63.9, 78.7]	37.5 [26.4, 48.6]	22.2 [8.3, 36.1]
B5 Forgetting curve	87.0 [81.5, 92.6]	90.7 [84.3, 96.3]	85.2 [78.7, 90.7]	81.5 [75.0, 88.0]	72.2 [61.1, 81.9]	75.0 [58.3, 88.9]
F4v1 Review-02 system	96.3 [92.6, 99.1]	87.0 [80.6, 92.6]	86.1 [79.6, 92.6]	90.7 [85.2, 95.4]	86.1 [79.2, 93.1]	94.4 [86.1, 100.0]
F4 Proposed	78.7 [71.3, 85.2]	85.2 [77.8, 91.7]	83.3 [76.9, 89.8]	81.5 [74.1, 88.0]	80.6 [70.8, 88.9]	91.7 [83.3, 100.0]
A1 No long-term memory	82.4 [75.0, 88.9]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
A2 No short-term buffer	85.2 [79.6, 90.7]	88.9 [83.3, 94.4]	88.0 [82.4, 93.5]	85.2 [77.8, 91.7]	84.7 [76.4, 93.1]	88.9 [77.8, 97.2]
A3 No scoping	63.9 [55.6, 72.2]	85.2 [78.7, 90.7]	85.2 [77.8, 91.7]	76.9 [69.4, 84.3]	79.2 [69.4, 87.5]	86.1 [75.0, 94.4]
A4 No fallback	83.3 [76.9, 89.8]	83.3 [75.9, 89.8]	83.3 [76.9, 89.8]	80.6 [73.1, 87.0]	81.9 [72.2, 90.3]	91.7 [83.3, 100.0]
n (F4 probes)	108	108	108	108	72	36

Table S11 lists retrieval quality and secondary memory metrics for every memory condition.

TABLE S11
RETRIEVAL QUALITY AND SECONDARY MEMORY METRICS (HELD-OUT WORLDS). RECALL@6 IS SCORED ON THE 432 PROBES OLDER THAN THE BUFFER. THE OTHER COLUMNS ON ALL 540. "CONFUSED": ANSWERED WITH THE DISTRACTOR'S VALUE. NO PROMPT REACHED THE 16,384-CHARACTER CAP.

Condition	Gold in prompt	Distractor in prompt	Confused	Recall@6	Parse success	In / out tok. per 100 turns
F4	100.0 [100.0, 100.0]	54.1 [50.2, 58.2]	2.0 [0.9, 3.3]	100.0 [100.0, 100.0]	96.1 [94.3, 97.8]	144,375 / 14,859
F4v1	100.0 [100.0, 100.0]	57.0 [52.9, 61.4]	0.9 [0.2, 1.7]	100.0 [100.0, 100.0]	98.1 [96.6, 99.3]	139,898 / 15,292
B0	100.0 [100.0, 100.0]	100.0 [100.0, 100.0]	4.4 [2.8, 6.2]	–	98.5 [97.5, 99.4]	440,632 / 13,635
B1, B	34.1 [31.0, 37.2]	58.7 [54.9, 62.6]	13.9 [10.7, 17.1]	–	99.6 [99.1, 100.0]	147,781 / 14,174
B1, $2B$	54.6 [50.9, 58.5]	73.9 [70.5, 77.5]	12.8 [10.4, 15.1]	–	98.7 [97.7, 99.5]	187,677 / 13,356
B2	100.0 [100.0, 100.0]	99.1 [98.0, 99.8]	0.2 [0.0, 0.6]	100.0 [100.0, 100.0]	98.3 [97.3, 99.3]	145,076 / 15,096
B3	99.8 [99.4, 100.0]	94.8 [92.5, 96.8]	9.8 [7.7, 12.0]	99.8 [99.3, 100.0]	98.3 [97.3, 99.3]	150,616 / 14,984
B4	85.7 [83.6, 87.9]	90.9 [88.6, 93.2]	2.0 [0.9, 3.3]	82.2 [79.6, 84.8]	97.6 [96.2, 98.9]	144,945 / 15,261
B5	96.3 [94.6, 97.9]	91.1 [88.5, 93.7]	0.4 [0.0, 0.9]	95.4 [93.3, 97.4]	98.0 [96.9, 98.9]	145,025 / 15,261
A1	20.0 [19.1, 20.9]	52.6 [48.9, 56.4]	15.9 [12.6, 19.4]	–	98.1 [96.8, 99.3]	140,363 / 14,611
A2	100.0 [100.0, 100.0]	10.2 [7.7, 13.0]	0.0 [0.0, 0.0]	100.0 [100.0, 100.0]	99.3 [98.5, 99.8]	118,086 / 14,273
A3	98.9 [98.0, 99.6]	90.7 [88.7, 92.8]	1.7 [0.7, 2.8]	98.6 [97.5, 99.5]	98.5 [97.5, 99.4]	144,420 / 14,801
A4	100.0 [100.0, 100.0]	49.6 [46.4, 53.1]	1.7 [0.7, 2.9]	100.0 [100.0, 100.0]	95.9 [94.1, 97.6]	144,119 / 14,945

Fig. S6 plots the retrieval metrics and the gold-in-prompt rate by fact age.




Fig. S6. Left: MRR@6 and Recall@6 of the gold memory for each retrieval condition, on the 432 held-out probes older than the buffer. Right: share of probes whose gold turn reached the prompt, by fact age, which bounds recall from above.

Table S12 lists the sensitivity sweeps plotted in Fig. S4.

TABLE S12
SENSITIVITY SWEEPS (RETRIEVAL ONLY, W1 AND W2A TO W2C, HORIZONS 100 AND 200, 880 PROBES PER SETTING).

	buffer 4	buffer 8	buffer 16	$k = 3$	$k = 12$	$\theta = 0$	$\theta = 6$
Gold in prompt	0.9989	0.9989	0.9989	0.9648	1.0000	1.0000	0.9955
MRR@k	0.8990	0.8990	0.8990	0.8390	0.9124	0.9227	0.8303

Fig. S7 plots the budget sweep and the trade-off between recall, tokens and latency.




Fig. S7. Left: share of probes whose gold turn reaches the prompt as each condition's budget is scaled from 0.25 to 4 times 1,600 characters (CPU sweep on W1 and W2). Right: recall at fact age 20 or more against mean input tokens, with marker size proportional to P50 single-stream latency, which is between 5.9 and 6.9 s for every condition except B0.

Fig. S8 breaks the live violations of Table S4 down by invariant.




Fig. S8. Oracle-flagged live turns per 100 turns by condition and invariant code (codes that never fired are omitted by the plot). Direct writes (F1 and F3) fail on O1, O3 and O7, with a few O5. The corrected-barrier conditions F2 and F4, and A6, have none. A5 has 0.5 O3 and 0.2 O7, and F4v1 0.2 O5 and 0.5 O8 per 100 turns.

Fig. S9 plots the main rows of Table V.




Fig. S9. Before (Review-02 system, grey) and after (corrected system, blue) on the same scenarios: attack success and currency validator gap under the two validators, inconsistent crash recoveries under the two load paths, judged contradictions of draft and repaired probe replies, and the live desynchronisation proxy of F4v1 and F4.

Fig. S10 plots the seed variance of Table S3 and the recall of all four models on their common subset.




Fig. S10. Left: recall over all ages for three sampling seeds on the calibration sessions. Right: recall at fact age 20 or more on the common subset (W1, W2a, W3, W4-32 at horizon 100, 72 probes per bar) for K2-Horizon-7B, K2-Horizon-3.7B, Qwen2.5-7B and Phi-4-mini. F4 stays between 81% and 94% across models and above every baseline for each model.

Fig. S11 plots the attack success and validator errors of Table IV.




Fig. S11. Left: attack success by category when the same model outputs are committed by direct writes, by the reducer without validation (A5), through the Review-02 barrier and through the corrected barrier. Right: the corrected barrier's false rejection of lawful twins (one trust and three currency twin proposals, each naming an NPC by display name, the trust bar is 1 of 14 proposals) and its validator gap (zero in every category), against the 5% bound of H4.

Fig. S12 plots the 2×2 cells of Table S4.




Fig. S12. Interaction plots for the 2×2 design. Left: live recall rises with memory under either control setting. With dual-tier memory it is 8.9 points higher with the barrier, which the session-level test does not find significant. Right: violations per 100 transitions fall to zero with the barrier under either memory setting. The mixed model (Table S5) finds a recall interaction.

Table S13 gives the per-stage latency of the live F4 graph.

TABLE S13
PER-STAGE LATENCY (MS) OF THE LIVE F4 GRAPH, SINGLE STREAM (24 UNCACHED TURNS, TWO WORLDS). REPAIR IS THE DIALOGUE-REPAIR LLM CALL, NEEDED ON 2 OF THE 24 TURNS. LOCAL TOTAL EXCLUDES THE LLM AND REPAIR CALLS (METRICS/TABLE6_STAGE_LATENCY.CSV).

	Input	Retrieval	Prompt	LLM	Parse	Validate	Repair	Commit	Output	Local total	End to end
P50	0.002	0.153	0.130	8,113	0.087	0.013	0.002	8.427	0.010	15.101	8,127
P95	0.002	0.241	0.167	14,933	0.125	1.397	4,491	12.980	0.012	19.210	17,673
P99	0.003	0.266	0.246	15,465	0.138	1.520	6,516	13.388	0.013	20.393	21,469

Fig. S13 plots the stage latencies of Table S13 and the single-stream LLM time per condition.




Fig. S13. Left: P50 (bars) and P95 (ticks) latency of each F4 stage, single stream, log scale, including the dialogue-repair stage (Table S13). Right: single-stream LLM time per request for each condition's recall prompts (12 requests per condition).

Fig. S14 plots the per-world effects of Table S8.




Fig. S14. Per-world effects with 95% bootstrap intervals. Left: recall gain of F4 over B1 at fact age 20 or more, positive on every world. Right: reduction in attack success from direct writes to the barrier (F4 context). Positive on W1, W2a to W2c and W3 and zero on W4-32 and W4-128, where no attack succeeded under direct writes. W1 (grey) is in-distribution.

Table S14 gives the automatically coded failures of Section S4-I.

TABLE S14
AUTOMATICALLY CODED FAILURES: RECALL CATEGORIES ON ALL WORLDS (MISS: GOLD NOT IN THE PROMPT, IGNORED: GOLD IN THE PROMPT, ANSWER WRONG, CONFUSED: ANSWERED WITH THE DISTRACTOR'S VALUE) AND LIVE DESYNCHRONISATION BY THE PROXY. UP TO 50 EXAMPLES PER CATEGORY AND CONDITION ARE EXPORTED TO ANNOTATION/ERROR_SAMPLES.CSV.

	F4	F4v1	B0	B1	B1×2	B2	B3	B4	B5	A1	A3	F2
Miss	0	0	0	335	220	0	1	65	17	388	6	–
Ignored	84	53	108	26	51	80	146	68	72	19	109	–
Confused	13	6	32	85	83	2	61	11	5	109	10	–
Schema failure	16	5	8	2	6	6	12	17	10	10	6	–
Desync (live)	52	103	–	–	–	–	–	–	–	–	–	68

S6. SAMPLE-SIZE LADDER

Table S15 lists the eight pre-declared sample-size levels of Section S3-B.

TABLE S15
PRE-DECLARED SAMPLE-SIZE LEVELS AND THE PLANNER'S ESTIMATED HOURS FOR THE REPORTED RUN (METRICS/BUDGET_PLAN.CSV). LEVEL 2 WAS RUN. ITS FOUR LLM STAGES TOOK 5.49 H AGAINST 6.76 H ESTIMATED.

Level	Sessions/(world, H)	Probes/(world, cat.)	Live/world	Recall (h)	Probes (h)	Live (h)	Seed var. (h)	Total (h)
0	1	4	1	0.90	0.60	0.89	0.54	2.94
1	2	6	1	1.86	0.94	0.89	0.54	4.24
2	**3**	**10**	**2**	**2.82**	**1.62**	**1.77**	**0.54**	**6.76**
3	4	14	2	3.78	2.30	1.77	0.54	8.40
4	6	20	3	5.71	3.32	2.66	0.54	12.23
5	10	30	4	9.55	5.01	3.54	0.54	18.65
6	20	45	6	19.15	7.55	4.43	0.54	31.68
7	40	60	10	38.37	10.10	7.09	0.54	56.10

REFERENCES

[1] J. Urbanek, A. Fan, S. Karamcheti, S. Jain, S. Humeau, E. Dinan, T. Rocktäschel, D. Kiela, A. Szlam, and J. Weston, "Learning to speak and act in a fantasy text adventure game," in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019, pp. 673–683. [Online]. Available: https://doi.org/10.18653/v1/D19-1062

[2] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023, pp. 79–90. [Online]. Available: https://doi.org/10.1145/3605764.3623985

[3] W. Kwon, Z. Li, S. Zhuang, Y. Sheng, L. Zheng, C. H. Yu, J. E. Gonzalez, H. Zhang, and I. Stoica, "Efficient memory management for large language model serving with PagedAttention," in *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP)*, 2023, pp. 611–626. [Online]. Available: https://doi.org/10.1145/3600006.3613165

[4] J. S. Park, J. C. O'Brien, C. J. Cai, M. R. Morris, P. Liang, and M. S. Bernstein, "Generative agents: Interactive simulacra of human behavior," in *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*, 2023, pp. 1–22. [Online]. Available: https://doi.org/10.1145/3586183.3606763

[5] Y. Ma, J. Yan, B. Shi, K. H. Kam, R. Wang, X. Liu, Y. Chen, Y. Zhang, and D. F. Wong, "Can LLM agents stick to the script? A benchmark for long-horizon consistency in interactive narratives," in *Proceedings of the 43rd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 306, 2026, pp. 85 171–85 192. [Online]. Available: https://proceedings.mlr.press/v306/ma26ap.html