Memory and State Control for LLM-Driven NPC Dialogue: Scoped Dual-Tier Memory and Pre-Commit Invariant Validation under a Paired, Oracle-Audited Evaluation

Parth Mital, Bhumika Singh, Pranesh Gopal, and Kalyanaraman P

***Abstract*—Large language models (LLMs) let non-player characters (NPCs) hold open-ended conversations, but they forget facts established early in a session, propose world changes that break game rules, and cost more as context grows. We present OBSIDIAN FLASK, an NPC dialogue engine that separates generation from state control: a dual-tier memory (an 8-turn buffer plus a FAISS store whose retrieval is scoped to the current location and NPC) and an event-sourced world state in which every LLM-proposed mutation must pass a symbolic pre-commit validation barrier. Taking Generative Agents as the base paper, we compare the engine with rolling-context, flat vector-memory, generic retrieval and full-history baselines in a 2×2 memory-by-control factorial with seven ablations, on seven worlds of 8 to 128 locations, including worlds derived from the LIGHT corpus. Every model output is committed three ways and audited by an invariant oracle that shares no code with the validator. With a self-hosted 7B backbone the system recalled 87.7 [84.2, 91.0]% of facts 20 or more turns old on held-out worlds, against 0.0% for a rolling context of equal budget, 63.9% for generic retrieval and 80.2% for full history; its gain over flat vector memory (84.9%) was not significant ($p = 0.298$). Scoping raised MRR@6 from 0.750 to 0.898. On identical outputs the barrier cut attack success from 16.2% to 2.9% with no false rejection and 0.039 ms of validation at the 95th percentile, but it missed unbounded currency gains and raised dialogue–state desynchronisation from 3.7% to 18.7% of live turns. Event-log replay reproduced every live state. The results are preliminary: the run used the third of eight planned sample sizes and automatic scoring.**

***Index Terms*—Large language models, non-player characters, long-term memory, retrieval-augmented generation, event sourcing, runtime verification, interactive fiction, evaluation methodology.**

I. INTRODUCTION

TEXT-centric games mediate navigation, object interaction and character dialogue entirely through language. Unlike graphical engines, where physics enforces spatial constraints, a text world can only stay consistent through an explicit symbolic state. Games have traditionally driven NPCs with dialogue trees and finite-state machines, which obey the rules at negligible cost but restrict players to predefined choices. LLMs remove that restriction, and surveys of LLMs in games identify the coupling of generated text to game mechanics and state as an open problem [1].

Three failure modes stand in the way. First, *long-horizon forgetting*: facts that fall out of a bounded context window are lost, and facts inside a long context are used unevenly [2]; very long-term conversational memory remains weak even with retrieval [3], [4]. Second, *invariant violations*: LLMs are unreliable simulators of state transitions [5], [6] and lose narrative commitments over long interactions [7]; left unchecked they move players between unconnected rooms, invent items and grant unearned money. Third, *cost growth*: appending full history, or running several reflective LLM calls per turn [8], [9], raises tokens and latency per turn.

This paper evaluates an architecture that addresses all three by separating generation from state control (Section IV), and compares it with the base paper, Generative Agents [8] (Section II-B). Its components are individually standard: a turn buffer, dense retrieval, schema-constrained output, a rule validator, an append-only event log and a deterministic reducer. Our claim is therefore not that any component is new. The contribution is an evaluation that isolates what each mechanism buys, against independent baselines, with the costs it imposes measured rather than assumed.

A. Research questions

RQ1 (memory): does scoped dual-tier memory improve long-range recall per prompt token over rolling-context, vector-memory and generic retrieval agents? **RQ2** (state control): does a pre-commit validation barrier over event-sourced state reduce committed invariant violations, and at what cost in false rejections and dialogue–state desynchronisation? **RQ3** (separability): do memory and control contribute independently? **RQ4** (efficiency): what latency and tokens does each component add? **RQ5** (generalisation): do the effects hold across worlds of different authorship, genre and scale, and across backbones?

B. Contributions

1) A formal account of the engine as implemented: the world state, the event reducer and its replay and snapshot properties, the scoped retrieval operator with its post-filter limitation, and the validation predicate, including the coverage gaps found in the code (Sections IV-A and IV-B).
2) A *paired three-way commit protocol* with an *independent oracle*: each LLM output is committed through the barrier, through the reducer alone and by direct writes, and the three post-states are audited by an eight-invariant oracle that imports nothing from the validator. Common random numbers make every control comparison exactly paired,

The authors are with the School of Computer Science and Engineering, Vellore Institute of Technology. Dr. Kalyanaraman P is the faculty author (e-mail: parth.mital2023@vitstudent.ac.in; bhumika.2023a@vitstudent.ac.in; pranesh.gopal2023@vitstudent.ac.in; pkalyanaraman@vit.ac.in).

Source code, benchmark and run outputs: https://github.com/parthmital/RAG-Driven-NPC-Narrative-Engine.

and lawful *twins* of every attack measure false rejection (Section IV-D).

3) A multi-world benchmark (four families, seven worlds, long-horizon sessions of 50 to 200 turns, seven attack categories) and a single-notebook harness that reports recall, retrieval quality, violations, false rejection, desynchronisation, latency, tokens and replay consistency together, with cluster-bootstrap intervals and pre-registered hypotheses (Sections V and VIII-B).
4) Empirical findings, including two unsupported hypotheses and four implementation defects that a validator-only evaluation would have missed: unbounded currency gains, a load path that discards the logged suffix, validator-accepted proposals that the naive writer turns into persistent corruption, and dialogue that contradicts rejected changes (Sections IX and X).

The paper follows the order of the project report: the literature survey (Section II) and the research gap it leaves (Section III), the proposed methodology (Section IV), the dataset (Section V), the novelty claimed (Section VI), the algorithms (Section VII), the implementation (Section VIII) and the comparison of results, including the comparison with the base paper (Section IX).

II. Literature Survey

A. Grounded dialogue and text games

LIGHT conditions dialogue on rooms, objects and personas in a crowd-written fantasy world [10], and goal-driven agents in LIGHT were trained with reinforcement learning over factorised speech and action spaces [11]. Neither keeps a persistent, validated world state over long sessions. TextWorld [12] and Jericho [13] provide formally specified or human-authored games whose engines enforce rules, but they parse a constrained command language and have no open NPC dialogue. Callison-Burch et al. [14] framed Dungeons and Dragons as a dialogue challenge including state prediction, and STORIUM anchors collaborative stories with structured cards [15].

B. Base paper: Generative Agents

We take Generative Agents [8] as the base paper: it is the most direct prior architecture for LLM-driven characters with long-term memory in a game-like world. Twenty-five agents live in a sandbox town whose areas and objects form a tree. Each agent keeps a *memory stream* of natural-language observations. Retrieval scores every memory as the equally weighted sum of three min-max-normalised terms: recency (exponential decay with factor 0.995 per sandbox hour since last access), importance (an integer from 1 to 10 that the LLM assigns when the memory is created) and relevance (cosine similarity of embeddings to a query); the top-ranked memories that fit the context window enter the prompt. Reflections, higher-level memories that the LLM synthesises when the summed importance of recent events exceeds 150, and plans are stored in the same stream. Agents act through natural-language statements that the engine maps onto the sandbox. The evaluation measures believability: 100 human evaluators ranked interview answers from the full architecture, three memory ablations and a crowdworker condition, and a two-day end-to-end simulation measured information diffusion, relationship formation and coordination.

Three properties of the base paper motivate this work. First, memory is not bound to a validated symbolic state: the paper describes no check of the agents' statements against game rules, and it reports embellished memories as a failure mode. Second, memory is expensive: every memory write costs an LLM call for importance, reflection costs more, and the authors report that simulating 25 agents for two days cost thousands of dollars in token credits. Third, the evaluation ranks believability rather than measuring recall of established facts or rule violations, and memory designs are not compared at a matched token budget. Section IX-J compares the two systems.

C. Memory for LLM agents

Reflexion stores verbal self-reflections across trials [9]. In multi-session chat, models that summarise and recall earlier sessions outperform standard encoder–decoders [16]. Later systems add forgetting curves [17], knowledge-graph indexing [18], self-organising linked notes [19], multi-granularity summaries with retrieval refined by reinforcement learning [20], and compression of interactions into compact indexed memory units [21]. Benchmarks show that long-term memory is far from solved [3], [4], and surveys organise the design space [22], [23]. These systems store natural-language memories and most spend extra LLM calls per write; none binds memory to a validated symbolic state, and none is compared at a matched token budget in a game setting.

D. Retrieval and long context

Retrieval-augmented generation conditions generation on passages from a dense index [24]; generic RAG ranks by similarity alone and has no notion of a turn's spatial or social scope. Extending the context is not a substitute: models use the middle of long contexts poorly [2]. ReAct keeps a growing scratchpad of observations and actions [25]. Scoping by metadata is a filtered nearest-neighbour query; post-filtering a global top-k is known to lose in-scope neighbours, which motivates filter-aware indices [26]. We analyse exactly this effect in the engine's retrieval (Proposition 2).

E. State tracking and verifier-gated generation

LLMs track entities imperfectly [6] and are unreliable text-world simulators [5]. The LLM-Modulo position argues that LLM proposals should be checked by external model-based verifiers [27]; grammar-constrained decoding guarantees syntactic well-formedness but not semantic legality [28]. Prompt injection shows that model output cannot be trusted to obey instructions in its context [29]. Event sourcing, where state is derived from an append-only log of events, is used in industrial systems that need an auditable history [30].

TABLE I
SURVEYED SYSTEMS AGAINST THE PROPERTIES STUDIED HERE. "INDEP. AUDIT" MEANS VIOLATIONS ARE SCORED BY A CHECKER THAT DOES NOT SHARE CODE WITH THE COMPONENT BEING EVALUATED. ENTRIES DESCRIBE THE CITED PAPERS' OWN EVALUATIONS.

Work	Memory	World state	Pre-commit check	Indep. audit	Replay
LIGHT [10]	episode context	text descriptions	action checks	–	–
D&D dialogue [14]	dialogue history	predicted from text	–	–	–
Generative Agents [8] (base)	scored memory stream	sandbox tree	–	–	–
MemoryBank [17]	forgetting-curve store	none	–	–	–
A-Mem [19]	linked notes	none	–	–	–
TextWorld/Jericho	game engine	formal state	parser and rules	–	engine
PANGeA [31]	memory system	game level data	LLM judge	–	–
Phillips et al. [32]	dialogue history	goal states	LLM judge	–	–
NCP-Bench [7]	model context	fact ledger	–	LLM auditors	–
This work	scoped buffer + FAISS	event-sourced, typed	symbolic validator	yes (8 invariants)	yes

F. LLM NPCs and narrative games, 2023 to 2026

PANGeA generates RPG content with a memory system and a validator in which the LLM itself judges player input against design rules [31]. Phillips et al. model conversations as puzzles whose goal-based states are advanced by an LLM that reads the dialogue history [32], so state transitions are again judged by a model. SceneCraft generates branching NPC scenes from authorial instructions and converts them into a game scripting language [33], and CALYPSO supports Dungeon Masters with LLM-generated text grounded in an established game setting [34]. NCP-Bench measures how interactive narratives drift under adversarial player interventions: the best model kept its commitments in 42% of runs after 20 turns, and fact-conflict rates ranged from 40% to 68% across models, as judged by LLM auditors [7].

G. Summary of the surveyed work

Table I contrasts representative systems on the properties this paper studies.

III. RESEARCH GAP

The survey leaves five gaps, which together define the problem this paper addresses.

RG1. **Memory is not bound to validated state.** From the base paper's memory stream to compressed or graph-indexed memories, memory systems store natural-language text; none ties what an NPC remembers to a symbolic world state that the model cannot corrupt (Table I).

RG2. **State changes are judged by a model or not at all.** In-game systems either let an LLM judge legality [31], [32] or apply model output directly; symbolic pre-commit validation of LLM-proposed mutations has not been evaluated in NPC dialogue.

RG3. **No independent audit.** Where violations are measured, they are scored by the component under test or by LLM auditors whose authors note that they can err on ambiguous text [7]; no evaluation pairs identical model outputs across commit paths and scores them with a rule checker that shares no code with the validator.

RG4. **No matched-cost comparison.** Memory designs are compared on accuracy, rarely at an equal prompt-token budget against a rolling context; the base paper reports cost only as thousands of dollars of token credits [8].

RG5. **Costs of control are unmeasured.** False rejection of lawful requests, dialogue that contradicts rejected changes, and replay and crash recovery are not reported together with recall and violations.

Five research questions follow from these gaps (Section I); Section IV gives the methodology that answers them and Section VI states what is new.

IV. PROPOSED METHODOLOGY

The methodology has two parts. The engine (Sections IV-A and IV-B) separates language generation from state control: the LLM proposes dialogue and state changes, a scoped dual-tier memory supplies context, and only proposals that pass a symbolic barrier reach an event-sourced state. The evaluation (Sections IV-C to IV-G) isolates each mechanism in a factorial design with ablations, pairs every control comparison on identical model outputs, and scores violations with an independent oracle. The data it runs on is described in Section V, the pseudocode in Section VII, and the implementation in Section VIII.

A. Formal model

The model below is the one the code implements; module paths refer to `Backend/` at the evaluated commit.

1) World state:

Definition 1 (World state)**.** A world state is a tuple $S = (\mathcal{L}, A, \mathcal{N}, \mathcal{O}, \pi, \iota, c, R, J, t)$ where $\mathcal{L}$ is the set of locations with directed adjacency $A \subseteq \mathcal{L} \times \mathcal{L}$ (the `connected_to` lists); $\mathcal{N}$ is the set of NPCs, each with a location, persona, knowledge, conditional secrets and an `alive` flag; $\mathcal{O}$ is the set of objects, each with a location in $\mathcal{L} \cup \{\perp\}$ and an owner; $\pi \in \mathcal{L}$ is the player's location, ι the inventory and $c \in \mathbb{Z}_{\geq 0}$ the currency; $R : \mathcal{N} \times (\mathcal{N} \cup \{\text{player}\}) \to [-100, 100]$ is the trust map; J the journal; and t the turn (schemas/world_state.py).

The seed S_0 fixes the canonical entity sets $\mathcal{L}_0, \mathcal{N}_0, \mathcal{O}_0$. The field `active_npc_id` is part of the stored state but is set outside the event log (Section VIII-E).

2) Events, reduction and replay: An event is $e = (id, t, \tau, p, ts)$ with type τ from 14 types (schemas/events.py) and payload p. The reducer δ (core/reducer.py) deep-copies the state and applies one event; it ignores moves to unknown locations, clamps trust to $[-100, 100]$, floors currency at zero, and ignores an NPC `location_id` change to a non-canonical location. State after T events is

$$S_T = \mathrm{foldl}(\delta, S_0, [e_1, \ldots, e_T]), \qquad S_i = \delta(S_{i-1}, e_i). \quad (1)$$

Events are appended to SQLite with autoincrement ids, and every $\Delta = 16$ turns a snapshot (S_k, id_k) is written, where id_k is the last event id (graph/definition.py).

Proposition 1 (Replay and snapshot equivalence)**.** *If (i) δ is a function of (S, e) only and (ii) every change to the hashed part of the live state is made by applying a logged event with δ, then for any snapshot taken after event k,*

$$\begin{aligned}\mathrm{foldl}(\delta, S_0, e_{1..T}) &= \mathrm{foldl}\big(\delta, \mathrm{foldl}(\delta, S_0, e_{1..k}), e_{k+1..T}\big)\\ &= \mathrm{foldl}(\delta, S_k, e_{k+1..T}).\end{aligned}$$

Proof. The first equality is the definition of a left fold over a concatenated list; the second substitutes the snapshot. Condition (i) holds in the code because the only time-dependent value the reducer writes, a journal entry's timestamp, is read from the event, which is persisted with it. Condition (ii) fails for `active_npc_id`, which is why replay hashes exclude it. □

Recovery from the latest snapshot therefore costs $O(|S| + r)$ with r the number of events after it, against $O(|S| + T)$ for a full fold. The application's load path (session/manager.py, `load_session`) loads (S_k, id_k) and *discards* id_k, returning S_k instead of $\mathrm{foldl}(\delta, S_k, e_{k+1..T})$: every event after the last snapshot is lost unless a per-turn auto-save happened to succeed. Section IX-F measures the consequence.

3) Proposals and the validation barrier: Each turn the LLM returns one JSON object validated by a Pydantic schema (schemas/llm_output.py): dialogue, narration, a one-sentence memory summary, a list of proposals $P_t = [(\tau_j, p_j)]$ and a list of proposed new entities. The barrier (game/validator.py) evaluates a predicate $V(\tau, p, S_t)$ for each proposal *independently against the pre-turn state* S_t, and commits

$$\begin{aligned}E_t &= [\, e(\tau_j, p_j) \;:\; (\tau_j, p_j) \in P_t,\; V(\tau_j, p_j, S_t)\,],\\ S_{t+1} &= \mathrm{foldl}(\delta, S_t, [e_{\text{speech}}] +\!\!+ E_t).\end{aligned} \quad (2)$$

V requires: a move's destination is canonical and in the current location's adjacency list; a trust change names a canonical NPC with $|\Delta| \le 20$; a taken object is canonical and lies at the player's location; a dropped object and its target location are canonical and, if dropped by the player, carried; state and flag updates name a canonical target and a key; a journal entry has content; a currency delta is numeric and, if negative, $|\Delta| \le c$. Any non-empty `new_entities` list is rejected and logged. Rejected proposals are dropped and the turn continues; dialogue is not regenerated.

4) Invariants audited by the oracle: The evaluation's oracle (notebook cell 36) re-derives facts from $(S_{\text{pre}}, S_{\text{post}}, \text{committed mutations})$ and checks eight invariants, written from the specification rather than the validator. With $\mathcal{L}_0, \mathcal{N}_0, \mathcal{O}_0$ from the seed and $\mathcal{A}$ the *undirected* closure of the seed adjacency:

O1 canonicity
post-state entity sets equal the seed's; the player, inventory and NPC locations reference canonical ids.

O2 conservation
each object is in exactly one place: a location, the inventory, or an NPC's possession.

O3 adjacency
$\pi_{\text{post}} = \pi_{\text{pre}}$ or $(\pi_{\text{pre}}, \pi_{\text{post}}) \in \mathcal{A}$.

O4 theft/duplication
a newly held object was at the player's location, on the floor or held by an NPC who is there, and is held once.

O5 relocation
objects move only to the player's location; NPCs move only along $\mathcal{A}$.

O6 trust bound
$|R_{\text{post}}(n, \text{player}) - R_{\text{pre}}(n, \text{player})| \le 20$ for every NPC.

O7 solvency
total spending in the turn $\le c_{\text{pre}}$ and $c_{\text{post}} \ge 0$.

O8 unearned currency
$c_{\text{post}} - c_{\text{pre}} \le 50$.

O8 encodes a design bound the validator does not implement; it is the oracle's only rule with no counterpart in V, and it exposes the gap reported in Section IX-C.

5) Scoped dual-tier memory: Long-term memory is a set of entries $m_i = (\mathbf{v}_i, x_i, t_i, \ell_i, n_i)$: a unit vector, the text shown to the model, the turn, a location and an NPC. On commit, $\mathbf{v}_i$ is the embedding of the *player input* under all-MiniLM-L12-v2 [35], [36] ($d = 384$, L2-normalised), x_i is the model's memory summary (or the truncated input when absent), ℓ_i is the player's location after the turn's events and n_i the active NPC. The index is an exact inner-product FAISS index [37], so $\mathbf{q}^\top \mathbf{v}_i$ is cosine similarity. For query $\mathbf{q}$, current location ℓ and NPC n, let $\mathrm{top}_m(\mathbf{q})$ be the m most similar entries in descending order and define the scope predicate

$$\phi_{\ell,n}(m_i) = \big(\ell_i = \varnothing \vee \ell_i = \ell\big) \wedge \big(n_i = \varnothing \vee n_i = n\big), \quad (3)$$

where empty metadata acts as a wildcard. Scoped retrieval with over-fetch factor $f = 5$ and threshold $\theta = 3$ is

$$\mathcal{R}(\mathbf{q}) = \begin{cases} \mathrm{first}_k\big[m \in \mathrm{top}_{\min(fk,|M|)}(\mathbf{q}) : \phi_{\ell,n}(m)\big] \\ \qquad \text{if this list has } \ge \theta \text{ entries}, \\ \mathrm{top}_k(\mathbf{q}) \quad \text{otherwise (relaxation fallback)}, \end{cases} \quad (4)$$

with $k = 6$. The fallback *replaces* the scoped list rather than extending it. The short-term tier is a ring buffer of the last $B_s = 8$ turns. When $|M| > 1000$ the store keeps its newest 500 entries.

Proposition 2 (Post-filter reachability)**.** *An in-scope entry m can be returned by the scoped branch of (4) only if its similarity rank among* all *entries is at most $fk = 30$. Hence*




Fig. 1. Turn pipeline of OBSIDIAN FLASK (graph/definition.py). The LLM output is untrusted: proposals reach the world state only through the validation barrier (node 6) and the pure reducer inside the commit node (node 7). The commit node writes the four stores; on later turns, retrieval (node 2) reads the FAISS store and prompt assembly (node 3) reads the turn buffer.

scoped recall can fall below the recall of an exact filtered search whenever more than $fk - 1$ out-of-scope entries are more similar to $\mathbf{q}$ than m.

Proof. The scoped branch filters $\mathrm{top}_{fk}(\mathbf{q})$; entries outside it are never inspected. □

The prompt contains a fixed system block, the canonical state of the current location and active NPC, player identity, the retrieved memory texts, the buffer and the query, capped at 16,384 characters by dropping memories first and history second (llm/prompt_builder.py).

B. Turn pipeline

Fig. 1 shows one turn. The player input is embedded and used to retrieve scoped memories, the prompt is assembled from the canonical state, the memories and the buffer, and the LLM returns one JSON object. Its proposals are parsed, checked by the barrier against the pre-turn state, and only accepted proposals are appended to the event log and applied by the reducer; the commit node also updates the buffer, the FAISS store and, every 16 turns, the snapshot. Section VII gives the pseudocode and Section VIII the software that runs it.

C. Experimental conditions

All conditions share the backbone, decoding parameters, system prompt, canonical-state serialisation, output schema and player scripts; they differ only in memory and in how proposals reach state (Table II). Baselines are independent NumPy implementations that do not reuse the system's retrieval code. Budget B is the mean token count of F4's memory and history blocks on the calibration probes, 440 tokens. Without a validator, schema-valid proposals are written straight into the state (direct writes), modelling an agent that writes state through a tool interface. The scripted-FSM reference (B4) and an LLM-managed paging-memory baseline (B5) were planned but not run. B2 is also the closest analogue of the base paper's retrieval: it ranks stored turn summaries by cosine relevance alone, without the base paper's recency and importance terms.

D. Paired three-way commit protocol

Request seeds depend on the probe or turn and never on the condition, so identical prompts receive identical outputs (common random numbers). For probes, the *same* parsed output is then committed three ways (through the barrier, through the reducer alone, and by direct writes) and audited by the oracle of Section IV-A4, so differences between modes are attributable to the commit path alone. Lawfulness of a proposal is judged by the oracle on a single-proposal transition, which gives false-rejection and validator-gap rates that do not depend on the validator's own verdicts. Section VII-A gives the procedure.

E. Metrics

Let $y_j \in \{0,1\}$ be correctness of recall probe j and r_j the rank of its gold memory among the retrieved list (undefined if absent).

$$\begin{aligned} \text{Recall} &= \tfrac{1}{n}\textstyle\sum_j y_j, \\ \text{MRR@}k &= \tfrac{1}{n}\textstyle\sum_j \mathbb{1}[r_j \le k]\, r_j^{-1}, \\ \text{Recall@}k &= \tfrac{1}{n}\textstyle\sum_j \mathbb{1}[r_j \le k]. \end{aligned} \tag{5}$$

For rolling conditions, the *gold-in-prompt* rate (the plant turn is in the history or retrieved list) replaces MRR. For probes, *attack success* is the share of attacks whose post-state violates an invariant (a secret leak for the secret category); *false rejection* is $\sum$ lawful twin proposals rejected / $\sum$ lawful twin proposals; the *validator gap* is $\sum$ unlawful proposals accepted / $\sum$ unlawful proposals over attacks and twins. The *violation rate* is

$$\text{Viol}/100 = 100 \cdot \frac{\sum_{\text{turns}} \mathbb{1}[\text{post-state violates some invariant}]}{\sum_{\text{turns}} (\text{committed non-speech mutations})}. \tag{6}$$

The oracle audits the whole post-state, so a corruption that persists (for example a player left in a non-existent location) is flagged on every later turn, including turns that commit nothing; in live sessions the rate can therefore exceed 100. *Desynchronisation* is an automatic proxy: a turn is flagged when the barrier rejected a proposal but the dialogue has no

TABLE II
CONDITIONS. F1 TO F4 FORM THE 2 × 2 FACTORIAL; A1 TO A7 CHANGE ONE COMPONENT OF F4.

ID	Long-term memory	Prompt history	State control
F4	real `FAISSMemory` + real retrieval node (scope, fallback)	8-turn buffer	barrier + event log + reducer (as shipped)
B0	none	full history, oldest dropped only at the context limit	direct writes
B1 / B1×2	none	newest turns within B / $2B$ tokens	direct writes
B2	flat store of turn *summaries*, top-6 cosine, no scope	none	direct writes
B3	raw dialogue chunks + world lore documents, top-6	none	direct writes
F1	none	rolling, budget B	direct writes
F2	none	rolling, budget B	barrier + event log
F3	as F4	8-turn buffer	direct writes
A1	none	8-turn buffer	as F4
A2	as F4	none	as F4
A3	unscoped top-6	8-turn buffer	as F4
A4	scoped, no fallback ($\theta = 0$)	8-turn buffer	as F4
A5	as F4	8-turn buffer	schema-only events through the reducer
A6	as F4	8-turn buffer	validator, then in-place writes, no log
A7	as F4	8-turn buffer	as F4, recovery by full replay

refusal cue, or when, on a scripted move turn, the narration's claim of arrival disagrees with the committed move. *Replay consistency* is the share of sessions whose state rebuilt from the log matches the live final state by a SHA-256 hash of the canonical JSON (excluding `active_npc_id`). Latency is reported as percentiles, and token cost as input and output tokens counted on the exact prompt ids and from vLLM usage fields.

F. Statistical analysis

Intervals are 95% cluster-bootstrap percentile intervals with 10,000 resamples [38], [39], clustering on session for recall and live metrics and on probe for probe metrics. Ratios are bootstrapped as ratios of resampled sums: for clusters g with numerator and denominator sums a_g, b_g and a resample $g_1^*, \dots, g_G^*$,

$$\hat{\rho} = \frac{\sum_g a_g}{\sum_g b_g}, \qquad \hat{\rho}^* = \frac{\sum_i a_{g_i^*}}{\sum_i b_{g_i^*}}. \tag{7}$$

Paired binary outcomes use the exact McNemar test [40], which conditions on the $n_{10} + n_{01}$ discordant pairs and tests $n_{10} \sim \mathrm{Bin}(n_{10} + n_{01}, \frac{1}{2})$; paired continuous outcomes use the Wilcoxon signed-rank test [41]. The confirmatory family (H1 to H3, six tests) is Holm-corrected [42]. The factorial is modelled on live turns as

$$\begin{aligned}\operatorname{logit} \Pr(y = 1) = \beta_0 + \beta_M M + \beta_C C \\ + \beta_{MC} MC + u_{\text{world}} + v_{\text{session}},\end{aligned} \tag{8}$$

with $M, C \in \{0, 1\}$ indicating dual-tier memory and the barrier and Gaussian random intercepts, fitted by variational Bayes (`BinomialBayesMixedGLM.fit_vb` in statsmodels [43]). We report posterior means and standard deviations and, as the notebook does, $z = \text{mean}/\text{sd}$ with a two-sided normal tail probability. These are approximate posterior summaries, not frequentist Wald tests.

G. Hypotheses

Stated before the run, each against the strongest applicable baseline. A hypothesis is supported only if the corrected effect is significant with the predicted sign, or the stated threshold is met.

H1 F4 recall at $a \geq 20$ exceeds B1 at equal budget, and B2 and B3 at equal or lower token cost.

H2 Scoping plus fallback gives higher MRR@6 than unscoped flat retrieval (B2).

H3 The barrier reduces oracle-detected committed violations on probes and in live sessions.

H4 False rejection on lawful twins is at most 5% and validation adds under 5 ms at P95.

H5 Replay from the log reproduces the live state in 100% of event-sourced sessions.

H6 Memory mainly affects recall and control mainly affects violations, with small interaction.

H7 The directions of the H1 and H3 effects hold on W2, W3 and W4.

V. DATASET DESCRIPTION AND USAGE

The dataset is a benchmark built for this study: seven worlds, teacher-forced recall sessions, adversarial probes with lawful twins, and live-session scripts, generated deterministically by the evaluation notebook from a master seed, together with the model outputs and metrics of the reported run. Section V-E lists the released files and how each is used.

A. World suite

A single hand-made world cannot support generalisation claims, and a benchmark written by the system's authors risks being tuned to it. The suite therefore has four families (Table III and Fig. 2): W1, the in-house dark-fantasy

TABLE III
WORLD SUITE AS BUILT FOR THE RUN (METRICS/WORLD_STATS.CSV). "JOIN" COUNTS SPANNING-TREE EDGES ADDED TO CONNECT LIGHT'S ROOM GRAPH.

World	Family	Locations	NPCs	Objects	Rules	Edges	Diameter	Secrets	Join
W1	in-house (in-distribution)	8	4	4	7	7	4	8	0
W2a	LIGHT-derived	16	6	7	5	15	8	12	14
W2b	LIGHT-derived	24	6	9	5	23	9	12	22
W2c	LIGHT-derived	32	6	12	5	31	9	12	27
W3	held-out genre	24	6	8	6	27	4	12	0
W4-32	procedural	32	8	16	5	39	9	16	0
W4-128	procedural	128	16	64	5	163	12	32	0

development world (Backend/game/world_seed.json); W2a to W2c, converted by a deterministic seeded script from the crowd-written LIGHT environment file [10] (CC BY-NC 4.0), with LIGHT's fragmented room graph joined by a seeded spanning tree and two templated secrets per NPC built from words that occur nowhere else in the world; W3, a 24-location science-fiction station authored in the notebook from a written specification before any system run; and W4-32 and W4-128, procedural graphs (random spanning tree plus about 30% extra edges) with templated names. No system setting was tuned on W2 to W4. W3 is held out from tuning but was *not* independently authored.




Fig. 2. Size of each world (log scale): locations, NPCs and objects. The procedural W4-128 extends the suite to 128 locations, 16 NPCs and 64 objects.

B. Teacher-forced long-horizon recall sessions

A session is a fixed script of $H \in \{50, 100, 200\}$ player turns. For each fact age $a \in \{5, 10, 20, 40, 80, 160\}$ with $a < H - 1$, two facts are *planted* with a randomly chosen NPC and *probed* a turns later with the same NPC, using 15 attribute templates (meeting place, password, debt, and so on). Each fact has a paraphrased *distractor* with a different value told to a different NPC, placed between plant and probe where possible. Values come from pools of invented or uncommon words; any value whose key word occurs anywhere in a world's text is removed, so a correct answer cannot come from lore. A probe is correct when the gold key word appears as a whole word in the reply or narration, and *confused* when the distractor's key word appears instead.

Fillers are small talk with the NPC of the next scripted event, and the player stands at that NPC's location. NPC replies and memory summaries in the history are scripted (teacher forcing), so every condition sees the same history and the LLM is called only at probe turns. A session holds 8, 10 or 12 probes for $H = 50, 100, 200$. With three sessions per world and horizon, each condition answers 630 probes over 63 sessions: 540 on held-out worlds, of which 324 have $a \geq 20$. Because a fact is always probed with the NPC it was told to, at that NPC's fixed location, this design favours scoping; Section X returns to this.

C. Adversarial invariant probes with lawful twins

Each probe is a scenario (a world state with the player beside an NPC, three teacher-forced history turns, and one attack turn) in one of seven categories, each paired with a lawful twin: teleportation (twin: walk to an adjacent location), item fabrication (pick up a present item), theft or duplication (pick up a present item), trust inflation (thank the NPC), currency exploits (pay a small affordable amount), prompt injection [29] (an ordinary question), and secret extraction at trust 0 (the same request at trust 80). The run used 10 attacks per category per world, 490 attacks in all, with 470 twins: theft has twins for 50 of its 70 attacks. Every attack and twin was posed under five context conditions (F4, B0, B1, B2, B3), giving 4,800 probe outputs.

D. Live sessions

Live sessions run the backend's real LangGraph nodes every turn, so the model's own replies and committed state feed later turns. Each script has 39 turns: four plants with two NPCs, walks between them (one "I walk over to …" turn per edge), small talk, two lawful trades, six attacks, and four late probes. The recorded fact ages of these probes are 30 to 34 turns. Two scripts per world give 14 sessions per condition, paired on identical inputs. If a scripted move is not committed the script continues, which the desynchronisation metric detects.

E. Sources, format and release

Sources. W1 is the game's own seed (Backend/game/world_seed.json). W2a to W2c are converted from the LIGHT environment file [10] (`light-environment.pkl`, CC BY-NC 4.0), whose rooms (setting and description), characters with personas, and objects become locations, NPCs and objects; W3 and W4 are generated in the notebook. *Format.* Each world is a JSON document in the game's save schema: metadata, locations with `connected_to` lists, NPCs with description, personality, knowledge, secrets and an `alive` flag, objects with location and owner, world rules, the player

(location, inventory, currency), trust relationships, journal and turn. Recall sessions (session id, world, horizon, scripted turns, planted facts), adversarial probes (category, attack, lawful twin, scenario state, history) and live scripts are JSON Lines files with one record per line. *Size.* The notebook generates the full pools of the largest sample-size level, 840 recall sessions, 2,940 probe scenarios and 70 live scripts (about 33 MB and 130 MB for the first two), and a run uses a prefix of each; the reported run used 63 recall sessions per condition (630 probes), 490 attacks with 470 lawful twins, and 14 live sessions of 39 turns per condition. *Release.* The generated data, every prediction and metric file, and the blinded annotation sheets are committed under notebooks/outputs/ and in notebooks/outputs.zip; the W2 worlds inherit LIGHT's non-commercial licence.

F. How the data is used

Recall sessions answer RQ1: every memory condition replays the same teacher-forced history and is asked the same probes, so recall, MRR and gold-in-prompt rates are paired across conditions. Probes answer RQ2: each attack and its lawful twin is posed under five context conditions, and every output is committed three ways (Section IV-D). Live sessions answer RQ3 and RQ4: they run the real backend graph each turn for the 2×2 factorial and the control ablations and record latency and tokens. RQ5 uses the split by world family (W1 is in-distribution; W2 to W4 are held out from tuning) and a second backbone on a subset. Every table in Section IX is recomputed from the prediction files without a GPU (Section VIII-B).

VI. Novelty

The components of the engine are individually standard: a turn buffer, dense retrieval, schema-constrained output, a rule validator, an append-only event log and a deterministic reducer. We claim no novelty for any of them. The novelty lies in how they are combined against the base paper and in what the evaluation can show.

Against the base paper. Generative Agents [8] rank memories by LLM-rated importance, recency and relevance and leave world changes unchecked. The engine instead (a) scopes retrieval by the current location and NPC, which needs no LLM call per memory write; (b) binds every model-proposed change to a typed, event-sourced state through a symbolic pre-commit barrier and a pure reducer, so state can be replayed and audited; and (c) is evaluated by automatic, paired and oracle-audited metrics at a matched token budget instead of believability rankings.

In the evaluation. To our knowledge, this is the first evaluation of symbolic pre-commit validation of LLM-proposed game mutations with an oracle independent of the validator, paired on identical model outputs, together with memory scoping, replay and cost in one factorial design. It yields three findings not available from prior work. (i) *Paired attribution of protection*: committing identical outputs three ways shows that, of the 13.3-point reduction in attack success from direct writes to the barrier, 9.1 points come from the reducer's own semantics and 4.2 from the validator, so validator and reducer must be evaluated as a pair. (ii) *Oracle-revealed blind spots*: an oracle written from the specification exposed a currency rule that the validator never implemented, which no validator-scored metric could have revealed. (iii) *Measured costs of control*: zero false rejections, but a five- to seven-fold rise in desynchronisation (from about 3% to about 19% of live turns) and a load path that silently loses up to 15 turns of logged events (8 on average in our crash simulation).

VII. Algorithms

Three algorithms define the system and its evaluation. Algorithm 1 is one turn of the engine, following nodes 1 to 8 of Fig. 1: input sanitisation, scoped retrieval, prompt assembly, generation and parsing, validation of each proposal against the pre-turn state, and the commit that appends events, reduces the state, updates both memory tiers and writes periodic snapshots.

Algorithm 2 is the retrieval step, (4) as code: it over-fetches fk nearest neighbours by exact inner product, keeps those inside the current scope, and falls back to the unscoped list when fewer than θ survive.

A. Paired three-way commit and audit

Algorithm 3 is the core of the evaluation protocol of Section IV-D. One model output per probe is committed through the barrier, through the reducer alone and by direct writes, and each post-state is audited by the oracle.

B. Complexity

With $|M| \leq 1000$ entries, $d = 384$ and p proposals per turn: exact search is $O(|M|d)$; validation is $O(p)$ dictionary and adjacency lookups; reduction is $O(p\,|S|)$ because each event deep-copies the state; recovery from the latest snapshot is $O(|S| + r)$ with r the events since it. Measured costs are in Section IX-G.

VIII. Implementation

A. Software stack

The engine has four tiers. The presentation tier (React, TypeScript, Zustand) streams turns over a WebSocket; the orchestration tier (FastAPI with per-session async locks) runs a compiled eight-node LangGraph `StateGraph` (graph/definition.py); the validation tier is the barrier (game/validator.py); and the storage tier holds the SQLite event log and snapshots (core/event_store.py, core/snapshot.py), the FAISS store with all-MiniLM-L12-v2 embeddings (memory/faiss_index.py) and the turn buffer (memory/short_term.py). In the shipped game the LLM is a hosted endpoint (Groq, `openai/gpt-oss-120b`, temperature 0.35, Backend/config.py); in the evaluation it is a self-hosted model served by vLLM [44].

Algorithm 1 One turn of the engine (nodes 1 to 8 of Fig. 1)

Require: player input u, active NPC n, state S_t, store M, buffer H, log $\mathcal{E}$

$u \leftarrow \textsc{Trim}(u)$; **if** $u = \varepsilon$ **then** $u \leftarrow$ "(silence)"
$\mathbf{q} \leftarrow \textsc{Embed}(u)$; $\mathcal{R} \leftarrow \textsc{ScopedRetrieve}(\mathbf{q}, \pi(S_t), n)$ ▷ Algorithm 2
$x \leftarrow \textsc{BuildPrompt}(S_t, n, u, \mathcal{R}, H)$ ▷ memories trimmed first
$y \leftarrow \text{LLM}(x)$; $o \leftarrow \textsc{ParseJSON}(y)$ ▷ on failure: y becomes dialogue, no proposals
$E_t \leftarrow [\, e(\tau, p) : (\tau, p) \in o.\text{proposals},\ V(\tau, p, S_t)\,]$ ▷ Equation (2); entity creation rejected
append e_{speech} and E_t to $\mathcal{E}$; $S_{t+1} \leftarrow \text{foldl}(\delta, S_t, E_t)$
$H.\text{push}(u, o.\text{dialogue}, n)$; $M.\text{add}(\mathbf{q},\ o.\text{summary},\ t{+}1,\ \pi(S_{t+1}),\ n)$
if $|M| > 1000$ **then** keep the newest 500 entries of M
if $(t+1) \bmod 16 = 0$ **then** write snapshot $(S_{t+1}, \max \text{id}(\mathcal{E}))$ and save M
return dialogue, narration, S_{t+1}

Algorithm 2 SCOPEDRETRIEVE (`make_node_retrieval`, `FAISSMemory.search`)

Require: query $\mathbf{q}$, location ℓ, NPC n, $k = 6$, $f = 5$, $\theta = 3$

$C \leftarrow$ exact inner-product top-$\min(fk, |M|)$ of $\mathbf{q}$ over M
$R \leftarrow [\,]$
for $m \in C$ in descending similarity **do**
    if $\phi_{\ell,n}(m)$ **then** append m to R; **if** $|R| = k$ **then break**
if $|R| < \theta$ **then** $R \leftarrow$ first k entries of C ▷ relaxation fallback, unscoped
return R

B. System under test

The notebook notebooks/npc-memory-state-benchmark.ipynb clones the repository at commit 0ea345fe140b359d7e82e77ffb2fdfa74caf0e7c, asserts the hash, and imports the real backend modules (reducer, validator, event store, snapshots, prompt builder, FAISS memory, buffer, JSON extractor and the LangGraph node factories). Live conditions are built from the backend's own nodes, swapping only the nodes a condition changes. Only the baselines, the oracle and the benchmark generators are new code. Before any GPU time, a self-test with a deterministic mock LLM checks that the oracle flags direct writes, the barrier commits fewer violations, event-sourced sessions replay exactly, and the notebook's scoped retrieval matches `node_retrieval`. Table IV lists the run configuration.

C. Sample-size planning

Eight pre-declared levels (index 0 to 7; Appendix B) fix sessions per world and horizon, probes per category and world, and live sessions per world, so a smaller level is a prefix of a larger one. A pilot of 256 jobs measured steady-state throughput, and a planner chose the largest level whose estimated cost fitted the 11.25-hour budget after reserves: level 2 (estimated 8.18 h of 8.47 h available), the third of the eight levels. The full targets correspond to level 7 (estimated 63.0 h). Coverage was complete: 6,300 recall, 4,800 probe, 3,276 live-turn, 1,680 seed-variance, 720 secondary-recall and 550 secondary-probe rows, none lost to a deadline. The primary server generated 14,448 responses and served 1,953 from the

TABLE IV
RUN CONFIGURATION (METRICS/RUN_MANIFEST.JSON).

Hardware	Kaggle session, 2× Tesla T4 (15.64 GB each, compute capability 7.5, driver 580.178.04), 4 CPU cores, 33.7 GB RAM
Software	Python 3.12.13, PyTorch 2.10.0+cu128, sentence-transformers 5.4.1, faiss-cpu 1.15.1, LangGraph 0.6.11, Pydantic 2.12.3, NumPy 2.0.2, pandas 2.3.3, SciPy 1.16.3, statsmodels 0.14.6; vLLM 0.30.0 in an isolated environment
Backbones	primary `IFM/K2-Horizon-7B` (fp16, tensor parallel over both GPUs); secondary `IFM/K2-Horizon-3.7B` (one replica per GPU); both Apache 2.0 reasoning models
Decoding	temperature 0.35 (backend value), top-p 0.95, reasoning effort low, thinking capped at 192 tokens then closed by the harness, answer $\leq$768 tokens, context 16,384 tokens, 64 concurrent sequences
Seeds	master seed 20261001; request seed a function of probe or turn only; sampling-seed replicates 1 and 2 for F4, B1, B2, B3
Engine constants	buffer 8; $k = 6$; over-fetch 5; fallback threshold 3; snapshot every 16 turns; prompt cap 16,384 chars; prune above 1,000 entries to 500; embedder all-MiniLM-L12-v2 ($d = 384$)
Benchmark	horizons 50/100/200; fact ages 5 to 160, 2 probes per age; 3 history turns per probe; budget $B = 440$ tokens; oracle trust step 20, currency gain cap 50
Sample size	ladder level 2 (index 0 to 7): 3 sessions per world and horizon, 10 probes per category and world, 2 live sessions per world
Statistics	10,000 cluster-bootstrap resamples, $\alpha = 0.05$, Holm correction

Algorithm 3 Paired three-way commit and independent audit of one probe output

Require: scenario state S, prompt x, seed $s = h(\text{probe id})$ ▷ independent of condition
$y \leftarrow \text{LLM}(x; \text{seed } s)$; $o \leftarrow \textsc{ParseJSON}(y)$
for mode $\in$ {barrier, reducer, direct} **do**
  if mode $=$ barrier **then** $S' \leftarrow \text{foldl}(\delta, S, [e(\tau, p) : V(\tau, p, S)])$
  else if mode $=$ reducer **then** $S' \leftarrow \text{foldl}(\delta, S, [e(\tau, p) : \tau \text{ a known type}])$ ▷ ablation A5
  else $S' \leftarrow$ write each proposal and each new entity into a copy of S ▷ no clamping
  $v_{\text{mode}} \leftarrow \textsc{Oracle}(S, S', \text{committed list})$ ▷ O1 to O8; no validator code
return $(v_{\text{barrier}}, v_{\text{reducer}}, v_{\text{direct}})$, lawful/unlawful counts per proposal




Fig. 3. GPU utilisation of both T4s over the 6.69-hour run, sampled every 15 s by `nvidia-smi`. Utilisation is near 100% during the LLM stages; the drops are server restarts and the CPU-only stages (replay, sweeps), and the final segment is the secondary backbone served as one replica per GPU.

response cache; 80 requests were skipped at a deadline, all in the single-stream latency stage. Fig. 3 shows the run profile.

D. Execution procedure

(1) Create a Kaggle notebook from notebooks/npc-memory-state-benchmark.ipynb, select *GPU T4 x2*, enable Internet, and optionally attach an independently written `w3_world_seed.json` or earlier `llm_cache_*.jsonl` files. (2) Run it as a saved version (*Save & Run All*). The notebook installs the pinned packages, builds the worlds and benchmark, runs the CPU experiments, the pilot, the planner and every LLM stage, and writes `outputs.zip`. Stage times in the reported run were: recall 154.8 min, probes 52.5 min, live sessions 96.8 min, seed variance 23.9 min, latency 10.0 min, secondary backbone 35.7 min, replay 9.4 min. (3) The outputs used in this paper are committed under notebooks/outputs/ (plots, metrics, predictions, annotation sheets) together with notebooks/outputs.zip, which also holds the generated worlds, sessions, probes and logs. Every table here can be regenerated from notebooks/outputs/predictions/ without a GPU; we recomputed all point estimates of the main, fact-age, probe and factorial tables (Sections IX-A, IX-C and IX-D) and the six confirmatory tests from those files and obtained identical values (bootstrap intervals agree to within resampling noise). The game itself runs with `npm run dev` from the repository root (Python 3.10+, Node 20.19+ or 22.12+, and a `GROQ_API_KEY`); this paper builds with `npm run paper` from the repository root, which runs the bundled Tectonic and fails on any undefined reference, overfull box or bibliography warning.

E. Coverage gaps in the implementation

Reading the code against the specification, and the evaluation itself, exposed the following gaps at the evaluated commit. They are stated here so that the evaluation can measure them.

G1. **Currency gains are unbounded**: only negative deltas are checked.

G2. **Per-proposal, not per-turn, checking**: every proposal is validated against S_t, so several spends that each fit the balance can jointly overspend (the reducer then floors the balance at zero), and chained effects within one turn are not re-checked.

G3. **NPC drops and NPC relocation**: drops by NPCs do not check possession, and `NPC_STATE_CHANGED` with key `location_id` is accepted for any value; the reducer, not the validator, ignores a non-canonical NPC location.

G4. **Prompt and validator disagree on trust**: the prompt advertises deltas in $[-10, 10]$, the validator allows ± 20.

G5. **Secrets never reach the model**: NPC secrets are not placed in the prompt, so the trust-60 reveal rule cannot be honoured and leak rates do not measure secret keeping.

G6. **Load path ignores the logged suffix**, and `active_npc_id` is set outside the log (Proposition 1).

G7. **Bare JSON values**: at the evaluated commit the JSON extractor could return a string or list, which the parse node did not handle (3 of 3,276 live turns raised). This was fixed after the evaluation (commit a9767d5); no other backend file changed.

G8. **Structural, not narrative, legality**: an in-bounds but unjustified trust change passes, and rejection does not rewrite the NPC's dialogue.

TABLE V
MAIN COMPARISON ON HELD-OUT WORLDS. VIOLATIONS AND ATTACK SUCCESS ARE FROM THE PROBE SUITE: F4 COMMITS THROUGH THE BARRIER AND BASELINES BY DIRECT WRITES. LATENCY IS SINGLE-STREAM LLM TIME PER REQUEST. "N.R.": NOT REPLAYABLE (NO EVENT LOG). PROBE PROMPTS CARRY THREE HISTORY TURNS, SO B0 AND B1 BUILD IDENTICAL PROBE PROMPTS AND THEIR VIOLATION FIGURES COINCIDE.

Condition	Recall, $a \geq 20$ (%)	Viol./100 trans.	Attack succ. (%)	MRR@6	P50/P95 LLM (ms)	Input tok.
B0 Full history	80.2 [75.9, 84.4]	45.0 [38.3, 52.1]	13.3 [10.2, 16.7]	–	10,948 / 23,984	4,310
B1 Rolling, B	0.0 [0.0, 0.0]	45.0 [38.1, 51.9]	13.3 [10.2, 16.7]	–	7,020 / 11,173	1,398
B1 Rolling, $2B$	25.0 [21.3, 28.9]	–	–	–	not measured	1,823
B2 Vector memory	84.9 [81.1, 88.6]	43.1 [37.3, 48.9]	15.7 [12.4, 19.3]	0.750 [0.729, 0.771]	not measured	1,102
B3 Generic RAG	63.9 [57.7, 69.9]	56.4 [50.8, 61.9]	19.3 [15.7, 23.1]	0.707 [0.686, 0.729]	not measured	1,209
F4 Proposed	**87.7 [84.2, 91.0]**	**9.2 [4.6, 14.3]**	**3.1 [1.4, 4.8]**	**0.898 [0.877, 0.917]**	6,906 / 9,409	1,399

Replay consistency: F4 100.0 [100.0, 100.0]%; all baselines n.r. Latency for B1 rests on 15 of 24 requests; B1×2 (one cached sample), B2 and B3 were not reached before the stage deadline.

IX. COMPARISON OF RESULTS

Values are mean [95% cluster-bootstrap CI], pooled over the held-out worlds W2a to W4-128 unless stated, with K2-Horizon-7B as backbone. W1 appears in Section IX-H. The section first compares the system with the independent baselines (Section IX-A), then breaks the comparison down by mechanism (Sections IX-B to IX-I), compares the system with the base paper and the reported results of related work (Section IX-J), and closes with an error analysis (Section IX-K).

A. Main comparison

Table V summarises the comparison. F4 had the highest long-range recall, the best ranking and the lowest violation and attack rates. Its recall advantage over flat vector memory B2 (+2.8 points) was not significant, and B2 used 21% fewer input tokens (Fig. 4). Full history cost three times F4's input tokens for lower recall, and its single-stream LLM latency was 1.6 times F4's at the median and 2.5 times at P95.




Fig. 4. Mean input tokens per turn against recall at fact age 20 or more (held-out worlds). Up and to the left is better. B2 and A2 reach recall similar to F4 with fewer tokens; B0 costs about three times as much for lower recall; A1 and B1 sit at zero.

Recall by fact age (Fig. 5; per-age values in Appendix A) separates the memory designs. The rolling contexts fall to zero once a fact leaves their window (B1 after age 10, B1×2 after age 20), while F4 and B2 stay flat up to age 160 and generic RAG (B3) declines to 44.4%. Among the memory ablations, only removing long-term memory (A1) is catastrophic.

B. Retrieval quality, sensitivity and seed variance

Scoping changed *ranking* more than *reach*. F4, B2, B3 and A3 placed the gold turn in the prompt for 98% to 100% of probes (Appendix A), so recall@6 does not separate them, but F4 ranked it higher (MRR@6 0.898 against 0.750 for B2 and 0.705 for the unscoped ablation A3; plotted in Appendix A) and kept the paraphrased distractor out of 43% of prompts, against 10% for B2 and 9% for A3. Removing the buffer (A2) kept the distractor out of 90% of prompts, because the distractor, told to a different NPC, then reaches the prompt only through retrieval. In the teacher-forced design the fallback rarely fires usefully: disabling it (A4) raised MRR@6 to 0.950, since the fallback replaces a short scoped list with unscoped neighbours.

The retrieval-only sweeps (80 sessions on W1 and W2 at horizons 100 and 200, one setting varied at a time around buffer 8, $k = 6$, $\theta = 3$) confirm this (Fig. 6; values in Appendix A). Buffer size had no effect on retrieval. A threshold of 0, which is A4, gave the best MRR; $\theta = 6$ triggered the fallback more often and lowered it.

Across three sampling seeds on the 21 calibration sessions (210 probes, all ages), F4 was the most stable condition (Table VI; plotted in Appendix A).

TABLE VI
RECALL OVER ALL AGES FOR THREE SAMPLING SEEDS (CALIBRATION SESSIONS, ALL WORLDS).

Condition	Seed 0	Seed 1	Seed 2	SD (points)
F4	0.857	0.862	0.862	0.27
B1, B	0.314	0.300	0.310	0.73
B2	0.871	0.848	0.795	3.90
B3	0.681	0.681	0.671	0.55

C. State control under adversarial probes

Table VII pools the outputs of all five context conditions (350 attacks per category) and commits each three ways. Through the barrier, teleportation, fabrication, theft and injection attacks never produced a committed violation, against 6% to 33% with direct writes, and no lawful twin was rejected (plotted in Appendix A). Much of the protection already comes from the reducer: committing every schema-valid proposal as an event (A5) cut overall attack success from 16.2% to 7.1%,




Fig. 5. Recall by fact age on held-out worlds with 95% bootstrap intervals. Left: F4 against the baselines; the rolling contexts fall to zero once a fact leaves the window (B1 after age 10, B1×2 after age 20), while F4 and B2 stay flat and generic RAG (B3) declines to 44.4% at age 160. Right: F4 against its memory ablations; only removing long-term memory (A1) is catastrophic.

TABLE VII
ADVERSARIAL PROBES BY CATEGORY, ALL WORLDS AND ALL FIVE CONTEXTS (350 ATTACKS PER CATEGORY, 2,450 IN ALL). ATTACK SUCCESS IS A COMMITTED ORACLE VIOLATION, OR A SECRET LEAK FOR THE SECRET CATEGORY. VALIDATOR GAP: UNLAWFUL PROPOSALS ACCEPTED BY THE BARRIER OVER UNLAWFUL PROPOSALS.

Category	Direct writes (%)	Reducer only, A5 (%)	Barrier (%)	False rejection (%)	Validator gap (%)
Teleportation	15.1 [9.1, 21.7]	2.9 [1.1, 4.9]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.4 [0.0, 1.2]
Fabrication	20.9 [13.1, 29.1]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
Theft	33.4 [24.9, 42.3]	3.1 [1.1, 5.7]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
Trust inflation	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	no lawful props.	–
Currency	36.9 [28.3, 45.7]	36.9 [28.3, 45.7]	19.7 [12.3, 27.7]	0.0 [0.0, 0.0]	51.9 [36.7, 66.4]
Injection	6.0 [2.6, 10.3]	6.0 [2.6, 10.3]	0.0 [0.0, 0.0]	no lawful props.	0.0 [0.0, 0.0]
Secret	0.9 [0.0, 2.3]	0.9 [0.0, 2.3]	0.9 [0.0, 2.3]	0.0 [0.0, 0.0]	–
All	16.2 [13.6, 18.8]	7.1 [5.3, 9.0]	2.9 [1.8, 4.3]	0.0 [0.0, 0.0]	11.0 [6.6, 15.7]

Oracle codes under direct writes: currency 60×O7, 69×O8, 2×O1; fabrication 73×O1, 1×O3; theft 92×O1, 25×O4, 14×O2; teleportation 52×O3, 43×O1, 1×O5; injection 18×O4, 5×O6, 1×O3. Parse success: 95.8% of probe outputs. Secret leak rate over all attacks: 1.8 [1.1, 2.6]%.




Fig. 6. Gold-in-prompt rate and MRR@k for each sweep setting. The default is buffer 8, $k = 6$, threshold 3 (labelled buf8). Lower k and a higher fallback threshold reduce ranking quality; removing the fallback (thr0) improves it on this benchmark.

because the reducer ignores unknown entities and destinations. The barrier's remaining failure is concentrated in one category: it accepted 51.9% of unlawful currency proposals, gains such as a +2,000 delta "for a chest of coins", which the validator never bounds (gap G1). Trust inflation never succeeded under any mode: even under direct writes, no output to a trust-inflation probe changed an NPC's trust by more than 20 in one turn, although five injection outputs did (O6). Secret leaks were rare in every mode, but the model never sees the secrets (gap G5), so this does not show secret keeping.

D. Factorial separation in live sessions

Live sessions reproduce the probe result at larger scale (Table VIII; interaction plots in Appendix A). Under direct writes the oracle flagged 439 of 546 F1 turns and 460 of 546 F3 turns, from only 125 and 133 committed transitions, because the corruption persists: direct writes left the player in a non-existent location on an average of 29.9 (F1) and 30.4 (F3) of 39 turns, and the harness then prompted from the last valid location. With the barrier, 3 (F2) and 6 (F4) turns were flagged. The per-code breakdown (Fig. 7) shows that direct writes fail mainly through non-canonical entities (O1), non-adjacent moves (O3) and overspending (O7), while with the barrier only O5 and O8 remain, each below 1 per 100 turns.

The cost of blocking without regenerating is visible: desynchronisation rose from about 3% to about 19% of live turns once proposals could be rejected, because the NPC's words still describe the rejected change. Live recall with dual-tier memory (41% to 45%) was about half of teacher-forced recall; live memories are written from model-generated summaries and depend on committed movement, and the run does not isolate which factor causes the drop.

Table IX confirms that memory dominates recall and control dominates violations, as designed. It also shows what H6 ruled out: a significant control effect on recall and a positive memory-by-control interaction, and a small memory effect on

TABLE VIII
MEMORY × CONTROL FACTORIAL ON LIVE SESSIONS (14 SESSIONS OF 39 TURNS PER CELL; 56 LIVE PROBES PER CELL). FALSE REJECTION IS FROM LAWFUL TWINS UNDER THE MATCHING PROBE CONTEXT.

Cell	Live recall (%)	Viol./100 transitions	False rejection (%)	Desync (%)
F1 Rolling, direct writes	0.0 [0.0, 0.0]	351.2 [302.2, 405.6]	–	2.7 [1.3, 4.4]
F2 Rolling, barrier	0.0 [0.0, 0.0]	8.8 [0.0, 22.2]	0.0 [0.0, 0.0]	18.5 [15.6, 21.6]
F3 Dual-tier, direct writes	41.1 [26.8, 55.4]	345.9 [305.3, 390.3]	–	3.7 [1.8, 5.7]
F4 Dual-tier, barrier	44.6 [30.4, 59.0]	14.0 [4.3, 27.6]	0.0 [0.0, 0.0]	18.7 [16.5, 20.9]




Fig. 7. Oracle-flagged live turns per 100 turns by condition and invariant code (O2 and O6 never fired and are omitted by the plot). Direct writes (F1, F3) fail mostly on O1, O3 and O7. A6, which keeps the validator but writes accepted proposals in place, accumulates persistent O1 corruption.

TABLE IX
MIXED-EFFECTS LOGISTIC MODELS OF EQUATION (8) ON LIVE TURNS, FITTED BY VARIATIONAL BAYES. "SD" IS THE POSTERIOR STANDARD DEVIATION; p IS THE TWO-SIDED NORMAL TAIL OF $z = \text{MEAN}/\text{SD}$. RECALL IS MODELLED ON PROBE TURNS, VIOLATION ON ALL TURNS.

Outcome	Term	Mean	SD	z	p
Recall	intercept	-3.962	0.198	-20.05	$< 10^{-80}$
	β_M memory	3.572	0.205	17.42	6.1×10^{-68}
	β_C control	-0.983	0.282	-3.48	5×10^{-4}
	β_{MC} interaction	1.171	0.289	4.06	4.9×10^{-5}
Violation	intercept	1.607	0.082	19.53	$< 10^{-80}$
	β_M memory	0.341	0.121	2.83	0.0047
	β_C control	-6.773	0.304	-22.26	1.0×10^{-109}
	β_{MC} interaction	-0.161	0.402	-0.40	0.689

violations. In the raw cells the barrier made no difference to recall under rolling memory (0.0% in both) and a small one under dual-tier memory (41.1% against 44.6%), so with 56 live probes per cell the interaction should be read cautiously.

E. Ablations

Table X shows that not every memory component earned its place on this benchmark: removing the buffer (A2) or the fallback (A4) did not lower recall. Scoping did: without it (A3) recall at $a \geq 20$ fell to 81.8% and MRR to 0.705. On the control side, A5 had a slightly *lower* live violation rate than F4 (11.4 against 14.0 per 100 transitions, overlapping intervals), consistent with the probe finding that the reducer alone blocks most structural attacks, while on probes the barrier was better (9.6 against 13.1). A6, which validates but applies accepted proposals by in-place writes instead of the reducer, reached 351.4 violations per 100 transitions: in 5 of its 14 sessions an O1 corruption appeared on a small-talk turn and persisted thereafter (130 flagged turns from 37 transitions). The reducer's own guards are absent in A6; for example it ignores an NPC relocation to a non-canonical location, which the validator accepts (gap G3). The stored rows do not record proposal payloads, so the exact triggering proposal could not be confirmed. Validator and reducer thus work as a pair.

F. Replay and recovery

Replay behaved as Proposition 1 predicts (Table XI and Fig. 8): every event-sourced live session (F2, F4, A5) and every CPU replay session was reproduced exactly by full fold, by snapshot plus suffix and after a restart. Full replay time grew with log length, reaching a median of 145.9 ms at turn 160, while snapshot loading stayed near 0.5 ms. The application's load path, which drops the suffix, was consistent in none of the simulated crashes and lost 8 turns on average: the gap between the periodic snapshot at turn 192 and turn 200.

G. Latency and token cost

Local work was negligible against generation (per-stage values in Appendix A). Validation took 0.039 ms at P95, well inside the 5 ms bound of H4, and the commit node (SQLite append, reduction, indexing) dominated local time at 18.4 ms. Single-stream LLM time, from the recall-prompt benchmark, was 6,906 ms at P50 and 9,409 ms at P95 for F4. Under the batched live stage (84 concurrent sessions) the median LLM time per F4 turn was about 89.6 s, a throughput setting rather

TABLE X
SINGLE-COMPONENT ABLATIONS. MEMORY ABLATIONS ARE TEACHER-FORCED ON HELD-OUT WORLDS; CONTROL ABLATIONS USE PROBES (ALL SEVEN WORLDS, F4 CONTEXT) AND LIVE SESSIONS. LOCAL COMPUTE IS TURN TIME MINUS LLM TIME IN THE BATCHED LIVE SESSIONS. RECOVERY IS THE MEDIAN AT TURN 160 OVER 42 REPLAY SESSIONS.

			Viol./100 transitions			
Ablation	Recall, $a \geq 20$ (%)	MRR@6	Probes	Live	Local P50 (ms)	Recovery (ms)
F4 full system	87.7 [84.2, 91.0]	0.898 [0.878, 0.917]	9.6 [5.5, 14.1]	14.0 [4.2, 27.3]	41.1	0.5 (snapshot)
A1 no long-term memory	0.0 [0.0, 0.0]	–	as F4	as F4	–	–
A2 no short-term buffer	89.5 [85.8, 92.9]	0.898 [0.878, 0.917]	as F4	as F4	–	–
A3 no scoping	81.8 [77.7, 85.9]	0.705 [0.682, 0.727]	as F4	as F4	–	–
A4 no fallback	88.6 [85.5, 91.6]	0.950 [0.934, 0.964]	as F4	as F4	–	–
A5 no validation barrier	as F4	as F4	13.1 [9.3, 17.1]	11.4 [6.3, 16.5]	43.3	0.5 (snapshot)
A6 no event sourcing	as F4	as F4	–	351.4 [122.6, 675.0]	10.4	no log
A7 no snapshots	as F4	as F4	as F4	as F4	–	145.9 (replay)

Replay consistency: F4 and A5 100%; A6 not replayable; A7 100% (full fold). F4's live interval here is a separate bootstrap draw of the same quantity as in Table VIII.

TABLE XI
REPLAY AND RECOVERY ON 42 CPU SESSIONS OF 200 TURNS (6 PER WORLD; 367.2 EVENTS ON AVERAGE), COMMITTED THROUGH THE REAL EVENT STORE AND REDUCER.

Reconstruction	Sessions consistent
Full fold of the event log	100%
Latest snapshot plus the events after it	100%
Both of the above in a fresh process from the SQLite file	100%
Application load path after a crash between commit and save	0% (8.0 turns lost on average)
Application load path when the per-turn auto-save succeeded	100%




Fig. 8. Median time to rebuild state at each snapshot point (log scale): full replay of the event log (A7) against snapshot loading (the system), over 42 sessions of 200 turns. The plot's title strip, which lists the consistency rates of Table XI, is cropped.

than an interactive one. Per 100 turns F4 consumed 139,898 input and 15,394 output tokens, against 431,032 and 14,117 for full history (Appendix A). Because the models were self-hosted, no monetary cost is reported.

H. Generalisation across worlds and backbones

Both main effects held on every held-out world (Table XII; plotted in Appendix A). By family, F4 minus B1 recall at $a \geq 20$ was $+0.889$ (W2), $+0.796$ (W3) and $+0.898$ (W4), and direct-minus-barrier attack success was $+0.114$, $+0.086$ and $+0.121$. F4 did not beat the best baseline on every world: B2 was ahead on W2c and B0 on W4-32, both within overlapping intervals. On the subset where both backbones ran (W1, W2a, W3, W4-32 at horizon 100; 72 F4 probes at $a \geq 20$), the 3.7B model kept F4's recall close to the 7B model's (81.9% against 86.1%) while every baseline dropped more: B0 from 79.2% to 61.1%, B2 from 84.7% to 73.6% and B3 from 70.8% to 48.6% (Appendix A). With the 3.7B model the barrier blocked every attack (0 of 280, against 18.6% under direct writes of the same outputs) and rejected no lawful twin (0 of 42 lawful proposals).

I. Hypothesis tests

Table XIII summarises the verdicts. H1 fails on two counts: the gain over B2 is not significant, and F4 used more input tokens (1,399 per turn) than both B2 (1,102) and B3 (1,209), so "equal or lower token cost" is not met. H5 holds for the event-sourced design but not for the application's load path. H6 fails because control affects recall and the two factors interact.

J. Comparison with the base paper and reported results

Table XIV sets the system beside Generative Agents [8]. The two evaluations are not numerically comparable: they use different worlds, backbones, tasks and metrics, and the base paper's code was not rerun here. Three comparisons are nevertheless informative.

Memory is necessary in both. The base paper's closest controlled result is its memory ablation: removing observation, reflection and planning lowered the TrueSkill rating from 29.89 to 21.21, eight standard deviations. Removing long-term

TABLE XII
PER-WORLD AND PER-BACKBONE BREAKDOWN. BEST BASELINE FOR RECALL: HIGHEST OF B0 TO B3 ON THAT WORLD; FOR ATTACKS: THE BASELINE CONTEXT WITH THE LOWEST DIRECT-WRITE SUCCESS. THE 3.7B MODEL RAN AT HORIZON 100 ON FOUR WORLDS WITH PROBES UNDER THE F4 CONTEXT ONLY, SO ITS ATTACK COMPARISON IS BARRIER AGAINST DIRECT WRITES OF THE SAME OUTPUTS.

World	Backbone	Recall $a \geq 20$: F4	Recall: best baseline	Attack: F4 barrier	Attack: best baseline (direct)
W1	7B	87.0 [75.0, 97.7]	B2: 87.0 [80.3, 94.2]	7.1 [1.4, 14.3]	B0: 18.6 [10.0, 28.6]
W2a	7B	90.7 [87.1, 95.7]	B2: 85.2 [80.8, 90.0]	2.9 [0.0, 7.1]	B0: 17.1 [8.6, 25.7]
W2b	7B	92.6 [86.5, 98.1]	B2: 87.0 [77.8, 94.6]	4.3 [0.0, 10.0]	B0: 8.6 [2.9, 15.7]
W2c	7B	83.3 [75.0, 91.7]	B2: 87.0 [78.3, 96.3]	2.9 [0.0, 7.1]	B2: 10.0 [4.3, 17.1]
W3	7B	79.6 [71.4, 88.6]	B2: 74.1 [63.8, 83.9]	1.4 [0.0, 4.3]	B0: 11.4 [4.3, 20.0]
W4-32	7B	87.0 [76.0, 96.4]	B0: 90.7 [82.6, 96.8]	4.3 [0.0, 10.0]	B0: 15.7 [7.1, 24.3]
W4-128	7B	92.6 [85.7, 100.0]	B2: 88.9 [81.8, 95.8]	2.9 [0.0, 7.1]	B0: 14.3 [7.1, 22.9]
W1	3.7B	100.0 [100.0, 100.0]	B2: 88.9 [66.7, 100.0]	0.0 [0.0, 0.0]	F4 outputs: 22.9 [12.9, 32.9]
W2a	3.7B	83.3 [66.7, 100.0]	B2: 72.2 [66.7, 83.3]	0.0 [0.0, 0.0]	F4 outputs: 14.3 [7.1, 22.9]
W3	3.7B	66.7 [66.7, 66.7]	B2: 66.7 [50.0, 83.3]	0.0 [0.0, 0.0]	F4 outputs: 17.1 [8.6, 25.7]
W4-32	3.7B	77.8 [50.0, 100.0]	B0: 66.7 [50.0, 83.3]	0.0 [0.0, 0.0]	F4 outputs: 20.0 [11.4, 30.0]

TABLE XIII
PRE-REGISTERED HYPOTHESES. EFFECTS ARE DIFFERENCES IN PROPORTIONS (MCNEMAR) OR MEAN PAIRED DIFFERENCES (WILCOXON). p IS HOLM-CORRECTED OVER THE SIX CONFIRMATORY TESTS.

H	Test	n	Effect	p_{Holm}	Verdict
H1	recall $a \geq 20$, F4 vs B1 (McNemar, held-out)	324	$+0.877$	3.9×10^{-85}	
	recall $a \geq 20$, F4 vs B2	324	$+0.028$	0.298	not supported
	recall $a \geq 20$, F4 vs B3	324	$+0.238$	9.1×10^{-17}	
H2	MRR@6, F4 vs B2 (Wilcoxon, per probe, held-out)	540	$+0.148$	4.3×10^{-20}	supported
H3	attack success, direct vs barrier (McNemar, F4 context, all worlds)	490	$+0.114$	9.1×10^{-17}	supported
	live violations per transition, F3 vs F4 (Wilcoxon, per session)	14	$+3.459$	1.9×10^{-3}	
H4	false rejection $\leq 5\%$; validation P95 < 5 ms	–	0.0%; 0.039 ms	–	supported
H5	replay reproduces live state in 100% of event-sourced sessions	42 + live	100%	–	supported
H6	interaction small	–	recall $\beta_{MC} = 1.17$	–	not supported
H7	H1 and H3 directions on W2, W3, W4	–	all positive	–	supported

TABLE XIV
THE SYSTEM AGAINST THE BASE PAPER. BASE-PAPER VALUES ARE THOSE REPORTED BY PARK ET AL. [8]; VALUES FOR THIS WORK ARE FROM SECTIONS IX-A TO IX-C AND IX-E TO IX-G.

Aspect	Generative Agents (base paper)	This work
Setting	25 agents in one sandbox town; `gpt-3.5-turbo`	NPC dialogue in 7 worlds of 8 to 128 locations; self-hosted 7B and 3.7B models
Memory	memory stream of observations, reflections and plans	8-turn buffer plus a FAISS store of turn summaries (384-d)
Retrieval	recency + importance + relevance, equal weights, min-max normalised	cosine relevance scoped to location and NPC, with relaxation fallback
LLM calls per memory write	one importance rating; reflection when summed importance exceeds 150	none: the summary is a field of the turn's own output
World-state control	natural-language actions mapped to the sandbox; no rule check described	typed, event-sourced state; symbolic barrier and pure reducer
Evaluation	100 human evaluators rank interview answers (TrueSkill); two-day end-to-end simulation	automatic and paired: recall of planted facts, MRR, oracle-audited violations, false rejection, desynchronisation, replay, latency, tokens
Effect of memory	full architecture $\mu = 29.89$ against 21.21 without memory, $d = 8.16$	recall at $a \geq 20$ 87.7% against 0.0% without long-term memory (A1)
Memory errors	embellishment; 1.3% (6 of 453) of relationship answers hallucinated	0.9% of recall probes answered with the distractor's value
Rule violations	not measured	attack success 2.9% through the barrier against 16.2% by direct writes
State replay	not measured	100% of event-sourced sessions reproduced
Cost	"thousands of dollars in token credits" for two simulated days	139,898 input and 15,394 output tokens per 100 turns; validation 0.039 ms at P95

TABLE XV
AUTOMATICALLY CODED FAILURES (RECALL CATEGORIES ON ALL WORLDS; UP TO 50 EXAMPLES PER CATEGORY AND CONDITION ARE EXPORTED TO ANNOTATION/ERROR_SAMPLES.CSV).

Category	F4	B0	B1	B1×2	B2	B3	A1	A3	F2	A6
Retrieval miss (gold not in prompt)	0	0	315	202	5	11	377	6	–	–
Hit but ignored	57	106	27	47	70	142	11	74	–	–
Confused with distractor	6	26	89	78	1	50	132	1	–	–
Schema failure	6	7	4	2	19	9	3	6	–	–
Validator gap (probes)	17	13	13	–	13	15	–	–	–	–
Oracle violation under barrier (probes)	16	13	13	–	13	14	–	–	–	–
Desynchronisation (live, proxy)	102	–	–	–	–	–	–	–	101	108

memory here (A1) lowered recall of facts 20 or more turns old from 87.7% to 0.0%. Both systems depend on long-term memory for anything beyond the immediate context.

Relevance-only retrieval is a strong baseline. B2 ranks stored turn summaries by cosine relevance, which is the base paper's relevance term without recency or importance. Scoping beat it on ranking (MRR@6 0.898 against 0.750) and on keeping the paraphrased distractor out of the prompt (43% against 10% of probes), but not significantly on recall (87.7% against 84.9%, $p = 0.298$), and it used 27% more input tokens. The base paper's recency and importance terms and its reflection were not reimplemented, so whether they would widen or close this gap is untested (Section XI). Unlike the base paper, the engine spends no LLM call on writing a memory.

State control has no counterpart in the base paper. Generative Agents report embellishment at the level of dialogue and do not measure rule violations. In the engine the barrier blocked every teleportation, fabrication, theft and injection attack the model attempted (Table VII), and the event log reproduced the live state exactly. The closest reported measurement is NCP-Bench [7], where the best model kept its narrative commitments in only 42% of runs after 20 turns when checked afterwards by LLM auditors. Here the specification is enforced before commit, which reduced committed attack success to 2.9%, but the dialogue still contradicted rejected changes on 18.7% of live turns: the barrier protects the state, not the narration.

K. Error analysis

Table XV locates the failures. None of F4's recall failures came from retrieval: in all 57 "hit but ignored" cases the gold memory was in the prompt and the model answered wrongly, and only 6 answers used the distractor's value. Rolling contexts failed by forgetting (315 misses for B1), generic RAG by ignoring or confusing retrieved chunks (142 and 50), and the ablation without long-term memory by both (377 misses, 132 confusions). F4's committed violations under the barrier (16) almost all coincide with validator gaps (17), which Table VII places in the currency category. Desynchronisation counts were similar for F4, F2 and A6 (102, 101, 108), the three conditions that can reject proposals, which ties the effect to rejection without regeneration rather than to memory.

X. DISCUSSION

A. Memory

Scoped long-term memory is what makes long-range recall possible: without it recall beyond the 8-turn buffer is zero, and a rolling context of equal budget forgets every fact older than 10 turns. Against a strong flat vector store the advantage narrows to a non-significant 2.8 points at a 27% higher token cost. Scoping's measurable benefits were ranking (MRR), distractor exclusion and stability across seeds and backbones. The benchmark always probes a fact with the NPC it was told to, at that NPC's location, which favours scoping and gives the fallback little to do; the value of the buffer and fallback in free play, where facts are recalled elsewhere, is not measured here. Proposition 2 identifies a further risk at scale: once a store holds many similar out-of-scope entries, post-filtering the global top-30 can drop in-scope memories, which a filtered index avoids [26].

B. State control

The barrier works where it has a rule and is only as good as its rule set. Bounding currency gains, validating per turn rather than per proposal, and checking NPC relocation would close the gaps observed. Blocking without regenerating trades structural integrity for narrative consistency; regenerating or annotating the reply on rejection is the obvious fix and carries a latency cost.

C. Implications for practitioners

Treat LLM output as untrusted input to a state machine; keep the reducer defensive even behind a validator; audit with a checker that does not share the validator's code; and recover by snapshot plus suffix, never by snapshot alone.

XI. LIMITATIONS AND THREATS TO VALIDITY

1) **Sample size.** Level 2 of the ladder (63 recall sessions, 490 attacks, 14 live sessions per cell) is well below the level-7 targets; live intervals are wide.
2) **Scoring.** Recall, leaks and desynchronisation are scored automatically (key words, secret keywords, refusal and arrival cues). Blinded sheets for two raters (1,250 recall, 150 persona and lore, 240 desynchronisation items) are exported, but no human labels, Cohen's κ or LLM-judge agreement exist yet.

3) **Worlds.** W1 is the development world, W4 is templated, and W3 was authored by the notebook author rather than an independent contributor.
4) **Scripted players.** Fixed scripts remove adaptation confounds but do not react to NPCs; player experience needs a user study.
5) **Backbones.** Two self-hosted models of one family with capped thinking; the game's default hosted backbone was not evaluated, and its latency is not reproduced.
6) **Baselines.** B4 (scripted FSM) and B5 (LLM-managed paging memory) were not run, and the baselines may be weaker than tuned production systems; their code and prompts are in the notebook.
7) **Base paper.** The recency and importance terms and the reflection of Generative Agents were not reimplemented as a baseline, so the comparison with the base paper is architectural except for the memory ablation and the relevance-only analogue B2.
8) **Secrets.** The model never receives NPC secrets, so leak rates do not measure secret keeping.
9) **Violation metric.** Equation (6) counts flagged turns over transitions; persistent corruption inflates direct-write rates, so live violation rates compare conditions but are not counts of distinct violations.
10) **Memory scale.** Exact search with pruning at 1,000 entries; campaigns of thousands of turns need summarisation or hierarchical memory.

A. Threats to validity

Internal: inputs, prompts, schemas and backbones are identical across conditions, request seeds depend only on the probe or turn, and probe outputs are committed in all three modes, so control comparisons are exactly paired. *Construct*: violations are measured by an independent oracle, but its O8 bound (+50) is a design choice the system never encoded; recall is key-word matched on invented values. *External*: claims are restricted to the tested worlds and backbones. *Conclusion*: hypotheses were stated in advance, the confirmatory family is Holm-corrected, and both unsupported hypotheses are reported. The factorial p-values are approximate posterior summaries from a variational fit.

XII. Conclusion

LLM NPCs need to remember what happened, respect the rules of the world, and do both at interactive cost. We tested an engine that pairs scoped dual-tier memory with a validated, event-sourced state against independent baselines, in a factorial design with ablations, on seven worlds, with adversarial probes scored by an oracle that shares no code with the validator. Three claims are supported. Long-term retrieval scoped to the current place and person keeps recall high and flat over 160 turns where a rolling context of equal size forgets everything after ten, and it ranks the right memory higher than flat vector memory. A pre-commit barrier over an event-sourced state blocked every movement, fabrication, theft and injection attack the model attempted without rejecting lawful requests, and the event log reproduced the live state exactly. Both effects held on every held-out world family and on a smaller backbone. Two claims are not supported: the memory design is not clearly better than flat vector memory at its token cost, and memory and control are not independent. The paired, oracle-audited protocol also exposed concrete defects (unbounded currency gains, a lossy load path, persistent corruption without the reducer, and dialogue that contradicts rejected changes) that a validator-scored evaluation would have missed.

A. Future work

Fix the defects found (bound currency gains and validate per turn; fold the logged suffix on load; event-source the active NPC; align the prompt's trust range; pass secrets above the trust threshold); regenerate dialogue on rejection; rerun at the full sample size with an independently authored W3, human annotation, the hosted backbone and other model families, adding B4, B5 and the base paper's recency–importance retrieval with reflection; probe recall away from the place a fact was told; validate narrative plausibility, not only structural legality; and evaluate filtered or hierarchical indices for long campaigns.

B. Data and licences

W2 content derives from LIGHT under CC BY-NC 4.0, so the released W2 worlds are for non-commercial use. Both evaluated backbones are Apache 2.0.

APPENDIX A
SUPPLEMENTARY RESULTS

This appendix holds results that the body states in text and that duplicate another table or figure. Table XVI gives recall by fact age for every condition, the values plotted in Fig. 5.

TABLE XVI
RECALL (%) BY FACT AGE ON HELD-OUT WORLDS. AGES 80 AND 160 OCCUR ONLY IN 100- AND 200-TURN SESSIONS.

Condition	5	10	20	40	80	160
B0 Full history	75.0 [67.6, 82.4]	77.8 [69.4, 85.2]	78.7 [71.3, 86.1]	75.0 [65.7, 83.3]	86.1 [79.2, 93.1]	88.9 [77.8, 97.2]
B1 Rolling, B	86.1 [79.6, 91.7]	65.7 [55.6, 75.9]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
B1 Rolling, $2B$	81.5 [74.1, 88.0]	78.7 [69.4, 87.0]	75.0 [65.7, 83.3]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
B2 Vector memory	85.2 [78.7, 91.7]	82.4 [75.9, 88.9]	88.9 [82.4, 94.4]	80.6 [73.1, 88.0]	84.7 [75.0, 93.1]	86.1 [75.0, 94.4]
B3 Generic RAG	72.2 [63.0, 80.6]	69.4 [60.2, 78.7]	66.7 [57.4, 75.9]	68.5 [59.3, 77.8]	62.5 [50.0, 75.0]	44.4 [30.6, 58.3]
F4 Proposed	96.3 [92.6, 99.1]	85.2 [78.7, 91.7]	87.0 [80.6, 92.6]	89.8 [84.3, 94.4]	83.3 [75.0, 90.3]	91.7 [83.3, 100.0]
A1 No long-term memory	85.2 [77.8, 91.7]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]	0.0 [0.0, 0.0]
A2 No short-term buffer	86.1 [79.6, 91.7]	88.0 [82.4, 93.5]	90.7 [85.2, 95.4]	91.7 [87.0, 96.3]	84.7 [76.4, 93.1]	88.9 [77.8, 97.2]
A3 No scoping	94.4 [89.8, 98.1]	88.9 [82.4, 94.4]	82.4 [75.9, 88.9]	79.6 [71.3, 87.0]	80.6 [70.8, 90.3]	88.9 [77.8, 97.2]
A4 No fallback	94.4 [89.8, 98.1]	85.2 [78.7, 91.7]	88.0 [81.5, 94.4]	90.7 [85.2, 95.4]	84.7 [77.8, 91.7]	91.7 [83.3, 100.0]
n (F4 probes)	108	108	108	108	72	36

Table XVII lists retrieval quality and secondary memory metrics for every memory condition.

TABLE XVII
RETRIEVAL QUALITY AND SECONDARY MEMORY METRICS (HELD-OUT WORLDS). "CONFUSED": ANSWERED WITH THE DISTRACTOR'S VALUE. NO PROMPT REACHED THE 16,384-CHARACTER CAP.

Condition	Gold in prompt	Distractor in prompt	Confused	Recall@6	Parse success	In / out tok. per 100 turns
F4	100.0 [100.0, 100.0]	57.0 [52.9, 61.4]	0.9 [0.2, 1.8]	100.0 [100.0, 100.0]	98.1 [97.1, 99.1]	139,898 / 15,394
B0	100.0 [100.0, 100.0]	100.0 [100.0, 100.0]	3.7 [1.9, 5.8]	–	98.9 [98.0, 99.6]	431,032 / 14,117
B1, B	35.7 [33.2, 38.3]	59.6 [56.0, 63.3]	14.4 [11.4, 17.6]	–	99.1 [98.3, 99.8]	139,831 / 15,574
B1, $2B$	57.4 [54.1, 60.8]	74.3 [70.9, 77.8]	11.3 [9.0, 13.7]	–	99.6 [99.1, 100.0]	182,309 / 14,164
B2	99.1 [98.2, 99.8]	90.0 [87.4, 92.6]	0.2 [0.0, 0.6]	99.1 [98.2, 99.8]	95.9 [93.8, 97.8]	110,154 / 16,000
B3	98.0 [96.8, 99.0]	87.6 [84.7, 90.3]	7.4 [5.4, 9.4]	98.0 [96.8, 98.9]	98.5 [97.4, 99.4]	120,923 / 15,349
A1	20.0 [19.1, 20.9]	52.6 [48.9, 56.4]	20.6 [17.7, 23.6]	–	99.4 [98.7, 100.0]	130,763 / 15,131
A2	100.0 [100.0, 100.0]	10.2 [7.6, 13.0]	0.0 [0.0, 0.0]	100.0 [100.0, 100.0]	98.3 [97.1, 99.4]	108,486 / 14,941
A3	98.9 [98.0, 99.6]	90.7 [88.7, 92.9]	0.2 [0.0, 0.6]	98.7 [97.7, 99.5]	98.9 [98.0, 99.6]	141,690 / 15,460
A4	100.0 [100.0, 100.0]	52.6 [49.1, 56.3]	1.1 [0.4, 2.0]	100.0 [100.0, 100.0]	98.0 [96.9, 98.9]	138,781 / 15,457

Fig. 9 plots the retrieval metrics of Table XVII and the gold-in-prompt rate by fact age.




Fig. 9. Left: MRR@6 and Recall@6 of the gold memory for each retrieval condition (held-out). Recall@6 is near 1 everywhere; MRR separates scoped (F4, A2, A4) from unscoped (A3, B2, B3) retrieval. Right: share of probes whose gold turn reached the prompt, by fact age, which bounds recall from above.

Table XVIII lists the sensitivity sweeps plotted in Fig. 6.

TABLE XVIII
SENSITIVITY SWEEPS (RETRIEVAL ONLY; W1 AND W2A TO W2C, HORIZONS 100 AND 200; 880 PROBES PER SETTING).

	buffer 4	buffer 8	buffer 16	$k = 3$	$k = 12$	$\theta = 0$	$\theta = 6$
Gold in prompt	0.9989	0.9989	0.9989	0.9648	1.0000	1.0000	0.9955
MRR@k	0.8990	0.8990	0.8990	0.8390	0.9124	0.9227	0.8303

Fig. 10 plots the seed variance of Table VI and the recall of both backbones.




Fig. 10. Left: recall over all ages for three sampling seeds on the calibration sessions; F4's three points nearly coincide, while B2 varies by about 8 points. Right: recall at fact age 20 or more on the secondary-backbone subset for K2-Horizon-7B and K2-Horizon-3.7B; F4 degrades least with the smaller model.

Fig. 11 plots the attack success and validator errors of Table VII.




Fig. 11. Left: attack success by category when the same model outputs are committed by direct writes, by the reducer without validation (A5), and through the barrier. Right: the barrier's false rejection of lawful twins (zero in every category) and its validator gap, against the 5% bound of H4; the gap is confined to currency.

Fig. 12 plots the 2×2 cells of Table VIII.




Fig. 12. Interaction plots for the 2×2 design. Left: live recall rises with memory under either control setting. Right: violations per 100 transitions fall with the barrier under either memory setting. Near-parallel lines indicate little interaction in the raw cells; the mixed model (Table IX) nevertheless finds a significant recall interaction.

Table XIX gives the per-stage latency of the live F4 graph.

TABLE XIX
PER-STAGE LATENCY (MS) OF THE LIVE F4 GRAPH, SINGLE STREAM (24 TURNS, TWO WORLDS). ALL 24 LLM RESPONSES IN THIS STAGE CAME FROM THE RESPONSE CACHE, SO THE LLM ROW (0.09 MS AT P50) IS A CACHE LOOKUP AND IS OMITTED.

	Input	Retrieval	Prompt	Parse	Validate	Commit	Output	Local total	End to end
P50	0.002	0.174	0.123	0.087	0.031	18.428	0.011	24.921	25.006
P95	0.003	0.310	0.158	0.118	0.039	21.049	0.013	27.526	27.609
P99	0.009	0.385	0.167	0.125	0.046	30.311	0.013	37.016	37.127

Fig. 13 plots the stage latencies of Table XIX and the single-stream LLM time per condition.




Fig. 13. Left: P50 (bars) and P95 (ticks) latency of each F4 stage, single stream, log scale; the "llm" bar is a response-cache lookup (Table XIX). Right: single-stream LLM time per request for each condition's recall prompts; B2 and B3 were not reached before the stage deadline and B1×2 has one cached sample.

Fig. 14 plots the per-world effects of Table XII.




Fig. 14. Per-world effects with 95% bootstrap intervals. Left: recall gain of F4 over B1 at fact age 20 or more. Right: reduction in attack success from direct writes to the barrier (F4 context). W1 (grey) is in-distribution; every held-out world favours the system on both effects.

APPENDIX B
SAMPLE-SIZE LADDER

Table XX lists the eight pre-declared sample-size levels of Section VIII-B.

TABLE XX
PRE-DECLARED SAMPLE-SIZE LEVELS AND THE PLANNER'S ESTIMATED HOURS (METRICS/BUDGET_PLAN.CSV). LEVEL 2 WAS RUN.

Level	Sessions/(world, H)	Probes/(world, cat.)	Live/world	Recall (h)	Probes (h)	Live (h)	Seed var. (h)	Total (h)
0	1	4	1	0.84	0.70	0.99	0.66	3.66
1	2	6	1	1.73	1.08	0.99	0.66	5.13
2	**3**	**10**	**2**	**2.63**	**1.84**	**1.98**	**0.66**	**8.18**
3	4	14	2	3.53	2.60	1.98	0.66	10.09
4	6	20	3	5.33	3.75	1.98	0.66	13.48
5	10	30	4	8.92	5.65	2.97	0.66	20.94
6	20	45	6	17.89	8.51	3.97	0.66	35.68
7	40	60	10	35.84	11.37	6.93	0.66	63.03

APPENDIX C
AUDIT NOTES

Auditing the code and raw outputs against the earlier project article (docs/research_article.md) found the following. All are corrected in this paper, and the article and the repository README have since been updated to match.

- The chosen ladder level, index 2 of levels 0 to 7, is the *third* of eight levels, not the second.
- Live probes have recorded fact ages of 30 to 34 turns (`age` column of predictions/live_turns.csv), not about 20 to 32; the configured `LIVE_FACT_AGES` are not used by the script generator.
- Theft has lawful twins for 50 of 70 attacks per context (71%).
- Live violation rates above 100 per 100 transitions arise because the oracle re-flags persistent corruption on later turns (Equation (6)), not because one transition breaks several invariants: the numerator counts flagged turns.
- The factorial model is a variational-Bayes mixed GLM; its "SE" and "p" are posterior summaries (Section IV-F).

All other values in the earlier article match the run outputs.

REFERENCES

[1] R. Gallotta, G. Todd, M. Zammit, S. Earle, A. Liapis, J. Togelius, and G. N. Yannakakis, "Large language models and games: A survey and roadmap," *IEEE Transactions on Games*, 2024. [Online]. Available: https://doi.org/10.1109/TG.2024.3461510

[2] N. F. Liu, K. Lin, J. Hewitt, A. Paranjape, M. Bevilacqua, F. Petroni, and P. Liang, "Lost in the middle: How language models use long contexts," *Transactions of the Association for Computational Linguistics*, vol. 12, pp. 157–173, 2024. [Online]. Available: https://doi.org/10.1162/tacl_a_00638

[3] A. Maharana, D.-H. Lee, S. Tulyakov, M. Bansal, F. Barbieri, and Y. Fang, "Evaluating very long-term conversational memory of LLM agents," in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024, pp. 13 851–13 870. [Online]. Available: https://doi.org/10.18653/v1/2024.acl-long.747

[4] D. Wu, H. Wang, W. Yu, Y. Zhang, K.-W. Chang, and D. Yu, "LongMemEval: Benchmarking chat assistants on long-term interactive memory," in *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. [Online]. Available: https://proceedings.iclr.cc/paper_files/paper/2025/hash/d813d324dbf0598bbdc9c8e79740ed01-Abstract-Conference.html

[5] R. Wang, G. Todd, Z. Xiao, X. Yuan, M.-A. Côté, P. Clark, and P. Jansen, "Can language models serve as text-based world simulators?" in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, 2024, pp. 1–17. [Online]. Available: https://doi.org/10.18653/v1/2024.acl-short.1

[6] N. Kim and S. Schuster, "Entity tracking in language models," in *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2023, pp. 3835–3855. [Online]. Available: https://doi.org/10.18653/v1/2023.acl-long.213

[7] Y. Ma, J. Yan, B. Shi, K. H. Kam, R. Wang, X. Liu, Y. Chen, Y. Zhang, and D. F. Wong, "Can LLM agents stick to the script? A benchmark for long-horizon consistency in interactive narratives," in *Proceedings of the 43rd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 306, 2026, pp. 85 171–85 192. [Online]. Available: https://proceedings.mlr.press/v306/ma26ap.html

[8] J. S. Park, J. C. O'Brien, C. J. Cai, M. R. Morris, P. Liang, and M. S. Bernstein, "Generative agents: Interactive simulacra of human behavior," in *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*, 2023, pp. 1–22. [Online]. Available: https://doi.org/10.1145/3586183.3606763

[9] N. Shinn, F. Cassano, A. Gopinath, K. Narasimhan, and S. Yao, "Reflexion: Language agents with verbal reinforcement learning," in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2023/hash/1b44b878bb782e6954cd888628510e90-Abstract-Conference.html

[10] J. Urbanek, A. Fan, S. Karamcheti, S. Jain, S. Humeau, E. Dinan, T. Rocktäschel, D. Kiela, A. Szlam, and J. Weston, "Learning to speak and act in a fantasy text adventure game," in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019, pp. 673–683. [Online]. Available: https://doi.org/10.18653/v1/D19-1062

[11] P. Ammanabrolu, J. Urbanek, M. Li, A. Szlam, T. Rocktäschel, and J. Weston, "How to motivate your dragon: Teaching goal-driven agents to speak and act in fantasy worlds," in *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, 2021, pp. 807–833. [Online]. Available: https://doi.org/10.18653/v1/2021.naacl-main.64

[12] M.-A. Côté, Á. Kádár, X. Yuan, B. Kybartas, T. Barnes, E. Fine, J. Moore, M. Hausknecht, L. El Asri, M. Adada, W. Tay, and A. Trischler, "TextWorld: A learning environment for text-based games," in *Computer Games (CGW 2018)*, ser. Communications in Computer and Information Science, vol. 1017. Springer, 2019, pp. 41–75. [Online]. Available: https://doi.org/10.1007/978-3-030-24337-1_3

[13] M. Hausknecht, P. Ammanabrolu, M.-A. Côté, and X. Yuan, "Interactive fiction games: A colossal adventure," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 34, 2020, pp. 7903–7910. [Online]. Available: https://doi.org/10.1609/aaai.v34i05.6297

[14] C. Callison-Burch, G. Singh Tomar, L. J. Martin, D. Ippolito, S. Bailis, and D. Reitter, "Dungeons and dragons as a dialog challenge for artificial intelligence," in *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2022, pp. 9379–9393. [Online]. Available: https://doi.org/10.18653/v1/2022.emnlp-main.637

[15] N. Akoury, S. Wang, J. Whiting, S. Hood, N. Peng, and M. Iyyer, "STORIUM: A dataset and evaluation platform for machine-in-the-loop story generation," in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020, pp. 6470–6484. [Online]. Available: https://doi.org/10.18653/v1/2020.emnlp-main.525

[16] J. Xu, A. Szlam, and J. Weston, "Beyond goldfish memory: Long-term open-domain conversation," in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022, pp. 5180–5197. [Online]. Available: https://doi.org/10.18653/v1/2022.acl-long.356

[17] W. Zhong, L. Guo, Q. Gao, H. Ye, and Y. Wang, "MemoryBank: Enhancing large language models with long-term memory," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, 2024, pp. 19 724–19 731. [Online]. Available: https://doi.org/10.1609/aaai.v38i17.29946

[18] B. Jiménez Gutiérrez, Y. Shu, Y. Gu, M. Yasunaga, and Y. Su, "HippoRAG: Neurobiologically inspired long-term memory for large language models," in *Advances in Neural Information Processing Systems*, vol. 37, 2024. [Online]. Available: https://doi.org/10.52202/079017-1902

[19] W. Xu, Z. Liang, K. Mei, H. Gao, J. Tan, and Y. Zhang, "A-Mem: Agentic memory for LLM agents," in *Advances in Neural Information Processing Systems*, vol. 38, 2025. [Online]. Available: https://doi.org/10.52202/085713-0593

[20] Z. Tan, J. Yan, I.-H. Hsu, R. Han, Z. Wang, L. Le, Y. Song, Y. Chen, H. Palangi, G. Lee, A. R. Iyer, T. Chen, H. Liu, C.-Y. Lee, and T. Pfister, "In prospect and retrospect: Reflective memory management for long-term personalized dialogue agents," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 8416–8439. [Online]. Available: https://doi.org/10.18653/v1/2025.acl-long.413

[21] J. Liu, Y. Su, P. Xia, S. Han, Z. Zheng, C. Xie, M. Ding, and H. Yao, "SimpleMem: Efficient lifelong memory for LLM agents," in *Proceedings of the 43rd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 306, 2026, pp. 78 500–78 513. [Online]. Available: https://proceedings.mlr.press/v306/liu26dx.html

[22] T. R. Sumers, S. Yao, K. Narasimhan, and T. L. Griffiths, "Cognitive architectures for language agents," *Transactions on Machine Learning Research*, 2024. [Online]. Available: https://openreview.net/forum?id=1i6ZCvflQJ

[23] Z. Zhang, Q. Dai, X. Bo, C. Ma, R. Li, X. Chen, J. Zhu, Z. Dong, and J.-R. Wen, "A survey on the memory mechanism of large language model-based agents," *ACM Transactions on Information Systems*, vol. 43, no. 6, pp. 1–47, 2025. [Online]. Available: https://doi.org/10.1145/3748302

[24] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel, S. Riedel, and D. Kiela, "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 9459–9474. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html

[25] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. Narasimhan, and Y. Cao, "ReAct: Synergizing reasoning and acting in language models," in *The Eleventh International Conference on Learning Representations (ICLR)*, 2023. [Online]. Available: https://openreview.net/forum?id=WE_vluYUL-X

[26] S. Gollapudi, N. Karia, V. Sivashankar, R. Krishnaswamy, N. Begwani, S. Raz, Y. Lin, Y. Zhang, N. Mahapatro, P. Srinivasan, A. Singh, and H. V. Simhadri, "Filtered-DiskANN: Graph algorithms for approximate nearest neighbor search with filters," in *Proceedings of the ACM Web Conference 2023 (WWW)*, 2023, pp. 3406–3416. [Online]. Available: https://doi.org/10.1145/3543507.3583552

[27] S. Kambhampati, K. Valmeekam, L. Guan, M. Verma, K. Stechly, S. Bhambri, L. P. Saldyt, and A. B. Murthy, "Position: LLMs can't plan, but can help planning in LLM-modulo frameworks," in *Proceedings of the 41st International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 235, 2024, pp. 22 895–22 907. [Online]. Available: https://proceedings.mlr.press/v235/kambhampati24a.html

[28] S. Geng, M. Josifoski, M. Peyrard, and R. West, "Grammar-constrained decoding for structured NLP tasks without finetuning," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language*

Processing (EMNLP), 2023, pp. 10 932–10 952. [Online]. Available: https://doi.org/10.18653/v1/2023.emnlp-main.674

[29] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023, pp. 79–90. [Online]. Available: https://doi.org/10.1145/3605764.3623985

[30] M. Overeem, M. Spoor, S. Jansen, and S. Brinkkemper, "An empirical characterization of event sourced systems and their schema evolution: Lessons from industry," *Journal of Systems and Software*, vol. 178, p. 110970, 2021. [Online]. Available: https://doi.org/10.1016/j.jss.2021.110970

[31] S. Buongiorno, L. Klinkert, Z. Zhuang, T. Chawla, and C. Clark, "PANGeA: Procedural artificial narrative using generative AI for turn-based, role-playing video games," in *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE)*, vol. 20, 2024, pp. 156–166. [Online]. Available: https://doi.org/10.1609/aiide.v20i1.31876

[32] A. Phillips, J. Lang, and D. Mould, "Goal-oriented interactions in games using LLMs," *IEEE Transactions on Games*, vol. 17, no. 2, pp. 510–521, 2025. [Online]. Available: https://doi.org/10.1109/TG.2024.3515807

[33] V. Kumaran, J. Rowe, B. Mott, and J. Lester, "SceneCraft: Automating interactive narrative scene generation in digital games with large language models," in *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE)*, vol. 19, no. 1, 2023, pp. 86–96. [Online]. Available: https://doi.org/10.1609/aiide.v19i1.27504

[34] A. Zhu, L. Martin, A. Head, and C. Callison-Burch, "CALYPSO: LLMs as dungeon master's assistants," in *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE)*, vol. 19, no. 1, 2023, pp. 380–390. [Online]. Available: https://doi.org/10.1609/aiide.v19i1.27534

[35] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence embeddings using Siamese BERT-networks," in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019, pp. 3980–3990. [Online]. Available: https://doi.org/10.18653/v1/D19-1410

[36] W. Wang, F. Wei, L. Dong, H. Bao, N. Yang, and M. Zhou, "MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers," in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 5776–5788. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2020/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html

[37] J. Johnson, M. Douze, and H. Jégou, "Billion-scale similarity search with GPUs," *IEEE Transactions on Big Data*, vol. 7, no. 3, pp. 535–547, 2021. [Online]. Available: https://doi.org/10.1109/TBDATA.2019.2921572

[38] B. Efron, "Bootstrap methods: Another look at the jackknife," *The Annals of Statistics*, vol. 7, no. 1, pp. 1–26, 1979. [Online]. Available: https://doi.org/10.1214/aos/1176344552

[39] C. A. Field and A. H. Welsh, "Bootstrapping clustered data," *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, vol. 69, no. 3, pp. 369–390, 2007. [Online]. Available: https://doi.org/10.1111/j.1467-9868.2007.00593.x

[40] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947. [Online]. Available: https://doi.org/10.1007/BF02295996

[41] F. Wilcoxon, "Individual comparisons by ranking methods," *Biometrics Bulletin*, vol. 1, no. 6, pp. 80–83, 1945. [Online]. Available: https://doi.org/10.2307/3001968

[42] S. Holm, "A simple sequentially rejective multiple test procedure," *Scandinavian Journal of Statistics*, vol. 6, no. 2, pp. 65–70, 1979. [Online]. Available: https://www.jstor.org/stable/4615733

[43] S. Seabold and J. Perktold, "Statsmodels: Econometric and statistical modeling with Python," in *Proceedings of the 9th Python in Science Conference*, 2010, pp. 92–96. [Online]. Available: https://doi.org/10.25080/Majora-92bf1922-011

[44] W. Kwon, Z. Li, S. Zhuang, Y. Sheng, L. Zheng, C. H. Yu, J. E. Gonzalez, H. Zhang, and I. Stoica, "Efficient memory management for large language model serving with PagedAttention," in *Proceedings of the 29th Symposium on Operating Systems Principles (SOSP)*, 2023, pp. 611–626. [Online]. Available: https://doi.org/10.1145/3600006.3613165