

DynoSure LoggerV1

Model: LoggerV1 (Standalone CAN Data Logger)

The DynoSure LoggerV1 is a standalone CAN bus data logger designed specifically to capture CAN 2.0 traffic to onboard storage without requiring a connected PC during operations. It logs data in the industry-standard Vector ASC file format, avoiding restrictive closed ecosystems and vendor lock-in.

Specifications

Parameter	Details
CAN Protocols	CAN 2.0A (11-bit ID), CAN 2.0B (29-bit extended ID)
Storage	Onboard microSD card (FAT32 filesystem)
Log Format	Vector ASC (standard ASCII format)
USB Interface	USB 2.0 (Mass Storage Device / Card Reader mode)
Power Modes	• Logging Mode: Requires +12V DC external supply • USB Mode: USB-powered (acts as SD card reader)
Firmware Update	User-programmable at customer end

Baud Rate Configuration

Bitrates are selected by creating a simple configuration.txt file in the root of the microSD card. The file should contain one of the following numbers:


Key Value	Resulting CAN Bus Speed
1	500 kbps (Standard default)
2	1 Mbps (High speed CAN)
3	250 kbps (Medium speed CAN)

DynoSure LoggerV1



Standalone CAN Data Logger with Raspberry Pi Pico 2

DB9 CAN & Power Pinout



DB9 Pin	Assignment
Pin 2	CAN-L (CAN Low)
Pin 3	GND (Power Ground)
Pin 7	CAN-H (CAN High)
Pin 9	+12V DC (Power Input)
Others	Not Connected

Operation Modes Summary:

- **Logging Mode:** Insert card, connect +12V power supply via Pin 9 and Pin 3 on DB9. Device starts logging automatically.
- **USB Mode:** Plug into PC via USB cable. Behaves as an external card reader to copy logs.

Inquiries & Ordering:

Email: dynosure.india@gmail.com
Mobile: +91 9898204057 (Mukesh Patel)