

# DynoSure SLCANv1

**Model:** SLCANv1 (USB-to-CAN Adapter)

The DynoSure SLCANv1 adapter provides a reliable and convenient connection between a PC and a CAN (Controller Area Network) bus. Based on the open-source CANable2 firmware and the Lawicel SLCAN protocol, it exposes the CAN interface as a standard virtual COM port, simplifying integration with existing tools and reducing software overhead.

## Specifications

| Parameter         | Details                                             |
|-------------------|-----------------------------------------------------|
| Microcontroller   | STM32G4 Series, 170 MHz                             |
| CAN Protocols     | CAN 2.0A (11-bit), CAN 2.0B (29-bit), CAN-FD        |
| USB Interface     | USB 2.0 Full-Speed (compatible with USB 1.1 / 3.0)  |
| Standard Bitrates | 5 kbps to 1 Mbps                                    |
| CAN-FD Bitrates   | Up to 8 Mbps data phase bitrates                    |
| Power Supply      | USB-powered (no external supply required)           |
| Compatibility     | Windows & Linux (exposes standard Virtual COM Port) |
| Software Support  | Compatible with BusMaster, Python, and C++ SDKs     |
| Operating Temp    | Extended range suitable for industrial environments |



## DB9 Pinout Assignment



| DB9 Pin | Assignment                     |
|---------|--------------------------------|
| Pin 1   | Not Connected                  |
| Pin 2   | <b>CAN-L</b> (CAN Low)         |
| Pin 3   | <b>GND</b> (Ground)            |
| Pin 4   | Not Connected                  |
| Pin 5   | Not Connected                  |
| Pin 6   | <b>GND</b> (Ground, secondary) |
| Pin 7   | <b>CAN-H</b> (CAN High)        |
| Pin 8   | Not Connected                  |
| Pin 9   | Not Connected                  |

**Inquiries & Ordering:**  
Email: [dynosure.india@gmail.com](mailto:dynosure.india@gmail.com)  
Mobile: **+91 9898204057 (Mukesh Patel)**  
Mobile 2: **+91 9422556559**