


# DynoSure SLCAN GPIO

**Model:** SLCAN GPIO (USB-to-CAN with 8-ch GPIO Control)

The DynoSure SLCAN GPIO combines a full-featured USB-to-CAN adapter with 8 configurable GPIO outputs. This gives hardware developers and test engineers both CAN bus communication and physical hardware control in a single compact device. Exposes CAN standard interfaces and digital outputs directly through internal messaging controls.



## Specifications

| Parameter        | Details                                        |
|------------------|------------------------------------------------|
| Microcontroller  | STM32G4 Series, 170 MHz                        |
| CAN Protocols    | CAN 2.0A (11-bit), CAN 2.0B (29-bit), CAN-FD   |
| USB Interface    | USB 2.0 Full-Speed                             |
| GPIO Channels    | 8 Configurable Digital Outputs                 |
| Power Supply     | USB-powered (no external supply required)      |
| Compatibility    | Windows & Linux (Virtual COM Port)             |
| Software Support | BusMaster, Python, C++ SDKs                    |
| GPIO Control     | Exposes GPIO via internal CAN message commands |

## GPIO Control Protocol

The 8 GPIO outputs are controlled by sending a special CAN command message. This message is processed internally by the firmware and is **not** transmitted on the physical CAN bus.

| Field  | Value / Description                                                |
|--------|--------------------------------------------------------------------|
| CAN ID | 0x1FFFFFF (Extended 29-bit ID)                                     |
| DLC    | 2                                                                  |
| Byte 0 | GPIO States (Bit 0 = GPIO 0 ... Bit 7 = GPIO 7). 1 = HIGH, 0 = LOW |
| Byte 1 | 0xAA (Fixed GPIO command identifier)                               |

## DB9 CAN Pinout



| DB9 Pin | Assignment       |
|---------|------------------|
| Pin 2   | CAN-L (CAN Low)  |
| Pin 3   | GND (Ground)     |
| Pin 7   | CAN-H (CAN High) |
| Pin 6   | GND (Ground)     |
| Others  | Not Connected    |

## GPIO Auxiliary Port Pinout

| Aux Pin | Assignment       |
|---------|------------------|
| Pin 1   | VCC (+5V Out)    |
| Pin 2-9 | GPIO 0 to GPIO 7 |
| Pin 10  | GND (Ground)     |

**Inquiries & Ordering:**  
Email: [dynosure.india@gmail.com](mailto:dynosure.india@gmail.com)  
Mobile: +91 9898204057 (Mukesh Patel)