

DynoSure SLCANv1

Model: SLCANv1 (USB-to-CAN Adapter)


The DynoSure SLCANv1 adapter provides a reliable and convenient connection between a PC and a CAN (Controller Area Network) bus. Based on the open-source CANable2 firmware and the Lawicel SLCAN protocol, it exposes the CAN interface as a standard virtual COM port, simplifying integration with existing tools and reducing software overhead.

Specifications

Parameter	Details
Microcontroller	STM32G4 Series, 170 MHz
CAN Protocols	CAN 2.0A (11-bit), CAN 2.0B (29-bit), CAN-FD
USB Interface	USB 2.0 Full-Speed (compatible with USB 1.1 / 3.0)
Standard Bitrates	5 kbps to 1 Mbps
CAN-FD Bitrates	Up to 8 Mbps data phase bitrates
Power Supply	USB-powered (no external supply required)
Compatibility	Windows & Linux (exposes standard Virtual COM Port)
Software Support	Compatible with BusMaster, Python, and C++ SDKs
Operating Temp	Extended range suitable for industrial environments



DB9 Pinout Assignment



DB9 Pin	Assignment
Pin 1	Not Connected
Pin 2	CAN-L (CAN Low)
Pin 3	GND (Ground)
Pin 4	Not Connected
Pin 5	Not Connected
Pin 6	GND (Ground, secondary)
Pin 7	CAN-H (CAN High)
Pin 8	Not Connected
Pin 9	Not Connected

Inquiries & Ordering:
Email: dynosure.india@gmail.com
Mobile: **+91 9898204057 (Mukesh Patel)**
Mobile 2: **+91 9422556559**