BCSE306L Artificial Intelligence

PROJECT REPORT

on

Adaptive Network Load Balancing and Dynamic Traffic Optimization System Using Q-Learning Reinforcement Learning

Prepared by

Rishit Bhagat - 24BDS0152
Parth Mudpe - 24BDS0353

Under the supervision of

Dr. Ramesh Babu Vemuluri,

Associate Professor,



VIT®
Vellore Institute of Technology
(Deemed to be University under section 3 of UGC Act, 1956)

School of Computer Science and Engineering
Vellore Institute of Technology, Vellore.

October 28, 2026

Table of Contents

Abstract
1. Introduction, Scientific / Technical Principle Note
2. Literature and Reference Log
3. Concept Sketches, Equations, and Models
4. Feasibility Calculation Sheet
5. Problem Statement and Objectives
6. Use Case and Stakeholder Definition
7. Functional / Performance Requirement Sheet
8. Analytical and Desk Study Report
9. Component Identification and Characterization Sheet
10. First-Pass Performance Prediction Document
11. Early Simulation Output (Feasibility Evidence)
12. Initial Qualitative Risk List
13. Lab Test / Simulation Report for Critical Functions
14. Analytical Model Validation Document
15. Conclusion
16. References

Abstract

Network load balancing is an essential operational mechanism in distributed systems and cloud data centers to distribute incoming client traffic efficiently across multiple computing resources. Traditional dispatching heuristics, such as Round Robin, Weighted Round Robin, Least Connections, and static multi-factor formulas, execute deterministic selection rules that cannot adapt dynamically to non-stationary workloads, varying service times, or sudden server impairments. In this case study, we develop an adaptive, intelligent load balancing system driven by tabular Q-Learning reinforcement learning. The Q-Learning agent continuously observes discrete state representations of candidate servers—incorporating active worker slot occupancy, waiting queue fullness, processing capacity ratio, and baseline network latency—and selects the optimal server action to minimize end-to-end response time, prevent buffer overflows, and maximize overall throughput. Trained across twenty-five simulated operational episodes with epsilon-greedy exploration, the agent converges to a robust policy without requiring manual heuristic weight tuning. Controlled benchmark experiments under identical workloads demonstrate that Q-Learning matches or outperforms traditional algorithms: under high traffic (2000 requests), it achieves an average response latency of 166.9 ms and zero dropped requests (surpassing Round Robin at 236.3 ms with 117 drops); under server failure and recovery conditions, it successfully yields zero packet drops compared to 5–8 dropped requests in conventional schemes; and under normal traffic, it delivers the lowest mean response time of 155.3 ms. The findings validate that reinforcement learning provides self-optimizing, fault-tolerant dispatching suitable for next-generation autonomous network infrastructure.

1.Introduction

In modern distributed computing infrastructures, cloud platforms, and large-scale web services, load balancers act as central decision-making nodes responsible for routing high-volume client requests across heterogeneous server clusters. As application demands become increasingly dynamic and bursty, static dispatching algorithms fail to maintain optimal resource utilization, frequently leading to localized queue congestion, prolonged latency, and unhandled request drops. This project investigates the application of reinforcement learning (RL) to develop an intelligent, self-optimizing network load balancer that learns optimal routing policies through direct interaction with its execution environment.

1.1 Domain Information

The intersection of artificial intelligence and distributed network optimization represents an active domain of contemporary systems engineering. Within cloud and web infrastructure, load balancing determines quality of service (QoS) and service level agreement (SLA) compliance. Reinforcement learning provides a mathematical foundation where an autonomous agent operates in a Markov Decision Process (MDP) framework, observing system states, executing server selection actions, and receiving numerical feedback signals based on processing completion or failure. By framing load balancing as an RL problem, the system dynamically balances workloads across heterogeneous capacities without requiring human operators to hand-craft static routing rules.

1.2 Software Libraries Used

Library / Technology	Version	Functional Role in Project
Python 3	3.10+	Primary programming language for system architecture and simulation logic
NumPy	≥ 1.24	Stochastic traffic arrival generation, state discretization, and vector math
Matplotlib	≥ 3.7	Generation of analytical performance charts and live GUI visual telemetry
Tkinter	Standard Library	Desktop graphical dashboard, live server card metrics, and interactive controls

1.3 Contributions by Team Members

Development & Research Task	Parth Mudpe (24BDS0353)	Rishit Bhagat (24BDS0152)
AI Load Balancer System Architecture & Discrete-Time Simulator	✓	✓
Q-Learning Reinforcement Learning Algorithm & Bellman Update		✓
Server State Feature Engineering & State Discretization Logic	✓	✓
Reward Function Formulation (Latency Penalties & Drop Deterrence)		✓
Traditional Baseline Algorithms (Round Robin, WRR, Least Connections, MF)	✓	✓
Training Loop with Epsilon-Greedy Exploration & Epsilon Decay		✓
Fault-Tolerance, Dynamic Server Failure, and Recovery Mechanics	✓	✓
Comprehensive Benchmark Experimentation (High, Burst, Normal, Failure)	✓	✓
Graphical Dashboard, Live Telemetry Charts, and Visualization Suite	✓	
Project Case Study Report, Mathematical Modeling & Verification	✓	✓

1.4 Challenges Faced

- **State Space Discretization:** Designing continuous state variables (CPU load, queue length) caused unbounded table dimensionality. Resolved by designing an optimal 4-dimensional discrete state tuple (5×5×3×2 = 150 discrete states) that captures essential server dynamics with fast convergence.
- **Reward Scaling & Convergence Stability:** Raw millisecond response times caused extreme gradient divergence in Q-value accumulation. Resolved by normalizing latencies to fractional seconds and establishing an asymmetric penalty (-10.0) for dropped requests.
- **Training vs. Evaluation Separation:** Ensuring the agent learned general routing policies rather than memorizing traffic sequences. Resolved by establishing strict pseudo-random seed separation (training across seeds 1000–1024, testing on seed 42).
- **Simulation Responsiveness:** Executing 25 training episodes inside an interactive desktop application. Resolved through optimized NumPy vectorized operations that execute full training in under 3 seconds.

1.5 Scientific / Technical Principle Note

The core technical principle governing this project is Model-Free Temporal-Difference (TD) Reinforcement Learning, specifically Watkins' Q-Learning algorithm. The operational environment is formalized as a finite Markov Decision Process defined by the 4-tuple (S, A, P, R). Rather than requiring prior transition probabilities P(s'|s, a), the agent learns an action-value function Q(s, a) directly from simulated transition samples:

$$Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \alpha \left[r_t + \gamma \cdot \max_{a'} Q(s_{t+1}, a') - Q(s_t, a_t) \right]$$

Here, α represents the learning rate (configured to 0.10), balancing the integration of fresh observations against historical estimates. The discount factor γ (configured to 0.50) determines the weighting of expected subsequent system states. The exploration-exploitation tradeoff is governed by an epsilon-greedy policy: the agent initially explores alternative routing paths with probability ε = 0.30, decaying exponentially by 0.85 per episode down to a floor of 0.05. During testing and comparative evaluation, ε is set to 0.0, ensuring deterministic, fully exploitative, and reproducible optimal server dispatching.

2. Literature and Reference Log

The integration of reinforcement learning into distributed scheduling and traffic routing builds upon extensive theoretical and empirical foundations in artificial intelligence and systems research. The following reference log summarizes foundational papers and contemporary applications informing our system design:

[1] Watkins, C. J. C. H. (1989) Learning from Delayed Rewards. Ph.D. Thesis, University of Cambridge.

Annotation: Introduced Q-Learning as a breakthrough model-free temporal difference reinforcement learning algorithm. Proved that TD control algorithms converge to optimal policies for finite Markovian decision processes with probability 1 under persistent excitation.

[2] Watkins, C. J. C. H., & Dayan, P. (1992) Q-learning. Machine Learning, 8(3–4), 279–292.

Annotation: Provided the rigorous mathematical convergence proof for Q-learning. Established that action-value iteration converges to the optimal Q* function provided all state-action pairs are visited infinitely often and the learning rate satisfies standard Robbins-Monro conditions.

[3] Sutton, R. S., & Barto, A. G. (2018) Reinforcement Learning: An Introduction (2nd ed.). MIT Press.

Annotation: Authoritative textbook on reinforcement learning theory, defining value iteration, temporal-difference error formulations, and epsilon-greedy exploration schedules utilized directly in our system architecture.

[4] Mnih, V., et al. (2015) Human-level control through deep reinforcement learning. Nature, 518, 529–533.

Annotation: Demonstrated deep Q-networks (DQN) for high-dimensional state spaces. Reviewed to evaluate tabular versus function approximation approaches, confirming that for a bounded 150-state space, tabular Q-Learning ensures provable stability and microsecond inference without GPU overhead.

[5] Cardellini, V., Colajanni, M., & Yu, P. S. (1999) Dynamic load balancing on web-server systems. IEEE Internet Computing, 3(3), 28–39.

Annotation: Analyzed dynamic dispatching mechanisms across heterogeneous web clusters, illustrating that state-aware algorithms significantly outperform static Round Robin under non-uniform request processing loads.

[6] Alakeel, A. M. (2010) A guide to dynamic load balancing in distributed computer systems. IJCSNS, 10(6), 153–160.

Annotation: Categorized distributed load balancing paradigms into static, dynamic, and adaptive algorithms, highlighting that dynamic methods require accurate runtime metrics such as queue lengths and latency.

[7] Khiyaita, A., et al. (2012) Load balancing cloud computing: State of art. IEEE JNS2, 106–109.

Annotation: Investigated cloud resource allocation challenges and demonstrated that static weight allocation schemes in Weighted Round Robin degrade severely when virtual machine availability or background processing loads fluctuate.

[8] Yin, L., et al. (2017) A reinforcement learning-based algorithm for load balancing in cloud computing. IEEE SMC, 3033–3038.

Annotation: Implemented tabular Q-Learning for virtual machine resource allocation, achieving 8–15%

response time improvements under varying operational loads. Validated our design choice of state discretization for server dispatching.

[9] Lim, N., Majumdar, S., & Ashwood-Smith, P. (2014) MDP framework for adaptive scheduling of tasks in NFV environments. VALUETOOLS, 285–288.
Annotation: Formulated network function task dispatching as an MDP, confirming that adaptive state-action feedback loops handle transient network congestion more effectively than static policies.

[10] Mao, H., et al. (2016) Resource management with deep reinforcement learning. ACM HotNets, 50–56.
Annotation: Pioneered reinforcement learning for multi-resource cluster scheduling, establishing that machine learning agents learn efficient packing and routing strategies directly from experience without human-designed heuristics.

3. Concept Sketches, Equations, and Models

3.1 Concept Sketches

The overall system architecture and reinforcement learning interaction loop are illustrated conceptually below. Client requests arrive at the centralized load balancer, which observes the current state vector across all active servers. The Q-Learning agent queries its action-value table, selects the optimal server, dispatches the request, and receives reward feedback upon request completion or rejection.




Figure 3.1: Conceptual Architecture and Q-Learning Interaction Loop of the Proposed System

3.2 Equations

1. Server State Feature Discretization Equations:

• Load Level ($L \in \{0, 1, 2, 3, 4\}$): $L = \min(4, \lfloor(\text{Active_Slots} / \text{Total_Slots}) \times 4\rfloor)$

• Queue Level ($Q \in \{0, 1, 2, 3, 4\}$): $Q = 0$ if Queue == 0 else (4 if Queue == Max_Q else $1 + \lfloor(\text{Queue} / \text{Max_Q}) \times 3\rfloor$)

• Speed Level ($C \in \{0, 1, 2\}$): $C = 0$ if Capacity $< 0.5 \cdot C_{max}$ else (1 if Capacity $< 0.8 \cdot C_{max}$ else 2)

• Latency Level ($R \in \{0, 1\}$): $R = 0$ if Base_Latency $\leq 1.5 \cdot$ Latency_min else 1

State Space Cardinality: $|S| = 5 \times 5 \times 3 \times 2 = 150$ discrete states.

2. Temporal Difference Learning Rule:

$$\mathbf{Q(s_t, a_t) \leftarrow Q(s_t, a_t) + \alpha \cdot [\, r_t + \gamma \cdot \max_\{a'\}\, Q(s_\{t+1\}, a') - Q(s_t, a_t)\,]}$$

Where $\alpha = 0.10$, $\gamma = 0.50$, and $\text{TD_error} = r_t + \gamma \cdot \max_\{a'\}\, Q(s_\{t+1\}, a') - Q(s_t, a_t)$.

3. Reward Formulation:

$r_t = -(d_ms / 1000.0)$ [For completed requests with response time d_ms]

$r_t = -10.0$ [For rejected/dropped requests due to full queue]

3.3 Models

1. Server Queueing & Execution Model: Each server is modeled as a multi-server M/M/c/K queueing node containing parallel worker execution slots ($c = \lfloor \text{Capacity} / 10 \rfloor$) and a finite FIFO waiting queue of capacity K. When all worker slots are occupied, incoming tasks buffer in the queue. If the queue is saturated (Queue == K), incoming dispatches are permanently dropped.

2. Baseline Heuristic Models for Comparative Benchmarking: The system models five established load balancing strategies: Round Robin (cyclic scheduling), Weighted Round Robin (capacity-proportional interleaving), Least Connections (greedy minimization of active plus queued connections), Random Selection (uniform stochastic dispatching), and Multi-Factor Dynamic Selection (hand-weighted scoring across load, queue, latency, capacity, and availability).

4. Feasibility Calculation Sheet

A rigorous engineering feasibility analysis was performed to verify computational tractability, memory bounds, and runtime efficiency prior to full deployment:

Feasibility Parameter	Theoretical Calculation / Metric	Empirical Evaluation Result
State Space Memory Footprint	150 states × 8 bytes (64-bit float) = 1,200 bytes	1.2 KB (Negligible, fits in L1 CPU cache)
Action Selection Time Complexity	O(N) lookup over N servers; 4 comparisons per server	< 0.05 ms per dispatch decision
Training Computational Budget	25 episodes × 3,000 requests = 75,000 dispatch steps	2.8 seconds total wall-clock time on CPU
Convergence State Coverage	75,000 requests / 150 states ≈ 500 visits per state	100% of high/medium load states visited
Full Simulation Execution Time	2,000 requests across 1,000 discrete time ticks	0.38 seconds execution time
Hardware Requirements	Standard single-core CPU, 512 MB RAM, no GPU required	Fully functional on any academic computing system

Conclusion: The tabular Q-Learning formulation eliminates the severe training latencies and GPU requirements of deep neural networks, rendering it exceptionally feasible for embedded, edge, and academic deployment.

5. Problem Statement and Objectives

5.1 Problem Statement

Modern high-concurrency web services, microservices, and distributed cloud applications face extreme variations in incoming request rates and heterogeneous server processing capacities. Conventional load-balancing algorithms apply rigid, pre-programmed decision rules (such as round-robin cycling or static capacity weights) that fail to dynamically adjust to changing operational conditions, localized queue buildups, or unexpected hardware degradations. Consequently, weaker servers suffer queue buffer exhaustion, causing significant request drops and degraded quality of service. There is an urgent requirement for an autonomous, self-learning traffic distribution system that dynamically learns optimal server selection policies directly from operational experience to minimize response latency and eliminate request drops without requiring manual parameter recalibration.

5.2 Objectives

- **1. Mathematical Formulation:** Formulate the network load-balancing optimization challenge as a discrete Markov Decision Process incorporating realistic server metrics.
- **2. AI Algorithm Implementation:** Implement an authentic tabular Q-Learning reinforcement learning agent that updates its state-action policy online via temporal-difference learning.
- **3. Feature Engineering:** Design an expressive 4-feature state discretization scheme and a mathematically justified reward function that severely penalizes request drops and incentivizes minimal response time.
- **4. Baseline Implementations:** Implement five traditional load-balancing algorithms (Round Robin, WRR, Least Connections, Random, Multi-Factor) as rigorous experimental baselines.
- **5. Empirical Evaluation:** Conduct controlled, repeatable simulation experiments across diverse operational conditions (High Traffic, Burst Traffic, Normal Traffic, and Mid-Run Server Failure).
- **6. Performance Verification:** Verify that the Q-Learning agent matches or exceeds the performance of traditional algorithms in throughput, latency, queue occupancy, and fault resilience.

6. Use Case and Stakeholder Definition

6.1 Use Cases

- **Use Case 1: High-Volume Traffic Optimization:** A web cluster experiences sustained heavy client request volume (2000 requests over 10 s). The Q-Learning agent directs traffic away from lower-capacity nodes to high-throughput servers, keeping all queues near zero and eliminating drops.
- **Use Case 2: Sudden Traffic Burst Absorption:** An e-commerce platform receives sudden traffic surges (75% of requests arriving in a 10% time slice). The agent dynamically spreads requests across all available queue buffers to maximize throughput.
- **Use Case 3: Steady-State Low-Latency Dispatching:** Under steady, moderate traffic, the agent routes requests preferentially to low-latency servers, minimizing user response times.
- **Use Case 4: Fault Tolerance & Server Recovery:** A primary server crashes during active execution. The agent immediately suppresses routing to the failed node and intelligently redistributes traffic among remaining healthy nodes without saturating their queues.

6.2 Stakeholders

Stakeholder Group	Operational Role	Practical Value Delivered by System
Cloud Service Providers (AWS, Azure, GCP)	Infrastructure operators hosting multi-tenant services	Autonomous traffic management, reduced server over-provisioning, and improved SLA compliance
DevOps & Network Reliability Engineers	System administrators maintaining web application uptime	Self-healing fault tolerance and elimination of manual heuristic weight tuning
End Users & Web Clients	Consumers accessing distributed web services	Lower response latencies, reduced connection timeouts, and seamless service continuity
Academic & AI Researchers	Students and researchers studying applied reinforcement learning	Clear, verifiable demonstration of RL applied to dynamic systems engineering

7. Functional / Performance Requirement Sheet

7.1 Functional Requirements

Req ID	Functional Requirement Specification	Verification Status
FR-01	The Q-Learning agent must continuously update Q-values using authentic Bellman temporal difference updates.	VERIFIED & PASSED
FR-02	The system must support dynamic state discretization into a 4-feature discrete state representation.	VERIFIED & PASSED
FR-03	The agent must employ an epsilon-greedy exploration strategy during training and pure exploitation ($\varepsilon=0$) during evaluation.	VERIFIED & PASSED
FR-04	The load balancer must detect server availability states and completely avoid dispatching to failed servers.	VERIFIED & PASSED
FR-05	The simulator must execute five baseline algorithms (RR, WRR, LC, Random, MF) under identical traffic profiles.	VERIFIED & PASSED
FR-06	The desktop GUI must display live server statuses, Q-values per server, real-time queues, and performance charts.	VERIFIED & PASSED
FR-07	The system must support heterogeneous server configurations ranging from 3 to 25 concurrent servers.	VERIFIED & PASSED

7.2 Performance Requirements

Metric	Target Performance Threshold	Demonstrated System Performance
RL Training Time	Complete 25 episodes in < 10 seconds	Completed in 2.8 seconds
Decision Latency	Per-request dispatch decision in < 1 ms	0.04 ms per request (CPU)
Request Dropped Rate (High Traffic)	0 dropped requests under 2000 requests	0 dropped (Round Robin dropped 117)
Average Response Latency (High)	Competitive with best heuristic (≤ 170 ms)	166.9 ms achieved (Lowest overall)
Server Failure Recovery	Zero dropped requests during active failure	0 dropped (Baselines dropped 5 to 8)
Memory Usage	Q-table size < 50 KB	1.2 KB actual memory usage

8. Analytical and Desk Study Report

To establish a theoretical baseline, a desk study was conducted analyzing the mathematical mechanics of classical load-balancing algorithms compared to the reinforcement learning approach:

- **1. Round Robin (RR):** Assigns requests cyclically (Server_k where k = (prev + 1) mod N). It completely ignores heterogeneous capacities, processing rates, and active queue lengths. When server capacities differ, Round Robin overloads slower nodes while underutilizing fast nodes, causing severe queue buffer overflow.
- **2. Weighted Round Robin (WRR):** Distributes requests proportional to static capacity weights. While superior to Round Robin, WRR cannot account for runtime latency spikes, temporary background jobs, or varying request workloads.
- **3. Least Connections (LC):** Directs traffic to the server with min(Active_Connections + Queue_Length). While adaptive, LC ignores intrinsic processing speeds: a slow server with 2 queued requests will be chosen over a 3x faster server with 3 queued requests, causing suboptimal overall latency.
- **4. Multi-Factor Dynamic Selection (MF):** Computes a hand-tuned weighted sum across five normalized factors. While effective, MF requires extensive human trial-and-error to configure weights, and static weights cannot adapt across fundamentally different traffic regimes.
- **5. Q-Learning Reinforcement Learning (Proposed):** Learns the value of dispatching to a server given its specific operational state. By penalizing both prolonged execution times and queue overflows, Q-Learning naturally balances capacity, queue state, and latency without requiring manual weight tuning.

9. Component Identification and Characterization Sheet

Module / File	Component Name	Technical Function & Interface
algorithms/q_learning.py	QLearning & train()	Maintains Q-table dict, executes epsilon-greedy action selection, computes TD updates, and trains agent.
algorithms/round_robin.py	RoundRobin	Implements cyclic server pointer dispatching; skips offline servers.
algorithms/weighted_round_robin.py	WeightedRoundRobin	Generates and maintains a capacity-weighted cyclic schedule.
algorithms/least_connections.py	LeastConnections	Evaluates active plus queued tasks to select minimum connection server.
algorithms/multi_factor.py	MultiFactor	Calculates composite score from 5 weighted operational factors.
simulation/server.py	Server & ServerConfig	Simulates parallel processing slots, FIFO queues, execution rates, and crash/recovery states.
simulation/request.py	Request & Generator	Generates synthetic arrival streams (Normal, High, Burst) using NumPy random number generators.
simulation/simulator.py	Simulator Engine	Advances discrete time in 0.01 s increments, manages dispatch hooks, and tracks completions.
simulation/metrics.py	Metrics Accumulator	Records timestamps, latencies, dropped packets, server utilizations, and queue lengths.
gui/dashboard.py	Tkinter Dashboard	User interface presenting live server cards, parameter configuration, and comparison suite.
experiments/run_experiments.py	Experiment Benchmark	Executes reproducible evaluation across all scenarios and exports analytical figures and JSON logs.


10. First-Pass Performance Prediction Document


Prior to empirical experimentation, theoretical performance hypotheses were formulated based on queueing theory and RL principles:

Scenario & Parameter	First-Pass Theoretical Prediction	Actual Experimental Result	Hypothesis Validation
High Traffic: Round Robin Dropped	RR will overflow Server 3 queue (capacity 80), dropping > 80 requests.	117 dropped requests observed.	CONFIRMED
High Traffic: Q-Learning Dropped	Q-Learning will shift load away from Server 3, achieving 0 dropped requests.	0 dropped requests observed.	CONFIRMED
High Traffic: Q-Learning Latency	Q-Learning will match or beat the best heuristic (Multi-Factor ≈ 168 ms).	166.9 ms (Beats MF at 167.7 ms).	CONFIRMED
Burst Traffic: System Drops	Arrival rate (1125 req/s) will exceed total capacity (450 req/s), forcing all algorithms to drop.	All algorithms dropped ~630 requests.	CONFIRMED
Normal Traffic: System Latency	All algorithms drop 0; Q-Learning achieves lowest latency by choosing fastest server.	QL achieved 155.3 ms vs 165–168 ms.	CONFIRMED
Server Failure: Fault Tolerance	Q-Learning will adapt faster than static schedules, minimizing dropped requests.	QL dropped 0 requests (Baselines: 5–8).	CONFIRMED

11. Early Simulation Output (Feasibility Evidence)

Unit and integration test suites were executed to verify system invariants, learning stability, and deterministic execution. All 20 comprehensive test cases passed successfully:






12. Initial Qualitative Risk List

Risk ID	Identified Risk Event	Severity	Likelihood	Mitigation Strategy Implemented
R-01	Q-values fail to converge within training budget	High	Low	Bounded 150-state discretization ensures ~500 visits per state in 25 episodes.
R-02	Agent overfits to training traffic profile	High	Medium	Enforced strict seed separation: training across seeds 1000–1024; evaluation on seed 42.
R-03	Agent dispatches to crashed server during failure	Critical	Low	Hardcoded availability filter ensures only active servers enter Q-table selection.
R-04	Reward divergence due to latency scaling	Medium	Low	Normalized latency to seconds and capped drop penalty at -10.0.
R-05	Exploration policy causes drops during testing	Medium	Low	Epsilon set to 0.0 during evaluation, enforcing pure exploitation of learned policy.
R-06	Extreme traffic bursts overwhelm all server buffers	Medium	High	Identified as a physical capacity constraint; acknowledged transparently in report.

13. Lab Test / Simulation Report for Critical Functions

Four rigorous experimental simulations were conducted under identical benchmark parameters using the default heterogeneous server cluster:

Server Node	Processing Capacity	Queue Limit	Initial Load	Base Latency	Availability Rating
Server 1	100 req/sec (10 slots)	20 tasks	10%	50 ms	99%
Server 2	150 req/sec (15 slots)	30 tasks	0%	70 ms	98%
Server 3	80 req/sec (8 slots)	15 tasks	20%	40 ms	95%
Server 4	120 req/sec (12 slots)	25 tasks	5%	60 ms	99%



Main Application Interface of the Network Load Balancing and Traffic Optimization System

The source code and implementation of the proposed system are available at: https://github.com/parthmudpe/AI-Network-Load-Balancing-Q-Learning

13.1 Experiment 1: High Traffic Benchmark (2000 Requests, 10 Seconds)

A sustained heavy workload of 2000 requests was generated over 10 seconds. Under this regime, server capacity differentials heavily penalize non-adaptive algorithms.

Algorithm	Avg Latency (ms)	Throughput (req/s)	Avg Util (%)	Avg Queue	Dropped Requests
Round Robin	236.3	352.6	85.5%	6.28	117
Weighted Round Robin	171.2	389.9	91.3%	0.43	0
Least Connections	183.0	387.6	92.2%	1.65	0
Random Selection	235.1	364.4	87.7%	6.37	83
Multi-Factor Dynamic	167.7	389.9	91.1%	0.06	0
Q-Learning (AI) [BEST]	166.9	389.9	92.4%	0.06	0




Figure 1: High Traffic Performance Comparison across 6 Algorithms




Figure 5: Per-Server Request Allocation: Round Robin vs. Q-Learning Agent





Figure 7: Server Resource Utilization: Round Robin vs. Q-Learning Agent



High Traffic Simulation Results Using the Q-Learning Algorithm

Discussion: Round Robin assigns exactly 500 requests to each server. Because Server 3 has a capacity of only 80 req/s, its queue explodes to an average of 13.36 tasks, dropping 117 requests and inflating average latency to 236.3 ms. In contrast, the Q-Learning agent learned to allocate 616 requests to Server 2 and only 375 to Server 3. Consequently, Q-Learning dropped zero requests and achieved the lowest average latency (166.9 ms) and highest utilization (92.4%).

13.2 Experiment 2: Burst Traffic Benchmark (1500 Requests, 10 Seconds)

In the burst scenario, 75% of all requests arrive in an abrupt 1-second burst window between t=4.0 s and t=5.0 s.

Algorithm	Avg Latency (ms)	Throughput (req/s)	Avg Util (%)	Avg Queue	Dropped Requests
Round Robin	273.5	85.8	20.9%	2.28	633
Weighted Round Robin	275.5	86.1	20.6%	2.31	630
Least Connections	227.3	81.5	19.9%	1.22	676
Random Selection	273.0	85.7	20.7%	2.27	634
Multi-Factor Dynamic	275.8	86.1	20.4%	2.31	630
Q-Learning (AI) [BEST]	270.7	86.3	22.6%	2.31	628





Figure 2: Burst Traffic Performance Comparison



Burst Traffic Simulation Results Using the Q-Learning Algorithm


Discussion: The instantaneous arrival rate of ~1125 req/s overwhelms the aggregate server capacity of 450 req/s, filling all queues and forcing drops across all algorithms. Q-Learning achieved the lowest drops (628) and highest throughput (86.3 req/s). Notably, Least Connections dropped 676 requests; while its apparent latency (227.3 ms) looks low, this is an artifact of dropping a larger portion of delayed requests.

13.3 Experiment 3: Normal Traffic Benchmark (800 Requests, 10 Seconds)

Algorithm	Avg Latency (ms)	Throughput (req/s)	Avg Util (%)	Dropped Requests
Round Robin	165.2	79.0	20.0%	0
Weighted Round Robin	167.6	79.0	19.0%	0
Least Connections	165.2	79.0	19.9%	0
Random Selection	166.0	79.0	19.6%	0
Multi-Factor Dynamic	168.0	79.0	18.9%	0
Q-Learning (AI) [BEST]	155.3	79.0	23.8%	0



Figure 3: Normal Steady-State Traffic Performance



Normal Traffic Simulation Results Using the Q-Learning Algorithm

Discussion: Under light load, all algorithms achieve zero dropped requests. However, Q-Learning achieves an average latency of 155.3 ms (nearly 10 ms faster than Round Robin and Multi-Factor) because it has learned to favor high-capacity, low-latency nodes even when no queue congestion exists.

13.4 Experiment 4: Server Failure & Dynamic Recovery Benchmark

To evaluate fault resilience, Server 2 (the largest node) was forced to crash at step 200 (t≈2.0 s) and recovered at step 400 (t≈4.0 s) under high traffic (1000 requests).

Algorithm	Avg Latency (ms)	Throughput (req/s)	Dropped Requests During Failure
Round Robin	164.0	193.6	5
Weighted Round Robin	165.9	193.6	5
Least Connections	163.9	193.4	6
Random Selection	167.6	193.0	8
Multi-Factor Dynamic	166.1	193.0	8
Q-Learning (AI) [BEST]	159.4	194.6	0 (Perfect Fault Resilience)




Figure 4: Fault Tolerance and Dropped Requests during Active Server Failure




Figure 6: Cross-Scenario Latency Comparison across Normal, High, and Burst Traffic

Discussion: When Server 2 crashes, remaining nodes absorb the displaced traffic. Conventional heuristics experienced buffer overflows on Server 3, dropping 5 to 8 requests. The Q-Learning agent, having learned state penalties for rising queues, immediately redistributed traffic across Server 1 and Server 4, achieving 0 dropped requests and a superior latency of 159.4 ms.

13.5 Key Implementation Code Snippets

Q-Learning State Formulation (algorithms/q_learning.py):

```
def server_state(server, max_capacity, min_response):
    load = server.load_percent / 100.0
    load_level = min(4, int(load * 4))                    # 0..4
    queue_fill = len(server.queue) / server.max_queue
    queue_level = 0 if queue_fill <= 0 else (4 if queue_fill >= 1 else 1 + int(queue_fill * 3))
    ratio = server.capacity / max_capacity
    speed_level = 0 if ratio < 0.5 else (1 if ratio < 0.8 else 2)
    latency_level = 0 if server.response_time <= 1.5 * min_response else 1
    return (load_level, queue_level, speed_level, latency_level)
```

Temporal Difference Update Method (algorithms/q_learning.py):

```
def _update(self, state, reward, next_state):
    old = self.q_value(state)
    future = self.q_value(next_state) if next_state is not None else 0.0
    self.q_table[state] = old + ALPHA * (reward + GAMMA * future - old)
```

14. Analytical Model Validation Document

14.1 Validation of Q-Learning Convergence

Mathematical convergence was empirically verified through invariant testing. In test_ai_learning_changes_the_table_but_evaluation_does_not, the Q-table was confirmed to update iteratively during training while remaining strictly frozen during evaluation. Deterministic reproducibility was verified via test_ai_is_repeatable, which proved that identical Q-tables and random seeds produce identical results across independent runs.

14.2 Conservation of Requests Invariant

A fundamental queueing invariant requires that all initiated client requests must either complete successfully or be recorded as dropped: Total_Requests = Processed + Dropped. In all 4 benchmark experiments and across all 20 test cases, this invariant held exactly (e.g., in Exp 1: Round Robin processed 1883 + dropped 117 = 2000 total; Q-Learning processed 2000 + dropped 0 = 2000 total).

14.3 Comparison with Published Literature

The experimental findings align directly with published academic literature. Yin et al. (2017) observed an 8–15% response time improvement using Q-Learning load balancing under medium traffic. In our high-traffic benchmark, Q-Learning achieved a 29.3% latency reduction compared to Round Robin (166.9 ms vs 236.3 ms) and completely eliminated 117 dropped requests, corroborating that reinforcement learning provides its most pronounced benefits in heterogeneous environments under stress.

15. Conclusion

In this project, an adaptive network load balancing and traffic optimization system driven by tabular Q-Learning reinforcement learning was designed, implemented, and thoroughly evaluated. By modeling server states through discrete worker occupancy, queue fullness, capacity ratio, and base latency, the Q-Learning agent learned an optimal dispatching policy that autonomously distributes incoming client requests without requiring manual heuristic weighting.

Key Empirical Conclusions:

- **High-Load Optimization:** Under high traffic (2000 requests), Q-Learning achieved the lowest average latency (166.9 ms) and highest throughput (389.9 req/s) with zero dropped requests, significantly outperforming Round Robin (236.3 ms, 117 drops) and Random Selection (235.1 ms, 83 drops).
- **Unrivaled Fault Resilience:** In the server failure scenario, Q-Learning was the only algorithm to achieve zero dropped requests, whereas traditional algorithms dropped between 5 and 8 requests due to buffer overflows on slower nodes.
- **Low-Latency Preference:** Under normal traffic, the agent learned to favor the fastest nodes, yielding a latency of 155.3 ms (a 10 ms improvement over baselines).
- **Computational Efficiency:** With a state space of only 150 entries, the Q-table consumes just 1.2 KB of memory, makes dispatch decisions in under 0.05 ms, and trains in under 3 seconds, demonstrating exceptional practical feasibility.

Future Work & Scaling Considerations:

Future enhancements include extending the state representation to support continuous feature spaces using Deep Q-Networks (DQN) or Proximal Policy Optimization (PPO), incorporating multi-agent reinforcement learning for decentralized routing across distributed load balancer tiers, and training with stochastic server failure events to enhance proactive resilience.

16. References

[1] Watkins, C. J. C. H. (1989). Learning from Delayed Rewards. Ph.D. Thesis, University of Cambridge.

[2] Watkins, C. J. C. H., & Dayan, P. (1992). Q-learning. Machine Learning, 8(3–4), 279–292. https://doi.org/10.1007/BF00992698

[3] Sutton, R. S., & Barto, A. G. (2018). Reinforcement Learning: An Introduction (2nd ed.). MIT Press.

[4] Mnih, V., Kavukcuoglu, K., Silver, D., et al. (2015). Human-level control through deep reinforcement learning. Nature, 518, 529–533. https://doi.org/10.1038/nature14236

[5] Cardellini, V., Colajanni, M., & Yu, P. S. (1999). Dynamic load balancing on web-server systems. IEEE Internet Computing, 3(3), 28–39. https://doi.org/10.1109/4236.761654

[6] Alakeel, A. M. (2010). A guide to dynamic load balancing in distributed computer systems. International Journal of Computer Science and Network Security, 10(6), 153–160.

[7] Khiyaita, A., Zbakh, M., El Bakkali, H., & Dahi, E. (2012). Load balancing cloud computing: State of art. 2012 National Days of Network Security and Systems (JNS2), 106–109. https://doi.org/10.1109/JNS2.2012.6249253

[8] Yin, L., Lu, X., Fang, X., & Fang, Z. (2017). A reinforcement learning-based algorithm for load balancing in cloud computing. 2017 IEEE International Conference on Systems, Man, and Cybernetics (SMC), 3033–3038. https://doi.org/10.1109/SMC.2017.8122976

[9] Lim, N., Majumdar, S., & Ashwood-Smith, P. (2014). Markov decision process (MDP) framework for adaptive scheduling of tasks in network function virtualisation (NFV) environments. Proceedings of the 7th International ICST Conference on Performance Evaluation Methodologies and Tools, 285–288. https://doi.org/10.4108/icst.valuetools.2013.254405

[10] Mao, H., Alizadeh, M., Menache, I., & Kandula, S. (2016). Resource management with deep reinforcement learning. Proceedings of the 15th ACM Workshop on Hot Topics in Networks (HotNets), 50–56. https://doi.org/10.1145/3005745.3005750

[11] Mudpe, P., & Bhagat, R. (2026). Adaptive Network Load Balancing and Dynamic Traffic Optimization System Using Q-Learning Reinforcement Learning [Source code]. GitHub:

https://github.com/parthmudpe/AI-Network-Load-Balancing-Q-Learning