

GHAED BASSIR

PETROCHEMICAL PRODUCTS



CERTIFICATE OF ANALYSIS

Customer: MOMENTUM COMMODITIES DMCC

Product grade : ABS 50N

Quantity : 22500 Kg

Delivery date : 23 Dec 2020

Lot NO : 89712,89714,94377,94379

Features

Applications

Physical	Test Method	Value
Melt Flow Index (220°C, 10 kg)	ASTM D1238	31-33 gr/10 min

Mechanical	Test Method	Value
Tensile Strength (at yield)	ASTM D638	>420 kg/cm ²
Elongation (at break)	ASTM D638	>18 %
Flexural Strength	ASTM D790	>600 kg /cm ²
Flexural Modulus	ASTM D790	> 18500 kg /cm ²
Izod Impact Strength (6.4 mm, 23°C)	ASTM D256	>23 kJ/m ²
Rockwell Hardness	ASTM D785	>108 (R scale)

Thermal	Test Method	Value
Heat Deflection Temperature (0.45Mpa, Unannealed)	ASTM D648	>90 °C
Flammability	UL-94	HB
Remark:		

Declared by

M.SOLEYMANI

Approved by

S.OSTADI

GHAED BASSIR

PETROCHEMICAL PRODUCTS



CERTIFICATE OF ANALYSIS

Customer: MOMENTUM COMMODITIES DMCC

Product grade : ABS 50N

Quantity : 22500 Kg

Delivery date : 23 Dec 2020

Lot NO : 89712,89714,94381,89715

Features

Applications

Physical	Test Method	Value
Melt Flow Index (220°C, 10 kg)	ASTM D1238	31-33 gr/10 min

Mechanical	Test Method	Value
Tensile Strength (at yield)	ASTM D638	>420 kg/cm ²
Elongation (at break)	ASTM D638	>16 %
Flexural Strength	ASTM D790	>600 kg /cm ²
Flexural Modulus	ASTM D790	> 18500 kg /cm ²
Izod Impact Strength (6.4 mm, 23°C)	ASTM D256	>22 kJ/m ²
Rockwell Hardness	ASTM D785	>108 (R scale)

Thermal	Test Method	Value
Heat Deflection Temperature (0.45Mpa, Unannealed)	ASTM D648	>90 °C
Flammability	UL-94	HB

Remark:

Declared by

M.SOLEYMANI

Approved by

S.OSTADI

GHAED BASSIR PETROCHEMICAL PRODUCTS



CERTIFICATE OF ANALYSIS

Customer: MOMENTUM COMMODITIES DMCC

Product grade : ABS 50N

Quantity : 22500 Kg

Delivery date : 23 Dec 2020

Lot NO : 94363,94376,89717,94377,94379

Features

Applications

Physical	Test Method	Value
Melt Flow Index (220°C, 10 kg)	ASTM D1238	31-33 gr/10 min

Mechanical	Test Method	Value
Tensile Strength (at yield)	ASTM D638	>410 kg/cm ²
Elongation (at break)	ASTM D638	>18 %
Flexural Strength	ASTM D790	>620 kg /cm ²
Flexural Modulus	ASTM D790	> 18500 kg /cm ²
Izod Impact Strength (6.4 mm, 23°C)	ASTM D256	>22 kJ/m ²
Rockwell Hardness	ASTM D785	>108 (R scale)

Thermal	Test Method	Value
Heat Deflection Temperature (0.45Mpa, Unannealed)	ASTM D648	>90 °C
Flammability	UL-94	HB

Remark:

Declared by

M.SOLEYMANI

Approved by

S.OSTADI

GHAED BASSIR

PETROCHEMICAL PRODUCTS



CERTIFICATE OF ANALYSIS

Customer: MOMENTUM COMMODITIES DMCC

Product grade : ABS 50N

Quantity : 22500 Kg

Delivery date : 23 Dec 2020

Lot NO : 92445,92444,92443,92441

Features

Applications

Physical	Test Method	Value
Melt Flow Index (220°C, 10 kg)	ASTM D1238	31-34 gr/10 min

Mechanical	Test Method	Value
Tensile Strength (at yield)	ASTM D638	>420 kg/cm ²
Elongation (at break)	ASTM D638	>15 %
Flexural Strength	ASTM D790	>600 kg /cm ²
Flexural Modulus	ASTM D790	> 19000 kg /cm ²
Izod Impact Strength (6.4 mm, 23°C)	ASTM D256	>21 kJ/m ²
Rockwell Hardness	ASTM D785	>108 (R scale)

Thermal	Test Method	Value
Heat Deflection Temperature (0.45Mpa, Unannealed)	ASTM D648	>90 °C
Flammability	UL-94	HB

Remark:

Declared by

M.SOLEYMANI

Approved by

S.OSTADI

GHAED BASSIR

PETROCHEMICAL PRODUCTS



CERTIFICATE OF ANALYSIS

Customer: MOMENTUM COMMODITIES DMCC

Product grade : ABS 50N

Quantity : 22500 Kg

Delivery date : 23 Dec 2020

Lot NO : 92441,92443,92444

Features

Applications

Physical	Test Method	Value
Melt Flow Index (220°C, 10 kg)	ASTM D1238	30-32 gr/10 min

Mechanical	Test Method	Value
Tensile Strength (at yield)	ASTM D638	>410 kg/cm ²
Elongation (at break)	ASTM D638	>16 %
Flexural Strength	ASTM D790	>600 kg /cm ²
Flexural Modulus	ASTM D790	> 19000 kg /cm ²
Izod Impact Strength (6.4 mm, 23°C)	ASTM D256	>21 kJ/m ²
Rockwell Hardness	ASTM D785	>108 (R scale)

Thermal	Test Method	Value
Heat Deflection Temperature (0.45Mpa, Unannealed)	ASTM D648	>90 °C
Flammability	UL-94	HB

Remark:

Declared by

M.SOLEYMANI

Approved by

S.OSTADI