



DOWLEX™ NG 2429.01G

Polyethylene Resin

Overview

- Intermediate bulk containers
- Drums for chemicals
- Boats, freezer containers, fish crates and tanks
- Complies with U.S. FDA 21 CFR 177.1520 (c) 3.1a
- Consult the regulations for complete details.

DOWLEX™ NG 2429.01G Polyethylene Resin is an ethylene octene copolymer for rotational moulding and is specifically designed for applications requiring excellent environmental stress crack resistance and impact strength combined with low warpage and good processing. DOWLEX NG 2429.01G is fully heat and UV stabilized resulting in a wide processing latitude, good colour retention, and long life expectancy.

Additive

- Antiblock: No
- Slip: No
- Processing Aid: No

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Density	0.935 g/cm ³	0.935 g/cm ³	ISO 1183
Melt Index (190°C/2.16 kg)	4.0 g/10 min	4.0 g/10 min	ISO 1133
Environmental Stress-Cracking Resistance (ESCR)			ASTM D1693
122°F (50°C), 10% AntaroX, Rotational Molded ¹	400 hr	400 hr	
122°F (50°C), 100% AntaroX, Compression Molded	> 1000 hr	> 1000 hr	
Mechanical	Nominal Value (English)	Nominal Value (SI)	Test Method
Tensile Stress			ISO 527-2
Yield, Compression Molded	2470 psi	17.0 MPa	
Yield, Rotational Molded ¹	2470 psi	17.0 MPa	
Break, Compression Molded	3580 psi	24.7 MPa	
Break, Rotational Molded ¹	3160 psi	21.8 MPa	
Tensile Strain			ISO 527-2
Break, Compression Molded	800 %	800 %	
Break, Rotational Molded ¹	700 %	700 %	
Flexural Modulus - 1% Secant (Compression Molded)	92800 psi	640 MPa	ISO 178
Tear Resistance			DIN 53515
... ²	20305 psi	140 MPa	
Compression Molded	21030 psi	145 MPa	
Impact	Nominal Value (English)	Nominal Value (SI)	Test Method
Multi-Axial Instrumented Impact Energy			ISO 6603-2
-4°F (-20°C), 0.0394 in (1.00 mm), Compression Molded	17.0 ft-lb	23.0 J	
73°F (23°C), Rotational Molded ¹	12.5 ft-lb	17.0 J	
73°F (23°C), 0.0394 in (1.00 mm), Compression Molded	12.5 ft-lb	17.0 J	
Hardness	Nominal Value (English)	Nominal Value (SI)	Test Method
Shore Hardness (Shore D, Compression Molded)	57	57	ISO 868

Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Deflection Temperature Under Load 264 psi (1.8 MPa), Unannealed	102 °F	38.9 °C	ISO 75-2/A
Vicat Softening Temperature	244 °F	118 °C	ISO 306/A120
Melting Temperature	257 °F	125 °C	DSC
Peak Crystallization Temperature (DSC)	221 °F	105 °C	DSC

Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

¹ 3 to 4 mm plate thickness

² Rotational Molded, 3 to 4 mm plate thickness

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Medical Applications Policy

Any and all medical application use of Dow materials, whether a device, a component, or any type of primary or secondary packaging of a medically related object or substance, needs to be reviewed and approved by Dow before any Dow material can be tested in such application.

Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. **DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

For further information contact your Dow sales or technical representative to request a Medical Application Review Request Form.

Additional details of Dow's Medical Applications Policy are available at: <https://www.dow.com/en-us/support/product-safety.html>

Tobacco and Marijuana Policy

Dow does not support or intend for its products to be used, directly or indirectly, in the production of tobacco, the manufacture of tobacco products, the manufacture and use of electronic cigarettes (including vaping devices), the production of marijuana, or the manufacture of marijuana products intended for human consumption, where the Dow product (or its residues) may be present in the finished product or be alleged to facilitate the delivery of nicotine, other tobacco components, marijuana, or marijuana components.

Harmful Applications Policy

Dow does not intend for its products to be used in applications specifically intended to harm humans.

Disclaimer

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications and/or discontinue production; and (4) although Dow may from time to time provide samples of such products, Dow is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

NOTICE: This data is based on information Dow believes to be reliable, as demonstrated in controlled laboratory testing. They are offered in good faith, but without guarantee, as conditions and method of use of Dow products are beyond Dow's control. Dow recommends that the prospective user determine the suitability of these materials and suggestions before adopting them on a commercial scale.

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability for the accuracy and completeness of such information.

For additional information, not covered by the content of this document, contact us via our web site http://www.dow.com/products_services/.

Additional Information

North America

U.S. & Canada:

1-800-441-4369

1-989-832-1426

Mexico:

+1-800-441-4369

Latin America

Argentina:

+54-11-4319-0100

Brazil:

+55-11-5188-9000

Colombia:

+57-1-219-6000

Mexico:

+52-55-5201-4700

Europe/Middle East

+800-3694-6367

+31-11567-2626

Italy:

+800-783-825

South Africa

+800-99-5078

Asia Pacific

+800-7776-7776

+603-7965-5392

www.dow.com

This document is intended for use within Asia Pacific

Published: 2009-12-15

© 2023 The Dow Chemical Company

