PT Asahimas Chemical
AGC Group

| Final Product Specification | PVC FJ-65R | Date : August 14, 2019 | |
|---|---|---|---|
| | | Rev. : 7 | Page : 1 of 1 |
| Refer to Approval no. : 001/05/2012/ASC, 05/25/2012 | | No. : SPC - QCA - 2013 | |

# POLY VINYL CHLORIDE, ASNYL FJ-65R SPECIFICATION

| Item | Unit | Specification | Analysis Method |
|---|---|---|---|
| Appearance | | White | WIM-QCA-3809 #) |
| MDP | | 1030 ± 40 | JIS K-6721 |
| K-Value | | 66.4 - 68.0 | ISO 1628 |
| Bulk Density | g/ml | 0.60 ± 0.05 | ISO 1068 |
| Particle Size 42 Mesh | % wt | 100 max | WIM-QCA-3804 #) |
| Volatile Matter | % wt | 0.30 max | JIS K-6721 |
| R-VCM | ppm | 1.0 max | ASTM D3749 -12 |
| Foreign Matter | pcs/100 g | 100 max | WIM-QCA-3808 #) |

Note #) : In house method

Approved by,

M. Usman Kamal
QA Department Manager

OTHERS

W:\06 ISO\Final Product Spec\FPS 2015\SPC 2013, FJ-65R