



中国石化
SINOPEC

TECHNICAL DATA SHEET

Product Name: **Polypropylene Fiber Grade**

Product Grade: **PPH-YH40X**

Product Description:

Sinopec is the largest PP fiber grade supplier in China. PP fiber grade by Sinopec is characterized by low ash content and good spinning properties.

Physical Properties:

Typical performance index (Not Warranted Value)

Item		Unit	Quality Index	Typical Value	Method
Appearance of Granules	Black Granule	/ kg	0	0	SH/T 1541.1-2019
	Trailing Granule	/ kg	≤ 30	2	
	Large & Small Particles	g/ kg	≤ 100	0	
Melt Mass-Flow Rate (MFR)		g/ 10min	38 ± 7	38.5	GB/T 3682.1-2018
Ash Content		%	≤ 0.03	0.015	GB/T 9345.1-2008
Tensile Stress at Yield		MPa	≥ 25.0	35.2	GB/T 1040.3-2006
Tensile Stress at Break		MPa	≥ 8.0	21.6	GB/T 1040.3-2006
Nominal Tensile Strain at Break		%	≥ 200	541	GB/T 1040.1-2018
Fish Eye Number 0.8mm		/1520cm ²	≤ 4	0	GB/T 6595-1986
Fish Eye Number 0.4mm		/1520cm ²	≤ 35	7	GB/T 6595-1986



中国石化
SINOPEC

TECHNICAL DATA SHEET

Product Name: **Polypropylene Fiber Grade**

Product Grade: **PPH-Y40X**

Product Characteristics:

- Low ash content
- Good spinning properties

Manufacturer:

Jinan Refinery Co., Ltd.

Typical Applications:

PP fiber grade is widely used in the production of bulked continuous filament (BCF), fine and superfine staple fiber, cigarette filter tow and superfine non-woven fabric in high-speed and ultrahigh-speed spinning and spunbonded non-woven fabric production. It has a variety of applications in the decoration, medical sanitation martial and clothing production sectors.