

Particle Video Revisited:


https://particle-video-revisited.github.io https://github.com/aharley/pips


Tracking Through Occlusions Using Point Trajectories _____/

TEL AVIV 2022

Adam W. Harley, Zhaoyuan Fang, Katerina Fragkiadaki

Goal: Given a target pixel specified on the first frame, track that pixel across the whole video.






Related: Optical flow and feature matching are general-purpose, but have difficulty with occlusions.

Optical flow provides fine-grained motion, but with a narrow timespan.


Feature matching provides long-range correspondence, but without a temporal prior.

Sand & Teller (2008) suggest to treat pixels like "particles". Let's revisit this!

Modern trackers for pedestrians and cars use strong temporal priors to help track through occlusions. Can we bring this power to pixel tracking?



Teed & Deng. RAFT: Recurrent All Pairs Field Transforms for Optical Flow ECCV 2020



Lai et al. MAST: A Memory-Augmented Self-Supervised Tracker. CVPR 2020.




Sand & Teller. Particle Video: Long-Range Motion Estimation Using Point Trajectories. IJCV 2008.



Rajasegaran et al., Tracking People by Predicting 3D Appearance, Location & Pose. CVPR 2022.

Persistent Independent Particles (PIPs): Every particle is tracked independently. We initialize a zero-velocity trajectory for each particle, and iteratively refine it, inspecting multi-frame




PIPs vs. RAFT


8-frame temporal window instead of 2-frame.

Deep temporal prior via MLP-Mixer, instead of shallow one by convGRU.

200ms for 8 frames for 256 particles, instead of 200ms/frame.


Results: Outperforms optical flow and feature matching. Despite training on synthetic data, generalizes to YouTube.





At test time, we chain our 8-frame trajectories to track for arbitrary timespans.














We outperform flow and feature matching in trajectory estimation in FlyingThings, KITTI, CroHD, and BADJA, mostly due to handling occlusions.

Future work: multi-trajectory inference, recurrence.