# Tables as Networks: A Byte-for-Byte Self-Hosting C Compiler Whose Weights Are Constructed, Not Trained

Yunzuo Chen
PartnerNet Software Pty Ltd, Australia
wanjochan@partnernetsoftware.com

September 2026*

**Abstract**

unisacc is a neural-network-based compiler: compilation stages run on integer threshold networks and one generic executor; weights are constructed from a TSV table DSL, not trained. T1 is key-by-key equality on the declared domain (Definition 2), not sample fit. The decision-network instance is 18 decision stages. The network-compiler instance is seven byte-stream stages: preprocess (pp), lex, parse, opt, prune, lowering, encode + image (enc). parse2 is an implementation name of the same contract, not a separate stage. An out-of-domain key fails; logits are not read; rejection does not fall back to the table. N1 = N2 = N3 is unsigned successive-generation byte identity on five named targets (osx/arm64, lnx/arm64, lnx/x86-64, win/arm64, win/x86-64), not a semantic self-host. Key identities: op-74 totals 8,509 keys; the op-87 label total is 8,769 keys; not interchangeable before a seal. Source `910f1e0a` / `0.0.42` is not a sealed release measurement. The referee ledger is `research/referee.tsv`. Systematic training comparison is preregistered study A2. Enumeration proves network = table, not table = C.

**Keywords:** neural-network-based compiler; TSV table DSL; weight construction; T1; finite control; byte-for-byte self-hosting

## 1 Contributions

1. **Method.** TSV table DSL → constructed weights → exhaustion on the declared domain (T1). The weights are not trained.

2. **Two layers.** The network-compiler contract is seven byte-stream stages: one generic executor $E$ runs finite transitions $\delta$. The decision-network instance is 18 decision stages, queried at ask points or via the enumerated DENSE table.

*Code, weights and all evidence: https://github.com/partnernetsoftware/unisacc (repository links in this paper are pinned to commit `910f1e0a`; see Appendix A).

3. **Implementation.** unisacc, a six-target C99 subset. The decision-network instance self-hosts byte-for-byte on five targets without Python. Source identity: Appendix A.

Not claimed: table = C99, whole-compiler semantic preservation (T3), or a speed advantage.

## 2 Definitions

**Definition 1 (decision stage).** Stage $s$ has fields $(f_1{:}V_1, \ldots, f_m{:}V_m)$, output vocabulary $Y$, and total $G_s : K_s \to Y$ on the finite product $K_s$. These 18 stages are the decision-network instance, not the seven byte-stream stages.

**Definition 2 (exact / T1).** $N$ is exact for $s$ iff for every $k \in K_s$, $\operatorname{argmax} N(k)$ is unique and equals $G_s(k)$.

**Check / artifacts.** `python3 -m unisa build-weights -from-tsv -check` compares TSV-built weights with the shipped file and writes nothing. `python3 -m unisa acc` enumerates the declared domain; an error or a tie fails. The reading is T1 = 1.000. Tables are `weights/gold/*.tsv`. Constructed weights are `weights/built.json`.

**Definition 3 (query discipline).** Use only $\mathrm{ask}(s, k)$. Do not read logits. Do not fall back to the table on rejection. $k \notin K_s$ fails.

$$\mathrm{Compile}(x) = \mathrm{dec}(\mathrm{Run}_{E,\delta}(\mathrm{enc}(x))).$$

$\delta$ takes the control state plus one finite observation and returns the next state and an action-sequence index. $E$ performs storage, stack, and output only. A TSV row `state, observation, next, actions` expands to a finite total $G_s$; the constructor emits $N_s$; the check proves only $N_s = G_s$. DSL syntax and the T2/T3 obligations are in `research/paper-a-notes.md`. T2a, T2b, and T3 are not theorems of this paper.

## 3 Construction

A one-hidden-unit-per-key one-hot construction yields an exact network of width at most $|K|$ (Lean `naive_exact`). Shipped decision stages use a cube cover: the hidden layer is a Boolean conjunction and the output layer an integer vote (cube cover; details in `research/paper-a-notes.md`). The parameter count 796,490→71,828 in the notes is not a new measurement on this tip. `decision_list_exact` covers only the globally monochrome first-hit case and does not prove the shipped networks. The release check is the integer network with strict argmax on the declared domain; a wrong answer or a tie rejects the build.

The op-74 total of 8,509 keys and the op-87 label total of 8,769 keys are two identities and are not interchangeable before a seal. On this tip the live `weights/gold` eighteen-stage `#field` domain product is 8,770 (against 8,769 in `research/seal-remeasure-20261009.md`; the difference is opinfo

72→73; the header of `weights/gold/opinfo.tsv` says 73 keys). Hidden units total 569, matching the README stages table and `weights/built.json`. 8,770 is not 8,509 and is not written as the label 8,769. combo is an isel∪abi control and is off the ship path; the census total below includes that row.

The table is generated by `python3 -m unisa docs` from `unisa/gold.py` and the constructed weights (`tests/docs.sh` fails when it differs).

| stage | key | out | keys | units |
|---|---|---|---|---|
| pp | dir(9) x defined(2) | 4 classes | 18 | 6 |
| lex | c(12) x peek(12) | 10 classes | 144 | 11 |
| parse | nt(5) x tok(68) | 36 classes | 340 | 34 |
| type | t1(15) x op(19) x t2(15) | 16 classes | 4,275 | 62 |
| scope | ctx(6) x kind(5) | 7 classes | 30 | 9 |
| irsel | family(6) x flavor(70) | 70 classes | 420 | 75 |
| enc | op(87) x os(3) x arch(2) | 5 classes | 522 | 5 |
| reloc | kind(3) x arch(2) | 3 classes | 6 | 3 |
| regmap | treg(8) x arch(2) | 16 classes | 16 | 10 |
| tyinfo | t(16) | 3 heads | 16 | 6 |
| pfconv | conv(9) | 7 classes | 9 | 7 |
| peep | a(8) x b(17) x rel(12) | 10 classes | 1,632 | 18 |
| opinfo | op(73) | 3 heads | 73 | 16 |
| prec | op(19) | 11 classes | 19 | 11 |
| binsel | op(16) x sign(2) | 23 classes | 32 | 18 |
| isel | op(87) x arch(2) | 2 heads | 174 | 88 |
| abi | op(87) x os(3) x arch(2) | 13 heads | 522 | 69 |
| combo | op(87) x os(3) x arch(2) | 15 heads | 522 | 121 |
| total | | | 8,770 | 569 |

Exactness is constructed. The weights are derived from the gold tables (`weights/gold/*.tsv` is the tables as data): $W_1 \in \{0, 1\}$, $b_1$ is recoverable from $W_1$, and $W_2$ is a small power of two. The hidden activation is always 0 or 1, so inference has no multiply and no float. Verification is exhaustive. Each stage is a total function on a finite domain, so network = table is decided by enumerating every key (the total is the table above). That does not prove table = C. Whether the table is right about C is checked separately against the system compiler (`tests/gold_audit.py`, `difftest`).

The deployment kernel is integer: one-hot, integer affine, ReLU, integer affine, strict argmax. No softmax, floating point, multiplication, or libm. The same table constructs the same weights. This paper does not quote a weight-byte total.

## 4 Seven byte-stream stages and two instances

The decision-network instance is 18 ask stages. The network-compiler instance is the seven stages below. They are not interchangeable. Each stage is a constructed integer threshold network run by one generic executor. parse2 is an implementation name of the same contract, not a separate stage.

| stage | input → output | role |
|---|---|---|
| preprocess (pp) | source bytes → preprocessed text | line continuation, comments, directives, macros, conditionals, includes |
| lex | preprocessed text → typed token stream | keywords, identifiers, operators, literals, longest match |
| parse | token stream → tape | declarations, scopes, types, precedence, statements, init, calls |
| opt | tape → tape | peephole / stack-to-reg style rewrites on tape |
| prune | tape → tape | drop unreachable whole functions on image/run routes (public tape out skips prune) |
| lowering | tape → target ops + data | ABI, regmap, syscalls, layout, reloc |
| encode + image (enc) | target ops → ELF / Mach-O / PE (or in-memory image) | encoding, branches, reloc, headers, Mach-O ad-hoc signature |

The tape has eight 64-bit registers and 71 operations in `SHAPE`. The executor has no primitive for C, the tape, an ISA, or an image format.

The decision-network instance calls `ask` from classic recursive descent, lowering, and image writing; no fallback. The network-compiler instance runs the seven stages; a model rejection is an error. This tip has no same-identity size or speed measurement; this paper claims none.

Threshold-prefix evaluation and declared returns do not change network answers: same network, same sum; the network–table check still covers every observation, including returns. Host code still loads packages and retains `src/tapelink.c`, `src/asmtext.c`, and `src/fwdstub.c`. Build-time Python is in the trusted base.

## 5 Self-host, T1, and referees

Decision-network instance, byte equality:

1. Front-end fixed point: A compiles itself to B, B compiles itself to C, B = C, and both match the Python front end.
2. Back-end closure: 94 probes × 6 targets, 564/564; the compiler itself 6/6.
3. No Python: N1 = N2 = N3 on osx/arm64, lnx/arm64, lnx/x86-64, win/arm64, and win/x86-64 (the last under system emulation).

N1 = N2 = N3 asserts only unsigned successive-generation identity. The network compiler's driver self-host is N1 = N2 = N3 on macOS arm64 for a fixed network package and does not construct that package.

T1 runs every cube network with deployment arithmetic on every key of its declared domain; an error or a tie fails construction. On the normal C path the decision-network instance reads DENSE and compares table lookup with direct inference.

Six-target fold: the machine model recognises only the (OS, call number) from lowering. The six (stdout, exit) pairs agree with each other and with a tape reference VM. Clearing the class bits of macOS system-call numbers must yield 4/6. This tip has no native-versus-emulation matrix.

Eight of the 18 decision stages have a named referee. The ledger is `research/referee.tsv`. The table is a pointer, not a proof of C.

| Referee | Check |
|---|---|
| Preprocess | `exec/pp/macrocheck.py`, `tests/ccparity.sh`, against `cc -E -P` |
| Parse | `tests/warn.sh`, (line, kind) against `cc -Wall` |
| Type | `_Generic`; 1,400 of 4,275 keys |
| ABI | host system-call headers; actual host OS and architecture only |
| Precedence | 324 pairs; 291 distinguishable and consistent; 33 indistinguishable |
| Type info | sizes of 11 types; signedness and narrowness of 8 integer types |
| Binary-operator selection | `tests/binsel_audit.py`; 7 of 16 operators depend on signedness |
| printf | `tests/pfconv_audit.py`; 9 conversion letters |

Recorded; not a new seal of this tip.

| Item | Record |
|---|---|
| T1 | 18×1.000 |
| type↔cc | 1399/1400 (1 intentional difference) |
| c-testsuite | 216/220 |
| C99 | 59/59 |
| difftest | 93/93 |
| opts | 279/279 |
| frontends | 190/190 |
| libs | 11/11 |
| closure | 564/564 + self 6/6 |
| `%f/%e/%g` | bit-identical with platform libc |

## 6 Boundaries

Systematic construction-versus-training comparison is preregistered study A2. This paper has no training table.

The verification discipline has exposed cross-table combination gaps under one identity. Details are in `archive/research/r20/design-review-2026-10-01.md` and `research/paper-a-notes.md` and are not restated here. T1 asserts only network = table on one table's declared domain.

This tip has no same-identity census of the seven stages, no speed measurement, and no platform matrix. The corpus does not extend to arbitrary C99. Build-time Python is in the trusted base.

Related work, as pointers only: exact network encodings of finite-state machines (Omlin and Giles, 1996; Siegelmann and Sontag, 1995); weights constructed from programs (Weiss et al., 2021; Lindner et al., 2023); table-driven compilers (Johnson, 1975; Glanville and Graham, 1978; Fraser et al., 1992); trained controllers (Graves et al., 2014); proved semantic preservation (Leroy, 2009; Kumar et al., 2014); diverse double-compiling (Wheeler, 2009). Gradient-method failures are left to A2.

## 7 Conclusion

On table-shaped decisions, exactness is decidable by exhaustion. unisacc runs constructed weights on two layers: 18 decision stages, and seven byte-stream stages. The decision-network instance meets N1 = N2 = N3 on the five targets in §5. Whether a table equals C is answered only by the named referees, inside their coverage.

## References


Boaz Barak, Benjamin L. Edelman, Surbhi Goel, Sham Kakade, Eran Malach, and Cyril Zhang. Hidden progress in deep learning: SGD learns parities near the computational limit. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. arXiv:2207.08799.

Matko Bošnjak, Tim Rocktäschel, Jason Naradowsky, and Sebastian Riedel. Programming with a differentiable Forth interpreter. Preprint, 2016. arXiv:1605.06640.

Chris Cummins, Volker Seeker, Dejan Grubisic, Baptiste Roziere, Jonas Gehring, Gabriel Synnaeve, and Hugh Leather. Meta Large Language Model Compiler: Foundation models of compiler optimization. Preprint, 2024. arXiv:2407.02524.

Christopher W. Fraser, David R. Hanson, and Todd A. Proebsting. Engineering a simple, efficient code-generator generator. *ACM Letters on Programming Languages and Systems*, 1(3):213–226, 1992. doi:10.1145/151640.151642.

Dan Friedman, Alexander Wettig, and Danqi Chen. Learning transformer programs. Preprint, 2023. arXiv:2306.01128.

Alexander L. Gaunt, Marc Brockschmidt, Rishabh Singh, Nate Kushman, Pushmeet Kohli, Jonathan Taylor, and Daniel Tarlow. TerpreT: A probabilistic programming language for program induction. Preprint, 2016. arXiv:1608.04428.

Angeliki Giannou, Shashank Rajput, Jy-yong Sohn, Kangwook Lee, Jason D. Lee, and Dimitris Papailiopoulos. Looped transformers as programmable computers. Preprint, 2023. arXiv:2301.13196.

R. Steven Glanville and Susan L. Graham. A new method for compiler code generation. In *Proceedings of the 5th ACM SIGACT-SIGPLAN Symposium on Principles of Programming Languages (POPL)*, pages 231–254, 1978. doi:10.1145/512760.512785.

Alex Graves, Greg Wayne, and Ivo Danihelka. Neural Turing machines. Preprint, 2014. arXiv:1410.5401.

Frédéric Gruau, Jean-Yves Ratajszczak, and Gilles Wiber. A neural compiler. *Theoretical Computer Science*, 141(1–2):1–52, 1995. doi:10.1016/0304-3975(94)00200-3.

Stephen C. Johnson. Yacc: Yet another compiler-compiler. Computing Science Technical Report 32, Bell Laboratories, Murray Hill, NJ, 1975.

Ramana Kumar, Magnus O. Myreen, Michael Norrish, and Scott Owens. CakeML: A verified implementation of ML. In *Proceedings of the 41st ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*, pages 179–191, 2014. doi:10.1145/2535838.2535841.

Xavier Leroy. Formal verification of a realistic compiler. *Communications of the ACM*, 52(7):107–115, 2009. doi:10.1145/1538788.1538814.

David Lindner, János Kramár, Sebastian Farquhar, Matthew Rahtz, Thomas McGrath, and Vladimir Mikulik. Tracr: Compiled transformers as a laboratory for interpretability. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. arXiv:2301.05062.

Eran Malach and Shai Shalev-Shwartz. When hardness of approximation meets hardness of learning. Preprint, 2020. arXiv:2008.08059.

Christian W. Omlin and C. Lee Giles. Constructing deterministic finite-state automata in recurrent neural networks. *Journal of the ACM*, 43(6):937–972, 1996. doi:10.1145/235809.235811.

Shai Shalev-Shwartz, Ohad Shamir, and Shaked Shammah. Failures of gradient-based deep learning. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, 2017. arXiv:1703.07950.

Ohad Shamir. Distribution-specific hardness of learning neural networks. *Journal of Machine Learning Research*, 19(32):1–29, 2018.

Peter Shaw, James Cohan, Jacob Eisenstein, Kenton Lee, Jonathan Berant, and Kristina Toutanova. ALTA: Compiler-based analysis of transformers. Preprint, 2024. arXiv:2410.18077.

Hava T. Siegelmann and Eduardo D. Sontag. On the computational power of neural nets. *Journal of Computer and System Sciences*, 50(1):132–150, 1995. doi:10.1006/jcss.1995.1013.

Hanzhuo Tan, Qi Luo, Jing Li, and Yuqun Zhang. LLM4Decompile: Decompiling binary code with large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2024. doi:10.18653/v1/2024.emnlp-main.203; arXiv:2403.05286.

Mircea Trofin, Yundi Qian, Eugene Brevdo, Zinan Lin, Krzysztof Choromanski, and David Li. MLGO: A machine learning guided compiler optimizations framework. Preprint, 2021. arXiv:2101.04808.

Petar Veličković and Charles Blundell. Neural algorithmic reasoning. *Patterns*, 2021. doi:10.1016/j.patter.2021.100273; arXiv:2105.02761.

Petar Veličković, Adrià Puigdomènech Badia, David Budden, Razvan Pascanu, Andrea Banino, Misha Dashevskiy, Raia Hadsell, and Charles Blundell. The CLRS algorithmic reasoning benchmark. Preprint, 2022. arXiv:2205.15659.

Gail Weiss, Yoav Goldberg, and Eran Yahav. Thinking like transformers. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, 2021. arXiv:2106.06981.

Yixuan Weng, Minjun Zhu, Fei Xia, Bin Li, Shizhu He, Kang Liu, and Jun Zhao. Mastering symbolic operations: Augmenting language models with compiled neural networks. Preprint, 2023. arXiv:2304.01665.

David A. Wheeler. *Fully Countering Trusting Trust through Diverse Double-Compiling*. PhD thesis, George Mason University, 2009. arXiv:1004.5534.

# A Artifacts and Evidence

| Identity | Content |
|---|---|
| Source tree | main `910f1e0a`; `src/version.h` is `0.0.42`. Not public Latest and not a sealed release measurement. |

Pointers: `research/referee.tsv`, `research/formalization-roadmap.md`, `research/lean/`, `research/prior-art.md`, `research/paper-a-notes.md`.

```
python3 -m unisa build-weights
python3 -m unisa acc
python3 -m unisa run examples/hello.c --fold
./tests/closure.sh examples/*.c tests/c/*.c
./tests/nativeboot.sh
./tests/gate.sh --list --com
```