Tables as Networks: A Byte-for-Byte Self-Hosting C Compiler Whose Weights Are Constructed, Not Trained

Yunzuo Chen
PartnerNet Software Pty Ltd, Australia
wanjochan@partnernetsoftware.com

October 2026*

Abstract

unisacc is a neural-network-based compiler: compilation stages run on integer threshold networks and one generic executor; weights are constructed from a TSV table DSL, not trained. T1 is key-by-key equality on the declared domain (Definition 2), not sample fit. The decision-network instance is 18 decision stages. The network-compiler instance is seven byte-stream stages: preprocess (pp), lex, parse, opt, prune, lowering, encode + image (enc). parse2 is an implementation name of the same contract, not a separate stage. An out-of-domain key fails; logits are not read; rejection does not fall back to the table. N1 = N2 = N3 is unsigned successive-generation byte identity on five named targets (osx/arm64, lnx/arm64, lnx/x86-64, win/arm64, win/x86-64), not a semantic self-host. Key identities: op-74 totals 8,509 keys; the op-87 label total is 8,769 keys; not interchangeable before a seal. Source `910f1e0a` / `0.0.42` is not a sealed release measurement. The referee ledger is `research/referee.tsv`. This paper's contribution is constructed exact integer decision networks checked by exhaustive T1. Learned training comparison is not in this paper; see preregistered study A2. Enumeration proves network = table, not table = C.

Keywords: neural-network-based compiler; constructed weights; T1; byte-for-byte self-hosting; N1=N2=N3

1 Contributions

1. **Method.** TSV table DSL → constructed weights → exhaustion on the declared domain (T1). The weights are not trained.
2. **Two layers.** The network-compiler contract is seven byte-stream stages: one generic executor E runs finite transitions δ. The decision-network instance is 18 decision stages, queried at ask points or via the enumerated DENSE table.

*Code, weights and all evidence: https://github.com/partnernetsoftware/unisacc (repository links in this paper are pinned to commit `910f1e0a`; see Appendix A).

3. **Implementation.** unisacc, a six-target C99 subset. The decision-network instance self-hosts byte-for-byte on five targets without Python. The six shipped targets include osx/x86-64; the five-name N1 list does not. Network-compiler driver self-host is not package self-construction. Source identity: Appendix A.

This paper's contribution is constructed exact integer decision networks checked by exhaustive T1. Learned training comparison is not in this paper; see preregistered study A2.

Not claimed: table = C99, whole-compiler semantic preservation (T3), or a speed advantage.

2 Definitions

Definition 1 (decision stage). Stage s has fields $(f_1{:}V_1, \ldots, f_m{:}V_m)$, output vocabulary Y, and total $G_s : K_s \to Y$ on the finite product K_s. These 18 stages are the decision-network instance, not the seven byte-stream stages.

Definition 2 (exact / T1). N is exact for s iff for every $k \in K_s$, $\operatorname{argmax} N(k)$ is unique and equals $G_s(k)$.

Check / artifacts. `python3 -m unisa build-weights -from-tsv -check` compares TSV-built weights with the shipped file and writes nothing. `python3 -m unisa acc` enumerates the declared domain; an error or a tie fails. The reading is T1 = 1.000. Tables are `weights/gold/*.tsv`. Constructed weights are `weights/built.json`.

Definition 3 (query discipline). Use only $\text{ask}(s, k)$. Do not read logits. Do not fall back to the table on rejection. $k \notin K_s$ fails. On the normal C path, DENSE is the shipped lookup enumerated from the network. Rejection and out-of-domain failure still do not fall back to the gold table.

$$\text{Compile}(x) = \text{dec}(\text{Run}_{E,\delta}(\text{enc}(x))).$$

δ takes the control state plus one finite observation and returns the next state and an action-sequence index. E performs storage, stack, and output only. A TSV row `state, observation, next, actions` expands to a finite total G_s; the constructor emits N_s; the check proves only $N_s = G_s$. DSL syntax and the T2/T3 obligations are in `research/paper-a-notes.md`. T2a, T2b, and T3 are not theorems of this paper.

3 Construction

A one-hidden-unit-per-key one-hot construction yields an exact network of width at most $|K|$ (Lean `naive_exact`). Shipped decision stages use a cube cover: the hidden layer is a Boolean conjunction and the output layer an integer vote (cube cover; details in `research/paper-a-notes.md`). The parameter count 796,490→71,828 in the notes is not a new measurement on this tip.

`decision_list_exact` covers only the globally monochrome first-hit case and does not prove the shipped networks. The release check is the integer network with strict argmax on the declared domain; a wrong answer or a tie rejects the build.

The op-74 total of 8,509 keys and the op-87 label total of 8,769 keys are two identities and are not interchangeable before a seal. On this tip the live `weights/gold` eighteen-stage `#field` domain product is 8,770 (against 8,769 in `research/seal-remeasure-20261009.md`; the difference is opinfo 72→73; the header of `weights/gold/opinfo.tsv` says 73 keys). Hidden units total 569, matching the README stages table and `weights/built.json`. 8,770 is not 8,509 and is not written as the label 8,769. combo is an isel∪abi control and is off the ship path; the census total below includes that row.

The table is generated by `python3 -m unisa docs` from `unisa/gold.py` and the constructed weights (`tests/docs.sh` fails when it differs).

stage	key	out	keys	units
pp	dir(9) x defined(2)	4 classes	18	6
lex	c(12) x peek(12)	10 classes	144	11
parse	nt(5) x tok(68)	36 classes	340	34
type	t1(15) x op(19) x t2(15)	16 classes	4,275	62
scope	ctx(6) x kind(5)	7 classes	30	9
irsel	family(6) x flavor(70)	70 classes	420	75
enc	op(87) x os(3) x arch(2)	5 classes	522	5
reloc	kind(3) x arch(2)	3 classes	6	3
regmap	treg(8) x arch(2)	16 classes	16	10
tyinfo	t(16)	3 heads	16	6
pfconv	conv(9)	7 classes	9	7
peep	a(8) x b(17) x rel(12)	10 classes	1,632	18
opinfo	op(73)	3 heads	73	16
prec	op(19)	11 classes	19	11
binsel	op(16) x sign(2)	23 classes	32	18
isel	op(87) x arch(2)	2 heads	174	88
abi	op(87) x os(3) x arch(2)	13 heads	522	69
combo	op(87) x os(3) x arch(2)	15 heads	522	121
total			8,770	569

Exactness is constructed. The weights are derived from the gold tables (`weights/gold/*.tsv` is the tables as data): $W_1 \in \{0, 1\}$, b_1 is recoverable from W_1, and W_2 is a small power of two. The hidden activation is always 0 or 1, so inference has no multiply and no float. Verification is exhaustive. Each stage is a total function on a finite domain, so network = table is decided by enumerating every key (the total is the table above). That does not prove table = C. Whether the table is right about C is checked separately against the system compiler (`tests/gold_audit.py`, `difftest`).

The deployment kernel is integer: one-hot, integer affine, ReLU, integer affine, strict argmax. No softmax, floating point, multiplication, or libm. The same table constructs the same weights. This paper does not quote a weight-byte total.

4 Seven byte-stream stages and two instances

The decision-network instance is 18 ask stages. The network-compiler instance is the seven stages below. They are not interchangeable. Each stage is a constructed integer threshold network run by one generic executor. parse2 is an implementation name of the same contract, not a separate stage.

stage	input → output	role
preprocess (pp)	source bytes → preprocessed text	line continuation, comments, directives, macros, conditionals, includes
lex	preprocessed text → typed token stream	keywords, identifiers, operators, literals, longest match
parse	token stream → tape	declarations, scopes, types, precedence, statements, init, calls
opt	tape → tape	peephole / stack-to-reg style rewrites on tape
prune	tape → tape	drop unreachable whole functions on image/run routes (public tape out skips prune)
lowering	tape → target ops + data	ABI, regmap, syscalls, layout, reloc
encode + image (enc)	target ops → ELF / Mach-O / PE (or in-memory image)	encoding, branches, reloc, headers, Mach-O ad-hoc signature

The short names pp, lex, parse, and enc may match names of the 18 decision stages. They are the seven-stage byte-stream contract and are not interchangeable with the ask-domain tables.

The tape has eight 64-bit registers and 71 operations in `SHAPE`. The executor has no primitive for C, the tape, an ISA, or an image format.

The decision-network instance calls `ask` from classic recursive descent, lowering, and image writing; no fallback. The network-compiler instance runs the seven stages; a model rejection is an error. This tip has no same-identity size or speed measurement; this paper claims none.

Threshold-prefix evaluation and declared returns do not change network answers: same network, same sum; the network–table check still covers every observation, including returns. Host code still loads packages and retains `src/tapelink.c`, `src/asmtext.c`, and `src/fwdstub.c`. Build-time Python is in the trusted base.

5 Self-host, T1, and referees

Decision-network instance, byte equality:

1. Front-end fixed point: A compiles itself to B, B compiles itself to C, B = C, and both match the Python front end.

2. Back-end closure: 94 probes × 6 targets, 564/564; the compiler itself 6/6.

3. No Python: N1 = N2 = N3 on osx/arm64, lnx/arm64, lnx/x86-64, win/arm64, and win/x86-64 (the last under system emulation).

N1 = N2 = N3 asserts only unsigned successive-generation identity. The network compiler's driver self-host is N1 = N2 = N3 on macOS arm64 for a fixed network package and does not construct that package.

T1 runs every cube network with deployment arithmetic on every key of its declared domain; an error or a tie fails construction. On the normal C path the decision-network instance reads DENSE and compares table lookup with direct inference.

Six-target fold: the machine model recognises only the (OS, call number) from lowering. The six (stdout, exit) pairs agree with each other and with a tape reference VM. Clearing the class bits of macOS system-call numbers must yield 4/6. This tip has no native-versus-emulation matrix.

Eight of the 18 decision stages have a named referee. The ledger is `research/referee.tsv`. The eight rows below are the ledger's external entries; agreement and the rest are in that file. The table is a pointer, not a proof of C.

Referee	Check
Preprocess	`exec/pp/macrocheck.py`, `tests/ccparity.sh`, against `cc -E -P`
Parse	`tests/warn.sh`, (line, kind) against `cc -Wall`
Type	`_Generic`; 1,400 of 4,275 keys
ABI	host system-call headers; actual host OS and architecture only
Precedence	324 pairs; 291 distinguishable and consistent; 33 indistinguishable
Type info	sizes of 11 types; signedness and narrowness of 8 integer types
Binary-operator selection	`tests/binsel_audit.py`; 7 of 16 operators depend on signedness
printf	`tests/pfconv_audit.py`; 9 conversion letters

The table below is a recorded result, not a new seal remeasure of this tip `910f1e0a`. It does not prove table = C.

Item	Record
T1	18×1.000
type↔cc	1399/1400 (1 intentional difference)
c-testsuite	216/220
C99	59/59
difftest	93/93
opts	279/279
frontends	190/190
libs	11/11
closure	564/564 + self 6/6
`%f/%e/%g`	bit-identical with platform libc

6 Boundaries

Systematic construction-versus-training comparison is preregistered study A2. This paper has no training table.

The verification discipline has exposed cross-table combination gaps under one identity. Details are in `archive/research/r20/design-review-2026-10-01.md` and `research/paper-a-notes.md` and are not restated here. T1 asserts only network = table on one table's declared domain.

This tip has no same-identity census of the seven stages, no speed measurement, and no platform matrix. The corpus does not extend to arbitrary C99. Build-time Python is in the trusted base.

Related work, as pointers only: exact network encodings of finite-state machines (Omlin and Giles, 1996; Siegelmann and Sontag, 1995); weights constructed from programs (Weiss et al., 2021; Lindner et al., 2023); table-driven compilers (Johnson, 1975; Glanville and Graham, 1978; Fraser et al., 1992); trained controllers (Graves et al., 2014); proved semantic preservation (Leroy, 2009; Kumar et al., 2014); diverse double-compiling (Wheeler, 2009). Gradient-method failures are left to A2.

7 Conclusion

On table-shaped decisions, exactness is decidable by exhaustion. unisacc runs constructed weights on two layers: 18 decision stages, and seven byte-stream stages. The decision-network instance meets N1 = N2 = N3 on the five targets in §5. Whether a table equals C is answered only by the named referees, inside their coverage.

References

Boaz Barak, Benjamin L. Edelman, Surbhi Goel, Sham Kakade, Eran Malach, and Cyril Zhang. Hidden progress in deep learning: SGD learns parities near the computational limit. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. arXiv:2207.08799.

Matko Bošnjak, Tim Rocktäschel, Jason Naradowsky, and Sebastian Riedel. Programming with a differentiable Forth interpreter. Preprint, 2016. arXiv:1605.06640.

Chris Cummins, Volker Seeker, Dejan Grubisic, Baptiste Roziere, Jonas Gehring, Gabriel Synnaeve, and Hugh Leather. Meta Large Language Model Compiler: Foundation models of compiler optimization. Preprint, 2024. arXiv:2407.02524.

Christopher W. Fraser, David R. Hanson, and Todd A. Proebsting. Engineering a simple, efficient code-generator generator. *ACM Letters on Programming Languages and Systems*, 1(3):213–226, 1992. doi:10.1145/151640.151642.

Dan Friedman, Alexander Wettig, and Danqi Chen. Learning transformer programs. Preprint, 2023. arXiv:2306.01128.

Alexander L. Gaunt, Marc Brockschmidt, Rishabh Singh, Nate Kushman, Pushmeet Kohli, Jonathan Taylor, and Daniel Tarlow. TerpreT: A probabilistic programming language for program induction. Preprint, 2016. arXiv:1608.04428.

Angeliki Giannou, Shashank Rajput, Jy-yong Sohn, Kangwook Lee, Jason D. Lee, and Dimitris Papailiopoulos. Looped transformers as programmable computers. Preprint, 2023. arXiv:2301.13196.

R. Steven Glanville and Susan L. Graham. A new method for compiler code generation. In *Proceedings of the 5th ACM SIGACT-SIGPLAN Symposium on Principles of Programming Languages (POPL)*, pages 231–254, 1978. doi:10.1145/512760.512785.

Alex Graves, Greg Wayne, and Ivo Danihelka. Neural Turing machines. Preprint, 2014. arXiv:1410.5401.

Frédéric Gruau, Jean-Yves Ratajszczak, and Gilles Wiber. A neural compiler. *Theoretical Computer Science*, 141(1–2):1–52, 1995. doi:10.1016/0304-3975(94)00200-3.

Stephen C. Johnson. Yacc: Yet another compiler-compiler. Computing Science Technical Report 32, Bell Laboratories, Murray Hill, NJ, 1975.

Ramana Kumar, Magnus O. Myreen, Michael Norrish, and Scott Owens. CakeML: A verified implementation of ML. In *Proceedings of the 41st ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*, pages 179–191, 2014. doi:10.1145/2535838.2535841.

Xavier Leroy. Formal verification of a realistic compiler. *Communications of the ACM*, 52(7):107–115, 2009. doi:10.1145/1538788.1538814.

David Lindner, János Kramár, Sebastian Farquhar, Matthew Rahtz, Thomas McGrath, and Vladimir Mikulik. Tracr: Compiled transformers as a laboratory for interpretability. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. arXiv:2301.05062.

Eran Malach and Shai Shalev-Shwartz. When hardness of approximation meets hardness of learning. Preprint, 2020. arXiv:2008.08059.

Christian W. Omlin and C. Lee Giles. Constructing deterministic finite-state automata in recurrent neural networks. *Journal of the ACM*, 43(6):937–972, 1996. doi:10.1145/235809.235811.

Shai Shalev-Shwartz, Ohad Shamir, and Shaked Shammah. Failures of gradient-based deep learning. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, 2017. arXiv:1703.07950.

Ohad Shamir. Distribution-specific hardness of learning neural networks. *Journal of Machine Learning Research*, 19(32):1–29, 2018.

Peter Shaw, James Cohan, Jacob Eisenstein, Kenton Lee, Jonathan Berant, and Kristina Toutanova. ALTA: Compiler-based analysis of transformers. Preprint, 2024. arXiv:2410.18077.

Hava T. Siegelmann and Eduardo D. Sontag. On the computational power of neural nets. *Journal of Computer and System Sciences*, 50(1):132–150, 1995. doi:10.1006/jcss.1995.1013.

Hanzhuo Tan, Qi Luo, Jing Li, and Yuqun Zhang. LLM4Decompile: Decompiling binary code with large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2024. doi:10.18653/v1/2024.emnlp-main.203; arXiv:2403.05286.

Mircea Trofin, Yundi Qian, Eugene Brevdo, Zinan Lin, Krzysztof Choromanski, and David Li. MLGO: A machine learning guided compiler optimizations framework. Preprint, 2021. arXiv:2101.04808.

Petar Veličković and Charles Blundell. Neural algorithmic reasoning. *Patterns*, 2021. doi:10.1016/j.patter.2021.100273; arXiv:2105.02761.

Petar Veličković, Adrià Puigdomènech Badia, David Budden, Razvan Pascanu, Andrea Banino, Misha Dashevskiy, Raia Hadsell, and Charles Blundell. The CLRS algorithmic reasoning benchmark. Preprint, 2022. arXiv:2205.15659.

Gail Weiss, Yoav Goldberg, and Eran Yahav. Thinking like transformers. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, 2021. arXiv:2106.06981.

Yixuan Weng, Minjun Zhu, Fei Xia, Bin Li, Shizhu He, Kang Liu, and Jun Zhao. Mastering symbolic operations: Augmenting language models with compiled neural networks. Preprint, 2023. arXiv:2304.01665.

David A. Wheeler. *Fully Countering Trusting Trust through Diverse Double-Compiling*. PhD thesis, George Mason University, 2009. arXiv:1004.5534.

A Artifacts and Evidence

Identity	Content
Source tree	main `910f1e0a`; `src/version.h` is `0.0.42`. Not public Latest and not a sealed release measurement.

Pointers: `research/referee.tsv`, `research/formalization-roadmap.md`, `research/lean/`, `research/prior-art.md`, `research/paper-a-notes.md`.

```
python3 -m unisa build-weights
python3 -m unisa acc
python3 -m unisa run examples/hello.c --fold
./tests/closure.sh examples/*.c tests/c/*.c
./tests/nativeboot.sh
./tests/gate.sh --list --com
```