

LAB -4 (Updated)

Operators in SQL

Objective: To be familiar with different operators in SQL

Problem:

👉 **Create a table named employee with the following attributes by considering employee_id as primary key**

employee(employee_id,first_name,last_name, age,address, department,postion,salary)

create table employee(employee_id int PRIMARY KEY,first_name varchar(20),last_name varchar(20),age int,address varchar(30),department varchar(30), position varchar(30),salary float(12,4));

👉 **Now insert at least any 10 records of employee.**

employee_id	first_name	last_name	age	Addresss	department	Position	salary
1	anish	Sharma	26	Kathmandu	Finance	Manager	80000
2	roshan	pokhrel	28	Pokhara	Sales	Analyst	60000
3	aakriti	Bagale	30	Butwal	Purchase	Manager	95000
4	rojina	Karki	25	Pokhara	Marketing	Manager	85000
5	keshav	ghimire	35	Kathmandu	Purchase	Analyst	65000
6	roshan	Pandey	38	Chitwan	Operations	Analyst	70000
7	sita	pokhrel	23	Lalitpur	Marketing	Analyst	68000
8	srijana	Bhattra	29	Butwal	Finance	Analyst	62000
9	niraj	Acharya	40	Kathmandu	Sales	Manager	90000
10	nikita	Giri	15	Pokhara	Purchase	Secretary	25000

```
insert into employee values(1,'anish','sharma',26,'kathmandu','finance','manager',80000);
insert into employee values(2,'roshan','pokhrel',28,'pokhara','sales','analyst',60000);
insert into employee values(3,'aakriti','bagale',30,'butwal','purchase','manager',95000);
insert into employee values(4,'rojina','karki',25,'pokhara','marketing','manager',85000);
insert into employee values(5,'keshav','ghimire',35,'kathmandu','purchase','analyst',65000);
insert into employee values(6,'roshan','pandey',38,'chitwan','operations','analyst',70000);
insert into employee values(7,'sita','pokhrel',23,'lalitpur','marketing','analyst',68000);
insert into employee values(8,'srijana','bhattra',29,'butwal','finance','analyst',62000);
insert into employee values(9,'niraj','acharya',40,'kathmandu','sales','manager',90000);
insert into employee values(10,'nikita','giri',15,'pokhara','purchase','secretary',25000);
```

Now, Write a query to perform the following operations

Arithmetic, logical and relational operators

1. **Display the first_name and last_name of employee whose department is finance**

```
select first_name,last_name from employee where department='finance';
```

2. **Display all the information of employee in employee table whose address is not kathmandu**

```
select * from employee where address!='kathmandu';
```

3. **Increment the salary of all employees by 15%**

```
update employee set salary=salary*1.15;
```

4. **Decrease the salary of manager by 5%**

```
update employee set salary=salary*0.95 where position='manager';
```

5. **Delete information of employee whose age is less than 18**

```
delete from employee where age<18;
```

6. **Display the position of employee whose salary is greater than or equals to 50000**

```
select distinct position from employee where salary >=50000;
```

7. **Display information of employee whose position is manager and address is kathmandu**

```
select * from employee where position='manager' and address='kathmandu';
```

8. **Display information of employee whose position is manager or address is kathmandu**

```
select * from employee where position='manager' or address='kathmandu';
```

9. **Display information of employee who either live in pokhara or kathmandu but age is greater than 25**

```
select * from employee where (address='kathmandu' or address='pokhara') and age>25;
```

10. Display first_name,last_name and position of employee whose salary is in the range of 70000 to 80000

```
select first_name,last_name,position from employee where salary between 70000 and 80000;
```

11. Display first_name,last_name and position of employee whose salary is not in the range of 70000 to 80000

```
select first_name,last_name,position from employee where salary not between 70000 and 80000;
```

12. Display the information of employee whose salary is equal to 69000,30000,35000,40000,71300,80500

```
select * from employee where salary in (69000,30000,35000,40000,71300,80500);
```

13. Display information of employee whose department is (sales, purchase) but not salary equal to (69000,71300,80500)

```
select * from employee where department in ('sales','purchase') and salary not in (69000,71300,80500);
```

Like operator with wildcard characters

14. Display information of employees whose first_name starts with letter 'a'

```
select * from employee where first_name like 'a%';
```

15. Display information of employees whose first_name starts with letter 'ro'

```
select * from employee where first_name like 'ro%';
```

16. Display information of employees whose last_name ends with letter 'el'

```
select * from employee where last_name like '%el';
```

17. Display information of employees whose first_name has exactly six characters

```
select * from employee where first_name like '____';
```

18. Display information of employees whose first_name starts with r and has exactly six characters

```
select * from employee where first_name like 'r_____';
```

19. Display the information of employees which contains substring of first_name as 'sha'

```
select * from employee where first_name like '%sha%';
```

20. Display information of employees whose second position of first_name contains letter 'o'

```
select * from employee where first_name like '_o%';
```

21. Display the information of employees whose third position of first_name contains the letter 's'

```
select * from employee where first_name like '__s%';
```

22. Display information of employees which have first_name of at least six characters

```
select * from employee where first_name like '_____%';
```

23. Display the information of employees whose first_name begins with a,k,m,s,r .

```
select * from employee where first_name like '[akmsr]%' ;
```

24. Display information of employees whose first_name begins with [a-s] and ends with l

```
select * from employee where name like '[a-s]%' ;
```

25. Display information of employees whose first_name does not start with d but ends with h

```
select * from employee where first_name like '[^d]%' ;
```

Select distinct in SQL

26. Display the different position available for employee

```
select distinct position from employee;
```

27. List out the unique address available for employee table

```
select distinct address from employee;
```

28. List out the employee who have unique first_name and address

```
select distinct first_name,address from employee;
```

AS

29. Write a query to get first_name,last_name , ssf of all employees .ssf is calculated as 31% of salary

```
select first_name,last_name, salary*0.31 as ssf from employee;
```

30. write a query to get the employee _id, name (first_name, last_name), location (address) from employee

```
select employee_id ,concat(first_name,' ',last_name) as name ,address as location from employee;
```

ORDER BY

31. Display the information of employees in ascending order by address

```
select * from employee order by address ;
```

or

```
select * from employee order by address asc;
```

32. Display the information of employees in descending order by address

```
select * from employee order by address desc;
```

33. Display the information of employees in ascending order by address and department

```
select * from employee order by address,department;
```

Aggregate functions

34. Count the number of employees

```
select count(*) from employee;
```

35. Count the number of unique first_name of employees

```
select count(distinct first_name) from employee;
```

36. To get the number of different number of positions available for employees table

```
select count(distinct position) from employee;
```

37.To get the total salaries payable to employees.

```
select sum(salary) from employee;
```

38. Find the average salary of employess

```
select avg(salary) from employee;
```

39. Find the minimum salary of employess

```
select min(salary) from employee;
```

40. Display first_name, last_name of employees with highest salary

```
select first_name,last_name from employee where salary=(select max(salary) from employee);
```

41. Display fist_name,last_name,department,postion whose salary is less than average salary of all employees

```
select first_name,last_name,department,position from employee where salary<(select avg(salary) from employee);
```

Group by and having clause

42. Find the average salary of employees in each department

```
select department,avg(salary) as average_salary from employee group by department;
```

43.Find the average salary of employees for each position

```
select position,avg(salary) as average_salary from employee group by position;
```

44.Find the department with their average salary is greater than 60000

```
select department ,avg(salary)
```

```
from employee
```

```
group by department
```

```
having avg(salary)>60000;
```

45. Find the position of the employee in which average salary of position is greater than 60000

```
select position from employee group by position having avg(salary)>60000;
```