Typed Decision Models as Passage Rerankers: Effectiveness, Calibration, and Context Selection

Parv Bhargava
Independent Researcher
parvbhargavapro@gmail.com

Abstract

Typed decision models return probabilities over caller-defined options without generating free text. We evaluate four model families (Jev, Clef, Jeff, and Laya) as pointwise passage rerankers on the BM25 top-100 candidates of TREC DL 2019–2023 and eight BEIR collections, and ask three questions: how well they rank, whether their relevance probabilities are calibrated, and whether those probabilities help select context for retrieval-augmented generation (RAG). Across its three question formats, Jev averages 55.3–56.1 nDCG@10, on par with Qwen3-Reranker-8B (56.0) and above bge-reranker-v2-m3 (53.7), with large variation across collections. Where the base model is known, same-base controls give mixed answers: Clef does not differ significantly from its base model on six of the seven collections tested (it is ahead on Robust04, where its base reads less text), while the small Jeff model improves on its base; Jev's base model is not public. Without any target-collection labels, Jev's raw yes/no probabilities have lower calibration error than bge-reranker-v2-m3 (ECE 15.0 vs. 20.0), but calibrating bge on other collections with the same relevance threshold closes this gap (6.9 vs. 6.8), and rewording the prompt changes raw calibration error by more than this difference. In RAG on MuSiQue and NQ with three generators, Jev's rankings improve multi-hop answer F1 over bge-reranker-v2-m3: on a family-disjoint MuSiQue split that shares no decomposition sub-question with the calibration or pilot questions, Jev wins 26 of 27 policy–generator comparisons, by up to 16.9 F1; on the original split, Jev also beats Qwen3-Reranker-8B, which matches it in ranking, in 26 of 27 MuSiQue comparisons. Probability thresholds, however, do not improve over fixed top-k selection. Typed decision models are thus competitive rerankers, but better-calibrated probabilities alone do not yield better context selection.

Keywords

reranking, decision models, calibration, retrieval-augmented generation, BEIR

1 Introduction

Retrieval-augmented generation (RAG) pipelines typically retrieve candidates with a cheap first stage, rerank them with a cross-encoder [34] or an LLM [47], and pass a fixed top-k to the generator. Two weaknesses of this recipe are well known: cross-encoders trained on MS MARCO transfer imperfectly to new domains [50], and their scores are not probabilities [36], so the cut-off k is chosen by habit rather than by evidence.

A recently released class of models targets both: *typed decision models* such as Jev [54], Cloudflare Clef [7], Jeff [18], and Laya [10]. Instead of generating text, they answer a typed question about a state—a choice among named options, a yes/no (Noul) question, or an ordered scale—and return per-option probabilities. A relevance judgment is a natural typed question (*Is this passage relevant to the query?*), and a per-option probability is exactly what a context-selection rule such as "keep passages with $P(\text{relevant}) > t$" needs. Whether that probability is actually calibrated, and whether such a threshold beats a fixed cut-off, are empirical questions that the interface alone does not answer.

Evidence so far is thin: decision models have been evaluated for recommendation reranking [27] and agent-memory selection [46], a practitioner blog reports Jev results on two BEIR datasets [21], and an early audit finds that typed readouts have not yet shown an accuracy advantage over comparable label-probability readouts [49]. No systematic study has evaluated decision models as passage rerankers on standard IR benchmarks against cross-encoders and label-probability LLM rerankers, or measured whether their relevance probabilities are calibrated.

We provide that study, organized around three research questions. **RQ1:** Can typed decision models, used without task-specific tuning as pointwise rerankers, match cross-encoders and label-probability LLM rerankers? **RQ2:** Are their relevance probabilities calibrated, with and without labels from the target collection? **RQ3:** Do these probabilities help decide which passages a retrieval-augmented generator should see? Our contributions and main findings are: (1) An evaluation of four decision-model families and three question formats on 13 collections against cross-encoders and label-probability LLM rerankers, with same-base controls for Clef and Jeff and equal-context ablations. The large decision models are on par with the strongest label-probability reranker we test; Clef is close to its own base LLM, and Jev's base is unknown. (2) A calibration analysis on nine collections with judged negatives. Raw yes/no probabilities from Jev and Laya are better calibrated than raw cross-encoder scores, but a cross-encoder calibrated on other collections closes the gap, so the practical advantage is not needing labelled source data; raw calibration also depends strongly on the prompt wording. (3) A RAG evaluation on MuSiQue and NQ with three generators, comparing fixed top-k, gap-based, and threshold-based context selection. Jev's rankings help multi-hop QA more than those of bge-reranker-v2-m3, including on a family-disjoint split, and on the original split more than those of the equally effective Qwen3-Reranker-8B, and Jev more often ranks the answer-bearing hop first, yet probability thresholds do not beat fixed k. (4) Code for reproducing and extending the evaluation, with input hashes, split IDs, and all statistical outputs.

2 Related Work

Neural and LLM reranking. Cross-encoders score each query–passage pair jointly [34, 35] and remain the default second stage; BEIR showed that their in-domain gains shrink out of domain [50].

LLM rerankers can be pointwise, pairwise, setwise, or listwise: RankGPT's sliding-window listwise prompting is competitive with supervised rerankers [47], distilled listwise models such as RankZephyr and FIRST make this cheaper [38, 42], and setwise prompting trades off the two [63]. Pointwise LLM rankers read relevance from the probability of a "yes" token and improve with graded rather than binary labels [62]; Qwen3-Reranker is a recent model trained for exactly this readout [61]. Typed decision models are also pointwise, but their answer space is a declared set of options, each of which receives a probability by construction; we compare them directly with label-probability rerankers.

LLMs as relevance assessors. LLMs can predict human relevance preferences [51] and are used to generate relevance labels at scale [55], with ongoing debate about the risks of doing so [9, 17]; the LLMJudge challenge benchmarks such assessors on TREC DL [41]. These studies measure label agreement; we measure whether the probabilities are calibrated.

Typed decision models. Jev [54], its open counterparts Jeff [18] and Laya [10], and Cloudflare's Clef [7] share a request format of a state plus typed questions. The public JevBench leaderboard [29] (not peer reviewed) ranks such models on accuracy, calibration, speed, and cost, but reports no retrieval tasks. The closest academic work evaluates Jev for product recommendation reranking [27]; others use it to select agent-memory records [46]. A study of the fine-tuned Laya typed-decisions checkpoint finds it uniformly under-confident on workflow decisions [31], and Jev is reported calibrated on familiar closed-choice tasks but over-confident beyond its knowledge boundary [44]; an early audit of 28 papers on Jev finds its clearest gains in latency and cost rather than accuracy over comparable label-probability readouts [49], which is the comparison our label-probability baselines make for retrieval. In non-peer-reviewed reports, practitioners have described Jev reranking results on SciFact and NFCorpus [21] and, in a pre-registered experiment on the roughly 1,000 MS MARCO candidates per DL19 query, found Jev's ten-level score readout below its Noul answer and both below monoBERT (65.2, 68.4, and 71.8 nDCG@10) [5]. We rerank only the BM25 top-100, where Jev's DL19 scores are 71.3–72.8.

Calibrated relevance and context selection. Neural rankers are known to be poorly calibrated [36], as are modern neural networks generally [20], and ranking losses leave the scale of scores unconstrained, which motivates scale-calibrated training [59]; Platt scaling [37] is the standard fix but needs labels. LLM rerankers' verbalized confidence in their own ranking quality is severely over-confident, although self-consistency estimates are better calibrated [33], and fine-tuned small LLMs can be trained to give calibrated relevance for RAG [32]. For deciding how much context a generator sees, learned selectors [30], score-gap heuristics [48], context filtering and compression [8, 56, 58], and retrieval evaluators that trigger corrective actions [60] replace a fixed k; other work decides whether and how often to retrieve at all [2, 22], or interleaves retrieval with reasoning for multi-hop questions [53]. Irrelevant passages and their position affect RAG answers in non-obvious ways [16, 26]. We test whether off-the-shelf decision-model probabilities make such selection a simple threshold.

Table 1: The three typed relevance questions (instructions and option criteria verbatim from our code) and how each answer is read out for ranking. p_x: probability of option x; $\mathbb{E}[\ell]$: probability-weighted level.

Format	Question and options	Primary score
Choice-3 (C3)	*How relevant is the passage to the search query?* relevant: "The passage directly answers or fully addresses the query."; partially: "The passage is on topic and partly addresses the query, but is incomplete or indirect."; not_relevant: "The passage does not address the query."	$\frac{1}{2}(2p_{\text{rel}} + p_{\text{part}})$
Noul	*Does the passage answer or address the search query?* true: "The passage answers or substantively addresses the query."; false: "The passage is off topic or does not help answer the query."	$P(\text{yes})$
Score-4 (S4)	*How relevant is the passage to the search query?* 0: "Irrelevant: the passage has nothing to do with the query."; 1: "Related: on topic but does not answer the query."; 2: "Highly relevant: partly answers the query."; 3: "Perfectly relevant: dedicated to the query and fully answers it."	$\mathbb{E}[\ell]/3$

3 Decision Models as Pointwise Rerankers

For a query q and candidate passage d, we send the state $\{\texttt{query} : q, \texttt{passage} : d\}$ with three typed relevance questions (Table 1). All three can be asked in one request (Jeff's server evaluates each question in a separate forward pass; Laya answers all three in one shared pass), so every decision model in our study answers all three formats in a single call per pair; the three answers are therefore not independent samples.

For every backend, the Score-4 value returned by the model equals the probability-weighted level $\mathbb{E}[\ell]$ computed from its option probabilities (checked on 20,000 answers per model; maximum deviation 0.03, from Jev's two-decimal rounding).

Probability readout. Calibration needs a probability for the *binarized* relevance a collection uses. The strict readout is p_{rel} (C3), $P(\ell \geq 2)$ (S4), or $P(\text{yes})$ (Noul); the lenient readout, for collections whose lowest relevant grade means *partially* relevant, is $p_{\text{rel}} + p_{\text{part}}$ (C3) or $P(\ell \geq 1)$ (S4). We assign the lenient readout to TREC-COVID, DBPedia, and News, whose label definitions describe the lowest relevant grade as partial, and the strict readout elsewhere. *Disclosure:* this assignment was introduced after we had observed a Choice-3 ECE of 43.9 on TREC-COVID under the strict readout. It is the most favorable readout policy for Jev's Choice-3 answers (mean ECE 14.8, versus 19.2 strict everywhere and 34.8 lenient everywhere); the Noul readout does not depend on it. We therefore lead with Noul and with the strict-everywhere readout in our calibration claims, treat the per-collection policy as a sensitivity analysis, report every Choice-3 and Score-4 system under the strict readout in Table 4 with the policy as marked sensitivity rows, and give both readouts for every collection in Appendix Table 8. We separately evaluate source-label transfer grouped by numeric binarization threshold (Section 4); this grouping does not imply identical relevance semantics or the same adaptation as the readout policy.

Ties. Some decision models report probabilities rounded to two decimals, producing thousands of exact ties per collection. To avoid `trec_eval`'s document-ID tie-breaking, exact model-score ties use

BM25 rank. Choice-3 first adds $10^{-6} p_{\text{rel}}$ to the listed expected-grade score, so ties in primary expected grade are distinguished by strict relevance probability before BM25. This perturbation is part of the cached scoring configuration; the table lists its primary score.

4 Experimental Setup

Collections and candidates. We use the candidates and relevance judgments of the RankGPT/RankLLM evaluation [45, 47] (our rerankers are pointwise, not listwise): TREC DL 2019–2023 passage [11–15] (43/54/53/76/82 queries) and eight BEIR collections [50]—TREC-COVID, NFCorpus, Touche, DBPedia, SciFact, Signal, News, and Robust04 (308 DL and 1,525 BEIR queries, 1,833 in total; 15 NFCorpus queries have no BM25 candidates and score zero for every system). Candidates are the Pyserini [25] BM25 top-100 runs distributed with RankLLM, evaluated with the official Pyserini qrels; our BM25 nDCG@10 reproduces RankGPT's reported values on DL19/20 and seven of the eight BEIR collections (NFCorpus: 32.2 vs. 30.8). Two caveats apply to the newer DL years: 31 of the 82 DL23 queries are synthetic (generated by T5 or GPT-4), and the DL22 judgments were propagated to near-duplicate passages; we follow common practice and keep both. All systems rerank the full top-100 and are evaluated with `ir_measures` [28]. We use depth 100 because it is the depth at which RankGPT and RankLLM report results on these runs, and because the strong rerankers still improve between depths 50 and 100 on TREC DL (Appendix Table 7). Since pointwise scores are computed independently per passage, shallower depths can be simulated exactly from the same scores, and a pointwise reranker's cost grows linearly with depth.

Systems. Cross-encoders, both trained with MS MARCO [4] data: `ms-marco-MiniLM-L6-v2` (22M) and `bge-reranker-v2-m3` (568M, fp16) [3, 6], both with a 512-token window. Label-probability LLM rerankers, which read relevance from the probability of a "yes" token rather than from a typed answer: Qwen3-Reranker-0.6B, 4B, and 8B [61] with their official instruction template (4B and 8B with 4-bit NF4 weights to fit an 8 GB GPU), and Qwen3-235B-A22B-Instruct-2507 [40] prompted pointwise for a Yes/No answer, with $P(\text{yes})$ renormalized over the Yes and No tokens among the top-5 next-token probabilities [62] (0.5 if neither appears, 1 or 0 if only one does; via OpenRouter, restricted to two fp8 deployments; DL19–23, TREC-COVID, NFCorpus, and Robust04 only, for cost). As a same-base control we ask Clef's base model, Qwen3.8-27B, the pointwise Yes/No prompt (Cloudflare's deployment via OpenRouter, reasoning disabled; on the seven collections where Clef was run), and Jeff's base model, Qwen3.5-0.8B (locally, thinking disabled, on all 13 collections; $P(\text{yes})$ from the full next-token distribution). For Qwen3-235B and Jeff's base model we also use a graded readout [62]: the same prompt asks for a 0–4 rating, and passages are ranked by the expected rating over the five digit tokens. All of these read the first 448 passage tokens, the cross-encoders' budget. Qwen3-Reranker-0.6B is close to bge-reranker-v2-m3 on average but significantly worse on DL22, DL23, and Touche. Decision models, all used without task-specific tuning on our side: Laya (421M, ModernBERT-large [57]) [10]; Jeff-Qwen3.5-0.8B v1.2 [18]; Jev 1.13 (snapshot `20260917`) via the OpenRouter Decisions API [54]; and Clef 27B [7], an open-weight decision model adapted from Qwen3.8-27B, through Cloudflare's deployment on the same API (DL19–23, TREC-COVID, and Robust04 only, for cost). Jev is a closed model whose training data we cannot inspect; MS MARCO, BEIR, and Robust04 are old, public collections that may overlap with it. For reference we also quote published results on the identical BM25 top-100 runs: monoT5-3B [35] and RankGPT [47].

Context budgets. Models read different amounts of each passage: the cross-encoders 512 tokens including the query, Laya about 320 passage tokens, Jev, Clef, and Jeff the first 4,000 characters (≈1,000 tokens), and the label-probability LLMs 448 passage tokens. On TREC DL, DBPedia, and Signal almost no passage is truncated; on the BEIR abstract collections (TREC-COVID, NFCorpus, SciFact) 29–38% exceed the cross-encoders' budget; and on Touche, News, and Robust04 69–97% do (Table 3). As newer-content benchmark checks we add NovelEval-2306 [47] (21 queries, 20 passages each, graded 0–2) and FutureQueryEval [1] (148 queries about events after April 2025, graded 0–2, BM25 top-100 built with `bm25s` over its 2,787-document corpus); they are reported separately and not included in the 13-collection averages. For the three long-document collections we add an equal-budget condition in which every passage is cut to its first 448 tokens before any model sees it, and bge-reranker-v2-m3 at a 2,048-token window.

Metrics and tests. Ranking: nDCG@10 with paired two-sided t-tests over queries; Holm correction covers the collections available for each system–baseline pair, not the roughly 40 pairs or formats. Table averages weight collections equally. We additionally pool collection effects with DerSimonian–Laird random effects and report both normal inference and a post-hoc modified Knapp–Hartung sensitivity analysis [43]. mKH uses Student-t with $k-1$ degrees of freedom and floors the residual variance multiplier at one. Pooled TOST with a ±2 nDCG margin is exploratory: the margin was chosen after seeing results, and normal/mKH conclusions are distinguished. We also report Judged@10 and condensed nDCG′@10 to assess sensitivity to incomplete pools. Calibration: ECE (15 equal-width bins) and Brier score on judged pairs from nine collections with negatives (DL19–23, TREC-COVID, DBPedia, News, Robust04), with paired query-cluster bootstrap 95% CIs (2,000 replicates; Holm over nine collections). Transfer Platt scaling uses no target labels: All pools the other collections with equal weight per pair; Group restricts sources to the same numeric binarization threshold and weights source collections equally (DL→DL, dense BEIR→BEIR). Numeric thresholds need not encode identical relevance semantics, especially for partial versus strict relevance in BEIR. In-collection Platt scaling uses target labels with 10× repeated five-fold query cross-fitting and serves as a reference floor. Because judged pairs are not a random sample of candidates, we also report ECE when unjudged candidates are treated as non-relevant (Appendix).

RQ3: context selection. We use MuSiQue-Ans dev [52] (multi-hop; 20 candidate paragraphs per question, 2–4 labelled as supporting) and NQ-open test [24] with the DPR top-20 passages [23] (single-hop; 18.6% of final-set questions have no answer-bearing passage; gold labels come from DPR's string-match `has_answer` flag). With seed 13, each dataset is split into calibration (200), pilot (300), and final (1,000) questions with disjoint IDs. MuSiQue families were not kept together: 494 of 1,000 final questions reuse their final decomposition sub-question ID from pilot, 349 from calibration,

and 578 from either (265 from both). Counting any decomposition sub-question ID, 671 final questions overlap either design split. For MuSiQue we therefore built a *family-disjoint* split after the original analysis. Families are connected components over all 2,417 MuSiQue dev questions, linking questions that share any decomposition ID. We drop every family that contains a pilot question, shuffle the remaining families with seed 13, and assign whole families to a calibration split (`calib_fd`, 199 questions in 95 families, hop-stratified) and a final split (`final_fd`, 597 questions in 270 families; largest family 20 questions). No decomposition ID or family is shared between `calib_fd`, `final_fd`, and the pilot. Because the large 3- and 4-hop families reach the pilot, `final_fd` is 88% 2-hop (526/58/13 two-, three-, and four-hop questions, versus 52/31/17% in the original final split). We reuse the nine policies and thresholds locked after the original pilot without re-tuning, and refit Platt scaling and Jev's readout on `calib_fd`. The family-disjoint split is our primary MuSiQue result; the original split and the retrospective 329-question subset without directly shared sub-question IDs are reported as sensitivity analyses. NQ questions have no decompositions and keep the original split. The calibration set is used to fit Platt scaling on gold labels and to choose Jev's probability readout by Brier score (Noul on MuSiQue, Choice-3 strict on NQ); thresholds are therefore applied to *Platt-scaled* probabilities that use target-dataset labels. Jev ranks candidates by its Score-4 expected level, bge-reranker-v2-m3 by its logit. After the final results we added, on the original split only, Qwen3-Reranker-8B (4-bit) and Qwen3-Reranker-0.6B, which rank by their yes-probability (448-token passage budget, as in RQ1; MuSiQue and DPR passages are shorter); they receive the same nine policies, with Platt scaling fit on the same calibration questions. Policies select passages by fixed top-k, Adaptive-k (cut at the largest gap in the ranker's own score [48]), a threshold $P > t$, or top-2 plus any further passage with $P > t$ ("top-2+threshold"). The nine policies compared between rankers are top-1/2/3/5, Adaptive-k, top-2+threshold at 0.3 and 0.5, and threshold at 0.2 and 0.3. Three generators answer with the selected passages (temperature 0, at most 32 tokens, no option to abstain; prompt in the Appendix): Qwen2.5-7B-Instruct [39], Llama-3.1-8B-Instruct [19], and Qwen3-30B-A3B-Instruct-2507, via OpenRouter. We score answers with SQuAD-normalized F1. Policies and thresholds were fixed after the pilot before final generation. The locked threshold-rule comparisons were against top-3 and Adaptive-k; comparisons against top-2 and top-5 were added later and are exploratory. The pilot motivated the top-2+threshold floor. Raw thresholds (MuSiQue pilot Qwen2.5-7B: 41.6 F1 at 0.3 versus 43.9 Platt-scaled) were dropped from the lock and added after final results as a post-hoc analysis. Their probability readout still uses labelled calibration questions, so they avoid Platt fitting but are not label-free. Comparisons are paired over questions. For each dataset and generator, Holm correction is applied separately to the nine ranker-effect tests (Jev vs. bge-reranker-v2-m3 under each policy) and to the four threshold-rule tests (top-2+threshold at 0.3 vs. top-2, top-3, top-5, and Adaptive-k); an earlier version of our analysis mixed the two families, and we separated them after an internal review. We add 95% CIs and, after seeing the final results, TOST equivalence tests with a ±2 F1 margin, which we report as post-hoc and without multiplicity correction. Question-level tests do not account for dependence between questions of the same MuSiQue family. For `final_fd` and for the 329-question sensitivity analysis we therefore add unadjusted paired family-bootstrap 95% percentile CIs (20,000 replicates, seed 13); 270 and 212 families contain questions of the two sets. Each replicate samples families with replacement and divides the summed paired F1 differences by the sampled question count, preserving the question-weighted estimand.

Hardware. Local models ran on a laptop RTX 4060 (8 GB); Jeff ran through its reference server, whose attention kernels fall back to a slow reference implementation on Windows, so its latency is pessimistic. API models were called through OpenRouter; Jev received all three questions per call. All API calls in this study cost about $31 in total, so every experiment can be reproduced on a small budget. OpenRouter routed the Llama and Qwen3-30B generators across several hosting providers (Qwen2.5-7B was served by one), which may serve differently quantized weights; provider assignment was balanced across policies, and we record the provider of every call.

5 Results

RQ1: Effectiveness. Large decision models are on par with the strongest label-probability reranker. Over the 13 collections (Table 2; all formats in Appendix Table 14), Jev averages 55.3–56.1 nDCG@10 across its three formats (Score-4: 56.1), Qwen3-Reranker-8B 56.0, Qwen3-Reranker-4B 55.7, bge-reranker-v2-m3 53.7, Qwen3-Reranker-0.6B 52.9, MiniLM 51.9, and BM25 41.9. Pooling per-collection effects with random effects, Jev S4 minus Qwen8B is +0.3 (90% CI $[-1.3, 1.9]$), and Jev S4 minus bge is +2.6 (95% CI $[0.1, 5.1]$). Collection heterogeneity is large ($I^2 \approx 0.9$); with the small-sample modified Knapp–Hartung (mKH) correction both intervals widen slightly ($[-1.4, 2.0]$ and $[-0.4, 5.6]$; Appendix Table 13), so we read the evidence as parity with Qwen8B and a likely but not conclusive pooled advantage over bge. Without Robust04, Jev S4 minus Qwen8B is −0.3 (90% CI $[-1.4, 0.8]$; mKH $[-1.6, 1.0]$), so the parity does not depend on that collection. At the collection level, Jev S4 is significantly better than bge on five collections (DL21, TREC-COVID, NFCorpus, SciFact, Robust04) and significantly worse on none; against Qwen8B it is better on Robust04 (+7.9) and worse on Signal (−3.9, Holm). No single system wins everywhere: Clef is best on DL20, DL23, and Robust04, Jev on DL21, NFCorpus, and SciFact, the Qwen rerankers on DL19, TREC-COVID, DBPedia, and News, bge on DL22, MiniLM on Signal, and BM25 on Touche, where every neural reranker falls below the first stage. On TREC DL alone, Jev S4 averages 61.1 versus bge 60.6 and MiniLM 59.6 (pooled Jev–bge +0.7, 90% CI $[-1.2, 2.6]$); on BEIR, 53.0 versus 49.3. These results use BM25 candidates. On SPLADE++ candidates for DL19, Jev falls 3.1–5.5 points behind bge and below the SPLADE++ ranking itself, while on DL20 Jev Noul is the best system (Appendix A); the DL parity with the cross-encoders is therefore specific to the first stage.

Robust04 contributes much of the margin. Without it, Jev and bge average 55.3 and 53.8 over 12 collections (pooled +1.7, 95% CI $[0.1, 3.4]$; mKH $[-0.4, 3.9]$). Every LLM-based system is unusually strong on Robust04 (Jev 65.9, Clef 66.5, Qwen235B 60.2, Qwen0.6B/4B/8B 55.8/57.4/58.0, versus bge 51.9), which is consistent with either an advantage on long news articles or familiarity with these public 2004 topics. On newer-content benchmarks, Jev scores 62.5–63.5 on FutureQueryEval versus bge 58.2 ($p \leq 0.001$)

Table 2: nDCG@10 for reranking the BM25 top-100 (Pyserini runs and qrels, as in RankGPT/RankLLM). $^{\uparrow}/^{\downarrow}$: significantly better/worse than bge-reranker-v2-m3 (paired t-test over queries, Holm-corrected over the collections each pair was evaluated on, $p < 0.05$). Best displayed configuration per column in bold; all formats and controls appear in Appendix Table 14. Averages are reported only for systems run on every collection of the group (dash otherwise); matched comparisons for Clef and the P(yes) LLMs are given in the text. Touche, News and Robust04 contain long documents that every model truncates (Table 3).

	TREC Deep Learning						BEIR									
System	DL19	DL20	DL21	DL22	DL23	*Avg*	Covid	NFC	Touche	DBP	SciF	Signal	News	Rob04	*Avg*	**All**
BM25 (first stage)	50.6	48.0	44.6	26.9	26.2	39.3	59.5	32.2	**44.2**	31.8	67.9	33.1	39.5	40.7	43.6	41.9
Cross-encoders																
MiniLM-L6 (22M)	72.7	67.5	65.6	49.9	42.2	59.6	74.5	34.9	28.4$^{\downarrow}$	43.9	69.5$^{\downarrow}$	**33.9**$^{\uparrow}$	44.3	47.3$^{\downarrow}$	47.1	51.9
bge-reranker-v2-m3 (568M)	72.4	68.1	66.2	**51.4**	45.1	60.6	78.3	34.3	38.3	44.0	75.0	29.0	43.6	51.9	49.3	53.7
Label-probability LLM rerankers																
Qwen3-Reranker-0.6B	69.4	64.0	65.1	46.3$^{\downarrow}$	38.8$^{\downarrow}$	56.7	**86.2**$^{\uparrow}$	36.8$^{\uparrow}$	29.2$^{\downarrow}$	43.3	76.8	30.6	45.5	55.8$^{\uparrow}$	50.5	52.9
Qwen3-Reranker-4B (4-bit)	**74.0**	68.2	66.2	50.4	45.0	60.7	84.1$^{\uparrow}$	37.1$^{\uparrow}$	34.9	**46.4**$^{\uparrow}$	77.8	33.8$^{\uparrow}$	48.6$^{\uparrow}$	57.4$^{\uparrow}$	52.5	55.7
Qwen3-Reranker-8B (4-bit)	73.6	66.5	66.2	51.1	44.9	60.5	83.8$^{\uparrow}$	37.5$^{\uparrow}$	36.2	45.5	79.2$^{\uparrow}$	33.7$^{\uparrow}$	**51.6**$^{\uparrow}$	58.0$^{\uparrow}$	**53.2**	56.0
Qwen3-235B, P(yes)	68.6	66.5	65.6	46.2	42.8	57.9	80.0	34.6	–	–	–	–	–	60.2$^{\uparrow}$	–	–
Qwen3.8-27B (Clef's base), P(yes)	73.0	69.8	69.2	48.8	45.5	61.2	83.7	–	–	–	–	–	–	62.5$^{\uparrow}$	–	–
Qwen3.5-0.8B (Jeff's base), P(yes)	42.9$^{\downarrow}$	38.9$^{\downarrow}$	50.6$^{\downarrow}$	26.3$^{\downarrow}$	28.6$^{\downarrow}$	37.4	60.2$^{\downarrow}$	17.3$^{\downarrow}$	19.1$^{\downarrow}$	21.4$^{\downarrow}$	28.0$^{\downarrow}$	24.4$^{\downarrow}$	22.7$^{\downarrow}$	33.5$^{\downarrow}$	28.3	31.8
Laya (421M)																
Noul	57.1$^{\downarrow}$	52.1$^{\downarrow}$	55.0$^{\downarrow}$	36.2$^{\downarrow}$	32.0$^{\downarrow}$	46.5	74.2	28.9$^{\downarrow}$	22.5$^{\downarrow}$	28.7$^{\downarrow}$	44.5$^{\downarrow}$	21.8$^{\downarrow}$	35.7$^{\downarrow}$	34.5$^{\downarrow}$	36.4	40.3
Jeff (0.8B)																
Noul	59.5$^{\downarrow}$	50.1$^{\downarrow}$	52.5$^{\downarrow}$	33.0$^{\downarrow}$	30.4$^{\downarrow}$	45.1	67.3$^{\downarrow}$	24.5$^{\downarrow}$	23.5$^{\downarrow}$	30.0$^{\downarrow}$	46.7$^{\downarrow}$	27.4	33.6$^{\downarrow}$	34.1$^{\downarrow}$	35.9	39.4
Clef 27B (open weights, API; 7 collections)																
Score-4	72.2	**70.2**	69.3	49.1	**46.8**	**61.5**	84.0	–	–	–	–	–	–	**66.5**$^{\uparrow}$	–	–
Jev 1.13 (API)																
Noul	71.3	70.0	69.5	50.1	45.0	61.2	84.1	37.7$^{\uparrow}$	35.5	42.7	79.8$^{\uparrow}$	28.3	47.6	66.0$^{\uparrow}$	52.7	56.0
Score-4	72.8	69.9	**70.0**$^{\uparrow}$	48.5	44.3	61.1	85.0$^{\uparrow}$	**38.4**$^{\uparrow}$	31.6	44.5	**80.0**$^{\uparrow}$	29.8	48.6	65.9$^{\uparrow}$	53.0	**56.1**

and 90.4–91.3 on NovelEval versus 81.8 ($p \approx 0.05$); its leads over Qwen8B (61.2 and 86.2) are not significant.

Comparison with published listwise and seq2seq rerankers. On identical candidates, published monoT5-3B scores 51.4 on BEIR-8 and 71.8/68.9 on DL19/20, versus Jev S4 53.0 and 72.8/69.9 [47] (50.6 and 51.1 on BEIR without Robust04). RankLLM reports DL19–23 averages of 62.1 for RankZephyr-7B, 61.0 for DuoT5, and 60.4 for monoT5, versus Jev S4 61.1 [45]; our 4-bit RankZephyr DL19 check scores 72.5 versus the published 74.1. Because published per-query outputs are unavailable, these comparisons are descriptive. Published GPT-4 BEIR results use GPT-3.5's top-30 and are not comparable.

Clef and the larger yes/no baseline. On the seven collections where Clef was run, Clef averages 64.4–65.4 across formats, Jev 64.1–65.2, and bge 61.9; Jev S4 minus Clef S4 is within ±2 (normal pooled 95% CI $[-1.0, 0.4]$; also under mKH). Qwen235B's $P(\text{yes})$ averages 58.1 on its eight collections versus Jev Noul 61.7 (Jev significantly better on five, worse on none); a graded 0–4 readout raises Qwen235B to 59.8 (+1.8, 95% CI $[0.8, 2.8]$), still below Jev S4 at 61.8.

Same-base controls: Clef is close to its base LLM; Jeff improves on its base. On the seven collections where Clef was run, Clef's base Qwen3.8-27B averages 64.6 as a $P(\text{yes})$ ranker versus Clef's 64.4–65.4, and itself exceeds Qwen235B by 2.3–4.4 points on each. On DL19–23 and TREC-COVID, none of the 18 collection-level differences is significant (all within 2.5 points); on Robust04, every Clef format is 3.7–4.0 points ahead (Holm $p < 10^{-5}$), where Clef reads 4,000 characters but its base only 448 tokens (92% of Robust04 candidates are longer; Table 3). Pooled over the seven collections, Clef S4 minus its base is +1.0 (90% CI $[-0.3, 2.2]$; mKH $[-0.5, 2.5]$; Appendix Table 13), so ±2 equivalence is not established. Outside Robust04 we therefore find no ranking benefit of Clef over its base, in line with the early audit's caution about attributing quality to typed readouts [49]. In contrast, Jeff's formats average 39.1–39.4 over 13 collections versus 31.8 for its base (graded: 26.4), significantly better on 7–8 collections and worse on none. Because prompts and context budgets differ between each model and its base, these are configuration comparisons rather than isolated training effects. Jev's base, size, and training data are unknown; its 4,000-character context also exceeds the 448-token budget of the label-probability controls, and on Robust04 its Noul lead over Qwen235B shrinks from 5.7 to 2.4 at equal passage budget.

Small decision models are weak deep rerankers. Laya and Jeff average 39.1–41.2, below BM25's 41.9 at depth 100. They retrieve more unjudged passages (DL Judged@10 76–81% versus bge 96%) and score higher on condensed nDCG′ (58.6/57.3 versus BM25 51.8 and bge 64.0), and Laya's BEIR nDCG falls from 43.7 at depth 10 to 37.4 at depth 100 while its condensed nDCG rises (60.4 to 61.9). Part of their deficit may therefore reflect incomplete pools, although removing unjudged passages cannot show that those passages are relevant. Jev retrieves few unjudged passages (DL Judged@10 90.0%; condensed nDCG 66.9 versus bge 64.0). Within each family, the three question formats differ by at most 1.3 average points, much less than the differences between families.

Long documents. At the same first 448 passage tokens, Jev S4 exceeds bge by +11.5 on Robust04 and +4.9 on News ($p < 0.01$, Holm over three collections), versus +13.9 and +5.0 with full context, and loses on Touche (−9.9; Table 3). Qwen8B reads 448 passage tokens by default, so the same truncated Jev runs also give an equal-budget comparison with it: Jev S4 is −8.0 on Touche, −2.1 on News, and +5.1 on Robust04 (Touche and Robust04 significant after Holm),

Table 3: Long-document collections. Top: share of candidate passages longer than each model's passage budget (XLM-R tokens; Laya English ≈320, cross-encoders 448 at a 512 window, bge at 2,048 tokens, Jev/Jeff 4,000 characters). Bottom: nDCG@10 with each model's own window and with every passage cut to the same first 448 tokens ("=448"). Qwen8B (4k chars) reads the same first 4,000 characters as Jev. Δ: Jev Score-4 minus bge or Qwen8B at equal budget (paired t-test; *: $p < 0.05$).

	Touche	News	Robust04
Passages truncated (%)			
Laya (>320 tok)	77	99	96
cross-enc. (>448 tok)	69	97	92
bge-2048 (>2,000 tok)	5	22	25
Jev/Jeff (>4k chars)	43	75	72
nDCG@10			
BM25	44.2	39.5	40.7
MiniLM (512)	28.4	44.3	47.3
MiniLM (=448)	29.2	43.5	47.4
bge (512)	38.3	43.6	51.9
bge (=448)	38.1	44.6	51.5
bge (2,048)	37.5	47.8	51.6
Jev S4 (4k chars)	31.6	48.6	65.9
Jev S4 (=448)	28.2	49.4	63.1
Qwen8B (448)	36.2	51.6	58.0
Qwen8B (4k chars)	38.7	53.2	60.5
Δ Jev−bge (=448)	-9.9*	+4.9*	+11.5*
Δ Jev−Qwen8B (4k chars)	-7.0*	-4.6*	+5.3*

versus −4.5, −3.0, and +7.9 when Jev reads 4,000 characters. Conversely, when Qwen8B reads the same first 4,000 characters as Jev, it gains 1.6–2.5 points on all three collections (38.7, 53.2, and 60.5), and Jev S4 minus Qwen8B becomes −7.0 on Touche, −4.6 on News, and +5.3 on Robust04 (all significant after Holm). Jev's Robust04 lead over Qwen8B therefore holds at equal context in both directions, while Qwen8B's leads on Touche and News widen; the context budget does not explain the Jev–Qwen8B comparison on these collections. Giving bge-reranker-v2-m3 a 2,048-token window, which reads most documents in full, essentially closes the gap on News (47.8) but does not help on Robust04 (51.6 vs. 51.9).

RQ2: Calibration. Raw cross-encoder scores were never trained to be probabilities, so a raw comparison mainly asks whether a model can be thresholded *out of the box*. The fairer comparison is with *transfer* calibration, which fits Platt scaling on other collections and uses no labels of the target collection (Table 4). We lead with the Noul readout, which needs no strict/lenient choice, and with the strict readout applied everywhere; the per-collection readout policy, chosen after observing TREC-COVID (Section 4), is reported as a sensitivity analysis.

Out of the box, Jev and Laya yes/no probabilities are better calibrated than raw cross-encoder scores. Jev Noul has mean ECE 5.0 points below bge (paired query-bootstrap 95% CI [−6.3, −3.9]), lower on eight of nine collections, significantly lower on five after Holm, and significantly higher on none (TREC-COVID is slightly higher, +0.17). Laya Noul is 9.2 points lower ([−10.8, −7.5]).

Table 4: Calibration of P(relevant) on the nine collections with judged negatives (DL19–23, TREC-COVID, DBPedia, News, Robust04; unweighted mean over collections, ECE×100, 15 bins, judged pairs only). Raw: no recalibration. Transfer (no target labels): Platt scaling fit on the other eight collections pooled (All) or only on the same numeric-threshold group, balancing source collections (Group: DL→DL, BEIR→BEIR); the group need not share identical relevance semantics. All weights pairs equally. In-coll.: Platt with 10× repeated 5-fold query cross-fitting on the target collection (needs target labels; SD ≤0.6). C3/S4: Choice-3/Score-4, strict readout on every collection. †Sensitivity row: post-hoc per-collection readout policy (lenient on TREC-COVID, DBPedia, News; Section 4); excluded from bold. *Seven of the nine collections (no DBPedia, News). Bold: best among systems on all nine.

	ECE					
		Transfer				
System	Raw	All	Group	In-coll.	Brier	$\bar{p}$
MiniLM-L6	35.4	16.8	8.7	3.0	0.345	0.58
bge-v2-m3	20.0	14.9	6.9	2.6	0.215	0.39
Qwen3-Rer.-0.6B	36.1	17.9	9.6	2.4	0.357	0.62
Qwen3-Rer.-4B	26.9	19.0	9.2	2.4	0.265	0.47
Qwen3-Rer.-8B	21.6	17.5	9.6	2.5	0.221	0.41
Qwen3-235B P(yes)*	20.5	10.5	9.5	3.1	0.211	0.39
Laya C3	12.2	11.0	9.6	2.5	0.189	0.25
policy†	11.0	7.5	9.3	2.3	0.184	0.36
Laya Noul	**10.7**	**10.7**	9.5	2.2	0.185	0.35
Jeff C3	13.9	13.5	10.8	2.2	0.194	0.35
policy†	15.3	5.2	5.9	2.5	0.195	0.46
Jeff Noul	25.6	11.7	8.6	**2.2**	0.253	0.56
Clef C3*	12.3	14.4	10.8	4.2	0.167	0.21
policy*†	7.8	8.3	10.4	3.3	0.134	0.28
Clef Noul*	12.5	12.4	7.3	2.7	0.146	0.36
Clef S4*	11.8	13.0	7.1	2.8	0.138	0.35
policy*†	11.6	8.9	9.1	2.7	0.139	0.40
Jev C3	19.2	15.1	9.1	3.6	0.206	0.18
policy†	14.8	9.1	8.9	4.4	0.169	0.36
Jev Noul	15.0	14.2	**6.8**	3.0	**0.170**	0.38
Jev S4	17.9	14.8	7.5	5.5	0.192	0.41
policy†	25.4	8.2	7.9	5.0	0.240	0.55
Base rate of relevance (mean over the nine collections): 0.31						

Jeff Noul is the exception (25.6 versus bge 20.0). On DL, the trained rerankers over-predict relevance (ECE 51.1/36.5/27.6 for Qwen0.6B/4B/8B, 47.0 for MiniLM, and 23.1 for bge; Figure 1). The advantage depends on the readout for the graded formats. With the strict readout everywhere, Jev C3 is only 0.7 points below bge ([−2.5, 0.9]) and Jev S4 2.1 points below ([−3.4, −0.9]); under the per-collection policy, Jev C3 is 5.1 points below ([−7.1, −3.4]), while Jev S4 over-predicts relevance (mean prediction 0.55 against a base rate of 0.31) because the lenient readout $P(\ell \geq 1)$ counts "related but not answering" as relevant. Jev's DBPedia ECE is worse than bge's by 9.9 under the policy and 14.1 under strict, and Robust04 by 0.9 under both. These differences change by at most 0.4 points with 5–30 bins or equal-mass binning. A Brier decomposition attributes Jev Noul's advantage to both reliability (0.043 vs. 0.067) and resolution (0.066 vs. 0.045).

Transfer calibration closes the gap. Pooling all other collections (pair-weighted) yields ECE 14.9 for bge and 16.8 for MiniLM, versus




Figure 1: Raw reliability on judged candidate pairs for bge, Qwen3-Reranker-8B, and the Noul readouts of Laya and Jev. Pooled within DL19–23 (left) and the four BEIR collections with negatives (right); 10 equal-width bins for readability (the ECE values in Table 4 use 15 bins), hiding bins with fewer than 15 pairs. Noul needs no strict/lenient policy choice. Decision models are closer to the diagonal on DL; BEIR behavior is mixed.

Jev C3/S4/Noul 15.1/14.8/14.2 and Laya C3 11.0 under the strict readout (9.1/8.2 for Jev C3/S4 and 7.5 for Laya C3 under the per-collection policy); collection-balanced pooling changes little. Restricting sources to collections with the same numeric relevance threshold (DL→DL and BEIR→BEIR, collections weighted equally) yields bge 6.9, essentially equal to Jev Noul at 6.8, slightly above Jev S4 (7.5), and below Jev C3 (9.1) and Laya C3 (9.6). The BEIR group mixes partial-relevance definitions with strict Robust04, so it approximates rather than matches target relevance semantics. The practical advantage of decision-model probabilities is therefore that they need no labelled source collections, not that they are better calibrated than a cross-encoder with a cheap transfer fit.

Raw calibration depends on the prompt wording. Rewording the question while keeping its meaning moves raw ECE far more than ranking (Appendix A): for Jev Noul, three paraphrases give 7.5–25.9 on DL19 (original 12.4) and 14.3–34.5 on DL20 (20.7), while nDCG@10 stays within 2.7 points; Qwen3-Reranker-0.6B's default instruction is its least calibrated wording, and Qwen3-235B's original prompt its best calibrated. The 5-point raw-ECE gap between Jev Noul and bge is thus smaller than the spread that rewording alone produces, and its direction could change under another prompt. We report it as a property of the prompts we used, not of decision models in general.

Other models. On the seven collections where Clef was run, Clef C3 has raw ECE 12.3 and Brier 0.167 under the strict readout, versus Jev C3 16.6 and bge 20.2; the per-collection policy, which differs only on TREC-COVID for these collections, lowers Clef C3 to 7.8 and Jev C3 to 12.5. On the same seven collections, Clef Noul has ECE 12.5 versus 12.1 for its base. Jeff Noul has ECE 25.6 versus 26.5 for its base across nine collections, and Jeff C3 13.9 (15.3 under the policy). Qwen235B's raw yes/no ECE is 20.5, which transfer reduces to 10.5, versus Jev Noul 13.0 on the same collections.

Pool dependence. Calibration is measured on judged candidates, whose mean base rate is 0.31. Treating unjudged candidates as non-relevant preserves the raw advantage of Jev Noul and Laya Noul but reverses that of Jeff C3 under either readout (Appendix Table 9).

Efficiency. Per query–passage pair, the local cross-encoders and Qwen3-Reranker-0.6B take 0.3–14 ms (median) on a laptop GPU, Qwen3-Reranker-4B and 8B 102 and 148 ms (4-bit), Laya 58 ms, and Jeff 100 ms (with slow reference kernels); the API models take a median 176 ms (Jev), 401 ms (Clef), and 850 ms (Qwen3-235B) per call with 8–24 concurrent requests. Reranking 100 passages costs $3.4 per 1k queries with Jev on average ($2.4–5.7; long documents cost more) and $2.3 with the Qwen3-235B yes/no baseline; on the seven collections where both were run, Clef 27B costs about 4.8 times as much as Jev ($15.3 vs. $3.2). Local and API latencies come from different hardware, serving stacks, and concurrency levels, so they indicate orders of magnitude rather than a controlled speed comparison.

RQ3: Context selection. Table 5 reports answer F1 on the 597 family-disjoint MuSiQue final questions, our primary multi-hop result; Table 6 reports the original 1,000-question final splits of MuSiQue and NQ.

Better ranking improves multi-hop answers. On the family-disjoint MuSiQue split, passages selected by Jev beat those selected by bge-reranker-v2-m3 under every policy and with every generator, by +2.8 to +16.9 F1. Twenty-six of the 27 comparisons (nine policies, three generators) pass question-level Holm tests and have family-bootstrap 95% intervals excluding zero; the exception is top-5 with Qwen3-30B (+2.8, [−0.6, 6.1]). The gains are largest when few passages are selected: top-1 +12.1 to +16.9 and Adaptive-k +11.8 to +12.7, against +5.2 to +7.8 for top-3 and +2.8 to +3.6 for top-5. With every generator, Jev's top-3 (45.5, 42.3, 51.8) is at least as good as giving the generator all 20 candidates (40.8, 38.5, 51.1) with a fifth of the generator input tokens (491 vs. 2,676 for Qwen2.5-7B, excluding the cost of scoring the candidates). On NQ, despite Jev's higher recall of answer-bearing passages (R@3 58.4 vs. 52.5; Appendix Table 10), only one of 27 comparisons is significant.

Sensitivity: the original split. On the original MuSiQue split, whose final questions share decomposition sub-questions with the calibration or pilot splits (Section 4), Jev's gains are somewhat larger (+2.6 to +23.2 F1; top-1 +18.5 to +23.2) and all 27 comparisons pass Holm. Exact match shows the same pattern there (Appendix Table 11): Jev's EM exceeds bge's in all 27 policy–generator pairs, by 2.6 to 21.7 points, and 26 pass Holm; on NQ, none does. On the retrospective subset of 329 original final questions that share no sub-question ID with either design split (Appendix Table 12), the top-1 and Adaptive-k gains (+10.7 to +18.8) hold for every generator with family intervals excluding zero, while the top-3 gains shrink to +2.4 to +5.7. The family-disjoint split differs from the original one in hop mix as well as overlap (88% vs. 52% 2-hop), so the smaller effects do not measure overlap-induced inflation alone; they do show that the ranking advantage does not depend on shared sub-questions.

The gain is not only that of a stronger reranker. On the original split (Table 6), Qwen3-Reranker-8B, which matches Jev in RQ1, recovers part of Jev's MuSiQue advantage over bge (top-1: 30.6, 25.2, and 31.6 F1 versus bge's 22.0, 18.0, and 23.7), but Jev beats it under every

Table 5: RQ3 on the family-disjoint MuSiQue split: answer F1 on the 597 final questions (88% 2-hop) whose decomposition families share no sub-question with the calibration split or the original pilot. Policies and thresholds are those locked after the original pilot; Platt scaling and Jev's readout are refit on the family-disjoint calibration split. †: Jev significantly better than bge-reranker-v2-m3 under the same policy (question-level paired t-test, Holm-corrected, $p < 0.05$). Family-bootstrap intervals are given in the text.

Policy	MuSiQue Qwen2.5-7B	MuSiQue Llama-3.1	MuSiQue Qwen3-30B	Avg. n
No context	13.5	10.4	20.2	0.0
All 20 passages	40.8	38.5	51.1	20.0
Gold passages (oracle)	62.0	58.7	68.6	2.1
Jev 1.13				
top-1	39.7†	33.0†	42.1†	1.0
top-3	45.5†	42.3†	51.8†	3.0
top-5	44.2†	40.4†	51.7	5.0
adaptive-k	42.6†	39.1†	48.9†	2.3
$P > 0.3$	38.2†	35.6†	44.0†	1.7
top-2 + $P > 0.3$	44.0†	40.5†	49.8†	2.5
bge-reranker-v2-m3				
top-1	22.8	20.9	28.8	1.0
top-3	40.3	34.4	46.0	3.0
adaptive-k	30.0	27.3	36.2	3.0
top-2 + $P > 0.3$	36.3	31.8	43.2	2.8

Table 6: RQ3: answer F1 on the original 1,000 ID-disjoint final questions per dataset; MuSiQue component families overlap design splits. Avg. n: mean number of selected passages (independent of generator). †: Jev significantly better than bge-reranker-v2-m3 under the same policy in the original question-level paired t-test (Holm-corrected, $p < 0.05$); these tests do not account for family dependence. ‡: Jev significantly better than Qwen3-Reranker-8B under the same policy (same test and correction, added after final results). Displayed policies and ranker-effect comparisons were fixed after separate pilot questions. Thresholds use a readout selected with labelled calibration questions; the $P > 0.3$ rows are Platt-scaled.

Policy	MuSiQue Qwen2.5-7B	MuSiQue Llama-3.1	MuSiQue Qwen3-30B	NQ Qwen2.5-7B	NQ Llama-3.1	NQ Qwen3-30B	Avg. n MuSiQue	Avg. n NQ
No context	10.5	9.3	12.6	26.7	31.4	35.2	0.0	0.0
All 20 passages	38.8	37.0	46.3	52.5	49.4	51.5	20.0	20.0
Gold passages (oracle)	60.9	54.7	64.1	60.2	59.1	59.7	2.6	3.4
Jev 1.13								
top-1	45.2†‡	36.4†‡	43.4†‡	50.4‡	50.4†‡	51.4‡	1.0	1.0
top-3	44.6†‡	39.3†‡	47.1†‡	52.1	50.5	52.9	3.0	3.0
top-5	42.4†	40.7†‡	47.9†‡	51.9	50.9	53.0	5.0	5.0
adaptive-k	46.7†‡	40.2†‡	47.2†‡	52.3	50.1	52.3	2.9	6.2
$P > 0.3$	43.6†‡	36.1†‡	43.5†‡	51.2	51.5	52.3	2.4	2.9
top-2 + $P > 0.3$	44.2†‡	39.1†‡	45.2†‡	51.8	51.0	53.2	3.0	3.5
bge-reranker-v2-m3								
top-1	22.0	18.0	23.7	47.9	47.1	49.1	1.0	1.0
top-3	38.5	31.5	39.1	51.4	50.5	52.6	3.0	3.0
adaptive-k	30.5	26.1	32.6	50.6	50.5	51.8	3.1	7.1
top-2 + $P > 0.3$	35.7	30.4	37.9	51.3	51.2	52.6	2.9	3.9
Qwen3-Reranker-8B (4-bit)								
top-1	30.6	25.2	31.6	47.4	45.6	47.8	1.0	1.0
top-3	40.3	34.0	44.3	50.9	50.4	52.2	3.0	3.0
adaptive-k	37.6	32.8	38.6	51.2	50.3	51.7	3.7	10.3
top-2 + $P > 0.3$	38.7	35.2	41.1	51.3	50.4	51.3	3.1	4.4
Qwen3-Reranker-0.6B								
top-1	23.8	19.2	23.5	42.2	42.2	44.2	1.0	1.0
top-3	34.6	29.7	36.2	49.1	47.6	49.9	3.0	3.0
adaptive-k	30.9	27.6	33.1	50.9	49.4	50.6	3.2	10.1
top-2 + $P > 0.3$	31.9	29.2	34.8	49.9	47.8	50.7	2.8	3.8

policy with every generator (+1.6 to +14.5 F1; top-1 +11.3 to +14.5, Adaptive-k +7.4 to +9.1), and 26 of 27 comparisons pass the same Holm correction (the exception is top-5 with Qwen2.5-7B, +1.6, $p = 0.18$). On NQ, Jev beats Qwen8B only at top-1 (+3.1 to +4.8 with every generator); the other 24 differences lie between −0.1 and +2.6 and are not significant after Holm. Qwen3-Reranker-0.6B is below Jev in all 27 MuSiQue and 18 of 27 NQ comparisons. These comparisons were added after the final results and have not yet been repeated on the family-disjoint split; they are marked ‡ in Table 6.

Jev ranks the answer-bearing hop first. On the original split, the ranking advantage coincides with a difference in *which* passage each

ranker puts first. bge-reranker-v2-m3's top passage is a supporting paragraph slightly more often (88.0% vs. 82.2%, McNemar $p < 10^{-4}$), but usually the first hop—the one that shares the question's entities (61.9%)—whereas Jev's top passage is the last, answer-bearing hop in 51.2% of questions against 15.2% ($p < 10^{-80}$; Appendix Table 10), and 56–64% across Jev's three readouts. This preference is not reproduced by rewording a label-probability reranker's instruction: asking Qwen0.6B whether the passage is relevant, answers, or contains the answer yields only 16.5–18.5% last-hop@1 and 51–56% first-hop@1. Qwen3-Reranker-8B lies in between: its top passage is the last hop in 30.2% of questions and the first hop in 44.5%, and contains the answer in 36.6% (Jev 56.5%, bge 22.3%). Its top-3 recall of supporting paragraphs equals Jev's (68.6% vs. 68.7%), yet Jev's top-3 contexts score 2.8–5.3 F1 higher, consistent with which supporting paragraph is selected mattering more than how many. Replacing gold-answer strings with `[MASKED]` reduces Jev S4 last-hop@1 to 43.8% (Noul: 50.3%) from 51.2% (56.4%); masked bge scores 13.4%. Because the marker itself reveals answer location (it appears in 999 of 1,000 last-hop paragraphs but only 1,621 of 19,988 candidates), this perturbation cannot separate question resolution from that cue, prior entity knowledge, or memorized chains.

Thresholds on probabilities do not beat fixed k. A pure threshold at 0.3 on Platt-scaled probabilities leaves the generator with no passage for 10.3% of MuSiQue and 21.6% of NQ questions, which then fall back to closed-book answering (the prompt does not allow abstention). Raw $P > 0.3$ is within 1.3 F1 of the Platt threshold and of top-3 on NQ for every generator; on MuSiQue it selects nothing for 25% of questions and is 3.4–5.9 F1 below top-3 (Appendix A). The top-2+threshold rule is within ±2 F1 (TOST) of top-2, top-3, top-5, and Adaptive-k on NQ for every generator. On MuSiQue it is equivalent to top-2 (and, for Llama, to top-3), but pooled over generators it is 1.9 F1 below Adaptive-k (95% CI $[-3.4, -0.4]$; Holm-adjusted $p = 0.065$), and individual comparisons against Adaptive-k, top-3, and top-5 trend lower by 1.9–2.7 F1 (unadjusted $p = 0.01$–0.05, none significant after Holm). On the family-disjoint split it is 1.5–2.0 F1 below top-3 and 0.9–1.4 F1 above Adaptive-k, with no comparison passing Holm and every family interval crossing zero; it is equivalent to top-2 for Llama and Qwen3-30B and pooled over generators (TOST $p < 0.05$). A pure Platt threshold at 0.3 leaves 16.2% of these questions without context. Because it selects more than two passages for 39% of MuSiQue and 45% of NQ questions (3.0 and 3.5 on average), it also saves no tokens over top-3. Jev's practical advantage for RAG is therefore its ranking, not thresholding on its probabilities.

6 Threats to Validity

Pre-specified versus post-hoc analyses. Several analyses were added or changed after results were observed, and we flag them here in one place. (i) The per-collection strict/lenient readout policy was introduced after observing a Choice-3 ECE of 43.9 on TREC-COVID; we therefore lead with the policy-free Noul readout and the strict-everywhere readout, and give both readouts for every collection (Appendix Table 8). (ii) The ±2 nDCG and ±2 F1 equivalence margins, the TOST analyses, and the modified Knapp–Hartung sensitivity analysis are post-hoc and exploratory. (iii) In RQ3, threshold-rule comparisons against top-3 and Adaptive-k were fixed after the pilot; comparisons against top-2 and top-5 and the raw (non-Platt) thresholds were added after final results. (iv) The 329-question MuSiQue subset is a retrospective sensitivity analysis on existing outputs, not a new confirmatory split. (v) Added during revision, after the original results were known: the family-disjoint MuSiQue split, the downstream comparison with Qwen3-Reranker-8B/0.6B, the strict readout as the primary calibration row for every Choice-3 and Score-4 system, the extension of the Clef base control from three to seven collections, the 4,000-character Qwen3-Reranker-8B control, the prompt paraphrases, the SPLADE++ first stage, and the exact-match tables. The policies, thresholds, and paraphrases were fixed before the corresponding runs, but the decision to run each analysis was not.

Statistical dependence. The three question formats of each decision model are answered in one call per pair and are not independent samples. Holm correction is applied within each system–baseline pair across collections, not across the roughly 40 systems and formats. The original MuSiQue split was by ID, and 671 of 1,000 final questions share at least one decomposition sub-question with the calibration or pilot splits. Our primary family-disjoint split removes this overlap, but it was built after the original results were seen, and excluding every family that reaches the pilot leaves a split that is 88% 2-hop, so its results speak mainly to 2-hop questions.

Configurations rather than isolated effects. Same-base comparisons differ in prompts and context budgets (4,000 characters for Jev, Clef, and Jeff; 448 tokens for the label-probability controls), so they compare configurations rather than isolate decision-model training. Qwen3-Reranker-4B/8B use 4-bit weights. Clef and Qwen3-235B cover subsets of collections, and the Clef base control covers Clef's seven. The main results use a single prompt per format; rewording the question changes raw DL calibration error by up to 17 points for Qwen3-Reranker-0.6B, 13 for Qwen3-235B, and 20 for Jev Noul, while nDCG@10 moves by at most 2.7 (Appendix A). Latencies come from different hardware and serving stacks.

Benchmarks and contamination. Our main experiments use BM25 candidates; on SPLADE++ candidates Jev trails the cross-encoders on DL19 but not on DL20 (Appendix A). Calibration is measured on judged candidates, and numeric-threshold transfer groups need not share identical relevance semantics. We retain the DL23 synthetic queries and DL22 propagated judgments. Jev is a closed model whose size, training data, and cutoff are unknown; Robust04, MuSiQue, NovelEval, and FutureQueryEval all predate its release, so contamination cannot be excluded, and the answer-masking perturbation cannot separate reasoning from memorization. The RAG comparison covers bge-reranker-v2-m3 and Qwen3-Reranker-8B/0.6B but not the API label-probability baselines, the Qwen comparisons were added after the final results, thresholds use target calibration labels, and the generator cannot abstain.

7 Conclusion

Large typed decision models are competitive pointwise passage rerankers: Jev is on par with Qwen3-Reranker-8B and ahead of bge-reranker-v2-m3 on average, with large variation across collections and on BM25 candidates (on SPLADE++ candidates for DL19 it falls behind), and its gains over bge persist at equal passage budgets on

News and Robust04, as does its Robust04 lead over Qwen3-Reranker-8B when both read the same 4,000 characters (Qwen3-Reranker-8B stays ahead on Touche and News). Same-base controls suggest that Clef's effectiveness comes largely from its underlying LLM: it does not differ significantly from its base on six of seven collections and is ahead only on Robust04, where the base reads less text, while the small Jeff model improves on its base; Jev's base model is unknown, so we cannot attribute its effectiveness either way. Out of the box, the yes/no probabilities of Jev and Laya are better calibrated than raw cross-encoder scores (Jeff's are not, and Jev's graded formats depend on the readout), but a cross-encoder calibrated on other collections with the same relevance threshold reaches similar error; their practical advantage is that no labelled source data are needed, and rewording the prompt moves raw calibration error by more than the gap to bge. Small open decision models remain weak deep rerankers under standard evaluation. For RAG, Jev improves multi-hop answer quality over bge with all three generators, and on the original split also over Qwen3-Reranker-8B despite equal ranking effectiveness, and it more often ranks the answer-bearing final hop first; on a family-disjoint MuSiQue split the gains remain (+2.8 to +16.9 F1; 26 of 27 comparisons significant), largest when few passages are selected. Thresholding its probabilities, however, does not improve over fixed top-k selection. Calibration alone, in short, does not make context selection a simple threshold. Future work should build family-disjoint multi-hop splits with more 3- and 4-hop questions, repeat the Qwen3-Reranker-8B comparison on them, extend the downstream comparison to the API label-probability baselines, and match context budgets across models on all collections.

Declarations

Data and code availability. All collections are publicly distributed and are downloaded automatically by the released code; the underlying Robust04, TREC News, and Signal-1M corpora remain subject to their providers' data agreements. Code, prompts, split IDs, input hashes, and aggregate results are available at https://github.com/parv-bhargava/ChoiceRank and archived at [TODO: Zenodo DOI, minted when the first public release is created].

Competing interests. The author declares no competing interests and has no relationship with TypeSafe (Jev), Cloudflare (Clef), firelex (Jeff), ConvAI Innovations (Laya), or OpenRouter.

Funding. This work received no external funding. All API costs were paid personally by the author; no company, including the providers of the evaluated models and OpenRouter, provided credits, payment, or other support.

References

[1] Abdelrahman Abdallah, Bhawna Piryani, Jamshid Mozafari, Mohammed Ali, and Adam Jatowt. 2025. How Good are LLM-based Rerankers? An Empirical Analysis of State-of-the-Art Reranking Models. In *Findings of EMNLP*. arXiv:2508.16757; FutureQueryEval: https://huggingface.co/datasets/abdoelsayed/FutureQueryEval.

[2] Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. 2024. Self-RAG: Learning to Retrieve, Generate, and Critique through Self-Reflection. In *Proceedings of ICLR*.

[3] BAAI. 2024. BAAI/bge-reranker-v2-m3. https://huggingface.co/BAAI/bge-reranker-v2-m3. Hugging Face model card; initialized from BGE-M3.

[4] Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, et al. 2016. MS MARCO: A Human Generated MAchine Reading COmprehension Dataset. *arXiv preprint arXiv:1611.09268* (2016).

[5] carlaiau. 2026. Experiment: ten-level JEV Score reranking on MS MARCO passages. GitHub issue, https://github.com/carlaiau/jev-reranking/issues/88. 2026-09-25.

[6] Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, et al. 2024. M3-Embedding: Multi-Linguality, Multi-Functionality, Multi-Granularity Text Embeddings Through Self-Knowledge Distillation. *arXiv preprint arXiv:2402.03216* (2024).

[7] Michelle Chen, Alex Reneau, and Kevin Flansburg. 2026. Introducing Clef: our open-source decision models, and new RL fine-tuning platform. Cloudflare Blog, https://blog.cloudflare.com/clef-decision-models/. 2026-10-01; served on OpenRouter as https://openrouter.ai/cloudflare/clef.

[8] Nadezhda Chirkova, Thibault Formal, Vassilina Nikoulina, and Stéphane Clinchant. 2025. Provence: Efficient and Robust Context Pruning for Retrieval-Augmented Generation. In *Proceedings of ICLR*. arXiv:2501.16214.

[9] Charles L. A. Clarke and Laura Dietz. 2024. LLM-based Relevance Assessment Still Can't Replace Human Relevance Assessment. *arXiv preprint arXiv:2412.17156* (2024).

[10] ConvAI Innovations. 2026. Laya: Multilingual Non-autoregressive System-1 Decision Model. https://huggingface.co/convaiinnovations/laya. laya 0.3.26.

[11] Nick Craswell, Bhaskar Mitra, Emine Yilmaz, and Daniel Campos. 2021. Overview of the TREC 2020 Deep Learning Track. *arXiv preprint arXiv:2102.07662* (2021).

[12] Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Daniel Campos, et al. 2020. Overview of the TREC 2019 Deep Learning Track. *arXiv preprint arXiv:2003.07820* (2020).

[13] Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Daniel Campos, and Jimmy Lin. 2021. Overview of the TREC 2021 Deep Learning Track. In *Proceedings of TREC*.

[14] Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Daniel Campos, Jimmy Lin, Ellen M. Voorhees, and Ian Soboroff. 2022. Overview of the TREC 2022 Deep Learning Track. In *Proceedings of TREC*.

[15] Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Hossein A. Rahmani, Daniel Campos, Jimmy Lin, Ellen M. Voorhees, and Ian Soboroff. 2023. Overview of the TREC 2023 Deep Learning Track. In *Proceedings of TREC*.

[16] Florin Cuconasu, Giovanni Trappolini, Federico Siciliano, Simone Filice, et al. 2024. The Power of Noise: Redefining Retrieval for RAG Systems. In *Proceedings of SIGIR*. arXiv:2401.14887.

[17] Guglielmo Faggioli, Laura Dietz, Charles Clarke, Gianluca Demartini, et al. 2023. Perspectives on Large Language Models for Relevance Judgment. *arXiv preprint arXiv:2304.09161* (2023).

[18] firelex. 2026. Jeff: Jev-compatible open decision models. https://github.com/firelex/jeff. Jeff-Qwen3.5-0.8B v1.2, commit d0173b4.

[19] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, et al. 2024. The Llama 3 Herd of Models. *arXiv preprint arXiv:2407.21783* (2024).

[20] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. 2017. On Calibration of Modern Neural Networks. In *Proceedings of ICML*.

[21] Z. Huang. 2026. Jev vs. Qwen: Choosing a Reranker for Quality, Cost, and Speed. Denser AI blog, https://denser.ai/research/jev-vs-qwen-reranker/. 2026-09-21.

[22] Soyeong Jeong, Jinheon Baek, Sukmin Cho, Sung Ju Hwang, and Jong C. Park. 2024. Adaptive-RAG: Learning to Adapt Retrieval-Augmented Large Language Models through Question Complexity. In *Proceedings of NAACL*.

[23] Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Patrick Lewis, et al. 2020. Dense Passage Retrieval for Open-Domain Question Answering. In *Proceedings of EMNLP*.

[24] Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, et al. 2019. Natural Questions: A Benchmark for Question Answering Research. *Transactions of the Association for Computational Linguistics* (2019).

[25] Jimmy Lin, Xueguang Ma, Sheng-Chieh Lin, Jheng-Hong Yang, et al. 2021. Pyserini: A Python Toolkit for Reproducible Information Retrieval Research with Sparse and Dense Representations. In *Proceedings of SIGIR*. arXiv:2102.10073.

[26] Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the Middle: How Language Models Use Long Contexts. *Transactions of the Association for Computational Linguistics* (2024).

[27] Hanjia Lyu and Yinglong Xia. 2026. Decision-Oriented Recommendation Reranking: An Empirical Study of Jev. *arXiv preprint arXiv:2609.40241* (2026).

[28] Sean MacAvaney, Craig Macdonald, and Iadh Ounis. 2022. Streamlining Evaluation with ir-measures. In *Proceedings of ECIR*.

[29] Made by Agents. 2026. JevBench: System One Model Composite. https://www.madebyagents.com/benchmarks/jevbench. Data as of 2026-09-24.

[30] Siyuan Meng, Junming Liu, Yirong Chen, Song Mao, Pinlong Cai, Guohang Yan, Botian Shi, and Ding Wang. 2025. From Ranking to Selection: A Simple but Efficient Dynamic Passage Selector for Retrieval Augmented Generation. *arXiv preprint arXiv:2508.09497* (2025).

[31] Gowthamkumar Nandakishore. 2026. Laya as a Typed Probabilistic Assessor: An Independent Reproduction and a Preregistered Study of Calibration and Selective Escalation. *arXiv preprint arXiv:2609.33843* (2026).

[32] Jingwei Ni, Tobias Schimanski, Meihong Lin, Mrinmaya Sachan, Elliott Ash, and Markus Leippold. 2025. DIRAS: Efficient LLM Annotation of Document Relevance in Retrieval Augmented Generation. In *Proceedings of NAACL*. arXiv:2406.14162.
[33] Shiyu Ni, Keping Bi, Jiafeng Guo, Jingtong Wu, Zengxin Han, and Xueqi Cheng. 2026. Can LLM Rerankers Predict Their Own Ranking Performance? *arXiv preprint arXiv:2606.03535* (2026).
[34] Rodrigo Nogueira and Kyunghyun Cho. 2019. Passage Re-ranking with BERT. *arXiv preprint arXiv:1901.04085* (2019).
[35] Rodrigo Nogueira, Zhiying Jiang, Ronak Pradeep, and Jimmy Lin. 2020. Document Ranking with a Pretrained Sequence-to-Sequence Model. In *Findings of EMNLP*. arXiv:2003.06713.
[36] Gustavo Penha and Claudia Hauff. 2021. On the Calibration and Uncertainty of Neural Learning to Rank Models for Conversational Search. In *Proceedings of EACL*. arXiv:2101.04356.
[37] John Platt. 1999. Probabilistic Outputs for Support Vector Machines and Comparisons to Regularized Likelihood Methods. In *Advances in Large Margin Classifiers*, Alexander J. Smola, Peter Bartlett, Bernhard Schölkopf, and Dale Schuurmans (Eds.). MIT Press.
[38] Ronak Pradeep, Sahel Sharifymoghaddam, and Jimmy Lin. 2023. RankZephyr: Effective and Robust Zero-Shot Listwise Reranking is a Breeze! *arXiv preprint arXiv:2312.02724* (2023).
[39] Qwen Team. 2024. Qwen2.5 Technical Report. *arXiv preprint arXiv:2412.15115* (2024).
[40] Qwen Team. 2025. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388* (2025).
[41] Hossein A. Rahmani, Emine Yilmaz, Nick Craswell, Bhaskar Mitra, et al. 2024. LLMJudge: LLMs for Relevance Judgments. *arXiv preprint arXiv:2408.08896* (2024).
[42] Revanth Gangi Reddy, JaeHyeok Doo, Yifei Xu, Md Arafat Sultan, et al. 2024. FIRST: Faster Improved Listwise Reranking with Single Token Decoding. In *Proceedings of EMNLP*. arXiv:2406.15657.
[43] Christian Röver, Guido Knapp, and Tim Friede. 2015. Hartung–Knapp–Sidik–Jonkman approach and its modification for random-effects meta-analysis with few studies. *BMC Medical Research Methodology* 15 (2015), 99. doi:10.1186/s12874-015-0091-1
[44] Sharath M. Shankaranarayana, Davor Runje, and Jan Jannink. 2026. Beyond Answer Confidence: A Controlled Audit of Self-Knowledge in a Black-Box Decision Model. *arXiv preprint arXiv:2610.01006* (2026).
[45] Sahel Sharifymoghaddam, Ronak Pradeep, Andre Slavescu, Ryan Nguyen, Andrew Xu, Zijian Chen, et al. 2025. RankLLM: A Python Package for Reranking with LLMs. In *Proceedings of SIGIR*. arXiv:2505.19284.
[46] Rishabh Sharma and Rishika Lall. 2026. When Does Selection Replace Extraction? A Pre-Registered Test of Agent Memory with a Typed Decision Model. *arXiv preprint arXiv:2609.34227* (2026).
[47] Weiwei Sun, Lingyong Yan, Xinyu Ma, Shuaiqiang Wang, Pengjie Ren, Zhumin Chen, Dawei Yin, and Zhaochun Ren. 2023. Is ChatGPT Good at Search? Investigating Large Language Models as Re-Ranking Agents. In *Proceedings of EMNLP*. arXiv:2304.09542.
[48] Chihiro Taguchi, Seiji Maekawa, and Nikita Bhutani. 2025. Efficient Context Selection for Long-Context QA: No Tuning, No Iteration, Just Adaptive-k. In *Proceedings of EMNLP*. arXiv:2506.08479.
[49] Lijuan Tang and Yuemeng Zheng. 2026. Typed Decision Models: An Early Evidence Audit and Evaluation Checklist. *arXiv preprint arXiv:2609.32160* (2026).
[50] Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. BEIR: A Heterogeneous Benchmark for Zero-shot Evaluation of Information Retrieval Models. In *NeurIPS Datasets and Benchmarks Track*.
[51] Paul Thomas, Seth Spielman, Nick Craswell, and Bhaskar Mitra. 2024. Large Language Models Can Accurately Predict Searcher Preferences. In *Proceedings of SIGIR*. arXiv:2309.10621.
[52] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022. MuSiQue: Multihop Questions via Single-hop Question Composition. *Transactions of the Association for Computational Linguistics* (2022).
[53] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2023. Interleaving Retrieval with Chain-of-Thought Reasoning for Knowledge-Intensive Multi-Step Questions. In *Proceedings of ACL*.
[54] TypeSafe. 2026. Jev 1.13 on OpenRouter (Decisions API). https://openrouter.ai/typesafe/jev-1.13. Snapshot typesafe/jev-1.13-20260917; accessed 2026-10-03.
[55] Shivani Upadhyay, Ronak Pradeep, Nandan Thakur, Nick Craswell, et al. 2024. UMBRELA: UMbrela is the (Open-Source Reproduction of the) Bing RELevance Assessor. *arXiv preprint arXiv:2406.06519* (2024).
[56] Zhiruo Wang, Jun Araki, Zhengbao Jiang, Md Rizwan Parvez, and Graham Neubig. 2023. Learning to Filter Context for Retrieval-Augmented Generation. *arXiv preprint arXiv:2311.08377* (2023).
[57] Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, et al. 2024. Smarter, Better, Faster, Longer: A Modern Bidirectional Encoder for Fast, Memory Efficient, and Long Context Finetuning and Inference. *arXiv preprint arXiv:2412.13663* (2024).
[58] Fangyuan Xu, Weijia Shi, and Eunsol Choi. 2024. RECOMP: Improving Retrieval-Augmented LMs with Context Compression and Selective Augmentation. In *Proceedings of ICLR*.
[59] Le Yan, Zhen Qin, Xuanhui Wang, Michael Bendersky, and Marc Najork. 2022. Scale Calibration of Deep Ranking Models. In *Proceedings of KDD*.
[60] Shi-Qi Yan, Jia-Chen Gu, Yun Zhu, and Zhen-Hua Ling. 2024. Corrective Retrieval Augmented Generation. *arXiv preprint arXiv:2401.15884* (2024).
[61] Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, et al. 2025. Qwen3 Embedding: Advancing Text Embedding and Reranking Through Foundation Models. *arXiv preprint arXiv:2506.05176* (2025).
[62] Honglei Zhuang, Zhen Qin, Kai Hui, Junru Wu, Le Yan, Xuanhui Wang, and Michael Bendersky. 2024. Beyond Yes and No: Improving Zero-Shot LLM Rankers via Scoring Fine-Grained Relevance Labels. In *Proceedings of NAACL (Short Papers)*. arXiv:2310.14122.
[63] Shengyao Zhuang, Honglei Zhuang, Bevan Koopman, and Guido Zuccon. 2024. A Setwise Approach for Effective and Highly Efficient Zero-shot Ranking with Large Language Models. In *Proceedings of SIGIR*. arXiv:2310.09497.

A Additional Results

Table 7 reports effectiveness as a function of reranking depth; Table 8 reports both probability readouts for every collection with judged negatives; Table 9 reports pool coverage and the pool-bias check for calibration; Table 10 reports generator-free selection quality for RQ3; Table 11 reports exact match for the RAG policies of Table 6. Code, prompts, and aggregate results are available in the reproduction repository (Declarations). All inputs are public and are downloaded by the code; the RAG splits are regenerated from a fixed seed, and the scripts reproduce every table and figure from the model outputs.

RAG prompt. System message: "Answer the question. Give only the short answer (a few words), with no explanation." User message: "Answer the question based on the given passages. Give only the short answer (a few words), with no explanation." followed by a blank line, the selected passages in rank order (each as "Passage i (Title: …): …", separated by blank lines), a blank line, and "Question: {question}\nAnswer:". When a policy selects no passage, the user message is only "Question: {question}\nAnswer:".

Yes/no prompt. System: "You are a search relevance assessor." User: "Query: {query}\nPassage: {passage}\n\nDoes the passage answer the query? Answer with Yes or No only."

RQ3 details. Generators were called through OpenRouter on 2026-10-04 by model name (qwen/qwen-2.5-7b-instruct, meta-llama/llama-3.1-8b-instruct, qwen/qwen3-30b-a3b-instruct-2507); OpenRouter does not expose weight snapshots. Qwen2.5-7B was served by one provider (Phala); Llama-3.1-8B by DeepInfra (61–64% of calls), Novita (25–28%), Groq (10%), and Cloudflare (1%); Qwen3-30B-A3B by six providers (StreamLake 31–32%, SiliconFlow 24%, Nebius 21–22%, Alibaba 11%, PrimeIntellect 11%, DekaLLM 1–2%). Jev's probability readout was chosen by Brier score on the calibration split (MuSiQue: Choice-3 strict 0.110, lenient 0.099, Noul 0.094 → Noul; NQ: 0.122, 0.286, 0.143 → Choice-3 strict; family-disjoint MuSiQue calibration split: 0.081, 0.080, 0.068 → Noul). Platt parameters (a, b) for $\sigma(a\,\mathrm{logit}(p) + b)$: Jev $(0.93, 0.60)$ and bge-reranker-v2-m3 $(0.42, 0.00)$ on MuSiQue; Jev $(1.01, 0.35)$ and bge-reranker-v2-m3 $(0.49, -0.01)$ on the family-disjoint MuSiQue split; Jev $(0.17, -0.77)$ and bge-reranker-v2-m3 $(0.34, -1.75)$ on NQ. Family-disjoint generations were run on 2026-10-17 with the same generator model names and prompt. Jev was called once per pair with default decoding. Its outputs are not fully deterministic:

Table 7: nDCG@10 when only the BM25 top-k is reranked (simulated exactly from the pointwise scores; passages below rank k keep their BM25 order). Averages over TREC DL19–23 and BEIR-8. The cost of a pointwise reranker grows linearly with k. BM25 alone: DL 39.3, BEIR 43.6.

	DL19–23					BEIR-8				
System	k=10	k=20	k=30	k=50	k=100	10	20	30	50	100
MiniLM	43.3	50.8	53.8	56.7	59.6	44.9	46.5	46.6	46.8	47.1
bge-v2-m3	43.7	51.6	54.6	57.8	60.6	45.9	48.4	48.7	49.3	49.3
Qwen3-Rer.-0.6B	42.9	49.5	52.0	54.1	56.7	45.7	48.4	49.2	50.0	50.5
Laya C3	41.8	46.2	46.9	48.0	47.3	43.7	43.1	41.5	39.6	37.4
Jeff Noul	41.9	46.1	46.3	46.7	45.1	43.1	42.3	40.5	38.8	35.9
Jev S4	44.0	51.9	55.1	58.0	61.1	46.8	50.4	51.4	52.5	53.0
BEIR-8: condensed nDCG′ @10 (left), Judged@10 in % (right)										
MiniLM	60.8	62.3	62.9	63.6	64.2	57	58	57	56	56
bge-v2-m3	61.2	63.4	64.1	65.1	65.7	57	57	57	56	55
Qwen3-Rer.-0.6B	61.4	63.8	64.9	66.0	66.9	57	57	57	57	56
Laya C3	60.4	61.5	61.7	61.9	61.9	57	55	53	51	48
Jeff Noul	60.2	61.1	61.0	61.3	60.8	57	55	53	51	48
Jev S4	61.6	64.8	66.2	67.7	69.1	57	58	57	56	56

Table 8: ECE×100 of Choice-3/Score-4 probabilities under the strict (s) and lenient (l) readouts. The readout used in the main text is underlined. Noul has a single readout.

System		DL19	DL20	DL21	DL22	DL23	Covid	DBP	News	Rob04
Laya C3	s	14.1	6.4	7.3	8.3	12.1	25.4	16.1	14.3	5.6
	l	24.5	34.0	36.6	42.9	41.9	6.9	16.7	22.0	30.4
Jeff C3	s	7.1	15.9	12.3	17.6	17.3	25.9	3.3	14.9	11.0
	l	36.3	45.3	42.8	48.6	47.7	11.6	21.0	23.9	48.2
Jev C3	s	12.9	9.3	13.1	8.2	14.3	43.9	26.7	30.6	14.2
	l	37.7	47.4	47.6	48.2	52.4	15.8	22.6	23.2	18.6
Jev S4	s	15.8	23.5	24.8	20.1	26.7	13.8	9.7	19.5	7.2
	l	52.8	68.0	59.8	70.3	69.3	27.4	42.6	40.6	32.3

Table 9: Pool coverage and pool-bias checks. Judged@10 (%) and condensed (judged-only) nDCG′@10, averaged over the collections each system was run on; ECE×100 over the nine dense collections on judged pairs only vs. treating unjudged candidates as non-relevant; mean P(rel) on judged relevant / non-relevant pairs. *Run on a subset of collections (Clef: 7; Qwen3-235B: 8), so its averages are not directly comparable.

	Judged@10		nDCG′	ECE		mean P	
System	DL	BEIR	All	judged	unj.=0	rel.	non-rel.
BM25	99.9	56.7	51.8	–	–	–	–
MiniLM	96.9	55.7	62.6	35.4	30.6	0.77	0.49
bge-v2-m3	95.9	55.5	64.0	20.0	15.2	0.64	0.28
Qwen3-Rer.-0.6B	93.4	56.4	63.5	36.1	31.5	0.83	0.51
Qwen3-235B P(yes)*	87.1	74.9	62.9	20.5	15.8	0.74	0.24
Laya C3	81.1	48.1	58.6	11.0	14.2	0.50	0.30
Jeff C3	76.4	48.1	57.3	15.3	23.5	0.57	0.41
Clef C3*	90.5	97.1	66.9	7.8	6.8	0.50	0.18
Clef S4*	91.5	97.4	67.5	11.6	14.0	0.66	0.30
Jev C3	89.7	55.4	66.3	14.8	13.3	0.62	0.23
Jev Noul	89.8	55.3	66.7	15.0	12.7	0.67	0.26
Jev S4	90.0	55.7	66.9	25.4	25.1	0.86	0.43

Table 10: Generator-free selection quality on the RQ3 final sets: recall of gold passages within the top-k (all-gold: every gold passage selected), and, on MuSiQue, whether the top-1 passage is the first-hop or the last (answer-bearing) supporting paragraph and whether it contains the answer string.

Data	Ranker	R@1	R@3	R@5	all-gold@5
MuSiQue	Jev	33.3	68.7	83.2	61.4
MuSiQue	bge-v2-m3	35.4	66.0	76.9	49.5
MuSiQue	Qwen3-Reranker-8B	34.9	68.6	78.7	51.5
MuSiQue	Qwen3-Reranker-0.6B	33.7	62.1	71.5	38.8
NQ	Jev	27.3	58.4	72.2	47.4
NQ	bge-v2-m3	26.1	52.5	65.8	39.1
NQ	Qwen3-Reranker-8B	25.6	55.1	69.0	43.0
NQ	Qwen3-Reranker-0.6B	21.4	47.1	61.6	34.8
MuSiQue top-1:	first hop / last hop / contains answer (%)				
	Jev	22.6 / 51.2 / 56.5			
	bge-v2-m3	61.9 / 15.2 / 22.3			
	Qwen3-Reranker-8B	44.5 / 30.2 / 36.6			
	Qwen3-Reranker-0.6B	56.0 / 16.5 / 23.0			

Table 11: RQ3: exact match (EM) on the same questions, policies, and generations as Table 6. Avg. n: mean number of selected passages. †: Jev significantly better than bge-reranker-v2-m3 under the same policy on EM (question-level paired t-test, Holm-corrected over the nine policies, $p < 0.05$); these tests do not account for MuSiQue family dependence. EM is a secondary metric.

	MuSiQue			NQ			Avg. n	
Policy	Qwen2.5-7B	Llama-3.1	Qwen3-30B	Qwen2.5-7B	Llama-3.1	Qwen3-30B	MuSiQue	NQ
No context	2.9	3.5	4.3	16.1	19.9	23.0	0.0	0.0
All 20 passages	27.8	27.0	34.9	40.6	38.4	37.4	20.0	20.0
Gold passages (oracle)	47.7	41.6	51.6	47.7	47.5	45.0	2.6	3.4
Jev 1.13								
top-1	34.4†	26.1†	33.1†	38.5	38.5	38.8	1.0	1.0
top-3	32.6†	29.0†	36.7†	39.7	38.2	39.0	3.0	3.0
top-5	31.2	30.8†	36.5†	39.0	39.2	39.2	5.0	5.0
adaptive-k	34.8†	29.3†	36.5†	39.8	38.6	38.1	2.9	6.2
$P > 0.3$	32.6†	26.1†	32.5†	38.8	39.9	38.3	2.4	2.9
top-2 + $P > 0.3$	32.7†	28.6†	34.7†	39.6	39.5	39.4	3.0	3.5
bge-reranker-v2-m3								
top-1	12.7	10.2	13.7	36.7	36.8	37.1	1.0	1.0
top-3	27.2	22.3	29.1	38.5	39.0	38.1	3.0	3.0
adaptive-k	20.2	16.4	22.4	38.5	39.3	38.5	3.1	7.1
top-2 + $P > 0.3$	24.9	21.1	27.6	38.3	39.9	38.5	2.9	3.9
Qwen3-Reranker-8B (4-bit)								
top-1	20.3	15.9	21.5	35.0	33.9	35.2	1.0	1.0
top-3	29.9	24.4	33.5	37.3	39.3	37.8	3.0	3.0
adaptive-k	26.6	23.0	27.9	39.0	38.5	37.2	3.7	10.3
top-2 + $P > 0.3$	27.9	25.3	31.0	37.7	39.0	36.9	3.1	4.4
Qwen3-Reranker-0.6B								
top-1	13.4	10.0	13.3	30.6	31.6	32.2	1.0	1.0
top-3	24.6	20.4	26.0	36.5	36.2	35.2	3.0	3.0
adaptive-k	20.5	17.9	22.6	39.1	38.4	36.5	3.2	10.1
top-2 + $P > 0.3$	22.2	19.9	24.8	37.7	36.0	36.4	2.8	3.8

Table 12: Retrospective MuSiQue sensitivity on 329 questions with no sub-question ID in calibration or pilot. Answer F1 under three ranker-effect policies; Δ is Jev minus bge. CIs resample 212 source-graph families (20,000 paired replicates, seed 13), retaining question weights; intervals are unadjusted. †: passes the original nine-policy question-level Holm correction (top-1 and Adaptive-k for every generator; no top-3 comparison).

Generator	Policy	Jev	bge	Δ	Family 95% CI
Qwen2.5-7B	top-1	41.8	23.1	+18.8†	[14.0, 23.8]
	Adaptive-k	42.1	31.3	+10.7†	[5.9, 15.7]
	top-3	43.6	41.3	+2.4	[−2.6, 7.3]
Llama-3.1-8B	top-1	35.0	20.6	+14.4†	[9.6, 19.2]
	Adaptive-k	38.4	27.1	+11.3†	[7.1, 15.7]
	top-3	41.1	35.7	+5.5	[1.0, 10.0]
Qwen3-30B-A3B	top-1	43.9	26.0	+17.9†	[12.5, 23.4]
	Adaptive-k	47.9	34.6	+13.3†	[9.0, 17.8]
	top-3	48.1	42.4	+5.7	[0.8, 10.5]

re-scoring DL19 and SciFact with the same snapshot in all three formats left 25–86% of pairs identical, changed probabilities by 0.0004–0.010 on average (at most 0.21), and gave a mean per-query Kendall τ of 0.92–0.96 between runs; nDCG@10 changed by at most 0.9 points on DL19 and 0.3 on SciFact. Complete SHA-256 hashes for the MuSiQue and DPR input files are recorded in the reproduction manifest.

Raw-probability thresholds (post-hoc). These avoid Platt fitting but retain the readout chosen by Brier score on labelled calibration questions. At $t = 0.3/0.5/0.7$, Jev selects on average 1.4/0.8/0.4 passages on MuSiQue (empty for 25/46/70%) and 3.1/2.5/1.9 on NQ (19/25/33%). On MuSiQue, raw $P > 0.3$ is 1.6–2.4 F1 below the Platt threshold and 3.4–5.9 below top-3 (all generators, $p < 0.02$ except Llama versus Platt, $p = 0.07$); on NQ it is within 1.3 F1 of both (only Qwen2.5-7B versus Platt is significant, +0.8). These are not label-free policies.

Pooled-inference sensitivity. Table 13 contrasts normal and modified Knapp–Hartung intervals using the same DL heterogeneity estimates. The CSV additionally covers the DL and Clef–Jev format comparisons. Jev S4 versus bge on DL has mKH 90% CI [−1.81, 3.16]: non-inferiority at −2 survives, while equivalence does not. Clef–Jev equivalence survives for all three formats. Jev S4 versus Qwen8B and Clef S4 versus its base do not establish ±2 equivalence under mKH. These analyses and margins are exploratory.

Prompt sensitivity. We fixed three paraphrases each of the Noul question, the Qwen3-235B yes/no prompt, and the Qwen3-Reranker instruction before running any of them (code: `PARAPHRASES`, `USER_PARAPHRASES`, `INSTRUCTIONS`). For Qwen3-Reranker-0.6B on DL19, DL20, and SciFact, the paraphrases change nDCG@10 by at most 2.0 points (DL19 69.4 with the default instruction versus 71.2–71.4), but they lower raw ECE on DL from 39.0 and 46.2 to 23.5–26.0 and 28.8–32.5; on SciFact ECE stays within 3.0–4.4. The default instruction is therefore the least calibrated of the four wordings, so raw-ECE comparisons with the Qwen rerankers depend on the prompt. Jev's Noul question is equally robust in ranking (nDCG@10 within 2.7 points of the original on all three collections) but not in calibration: raw ECE ranges from 7.5 to 25.9 on DL19 (original 12.4), 14.3 to 34.5 on DL20 (20.7), and 2.0 to 6.5 on SciFact (3.1). The original wording sits in the middle of

this range, and the most direct wording ("Is the passage relevant to the search query?") is the least calibrated on every collection. Raw-ECE differences of a few points between Jev and the baselines (Table 4) are therefore within the spread that rewording alone produces. For Qwen3-235B, the paraphrases also keep nDCG@10 within 2.3 points (DL19 68.6 versus 69.8–70.9; DL20 66.5 versus 65.5–66.6), but the original wording is the best calibrated: raw ECE rises from 18.6 to 20.6–30.4 on DL19 and from 22.0 to 25.3–34.9 on DL20. On SciFact (no original run) the paraphrases agree within 0.3 nDCG@10 and 1.6 ECE points. Paraphrase 3 and the last 6% of paraphrase 2 were served by one deployment, after the other retired the model.

Neural first stage. To check whether the system ordering depends on BM25, we reranked RankLLM's SPLADE++ EnsembleDistil top-100 candidates for DL19 and DL20 (same qrels) with bge-reranker-v2-m3, MiniLM, Qwen3-Reranker-8B, and Jev's three formats. SPLADE++ alone reaches 73.1/72.0 nDCG@10 on DL19/DL20 (BM25: 50.6/48.0), so every reranker gains much less. bge-reranker-v2-m3 scores 76.0/75.6, Qwen8B 75.5/73.1, and MiniLM 74.9/74.4. Jev scores 70.5–72.9 on DL19, 3.1–5.5 points below bge (Score-4: $p = 0.03$, unadjusted) and below the SPLADE++ ranking itself, whereas on BM25 candidates it was within 1.1 points of bge. On DL20 it scores 74.6–77.1, and Noul is the best system (77.1, +1.5 over bge, $p = 0.50$). With 43 and 54 queries these differences are imprecise, but the parity between Jev and the cross-encoders on DL19 does not carry over to a strong neural first stage. Unjudged candidates count as non-relevant, and we did not check whether Jev ranks more unjudged SPLADE++ candidates highly than the cross-encoders do, so part of the DL19 drop may reflect pool coverage rather than ranking quality.

Split and provenance audit. Calibration, pilot, and final question IDs are disjoint, but MuSiQue families overlap substantially. Comparing `question_decomposition[-1].id`, 494 final questions share the terminal sub-question with pilot, 349 with calibration, 265 with both, and 578 with either. Comparing any decomposition ID gives 593 pilot overlaps, 430 calibration overlaps, and 671 with either (352 with both). Counts are affected final questions, not unique IDs or matching pairs. The earlier whole-question normalization check found one pilot/final duplicate but missed component reuse. The local component audit checks the source hash and all six cached ranker split-ID sets; its CSV records question-level memberships. The 329-question sensitivity excludes any directly shared component, yet 23 questions in 18 source-graph families remain indirectly connected to design questions. It therefore cannot establish fully family-disjoint generalization. The audit and sensitivity scripts preserve the original splits and model outputs. The reproduction manifest records complete input SHA-256 hashes, all split IDs, installed package versions, analysis-source hashes, and the run-manifest hash, and links the component audit. Historical Hugging Face weight commits were not recorded; architecture strings cannot recover exact weight revisions. Original cached outputs should be preserved for historical numerical verification.

Table 13: Post-hoc sensitivity of pooled ranking inference to small-sample uncertainty. Both methods use the same DerSimonian–Laird heterogeneity estimate; mKH uses a Student-t reference with $k-1$ degrees of freedom and a residual variance multiplier floored at one. Units: nDCG@10 points. A 90% interval inside ± 2 corresponds to the exploratory equivalence criterion; the margin was chosen after observing results.

Comparison	k	Pooled difference	Normal CI	mKH CI
Jev S4 – bge, all (95%)	13	+2.60	[0.07, 5.13]	[-0.37, 5.57]
Jev S4 – bge, no Robust04 (95%)	12	+1.73	[0.09, 3.36]	[-0.42, 3.87]
Jev S4 – Qwen8B, all (90%)	13	+0.31	[-1.26, 1.89]	[-1.39, 2.02]
Clef S4 – base, seven collections (90%)	7	+0.98	[-0.27, 2.23]	[-0.50, 2.46]
Jev S4 – Qwen8B, no Robust04 (90%)	12	-0.29	[-1.36, 0.77]	[-1.59, 1.00]

Table 14: nDCG@10 for reranking the BM25 top-100 (Pyserini runs and qrels, as in RankGPT/RankLLM). $^{\uparrow}/^{\downarrow}$: significantly better/worse than bge-reranker-v2-m3 (paired t-test over queries, Holm-corrected over the collections each pair was evaluated on, $p < 0.05$). Best per column in bold. Averages are reported only for systems run on every collection of the group (dash otherwise); matched comparisons for Clef and the P(yes) LLMs are given in the text. Touche, News and Robust04 contain long documents that every model truncates (Table 3).

	TREC Deep Learning						BEIR									
System	DL19	DL20	DL21	DL22	DL23	*Avg*	Covid	NFC	Touche	DBP	SciF	Signal	News	Rob04	*Avg*	**All**
BM25 (first stage)	50.6	48.0	44.6	26.9	26.2	39.3	59.5	32.2	**44.2**	31.8	67.9	33.1	39.5	40.7	43.6	41.9
Cross-encoders																
MiniLM-L6 (22M)	72.7	67.5	65.6	49.9	42.2	59.6	74.5	34.9	28.4$^{\downarrow}$	43.9	69.5$^{\downarrow}$	**33.9**$^{\uparrow}$	44.3	47.3$^{\downarrow}$	47.1	51.9
bge-reranker-v2-m3 (568M)	72.4	68.1	66.2	**51.4**	45.1	60.6	78.3	34.3	38.3	44.0	75.0	29.0	43.6	51.9	49.3	53.7
Label-probability LLM rerankers																
Qwen3-Reranker-0.6B	69.4	64.0	65.1	46.3$^{\downarrow}$	38.8$^{\downarrow}$	56.7	**86.2**$^{\uparrow}$	36.8$^{\uparrow}$	29.2$^{\downarrow}$	43.3	76.8	30.6	45.5	55.8$^{\uparrow}$	50.5	52.9
Qwen3-Reranker-4B (4-bit)	**74.0**	68.2	66.2	50.4	45.0	60.7	84.1$^{\uparrow}$	37.1$^{\uparrow}$	34.9	**46.4**$^{\uparrow}$	77.8	33.8$^{\uparrow}$	48.6$^{\uparrow}$	57.4$^{\uparrow}$	52.5	55.7
Qwen3-Reranker-8B (4-bit)	73.6	66.5	66.2	51.1	44.9	60.5	83.8$^{\uparrow}$	37.5$^{\uparrow}$	36.2	45.5	79.2$^{\uparrow}$	33.7$^{\uparrow}$	**51.6**$^{\uparrow}$	58.0$^{\uparrow}$	**53.2**	56.0
Qwen3-235B, P(yes)	68.6	66.5	65.6	46.2	42.8	57.9	80.0	34.6	–	–	–	–	–	60.2$^{\uparrow}$	–	–
Qwen3-235B, graded 0–4	71.6	66.3	68.5	45.5$^{\downarrow}$	44.1	59.2	83.0	37.5$^{\uparrow}$	–	–	–	–	–	61.9$^{\uparrow}$	–	–
Qwen3.8-27B (Clef's base), P(yes)	73.0	69.8	69.2	48.8	45.5	61.2	83.7	–	–	–	–	–	–	62.5$^{\uparrow}$	–	–
Qwen3.5-0.8B (Jeff's base), P(yes)	42.9$^{\downarrow}$	38.9$^{\downarrow}$	50.6$^{\downarrow}$	26.3$^{\downarrow}$	28.6$^{\downarrow}$	37.4	60.2$^{\downarrow}$	17.3$^{\downarrow}$	19.1$^{\downarrow}$	21.4$^{\downarrow}$	28.0$^{\downarrow}$	24.4$^{\downarrow}$	22.7$^{\downarrow}$	33.5$^{\downarrow}$	28.3	31.8
Qwen3.5-0.8B (Jeff's base), graded 0–4	34.8$^{\downarrow}$	31.7$^{\downarrow}$	33.5$^{\downarrow}$	18.7$^{\downarrow}$	20.6$^{\downarrow}$	27.9	60.0$^{\downarrow}$	17.1$^{\downarrow}$	16.7$^{\downarrow}$	20.1$^{\downarrow}$	28.0$^{\downarrow}$	14.2$^{\downarrow}$	22.1$^{\downarrow}$	25.1$^{\downarrow}$	25.4	26.4
Laya (421M)																
Choice-3	60.0$^{\downarrow}$	52.1$^{\downarrow}$	54.7$^{\downarrow}$	36.0$^{\downarrow}$	33.8$^{\downarrow}$	47.3	74.1	29.3$^{\downarrow}$	23.3$^{\downarrow}$	29.6$^{\downarrow}$	48.6$^{\downarrow}$	22.6$^{\downarrow}$	37.2$^{\downarrow}$	34.6$^{\downarrow}$	37.4	41.2
Noul	57.1$^{\downarrow}$	52.1$^{\downarrow}$	55.0$^{\downarrow}$	36.2$^{\downarrow}$	32.0$^{\downarrow}$	46.5	74.2	28.9$^{\downarrow}$	22.5$^{\downarrow}$	28.7$^{\downarrow}$	44.5$^{\downarrow}$	21.8$^{\downarrow}$	35.7$^{\downarrow}$	34.5$^{\downarrow}$	36.4	40.3
Score-4	62.2$^{\downarrow}$	53.0$^{\downarrow}$	53.0$^{\downarrow}$	37.5$^{\downarrow}$	33.4$^{\downarrow}$	47.8	74.1	27.2$^{\downarrow}$	23.5$^{\downarrow}$	25.9$^{\downarrow}$	39.4$^{\downarrow}$	21.3$^{\downarrow}$	36.0$^{\downarrow}$	32.8$^{\downarrow}$	35.0	40.0
Jeff (0.8B)																
Choice-3	55.4$^{\downarrow}$	46.1$^{\downarrow}$	49.0$^{\downarrow}$	32.1$^{\downarrow}$	28.9$^{\downarrow}$	42.3	68.7$^{\downarrow}$	24.6$^{\downarrow}$	22.9$^{\downarrow}$	29.3$^{\downarrow}$	54.4$^{\downarrow}$	27.0	34.2$^{\downarrow}$	35.8$^{\downarrow}$	37.1	39.1
Noul	59.5$^{\downarrow}$	50.1$^{\downarrow}$	52.5$^{\downarrow}$	33.0$^{\downarrow}$	30.4$^{\downarrow}$	45.1	67.3$^{\downarrow}$	24.5$^{\downarrow}$	23.5$^{\downarrow}$	30.0$^{\downarrow}$	46.7$^{\downarrow}$	27.4	33.6$^{\downarrow}$	34.1$^{\downarrow}$	35.9	39.4
Score-4	55.1$^{\downarrow}$	47.1$^{\downarrow}$	50.0$^{\downarrow}$	32.4$^{\downarrow}$	30.1$^{\downarrow}$	42.9	67.9$^{\downarrow}$	24.6$^{\downarrow}$	23.4$^{\downarrow}$	27.4$^{\downarrow}$	55.0$^{\downarrow}$	27.0	34.5$^{\downarrow}$	35.6$^{\downarrow}$	36.9	39.2
Clef 27B (open weights, API; 7 collections)																
Choice-3	71.5	70.0	66.8	48.5	44.7	60.3	82.8	–	–	–	–	–	–	66.5$^{\uparrow}$	–	–
Noul	71.3	69.9	67.3	47.7	46.4	60.5	83.1	–	–	–	–	–	–	66.2$^{\uparrow}$	–	–
Score-4	72.2	**70.2**	69.3	49.1	**46.8**	**61.5**	84.0	–	–	–	–	–	–	**66.5**$^{\uparrow}$	–	–
Jev 1.13 (API)																
Choice-3	71.7	70.0	68.5	46.8	43.1	60.0	82.8	37.9$^{\uparrow}$	32.1	43.2	79.6$^{\uparrow}$	30.3	46.6	66.0$^{\uparrow}$	52.3	55.3
Noul	71.3	70.0	69.5	50.1	45.0	61.2	84.1	37.7$^{\uparrow}$	35.5	42.7	79.8$^{\uparrow}$	28.3	47.6	66.0$^{\uparrow}$	52.7	56.0
Score-4	72.8	69.9	**70.0**$^{\uparrow}$	48.5	44.3	61.1	85.0$^{\uparrow}$	**38.4**$^{\uparrow}$	31.6	44.5	**80.0**$^{\uparrow}$	29.8	48.6	65.9$^{\uparrow}$	53.0	**56.1**