Here is a list of tips to make your LaTeX projects more modular, readable, and maintainable:

- A latex page often have - Lists, Tables, Images. Create seprate tex files for them and use input command to include then in the page.
- **Use** `subfiles` to divide the content into separate files, allowing independent compilation of chapters or sections. **Use** `\input` **or** `\include` to separate sections or chapters into different files for better structure.
- **Define reusable variables and commands** with `\newcommand` or `\def` to keep your code cleaner and avoid repetition.
- **Use** `\begingroup` **and** `\endgroup` to limit the scope of variables or formatting changes, which are automatically destroyed after use. Use a group to safely define macros in one subfile and use them in another, without polluting the global scope. For example:

```
\begingroup
    \input{\subfix{cat.tex}}   % defines macros (e.g., \myVar)
    \input{\subfix{apple.tex}} % uses \myVar
\endgroup
```

  This ensures macros like `\myVar` do not affect other parts of the document.
- **Create custom environments** with `NewDocumentEnvironment` to define consistent styles or formatting for repeated structures.
- **Organize packages and settings** in a separate preamble file or style file (`.sty`) to avoid cluttering the main document.
- **Comment generously** and maintain a changelog for collaborative projects or long-term maintenance.
- **Use bibliographies modularly** with BibTeX or BibLaTeX in separate files for easier management of references.
- **Avoid hard-coded formatting** in the main document; define styles and colors globally using commands or custom environments.
- **Use consistent naming conventions** for labels, commands, and files to reduce confusion and improve readability.
- **Test small sections independently** before compiling the whole document to quickly catch errors.

Tips while writing latex code

- Avoid `\begin{center}` around floats — use `\centering`.

- `\centering` centers content inside the float.
- Always add `\caption{}` inside the table if you want it to appear in the List of Tables.
- Use `\label{}` after `\caption{}` to reference the table in text.
- `[h!]` → "try to place here as much as possible".

Chapter 1

Tables in LaTeX

1.1 Simple Table With Variables

Apple	Fruit

Table 1.1: Simple table

```
% usepackage : [table]{xcolor}, float(h!), caption
\begingroup
    % Define variables(macros) for table using \def or \newcommand
    \def\cellOneA{\textbf{Apple}}
    \def\cellOneB{\textcolor{red}{Fruit}}
    \setlength{\tabcolsep}{10pt}
    % Now use these variables inside a table
    \begin{center}
        \renewcommand{\arraystretch}{1.2}
        \begin{tabular}{|c|c|}
        \hline
        \cellOneA & \cellOneB \\ \hline
        \end{tabular}
        \begin{table}[!h]
          \caption{Simple table}
        \end{table}
    \end{center}
    \medskip
\endgroup % After \endgroup, macros \cellOneA etc. are no longer defined.
```

1.2 Simple Table using centering without begin(center)

Fruit	Apple
Animal	Cat

Table 1.2: Table with environment

Code:

```
\begin{simpleCenteringTempChapterTable}{Table with environment}
    \def\cellOneA{\textbf{Fruit}}
    \def\cellOneB{\textcolor{red}{Apple}}
    \def\cellTwoA{\textbf{Animal}}
    \def\cellTwoB{\textcolor{orange}{Cat}}

    \begin{tabular}{|c|c|} \hline
        \cellOneA    & \cellOneB     \\ \hline
        \cellTwoA    & \cellTwoB                \\ \hline
    \end{tabular}
\end{simpleCenteringTempChapterTable}
```

Listing 1.1: Simple Table Example

```
\NewDocumentEnvironment{simpleCenteringTempChapterTable}{m} % #1 = caption
{%
  \begingroup                          % <--- start local scope
  \begin{table}[!h]
    \centering
    \setlength{\tabcolsep}{10pt}
    \renewcommand{\arraystretch}{1.4}
}{%
    \caption{#1}
  \end{table}
  \endgroup                            % <--- end local scope (cleans variables)
}
```

Listing 1.2: Simple Table Example

1.3 Custom Tables

Description(c)	Content(c)	Tag Used(p)
Table Cell with 2 rows	Apple Mango	makecell, \\
Table Cell with 2 rows	newlinecol c	newline col p
A multi row cell	Eagle	multirow, cline
	Parrot	6em or *
Multi column cell		multicolumn, l, c, r

Table 1.3: Customizing The Cells

```
% \makecell[l]{\textcolor{red}{Apple} \\ \textcolor{green}{Mango}}
```

```
% \multirow{2}{6em}{Birds}    & Eagle  & Apple  \\ \cline{2-3}
%                             & Parrot & Banana \\ \hline
```

```
% \multicolumn{2}{|l|}{Multi column cell} &  Apple \\ \hline
```

```
\begin{myTableStyle}{Customizing The Cells}
    \def\HA{\textbf{Description(c)}}    \def\HB{\textbf{Content(c)}}
    \def\HC{\textbf{Tag Used(p)}}
    \def\cellOneA{Table Cell with 2 rows}
    \def\cellOneB{\makecell[l]{\textcolor{red}{Apple} \\ \textcolor{green}{Mango}}}
    \def\cellOneC{makecell, \texttt{\textbackslash\textbackslash}}
    \def\cellTwoA{Table Cell with 2 rows}
    \def\cellTwoB{\textcolor{red}{newline} \newline \textcolor{green}{col c}}
    \def\cellTwoC{\textcolor{red}{newline} \newline \textcolor{green}{col p}}
    \def\cellThreeA{\multirow{2}{6em}{A multi row cell}}
    \def\cellThreeB{Eagle}  \def\cellThreeC{multirow, cline}
    \def\cellFourB{Parrot}  \def\cellFourC{6em or *}
    \def\cellFiveAB{\multicolumn{2}{|l|}{Multi column cell}}
    \def\cellFiveC{multicolumn, l, c, r}
    \begin{tabular}{|c|c|p{6cm}|} \hline
        \HA             & \HB           &   \HC             \\ \hline
        \cellOneA       & \cellOneB     &   \cellOneC       \\ \hline
        \cellTwoA       & \cellTwoB     &   \cellTwoC       \\ \hline
        \cellThreeA     & \cellThreeB   &   \cellThreeC     \\ \cline{2-3}
                        & \cellFourB    &   \cellFourC      \\ \hline
        \cellFiveAB                     &   \cellFiveC      \\ \hline
    \end{tabular}
\end{myTableStyle}
```

1.4 Not recommended : Table Using begin{center}.

Fruit	Apple
Animal	Cat

Table 1.4: Table with environment

Code:

```
\begin{simpleTableEnvTempChapterTable}{Table with environment}
    \def\cellOneA{\textbf{Fruit}}
    \def\cellOneB{\textcolor{red}{Apple}}
    \def\cellTwoA{\textbf{Animal}}
    \def\cellTwoB{\textcolor{orange}{Cat}}

    \begin{tabular}{|c|c|} \hline
        \cellOneA    & \cellOneB     \\ \hline
        \cellTwoA    & \cellTwoB                \\ \hline
    \end{tabular}
\end{simpleTableEnvTempChapterTable}
```

Listing 1.3: Simple Table Example

```
\NewDocumentEnvironment{simpleTableEnvTempChapterTable}{m}
{
    \begingroup
    \setlength{\tabcolsep}{10pt}
    \begin{center}
    \renewcommand{\arraystretch}{1.2}
}{
    \begin{table}[!h]
        \caption{#1}
    \end{table}
    \end{center}
    \endgroup
}
```

Listing 1.4: Simple Table Example

Chapter 2

Lists in LaTeX

2.1 Lists in LaTeX

2.1.1 Basic lists

Basic unordered list:

- Apple
- Orange

Basic ordered list:

1. Apple
2. Orange

```
% usepackage : enumitem
\noindent Basic unordered list:
\par
\begin{itemize}[nosep]  % nosep(no extra vertical space)
  \item Apple
  \item Orange
\end{itemize}

\noindent Basic ordered list:
\par
\begin{enumerate}
  \item Apple
  \item Orange
\end{enumerate}
```

2.1.2 Basic lists

Description list:

XX Apple
AAA Orange

```
% usepackage : enumitem
\noindent Description list:
\par
\begin{description}[itemsep=0pt,parsep=0pt] % itemsep and parsep
  \item[XX] Apple
  \item[AAA] Orange
\end{description}
```

2.1.3 Wide lists

Wide list for paragraph-like items:

- This item demonstrates wide layout so that wrapped lines align with the text block instead of being indented.
- Another wide item to illustrate multi-line behavior with compact spacing.

```
% chapters/chap03-lists/example_codes/wide_lists_example.tex
% Wide lists: labels align with paragraph, subsequent lines unindented
\noindent Wide list for paragraph-like items:
\par
\begin{itemize}[wide,nosep]
  \item This item demonstrates wide layout so that wrapped lines align with the text
    ↪ block instead of being indented.
  \item Another wide item to illustrate multi-line behavior with compact spacing.
\end{itemize}
```

2.1.4 Nested lists

Nested lists:

- Outer A
- Outer B
  - Inner B.1
  - Inner B.2
    1. Numbered subpoint 1
    2. Numbered subpoint 2
- Outer C

```
% usepackage : enumitem
\noindent Nested lists:
\par
\begin{itemize}
  \item Outer A
  \item Outer B
  \begin{itemize}
    \item Inner B.1
    \item Inner B.2
    \begin{enumerate}
      \item Numbered subpoint 1
      \item Numbered subpoint 2
    \end{enumerate}
  \end{itemize}
  \item Outer C
\end{itemize}
```

2.1.5 Custom labels and refs

Custom-labeled enumerate/ref. See Q2, and Q3 [uses ref= to mirror labels].

Q1. What is your name?

Q2. What is your quest?

Q3. What is your favorite color?

In-paragraph list (manual punctuation), useful for compact text:
(a) apples,
(b) bananas,
(c) cherries,
(d) dates.

```
% usepackage : enumitem
\noindent Custom-labeled enumerate/ref. See \ref{itm:q2}, and \ref{itm:q3} [uses ref= to
    ↪ mirror labels].
\par
\begin{enumerate}[label=Q\arabic*.,ref=Q\arabic*]
  \item\label{itm:q1} What is your name?
  \item\label{itm:q2} What is your quest?
  \item\label{itm:q3} What is your favorite color?
\end{enumerate}


\noindent In-paragraph list (manual punctuation), useful for compact text:
\par
\begin{enumerate}[label=(\alph*),nosep]
  \item apples, \item bananas, \item cherries, \item dates.
\end{enumerate}
```

Chapter 3

Figures in LaTeX

3.1 Environment For Using Figures

```
% usepackage : xparse(NewDocumentEnvironment), graphicx(includegraphics), float(h!),
    ↪ subfiles(subfix), caption
\NewDocumentEnvironment{simpleImage}{ m m o o }
{
  \begin{figure}[h!]
    \centering
    \includegraphics[width=#2]{#1}
    \IfValueTF{#3}{\caption{#3}}{}
    \IfValueTF{#4}{\label{#4}}{}
}{ \end{figure} }

\begin{simpleImage}
        {\subfix{example_codes/img_02.jpg}}
        {0.6\linewidth}
        [A simple example image]
        [fig:simple_image]    % use [] to provide empty values
\end{simpleImage}}
```

```
% 2 mandatory, 2 optional args
% #1=image, #2=width, #3=caption, #4=label
% m(mandatory), o(optional []), O({default}), s(starred version)
```

3.2 Environment For Box Figures and List figures

```
% usepackage : xparse(NewDocumentEnvironment), graphicx(includegraphics), subfiles(
    ↪ subfix), caption
\NewDocumentEnvironment{centerBoxImageStyle}{ m m m m m }
{
\begin{center}
  \fbox{%
    \begin{minipage}{#2}
      \centering
      \includegraphics[width=#3]{#1}
      \captionof{figure}{#4}
      \label{#5}
    \end{minipage}
  }
\end{center}
}{}
\begin{comment}
```

```
  \begin{centerBoxImageStyle}
    {\subfix{example_codes/img_02.jpg}}     % #1 image path
    {0.6\linewidth}                         % #2 minipage width (box width)
    {0.9\linewidth}                         % #3 image width inside box
    {A simple example image inside a box.}  % #4 caption
    {}                                      % #5 label
  \end{centerBoxImageStyle}
\end{comment}
% m(mandatory), o(optional []), O({default}), s(starred version)
```

3.3 Simple Figures



Figure 3.1: A simple example image.

```
% usepackage : graphicx(includegraphics), float(h!), subfiles(subfix), caption
\begin{figure}[h!]
    \centering
    \includegraphics[width=0.6\linewidth]{\subfix{example_codes/img_02.jpg}}
    \caption{A simple example image.}
    \label{fig:simple_image}
\end{figure}
```

3.4 Figures in Box, keep in list



Figure 3.2: A simple example image inside a box.

```
% usepackage : graphicx(includegraphics), float(h!), subfiles(subfix), caption
\begin{center} % Boxed image
  \fbox{%
    \begin{minipage}{0.6\linewidth}
      \centering
      \includegraphics[width=0.9\linewidth]{\subfix{example_codes/img_02.jpg}}
      \captionof{figure}{A simple example image inside a box.}
      \label{fig:simple_boxed_image}
    \end{minipage}
  }
\end{center}
```

3.5 Importatnt Points to add Figures

- Create environment(template) which take arguments and display image.
- Create a seprate tex file that will use the template to display image.
- Import the tex file create in above step to your main code.

Chapter 4

Variables in LaTeX

Variables are destroyed after endgroup. (begingroup - endgroup)

4.1 Simple Text Variables in tables

Apple	Fruit
Carrot	Vegetable

```
\begingroup
    % Define "variables" (macros) for table cells using \def or \newcommand
    \def\cellOneA{\textbf{Apple}}
    \def\cellOneB{\textcolor{red}{Fruit}}
    \def\cellTwoA{\textbf{Carrot}}
    \def\cellTwoB{\textcolor{orange}{Vegetable}}

    % Now use these variables inside a table
    \begin{center}
        \begin{tabular}{|c|c|}
        \hline
        \cellOneA & \cellOneB \\ \hline
        \cellTwoA & \cellTwoB \\ \hline
        \end{tabular}
    \end{center}
    \medskip
    % After \endgroup, macros \cellA, \cellB, etc. are no longer defined.
\endgroup
```

4.2 Simple Text Variables

Text Variable.

```
\newcommand{\varText}{\textbf{Text Variable}.}
```

4.3 Simple Maths Variables

$$E = mc^2$$

```
\def\varMath{$E = mc^2$}   \varMath
```

4.4 Simple tikz image Variables

Figure 4.1: Stored Figure

```
\begingroup
    \newsavebox{\figBox}
    \begin{lrbox}{\figBox}
        \begin{tikzpicture}[scale=0.8]
            \draw[fill=orange!40] (2.5,0) rectangle (3.5,1);
            \node at (3,0.5) {Box};
        \end{tikzpicture}
    \end{lrbox}

    \begin{figure}[h]
        \centering
        \usebox{\figBox}
        \caption{Stored Figure}
    \end{figure}
\bigskip
\endgroup
```

4.5 Simple Table Variables

Fruit	**Color**
Apple	Red

Stored Figure

```
\begingroup
        \newsavebox{\tableBox}
        \begin{lrbox}{\tableBox}
                \begin{tabular}{|c|c|} \hline
                        \textbf{Fruit} & \textbf{Color} \\ \hline
                        Apple & Red \\ \hline
                \end{tabular}
        \end{lrbox}

        \begin{center}
                \usebox{\tableBox}\\[3pt]
                \textbf{Stored Figure}
        \end{center}
\endgroup
```

4.6 Dynamic content variable using newtoks

This is *stored* in a token register.

```
\begingroup
    \newtoks\varTokens
    \varTokens={This is \textit{stored} in a token register.}
    \the\varTokens
\endgroup
```

4.7 Temporary macros (auto-destroyed after scope)

Scoped **variable A**

```
\begingroup
    \def\tempA{Scoped \textbf{variable A}}
    \medskip
    \noindent \tempA
\endgroup
```

Chapter 5

Code listing in LaTeX

5.1 Simple Text Variables in tables

```
% Core package for syntax-highlighted code listings
% \usepackage{listings}

% Automatically remove common indentation in code blocks
% \usepackage{lstautogobble}

% Define custom float environments (e.g., for code listings)
% \usepackage{newfloat}

% Define a float type "listing" for displaying code blocks with captions and numbering
\DeclareFloatingEnvironment[
    fileext=lol,
    listname=List of Listings,
    name=Listing
]{listing}
```

```
\input{\subfix{example_codes/variable_newtoks.tex}}

\lstinputlisting[
    language=TeXish,
    linerange={1-19}
]{\subfix{example_codes/code_01.tex}}
```

```
\lstinputlisting{\subfix{example_codes/itemize_example.tex}}
```

```
% A lightweight LaTeX language so LaTeX code looks colorful
\lstdefinelanguage{TeXish}{
  sensitive=true,
  morekeywords=[1]{\\begin,\\end,\\usepackage,\\documentclass,\\section,\\subsection,\\
    ↪ emph,\\textbf,\\textit,\\item,\\label,\\ref,\\cite,\\caption,\\includegraphics,\\
    ↪ color,\\lstset,\\lstdefinestyle,\\lstdefinelanguage,\\NewDocumentEnvironment,\\
    ↪ IfBooleanTF,\\IfValueTF,\\centering},

  morekeywords=[2]{\\newcommand,\\renewcommand,\\DeclareMathOperator,\\title,\\author,\\
    ↪ date,\\maketitle,\\includegraphics},

  morekeywords=[3]{\\LaTeX,\\TeX},

  alsoletter=\\,

  morecomment=[l]{\%},

  morestring=[b]",

  morestring=[b]'
}
```

```latex
\lstset{
  basicstyle=\ttfamily\small,                    % Monospaced small font
  backgroundcolor=\color{gray!5},                % Light gray background
  frame=single,                                  % Draw a box around the code
  breaklines=true,                               % Allow automatic line breaking
  postbreak=\mbox{\textcolor{red}{$\hookrightarrow$}\space}, % Indicate wrapped lines
  numbers=none,                                  % Line numbers on the left
  keepspaces=true,                               % Preserve spaces exactly as in source
  columns=flexible,                              % Improves copying of tabular alignment
  % numberstyle=\tiny\color{gray},               % Style of line numbers
  captionpos=b,                                  % Caption position (bottom)
  autogobble=true,                               % Trim indentation from source
  showstringspaces=false                         % Dont mark spaces in strings
  % Add only color-oriented styling below:
  language=TeXish,
  keywordstyle=\color{codekw}\bfseries,              % [1]
  keywordstyle={[2]\color{codekw2}\bfseries},        % [2]
  keywordstyle={[3]\color{codekw3}\bfseries},        % [3]
  stringstyle=\color{codestr},
  commentstyle=\color{codecm}\itshape,
  identifierstyle=\color{codeid},
  emph={\return},
  emphstyle=\color{codestr}\bfseries,
  literate=
    {*}{{\textcolor{codedelim}{*}}}1
    {=}{{\textcolor{codedelim}{=}}}1
    {(}{{\textcolor{codedelim}{(}}}1
    {)}{{\textcolor{codedelim}{)}}}1
    {[}{{\textcolor{codedelim}{[}}}1
    {]}{{\textcolor{codedelim}{]}}}1
    {,}{{\textcolor{codedelim}{,}}}1
}
```

Chapter 6

Drawing tikz in LaTeX

6.1 Drawing

```
% \usepackage{tikz}
% \usetikzlibrary{shapes.geometric, shapes.symbols, arrows, arrows.meta, positioning,
    ↪ shadows.blur, backgrounds}
```

```
\tikzstyle{rectangle_a_blue} = [
    rectangle,
    rounded corners=4pt,
    minimum width=3.2cm,
    minimum height=1.2cm,
    text centered,
    text width=3cm,
    inner sep=6pt,
    font=\bfseries\small,
    draw=blue!40!black,
    line width=0.9pt,
    fill={rgb,255:red,110; green,140; blue,210},
    text=white,
    blur shadow={shadow blur steps=5}
]
```

```
\tikzstyle{rec_b_pink} = [
    rectangle,
    rounded corners=4pt,
    minimum width=3.2cm,
    minimum height=1.2cm,
    text centered,
    text width=3cm,
    inner sep=6pt,
    font=\bfseries\small,
    draw=pink!60!red,
    line width=0.9pt,
    fill={rgb,255:red,255; green,200; blue,220}, % light pink
    text={rgb,255:red,180; green,20; blue,90},   % dark pink
    blur shadow={shadow blur steps=5}
]

\tikzstyle{rec_b_pink_a} = [
    rectangle,
    rounded corners=4pt,
    % minimum width=3.2cm,
    minimum height=1.2cm,
    text centered,
    % text width=3cm,
    inner sep=6pt,
    font=\bfseries\small,
    draw=pink!60!red,
    line width=0.9pt,
    fill={rgb,255:red,255; green,200; blue,220}, % light pink
    text={rgb,255:red,180; green,20; blue,90},   % dark pink
    blur shadow={shadow blur steps=5}
]

\tikzstyle{cylinder_a_db} = [cylinder,
    draw = violet,
    text = purple,
    cylinder uses custom fill,
    cylinder body fill = magenta!10,
    cylinder end fill = magenta!40,
    minimum height=2cm,
    aspect = 0.2,
    shape border rotate = 90,
    text centered
]
```

```
\tikzstyle{rec_c_green} = [
    rectangle,
    rounded corners=4pt,
    minimum width=3.2cm,
    minimum height=1.2cm,
    text centered,
    text width=3cm,
    inner sep=6pt,
    font=\bfseries\small,
    draw=green!40!black,
    line width=0.9pt,
    fill={rgb,255:red,90; green,180; blue,110},
    text={rgb,255:red,20; green,90; blue,20},
    blur shadow={shadow blur steps=5}
]

\tikzstyle{cloud_a} = [cloud,
        draw =blue,
        text=cyan,
        % fill = gray!10,
        % minimum width = 3cm,
        % minimum height = 2cm,
    text centered]

\tikzstyle{cloud_a_blue} = [
    cloud,
    draw = blue!60!black,
    fill = {rgb,255:red,220; green,240; blue,255}, % light sky blue
    text = {rgb,255:red,0; green,80; blue,150},    % deep teal-blue text
    text centered,
    minimum width = 3cm,
    minimum height = 2cm
]

\tikzstyle{cloud_a_green} = [
    cloud,
    draw = green!50!black,
    fill = {rgb,255:red,220; green,255; blue,220},   % light pastel green background
    text = {rgb,255:red,60; green,140; blue,60},     % light-medium green text
    text centered,
    minimum width = 3cm,
    minimum height = 2cm
]
```

```
\tikzstyle{cloud_a_pink} = [
    cloud,
    draw = violet!60!black,
    fill = {rgb,255:red,255; green,225; blue,245}, % baby pink
    text = {rgb,255:red,160; green,0; blue,90},   % dark rose text
    text centered,
    minimum width = 3cm,
    minimum height = 2cm
]

\tikzstyle{trapezium_a_io} = [trapezium,
trapezium stretches=true, % A later addition
trapezium left angle=70,
trapezium right angle=110,
minimum width=3cm,
minimum height=1cm, text centered,
draw=black, fill=blue!30]

\tikzstyle{diamond_a_dec} = [diamond,
minimum width=3cm,
minimum height=1cm,
text centered,
draw=black,
fill=green!30]

\tikzstyle{arrow} = [ultra thick,->,>=stealth]
```

6.2 Drawings 01




```
\begin{tikzpicture}[node distance=1.5cm, scale=0.95, transform shape, framed, background
    ↪ rectangle/.style={draw=black, thick}]

\node[rectangle_a_blue] (n1) {Docs};

\node[rec_b_pink, right=of n1] (n2) {pre-processing};

\node[rec_b_pink, right=of n2] (n3) {tokenizaton};

\node[rec_b_pink, right=of n3] (n4) {Chunking};

\node[rec_b_pink, below=of n4] (n5) {Emb Model};

\node[cylinder_a_db, text width=1.8cm, left=3cm of n5] (n6) {Vector\\Database};


\draw[arrow] (n1) -- (n2);
\draw[arrow] (n2) -- (n3);
\draw[arrow] (n3) -- (n4);
\draw[arrow] (n4) -- node[anchor=west] {Chunks} (n5);
\draw[arrow] (n5) -- node[anchor=south] {Vectors} (n6);

\end{tikzpicture}
```

6.3 Drawings 02




```
% package needed \usetikzlibrary{calc}

\begin{tikzpicture}[node distance=1.5cm, scale=0.95, transform shape, framed, background
    ↪  rectangle/.style={draw=black, thick}]
    \node[rectangle_a_blue_a] at (0,0) (A) {User Input};
    % \coordinate (x) at ([yshift=-1cm]n3.south);
    % \coordinate (y) at (start |- x);
    \node[rec_b_pink_a, right= 2cm of A] (B) {OCI};
    \node[rec_b_pink_a, right= 2cm of B] (C) {Template 1};
    \node[circle,draw,minimum size=0.5cm,right= 3cm of C] (F) {LLM};
    \node[rectangle_a_blue_a,right= 1cm of F] (G) {Response};

    \draw[arrow] (A) -- node[anchor=south] {PDF} (B);
    \draw[arrow] (B) -- node[anchor=south] {text} (C);
    \draw[arrow] (C) -- node[anchor=south] {Sys Prompt} (F);
    \draw[->] (A.south) |- ($(A.south) + (0,-1)$) -- node[midway, above] {User Prompt} (
    ↪ $(F.south) + (0,-1)$) -| (F.south);
    \draw[arrow] (F) -- (G);
\end{tikzpicture}
```

6.4 Drawings 03




```latex
\begin{tikzpicture}[node distance=1.5cm, scale=1.1, transform shape, framed, background
    ↪ rectangle/.style={draw=black, thick}]

    % Nodes with explicit positioning to prevent overlap
    \node[rectangle_a_blue, align=left, text width=6cm] (ip) {RAG chunks\\User Input-\\
    ↪ Topic\\Difficulty\\Blooms level};
    \node[rec_b_pink_a, right=3cm of ip] (llm) {LLM};
    \node[cloud_a, aspect=1.7, text width=2cm, right=2cm of llm] (op) {Initial MCQs};

    % Arrows
    \draw[arrow] (ip) -- node[anchor=south] {Prompt} (llm);
    \draw[arrow] (llm) -- (op);




    % Nodes with explicit positioning to prevent overlap
    \node[rectangle_a_blue, align=left, text width=6cm, below=of ip] (ip2) {Initial MCQ
    ↪ drafts\\CoT reasoning instructions};
    \node[rec_b_pink_a, right=3cm of ip2] (llm2) {LLM};
    \node[cloud_a, aspect=1.7, text width=2cm, right=2cm of llm2] (op2) {Refined MCQs};

    % Arrows
    \draw[arrow] (ip2) -- node[align=center, text width=2cm] {COT Prompt} (llm2);
    \draw[arrow] (llm2) -- (op2);

\end{tikzpicture}
```

6.5 Drawings 04




```latex
\begin{tikzpicture}[node distance=1.5cm, framed, background rectangle/.style={draw=black
    ↪ , thick}]

    % Nodes with explicit positioning to prevent overlap
    \node[rectangle_a_blue, align=left, text width=6cm] (ip) {Current MCQs\\Self-refine
    ↪ critique templates\\Difficulty scoring instructions};
    \node[rec_b_pink_a, right=3cm of ip] (llm) {LLM};
    \node[rec_c_green, align=left, text width=4cm, right=2cm of llm] (op) {Difficulty
    ↪ scores\\critique instructions};

    % Arrows
    \draw[arrow] (ip) -- node[align=center, text width=2cm] {Critique Prompt} (llm);
    \draw[arrow] (llm) -- (op);

    % Nodes with explicit positioning to prevent overlap
    \node[rectangle_a_blue, align=left, text width=6cm, below=of ip] (ip2) {Current MCQ
    ↪ drafts\\Difficulty scores\\critique instructions};
    \node[rec_b_pink_a, right=3cm of ip2] (llm2) {LLM};
    \node[cloud_a, aspect=1.7, text width=3cm, right=2cm of llm2] (op2) {Refine MCQs\\
    ↪ Stem Updated};

    % Arrows
    \draw[arrow] (ip2) -- node[align=center, text width=2cm] {Refining Prompt} (llm2);
    \draw[arrow] (llm2) -- (op2);

\end{tikzpicture}
```