Computational MR imaging Laboratory 3: Partial Fourier imaging

Code submission is due by 12:00 before the next Thursday lab section. Please upload your code to StudOn in a described format. Late submissions will not be accepted.

Learning objectives

- Accelerate the acquisition of real-valued images using Hermitian symmetry in kspace
- Estimate the phase for partial Fourier reconstruction
- Apply the Margosian and POCS methods to reconstruct partial Fourier data
- 1. Zero-filled Fourier reconstruction and Hermitian symmetry reconstruction.
 - 1.1. Kdata is loaded by *load_kdata_pf*, which was acquired with a partial Fourier factor, PF=9/16.
 - 1.2. Define the half zero-filled kdata and the theoretical Hermitian symmetric kdata
 - 1.2.1. Define a method, *get_half_zf_kdata*, which returns a half zero-filled kdata.
 - 1.2.2. Define a method, *hermitian_symmetry*, which returns a theorical hermitian semmetric kdata of the half zero-filled kdata.
 - 1.2.3. Plot both kdata
 - 1.3. Compute and plot the half zero-filled Fourier reconstruction and the theoretical half-Fourier reconstruction (Hermitian symmetry only, no phase-correction).
 - 1.4. Discuss artifacts for each case.
- 2. Phase estimation function
 - 2.1. Write a method, *estim_phs* to estimate the phase of an image from a symmetric region at the center of k-space.
 - 2.2. Estimate the phase of the zero-filled kdata.
 - 2.3. Plot estimated phase
- 3. Margosian partial Fourier reconstruction
 - 3.1. Define a method, *get_window*, returning a window filter of type either Ramp or Hamming.
 - 3.2. Define a method, *pf_margosian*, for Margosian reconstruction.
 - 3.3. Reconstruct PF kdata using Margosian method with both Ramp and Hamming window filters.
 - 3.4. Discuss results between two filters in terms of SNR and potential artifacts.

Hamming has better SNR as it suppresses higher frequency components, but it also blurs the image

- 4. POCS partial Fourier reconstruction components, but it
 - 4.1. Define a method, *pf_pocs*, for POCS reconstruction.
 - 4.2. Perform POCS reconstruction on the PF kdata with multiple iterations (2, 4, 6, 8, and 10)
 - 4.3. Choose the minimum number of iterations where the algorithm has converged by comparing reconstructed images to each other. Hint: when comparing reconstructed images, do not forget to normalize images in a range of 0-1. Plot the change in the solution with respect to the number of iterations.

- 5. Comparison of reconstructions
 - 5.1. Plot the zero-filled FFT, two Margosian reconstructions, and POCS reconstruction.
 - 5.1.1. Fill 0s to the kdata in the original shape for the zero-filled FFT.
 - 5.2. Load fully-sampled kdata by calling a method, *load_kdata_full*, from the exercise from the previous week and plot the difference of your reconstructions to the IFFT reconstruction of the fully sampled. Which method provides a better reconstruction? Explain in terms of SNR, spatial resolution, residual artifacts and ringing.