

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT
on

OPERATING SYSTEMS

Submitted by

PARV JAIN (1WA24CS205)

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

Feb-2026 to June-2026

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “OPERATING SYSTEMS – 23CS4PCOPS” carried out by Parv Jain (1WA24CS205), who is Bonafide student of B. M. S. College of Engineering. It is in partial fulfilment for the award of Bachelor of Engineering in Computer Science and Engineering of the Visvesvaraya Technological University, Belgaum during the year Feb-2026 to June-2026

. The Lab report has been approved as it satisfies the academic requirements in respect of a OPERATING SYSTEMS - (23CS4PCOPS) work prescribed for the said degree.

Dr. Seema Patil
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Kavitha Sooda
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index Sheet

Sl. No.	Experiment Title	Page No.
1.	Write a C program to simulate the following CPU scheduling algorithm to find turnaround time and waiting time. a) FCFS b) SJF (Preemptive and Non-Preemptive) c) Priority (Preemptive and Non-Preemptive) d) Round Robin (Experiment with different quantum sizes for RR algorithm)	1-18
2.	Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.	19-22
3.	Write a C program to simulate Real-Time CPU Scheduling algorithms: a) Rate- Monotonic b) Earliest-deadline First c) Proportional scheduling	23-29
4.	Write a C program to simulate: a) Producer-Consumer problem using semaphores. b) Dining-Philosopher's problem	30-34
5.	Write a C program to simulate: a) Bankers' algorithm for the purpose of deadlock avoidance. b) Deadlock Detection	35-39
6.	Write a C program to simulate the following contiguous memory allocation techniques. a) Worst-fit b) Best-fit c) First-fit	40-42
7.	Write a C program to simulate page replacement algorithms. a) FIFO b) LRU c) Optimal	43-47

Course Outcomes:

C01	Apply the different concepts and functionalities of Operating System
C02	Analyse various Operating system strategies and techniques
C03	Demonstrate the different functionalities of Operating System.
C04	Conduct practical experiments to implement the functionalities of Operating system.

Program 1: Write a C program to simulate the following CPU scheduling algorithm to find turnaround time and waiting time.

a).FCFS:

```
#include<stdio.h>

int main(){

    int n;

    printf("Enter number of processes: ");

    scanf("%d",&n);

    int pid[n], at[n], bt[n], ct[n], tat[n], wt[n];

    printf("\nEnter Process ID, Arrival Time and Burst Time:\n");

    for(int i=0;i<n;i++){

        scanf("%d %d %d",&pid[i],&at[i],&bt[i]);

    }

    for(int i=0;i<n-1;i++){

        for(int j=i+1;j<n;j++){

            if(at[i] > at[j]){

                int temp;

                temp = at[i];

                at[i] = at[j];

                at[j] = temp;

                temp = bt[i];

                bt[i] = bt[j];

                bt[j] = temp;

                temp = pid[i];

                pid[i] = pid[j];

                pid[j] = temp;

            }

        }

    }

}
```

```

        }

    }

}

int time = 0;
for(int i=0;i<n;i++){
    if(time < at[i])
        time = at[i];
    ct[i] = time + bt[i];
    time = ct[i];
    tat[i] = ct[i] - at[i];
    wt[i] = tat[i] - bt[i];
}

float avgTAT = 0, avgWT = 0;
printf("\nProcess  AT  BT  CT  TAT  WT\n");
for(int i=0;i<n;i++){
    printf("%5d %3d %3d %3d %4d %4d\n",
        pid[i],at[i],bt[i],ct[i],tat[i],wt[i]);
    avgTAT += tat[i];
    avgWT += wt[i];
}

avgTAT /= n;
avgWT /= n;

printf("\nAverage Turnaround Time = %.2f",avgTAT);
printf("\nAverage Waiting Time = %.2f",avgWT);

return 0;
}

```

Output:

```
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\FCFS.exe"
Name:Parv Jain || USN: 1WA24CS205
Enter number of processes: 4

Enter Process ID, Arrival Time and Burst Time:
1 0 7
2 8 3
3 3 4
4 5 6

Process  AT  BT  CT  TAT  WT
      1  0  7  7   7   0
      3  3  4  11  8   4
      4  5  6  17  12  6
      2  8  3  20  12  9

Average Turnaround Time = 9.75
Average Waiting Time = 4.75
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> █
```

b) SJF

1. Preemptive:

```
#include <stdio.h>

int main(){

    int n, completed = 0, curr_time = 0, pid[10], at[10], bt[10],
    remt[10],

        ct[10], tat[10], wt[10], st[10], rt[10], i, j;

    double tat_sum = 0, wt_sum = 0;

    printf("Enter no. of processes: ");

    scanf("%d", &n);

    for (i = 0; i < n; i++) {

        pid[i] = i + 1;

        printf("Enter arrival time for process[%d]: ", i + 1);

        scanf("%d", &at[i]);
```

```

printf("Enter burst time for process[%d]: ", i + 1);

scanf("%d", &bt[i]);

remt[i] = bt[i];
}

while (completed != n) {
    int min = 99999999,
        s = -1;
    for (i = 0; i < n; i++) {
        if (at[i] <= curr_time && remt[i] > 0 && remt[i] < min) {
            min = remt[i];
            s = i;
        }
    }

    if (s == -1) {
        curr_time++;
        continue;
    }

    if (remt[s] == bt[s])
        st[s] = curr_time;
    remt[s]--;

    if (remt[s] == 0) {
        ct[s] = curr_time + 1;
        tat[s] = ct[s] - at[s];
        tat_sum += tat[s];
        wt[s] = tat[s] - bt[s];
        wt_sum += wt[s];
        rt[s] = st[s] - at[s];
    }
}

```



```

        completed++;

    }

    curr_time++;

}

printf("\nP\tAT\tBT\tCT\tTAT\tWT\tRT\n\n");

for (j = 1; j < n + 1; j++) {

    for (i = 0; i < n; i++) {

        if (pid[i] == j)

            printf("P%d\t%d\t%d\t%d\t%d\t%d\t%d\n", pid[i], at[i], bt[i],
ct[i],

                    tat[i], wt[i], rt[i]);

    }

}

printf("\nAverage TAT: %.2f\n", (tat_sum / n));

printf("Average WT: %.2f\n", (wt_sum / n));

}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\SRTF.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter no. of processes: 4
Enter arrival time for process[1]: 0
Enter burst time for process[1]: 7
Enter arrival time for process[2]: 8
Enter burst time for process[2]: 3
Enter arrival time for process[3]: 3
Enter burst time for process[3]: 2
Enter arrival time for process[4]: 3
Enter burst time for process[4]: 6

P      AT      BT      CT      TAT      WT      RT
P1      0       7       9       9       2       0
P2      8       3      12       4       1       1
P3      3       2       5       2       0       0
P4      3       6      18      15       9       9

Average TAT: 7.50
Average WT: 3.00
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

2. Non-Preemptive:

```
#include<stdio.h>

#include<stdlib.h>

#define max(a,b) ((a>b)? (a):(b))

int main(){

    int a=4,b=6,temp,comp_count=0;

    int sjf[a][b];

    printf("Enter the Process, Arrival Time and Burst Time:\n");

    for(int i=0; i<a; i++){

        for(int j=0; j<3; j++){

            scanf("%d",&sjf[i][j]);

        }

    }

    for(int i=0; i<a-1; i++){

        for(int j=0; j<a-i-1; j++){

            if(sjf[j][1] > sjf[j+1][1]){

                for(int k=0; k<3; k++){

                    temp = sjf[j][k];

                    sjf[j][k] = sjf[j+1][k];

                    sjf[j+1][k] = temp;

                }

            }

        }

    }

    int curr_time =0, is_comp[4] = {0};
```

```

while(comp_count < a){

    int best_index = -1, min_burst = 9999;

    for(int i=0; i<a; i++){

        if(sjf[i][1] <= curr_time && is_comp[i] == 0){

            if(sjf[i][2] < min_burst) {

                min_burst = sjf[i][2];

                best_index = i;

            }

        }

    }

    if(best_index != -1){

        curr_time += sjf[best_index][2];

        sjf[best_index][3] = curr_time;

        sjf[best_index][4] = sjf[best_index][3] -
sjf[best_index][1];

        sjf[best_index][5] = sjf[best_index][4] -
sjf[best_index][2];

        is_comp[best_index] = 1;

        comp_count++;

    }

    else{

        curr_time++;

    }

}

printf("Process\tAT\tBT\tCT\tTAT\tWT\n");

```

```

for(int i=0; i<a; i++){
    for(int j=0; j<b; j++){
        printf("%d\t",sjf[i][j]);
    }
    printf("\n");
}

int sumTAT =0, sumWT=0;
for(int i=0; i<a; i++){
    sumTAT += sjf[i][4];
    sumWT += sjf[i][5];
}

printf("Average TAT: %2f", (float) sumTAT/a);
printf("Average WT: %2f", (float) sumWT/a);
}

```

Output:

```

● PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\SJF.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter the Process, Arrival Time and Burst Time:
1 0 7
2 8 3
3 3 4
4 5 6
Process AT      BT      CT      TAT      WT
1      0      7      7      7      0
3      3      4      11     8      4
4      5      6      20     15     9
2      8      3      14     6      3
Average TAT: 9.000000Average WT: 4.000000
○ PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

c). Priority (Preemptive and Non-Preemptive)

1. Preemptive:

```

#include <stdio.h>

int main() {
    int n, i, time = 0, completed = 0;
    int bt[20], at[20], pr[20], rt[20];
    int wt[20], tat[20], ct[20];
    int highest, min_pr;
    int total_wt = 0, total_tat = 0;
    printf("Enter number of processes: ");
    scanf("%d", &n);
    for(i = 0; i < n; i++) {
        printf("\nProcess %d\n", i + 1);
        printf("Enter Arrival Time: ");
        scanf("%d", &at[i]);
        printf("Enter Burst Time: ");
        scanf("%d", &bt[i]);
        printf("Enter Priority: ");
        scanf("%d", &pr[i]);
        rt[i] = bt[i];
    }
    while(completed < n) {
        highest = -1;
        min_pr = 9999;
        for(i = 0; i < n; i++) {
            if(at[i] <= time && rt[i] > 0 && pr[i] < min_pr) {
                min_pr = pr[i];
                highest = i;
            }
        }
        if(highest == -1) {

```

```

        time++;
        continue;
    }
    rt[highest]--;
    time++;
    if(rt[highest] == 0) {
        completed++;
        ct[highest] = time;
        tat[highest] = ct[highest] - at[highest];
        wt[highest] = tat[highest] - bt[highest];
        total_wt += wt[highest];
        total_tat += tat[highest];
    }
}

printf("\nPID\tAT\tBT\tPR\tCT\tWT\tTAT\n");
for(i = 0; i < n; i++) {
    printf("%d\t%d\t%d\t%d\t%d\t%d\t%d\n",
        i + 1, at[i], bt[i], pr[i], ct[i], wt[i], tat[i]);
}

printf("\nAverage Waiting Time = %.2f", (float)total_wt/n);
printf("\nAverage Turnaround Time = %.2f\n", (float)total_tat/n);
return 0;
}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\PriorityP.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of processes: 3

Process 1
Enter Arrival Time: 0
Enter Burst Time: 3
Enter Priority: 1

Process 2
Enter Arrival Time: 1
Enter Burst Time: 3
Enter Priority: 4

Process 3
Enter Arrival Time: 2
Enter Burst Time: 5
Enter Priority: 3

  PID    AT    BT    PR    CT    WT    TAT
  ---    --    --    --    --    --    ---
  1       0     3     1     3     0     3
  2       1     3     4    11     7    10
  3       2     5     3     8     1     6

Average Waiting Time = 2.67
Average Turnaround Time = 6.33
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

2. Non- Preemptive:

```

#include <stdio.h>

struct Process {
    int pid;
    int burst;
    int priority;
    int waiting;
    int turnaround;
    int completion;
};

int main() {
    int n, i, j;
    struct Process p[20], temp;

```

```

printf("Enter number of processes: ");
scanf("%d", &n);
for(i = 0; i < n; i++) {
    printf("\nProcess %d\n", i + 1);
    p[i].pid = i + 1;
    printf("Enter Burst Time: ");
    scanf("%d", &p[i].burst);
    printf("Enter Priority: ");
    scanf("%d", &p[i].priority);
}
for(i = 0; i < n - 1; i++) {
    for(j = i + 1; j < n; j++) {
        if(p[i].priority > p[j].priority) {
            temp = p[i];
            p[i] = p[j];
            p[j] = temp;
        }
    }
}
p[0].waiting = 0;
for(i = 1; i < n; i++) {
    p[i].waiting = 0;
    for(j = 0; j < i; j++) {
        p[i].waiting += p[j].burst;
    }
}
for(i = 0; i < n; i++) {
    p[i].turnaround = p[i].burst + p[i].waiting;
}

```



```

        p[i].completion = p[i].turnaround;
    }

    float total_wt = 0, total_tat = 0;
    printf("\nPID\tBT\tPR\tWT\tTAT\tCT\n");
    for(i = 0; i < n; i++) {
        printf("%d\t%d\t%d\t%d\t%d\t%d\n",
               p[i].pid, p[i].burst, p[i].priority, p[i].completion,
               p[i].waiting, p[i].turnaround);

        total_wt += p[i].waiting;
        total_tat += p[i].turnaround;
    }

    printf("\nAverage Waiting Time = %.2f", total_wt / n);
    printf("\nAverage Turnaround Time = %.2f\n", total_tat / n);

    return 0;
}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\PriorityNP.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of processes: 3

Process 1
Enter Burst Time: 3
Enter Priority: 1

Process 2
Enter Burst Time: 4
Enter Priority: 3

Process 3
Enter Burst Time: 4
Enter Priority: 5

PID    BT    PR    WT    TAT    CT
1       3     1     3     0     3
2       4     3     7     3     7
3       4     5    11     7    11

Average Waiting Time = 3.33
Average Turnaround Time = 7.00
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

d). Round Robin (Experiment with different quantum sizes for RR algorithm)

```
#include <stdio.h>

int main() {
    int n, tq;

    int pid[20], at[20], bt[20], rt[20];

    int wt[20] = {0}, tat[20] = {0}, ct[20];

    int queue[100];

    int front = 0, rear = 0;

    int visited[20] = {0};

    int current_time = 0, completed = 0;

    float total_wt = 0, total_tat = 0;

    printf("Enter number of processes: ");

    scanf("%d", &n);

    printf("Enter time quantum: ");

    scanf("%d", &tq);

    for(int i = 0; i < n; i++) {
        printf("\nProcess %d\n", i + 1);

        printf("Enter Process ID: ");

        scanf("%d", &pid[i]);

        printf("Enter Arrival Time: ");

        scanf("%d", &at[i]);

        printf("Enter Burst Time: ");

        scanf("%d", &bt[i]);

        rt[i] = bt[i];
    }

    while(completed < n) {
        for(int i = 0; i < n; i++) {
            if(at[i] <= current_time && visited[i] == 0) {
```

```

        queue[rear++] = i;
        visited[i] = 1;
    }
}

if(front == rear) {
    current_time++;
    continue;
}

int p = queue[front++];
if(rt[p] > tq) {
    current_time += tq;
    rt[p] -= tq;
    for(int i = 0; i < n; i++) {
        if(at[i] <= current_time && visited[i] == 0) {
            queue[rear++] = i;
            visited[i] = 1;
        }
    }
    queue[rear++] = p;
}

else {
    current_time += rt[p];
    ct[p] = current_time;
    tat[p] = ct[p] - at[p];
    wt[p] = tat[p] - bt[p];
    rt[p] = 0;
    completed++;
}
}

```

```

printf("\nPID\tAT\tBT\tCT\tWT\tTAT\n");

for(int i = 0; i < n; i++) {

    printf("%d\t%d\t%d\t%d\t%d\t%d\n", pid[i], at[i], bt[i], ct[i],
wt[i], tat[i]);

    total_wt += wt[i];

    total_tat += tat[i];

}

printf("\nAverage Waiting Time = %.2f", total_wt / n);

printf("\nAverage Turnaround Time = %.2f\n", total_tat / n);

return 0;

}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\RoundRobin.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of processes: 3
Enter time quantum: 2

Process 1
Enter Process ID: 1
Enter Arrival Time: 0
Enter Burst Time: 3

Process 2
Enter Process ID: 2
Enter Arrival Time: 3
Enter Burst Time: 4

Process 3
Enter Process ID: 3
Enter Arrival Time: 2
Enter Burst Time: 4

PID    AT    BT    CT    WT    TAT
1       0     3     5     2     5
2       3     4    11     4     8
3       2     4     9     3     7

Average Waiting Time = 3.00
Average Turnaround Time = 6.67
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

2. Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.

```
#include <stdio.h>
#include <string.h>
#define MAX 100
#define TQ 2
struct Process {
    char pid[10];
    int at, bt, rt, type;
    int ct, tat, wt;
    int done;
};
int main() {
    struct Process p[MAX];
    int n;
    printf("Enter number of processes: ");
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        printf("\nProcess %d\n", i + 1);
        printf("Enter PID: ");
        scanf("%s", p[i].pid);
        printf("Enter Arrival Time: ");
        scanf("%d", &p[i].at);
        printf("Enter Burst Time: ");
        scanf("%d", &p[i].bt);
        printf("Enter Type (1=System, 2=User): ");
```

```

        scanf("%d", &p[i].type);

        p[i].rt = p[i].bt;

        p[i].done = 0;
    }

    int time = 0, completed = 0;

    char ganttPID[MAX][10];

    int ganttTime[MAX];

    int gIndex = 0;

    int lastSysIndex = 0;

    while (completed < n) {

        int executed = 0;

        for (int i = 0; i < n; i++) {

            int idx = (lastSysIndex + i) % n;

            if (p[idx].type == 1 && p[idx].rt > 0 && p[idx].at <= time)
{

                ganttTime[gIndex] = time;

                strcpy(ganttPID[gIndex], p[idx].pid);

                gIndex++;

                if (p[idx].rt > TQ) {

                    time += TQ;

                    p[idx].rt -= TQ;

                } else {

                    time += p[idx].rt;

                    p[idx].rt = 0;

                    p[idx].ct = time;

                    p[idx].tat = p[idx].ct - p[idx].at;

                    p[idx].wt = p[idx].tat - p[idx].bt;

                    p[idx].done = 1;

                    completed++;

```

```

        }

        lastSysIndex = (idx + 1) % n;

        executed = 1;

        break;
    }
}

if (executed) continue;

int earliest = -1;

for (int i = 0; i < n; i++) {
    if (p[i].type == 2 && p[i].rt > 0 && p[i].at <= time) {
        if (earliest == -1 || p[i].at < p[earliest].at) {
            earliest = i;
        }
    }
}

if (earliest != -1) {
    ganttTime[gIndex] = time;

    strcpy(ganttPID[gIndex], p[earliest].pid);

    gIndex++;

    int nextSysArrival = 1e9;

    for (int i = 0; i < n; i++) {
        if (p[i].type == 1 && p[i].rt > 0 && p[i].at > time) {
            if (p[i].at < nextSysArrival)
                nextSysArrival = p[i].at;
        }
    }

    if (time + p[earliest].rt <= nextSysArrival) {
        time += p[earliest].rt;

        p[earliest].rt = 0;
    }
}

```

```

        p[earliest].ct = time;
        p[earliest].tat = p[earliest].ct - p[earliest].at;
        p[earliest].wt = p[earliest].tat - p[earliest].bt;
        p[earliest].done = 1;
        completed++;
    } else {
        int execTime = nextSysArrival - time;
        p[earliest].rt -= execTime;
        time = nextSysArrival;
    }
    continue;
}
time++;
}

gantTime[gIndex] = time;
printf("\n===== MULTI-LEVEL QUEUE SCHEDULING =====\n");
printf("+-----+-----+-----+-----+-----+-----+-----+-----\n");
printf("| PID   | TYPE | AT | BT | CT | TAT | WT | \n");
printf("+-----+-----+-----+-----+-----+-----+-----+-----\n");
float total_tat = 0, total_wt = 0;
for (int i = 0; i < n; i++) {
    printf("| %-4s | %-4s | %-2d | %-2d | %-2d | %-3d | %-2d | \n",
        p[i].pid,
        p[i].type == 1 ? "SYS" : "USR",
        p[i].at,
        p[i].bt,
        p[i].ct,
        p[i].tat,

```



```

        p[i].wt);

    total_tat += p[i].tat;

    total_wt += p[i].wt;

}

printf("+-----+-----+----+----+----+-----+----+\n");

printf("\nAverage Turnaround Time = %.2f\n", total_tat / n);

printf("Average Waiting Time      = %.2f\n", total_wt / n);

printf("\n===== GANTT CHART =====\n\n");

for (int i = 0; i < gIndex; i++) {

    printf("| %s ", ganttPID[i]);

}

printf("|\n");

for (int i = 0; i < gIndex; i++) {

    printf("+----");

}

printf("+\n");

for (int i = 0; i <= gIndex; i++) {

    printf("%-4d", ganttTime[i]);

}

printf("\n");

return 0;

}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\MultiLevelQueue.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of processes: 4

Process 1
Enter PID: P1
Enter Arrival Time: 0
Enter Burst Time: 4
Enter Type (1=System, 2=User): 1

Process 2
Enter PID: P2
Enter Arrival Time: 0
Enter Burst Time: 3
Enter Type (1=System, 2=User): 1

Process 3
Enter PID: P3
Enter Arrival Time: 0
Enter Burst Time: 8
Enter Type (1=System, 2=User): 2

Process 4
Enter PID: P4
Enter Arrival Time: 10
Enter Burst Time: 8
Enter Type (1=System, 2=User): 1

===== MULTI-LEVEL QUEUE SCHEDULING =====
+-----+-----+-----+-----+-----+-----+
| PID | TYPE | AT | BT | CT | TAT | WT |
+-----+-----+-----+-----+-----+-----+
| P1 | SYS | 0 | 4 | 6 | 6 | 2 |
| P2 | SYS | 0 | 3 | 7 | 7 | 4 |
| P3 | USR | 0 | 8 | 23 | 23 | 15 |
| P4 | SYS | 10 | 8 | 18 | 8 | 0 |
+-----+-----+-----+-----+-----+-----+

Average Turnaround Time = 11.00
Average Waiting Time = 5.25

```

```

===== GANTT CHART =====

| P1 | P2 | P1 | P2 | P3 | P4 | P4 | P4 | P4 | P3 |
+---+---+---+---+---+---+---+---+---+---+
0   2   4   6   7   10  12  14  16  18  23
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> █

```

3. Write a C program to simulate Real-Time CPU Scheduling algorithms:

- a) Rate- Monotonic
- b) Earliest-deadline First
- c) Proportional scheduling

a). RMS:

```
#include <stdio.h>
#include <math.h>
int gcd(int a, int b) {
    if (b == 0)
        return a;
    return gcd(b, a % b);
}
int lcm(int a, int b) {
    return (a * b) / gcd(a, b);
}
int main() {
    int n;
    printf("Enter number of processes: ");
    scanf("%d", &n);
    int Ci[n], Ti[n], remaining[n], original_id[n];
    for (int i = 0; i < n; i++) {
        printf("Enter execution time (C%d): ", i + 1);
        scanf("%d", &Ci[i]);
        printf("Enter period (T%d): ", i + 1);
        scanf("%d", &Ti[i]);
        remaining[i] = 0;
        original_id[i] = i + 1;
    }
    double U = 0;
    for (int i = 0; i < n; i++) {
        U += (double)Ci[i] / Ti[i];
    }
    double U_bound = n * (pow(2, (double)1/n) - 1);
    printf("\nCPU Utilization (U) = %.4f\n", U);
    printf("Utilization Bound (U_bound) = %.4f\n", U_bound);
    if (U > U_bound) {
        printf("Not Schedulable under RMS\n");
    }
}
```

```

        return 0;
    }
    printf("Schedulable under RMS\n");
    int hyperperiod = Ti[0];
    for (int i = 1; i < n; i++) {
        hyperperiod = lcm(hyperperiod, Ti[i]);
    }
    printf("\nLCM (Hyperperiod) = %d\n", hyperperiod);
    for (int i = 0; i < n - 1; i++) {
        for (int j = i + 1; j < n; j++) {
            if (Ti[i] > Ti[j]) {
                int temp;
                temp = Ti[i]; Ti[i] = Ti[j]; Ti[j] = temp;
                temp = Ci[i]; Ci[i] = Ci[j]; Ci[j] = temp;
                temp = original_id[i]; original_id[i] = original_id[j];
original_id[j] = temp;
            }
        }
    }
    printf("\nRMS Table:\n");
    printf("Process\tExecution Time\tPeriod\n");
    for (int i = 0; i < n; i++) {
        printf("P%d\t%d\t%d\n", original_id[i], Ci[i], Ti[i]);
    }
    int schedule[hyperperiod];
    for (int t = 0; t < hyperperiod; t++) {

        for (int i = 0; i < n; i++) {
            if (t % Ti[i] == 0) {
                remaining[i] = Ci[i];
            }
        }
        int selected = -1;
        for (int i = 0; i < n; i++) {
            if (remaining[i] > 0) {
                selected = i;
                break;
            }
        }
    }
}

```

```

        if (selected != -1) {
            schedule[t] = original_id[selected];
            remaining[selected]--;
        } else {
            schedule[t] = 0;
        }
    }
    printf("\nTimeline (Intervals):\n");
    int start = 0;
    for (int t = 1; t <= hyperperiod; t++) {
        if (t == hyperperiod || schedule[t] != schedule[start]) {
            if (schedule[start] == 0)
                printf("Time %d to %d: Idle\n", start, t);
            else
                printf("Time %d to %d: P%d\n", start, t,
schedule[start]);
            start = t;
        }
    }
    return 0;
}

```

Output:

```

● PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\RMS.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of processes: 2
Enter execution time (C1): 20
Enter period (T1): 50
Enter execution time (C2): 35
Enter period (T2): 100

CPU Utilization (U) = 0.7500
Utilization Bound (U_bound) = 0.8284
Schedulable under RMS

LCM (Hyperperiod) = 100

RMS Table:
Process Execution Time Period
P1      20             50
P2      35            100

Timeline (Intervals):
Time 0 to 20: P1
Time 20 to 50: P2
Time 50 to 70: P1
Time 70 to 75: P2
Time 75 to 100: Idle
○ PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

b). EDF:

```
#include <stdio.h>
#define MAX 10
int main() {
    int n;
    int burst[MAX], deadline[MAX], period[MAX];
    int remaining[MAX];
    int time = 0;
    printf("Enter number of tasks: ");
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        printf("Task %d (burst deadline period): ", i + 1);
        scanf("%d %d %d", &burst[i], &deadline[i], &period[i]);
        remaining[i] = 0; // initially no job released
    }
    printf("\nPID\tBurst\tDeadline\tPeriod\n");
    for (int i = 0; i < n; i++) {
        printf("%d\t%d\t%d\t%d\n", i + 1, burst[i], deadline[i],
period[i]);
    }
    int limit = 20;
    printf("\nScheduling occurs for %d ms\n\n", limit);

    while (time < limit) {
        for (int i = 0; i < n; i++) {
            if (time % period[i] == 0) {
                remaining[i] = burst[i];
            }
        }
        int min_deadline = 9999;
        int selected = -1;
        for (int i = 0; i < n; i++) {
            if (remaining[i] > 0) {
                if (deadline[i] < min_deadline) {
                    min_deadline = deadline[i];
                    selected = i;
                }
            }
        }
    }
}
```

```

        if (selected == -1) {
            printf("%dms : CPU is idle.\n", time);
        } else {
            printf("%dms : Task %d is running.\n", time, selected + 1);
            remaining[selected]--;
        }
        time++;
    }
    return 0;
}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\EDF.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of tasks: 3
Task 1 (burst deadline period): 3 7 20
Task 2 (burst deadline period): 2 4 5
Task 3 (burst deadline period): 2 8 10

PID    Burst  Deadline  Period
1       3      7         20
2       2      4          5
3       2      8         10

Scheduling occurs for 20 ms

0ms : Task 2 is running.
1ms : Task 2 is running.
2ms : Task 1 is running.
3ms : Task 1 is running.
4ms : Task 1 is running.
5ms : Task 2 is running.
6ms : Task 2 is running.
7ms : Task 3 is running.
8ms : Task 3 is running.
9ms : CPU is idle.
10ms : Task 2 is running.
11ms : Task 2 is running.
12ms : Task 3 is running.
13ms : Task 3 is running.
14ms : CPU is idle.
15ms : Task 2 is running.
16ms : Task 2 is running.
17ms : CPU is idle.
18ms : CPU is idle.
19ms : CPU is idle.
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

c). Proportional Share:

```
#include<stdio.h>
#include <stdlib.h>
#include <time.h>
typedef struct
{
    char name[5]; int tickets;
}
Process;
int main() {
    int n, total_tickets = 0; float total_T =0.0;
    printf("Enter the number of Processes: ");
    scanf("%d", &n);
    Process p[n];
    srand(time(NULL));
    for (int i = 0; i < n; i++)
    {
        printf("\nProcess %d:\n", i + 1);
        sprintf(p[i].name, "P%d", i + 1);
        printf("Tickets: ");
        scanf("%d", &p[i].tickets);
        total_tickets += p[i].tickets;
        total_T +=p[i].tickets;
    }
    printf("\n--- Proportional Share Scheduling ---\n");
    printf("Enter the Time Period for scheduling: ");
    int m;

    scanf("%d",&m);
    for (int i = 0; i < m; i++)
    {
        int winning_ticket = rand() % total_tickets + 1;
        int accumulated_tickets = 0;
        int winner_index;
        for (int j = 0; j < n; j++)
        {
            accumulated_tickets += p[j].tickets;
            if (winning_ticket <= accumulated_tickets)
            {
```



```

        winner_index = j; break;
    }
}
printf("Tickets picked: %d, Winner: %s\n", winning_ticket,
p[winner_index].name);
}
for (int i = 0; i < n; i++)
{
    printf("\nThe Process: %s gets %0.2f%% of Processor Time.\n",
p[i].name,
        ((p[i].tickets / total_T) * 100));

}
return 0;
}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\PropotionalShare.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter the number of Processes: 3

Process 1:
Tickets: 10

Process 2:
Tickets: 20

Process 3:
Tickets: 30

--- Proportional Share Scheduling ---
Enter the Time Period for scheduling: 5
Tickets picked: 21, Winner: P2
Tickets picked: 59, Winner: P3
Tickets picked: 45, Winner: P3
Tickets picked: 37, Winner: P3
Tickets picked: 1, Winner: P1

The Process: P1 gets 16.67% of Processor Time.

The Process: P2 gets 33.33% of Processor Time.

The Process: P3 gets 50.00% of Processor Time.
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

4. Write a C program to simulate:

- a) Producer-Consumer problem using semaphores.
- b) Dining-Philosopher's problem

a). Producer-Consumer problem using semaphores.

```
#include <stdio.h>
#include <pthread.h>
#include <unistd.h>
#include <semaphore.h>

#define BUFFER_SIZE 5

int buffer[BUFFER_SIZE];
int in = 0, out = 0;

sem_t empty;
sem_t full;
pthread_mutex_t mutex;

void* producer(void* arg) {
    int item, i = 0;
    while (1) {
        item = i++;
        sem_wait(&empty);
        pthread_mutex_lock(&mutex);
        buffer[in] = item;
        printf("Produced: %d at buffer[%d]\n", item, in);
        in = (in + 1) % BUFFER_SIZE;
        pthread_mutex_unlock(&mutex);
        sem_post(&full);
        sleep(1);
    }
}

void* consumer(void* arg) {
```

```

    int item;

    while (1) {

        sem_wait(&full);

        pthread_mutex_lock(&mutex);

        item = buffer[out];

        printf("Consumed: %d from buffer[%d]\n", item, out);

        out = (out + 1) % BUFFER_SIZE;

        pthread_mutex_unlock(&mutex);

        sem_post(&empty);

        sleep(2);

    }
}

int main() {

    pthread_t prod, cons;

    sem_init(&empty, 0, BUFFER_SIZE);

    sem_init(&full, 0, 0);

    pthread_mutex_init(&mutex, NULL);

    pthread_create(&prod, NULL, producer, NULL);

    pthread_create(&cons, NULL, consumer, NULL);

    pthread_join(prod, NULL);

    pthread_join(cons, NULL);

    sem_destroy(&empty);

    sem_destroy(&full);

    pthread_mutex_destroy(&mutex);

    return 0;

}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\ProdConsSemp.exe"
Name: Parv Jain || USN: 1WA24CS205
Produced: 0 at buffer[0]
Consumed: 0 from buffer[0]
Produced: 1 at buffer[1]
Consumed: 1 from buffer[1]
Produced: 2 at buffer[2]
Produced: 3 at buffer[3]
Consumed: 2 from buffer[2]
Produced: 4 at buffer[4]
Produced: 5 at buffer[0]
Consumed: 3 from buffer[3]
Produced: 6 at buffer[1]
Produced: 7 at buffer[2]
Consumed: 4 from buffer[4]
Produced: 8 at buffer[3]
Produced: 9 at buffer[4]
Consumed: 5 from buffer[0]
Produced: 10 at buffer[0]

```

b) Dining-Philosopher's problem

```

#include <stdio.h>
#include <pthread.h>
#include <unistd.h>
#define N 5
pthread_mutex_t forks[N];
pthread_t philosophers[N];
void* philosopher(void* num) {
    int id = *(int*)num;
    int left = id;
    int right = (id + 1) % N;
    while (1) {
        printf("Philosopher %d is thinking.\n", id);
        if (id % 2 == 0) {
            pthread_mutex_lock(&forks[left]);
            printf("Philosopher %d picked up left fork %d.\n", id,
left);
            pthread_mutex_lock(&forks[right]);
            printf("Philosopher %d picked up right fork %d.\n", id,
right);
        } else {
            pthread_mutex_lock(&forks[right]);
            printf("Philosopher %d picked up right fork %d.\n", id,
right);
            pthread_mutex_lock(&forks[left]);

```

```

        printf("Philosopher %d picked up left fork %d.\n", id,
left);
    }
    printf("Philosopher %d is eating.\n", id);
    sleep(2);
    pthread_mutex_unlock(&forks[left]);
    pthread_mutex_unlock(&forks[right]);
    printf("Philosopher %d put down forks %d and %d.\n", id, left,
right);
}
}
int main() {
    int i;
    int ids[N];
    for (i = 0; i < N; i++) {
        pthread_mutex_init(&forks[i], NULL);
        ids[i] = i;
    }
    for (i = 0; i < N; i++) {
        pthread_create(&philosophers[i], NULL, philosopher, &ids[i]);
    }
    for (i = 0; i < N; i++) {
        pthread_join(philosophers[i], NULL);
    }
    for (i = 0; i < N; i++) {
        pthread_mutex_destroy(&forks[i]);
    }
    return 0;
}

```

Output:

```
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\DiningPhil.exe"
Name: Parv Jain || USN: 1WA24CS205
Philosopher 0 is thinking.
Philosopher 1 is thinking.
Philosopher 4 is thinking.
Philosopher 2 is thinking.
Philosopher 3 is thinking.
Philosopher 4 picked up left fork 4.
Philosopher 2 picked up left fork 2.
Philosopher 2 picked up right fork 3.
Philosopher 2 is eating.
Philosopher 0 picked up left fork 0.
Philosopher 0 picked up right fork 1.
Philosopher 0 is eating.
Philosopher 4 picked up right fork 0.
Philosopher 4 is eating.
Philosopher 2 put down forks 2 and 3.
Philosopher 2 is thinking.
Philosopher 0 put down forks 0 and 1.
Philosopher 0 is thinking.
Philosopher 1 picked up right fork 2.
Philosopher 1 picked up left fork 1.
Philosopher 1 is eating.
Philosopher 1 put down forks 1 and 2.
Philosopher 1 is thinking.
Philosopher 3 picked up right fork 4.
Philosopher 3 picked up left fork 3.
Philosopher 3 is eating.
Philosopher 0 picked up left fork 0.
Philosopher 0 picked up right fork 1.
Philosopher 0 is eating.
Philosopher 4 put down forks 4 and 0.
Philosopher 4 is thinking.
```

5. Write a C program to simulate:

- a) Bankers' algorithm for the purpose of deadlock avoidance.
- b) Deadlock Detection

a). Bankers' algorithm for the purpose of deadlock avoidance.

```
#include <stdio.h>
int main() {
    int n, r;
    printf("Enter number of processes: ");
    scanf("%d", &n);
    printf("Enter number of resources: ");
    scanf("%d", &r);
    int alloc[n][r], max[n][r], avail[r], need[n][r], safeSeq[n];
    int finish[n];
    printf("Enter Allocation Matrix:\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < r; j++) {
            scanf("%d", &alloc[i][j]);
        }
    }
    printf("Enter Maximum Demand Matrix:\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < r; j++) {
            scanf("%d", &max[i][j]);
            need[i][j] = max[i][j] - alloc[i][j];
        }
    }
    printf("Enter Available Resources:\n");
    for (int i = 0; i < r; i++) {
        scanf("%d", &avail[i]);
    }
    for (int i = 0; i < n; i++) {
        finish[i] = 0;
    }
    int count = 0;
    while (count < n) {
        int found = 0;
        for (int p = 0; p < n; p++) {
```

```

        if (finish[p] == 0) {
            int j;
            for (j = 0; j < r; j++) {
                if (need[p][j] > avail[j])
                    break;
            }
            if (j == r) {
                for (int k = 0; k < r; k++) {
                    avail[k] += alloc[p][k];
                }
                safeSeq[count++] = p;
                finish[p] = 1;
                found = 1;
            }
        }
    }
    if (found == 0) {
        printf("\nSystem is not in a safe state.");
        return 0;
    }
}

printf("\nSystem is in a safe state.\n");
printf("Safe sequence is: ");
for (int i = 0; i < n; i++) {
    printf("P%d", safeSeq[i]);
    if (i != n - 1) printf(" -> ");
}
printf("\n");
return 0;
}

```

Output:


```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\Bankers.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of processes: 5
Enter number of resources: 3
Enter Allocation Matrix:
0 1 0
2 0 0
3 0 2
2 1 1
0 0 2
Enter Maximum Demand Matrix:
7 5 3
3 2 2
3 0 2
2 2 2
4 3 3
Enter Available Resources:
3 3 2

System is in a safe state.
Safe sequence is: P1 -> P2 -> P3 -> P4 -> P0
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

b). Deadlock Detection

```

#include <stdio.h>
int main() {
    int n, r;
    printf("Enter the number of processes: ");
    scanf("%d", &n);
    printf("Enter the number of resources: ");
    scanf("%d", &r);
    int alloc[n][r], request[n][r], avail[r], safeSeq[n];
    int finish[n];
    printf("Enter the allocation matrix:\n");
    for (int i = 0; i < n; i++) {
        printf("Process %d: ", i);
        for (int j = 0; j < r; j++) {
            scanf("%d", &alloc[i][j]);
        }
    }
    printf("Enter the request matrix:\n");
    for (int i = 0; i < n; i++) {
        printf("Process %d: ", i);
        for (int j = 0; j < r; j++) {
            scanf("%d", &request[i][j]);
        }
    }
}

```

```

    }
    printf("Enter the available resources: ");
    for (int i = 0; i < r; i++) {
        scanf("%d", &avail[i]);
    }
    for (int i = 0; i < n; i++) {
        finish[i] = 0;
    }
    int count = 0;
    while (count < n) {
        int found = 0;
        for (int p = 0; p < n; p++) {
            if (finish[p] == 0) {
                int j;
                for (j = 0; j < r; j++) {
                    if (request[p][j] > avail[j])
                        break;
                }
                if (j == r) {
                    for (int k = 0; k < r; k++) {
                        avail[k] += alloc[p][k];
                    }
                    safeSeq[count++] = p;
                    finish[p] = 1;
                    found = 1;
                }
            }
        }
        if (found == 0) {
            printf("\nSystem is not in a safe state.\n");
            return 0;
        }
    }
    printf("System is in safe state.\n");
    printf("Safe Sequence is: ");
    for (int i = 0; i < n; i++) {
        printf("P%d", safeSeq[i]);
        if (i != n - 1) printf(" ");
    }
}

```

```
    printf("\n");  
    return 0;  
}
```

Output:

```
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\DeadlockDetection.exe"  
Name: Parv Jain || USN: 1WA24CS205  
Enter the number of processes: 5  
Enter the number of resources: 3  
Enter the allocation matrix:  
Process 0: 0 1 0  
Process 1: 2 0 0  
Process 2: 3 0 3  
Process 3: 2 1 1  
Process 4: 0 0 2  
Enter the request matrix:  
Process 0: 0 0 0  
Process 1: 2 0 2  
Process 2: 0 0 0  
Process 3: 1 0 0  
Process 4: 0 0 2  
Enter the available resources: 0 0 0  
System is in safe state.  
Safe Sequence is: P0 P2 P3 P4 P1  
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>
```

6. Write a C program to simulate the following contiguous memory allocation techniques.

a) Worst-fit b) Best-fit c) First-fit

```
#include <stdio.h>
#define MAX 20
void firstFit(int blocks[], int m, int processes[], int n) {
    int allocation[MAX], occupied[MAX];
    for (int i = 0; i < n; i++) allocation[i] = -1;
    for (int i = 0; i < m; i++) occupied[i] = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            if (!occupied[j] && blocks[j] >= processes[i]) {
                allocation[i] = j;
                occupied[j] = 1;
                break;
            }
        }
    }
    printf("\n--- First Fit ---\n");
    printf("Process No.   Process Size   Block No.\n");
    for (int i = 0; i < n; i++) {
        printf("%d \t\t %d \t\t ", i + 1, processes[i]);
        if (allocation[i] != -1)
            printf("%d\n", allocation[i] + 1);
        else
            printf("Not Allocated\n");
    }
}

void bestFit(int blocks[], int m, int processes[], int n) {
    int allocation[MAX], occupied[MAX];
    for (int i = 0; i < n; i++) allocation[i] = -1;
    for (int i = 0; i < m; i++) occupied[i] = 0;
    for (int i = 0; i < n; i++) {
        int bestIdx = -1;
        for (int j = 0; j < m; j++) {
            if (!occupied[j] && blocks[j] >= processes[i]) {
                if (bestIdx == -1 || blocks[j] < blocks[bestIdx]) {
                    bestIdx = j;
                }
            }
        }
    }
}
```

```

    }
}
if (bestIdx != -1) {
    allocation[i] = bestIdx;
    occupied[bestIdx] = 1;
}
}
printf("\n--- Best Fit ---\n");
printf("Process No.   Process Size   Block No.\n");
for (int i = 0; i < n; i++) {
    printf("%d \t\t %d \t\t ", i + 1, processes[i]);
    if (allocation[i] != -1)
        printf("%d\n", allocation[i] + 1);
    else
        printf("Not Allocated\n");
}
}
void worstFit(int blocks[], int m, int processes[], int n) {
    int allocation[MAX], occupied[MAX];
    for (int i = 0; i < n; i++) allocation[i] = -1;
    for (int i = 0; i < m; i++) occupied[i] = 0;
    for (int i = 0; i < n; i++) {
        int worstIdx = -1;
        for (int j = 0; j < m; j++) {
            if (!occupied[j] && blocks[j] >= processes[i]) {
                if (worstIdx == -1 || blocks[j] > blocks[worstIdx]) {
                    worstIdx = j;
                }
            }
        }
        if (worstIdx != -1) {
            allocation[i] = worstIdx;
            occupied[worstIdx] = 1;
        }
    }
    printf("\n--- Worst Fit ---\n");
    printf("Process No.   Process Size   Block No.\n");
    for (int i = 0; i < n; i++) {
        printf("%d \t\t %d \t\t ", i + 1, processes[i]);

```

```

        if (allocation[i] != -1)
            printf("%d\n", allocation[i] + 1);
        else
            printf("Not Allocated\n");
    }
}

int main() {
    int m, n;
    int blocks[MAX], processes[MAX];
    printf("Enter number of memory blocks: ");
    scanf("%d", &m);
    printf("Enter sizes of %d memory blocks:\n", m);
    for (int i = 0; i < m; i++) scanf("%d", &blocks[i]);
    printf("Enter number of processes: ");
    scanf("%d", &n);
    printf("Enter sizes of %d processes:\n", n);
    for (int i = 0; i < n; i++) scanf("%d", &processes[i]);
    firstFit(blocks, m, processes, n);
    bestFit(blocks, m, processes, n);
    worstFit(blocks, m, processes, n);
    return 0;
}

```

Output:

```

PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\FirstBestWorstFit.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of memory blocks: 5
Enter sizes of 5 memory blocks:
100 500 200 300 600
Enter number of processes: 4
Enter sizes of 4 processes:
212 417 112 426

--- First Fit ---
Process No.  Process Size  Block No.
1             212          2
2             417          5
3             112          3
4             426          Not Allocated

--- Best Fit ---
Process No.  Process Size  Block No.
1             212          4
2             417          2
3             112          3
4             426          5

--- Worst Fit ---
Process No.  Process Size  Block No.
1             212          5
2             417          2
3             112          4
4             426          Not Allocated
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab>

```

7. Write a C program to simulate page replacement algorithms.

a) FIFO

b) LRU

c) Optimal

```
#include <stdio.h>
#include <stdbool.h>
void print_frames(int frames[], int count) {
    printf("[");
    for (int i = 0; i < count; i++) {
        printf("%d", frames[i]);
        if (i < count - 1) {
            printf(" ");
        }
    }
    printf("]\n");
}

void fifo(int pages[], int n, int f) {
    printf("\n--- FIFO Page Replacement ---\n");
    int frames[f];
    int count = 0;
    int next = 0;
    int faults = 0;
    for (int i = 0; i < n; i++) {
        int p = pages[i];
        bool hit = false;
        for (int j = 0; j < count; j++) {
            if (frames[j] == p) {
                hit = true;
                break;
            }
        }
        if (!hit) {
            if (count < f) {
                frames[count++] = p;
            } else {
                frames[next] = p;
                next = (next + 1) % f;
            }
        }
    }
}
```

```

        faults++;
    }
    printf("Page %d -> ", p);
    print_frames(frames, count);
}
printf("Total Page Faults (FIFO): %d\n", faults);
}

void lru(int pages[], int n, int f) {
    printf("\n--- LRU Page Replacement ---\n");
    int frames[f];
    int count = 0;
    int faults = 0;
    for (int i = 0; i < n; i++) {
        int p = pages[i];
        int hit_index = -1;
        for (int j = 0; j < count; j++) {
            if (frames[j] == p) {
                hit_index = j;
                break;
            }
        }
        if (hit_index != -1) {
            int val = frames[hit_index];
            for (int j = hit_index; j < count - 1; j++) {
                frames[j] = frames[j + 1];
            }
            frames[count - 1] = val;
        } else {
            if (count < f) {
                frames[count++] = p;
            } else {
                for (int j = 0; j < f - 1; j++) {
                    frames[j] = frames[j + 1];
                }
                frames[f - 1] = p;
            }
            faults++;
        }
        printf("Page %d -> ", p);
    }
}

```



```

        print_frames(frames, count);
    }
    printf("Total Page Faults (LRU): %d\n", faults);
}

void optimal(int pages[], int n, int f) {
    printf("\n--- Optimal Page Replacement ---\n");
    int frames[f];
    int count = 0;
    int faults = 0;
    for (int i = 0; i < n; i++) {
        int p = pages[i];
        bool hit = false;
        for (int j = 0; j < count; j++) {
            if (frames[j] == p) {
                hit = true;
                break;
            }
        }
        if (!hit) {
            if (count < f) {
                frames[count++] = p;
            } else {
                int farthest = -1;
                int replace_idx = -1;
                for (int j = 0; j < f; j++) {
                    int next_use = -1;
                    for (int k = i + 1; k < n; k++) {
                        if (frames[j] == pages[k]) {
                            next_use = k;
                            break;
                        }
                    }
                    if (next_use == -1) {
                        replace_idx = j;
                        break;
                    }
                    if (next_use > farthest) {
                        farthest = next_use;
                        replace_idx = j;
                    }
                }
            }
        }
    }
}

```

```

        }
    }
    frames[replace_idx] = p;
}
faults++;
}
printf("Page %d -> ", p);
print_frames(frames, count);
}
printf("Total Page Faults (Optimal): %d\n", faults);
}
int main() {
    int n, f;
    printf("Enter number of pages: ");
    scanf("%d", &n);
    int pages[n];
    printf("Enter page reference string:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &pages[i]);
    }
    printf("Enter number of frames: ");
    scanf("%d", &f);
    fifo(pages, n, f);
    lru(pages, n, f);
    optimal(pages, n, f);
    return 0;
}

```

Output:

```
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> & "C:\Users\Parv Jain\OneDrive\Desktop\OS Lab\PageReplacement.exe"
Name: Parv Jain || USN: 1WA24CS205
Enter number of pages: 12
Enter page reference string:
7 0 1 2 0 3 0 4 2 3 0 3
Enter number of frames: 3
```

```
--- FIFO Page Replacement ---
```

```
Page 7 -> [7]
Page 0 -> [7 0]
Page 1 -> [7 0 1]
Page 2 -> [2 0 1]
Page 0 -> [2 0 1]
Page 3 -> [2 3 1]
Page 0 -> [2 3 0]
Page 4 -> [4 3 0]
Page 2 -> [4 2 0]
Page 3 -> [4 2 3]
Page 0 -> [0 2 3]
Page 3 -> [0 2 3]
Total Page Faults (FIFO): 10
```

```
--- LRU Page Replacement ---
```

```
Page 7 -> [7]
Page 0 -> [7 0]
Page 1 -> [7 0 1]
Page 2 -> [0 1 2]
Page 0 -> [1 2 0]
Page 3 -> [2 0 3]
Page 0 -> [2 3 0]
Page 4 -> [3 0 4]
Page 2 -> [0 4 2]
Page 3 -> [4 2 3]
Page 0 -> [2 3 0]
Page 3 -> [2 0 3]
Total Page Faults (LRU): 9
```

```
--- Optimal Page Replacement ---
```

```
Page 7 -> [7]
Page 0 -> [7 0]
Page 1 -> [7 0 1]
Page 2 -> [2 0 1]
Page 0 -> [2 0 1]
Page 3 -> [2 0 3]
Page 0 -> [2 0 3]
Page 4 -> [2 4 3]
Page 2 -> [2 4 3]
Page 3 -> [2 4 3]
Page 0 -> [0 4 3]
Page 3 -> [0 4 3]
Total Page Faults (Optimal): 7
```

```
PS C:\Users\Parv Jain\OneDrive\Desktop\OS Lab> █
```