

00:08

Predicate Logic in AI

1. Marcus was a man.
2. Marcus was a Pompeian.
3. All Pompeian were Romans.
4. Caesar was a ruler.
5. All Romans were either loyal to Caesar or hated him.
6. Everyone is loyal to someone.
7. People only try to assassinate rulers they are not loyal to.
8. Marcus tried to assassinate Caesar.

**Sentences as
Well formed
Formulas**

Like, Share and Subscribe to Mahesh Huddar

Visit: vtupulse.com

01:00

Sentences to Well formed Formulas in Predicate Logic

- | | |
|---------------------------|-----------------------|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |

01:31

Sentences to Well formed Formulas in Predicate Logic

- | | |
|------------------------------|---|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |
| 3. All Pompeian were Romans. | 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$ |

01:59

Sentences to Well formed Formulas in Predicate Logic

- | | |
|------------------------------|---|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |
| 3. All Pompeian were Romans. | 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$ |
| 4. Caesar was a ruler. | 4. $ruler(Caesar)$ |

02:50

Sentences to Well formed Formulas in Predicate Logic

- | | |
|---|---|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |
| 3. All Pompeian were Romans. | 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$ |
| 4. Caesar was a ruler. | 4. $ruler(Caesar)$ |
| 5. All Romans were either loyal to Caesar or hated him. | 5. $\forall x : Roman(x) \rightarrow loyalto(x, Caesar) \vee hate(x, Caesar)$ |

03:40

Sentences to Well formed Formulas in Predicate Logic

- | | |
|---|---|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |
| 3. All Pompeian were Romans. | 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$ |
| 4. Caesar was a ruler. | 4. $ruler(Caesar)$ |
| 5. All Romans were either loyal to Caesar or hated him. | 5. $\forall x : Roman(x) \rightarrow loyalto(x, Caesar) \vee hate(x, Caesar)$ |
| 6. Everyone is loyal to someone. | 6. $\forall x : \exists y : loyalto(x, y)$ |

04:32

Sentences to Well formed Formulas in Predicate Logic

- | | |
|---|---|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |
| 3. All Pompeian were Romans. | 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$ |
| 4. Caesar was a ruler. | 4. $ruler(Caesar)$ |
| 5. All Romans were either loyal to Caesar or hated him. | 5. $\forall x : Roman(x) \rightarrow loyalto(x, Caesar) \vee hate(x, Caesar)$ |
| 6. Everyone is loyal to someone. | 6. $\forall x : \exists y : loyalto(x, y)$ |
| 7. People only try to assassinate rulers they are not loyal to. | |

04:59

Sentences to Well formed Formulas in Predicate Logic

- | | |
|------------------------------|---|
| 1. Marcus was a man. | 1. $man(Marcus)$ |
| 2. Marcus was a Pompeian. | 2. $Pompeian(Marcus)$ |
| 3. All Pompeian were Romans. | 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$ |
| 4. Caesar was a ruler. | 4. $ruler(Caesar)$ |

5. All Romans were either loyal to Caesar or hated him. 5. $\forall x : Roman(x) \rightarrow loyalto(x, Caesar) \vee hate(x, Caesar)$
6. Everyone is loyal to someone. 6. $\forall x : \exists y : loyalto(x, y)$
7. People only try to assassinate rulers they are not loyal to.
7. $\forall x : \forall y : person(x) \wedge ruler(y) \wedge tryassassinate(x, y) \rightarrow \neg loyalto(x, y)$

05:49

Sentences to Well formed Formulas in Predicate Logic

1. Marcus was a man. 1. $man(Marcus)$
2. Marcus was a Pompeian. 2. $Pompeian(Marcus)$
3. All Pompeian were Romans. 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$
4. Caesar was a ruler. 4. $ruler(Caesar)$
5. All Romans were either loyal to Caesar or hated him. 5. $\forall x : Roman(x) \rightarrow loyalto(x, Caesar) \vee hate(x, Caesar)$
6. Everyone is loyal to someone. 6. $\forall x : \exists y : loyalto(x, y)$
7. People only try to assassinate rulers they are not loyal to.
7. $\forall x : \forall y : person(x) \wedge ruler(y) \wedge tryassassinate(x, y) \rightarrow \neg loyalto(x, y)$
8. Marcus tried to assassinate Caesar. 8. $tryassassinate(Marcus, Caesar)$
9. All men are people

06:16

Sentences to Well formed Formulas in Predicate Logic

1. Marcus was a man. 1. $man(Marcus)$
2. Marcus was a Pompeian. 2. $Pompeian(Marcus)$
3. All Pompeian were Romans. 3. $\forall x : Pompeian(x) \rightarrow Roman(x)$

4. Caesar was a ruler. 4. $ruler(Caesar)$
5. All Romans were either loyal to Caesar or hated him. 5. $\forall x : Roman(x) \rightarrow loyalto(x, Caesar) \vee hate(x, Caesar)$
6. Everyone is loyal to someone. 6. $\forall x : \exists y : loyalto(x, y)$
7. People only try to assassinate rulers they are not loyal to.
7. $\forall x : \forall y : person(x) \wedge ruler(y) \wedge tryassassinate(x, y) \rightarrow \neg loyalto(x, y)$
8. Marcus tried to assassinate Caesar. 8. $tryassassinate(Marcus, Caesar)$
9. All men are people 9. $\forall x : man(x) \rightarrow person(x)$

