

ALUCOTECH SYSTEMS — FW60-SG UNITIZED CURTAIN WALL SYSTEM

Manufacturer Technical Data Sheet — Structural Glazing Facade System

Submitted for: Makkah Hospitality Expansion — Al-Baraka Curtain Wall Systems Co.
Submittal Ref: ABK-MKH-CW-SUB-014 Rev 2

1. System Description

FW60-SG is a unitized, structurally-glazed aluminium curtain wall system designed for high-rise and hospitality applications in high-wind, high-solar-gain coastal environments. Mullion depth 60mm, thermal break polyamide strip construction.

2. Technical Performance Data

Property	Value	Test Standard
Air Infiltration	≤ 0.06 m3/h.m2 @ 600 Pa	ASTM E283
Water Penetration	No leakage @ 720 Pa	ASTM E331
Structural Wind Load	Design pressure ±3.0 kPa	ASTM E330
Thermal Transmittance (U-value)	1.6 W/m2K (double IGU)	EN ISO 12567-1
Glazing Type	6mm HS Low-E + 12mm Argon + 6mm HS Clear-	
Fire Rating (spandrel panel)	60 minutes integrity	BS 476 Part 22
Seismic Movement Capacity	±25mm inter-storey drift	AAMA 501.4
Finish	PVDF (Kynar 500), 3-coat, RAL 9006	AAMA 2605

3. Warranty

10-year system warranty against water infiltration and structural glazing failure; 20-year warranty on PVDF finish coating retention (chalking/fading), subject to manufacturer's maintenance schedule.

Manufacturer: Alucotech Systems B.V. — Authorized KSA Distributor: Al-Baraka Curtain Wall Systems Co.