

Add: A、E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com

E-mail: <u>bfn@bfnbatterycom</u>

NO.:GJW2017-0030

Material Safety Data Sheet 材料安全数据表

| 样品名 | 名 称: _ | 锂离子电池 | | |
|---|---------|---------------------|--|--|
| Name of S | Sample: | Lithium-ion Battery | | |
| 委 托 | 单 位: | 深圳市博富能鬼池有限公司 | | |
| Commissioner: SHENZHEN BOFUNENG BATTERY CO.,LTD | | | | |
| | | | | |



Add: A、E Building Chun yang Industrial park, Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China 86-755-84642975 Fax: +86-755-84642732

Tel: +86-755-84642975 http://www.bfnbattery.com E-mail: <u>bfn@bfnbatterycom</u>

材料安全数据表

Material Safety Data Sheet

| 1. 化学品及企业标识 Chemical product and company identification | | | | |
|--|---|---|--|--|
| 样品名称 Name of Sample | 锂离子电池 Lithium-ion Battery | | | |
| 样品型号 Type/Mode | 18650 2000mAh 3.7V 2000mAh 7.4Wh | | | |
| 委托单位 Commissioned by | 深圳市博富能电池有限公司 SHENZHEN BOFUNENG BATTERY CO.,I | LTD | | |
| 委托单位地址 Commissioner address | As E Building Chun yang Industrial park. Zhu gu shi Road Wu lian | | | |
| 生产单位 Manufacturer | 深圳市博富能电池有限公司 SHENZHEN BOFUNENG BATTERY CO.,I | LTD | | |
| 生产单位地址 Manufacturer address | 深圳市龙岗区龙城街道五联社区朱古石路春洋工业园AE栋 A、E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China | | | |
| 鉴定依据 Inspection according to | EEC Directive 93/112/EC 联合国《关于危险品货物运输的建议书》 UN "Recommendations on the TRANSPORT | OF DANGEROUS GOODS" | | |
| 应急电话 Emergency telephone | 0755-84642975 | | | |
| | 送样日期: 2017-03-03 Receiving date: 2017-03-03 | 签发日期: 2017-03-15 Date of issue :2017-03-15 | | |



Add: A、E Building Chun yang Industrial park, Zhu gu shi Road Wu lian community LongCheng Street, Longgang district, Shenzhen China
Tel: +86-755-84642975 Fax: +86-755-84642732

http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

| | 2. 成分组成信息 Composition informa | ition | |
|-------------------------------------|--|------------|-------------------|
| 材料及组分 | 化学式 | CAS 号 | 重量含量 |
| Chemical Name | Chemical Formula | CAS NO. | Wt% |
| 氧化锂钴 Lithium Cobalt Oxide | LiCoO ₂ | 12190-79-3 | 39.6 |
| 丁苯橡胶 SBR | (C8H8.C4H6)X | 9003-55-8 | 1.78 |
| (PE)聚乙烯 Polyethylene | (C ₂ H ₄)n | 9002-88-4 | 0.06 |
| 聚偏二氟乙烯 PVDF | (CH2CF2)n | 24937-79-9 | 1.15 |
| 石墨 Graphite | С | 7782-42-5 | 23.2 |
| 六氟磷酸锂 Lithium Hexafluorophoshate | LiPF ₆ | 21324-40-3 | 15.35 |
| 碳酸乙烯酯 Ethylene carbonate | C ₃ H ₄ O ₃ | 96-49-1 | 2.72 |
| 铜箔 Copper Foil | Cu | 7440-50-8 | 9.8 |
| 铝箔 Aluminum Foil | Al | 7429-90-5 | 5.56 |
| (PP)聚丙烯 Polypropylene | (C ₃ H ₆)n | 9003-07-0 | 0.78 |
| 铅 Lead | Pb | 7439-92-1 | 无 Not Detected |
| 镉 Cadmium | Cd | 7440-43-9 | 无 Not Detected |
| 汞 Mercury | Нд | 7439-97-6 | 无 Not Detected |

| 3.危险性概述 Hazards Identification | | |
|-----------------------------------|---|--|
| 爆炸危险性 | 该物品不属于爆炸危险品 | |
| Explosive Risk | This article does not belong to the explosion dangerous goods. | |
| 易燃危险性 | 该物品不属于易燃危险品 | |
| Flammable Risk | This article does not belong to the flammable material. | |
| 氧化危险性 | 该物品不属于氧化危险品 | |
| Oxidation Risk | This article does not belong to the oxidation of dangerous goods. | |



Add: A、E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

| 毒害危险性 | 该物品不属于毒害危险品 |
|------------------|---|
| Toxic Risk | This article does not belong to the toxic dangerous goods. |
| 放射危险性 | 该物品不属于放射性危险品 |
| Radioactive Risk | This article does not belong to the radiation of dangerous goods. |
| 腐蚀危险性 | 该物品不属于腐蚀危险品 |
| Mordant Risk | This article does not belong to the corrosion of dangerous goods. |
| | 该物品为锂离子电池,瓦时率 7.4Wh,属于锂离子电池(包括锂聚 |
| 其他危险性 | 合物电池) |
| Other Risk | This article is Li-ion Battery, Watt hour rate 7.4Wh, Which belong to |
| | the Lithium ion batteries (including lithium polymer batteries) |

4. 急救措施 First aid measures

眼睛:万一接触,立即用大量的清水冲洗至少 15 分钟,泛起上下眼脸。直到化学的残留物消失为止,迅速就医。

Eye: Flush eyes with plenty of water for at least 15 minutes,occasionally lifting the upper and lower eyelids. Get medical aid.

皮肤: 万一接触,用大量水冲洗至少 15 分钟,同时除去污染的衣物和鞋子,迅速就医。

Skin: Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes.Get medical aid .

吸入: 立即从暴露处移至空气清新处,如果呼吸困难给及输氧,立即就医。

Inhalation: Remove from exposure and move to fresh air immediately. Use oxygen if available.

食入: 饮用两杯牛奶或水。如果当事人仍然清醒可以采取催吐的方法,并且立即就医。

Ingestion: Give at least 2 glasses of milk or water .Induce vomiting unless patient is unconscious. Call a physician .

5. 消防措施 Fire-fighting measures

燃点:不适用 Flash Point: N/A 自燃温度:不适用

Anto-Ignition Temperature: N/A

灭火介质:大量水(降温),二氧化碳 Extinguishing Media: Water .CO₂ 特殊灭火程序: 自给式呼吸器

Special Fire-Fighting Procedures: Self-contained breathing apparatus. 异常火灾或爆炸: 当电芯暴露于过热的环境中时,安全阀可能会打开。

Unusual Fire and Explosion Hazards:



Add: A、E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

Cell may vent when subjected to excessive heat-exposing battery contents .

燃烧产生的危险物品:一氧化碳,二氧化碳,锂氧化物烟气

Hazardous Combustion Products:

Carbon monoxide. Carbon dioxide, lithium oxide fumes .

6. 泄露应急处理

Accidental release measures

为防止电池材料泄露或释放采取的措施

如果电池内部材料泄露,实验人员应立刻撤离试验区直到烟气消散。将通风设备打开吹散危险性气体。用抹布擦净试验区,清除溢出的液体,将泄露电池放进塑料袋中,然后放进钢制容器。避免皮肤和眼睛接触或吸入有害气体。

Steps to be taken in case Material is Released or Spilled

If the battery material is released , remove the personnel form area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can . The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate .

废弃物处置方法

建议将电池完全放电,消耗电池内部的锂金属,并且深埋于土壤中。

Waste Disposal Method

It is recommended to discharge the battery to the end ,to use up the metal lithium inside the battery, and to bury the discharged battery in soil .

7. 操作处置和储存

Handing and Storage

禁止打开、毁坏活焚烧电池,因为电池有可能在这些处理过程中发生爆炸、破裂或者泄露等事故。禁止将电池短路、过充、强制放电或扔入火中。禁止挤压刺穿电池或将电池浸入溶液中。

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

操作处置和储存中的防范措施

禁止物理或电滥用,禁止高温储存,最好将电池储存在阴凉、干燥、通风及温度变化较小的环境中,禁止将电池接触加热设备或电池直接暴露与阳光中。

Precautions to be taken in handing and storing.

Avoid mechanical or electrical abuse. Storage preferably in cool ,dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment , nor expose to direct sunlight for long periods .



Add: A、E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

其他要注意的防范措施

拆解、挤压、直接放入火中或高温条件下,电池可能发生爆炸和燃烧。禁止短接或电池正负极 错误的安装在设备中。

Other Precautions

The battery may explode or cause bums, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. 接触控制/个人防护

Exposure controls/personal protection

呼吸防护:

当电池排气阀打开时,应尽量使通风设备开至最大,避免将打开排气阀的电芯局限在某一狭窄空间内。正常操作条件下。呼吸保护是不必要的。

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory protection is not necessary under conditions of normal use.

通风条件

正常使用条件下不必考虑

Ventilation

No necessary under conditions of normal use.

防护手套

正常使用条件下不必考虑

Protective Gloves

No necessary under conditions of normal use.

其他防护服装或设备

正常使用条件下不必考虑

Other Protective Clothing or Equipment

No necessary under conditions of normal use.

电池开阀试验时应做好个人防护

呼吸防护、防护手套、防护服装和有护边的安全玻璃罩都是要准备的。

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields .

9. 物理和化学特性

Physical and chemical properties

外形:圆柱形

Appearance: Cylindrical 认证编号: RZUN2016-0107 Ref,NO::RZUN2016-0107



Add: A、E Building Chun yang Industrial park, Zhu gu shi Road Wu lian community LongCheng Street, Longgang district, Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

充放电性能:最大持续电流 6A,

Charge discharge performance: Maximum continuous current 6A

气味: 泄露时, 有醚的气味

O dour: If leaking, smells of medical ether

酸碱度: 不适用

PH: Not applicable as supplied

闪点:针对单个组暴露情况,其他不适用

Flash Point: Not applicable unless individual components exposed.

易燃度:针对单个组暴露情况,其他不适用

Flammability: Not applicable unless individual components exposed .

相对密度: 针对单个组暴露情况, 其他不适用

Relative density: Not applicable unless individual components exposed .

溶解性(水溶性):针对单个组暴露情况,其他不适用

Solubility(water): Not applicable unless individual components exposed.

溶解性(其他):针对单个组暴露情况,其他不适用

Solubility(other): Not applicable unless individual components exposed.

10. 稳定性和反应活性

Stability and reactivity

稳定性:产品在第7节所述的条件下稳定。

Stability: Product is stable under conditions described in Section 7.

应避免的条件:加热 **70**℃以上或焚烧、变形、毁坏、粉碎、拆卸、过充电、短路、长时间暴露在潮湿的条件下.

Conditions to Avoid: Heat above 70 °C or incinerate .Deform, Mutilate, Crush, Disassemble,

Overcharge, Short circuit, Expose over a long period to humid conditions.

应避免的材料:氧化剂、碱、水

Materials to avoid: Oxidising agents, alkalis, water

危险分解物:不适用

Hazardous Polymerization: N/A

如果发生泄露,避免与强氧化剂、无机酸、强碱、卤代烃接触

If leaked ,forbidden to contact with strong oxidizers,mineral acids,strong alkalies, halogenated hydrocarbons.

11. 毒理学资料

Toxicological information

标志及症状: 无,除非电池破裂。

Signs & symptoms: None ,unless battery ruptures.

内部物质暴露的情况下,蒸汽烟雾可能对眼睛和皮肤的刺激性。

In the event of exposure to internal contents ,vapour fumes may be very irritating to the eyes and skin .

第 7 页 共 10 页

QJ/11.4393-2011.05



Add: A E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

吸入:对肺有刺激性
Inhalation: Lung irritant
皮肤接触: 对皮肤有刺激性
Skin contact: Skin irritant
眼睛接触: 对眼睛有刺激性
Eye contact: Eye irritant

食入: 吞下中毒

Ingestion: Poisoning if swallowed

下列情况下会危险人员身体健康:如果与电池内部材料直接接触,皮肤可能会出现干燥灼烧等轻微或严重的刺激,并且损坏靶器官的神经,肝脏和肾脏。

Medical conditions generally aggravated by exposure:In the event of exposure to internal contents ,moderate to server irritation, burning and dryness of the skin may occur, target organs nerves , liver and kidneys .

12. 生态学资料

Ecological information

对哺乳动物的影响:目前未知

Mammalian effects: None know at present

生态毒性:目前未知

Eco-toxicity: None know at present 生物体内累积: 慢慢的生物降解

Bio-accumulation potential: Slowly Bio-accumulation

环境危害: 目前没有已知的环境危害

Environmental fate: None know environmental hazards at present.

13. 废弃处置

Disposal consideration

禁止焚烧,或使电池温度超过 **70**℃,这种滥用可导致泄漏或电池爆炸。应按照相应的地方性法规处理。

14. 运输信息

Transport information

运输标签: 锂电池标签

Label for conveyance: Lithium battery label .

图片/Picture:



Add: A、E Building Chun yang Industrial park, Zhu gu shi Road Wu lian community LongCheng Street, Longgang district, Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

UN 编号: 3481 UN Number: 3481 包装等级:不适用 Packaging Group: N/A EMS 编号: F-A-S-I EMS NO.: F-A-S-I

海洋污染物: 无

Marine pollutant: NO

正确装运名称:安装在设备中的锂离子电池(包括锂离子聚合物电池)

Proper Shipping name: Lithium ion batteries contained in equipment (including lithium polymer batteries)

危害分类: 货物应遵守 IATA 第 58 版 DGR 手册包装说明967 第 Ⅱ 节规定(2017 年版)和特殊规定 188 海运危险货物规则(Amdt.37-14)2014 版,包括通过 UN38.3 测试手册要求。此货物不受危险品管制。

Hazard Classification: The goods shall be complied with the requirements of Section II of Packing Instructions 967 of 58th DGR Manual of IATA(2017 Edition) or special provision 188 of IMDG CODE (Amdt.37-14)2014 Edition, including the passing of the UN38.3 test .The products are not subject to dangerous goods .

运输时应该将电池隔开摆放避免短路。电池在运输过程中应该确保包装牢固,装运前确保货物不会出现跌落,掉落和损坏。避免货物倒塌或者雨淋。

Separate batteries when shipping to prevent short-circuiting .They should be packed in strong packaging for support during transport.Take in a cargo of them without falling,dropping,and breakage .Prevent collapse of cargo piles and wet by rain.

运输方式: 空运 海运 陆运 铁路

Transport Fashion: By air, by sea, by road, by railway

15. 法规信息

Regulation information

法律信息

Law information

- 《危险物品规则》
- 《Dangerous Goods Regulations》
- 《对危险货物运输的有关规定的建议》
- 《Recommendations on the Transport of Dangerous Goods Model Regulations》
- 《国际海运危险货物规则》
- 《International Maritime Dangerous Goods》
- 《危险品安全运输技术指令》
- 《Technical Instructions for the Safe Transport of Dangerous Goods》
- 《危险货物分类和品名编号》
- 《Classification and code of Dangerous Goods》
- 《职业安全卫生法》



Add: A E Building Chun yang Industrial park , Zhu gu shi Road Wu lian community LongCheng Street ,Longgang district ,Shenzhen China

Tel: +86-755-84642975 Fax: +86-755-84642732 http://www.bfnbattery.com E-mail: bfn@bfnbattery.com

《Occupational Safety and Health Act》(OSHA)

《有毒物质控制法》

《Toxic Substance Control Act》(TSCA)

《消费产品安全法》

《Consumer Product Safety Act》(CPSA)

《联邦环境污染控制法》

《Federal Environmental Pollution Control Act》(FEPCA)

《石油污染法案》

《The Oil Pollution Act》(OPA)

《超级基金修正案和再授权法案III(302/311/312/313)》

«Superfund Amendments and Re-authorization Act Title∭(302/311/312/313)» (SARA)

《资源保护及恢复法案》

《Resource Conservation and Recovery Act》(RARA)

《安全饮用水法》

《Safety Drinking Water Act》 (CWA)

《加州 65 提案》

《California Proposition 65》

《美国联邦法规》

《Code of Federal Regulations》(CFR)

根据所有联邦、州和地方法律

In accordance with all Federal, State and Local laws.

16. 其他信息 Other information

本文件仅对由深圳市博富能电池有限公司提供的,并由深圳市博富能电池有限公司生产的单电芯电池(18650 2000mAh)有效。该电池的成分信息由委托方提供并承诺其完整性和准确性。用户应仔细阅读此文件,并按照正确的方法使用电池。如因电池使用不当造成的损害或损失,深圳市博富能电池有限公司不承担任何责任。

This file is only effective to the batteries (18650 2000mAh) provided bu SHENZHEN BOFUNENG BATTERY CO.,LTD, which manufactured by SHENZHEN BOFUNENG BATTERY CO., LTD. The commissioner provides the composition information of batteries, and promises it's integrity and accuracy. Users should read this file carefully and use the batteries in correct method .SHENZHEN BOFUNENG BATTERY CO.,LTD doesn't assume responsibility for any damage or loss because of misuse of batteries .