

LESSON 4.4: Scheduling

What this lesson is about

The lesson introduces the phases to create, enable, disable, and delete schedules and procedures to set up schedules for report creation.

What you should be able to do

After completing this lesson, you should be able to:

- Describe scheduling basics.
- Explain different phases in creating schedules.
- Explain the procedure to enable, disable, and delete schedules.
- Explain the steps to set up schedules for reports and stand-alone services.

How you will check your progress

- The progress of the lesson is analyzed based on the successful application of the topics in the scenario and test the exercise independently.

References

Documentation

- Monitoring Operations:

https://www.ibm.com/support/knowledgecenter/en/SS3JSW_5.2.0/com.ibm.help.performance_mgmt.doc/SIPM_MO_Overview.html

Scheduling Basics

Scheduling Basics

In the application, a schedule is a resource in the database that stores time and date information separately from the scheduled activity. Schedules identify when to run the activity (hourly, daily, weekly, or monthly) and when to skip the normal interval by excluding a certain time, time range, or date. Each schedule is used for just one business process, service, or report, so you must create separate schedules for each business activity.

Phase 1 Scheduling Prerequisites and Setup in a Test Environment

1. Meet the licensing, permissions, and environmental requirements for the resource you want to schedule.
2. In a test environment, create or configure the business process, service, or scheduled report. Manually test the business process, service, or report to verify that the activity works as planned.
3. In a test environment, create the schedule for the business process, service, or report.

When you complete the scheduling wizard, the new schedule is enabled and runs when the first scheduled time period is reached. Additionally, if you select, it runs at startup option, the scheduled activity runs one time immediately after the schedule is saved in the database. Thereafter, the activity runs when the application is restarted.

Phase 2 Testing Schedules in a Test Environment

Test and troubleshoot the schedule in the test environment

- Know how to test scheduled activities by disabling the schedule, running the activity manually, and enabling the schedule. Newly created schedules are automatically enabled, so you must disable the schedule running the activity manually. Schedule can result with errors if you run the same activity manually when the schedule is running the activity automatically. After the manual test, you must enable the schedule again or it does not operate.

(Continued on next page)

Scheduling Basics

(Continued)

Scheduling Basics

....(Continued)

In the scheduling wizard, do not use the Do not schedule option to stop or disable a schedule. If you select this option, you cannot enable the schedule in the future. Instead, you must re-create the schedule. Use this option only to indicate that a service or report never use a schedule.

- Test the schedules in your test environment to verify that the service, business process, or report runs as scheduled and within the acceptable time parameters. For example, you might create a file system adapter configuration to collect files from a file system with a schedule of every day, every 20 minutes. The schedule is not important if the file system adapter configuration does not collect the correct files from the correct file system. In this case, you must correct the service configuration testing the schedule.
- Be sure to test the schedule under regular performance conditions in your test environment. For example, testing can reveal that the size of scheduled reports or business processes and requires you to move the scheduled times based on the system processing loads. In addition, you can find that running an activity at an interval that is too short is not productive. In this case, you can edit the schedule and extend the time interval between executions.
- Create processing time benchmarks based on the size of the reports or outputs expected to refine the schedule further, so that you can schedule similar activities in the future with accuracy.

Phase 3 Exporting Schedules to the Production Environment

1. Export the schedule from your test environment and import it into your production environment.

You import and export schedules just like you import and export any other resource. You can export and import one or more schedules at the same time.

(Continued on next page)

Scheduling Basics

(Continued)

Scheduling Basics

....(Continued)

- a. In your production environment, verify that the imported schedule is enabled and monitor the scheduled activity. After the time interval for the schedule, verify the outputs for the business process, service or adapter, or report.
 - b. If the outputs were correct and within the acceptable time parameters, the test was successful.
 - c. If the outputs were correct, but not within the acceptable time parameters, you need to edit the schedule.
 - d. If the scheduled output does not run, verify the activity by using monitoring capabilities in the application.
2. In the production environment, monitor and adjust the schedule as needed.
 - a. You need to disable and enable schedules in your production environment if you need the output of the scheduled activity at a time outside of the normal schedule. For example, you need to run a report for an urgent meeting when the next scheduled report run is the following day. In this case, you run the report manually to have the most current information for the meeting. In this case, you must disable the schedule to reduce the chances of errors, run the report manually, and then re-enable the schedule so the report runs automatically again
-

Scheduling Prerequisites and Planning

Introduction

When you create a schedule, you are doing more than setting a time and a date for an activity to run. You must consider how the schedule works within the application overall, and with your and your trading partners' businesses.

Creating a schedule to automate activities can help your business in many ways, such as faster response times and improved communications with your value chain partners. However, creating a schedule for an activity that runs at the wrong time results in a missed business opportunity or scheduling an activity, that is resource-intensive during your peak processing times can cause decreased system performance, errors, or lost revenue for the company.

Scheduling Licenses and Permissions

Before you can set up schedules in a test or production environment, you must meet the following prerequisites:

- You must have the license file for the services and activities you want to schedule.
- You must have the security permissions that are applied to your user account.

Permission	Description
UI BP Manager	Allows you to download the Graphical Process Modeler, and create and manage business processes.
UI Reports	Allows you to create, manage, and schedule reports.
UI Services	Allows you to install, configure, manage, and schedule services.

(Continued on next page)

Scheduling Prerequisites and Planning

(Continued)

Scheduling Licenses and Permissions

....(Continued)

Permission	Description
UI Scheduler	Allows you to schedule business processes, search for schedules and edit business process and service schedules.
UI Import/Expor	Allows you to export the schedules and associated business processes, services, or reports to another system of the application, and import the schedules and resources into the application.
UI Logs	Allows you to view the schedule.log and reports.log files for troubleshooting schedules.

Scheduling Considerations for Upgrades and Environments

Schedules After Upgrades

When you upgrade the application, your schedules are upgraded to the new version, and run based on the configured schedule setting.

After you upgrade the application, you can verify schedules by selecting **Deployment > Schedules > Search**. Locate each schedule and verify that it is enabled and defined correctly.

Schedules in the AS2 Edition

In the AS2 Edition of the application, you can set up schedules for business processes only. The AS2 Edition does not support reports or schedules for services.

- The default schedules for business processes after you install AS2 Edition.
- AS2 Edition lists only the schedules for business processes that are created in the AS2 Edition.

However, the complete version of the application lists schedules for business processes that are created in both the complete version and in the AS2 Edition.

Scheduling Consideration

This section summarizes various considerations for scheduling business processes, services, and reports.

Basic information about the Activity Being Scheduled

What type of activity are you scheduling and where does the output from the activity go?

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

Example	Comments
Are you scheduling a business process, report, or service?	Be sure the business process, report, or service is created or configured and that you know the name of the resource. For example, you need to schedule an export activity, but you can schedule only the Export service when the service is in a business process. You must create the business process that includes the Export service and then schedule the business process. The activity that is scheduled determines how you create the schedule. Some services can be scheduled independent of a business process.
If scheduling a business process, does data need to be passed to the business process?	The Scheduler can pass XML data to a business process when it invokes it. You define name-value pairs for the data when creating the schedule.

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

Example	Comments
Who or what business process or service needs the output from the scheduled business process, service, or report?	For example, your manager may require a report at a specific time daily, or a business process may require the output from another business process. This example question determines who to send the output to or what business process or service is invoked by the scheduled activity.
Is the business process or service that uses the output also scheduled?	For example, you may schedule a business process that produces an invoice that is required by another scheduled business process. This example question determines the dates and times of the schedule, since the scheduled activity that produces the output must complete before the second scheduled activity starts.
Are you running the business process, service, or report manually as well as on a schedule?	For example, you may need to run a report manually at times in a rush situation, but the report is scheduled to run every hour. To avoid errors, you do not want to manually run the report at the time it is scheduled to run. You must disable the schedule before manually running the scheduled activity.

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

Deadlines that impact scheduled times

Are there internal and external deadlines that impact when the schedule must be set? Deadlines can determine the dates and times when an activity must be scheduled to run

Example	Comments
Reporting time frames for your company	Reporting various types of information to different departments within your company can affect schedules for your business processes, services, and reports
Priority or strategy changes of your company	Priority and strategy changes can cause changes in which business processes take priority over other business processes, and which reports rise in importance over other reports. These situations can affect the scheduling of activities in the application. Considering these issues helps you determine types of schedules, and which activities to run during peak or non-peak processing hours.
Trading partner agreements	Trading partner agreements includes stipulations regarding document turnaround times, fines associated with missing critical response times, and other information that is important to your communication with your trading partners throughout your value chain. For example, a trading partner that requires you to process a document within 30 minutes of receiving the document.

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

Dates that impact excluded times

Are there dates or times when the schedule does not need to run? Holidays and other events can determine the dates and times that a schedule must exclude or that a low priority schedule must include.

Example	Comments
Holidays and company calendars	Holidays and company calendars can determine the best time to run a large report or business process. Alternatively, holidays can determine dates to exclude in your schedules. For example, if you have a large report that is due on January 3 of each year and your company is closed January 1 for New Year's day, you can decide to schedule the report to run on January 1 when more resources are available in the application. On the other hand, you may skip January 1 for a routine report that is not needed when the company is closed.
Periods of higher processing times during the quarter	Low priority schedules must exclude high-volume processing times.

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

Example	Comments
Scheduled maintenance of the application or other systems that integrate with the application, either at your company or your trading partners.	Scheduled maintenance is necessary for all systems. When you are conducting maintenance on the application or other systems that integrate with it, you can disable schedules that are to run during those periods. Or you can schedule activities around those periods. Either of these adjustments reduces performance level problems caused by schedules attempting to run but generating errors, or by schedules placed in a waiting status. In addition, if you consider your trading partners scheduled maintenance, you can schedule your activities around those periods and use the application resources for other processing.

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

Peak and Non-peak Processing Time

On your system, what are the peak and non-peak processing times during the day, week, or month?

Peak and non-peak processing times can help you determine when to run high priority and low priority activities in the application to increase performance and maximize the use of system resources.

Example	Comments
For example, you receive the largest amount of processing requests for the application every day between 8:00 a.m. and 5:00 p.m. You do not want to schedule non-priority work during this time interval.	Peak processing times are times that low priority schedules must avoid or exclude, so that the application performance levels are not reduced.
For example, you receive the least amount of processing requests for the application every day between 2:00 a.m. and 5:00 p.m. Schedule non-priority work during this time interval.	Non-peak processing times are times that low priority schedules must include, so that the application performance levels are not reduced.

(Continued on next page)

Scheduling Considerations for Upgrades and Environments

(Continued)

Scheduling Consideration

....(Continued)

The Processing Time and Frequency of the Scheduled Activity

The processing time and frequency of the scheduled activity affects scheduling intervals.

Example	Comments
Total processing time required for the business process, service, or report	Total processing time is critical for scheduling business processes, services, and reports, so that you do not have overlapping executions. For example, if a business process takes 30 minutes to complete, you should not schedule the business process to run every 10 minutes; otherwise, errors can occur
Frequency at which the data or processing is required	Determining the frequency at which data or processing is required helps you determine the schedule type to use with the activity. For example, if a File System adapter configuration collects documents from a file system every 10 minutes, so the documents can be used in another business process, the best schedule type is timer. If, however, the service configuration collects documents every Friday at 3:00 p.m., then the best schedule type is weekly.

Enable, Disable, or Delete a Schedule

Enable a Schedule

Enabling a schedule makes the schedule active and causes the associated activity to run according to the schedule settings. A schedule must be enabled to run.

1. Select Deployment > Schedules.
2. Use Search or List to identify the schedule you want and click Go!.
To find a report schedule, look for the business process created for the schedule. The format is reportname_scheduleBP.
3. On the Schedules page, locate the schedule and select the check box in the Enabled column.

The schedule is enabled immediately and runs at the next scheduled time

Disable a Schedule

Disabling a schedule makes the schedule inactive. Disable a schedule to stop it for editing or to run the activity manually.

1. Select Deployment > Schedules.
2. Use Search or List to identify the schedule you want and click Go!.
To find a report schedule, look for the business process created for the schedule. The format is reportname_scheduleBP.
3. On the Schedules page, locate the schedule and clear the check box in the Enabled column.
The schedule is disabled immediately, till it is enabled again.

(Continued on next page)

Enable, Disable, or Delete a Schedule

(Continued)

Delete a Schedule

Delete a schedule independently of the activity that it is scheduled to invoke. The Delete function does not delete the business process, service, or report that the schedule invokes. Disabling a schedule stops the schedule from running, but keeps the activity active in the application.



Note

Do not delete the pre-configured services for archiving, indexing, or purging. Deleting these services negatively impact the performance of your system.

1. Select Deployment > Schedules.
2. Use Search or List to identify the schedule you want and click Go!.
To find a report schedule, look for the business process created for the schedule. The format is reportname_scheduleBP.
3. On the Schedules page, locate the schedule and select Delete.
The Resource Summary screen displays the scheduling data for you to review.
4. Click Next to continue with the deletion.
The Confirm screen is displayed.
5. Click Delete to confirm that you want to delete the business process schedule.
The schedule is deleted immediately. Other business processes associated with this schedule, such as bootstrapped processes.
6. Click Return to continue.

(Continued on next page)

Schedules for Report

(Continued)

Introduction

You can set up schedules for reports so that they run automatically at hourly, daily, weekly, or monthly intervals. The application does not schedule any reports by default. Consider these guidelines:

- The report configuration must exist before you set up the schedule.
- You can have only one schedule per report configuration.
- After a scheduled report is generated, it can be stored on your file system or sent via email (in .zip format) to a recipient. You set up these choices as part of the report schedule.
- Creating a schedule for a report automatically creates a business process by using the default report name `reportname_scheduleBP`. The business process for a schedule is listed with other business processes when you select **Deployment > Schedules > List > Business Processes**.
- You can also schedule a report through the Report Service, if the report configuration is predefined and you provide the report configuration name and the format of the report.

(Continued on next page)

Exercise 4.4.1: Create a Report Schedule

Introduction

Alice configures to create a scheduled report, that runs every 24 hours.

Instructions

Complete the following steps to create a scheduled report:

Step 1: From the Administration Menu, select **Operations > Reports**

Step 2: Click **Go!** Next to **Schedule Report**, under **Schedule**. The **Report Configurations** page is displayed.

Step 3: Select the report **BPDetail_ByBPName** from the Choose Report To Schedule list.

Step 4: Select the output format as **PDF** from the Format list and click **Next**.

Step 5: To store the report on the file system, select the **Store Reports On File System** checkbox.

Step 6: If you want to send the report as an email, select email Address and enter the Subject, email Address, Host, and Port.

Step 7: Click **Next**.

Step 8: Select the **24 Hour Clock Display** check box to use the 24 hr clock.

Step 9: Select the schedule type as **Run based on timer** and click **Next**.



Note

Depending on the schedule type, schedule report wizard displays different **Schedule Settings** pages.

Step 10: Enter the required time interval in Select Time of the Timer Schedule Setting page. For this example, to view the report, give time interval as 2 minutes and click **Next**.

Step 11: Enter any time duration that you want to exclude in the **Schedule Exclusions** page. In this exercise, do not enter any exclusions and click **Next**.

Step 12: Enter any dates that you want to exclude in the **Date Exclusions** page. In this exercise, do not enter any exclusions and click **Next**.

(Continued on next page)

Exercise 4.4.1: Create a Report Schedule

(Continued)

Instructions

....(Continued)

Step 13: Review the setting in the **Confirm** page and click **Finish**.

Step 14: Go to **/opt/apps/sfg1_9000/install/reports** in FileZilla and then view the PDF report.

Step 15: From the Administration Menu, select **Deployment > Schedules**. The Schedules page is displayed.

Step 16: Enter **BPDDetails_BYBPName_ScheduleBP** in the text box next to Search by Name and click **Go!**.

Step 17: You can view the schedule **BPDDetails_BPName_ScheduleBP**. For this exercise, since you scheduled the report for every 2 minutes, disable this schedule to avoid unnecessary creation of reports.

(Continued on next page)

Edit a Report Schedule

Edit a Report Schedule

You can edit a report schedule in two ways:

- From Operations > Reports, you can locate the report that you want and edit its schedule. Use this method if you want to modify the format of the report or how it is delivered to the file system or to an email recipient. However, this method makes disabling the schedule more cumbersome.
- From Deployment > Schedules, you can locate the business process that was created for the report schedule and edit it. This method makes it easy to disable the schedule editing it. However, you cannot adjust the format of the report or how it is delivered to the file system or to an email recipient.

To edit a report schedule

1. Know the name of the business process that corresponds to the report schedule you want. Business processes for report schedules are named reportname_scheduleBP (where is the name of the default report configuration).

(Continued on next page)

Edit a Report Schedule

(Continued)

Edit a Report Schedule

....(Continued)

2. Choose any of the following methods in the table:

**Note**

In the table heading, Method A and Method B represents

Method A: To modify the format of the report, how it is delivered, and scheduling times:

Method B: To modify only scheduling times and preserve the report format and delivery option.

Method A	Method B
1. Disable the business process for the report schedule you want. Select Deployment > Schedules > List > Business Processes. In the list, clear the Enabled check box next to the report schedule you want. Click Return. 2. Select Operations > Reports. Use Search or List to display the report you want. In the list, click edit in the Schedule column for the report you want. 3. Indicate the report format. Click Next. 4. Indicate the delivery options for storing the report on the file system or for sending it to an e-mail recipient. Click Next.	1. Disable the business process for the report schedule you want. Select Deployment > Schedules > List > Business Processes. In the list, clear the Enabled check box next to the report schedule you want. 2. In the list, click edit next to the report schedule you want.

(Continued on next page)

Edit a Report Schedule

(Continued)

Edit a Report Schedule

....(Continued)

3. Work through the scheduling wizard to adjust the schedule.
You can run a schedule based on a timer, daily, days of the week, or days of the month.
Click **Finish** to save and apply the changes to the schedule.
4. Enable the business process that corresponds to the report schedule you edited.

Example of a Report Schedule

This scheduling example consists of three scheduling activities:

- Scheduling a report every day at a specific time, including exclusions. (Daily schedule)
- Scheduling a report one day each week at a specific time. (Weekly schedule)
- Scheduling a report one day a month at a specific time. (Monthly schedule)

Your manager requires you to provide three reports at different times, all in HTML format:

- Report 1 on business processes that are in a waiting status each day by 10:00 AM, except on holidays such as New Year day, January 1.
- Report 2 on the number of functional acknowledgements from a specified sender ID that are overdue during the week by 11:00 AM each Wednesday.
- Report 3 on business process definitions that were modified during the month by 4:00 PM on the last day of the month.

You can set schedules to automatically generate these reports for you and have the report information e-mailed to you, reducing your time spent on reporting issues. The preceding requirements set by your manager, you determine that you need 45 minutes to prepare each of the reports for your manager, so the email report shows you 1 hour before the deadlines set by your manager.

(Continued on next page)

Edit a Report Schedule

(Continued)

Edit a Report Schedule

....(Continued)

The following table describes the schedule parameters that you set for each report:

Report	Schedule Settings
Report 1	Report to schedule: BPDetail_ByState. This report provides the states of each business process that are running in the application. Format: HTML E-mail Address: ■ Subject: Report 1 ■ E-mail Address: yourname@yourcompany.com ■ E-mail Host: your e-mail host server name ■ E-mail Port: your e-mail port number Schedule Type: Daily Schedule Time: 9:00 a.m. Date Exclusions: 1 - January
Report 2	Report to schedule: EDIOutAck_GroupLevel_BySenderReceiver. This report provides the status of acknowledgements based on sender or receiver IDs. Format: HTML E-mail Address: ■ Subject: Report 2 ■ E-mail Address: yourname@yourcompany.com ■ E-mail Host: your e-mail host server name ■ E-mail Port: your e-mail port number Schedule Type: Day(s) of the week Schedule Time: 10:00 a.m. Wednesday

(Continued on next page)

Edit a Report Schedule


(Continued)

Edit a Report Schedule

....(Continued)

Report	Schedule Settings
Report 3	Report to schedule: BPDefList_ByBPDefStatus. This report provides a list of business process definitions by status. Format: HTML E-mail Address: ■ Subject: Report 3 ■ E-mail Address: yourname@yourcompany.com ■ E-mail Host: your e-mail host server name ■ E-mail Port: your e-mail port number Schedule Type: Day(s) of the month Schedule Time: 3:00 p.m. LDOM (Last Day Of Month) Date Exclusions: None

The following figure shows the reports that are running on schedule, being e-mailed to you, and you providing the reports to your manager:



(Continued on next page)

Edit a Report Schedule

(Continued)

Edit a Report Schedule

....(Continued)

1. The BPDetail_ByState report (Report 1) runs at 09:00 AM. every day.
 2. The report is created and mailed to your email account.
 3. Each Wednesday at 10:00 AM, the EDIOutAck_GroupLevel_BySenderReceiver report (Report 2) runs.
 4. The report is created and mailed to your email account.
 5. On the last day of each month (LDOM) at 3:00 PM, the BPDefList_ByBPDefStatus report (Report 3) runs.
 6. The report is created and mailed to your email account.
 7. You retrieve the reports from your email account at the appropriate times and create the reports for your manager.
 8. You deliver the reports to your manager by the specified deadlines.
-

Schedules for Stand-alone Services

Introduction

You can set up schedules only for those services and adapters that can be run as a stand-alone service. However, all services and adapters can be included in a business process that is scheduled.

Creating a schedule for a service is part of creating the service configuration. You can schedule stand-alone services so that they run automatically on hourly, daily, weekly, or monthly intervals. Consider these guidelines:

- You schedule only that service. You cannot create a schedule and apply it to many services at the same time.
- The schedule settings are stored in the database you use with the application and are internal to the application *only*. Schedules for applications that are external to the application do not affect the service and adapters schedules that you create within the application.
- Some stand-alone services and adapters are supplied with default schedules when the application is installed.
- The run as User option is available only to super users. It is not available to subgroups of the Admin group or other groups.

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Introduction

....(Continued)

Following table lists the stand-alone services and adapters that can create schedules:

Stand-alone Services and Adapters	
B2B Mail Client adapter	IBM Information Exchange FTP adapter
BackupService	Index Business Process Service
Command Line2 adapter	Java Database Connectivity (JDBC) adapter
Connect:Enterprise adapter	Lightweight JDBC adapter
EDI Enveloping Service	Mailbox Evaluate All Automatic Routing Rules service
EDI Overdue Acknowledgment Check Service	Mailbox Evaluate Routing Rules service
File System adapter	Mailbox Scheduled Delete service
FTP Get adapter	Oracle AQ JMS Queue adapter
Gentran:Server UNIX Purge Process Service	Oracle AQ JMS Topic adapter
Gentran:Server Windows adapter	Perf Data Purge service
GXS ICS FTP adapter	Purge service
	Purge Business Process Linkage service
	Retention processor

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Create a Schedule for a stand-alone Service

You create a service schedule when you configure the service.

1. Install the service or adapter.
2. To configure the service, select Deployment > Services > Configuration.
3. Search for the services that you want to schedule and click edit.
4. Complete the steps that are required for the service or adapter in the scheduling wizard.
5. You can run a schedule based on a timer, daily, days of the week, or days of the month.
6. Click Finish. The schedule is saved, enabled, and ready to run.

Edit a Schedule for a stand-alone Service

1. Disable the schedule that you are editing. This action prevents errors in case the schedule is running at the time you are working.
2. Select Deployment > Schedules.
3. Type the name of the schedule in the Search field and click Go!.
4. Alternately, select Services in the List box, click Go!., and click Edit next to the schedule you want in the list.
5. Work through the scheduling wizard to adjust the schedule.
6. You can run a schedule based on a timer, daily, days of the week, or days of the month.
7. Click Finish to save and apply the changes to the schedule.
8. Enable the schedule.

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Delete a Schedule for a stand-alone Business Process or Service

1. In the application, select Deployment > Schedules.
In the application AS2 Edition, select Administration Menu > Schedules.
2. Type the name of the schedule in the Search field and click Go!.
Alternately, use the List box, select Business processes or Services, and click Go!.
3. Click Delete next to the schedule you want to delete.
The Resource Summary screen displays with the scheduling data for you to review.
4. Click Next to continue with the deletion.
The Confirm screen displays.
5. Click Delete to confirm.
The schedule is deleted immediately. Any other business processes associated with this schedule, such as bootstrapped processes.

Example of a stand-alone Service Schedule

This example consists of two scheduling activities:

- Weekly schedule
Scheduling a file system adapter one day each week at a specific time.
- Monthly schedule
Scheduling a Gentran:Server Windows adapter one day a month at a specific time.

By analyzing your past processing trends, you determine you have a file system that you must collect data for every week, and you also need to collect information from a rarely used file system one time a month from which you create a report for your manager.

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Example of a stand-alone Service Schedule

....(Continued)

Using the analysis of your processing volumes and peak times, and the importance of both of these processes, you determine that you can schedule both services during non-peak hours:

- File System adapter 1 (weekly) – 07:00 AM. each Monday
- File System adapter 2 (monthly) – 06:00 AM. LDOM (last day of month)

The following table describes the schedule parameters that you set for the file system adapters:

Service	Schedule Settings
File System adapter 1	Service to schedule: File System adapter Timer or Clock: Clock (Weekly) System: node1 Execution Day: Every Monday Scheduled Time(s): 07:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No,Run As User: Admin
File System adapter 2	Service to schedule: File System adapter Timer or Clock: Clock (Monthly)) System: node1 Execution Day: LDOM (last day of the month) Scheduled Time(s): 06:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)


Schedules for Stand-alone Services

(Continued)

Example of a stand-alone Service Schedule

....(Continued)

This figure shows the services that are running on schedule and the data that is being collected from the file systems:



1. Every Monday at 07:00 AM. the File System adapter 1 runs in the application and checks File System 1 for data.
2. Data in File System 1 is collected and brought into the application for use by the appropriate business process or service.
3. At 06:00 AM. on the last day of each month, the File System adapter 2 service runs in the application and checks File System 2 for data.
4. Data in File System 2 is collected and brought into the application for use by the appropriate business process or service, so that you can create the report for your manager.

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

Some services and adapters are supplied with default schedules when the application is installed. You can edit the default schedules to meet your needs.

Service or Adapter Supplied During Installation	Default Schedule Settings
AFTPurgeArchiveMailboxes Ensures that messages stored in AFT's archive mailboxes are made eligible for purging soon after their corresponding AFT Routes are purged	Enabled: Yes Schedule Type: Business Process Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 04:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
AssociateBPsToDocs Associates expired documents with the business process to enable archiving and purging Note: Do not delete this service. Deleting it will impair system performance.	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 30 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
AutoTerminate Terminates business processes that have been in a specified state for more than a specified number of days	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 04:00 AM Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
BackupService Backs up complete or terminated business process data	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 02:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
BPEXpirator Continues waiting services when their timeout period expires	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 15 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin
BPLinkagePurgeService Purges expired business process hierarchical data. Note: Do not delete this service. Deleting it impairs the system performance	Enabled: Yes Schedule Type: Service Timer or Clock: Clock (Daily) System: node1 Execution Day: Every Day Scheduled Time(s): 02:30 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin.

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
BPREcovery Recovers incomplete business processes	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 45 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin
CheckExpireService Checks to see if certificates are about to expire	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 02:30 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
DataStoreFileSyste	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 1 minute Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin
DBMonitor Monitors the database for common conditions that may be signs of problems with database health	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Monday Scheduled Time(s): 04:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
DocumentStatsArchive Recalculates the documents statistics	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 30 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
IndexBusinessProcessService Moves completed or terminated business process data into the index tables in the database Note: Do not delete this service. Deleting it impairs system performance.	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 10 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
IWFCDriverService Recovers IWFC objects from the wfc_error/iwfc directory and attempts to start the subprocess. If the subprocess starts, the file is deleted; otherwise, the file remains in the directory for the next scheduled run time.	Enabled: Yes Schedule Type: Service Timer or Clock: Clock (Daily) System: node1 Execution Day: Every Day Scheduled Time(s): 03:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
MailboxEvaluateAllAutomaticRules Evaluates all mailbox rules designated for automatic processing	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 1 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
MailboxEvaluateAllAutomaticRulesSubMin Evaluates all mailbox rules designated for automatic processing	Enabled: No Schedule Type: Business Process Timer or Clock: Timer System: node1 Execution Day: Every Day Execution Time: Every 0 hours and 10 seconds Excluded Time(s): None Excluded Dates: None At startup: No Run As User: admin
MessagePurge Purges expired user messages Note: Do not delete this service. Deleting it impairs system performance.	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 30 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
NonEDiInboundFSAdapter Collects files from the install_dir/nonediinbound/collect directory for translation purposes	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 2 hours and 0 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin
NonEDiOutboundFSAdapter Collects files from the install_dir/nonedioutbound/collect directory for translation purposes	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 2 hours and 0 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
PartialDocumentCleanUp Purges incomplete documents that have expired	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node 1 Execution Day: Every Day Scheduled Time(s): Every 2 hours and 0 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
PerfDataPurgeService Purges data from YFS_STATISTICS_DETAILS	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 03:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
ProduceMsgPurgeService Purges expired user messages Note: Do not delete this service. Deleting it impairs system performance.	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 02:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
PurgeService Purges completed or terminated business process data from live tables Note: Do not delete this service. Deleting it impairs system performance.	Enabled: Yes Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 10 minutes Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
RetentionProcessor Purge eligible records from the Reporting Services data repository	Enabled: Yes Schedule Type: Service Timer or Clock: Clock System: node1 Execution Day: Every Day Scheduled Time(s): 02:00 a.m. Excluded Time(s): None Excluded Dates: None At startup: No Run As User: Admin
Scheduled_AlertService Checks business processes for error statuses	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 0 hours and 30 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin

(Continued on next page)

Schedules for Stand-alone Services

(Continued)

Default Schedules for Supplied Services and Adapters

....(Continued)

Service or Adapter Supplied During Installation	Default Schedule Settings
SyncEngine_DataCleanManager Cleans the data in the SyncEngine tables when all of the tasks are completed based on a syncopsetid process	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 20 hours and 45 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin
SyncEngine_TaskManager Manages tasks for the SyncEngine	Enabled: No Schedule Type: Service Timer or Clock: Timer System: node1 Execution Day: Every Day Scheduled Time(s): Every 6 hours and 0 minutes Excluded Time(s): None Excluded Dates: None At startup: Yes Run As User: Admin

Lesson review

What you have been able to do

After completing this lesson, you should have been able to:

- View database Usage, Services, and Pools.
 - Describe the basic of schedules.
 - Explain different phases in creating schedules.
 - Explain the procedure to enable, disable, and delete schedules.
 - Explain the steps to set up schedules for reports and stand-alone services.
-