

Practical Exercise: Associating Roles with User Store Groups

Training Objective

Learn how to associate user store groups to permissions inside WSO2 API Manager and transform them into roles.

Business Scenario

PizzaShack wants to reuse existing user store groups to maintain access control on its API Management platform.

High-Level Steps

• Associate permissions to existing groups

Detailed Instructions

Create three new LDAP groups by creating new roles on WSO2 API Manager:

Role	Permissions
Architect	Admin Permissions->Login Admin Permissions->Manage->Search Admin Permissions->Manage->Manage Tiers Admin Permissions->Manage->API Admin Permissions->Manage->Resources
Developer	Admin Permissions->Login Admin Permissions->Manage->Search Admin Permissions->Manage->API->Subscribe Admin Permissions->Manage->API->Create Admin Permissions->Manage->Resources
Admin	All Permissions

Managing Role Mappings

The new API Manager Publisher and Developer portals use Publisher and Developer portal REST APIs, with resources secured with scopes. Each action of the UI, login/ create api/ publish/ subscribe are governed by the scopes.

These scopes are mapped with the API Manager Internal/* roles. (Internal/creator, Internal/publisher etc)


Therefore, in order to provide access to the portals, the LDAP groups must be mapped with the respective Internal/* role in API Manager.



Adding Role Mappings

You can use role mapping to map the above created roles to the existing default internal roles of API-M. This enables users with new roles to use REST API scopes of API-M Portals easily.

- 1. Sign in to the Admin Portal (https://<APIM_Host>:<APIM_Port>/admin) if you have not done so already.
- 2. Navigate to **Settings > Role Permissions** in Admin Portal and click on **Add Role Permission**.




3. Provide the name of the newly created role.




4. The newly created role can be mapped to an existing internal or admin role if required.





5. Select the required existing scopes for the newly created role and save the changes.





This will update all the scope mappings in the tenant-conf.json file with the Internal/creator role as an allowed role. As a result, the new creator role will also be allowed for all scopes that are allowed for the Internal/creator role.

Info

The following are the scopes that are allowed for each default Internal role under the default configurations section.

Scope	ad	Internal/pu	Internal/c	Internal/sub	Internal/an	Internal/ev
	min	blisher	reator	scriber	alytics	eryone
apim:api_publish	✓	✓				





Scope	ad min	Internal/pu blisher	Internal/c reator	Internal/sub	Internal/an alytics	Internal/ev eryone
apim:api_create	✓		√			
apim:api_view	\checkmark	✓	\checkmark		✓	
apim:api_delete	\checkmark		\checkmark			
apim:subscribe	\checkmark			✓		
apim:tier_view	✓	✓	✓			
apim:tier_manage	\checkmark					
apim:bl_view	✓					
apim:subscription_view	✓	✓	✓			
apim:subscription_block	\checkmark	✓				
apim:mediation_policy_vie w	✓		✓			
apim:mediation_policy_cre ate	✓		✓			
apim:api_workflow	\checkmark					
apim:app_owner_change	✓					
apim:app_import_export	✓					
apim:api_import_export	\checkmark					
apim:label_manage	\checkmark					
apim:label_read	\checkmark					
apim:app_update	✓			✓		
apim:app_manage	✓			✓		
apim:sub_manage	✓			✓		
apim:monetization_usage_ publish	✓	✓				
apim:document_create	\checkmark	✓	✓			
apim:ep_certificates_updat e	✓		✓			
apim:client_certificates_up date	✓		✓			
apim:threat_protection_policy_manage	✓		✓			
apim:document_manage	√	✓	✓			




Scope	ad min	Internal/pu blisher	Internal/c reator	Internal/sub	Internal/an alytics	Internal/ev eryone
apim:client_certificates_ad d	✓		√			
apim:publisher_settings	\checkmark	✓	\checkmark			
apim:store_settings	\checkmark			✓		
apim:client_certificates_vie w	✓		✓			
apim:mediation_policy_ma nage	✓		✓			
apim:threat_protection_policy_create	✓		✓			
apim:ep_certificates_add	\checkmark		\checkmark			
apim:ep_certificates_view	\checkmark		\checkmark			
apim:api_key	\checkmark		\checkmark			
apim_analytics:admin	\checkmark					
apim_analytics:api_analytics:own	: ✓					
apim_analytics:api_analytics:edit	: ✓					
apim_analytics:api_analytics:view	· <	✓	✓			
apim_analytics:application_ analytics:own	- ✓					
apim_analytics:application_ analytics:edit	- ✓					
apim_analytics:application_ analytics:view	- √			✓		
apim_analytics:monitoring_ dashboard:own	. ✓					
apim_analytics:monitoring_ dashboard:edit	. ✓					
apim_analytics:monitoring_ dashboard:view	. ✓				✓	
apim_analytics:business_a nalytics:own	✓					
apim_analytics:business_a nalytics:edit	✓					



Scope	ad min	 Internal/c reator	Internal/sub scriber	Internal/an alytics	Internal/ev eryone
apim_analytics:business_a nalytics:view	✓			✓	
apim:pub_alert_manage	\checkmark	\checkmark			
apim:sub_alert_manage	\checkmark		✓		
apim:tenantInfo	\checkmark				
apim:admin_operations	\checkmark				
apim:shared_scope_mana ge	✓				

Editing or deleting a role

- 1. Sign in to the management console (https://<APIM_Host>:<APIM_Port>/carbon) if you have not done so already.
- 2. In the **Main** menu, click **List** under **Users and Roles**.



3. Click Roles.





4. If you need to modify to a role, select the domain (user store) under **Search Roles** > **Select Domain** where the role resides.



Then use the relevant links in the **Actions** column that corresponds to the role listing to perform the following:



- Rename the role
- Change the default permissions associated with this role
- Assign this role to users
- View the users who are assigned this role
- Delete the role if you no longer need it

Info

If the role is in an external user store to which you are connected in read-only mode, you will be able to view the existing roles but not edit or delete them. However, you can still create new editable roles.



Updating before the first startup (recommended)

The default role name of the Administrator, (admin) can be changed before starting WSO2 API Manager by editing <api-M_HOME>/repository/conf/deployment.toml file. For more information, see Change the super admin credentials. Configure the property admin role with your custom role (administrator) in

the deployment.toml file as follows and start the server.

```
[super_admin]
admin_role = "administrator"
username = "admin"
password = "admin"
create_admin_account = true
```

Updating the role name after the product is used for some time (advanced configuration)

Tip

These steps are not necessary if you have already updated the role names before the first startup of the product.

The following steps guide you through updating the role names after you have used the product for some time.

- 1. Make the configuration changes indicated in the above section.
- 2. Do the following user store level changes for existing users:

If you are connected to the JDBCUserStoreManager, update the UM_ROLE table with the new role name that you defined in place of the admin role.

Info

The schema can be located by referring to the data source [database.shared_db] defined in the deployment.toml file. The data source definition can also be found in the same file.

- If you are connected to the ReadWriteLdapUserStoreManager, populate the members of the previous admin role to the new role under **Groups**.
- 3. Restart the server.

Original Role	Mapped Role
Internal/publisher	Architect





Internal/creator	Developer
Internal/subscriber	Developer
admin	Admin

Expected Outcome

Understand how to define roles in your organization based on user store groups already created or by verifying the need to create new groups to manage such permissions and providing access to the roles by mapping with Internal/* roles.