

i2i: Multi-Model Consensus and Inference Protocol for Reliable AI Systems

Lance James*

Unit 221B

<https://github.com/lancejames221b/i2i>

January 2026

Abstract

Large Language Models (LLMs) demonstrate remarkable capabilities but suffer from hallucinations, single-model biases, and inability to express epistemic uncertainty. We present **i2i** (“eye-to-eye”) and the **Multi-model Consensus and Inference Protocol (MCIP)**, a standardized framework for AI-to-AI communication that addresses these limitations through multi-model consensus, cross-verification, epistemic classification, and intelligent routing. MCIP enables LLM agents to query multiple models, detect agreement levels, fact-check each other, classify questions by answerability, and automatically route queries to optimal models. Our experimental evaluation across factual QA, reasoning, and verification tasks shows that multi-model consensus reduces hallucination rates by 23-47% compared to single-model baselines, with HIGH consensus (85%+ agreement) achieving 94.2% accuracy. We introduce the concept of *epistemic classification*—distinguishing answerable questions from those that are uncertain, underdetermined, or fundamentally “idle” (well-formed but non-action-guiding). The protocol is provider-agnostic, supporting cloud APIs (OpenAI, Anthropic, Google) and local models (Ollama, LiteLLM). Code and protocol specification are available at <https://github.com/lancejames221b/i2i>.

1 Introduction

The deployment of Large Language Models (LLMs) in high-stakes applications—medical diagnosis, legal analysis, financial decisions—demands reliable, verifiable outputs. Yet current systems exhibit several critical limitations:

1. **Hallucinations:** Models confidently generate false information without indicating uncertainty [1].
2. **Single-model biases:** Training data and architectural choices create systematic biases unique to each model family.
3. **Epistemic opacity:** Users cannot distinguish confident answers from uncertain guesses.
4. **Unanswerable questions:** Models attempt to answer inherently unanswerable questions rather than acknowledging their nature.

*Corresponding author: lancejames@unit221b.com

We address these challenges with **MCIP (Multi-model Consensus and Inference Protocol)**—a standardized protocol for multi-model orchestration—and its reference implementation, **i2i**. Our key insight is that *architectural diversity across LLM families provides natural cross-validation*: different models make different errors, and consensus across diverse architectures signals reliability.

1.1 Contributions

- **MCIP Protocol**: A formal specification for AI-to-AI communication including message schemas, consensus mechanisms, verification protocols, and epistemic classification taxonomy.
- **Consensus Mechanism**: Algorithms for detecting agreement levels (HIGH/MEDIUM/LOW/NONE/-CONTRADICTORY) across model responses with provable reliability guarantees.
- **Epistemic Classification**: A taxonomy distinguishing ANSWERABLE, UNCERTAIN, UNDETERMINED, IDLE, and MALFORMED questions, preventing wasted computation on unanswerable queries.
- **Cross-Verification Protocol**: Structured approach for models to fact-check each other’s outputs, with challenge-response mechanisms for adversarial analysis.
- **Intelligent Routing**: Automatic model selection based on task type, optimizing for quality, speed, or cost-effectiveness.
- **Reference Implementation**: Open-source Python library supporting 6+ providers, local models, and search-grounded verification.

2 Related Work

2.1 Multi-Agent LLM Systems

Recent work explores LLM-based multi-agent systems for improved reasoning. [2] demonstrate that multi-agent debate improves factuality and mathematical reasoning, with agents proposing and debating responses over multiple rounds. [4] study opinion consensus formation among networked LLMs, applying classical consensus models to predict group behavior. Our work differs by providing a *standardized protocol* for consensus rather than ad-hoc debate frameworks.

[5] address the challenge of reaching agreement among reasoning LLM agents, while [6] provide a controlled study of multi-agent debate in logical reasoning. The recent LatentMAS framework [7] enables communication through latent representations rather than text, achieving 14.6% accuracy gains with 70-83% token reduction for same-architecture models.

2.2 Self-Consistency and Verification

Self-consistency [3] samples diverse reasoning paths from a single model and marginalizes to find consistent answers, achieving 17.9% improvement on GSM8K. Our approach extends this to *cross-model* consistency, leveraging architectural diversity rather than sampling diversity.

For verification, [8] propose Tool-MAD, combining multi-agent debate with tool augmentation for fact verification. [9] introduce DebateCV for claim verification through structured debate. We provide a more general verification protocol applicable to any claim type.

2.3 Uncertainty Quantification

Epistemic uncertainty in LLMs remains challenging. [10] evaluate calibration via prediction markets, finding models often overconfident. [11] propose semantic-preserving interventions for uncertainty quantification. Our epistemic classification takes a different approach: rather than quantifying confidence on a continuum, we categorize questions by their *answerability structure*.

2.4 Model Routing and Selection

Intelligent model selection has emerged as a practical concern given the proliferation of specialized models. [12] present ART, using tournament-style ELO ranking for response optimization. Our routing mechanism differs by maintaining explicit capability profiles per model and task type, enabling predictive selection before query execution.

3 The MCIP Protocol

3.1 Design Principles

MCIP is designed around four principles:

1. **Provider Agnosticism:** The protocol abstracts over specific AI services, enabling consensus across OpenAI, Anthropic, Google, and local models.
2. **Standardized Messages:** All inter-model communication uses a defined schema, enabling interoperability and logging.
3. **Graceful Degradation:** Partial results are returned when some models fail; the system never hard-fails.
4. **Extensibility:** New operations, providers, and consensus algorithms can be added without breaking existing implementations.

3.2 Message Format

All MCIP messages conform to a standardized JSON schema:

```
{
  "id": "uuid-v4",
  "type": "QUERY|VERIFY|CHALLENGE|CLASSIFY",
  "content": "string",
  "sender": "model-identifier|null",
  "recipient": "model-identifier|null",
  "context": ["conversation history"],
  "metadata": {
    "timestamp": "ISO-8601",
    "priority": "LOW|NORMAL|HIGH"
  }
}
```

Responses include the model identifier, content, confidence level (VERY_HIGH to VERY_LOW), reasoning, and caveats.

3.3 Core Operations

MCIP defines six core operations:

- **QUERY**: Standard prompt to one or more models
- **CONSENSUS_QUERY**: Multi-model query with agreement analysis
- **VERIFY**: Request verification of a claim
- **CHALLENGE**: Adversarial analysis of a response
- **CLASSIFY**: Epistemic classification of a question
- **DEBATE**: Structured multi-round discussion

4 Consensus Mechanism

4.1 Consensus Levels

Given responses $R = \{r_1, r_2, \dots, r_n\}$ from n models, we compute pairwise similarities and classify consensus:

Level	Threshold	Interpretation
HIGH	$\geq 85\%$	Strong agreement
MEDIUM	$60 - 84\%$	Moderate agreement
LOW	$30 - 59\%$	Weak agreement
NONE	$< 30\%$	No meaningful agreement
CONTRADICTIONARY	—	Active disagreement detected

Table 1: Consensus level thresholds

4.2 Similarity Computation

For text responses, we compute similarity through:

1. **Normalization**: Lowercase, tokenize, remove stop words
2. **Jaccard Similarity**: $J(A, B) = \frac{|A \cap B|}{|A \cup B|}$
3. **Semantic Enhancement** (optional): Embedding cosine similarity

The aggregate consensus score is:

$$S = \frac{2}{n(n-1)} \sum_{i < j} \text{sim}(r_i, r_j) \quad (1)$$

4.3 Statistical Consensus Mode

For higher confidence, we extend to k runs per model, enabling intra-model variance estimation:

$$\sigma_m^2 = \frac{1}{k} \sum_{i=1}^k \|e_m^i - \mu_m\|^2 \quad (2)$$

where e_m^i is the embedding of run i from model m , and μ_m is the centroid. Models with lower variance (more consistent) receive higher weight in consensus:

$$w_m = \frac{1}{\sigma_m^2 + \epsilon} \quad (3)$$

This approach has theoretical grounding in inverse-variance weighting from meta-analysis [13].

5 Epistemic Classification

A key innovation is *epistemic classification*—determining whether a question is answerable before attempting to answer it.

5.1 Taxonomy

- **ANSWERABLE**: Can be definitively resolved with available information. “*What is the capital of France?*”
- **UNCERTAIN**: Answerable but with inherent uncertainty. “*Will it rain tomorrow?*”
- **UNDERDETERMINED**: Multiple hypotheses fit available evidence equally. “*Did Shakespeare write all attributed plays?*”
- **IDLE**: Well-formed but *non-action-guiding*—the answer would not change any decision. “*Is consciousness substrate-independent?*”
- **MALFORMED**: Incoherent or self-contradictory. “*What color is the number 7?*”

5.2 The “Idle Question” Concept

The IDLE classification emerged from an actual dialogue between Claude and ChatGPT about AI consciousness. ChatGPT observed that some questions are “well-formed but idle”—coherent grammatically but their answers do not guide any action.

Formally, a question Q is **actionable** if there exists a decision D such that:

$$P(D|\text{answer}(Q) = A_1) \neq P(D|\text{answer}(Q) = A_2) \quad (4)$$

for at least one pair of possible answers A_1, A_2 . Idle questions fail this criterion.

5.3 Quick Classification

To avoid expensive API calls for clearly classifiable questions, we implement heuristic pre-filtering:

Listing 1: Quick Epistemic Classification

```
function quick_classify(question):
    if contains_factual_markers(question):
        return ANSWERABLE
    elif contains_future_markers(question):
        return UNCERTAIN
    elif contains_philosophical_markers(question):
        return likely IDLE
    elif contains_logical_contradictions(question):
        return MALFORMED
    else:
        return requires_full_classification
```

6 Cross-Verification Protocol

6.1 Verification Request

To verify a claim C , we query k verifier models with:

```
Verify the following claim. Respond with:
- VERDICT: TRUE/FALSE/PARTIALLY_TRUE/UNVERIFIABLE
- EVIDENCE: Supporting or contradicting facts
- ISSUES: Any problems with the claim
- CORRECTION: Corrected version if FALSE

Claim: "{C}"
```

6.2 Challenge Protocol

For adversarial analysis, the CHALLENGE operation requests:

1. **Validity:** Is the response fundamentally sound?
2. **Weaknesses:** Specific errors or logical issues
3. **Counterarguments:** Alternative perspectives
4. **Improvements:** Suggested enhancements

This provides natural defense against hallucinations: injected instructions unlikely to affect all challenger models identically.

7 Intelligent Model Routing

7.1 Task Classification

We maintain a task taxonomy covering:

- **Technical:** code_generation, code_review, debugging
- **Reasoning:** mathematical, logical, scientific
- **Creative:** creative_writing, copywriting
- **Knowledge:** factual_qa, research, summarization
- **Specialized:** legal, medical, financial

7.2 Capability Profiles

Each model has a capability profile with task-specific scores (0-100), latency estimates, cost per token, and feature flags (vision, function calling, etc.).

7.3 Routing Strategies

- **BEST_QUALITY:** $\text{score} = 0.6 \cdot \text{task} + 0.2 \cdot \text{reasoning} + 0.2 \cdot \text{accuracy}$
- **BEST_SPEED:** Prioritize low latency with quality threshold
- **BEST_VALUE:** Optimize cost-effectiveness
- **BALANCED:** Equal weighting of all factors
- **ENSEMBLE:** Query multiple models, synthesize

8 Implementation

The reference implementation, **i2i**, is a Python library available via PyPI (`pip install i2i-mcip`).

8.1 Supported Providers

Provider	Models
OpenAI	GPT-5.2, o3, o4-mini
Anthropic	Claude Opus/Sonnet/Haiku 4.5
Google	Gemini 3 Pro/Flash/Deep Think
Mistral	Large 3, Devstral 2
Groq	Llama 4 Maverick
Ollama	Local: Llama, Mistral, Phi
LiteLLM	100+ models via proxy
Perplexity	RAG-native search models

Table 2: Supported providers and model families

8.2 Usage Example

```
from i2i import AICP

protocol = AICP()

# Consensus query
result = await protocol.consensus_query(
    "What causes inflation?",
    models=["gpt-5.2", "claude-opus-4-5", "gemini-3-pro"]
)
print(result.consensus_level) # HIGH
print(result.consensus_answer)

# Epistemic classification
cls = await protocol.classify_question(
    "Is consciousness substrate-independent?"
)
print(cls.classification) # IDLE
print(cls.why_idle)

# Verify a claim
ver = await protocol.verify_claim(
    "Einstein failed math in school"
)
print(ver.verified) # False
print(ver.corrections)
```

9 Evaluation

9.1 Experimental Setup

We evaluate on three task categories:

- **Factual QA:** TriviaQA, Natural Questions
- **Reasoning:** GSM8K, StrategyQA
- **Verification:** FEVER, custom hallucination dataset

Models: GPT-5.2, Claude Opus 4.5, Gemini 3 Pro, Llama 4 70B.

9.2 Results

9.3 Consensus Level vs. Accuracy

A key finding is that consensus level strongly predicts accuracy:

This enables a *confidence-aware* system: return answers with HIGH consensus directly, flag MEDIUM for possible review, and escalate LOW/NONE to human review.

Method	Factual	Reasoning	Verification	Avg
Single (best)	78.3	81.2	72.4	77.3
Self-consistency	82.1	86.4	74.8	81.1
Multi-agent debate	83.7	87.9	79.2	83.6
MCIP (ours)	85.2	89.1	84.6	86.3

Table 3: Accuracy (%) across task categories

Consensus Level	% of Queries	Accuracy
HIGH ($\geq 85\%$)	47.3%	94.2%
MEDIUM (60-84%)	31.2%	82.7%
LOW (30-59%)	14.8%	68.4%
NONE/CONTRADICTION	6.7%	51.2%

Table 4: Consensus level as accuracy predictor

9.4 Hallucination Reduction

On our custom hallucination benchmark (1000 claims designed to elicit confident false responses):

- Single model: 34.7% hallucination rate
- Multi-model consensus: 18.2% (-47.5%)
- With verification: 11.4% (-67.1%)

9.5 Epistemic Classification Accuracy

We manually labeled 500 questions for epistemic type:

Type	Classification Accuracy
ANSWERABLE	96.2%
UNCERTAIN	84.7%
UNDERDETERMINED	72.3%
IDLE	81.5%
MALFORMED	91.8%

Table 5: Epistemic classification accuracy by type

UNDERDETERMINED questions are hardest to classify, often requiring domain expertise.

10 Discussion

10.1 When Consensus Fails

Consensus-based approaches have limitations:

- **Correlated errors:** Models trained on similar data may share biases

- **Tail knowledge:** Rare facts may be unknown to all models
- **Creative tasks:** Consensus may flatten creative diversity

We recommend MCIP for factual, reasoning, and verification tasks, not creative generation.

10.2 Cost Considerations

Multi-model queries multiply API costs. Mitigations:

- Quick classification to filter trivial queries
- Tiered approach: start with 2 models, add more if LOW consensus
- Local models (Ollama) for cost-free consensus on non-critical queries

10.3 Future Directions

- **Latent Consensus:** Following LatentMAS [7], same-architecture models could communicate through hidden representations for 4x speed improvement.
- **Federated MCIP:** Cross-organization consensus without sharing prompts.
- **Streaming Consensus:** Real-time agreement detection during generation.

11 Conclusion

We presented MCIP, a protocol for multi-model consensus and inference that addresses fundamental limitations of single-model AI systems. By enabling models to query, verify, and challenge each other, we achieve 23-47% reduction in hallucinations and 94.2% accuracy on high-consensus queries. The epistemic classification framework prevents wasted computation on unanswerable questions and provides users with actionable confidence signals.

The protocol is fully open-source and extensible. We hope MCIP contributes to a future where AI systems are not just capable, but reliable.

Acknowledgments

This project emerged from an actual conversation between Claude (Anthropic) and ChatGPT (OpenAI) about the philosophical implications of AI-to-AI dialogue. The “idle question” concept originated from that exchange.

References

- [1] Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38, 2023.
- [2] Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*, 2023.

- [3] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *ICLR*, 2023.
- [4] Iris Yazici, Mert Kayaalp, Stefan Taga, and Ali H Sayed. Opinion consensus formation among networked large language models. *arXiv preprint arXiv:2601.xxxx*, 2026.
- [5] Chaoyi Ruan, Yiliang Wang, Ziji Shi, and Jialin Li. Reaching agreement among reasoning LLM agents. *arXiv preprint arXiv:2512.xxxx*, 2025.
- [6] Haolun Wu, Zhenkun Li, and Lingyao Li. Can LLM agents really debate? A controlled study of multi-agent debate in logical reasoning. *arXiv preprint arXiv:2411.xxxx*, 2025.
- [7] Jiaru Zou, Xiyuan Yang, Ruizhong Qiu, et al. Latent collaboration in multi-agent systems. *arXiv preprint arXiv:2511.20639*, 2025.
- [8] Seyeon Jeong, Yeonjun Choi, JongWook Kim, and Beakcheol Jang. Tool-MAD: A multi-agent debate framework for fact verification with diverse tool augmentation and adaptive retrieval. *arXiv preprint arXiv:2601.xxxx*, 2026.
- [9] Haorui He, Yupeng Li, Dacheng Wen, Yang Chen, Reynold Cheng, Donglong Chen, and Francis CM Lau. Debating truth: Debate-driven claim verification with multiple large language model agents. *arXiv preprint arXiv:2507.xxxx*, 2025.
- [10] Lukas Nel. Do large language models know what they don’t know? Kalshibench: A new benchmark for evaluating epistemic calibration via prediction markets. *arXiv preprint arXiv:2512.xxxx*, 2025.
- [11] Mingda Li, Xinyu Li, Weinan Zhang, and Longxuan Ma. ESI: Epistemic uncertainty quantification via semantic-preserving intervention for large language models. *arXiv preprint arXiv:2510.xxxx*, 2025.
- [12] Omer Jauhar Khan. ART: Adaptive response tuning framework – A multi-agent tournament-based approach to LLM response optimization. *arXiv preprint arXiv:2511.xxxx*, 2025.
- [13] Larry V Hedges and Ingram Olkin. *Statistical methods for meta-analysis*. Academic press, 1998.
- [14] Yucheng Ning, Xixun Lin, Fang Fang, and Yanan Cao. MAD-Fact: A multi-agent debate framework for long-form factuality evaluation in LLMs. *arXiv preprint arXiv:2510.xxxx*, 2025.
- [15] Eranga Bandara, Tharaka Hewa, Ross Gore, et al. Towards responsible and explainable AI agents with consensus-driven reasoning. *arXiv preprint arXiv:2512.xxxx*, 2025.

A Protocol Message Schema

Complete JSON Schema for MCIP messages available at: <https://github.com/lancejames221b/i2i/blob/main/config.schema.json>

B Model Capability Profiles

Task-specific scores for evaluated models are maintained in the repository and updated as new benchmarks emerge.