

QPLIX Links – Web Resource Documentation

Overview

This HTML web resource is embedded as an IFrame inside a Dynamics 365 form. It reads a UID from the form field `mhwrmb_qplix_ve_uid`, retrieves a URL configuration from the `nev_config` table, and renders one clickable button per configured URL.

How It Works

Step 1 – Read UID from Form

On page load, the script reads the field `mhwrmb_qplix_ve_uid` from the parent form. If the field is empty, the web resource renders nothing and exits silently.

Step 2 – Retrieve URL Configuration

The script calls the Dynamics 365 Web API to retrieve the config record from the `nev_config` table:

- **Table:** `nev_config`
- **Filter:** `nev_key = 'idQplixBaseUrl'`
- **Value column:** `nev_value_ntext` (JSON format)

Step 3 – Build & Render Links

The JSON is parsed and iterated. For each entry, the placeholder `{UID}` in the URL is replaced with the actual UID from the form. A button is rendered per entry using `urlDescription` as the label.

Configuration JSON Structure

The JSON stored in `nev_value_ntext` must follow this structure:

```
{
  "QplixAnalytics": {
    "urlDescription": "Open in QPLIX - Analytics",
    "url":
      "https://portal.marcuardheritage.com/CoreUI/#/administration/legalEntities/editLegalEntity?id={UID}"
  },
  "QplixNeoPortal": {
    "urlDescription": "Open in Neo Portal",
    "url": "https://portal.marcuardheritage.com/neo/#/story/overview?perspectiveId={UID}"
  }
}
```

Field	Description	Example
Key (e.g. <code>QplixAnalytics</code>)	Unique identifier for the entry	<code>QplixAnalytics</code>
<code>urlDescription</code>	Button label displayed to the user	<code>Open in QPLIX - Analytics</code>
<code>url</code>	Target URL – use <code>{UID}</code> as placeholder for the record UID	<code>https://portal.marcuardheritage.com/...?id={UID}</code>

Maintenance

To keep the buttons working, the following conditions must be met:

1. Config Record in `nev_config`

A record must exist in the `nev_config` table with:

- `nev_key = idQplixBaseUrl`
- `nev_value_ntext` = valid JSON with at least one entry containing `urlDescription` and `url`

2. URL Contains `{UID}` Placeholder

Each URL in the JSON must contain the exact placeholder `{UID}` (case-sensitive). This is replaced at runtime with the value from the form field.

3. Form Field `mhwrm_b_qplix_ve_uid`

The field `mhwrm_b_qplix_ve_uid` must exist on the form and contain a valid UID for the buttons to appear. If the field is empty, no buttons are shown.

4. Web Resource Registered on the Form

The web resource must be added as an `IFrame` in the Form Editor with the option **"Pass record object-type code and unique identifier as parameters"** enabled.

Adding a New Link

To add a new button, add a new entry to the JSON in `nev_value_ntext`. **No code changes are required.**

```
{
  "QplixAnalytics": {
    "urlDescription": "Open in QPLIX - Analytics",
    "url":
      "https://portal.marcuardheritage.com/CoreUI/#/administration/legalEntities/editLegalEntity?id={UID}"
  },
  "QplixNeoPortal": {
```

```
    "urlDescription": "Open in Neo Portal",  
    "url": "https://portal.marcuardheritage.com/neo/#/story/overview?  
perspectiveId={UID}"  
  },  
  "QpplxReports": {  
    "urlDescription": "Open Reports",  
    "url": "https://portal.marcuardheritage.com/reports?id={UID}"  
  }  
}
```

The new button will appear automatically without any changes to the web resource file.