

Base elements

<html>	
o <head>	
▪ <title>	
▪ <meta>	
▪ <link>	
o <body>	
o <script>	
<div>	generic block element
	generic inline element

Sectioning content

<article>	an independent part of a the page
<aside>	content that is tangentially related to the content around the aside element
<nav>	section with navigation links
<section>	generic section of an app/document
<header>	group of introductory or navigational aids.
<footer>	footer for its nearest ancestor sectioning content
<dialog>	for pop-ins / modal windows

Text hierarchy

<h1>, <h2>, <h3>, <h4>, <h5>, <h6>	headings (respect hierarchy !)
<p>	paragraph block
<small>	smaller importance, by default has a lower font size
	high importance, by default in bold
	put emphasis on text, by default in <i>italic</i>
	indicate a deleted content, by default with a line through
<mark>	highlight text, by default in yellow

Text classification

<a>	link, use it with href attribute
<abbr>	abbreviation, use it with title attribute
<time>	used with datetime attribute to refer to a date and time
<address>	used to refer to a postal address
<q>, <blockquote>	quotes, either inline or in a block, by default “surrounded with quotes”
<pre>	preformatted text, preserve whitespaces, by default in monospace
<code>	snippet of code, by default in <monospace>

Lists

	unordered list
	ordered list
	list item
<dl>	list of terms/definitions. Terms are in <dt> followed directly by definitions in <dd>
<menu>	list of menu actions used for navigation or application controls
<datalist>	list of autocomplete suggestions in <option> children to link with <input>

Tables

<table>	<i>use it only for data tables !</i>
<thead>, <tbody>, <tfoot>	header, body and footer of a <table>
<tr>	table row
<th>	column heading in a <tr> in a <thead>
<td>	data cell heading in a <tr> in a <tbody>

Forms

<form>	
<search>	contains a search form
<fieldset>	group a list of inputs
<legend>	caption of a <fielset>
<label>	use with for attribute
<button>	
<textarea>	
<input>	
o types:	text, number, range, color, search, tel, email, url, datetime, datetime-local, date, month, week, time, checkbox, range
<select>	
o <option>, <optgroup>	
<output>	a computed result

Media and other content

	if you need several sources for an image, use <picture> and <source> tags
<audio>, <video>	Use either the src attribute or <source> children elements.
<svg>	inline vectorial images
<canvas>	used for 2D/3D drawing/scenes
<figure>	wrap around a media or table to link it with a caption inside a <figcaption> tag
<progress>, <meter>	progress bar and scalar value output