

AN ABSTRACT OF THE DISSERTATION OF

Parisa Ataei for the degree of Doctor of Philosophy in Computer Science
presented on June 20, 2021.

Title: Theory and Implementation of a Variational Database Management
System

Abstract approved: _____

Eric Walkingshaw

In this thesis, I present the variational database management system, a formal framework and its implementation for representing variation in relational databases and managing variational information needs. A variational database is intended to support any kind of variation in a database. Specific kinds of variation in databases have already been studied and are well-supported, for example, schema evolution systems address the variation of a database's schema over time and data integration systems address variation caused by accessing data from multiple data sources simultaneously. However, many other kinds of variation in databases arise in practice, and different kinds of variation often interact, but these scenarios are not well-supported by the existing work. For example, neither the schema evolution systems nor the database integration systems can address variation that arises when data sources combined in one database evolve over time.

This thesis collects a large amount of work: It defines the variational database framework and the syntax and denotational semantics of the variational relational algebra, a query language for variational databases. It presents two use cases of the variational database framework that are based on existing data sets and scenarios that are partially supported by existing techniques. It presents the variational database management system which is the implementation of variational databases and variational relational algebra as an abstract layer written in Haskell on top of a traditional RDBMS. It also presents several theoretical results related to the framework and the query language, such as syntax-based equivalence rules that preserve the semantics of a query, a type system for ensuring that a variational query is well-formed with respect to the underlying variational schema, and a confluence property of the variational relational algebra type system with respect to the relational algebra type system.

©Copyright by Parisa Ataei
June 20, 2021
All Rights Reserved

Theory and Implementation of a Variational Database Management System

by

Parisa Ataei

A DISSERTATION

submitted to

Oregon State University

in partial fulfillment of
the requirements for the
degree of

Doctor of Philosophy

Presented June 20, 2021
Commencement June 2021

Doctor of Philosophy dissertation of Parisa Ataei presented on June 20, 2021.

APPROVED:

Major Professor, representing Computer Science

Director of the School of Electrical Engineering and Computer Science

Dean of the Graduate School

I understand that my dissertation will become part of the permanent collection of Oregon State University libraries. My signature below authorizes release of my dissertation to any reader upon request.

Parisa Ataei, Author

ACKNOWLEDGEMENTS

First and foremost, thank you to my advisor Eric Walkingshaw, who had a significant role in forming the researcher and the person I am today. I am forever grateful for your unconditional support (both personally and professionally), guidance, enthusiasm, and encouragement.

rewrite
Mahtab's
and
Saereh's
and Eric's.

A very special thank you to my partner Jeffrey Young for his love, support, and encouragement. Thank you for helping me learn Haskell, discussing research ideas and problems, practicing many presentations, and studying various books and papers with me. Thank you for your support through emotionally tough moments, from dealing with racist policies to depression from a pandemic and a harsh immigration process. I am proud of us for finishing our PhDs together during a pandemic, OSU's lack of support of our group, and immigration process. Thank you for an amazing graduation gift. I cannot wait to get fit again and drop the PhD weight! Thank you for sharing your life with me. I look forward to our life together, out of the brutality of graduate school. It is only uphill from here on out.

Thank you to the many OSU faculty members during my time here. Special thank you to Glencora Borradaile for her unwavering support of graduate students and Martin Erwig for many constructive advice on Programming Languages research. Thank you to the members of my program committee—Martin Erwig, Alan Fern, Amir Nayyeri—for all their support and advice. Thank you to other mentors. Thank you David Christiansen for a great Dependent Typed Languages class and

thank you Jose Calderon for conversation and guidance on building a research career.

Thank you to my strong amazing ladies–Lily Ranjbar, Nasim Adami, Mahtab Aboufazeli, and Saereh Mirzababaei–for their constant help and support during my graduate school years. Thank you Lily and Ali Jafarnejad for your continuous support through the years–from hosting me when I came to the US to throwing me a wedding during a pandemic. Thank you Nasim and Ali Mohtat for your many wise words and kind support–from holding my hand when I was tired of putting up with the unfair single-entrance Visa and was on the edge of leaving the US to present my work in Europe to translating my wedding for my parents. Thank you Mahtab for simply making my life sweeter, both figuratively and literally. Thank you Saereh for being a role model of a strong independent Persian woman. You are inspiring.

Thank you to the many friends for check-ins, deep conversations, professional and personal help, sharing lots of coffee over complaining about grad school, many drinks and dinners, and movie nights including Reyhaneh Shahmohamadi, Wesley [blah], Ben McCamish, Mike McGirr, Beatrice [blah], Mandana Hamidi-Haines, Ralph Haines, Esther and Hamid [blah], Reza Ghaeini, Farzad Zafarani, Hamidreza Maghami, and Hossein Mirzaie. Thank you to collaborators for professional help and feedback including Vahid Ghadakchi, Jose [blah], Arash Termehchy, Qiaoran Li, Fariba Khan. Thank you to the CrossFit 97333 community, especially the 9 am class, and coaches including Derek Eason, Austin [blah], Michael Hernandez, Tanna [blah], Sean [blah], Caitlin Brannen, Joey Kimdon, Katherine Eastlake, Jeremy

[blah], and David and Heidi Evaland. Thank you for providing an environment that allowed me to escape the grad school's problems even just for a couple of hours a week. Thank you for pushing me physically and mentally through lots of tough yet enjoyable workouts. And thank you for being such inspirational individuals in and out of the box. I am very excited to get after it again.

Thank you to my many family members all over the world for your support, hospitality, and care including Maryam Soltanolkotabi, Hamed Asghari, Mahdi Soltanolkotabi, Amirreza Ataei, Mohammad Reza Bazrafshan, Mehri Ataei, Reza Khodadadi, Tahereh Bazrafshan, Mahmood Soltanolkotabi, and my loving sister Parvin Ataei. A very special thank you to my parents for directing me into this path and prioritizing my education over the years. Thank you for giving me a comfortable life and the freedom to grow into the person I am today. I appreciate all your sacrifices and I am deeply sorry for the pain of separation over the last six years. I cannot wait to be reunited with you both.

TABLE OF CONTENTS

	<u>Page</u>
1 Introduction	1
1.1 Motivation and Impact	2
1.1.1 Motivating Example	4
1.1.2 New Instance of Data Variation in Industry	8
1.2 Contributions and Outline of this Thesis	9
2 Background	12
2.1 Relational Databases	13
2.2 The SPC Relational Algebra	17
2.3 Variation Space and Encoding	21
2.4 Annotations and Variational Sets	25
2.5 The Formula Choice Calculus	29
3 Variational Database Framework	31
3.1 Variational Schema	31
3.2 Variational Table	39
3.3 Properties of a Variational Database Framework	43
4 Variational Queries	45
4.1 Variational Relational Algebra	46
4.2 VRA Semantics	53
4.2.1 VRA Configuration	53
4.2.2 Accumulation of Relational Tables to a Variational Table . .	59
4.2.3 VRA Denotational Semantics	65
4.3 VRA Type System	66
4.4 Explicitly Annotating Queries	67
4.5 Variation-Minimization Rules	72
4.6 Variational Relational Algebra Properties	73
4.6.1 Expressiveness	74
4.6.2 Type Safety	75
4.6.3 Variation-Preserving Property at the Semantics Level	77

TABLE OF CONTENTS (Continued)

	<u>Page</u>
5 Variational Database Use Cases	79
5.1 Variation in Space: Email SPL Use Case	82
5.1.1 Variation Scenario: An Email SPL	85
5.1.2 Generating Variational Schema of the Email SPL VDB . . .	86
5.1.3 Populating the Email SPL VDB	90
5.1.4 Email Query Set	93
5.2 Variation in Time: Employee Use Case	99
5.2.1 Variation Scenario: An Evolving Employee Database	100
5.2.2 Generating Variational Schema of the Employee VDB	102
5.2.3 Populating the Employee VDB	103
5.2.4 Employee Query Set	105
5.3 Discussion: Should Variation Be Encoded Explicitly in Databases? . .	109
6 Variational Database Management System (VDBMS)	114
6.1 VDBMS Architecture	114
6.2 SQL Generator	116
6.3 Experiments	119
7 Related Work	120
7.1 Instances of Variation in Databases	120
7.2 Instances of Database Variation Resulted from Software Development	120
7.3 Variational Research	120
8 Conclusion	124
8.1 Future Work	126
8.2 Summary of Contributions	126
Bibliography	126

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
2.1 Relational databases definition	16
2.2 Syntax of relational algebra	20
2.3 Feature expression syntax and evaluation	22
2.4 (Annotated) Variational set configuration and operations	26
3.1 Variational schema definition and configuration	36
3.2 Variational database syntax and configuration	41
4.1 Syntax of variational relational algebra	47
4.2 Configuration of variational queries and conditions	54
4.3 Unique configuration of variational queries	58
4.4 Accumulation function of a set of relational tables with their at- tached configuration into a variational table	60
4.5 Accumulation function of a set of relational tables annotated with a feature expression into a variational table	65
4.6 VRA denotational semantics	66
4.7 Typing rules of variational relational algebra and variational condition	68
4.8 Example of derivation tree to determine the type of a query	69
4.9 Example of derivation tree to determine the type of a query	70
4.10 Explicitly annotating a variational query with a variational schema	71
4.11 Variation minimization rules	73

LIST OF FIGURES (Continued)

<u>Figure</u>		<u>Page</u>
6.1	VDBMS architecture and execution flow of a variational query. The dotted double-line from the input variational query indicates the dependency of passing the variational query to this module only if it is valid. The dashed gray arrows with diamond heads demonstrate an option for the flow of the variational query. The blue filled arrows track the data flow, the green hollow arrows indicate an input to a module.	115

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1.1 Variants of the employee database schema	5
2.1 Example of a relational database	15
2.2 Results of subqueries to build up the query in Example 2.2.1	19
3.1 Examples of encoding variation at the schema level	33
3.2 The role of feature model in a variational table	34
3.3 Variational schema of the motivating example	38
3.4 Example of encoding variation at the content level	40
4.1 Result of a variational query	49
4.2 Result of a variational query	50
4.3 Result of a variational query	51
4.4 Results of relational queries from configuring a variational query . .	56
4.5 Example of step two of table accumulation	62
4.6 Example of step two of table accumulation	62
4.7 Example of step two of table accumulation	63
4.8 Example of step three of table accumulation	64
4.9 Example of the final step of table accumulation	64
5.1 Original Enron email dataset schema	86
5.2 Variational schema of the email VDB	87
5.3 Evolution of an employee database schema	101
5.4 Variational schema of the employee database evolution	102

To my loving parents,

Sedigheh Bazrafshan and Seyed Jalal Ataei.

I count the days to embrace you both in my arms again

(after 2,109 days and still counting).

Chapter 1 Introduction

Managing variation in databases is a perennial problem in database literature and appears in different forms and contexts [51, 10, 15, 24, 12] and it is unavoidable [49]. Variation in databases mainly arises when multiple database instances conceptually represent the same database but differ in their schema, content, or constraints. Specific kinds of variation in databases have been addressed by context-specific solutions, such as schema evolution [39, 14, 7, 48, 41], data integration [20], and database versioning [13, 31]. However, there are no generic solution that addresses all kind of variation in databases. We motivate the need for a generic solution to variation in databases in Section 1.1.

The major contribution of this thesis is the *variational database* framework, a generic relational database framework that explicitly accounts for database variation, and *variational relational algebra*, a query language for our framework that allows for information extraction from a variational database. The framework is generic because it can encode any kind of variation in databases. Additionally and more importantly, it is designed such that it can satisfy any information need that a user may have in a variational database scenario.

In addition to a formal description of the variational database framework and variational relational algebra and some theoretical results, this thesis distributes and presents two variational data sets (including both a variational database and

a set of queries) as well as a *variational database management system* that implements the variational database framework as an abstraction layer on top of a traditional relational database management system in Haskell. Section 1.2 enumerates the specific contributions in the context of an outline of the structure of the rest of the thesis.

1.1 Motivation and Impact

Managing variation in databases is a perennial problem that appears in different forms and contexts [51, 10, 15, 24, 12]. In databases, variation arises when several database instances, which may differ in schema, content, or constraints, conceptually represent the same database. Existing work on database variation focuses on specific kinds of variation such as schema evolution [39, 14, 7, 48, 41], data integration [20], and database versioning [13, 31]. These works provide solutions specific to the kinds of variation they address, but do not provide a general-purpose solution to managing variation in databases. This is a problem because new kinds of variation frequently arise and different kinds of variation often interact, and the existing solutions are often ill-suited to these scenarios.

Schema evolution is an example of a kind of variation in databases that is well-supported [39, 14, 7, 48, 41]. In the schema evolution scenario, a database’s schema changes over time as the database is extended or refactored to support new information needs, and the goal is to automatically migrate data and queries to new versions of the database. Thus, schema evolution is a kind of *variation* over

the dimension of time, and each version of the database can be viewed as a *variant* of the same database.

However, other kinds of database variation are less well supported. One example arises in the context of *software product lines* (SPLs) [5]. An SPL arises when the same code base is used to produce multiple different variants of a software system, customized with different sets of features or tailored for different clients. Naturally, the data requirements of each variant of an SPL may differ [47]. SPL researchers have developed various encodings that allow describing variation in the data model among variants by annotating elements of the model with features from the SPL [47, 45, 2]. These solutions can generate a database schema variant for each software variant of the SPL. However, these solutions address only variation in the data model but do not extend to the level of data or queries. The lack of variation support in queries leads to unsafe techniques such as encoding different variants of query through string munging, while the lack of variation support in data precludes testing with multiple variants of a database at once.

Worse still is when multiple kinds of variation interact. Although structural variation over time is well-supported via schema evolution, and structural variation in “space” is partially supported by recent SPL research, there is no support for the inevitable evolution of an SPL’s variational data model [29]. Nor do existing approaches support variation across all levels of a relational database: schema, queries, and content. In our previous work, we have argued that schema evolution, SPL-like variation, and other forms of database variation, such as data integration and database versioning, are all facets of a similar problem that can be addressed

by *treating variation as a general and orthogonal concern* in relational databases [8, 9, 10]. A significant advantage of treating different kinds of variation uniformly is that it is easy to support the interaction of multiple kinds of variation, and to coordinate variation in structure with corresponding variation in queries and content. We illustrate these aspects throughout the thesis using a motivating example described in Section 1.1.1.

To summarize, variation in databases is abundant and inexorable [49] and arises in many different contexts. Existing solutions are specialized to address specific kinds of variation but do not support the interaction of multiple kinds of variation, nor many variation scenarios that cut across different levels of a database. The lack of support for these scenarios negatively impact database administrators, data analysts, and software developers [29].

1.1.1 Motivating Example

In this section, we motivate the interaction of two kinds of variation in databases resulting in a new kind: database-backed software produced by an SPL and schema evolution. An SPL uses a set of boolean variables called *features* to indicate the functionalities that each software variant requires. Consider an SPL that generates management software for companies. It has a feature *edu* that indicates whether a company provides educational means such as courses for its employees. Software variants in which *edu* is disabled (i.e., *edu* = **false**) only provide basic functionalities while ones in which *edu* is enabled provide educational functionalities in

Table 1.1: Schema variants of the employee database developed for multiple software variants by an SPL. Note that an **educational** database variant must contain a **basic** database variant too.

(a) Database schema variants for **basic** software variants.

Temporal Features	basic Database Schema Variants
V_1	<i>engineerpersonnel</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>) <i>otherpersonnel</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>) <i>job</i> (<i>title</i> , <i>salary</i>)
V_2	<i>empacct</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>) <i>job</i> (<i>title</i> , <i>salary</i>)
V_3	<i>empacct</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptno</i>) <i>job</i> (<i>title</i> , <i>salary</i>) <i>dept</i> (<i>deptname</i> , <i>deptno</i> , <i>managerno</i>) <i>empbio</i> (<i>empno</i> , <i>sex</i> , <i>birthdate</i>)
V_4	<i>empacct</i> (<i>empno</i> , <i>hiredate</i> , <i>title</i> , <i>deptno</i> , <i>std</i> , <i>instr</i>) <i>job</i> (<i>title</i> , <i>salary</i>) <i>dept</i> (<i>deptname</i> , <i>deptno</i> , <i>managerno</i>) <i>empbio</i> (<i>empno</i> , <i>sex</i> , <i>birthdate</i> , <i>name</i>)
V_5	<i>empacct</i> (<i>empno</i> , <i>hiredate</i> , <i>title</i> , <i>deptno</i> , <i>std</i> , <i>instr</i> , <i>salary</i>) <i>dept</i> (<i>deptname</i> , <i>deptno</i> , <i>managerno</i> , <i>stdnum</i> , <i>instrnum</i>) <i>empbio</i> (<i>empno</i> , <i>sex</i> , <i>birthdate</i> , <i>firstname</i> , <i>lastname</i>)

(b) Database schema variants for **educational** software variants.

Temporal Feature	educational Database Schema Variants
T_1	<i>course</i> (<i>coursename</i> , <i>teacherno</i>) <i>student</i> (<i>studentno</i> , <i>coursename</i>)
T_2	<i>course</i> (<i>courseno</i> , <i>coursename</i> , <i>teacherno</i>) <i>student</i> (<i>studentno</i> , <i>courseno</i>)
T_3	<i>course</i> (<i>courseno</i> , <i>coursename</i>) <i>teach</i> (<i>teacherno</i> , <i>courseno</i>) <i>student</i> (<i>studentno</i> , <i>courseno</i> , <i>grade</i>)
T_4	<i>ecourse</i> (<i>courseno</i> , <i>coursename</i>) <i>course</i> (<i>courseno</i> , <i>coursename</i> , <i>time</i> , <i>class</i>) <i>teach</i> (<i>teacherno</i> , <i>courseno</i>) <i>student</i> (<i>studentno</i> , <i>courseno</i> , <i>grade</i>)
T_5	<i>ecourse</i> (<i>courseno</i> , <i>coursename</i> , <i>deptno</i>) <i>course</i> (<i>courseno</i> , <i>coursename</i> , <i>time</i> , <i>class</i> , <i>deptno</i>) <i>teach</i> (<i>teacherno</i> , <i>courseno</i>) <i>take</i> (<i>studentno</i> , <i>courseno</i> , <i>grade</i>)

addition to the basic ones. Thus, this SPL yields two types of variants: **basic** and **educational**.

Each variant of this SPL needs a database to store information about employees, but SPL features impact the database: While **basic** variants do not need to store any education-related records **educational** variants do. refs here have changed.

We visualize the impact of features on the schema variants in Table 1.1: It has two schema types: **basic**, shown in Table 1.1a, and **educational**, shown in Table 1.1b. A **basic** schema variant contains only the schema in one of the cells in Table 1.1a while an **educational** schema variant consists of two sub-schemas: one from the **basic** and another from Table 1.1b. For example, the yellow highlighted cells include relation schemas for an **educational** schema variant.

Rows of Table 1.1 indicate the evolution of schema variants in time. To capture the evolution of the software and its database we add two disjoint sets of features which again are boolean variables. The temporal feature sets are disjoint to allow individual paces for the evolution of each type of schema. For example, yellow cells of Table 1.1 show a valid schema variant even though the **basic** and **educational** sub-schemas are not in the same row.

refs here have changed. mot to mot-basic

Now, consider the following scenario: In the initial design of the **basic** database, SPL DBAs settle on three tables *engineerpersonnel*, *otherpersonnel*, and *job*; shown in Table 1.1a and associated with feature V_1 . After some time, they decide to refactor the schema to remove redundant tables, thus, they combine the two

relations *engineerpersonnel* and *otherpersonnel* into one, *empacct*; associated with feature V_2 . Since some clients' software relies on a previous design the two schemas have to coexist in parallel. Therefore, the existence (presence) of *engineerpersonnel* and *otherpersonnel* relations is *variational*, i.e., they only exist in the **basic** schema when $V_1 = \mathbf{true}$. This scenario describes *component evolution*: developers update, refactor, and improve components including the database [29].

Now, consider the case where a client that previously requested a **basic** variant of the management software has recently added courses to educate its employees in specific subjects. Hence, an SPL developer needs to enable the *edu* feature for this client, forcing the adjustment of the schema variant to **educational**. This case describes *product evolution*: database evolution in SPL resulted from clients adding/removing features/components [29].

The situation is further complicated since the **basic** and **educational** schemas are interdependent: Consider the **basic** schema variant for feature V_4 . Attributes *std* and *instr* only exists in the *empacct* relation when *edu* = **true**, represented by a dash-underline, otherwise the *empacct* relation has only four attributes: *empno*, *hiredate*, *title*, and *deptno*. Hence, the presence of attributes *std* and *instr* in *empacct* relation is *variational*, i.e., they only exist in *empacct* relation when *edu* = **true**.

DO NOT
ERASE
THIS!!!

Our example demonstrates how different kinds of variation interact with each other, an indispensable consequence of modern software development. The described interaction is similar to a recent scenario we discussed with an industry contact in Section 1.1.2.

1.1.2 New Instance of Data Variation in Industry

New variational scenarios could appear, either from combination of other scenarios or even a new scenario could reveal itself. For example, the following is a scenario we recently discussed with an industry contact: A software company develops software for different networking companies and analyzes data from its clients to advise them accordingly. The company records information from each of its clients' networks in databases customized to the particular hardware, operating systems, etc. that each client uses. The company analysts need to query information from all clients who agreed to share their information, but the same information need will be represented differently for each client. This problem is essentially a combination of the SPL variation problem (the company develops and maintains many databases that vary in structure and content) and the data integration problem (querying over many databases that vary in structure and content). However, neither the existing solutions from the SPL community nor database integration address both sides of the problem. Currently the company manually maintains variant schemas and queries, but this does not take advantage of sharing and is a major maintenance challenge. With a database encoding that supports explicit variation in schemas, content, and queries, the company could maintain a single variational database that can be configured for each client, import shared data into a variational database, and write variational queries over the variational database to analyze the data, significantly reducing redundancy across clients.

1.2 Contributions and Outline of this Thesis

The high level goal of this thesis is to emphasize the need for a variation-aware database framework and to present one such framework. Therefore, in addition to the formal definition of the framework and query language, it also provides variational data sets (including both the variational database and a set of queries) to illustrate the feasibility of the proposed framework. Furthermore, it illustrates various approaches to implement such a framework and compares their performance.

The rest of this section describes the structure of this thesis, enumerating the specific contribution that each chapter makes.

Chapter 2 (*Background*) introduces several concepts and terms that are the basis of this thesis. It describes types and how to interpret them. It explains relational databases with assumptions that are held throughout the thesis and relational algebra. It also describes various ways of incorporating variation into elements of a database.

Chapter 3 (*Variational Database Framework*) describes a formal model of *variational databases* (VDBs), whose structure are given by a *variational schema* (Section 3.1) and whose content are given by *variational tables* (Section 3.2). In essence, a variational database gathers multiple relational databases in one place. Section 3.1 and Section 3.2 also describe how a relational database can be generated from a VDB. Finally, Section 3.3 defines properties of a well-formed VDB.

Chapter 4 (*Variational Queries*) describes the need for a query language to extract information from a VDB. It formally defines *variational relational algebra*

(VRA) as a query language for VDB in Section 4.1. It also defines the denotational semantics of VRA through the semantics of relational algebra in Section 4.2. Additionally, it describes a *static type system* for ensuring that all variants of a query are compatible with the corresponding variants of the VDB in Section 4.3. Then, it describes an *explicitly annotating queries* function to relieve the user from repeating the VDB’s variation in their queries in Section 4.4. It also defines a set of syntactic-based rules to *minimize variation* in variational queries in Section 4.5. Finally, it discusses the properties of the VRA in Section 4.6 including its expressiveness and type safety.

Chapter 5 (*Variational Database Use Cases*) aims at guiding an expert through generating a VDB and writing variational queries for a variation scenario where unfortunately the database variants do not exist and thus, generating the VDB requires the expert knowledge and cannot be automated. It details two such variation scenario and introduces two use cases of VDB, one over space (adopts the email SPL described by Hall [28] and explained in Section 5.1) and another over time (adopts the evolution of an employee schema described by Moon et al. [41] and explained in Section 5.2), in addition to how a VDB can store all database variants in a single database and how variational queries can capture various information needs over different database variants in a single query. It also describes how the VDBs were systematically generated and how the variational queries were adapted and adjusted from papers describing the variation scenario. The last section of this chapter, Section 5.3, discusses the question “should variation be encoded explicitly in databases?” through the lessons learned while generating these use cases.

write this
after you
finish the
chapter.

[Chapter 6]

Chapter 7 (*Related Work*) collects research related to different kinds of variation in databases and other related variational research.

Finally, Chapter 8 (*Conclusion*) briefly presents ...

write this
after you
finish the
chapter
and do
your re-
search.

write this
after you
finish the
chapter.

Chapter 2 Background

The core of this thesis is injecting a new aspect to relational databases: *variation*. Thus, the goals of this chapter are twofold: first, to introduce how variation is encoded and represented in our variational database framework; second, to provide the reader with the concepts and notations used to build up the main contributions of this thesis, mainly relational databases and relational algebra and approaches used to add variation to them.

Throughout the thesis, we use types when defining concepts. A type is a set of possible values. For example, the type **Int** denotes all possible integers. In our formalization, we use the notation of $i \in \mathbf{Int}$ to state that the variable i is of type **Int**. Types can be more general. Consider the type **Set a** that indicates the set all sets of values of type **a**. Here, **a** is type variable and stands for any possible type. Note that concrete types start with a capital letters but type variables do not. For example, the type **Set Int** is the type of sets of integers and it has values such as $\{1, 3, 4\}$ and $\{\}$. We also use type synonyms for simplicity. For example, instead of referring to **Set Int** we can give it a new name (**SetInt** = **Set Int**) and refer to it with the new name **SetInt**. Sometimes we must extend a type with an additional “bottom” element \perp and to account for this extension at the type level we subscript the type with \perp . For example, \mathcal{I}_{\perp} denotes the extension of the type \mathcal{I} with \perp . Furthermore, sometimes we pair two types together. For

pair and
function
types

example, a variable of type **(Int, String)** can take the value $(3, \text{"three"})$. Finally, we use function types to provide the type signature of functions. For example, the function $id : \mathbf{a} \rightarrow \mathbf{a}$ states that the function id takes a value of type \mathbf{a} and returns a value of type \mathbf{a} .

Throughout the thesis, we discuss relational concepts and their variational counterparts. For clarity or when it is unclear from context, we use an underline to distinguish a non-variational entity from its variational counterpart, both at the value level and the type level, e.g., \underline{x} is a non-variational entity while x is its variational counterpart, if it exists.

Section 2.1 describes the database model of relational databases and the specification of the structure used to store the data [1]. Section 2.2 describes the relational algebra, a query language used to query relational databases [1]. Section 2.3 defines our encoding of the variation space used in variational database and how we describe parts of that space using propositional formulas of boolean variables [9, 8]. Finally, we introduce the main techniques used to incorporate variation into our variational database framework. Section 2.4 introduces variation into sets which forms the basis of the variational database framework [23, 56, 8] and Section 2.5 describes the formula choice calculus used to incorporate variation into relational algebra [32].

2.1 Relational Databases

We introduce relational databases concepts, which variational databases are based on. Table 2.1 represents an example relational database instance corresponding to V_2 introduced in our motivating example in Table 1.1a. Intuitively, the data is represented in tables with rows of uniform structure where each row contains data about a specific object or sets of object [1]. Each table is associated with a relation and has a name, for example, the relation *job* contains rows specifying the salary of a position in a company. The columns form the structure of the table and are called attributes, for example, the relation *job* has two attributes: *title* and *salary*. The values of attributes are taken from a set of constants called the domain. For simplicity, we do not distinguish between different types of values such as strings, numbers, dates.¹ Finally, we differentiate between the database schema, which is the structure data is stored, and the database instance, which is the actual content of the database. For example, Table 2.1b and Table 2.1c illustrate the database instance while Table 2.1a shows the database schema. This differentiation can be viewed as the differentiation of types and values in programming languages. For example, x is variable of type *Int* and may have value 15.

We now shift our focus to the formal definitions of a relational database. A relational database \underline{D} stores information in a structured manner by forcing data to conform to a *schema* \underline{S} that is a finite set $\{\underline{s}_1, \dots, \underline{s}_n\}$ of *relation schemas*. A

¹This design decision was made to make proofs easier, however, our database system implementation distinguishes between different kinds of values and considers a unique domain for each.

Table 2.1: An example of a relational database corresponding to V_2 of our motivating example given in Table 1.1a.

(a) The schema of a relational database.

<i>empacct</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>)
<i>job</i> (<i>title</i> , <i>salary</i>)

(b) The *empacct* table.

<i>empacct</i>	<i>empno</i>	<i>name</i>	<i>hiredate</i>	<i>title</i>	<i>deptname</i>
	10001	Georgi Facello	1986-06-26	Senior Engineer	Development
	10002	Bezalel Simmel	1985-11-21	Staff	Sales

	499998	Patricia Breugel	1993-10-13	Senior Staff	Finance
	499999	Sachin Tsukuda	1997-11-30	Engineer	Production

(c) The *job* table.

<i>job</i>	<i>title</i>	<i>salary</i>
	Assistant Engineer	61594
	Senior Engineer	96646

	Staff	77935
	Technique Leader	58345

Relational database objects:

$a \in \mathbf{AttrName}$		<i>Attribute Name</i>
$r \in \mathbf{RelName}$		<i>Relation Name</i>
$\underline{u} \in \mathbf{Tuple}$	$:= (v_1, \dots, v_l)$	<i>Tuple</i>
$\underline{A} \in \mathbf{Set\ AttrName}$	$:= \{a_1, a_2, \dots, a_l\}$	<i>Set of Attributes</i>
$\underline{s} \in \mathbf{RelSch}$	$:= r(\underline{A})$	<i>Relation Schema</i>
$\underline{U} \in \mathbf{RelCont}$	$:= \{\underline{u}_1, \underline{u}_2, \dots, \underline{u}_k\}$	<i>Relation Content</i>
$\underline{t} \in \mathbf{Table}$	$:= (\underline{s}, \underline{U})$	<i>Table</i>
$\underline{S} \in \mathbf{Sch}$	$:= \{s_1, \dots, s_n\}^e$	<i>Schema</i>
$\underline{I} \in \mathbf{DBInst}$	$:= \{t_1, t_2, \dots, t_n\}$	<i>Database Instance</i>

Relational database type synonyms:

$$\begin{aligned}
 \mathbf{RelCont} &= \mathbf{Set\ Tuple} \\
 \mathbf{Table} &= (\mathbf{RelSch}, \mathbf{RelCont}) \\
 \mathbf{Sch} &= \mathbf{Set\ RelSch} \\
 \mathbf{DBInst} &= \mathbf{Set\ (RelSch, RelCont)}
 \end{aligned}$$

Figure 2.1: Relational database objects and type synonyms.

relation schema is defined as $\underline{s} = r(a_1, \dots, a_k)$ where each $a_i \in \mathbf{AttrName}$ is an *attribute* contained in the relation named r and $\mathbf{AttrName}$ is a fixed countably infinite set of attributes. We assume a total order $\leq_{\mathbf{AttrName}}$ on $\mathbf{AttrName}$, and assume for simplicity that sets of attributes are sorted according to $\leq_{\mathbf{AttrName}}$.

Figure 2.1 defines the relational database objects and type synonyms compactly. The content of database \underline{D} is stored in the form of *tuples*. A tuple \underline{u} is a list of *values*. We do not distinguish between different types of values within a relational database. The order of values within a tuple correspond to the order of attributes in its corresponding relation schema, that is, given tuple $\underline{u} = (\underline{v}_1, \dots, \underline{v}_k)$ in the relation with relation schema $r(a_1, \dots, a_k)$, \underline{v}_i corresponds to attribute \underline{a}_i . A *relation content*, \underline{U} , is the set of all tuples $\{\underline{u}_1, \dots, \underline{u}_m\}$ corresponding to a particular relation. The operation $att(i)$ returns the attribute corresponding to index i in a tuple, implicitly looking up the attribute in the corresponding relation schema. A *table* $\underline{t} = (\underline{s}, \underline{U})$ is a pair of a relation schema and relation content. A *database instance*, $\underline{\mathcal{I}}$, of the database \underline{D} with schema \underline{S} , is a set of tables $\{\underline{t}_1, \dots, \underline{t}_n\}$ for each relation in \underline{S} . For brevity, when it is clear from context, we refer to a database instance as simply a *database*.

2.2 The SPC Relational Algebra

Having introduced relational databases we now shift gears into querying these databases, that is, extracting information from tables. For almost all relational query languages, the result of a query is a table called *result*. We base our vari-

add type
system

maybe add
semantics
later on

ational query language on the SPC relational algebra. Three primitive operators form the SPC algebra: *selection*, *projection*, and *cross-product* (or Cartesian product) [1]. We introduce these operators through Example 2.2.1 by stating an intent and then building up a query to extract the information required by the intent.

Example 2.2.1. Consider the database instance given in Table 2.1. We want to get a list of employees (by their names) whose salary is more than 65000 dollars. As the first step, we use the selection operator to get the tuples for all jobs with salaries that are more than 65000 dollars.

$$\underline{q}_1 = \sigma_{salary \geq 65000}(job)$$

A sample of the results returned by the query \underline{q}_1 is given in Table 2.2a. Next a set of tuples is created by taking the cross-product of \underline{q}_1 and *empacct*.

$$\underline{q}_2 = \underline{q}_1 \times empacct$$

A sample of the results returned by the query \underline{q}_2 is given in Table 2.2b. However, looking closely at these results there is no connection between an employee in the *empacct* relation and their salary in the *job* relation. Thus, we have to perform another selection to connect each employee with their title.

$$\underline{q}_3 = \sigma_{empacct.title=job.title}(\underline{q}_2)$$

A sample of the results returned by the query \underline{q}_3 is given in Table 2.2c. At this point, we are only interested in two attributes, that is, *name* and *salary*. Thus, we use projection to discard the unneeded columns.

$$\underline{q}_4 = \pi_{name,salary}(\underline{q}_3)$$

A sample of the results returned by the query \underline{q}_4 is given in Table 2.2d.

The relational algebra that we use also includes standard set operations, a join

Table 2.2: Results of each step of building the final query in Example 2.2.1.

(a) Result of the query $q_1 = \sigma_{salary \geq 65000}(job)$.

<i>result</i>	<i>title</i>	<i>salary</i>
	Senior Staff	77935
	Senior Engineer	96646

	Staff	77935
	Engineer	96646

(b) Result of the query $q_2 = (\sigma_{salary \geq 65000}(job)) \times empacct$.

<i>result</i>	<i>title</i>	<i>salary</i>	<i>empno</i>	<i>name</i>	<i>hiredate</i>	<i>title</i>	<i>deptname</i>
	Senior Engineer	96646	13094	Sanjay Servieres	1986-01-01	Engineer	Research
	Staff	77935	16099	Mohan Ferretti	1987-09-20	Senior Staff	Human Resources

	Engineer	80324	19162	Chinho Fadgyas	1986-05-19	Technique Leader	Production
	Senior Staff	88070	22255	Kristian Merel	1986-09-12	Senior Engineer	Development

(c) Result of the query $q_3 = \sigma_{empacct.title=job.title} ((\sigma_{salary \geq 65000}(job)) \times empacct)$.

<i>result</i>	<i>title</i>	<i>salary</i>	<i>empno</i>	<i>name</i>	<i>hiredate</i>	<i>title</i>	<i>deptname</i>
	Engineer	96646	13094	Sanjay Servieres	1986-01-01	Engineer	Research
	Senior Staff	77935	16099	Mohan Ferretti	1987-09-20	Senior Staff	Human Resources

	Senior Engineer	96646	22255	Kristian Merel	1986-09-12	Senior Engineer	Development
	Staff	77935	43670	JoAnna Randi	1987-10-18	Staff	Marketing

(d) Result of the query $q_4 = \pi_{name, salary} (\sigma_{empacct.title=job.title} ((\sigma_{salary \geq 65000}(job)) \times empacct))$.

<i>result</i>	<i>name</i>	<i>salary</i>
	Sanjay Servieres	96646
	Mohan Ferretti	77935

	Kristian Mere	96646
	JoAnna Randi	77935

Operators:

$$\begin{aligned} \bullet &:= < \mid \leq \mid = \mid \neq \mid > \mid \geq \\ \circ &:= \cup \mid \cap \end{aligned}$$

Variational conditions:

$$\underline{\theta} \in \underline{\text{Condition}} \quad := \quad \text{true} \mid \text{false} \mid a \bullet k \mid a \bullet a \mid \neg \underline{\theta} \mid \underline{\theta} \vee \underline{\theta}$$

Relational queries:

$$\begin{aligned} \underline{q} \in \underline{\mathbf{Q}} \quad &:= \quad \underline{r} && \text{Relation} \\ & \mid \pi_{\underline{A}} \underline{q} && \text{Projection} \\ & \mid \sigma_{\underline{\theta}} \underline{q} && \text{Selection} \\ & \mid \underline{q} \times \underline{q} && \text{Cross-Product} \\ & \mid \underline{q} \circ \underline{q} && \text{Set Operation} \\ & \mid \underline{q} \bowtie_{\underline{\theta}} \underline{q} && \text{Join} \\ & \mid \varepsilon && \text{Empty Relation} \end{aligned}$$

Figure 2.2: Syntax of relational algebra.

operation, and an empty relation. The syntax is defined in Figure 2.2. The set operations, union and intersection, require two subqueries to have the same relation schema and simply applies the corresponding operation, either union or intersection, to the tuples returned by the subqueries. The *join* operation is equivalent to selection applied to cross-product, that is, $\underline{q}_1 \bowtie_{\underline{\theta}} \underline{q}_2 = \sigma_{\underline{\theta}}(\underline{q}_1 \times \underline{q}_2)$. For example, \underline{q}_3 in Example 2.2.1 can be rewritten as

$$\underline{q}_3' = (\sigma_{\text{salary} \geq 65000}(\text{job})) \bowtie_{\text{empacct.title}=\text{job.title}} \text{empacct} \quad .$$

Throughout our examples, omitting the condition of join implies it is a *natural join*, that is, join on the shared attribute of the two subqueries. For example, \underline{q}_3' can be rewritten using the natural join

$$\underline{q}_3'' = (\sigma_{\text{salary} \geq 65000}(\text{job})) \bowtie \text{empacct} \quad .$$

We also extend relational algebra such that projection of an empty set of attributes is a valid query that returns an empty set of tuples. We define the *empty* query ε as shorthand for projecting an empty set of attributes, that is, $\varepsilon = \pi_{\{\}} \underline{q}$. Note that we do not extend the notation of using underline for relational algebra operators. Instead, relational algebra operators are overloaded and are used as both plain relational and variational operators. It should be clear from context when an operation is variational or not.

Although we do not consider renaming of queries in the formal definition of relational algebra we do support this in our implementation. Furthermore, we use it to rename subqueries of our examples to make them easier to understand. For example, query \underline{q}_3'' can be written as:

$$\begin{aligned} \underline{q}_3'' &= \underline{temp} \bowtie empacct \\ \underline{temp} &\leftarrow \sigma_{salary \geq 65000} (job) \end{aligned}$$

Making this renaming explicit is necessary to avoid names conflicting in some cases.

2.3 Variation Space and Encoding

In this section, we describe how we represent variation throughout this thesis. We encode variation in terms of *features*. The *feature space*, **FeatName**, of a variational database is a closed set of boolean variables called features. A feature $f \in \mathbf{FeatName}$ can be enabled (i.e., $f = \mathbf{true}$) or disabled ($f = \mathbf{false}$). Features

Feature expression syntax:

$f \in \mathbf{FeatName}$		<i>Feature Name</i>
$F \in \mathbf{Set\ FeatName}$		<i>Closed Set of Features</i>
$b \in \mathbf{Bool} \quad := \quad \mathbf{true} \mid \mathbf{false}$		<i>Boolean Value</i>
$e \in \mathbf{FeatExpr} \quad := \quad b \mid f \mid \neg e \mid e \wedge e \mid e \vee e$		<i>Feature Expression</i>
$c \in \mathbf{Config} \quad : \quad \mathbf{FeatName} \rightarrow \mathbf{Bool}$		<i>Configuration</i>

Evaluation of feature expressions:

$$\begin{aligned}
& \mathbb{E}[\cdot] : \mathbf{FeatExpr} \rightarrow \mathbf{Config} \rightarrow \mathbf{Bool} \\
& \mathbb{E}[b]_c = b \\
& \mathbb{E}[f]_c = c\ f \\
& \mathbb{E}[\neg f]_c = \neg \mathbb{E}[f]_c \\
& \mathbb{E}[e_1 \wedge e_2]_c = \mathbb{E}[e_1]_c \wedge \mathbb{E}[e_2]_c \\
& \mathbb{E}[e_1 \vee e_2]_c = \mathbb{E}[e_1]_c \vee \mathbb{E}[e_2]_c
\end{aligned}$$

Relations over feature expressions:

$$\begin{aligned}
e_1 &\equiv e_2 \text{ iff } \forall c \in \mathbf{Config}. \mathbb{E}[e_1]_c = \mathbb{E}[e_2]_c \\
\text{sat}(e) &\text{ iff } \exists c \in \mathbf{Config}. \mathbb{E}[e]_c = \mathbf{true} \\
\text{unsat}(e) &\text{ iff } \forall c \in \mathbf{Config}. \mathbb{E}[e]_c = \mathbf{false} \\
\text{oneof}(f_1, f_2, \dots, f_n) &= (f_1 \wedge \neg f_2 \wedge \dots \wedge \neg f_n) \vee (\neg f_1 \wedge f_2 \wedge \dots \wedge \neg f_n) \\
&\quad \vee (\neg f_1 \wedge \neg f_2 \wedge \dots \wedge f_n)
\end{aligned}$$

Figure 2.3: Feature expression syntax, relations, and evaluation.

describe the variation in a given variational scenario. For example, in the context of schema evolution, features can be generated from version numbers (e.g., features V_1 to V_5 and T_1 to T_5 in the motivating example, Table 1.1); for SPLs, the features can be adopted from the SPL feature set (e.g., the *edu* feature in our motivating example, Table 1.1); and for data integration, the features may represent different data sources. Note that it is easy to extend features to multi-valued variables that have a finite set of countable values. Consider our motivating example, Table 1.1. We could choose to have a feature V as a multi-valued variable which takes one of the values in set $\{1, 2, \dots, 32\}$. This new multi-valued feature V is equivalent to having five boolean variables V_1 , V_2 , V_3 , V_4 , and V_5 since it represents all 32 possible combinations of V_1 – V_5 . The feature space is captured by a closed set of features F .

closed set
of features
added

Features are used at variation points to indicate which variants a particular element belongs to. Thus, enabling or disabling each of the features in the feature set produces a particular database *variant* where all variation has been removed. A *configuration* is a *total* function that maps every feature in the feature set to a boolean value and is denoted by $c \in \mathbf{Config} : \mathbf{FeatName} \rightarrow \mathbf{Bool}$. We represent a configuration by the set of enabled features. For example, in our motivating scenario, the configuration $\{V_2, T_3, edu\}$ represents a database variant where only features V_2 , T_3 , and *edu* are enabled (and the rest are disabled). This database variant contains relation schemas in the yellow cells of Table 1.1. We refer to a variant by the configuration that produces it. For example, variant $\{V_2, T_3, edu\}$ refers to the variant produced by applying that configuration.

When describing variation points in the database, we need to refer to subsets of the configuration space. We do this with propositional formulas of features. Thus, such a propositional formula defines a condition that holds for a subset of configurations and their corresponding variants. For example, the propositional formula $\neg edu$ represents all variants of our motivating example where the *edu* feature is disabled, that is, variant schemas of Table 1.1b. We call a propositional formula of features a *feature expression* and define it formally in Figure 2.3. Additionally, in Figure 2.3, we formally define the evaluation function of feature expressions $\mathbb{E}\llbracket e \rrbracket_c : \mathbf{FeatExpr} \rightarrow \mathbf{Config} \rightarrow \mathbf{Bool}$. This function simply substitutes each feature f in the expression e with the boolean value given by configuration c and then simplifies the propositional formula to a boolean value. For example, $\mathbb{E}\llbracket f_1 \vee f_2 \rrbracket_{\{f_1\}} = \mathbf{true} \vee \mathbf{false} = \mathbf{true}$, while $\mathbb{E}\llbracket f_1 \vee f_2 \rrbracket_{\{\}} = \mathbf{false} \vee \mathbf{false} = \mathbf{false}$. Furthermore, in Figure 2.3, we define a binary *equivalence relation* (\equiv) relation on feature expressions corresponding to logical equivalence, unary *sat* and *unsat* predicates that determine whether a feature expression is satisfiable or unsatisfiable, respectively. We also define the n -ary operation *oneof* for mutually exclusive features. For example, *oneof* (V_1, V_2, V_3, V_4, V_5) indicates that only one of the features V_1 – V_5 can be enabled at a time.

No matter the context, features often have a relationship with each other that constrains the set of possible configurations. For example, in our motivating example (Section 1.1) only one of the temporal features of V_1 – V_5 can be **true** for a given variant. This relationship is captured by a feature expression, called a *feature model*, which restricts the set of *valid configurations*. That is, a configuration

c is only valid if the evaluation of feature model e under configuration c is **true**, that is $\mathbb{E}[e]_c = \mathbf{true}$. For example, the restriction that at a given time only one of temporal features V_1 – V_5 can be enabled is represented by the feature model *oneof* (V_1, V_2, V_3, V_4, V_5).

2.4 Annotations and Variational Sets

We now introduce the first approach used to incorporate variation into a database. To incorporate feature expressions into the database, we *annotate* database elements (including attributes, relations, and tuples) with feature expressions. An *annotated element* x with feature expression e is denoted by x^e , that is, if x has type \mathbf{a} (i.e., $x \in \mathbf{a}$) then x^e has the corresponding variational type **Var a** (i.e., $x^e \in \mathbf{Var a}$). The feature expression attached to an element is called its *presence condition* since it determines the condition (set of configurations) under which the element is present in the database. This is done by the *configuration* function $\mathbf{x}[\![\cdot]\!] : \mathbf{Var a} \rightarrow \mathbf{Config} \rightarrow \mathbf{a}_\perp$ defined in Figure 2.4. For example, assuming $F = \{f_1, f_2\}$, the annotated number $2^{f_1 \vee f_2}$ is present in variants $\{f_1\}$ (i.e., $\mathbf{x}[\![2^{f_1 \vee f_2}]\!]_{\{f_1\}} = 2$), $\{f_2\}$ (i.e., $\mathbf{x}[\![2^{f_1 \vee f_2}]\!]_{\{f_2\}} = 2$), and $\{f_1, f_2\}$ (i.e., $\mathbf{x}[\![2^{f_1 \vee f_2}]\!]_{\{f_1, f_2\}} = 2$) but not in variant $\{\}$ (i.e., $\mathbf{x}[\![2^{f_1 \vee f_2}]\!]_{\{\}} = \perp$). The operation $pc(x^e) = e$ returns the presence condition of an annotated element.

A *variational set* (*v-set*) $X = \{x_1^{e_1}, \dots, x_n^{e_n}\}$ is a set of annotated elements, that is, $X \in \mathbf{Set}(\mathbf{Var a})$ [23, 56, 8]. We typically omit the presence condition **true** in a variational set, e.g., $4^{\mathbf{true}} = 4$. Conceptually, a variational set represents

Configuration of an annotated element:

$$\begin{aligned} \mathbf{x}[\![\cdot]\!] &: \mathbf{Var} \ \mathbf{a} \rightarrow \mathbf{Config} \rightarrow \mathbf{a}_\perp \\ \mathbf{x}[\![x^e]\!]_c &= \begin{cases} \underline{x}, & \text{if } \mathbb{E}[e]_c = \mathbf{true} \\ \perp, & \text{otherwise} \end{cases} \end{aligned}$$

Configuration of (annotated) variational sets:

$$\begin{aligned} \mathbb{X}[\![\cdot]\!] &: \mathbf{Set} \ (\mathbf{Var} \ \mathbf{a}) \rightarrow \mathbf{Config} \rightarrow \mathbf{Set} \ \mathbf{a} \\ \mathbb{X}[\![\{x_1^{e_1}, x_2^{e_2}, \dots, x_n^{e_n}\}]\!]_c &= \otimes \{\mathbf{x}[\![x_1^{e_1}]\!]_c, \mathbf{x}[\![x_2^{e_2}]\!]_c, \dots, \mathbf{x}[\![x_n^{e_n}]\!]_c\} \\ \mathbb{X}[\![\{\ \}]\!]_c &= \{\ \} \end{aligned}$$

$$\begin{aligned} \mathbb{X}[\![\cdot]\!] &: \mathbf{Var} \ (\mathbf{Set} \ (\mathbf{Var} \ \mathbf{a})) \rightarrow \mathbf{Config} \rightarrow \mathbf{Set} \ \mathbf{a} \\ \mathbb{X}[\![X^e]\!]_c &= \mathbb{X}[\![\downarrow(X^e)]\!]_c \\ \mathbb{X}[\![\{\ \}^{\mathbf{true}}]\!]_c &= \{\ \} \\ \mathbb{X}[\![\{\ \}^{\mathbf{false}}]\!]_c &= \{\ \} \end{aligned}$$

Dropping bots from a plain set:

$$\otimes \{\underline{x}_1, \underline{x}_2, \dots, \underline{x}_n\} = \{\underline{x}_i \mid \underline{x}_i \neq \perp\}$$

Normalization of (annotated) variational sets:

$$\begin{aligned} \downarrow(\{x_1^{e_1}, x_2^{e_2}, \dots, x_n^{e_n}\}) &= \{x_i^{e_i} \mid 1 \leq i \leq n, \text{sat}(e_i)\} \\ \downarrow(X^e) &= \{x_i^{e_i \wedge e} \mid x_i^{e_i} \in X^e, \text{sat}(e_i \wedge e)\} \end{aligned}$$

Operations over (annotated) variational sets:

$$\begin{aligned} X_1 \cup X_2 &= \{x^{e_1} \mid x^{e_1} \in \downarrow(X_1), \exists e_2. x^{e_2} \notin \downarrow(X_2)\} \\ &\quad \cup \{x^{e_2} \mid x^{e_2} \in \downarrow(X_2), \exists e_1. x^{e_1} \notin \downarrow(X_1)\} \cup \{x^{e_1 \vee e_2} \mid x^{e_1} \in \downarrow(X_1), x^{e_2} \in \downarrow(X_2)\} \\ X_1 \cap X_2 &= \{x^{e_1 \wedge e_2} \mid x^{e_1} \in X_1, x^{e_2} \in X_2, \text{sat}(e_1 \wedge e_2)\} \\ X_1 \times X_2 &= \{(x_1, x_2)^{e_1 \wedge e_2} \mid x_1^{e_1} \in X_1, x_2^{e_2} \in X_2\} \\ X_1 \equiv X_2 &\text{ iff } \forall x^e \in (\downarrow(X_1) \cup \downarrow(X_2)), x^{e_1} \in \downarrow(X_1), x^{e_2} \in \downarrow(X_2). e_1 \equiv e_2, e \equiv e_1 \end{aligned}$$

Figure 2.4: Configuration of variational set and annotated variational set, normalization of variational sets and annotated variational sets, and operations over variational sets. The operations on variational sets are overloaded, that is, \cup is used to both denote the union of variational sets and plain sets.

many different plain sets simultaneously. These plain sets can be generated by *configuring* a variational set with a configuration. This is done by the *variational set configuration* function $\mathbb{X}[\![X]\!]_c : \mathbf{Set}(\mathbf{Var} \mathbf{a}) \rightarrow \mathbf{Config} \rightarrow \mathbf{Set} \mathbf{a}$, defined in Figure 2.4. The configuration function evaluates the presence condition e_i of each element x_i of the variational set with the configuration c . If the evaluation results in **true** it includes x_i in the plain set and otherwise it does not. Example 2.4.1 illustrates the configuration of a variational set for all possible configurations.

Example 2.4.1. Assume we have the feature space $F = \{f_1, f_2\}$ and the variational set $X_1 = \{2^{f_1}, 3^{f_2}, 4\}$. X_1 represents four plain sets:

$$\mathbb{X}[\![X_1]\!]_c = \begin{cases} \{2, 3, 4\}, & c = \{f_1, f_2\} \\ \{2, 4\}, & c = \{f_1\} \\ \{3, 4\}, & c = \{f_2\} \\ \{4\}, & c = \{\} \end{cases}$$

This states that, for example, configuring X_1 for the variant that enables both f_1 and f_2 (that is, $f_1 = \mathbf{true}$, $f_2 = \mathbf{true}$) results in the plain set $\mathbb{X}[\![X_1]\!]_{\{f_1, f_2\}} = \{2, 3, 4\}$.

Following database notational conventions we drop the brackets of a variational set when used in database schema definitions and queries.

A variational set itself can also be annotated with a feature expression. $X^e = \{x_1^{e_1}, \dots, x_n^{e_n}\}^e$ is an *annotated variational set*, that is, $X^e \in \mathbf{Var}(\mathbf{Set}(\mathbf{Var} \mathbf{a}))$. Annotating a variational set with the feature expression e means that all elements

it'd be nice to have the entire ex in the same page.

in the variational set are only present when e evaluates to **true**. The *normalization* operation $\downarrow(X^e)$ applies this restriction by pushing it into the presence conditions of the individual elements: $\downarrow(X^e) = \{x_i^{e_i \wedge e} \mid x_i^{e_i} \in X^e, \text{sat}(e_i \wedge e)\}$. Note that both the normalization operation and variational set configuration are overloaded, that is, they are defined for both variational sets and annotated variational sets. Also, note that the *normalization* operation also removes elements with unsatisfiable presence conditions and may also be applied to an unannotated variational set X since $X^{\mathbf{true}} = X$. For example, the annotated variational set $X_1 = \{2^{f_1}, 3^{\neg f_2}, 4, 5^{f_3}\}^{f_1 \wedge f_2}$ indicates that all the elements of the set can only exist when both f_1 and f_2 are enabled. Thus, normalizing the variational set X_1 results in $\{2^{f_1 \wedge f_2}, 4^{f_1 \wedge f_2}, 5^{f_1 \wedge f_2 \wedge f_3}\}$. The element 3 is dropped since $\neg \text{sat}(pc(3, X_1))$, where $pc(3, X_1) = \neg f_2 \wedge (f_1 \wedge f_2)$. Note that we use the function $pc(x, X^e)$ to return the presence condition of a unique variational element within a bigger variational structure. Note that, without loss of generality, we assume that elements in a variational set are unique since we can simply disjoin the presence conditions of a repeated element, that is, $\{x^e, x^e, x_1^{e_1}, \dots, x_n^{e_n}\} = \{x^{e \vee e'}, x_1^{e_1}, \dots, x_n^{e_n}\}$.

In Figure 2.4, we also define several operations, such as union and intersection, over variational sets; these operations are used in Section 4.3. The semantics of a variational set operation is equivalent to applying the corresponding plain set operation to every corresponding variant of the argument variational sets. For example, the union of two variational sets $X_1 \cup X_2$ should produce a new variational set X_3 such that $\forall c \in \mathbf{Config}. \mathbb{X}[X_3]_c = \mathbb{X}[X_1]_c \cup \mathbb{X}[X_2]_c$, where \cup is the plain set union operation. This property must hold for all operations over variational

sets, that is, for all possible operations, \odot , defined on variational sets the property $(P_1) : \forall c \in \mathbf{Config}. \mathbb{X}[\downarrow(X_1) \odot \downarrow(X_2)]_c = \mathbb{X}[\mathbb{X}[X_1]_c \underline{\odot} \mathbb{X}[X_2]_c]$ must hold, where $\underline{\odot}$ is the counterpart operation on plain sets.²

2.5 The Formula Choice Calculus

The second approach we use to incorporate variation into queries is the formula choice calculus [32] which is an extension of the choice calculus [54, 21]. The choice calculus is a metalanguage for describing variation in programs and its elements such as data structures [56, 23]. In the choice calculus, variation is represented in-place as choices between alternative subexpressions. For example, the variational expression $expr = f_1\langle 1, 2 \rangle + f_2\langle 3, 4 \rangle + f_1\langle 5, 6 \rangle$ contains three choices. Each choice has an associated *dimension*, which is a boolean variable equivalent to a feature and is used to synchronize the choice with other choices in different parts of the expression. For example, expression $expr$ contains two dimensions, f_1 and f_2 , and the two choices in dimension f_1 are synchronized. Therefore, the variational expression $expr$ represents four different plain expressions, depending on whether the left or right alternatives are selected from each dimension. Assuming that dimensions may be set to boolean values where **true** indicates the left alternative

²This property is proved for the operations we define over variational sets in Coq proof assistant [?].

and **false** indicates the right alternative, we have:

$$f_1\langle 1, 2 \rangle + f_2\langle 3, 4 \rangle + f_1\langle 5, 6 \rangle = \begin{cases} 1 + 3 + 5, & f_1 = \mathbf{true}, f_2 = \mathbf{true} \\ 1 + 4 + 5, & f_1 = \mathbf{true}, f_2 = \mathbf{false} \\ 2 + 3 + 6, & f_1 = \mathbf{false}, f_2 = \mathbf{true} \\ 2 + 4 + 6, & f_1 = \mathbf{false}, f_2 = \mathbf{false} \end{cases}$$

The formula choice calculus extends the choice calculus by allowing dimensions to be propositional formulas [32]. For example, the variational expression $expr' = f_1 \vee f_2\langle 1, 2 \rangle + f_2\langle 3, 4 \rangle + f_1\langle 5, 6 \rangle$ represents four plain expressions:

$$f_1 \vee f_2\langle 1, 2 \rangle + f_2\langle 3, 4 \rangle + f_1\langle 5, 6 \rangle = \begin{cases} 1 + 3 + 5, & f_1 = \mathbf{true}, f_2 = \mathbf{true} \\ 1 + 4 + 5, & f_1 = \mathbf{true}, f_2 = \mathbf{false} \\ 1 + 3 + 6, & f_1 = \mathbf{false}, f_2 = \mathbf{true} \\ 2 + 4 + 6, & f_1 = \mathbf{false}, f_2 = \mathbf{false} \end{cases}$$

Chapter 3 Variational Database Framework

In this chapter, we introduce the *variational database* framework and how it encodes variation directly in relational databases resulting in a variational database (VDB). To incorporate variation within a database, we annotate elements with feature expressions, as introduced in Section 2.4. We use annotated elements both in the schema and content. Within a schema we allow attributes and relations to exist conditionally based on the feature expression assigned to them (Section 3.1). At the content level, we annotate each tuple with a feature expression, indicating when the tuple is present (Section 3.2).

3.1 Variational Schema

In this section, we define how variation is encoded at the schema level. We first present an example that illustrates how relational databases fail to encode variation at the schema level and how we can express variation in their schemas. Recall from Section 2.1 that the schema of a database is essentially its type. This is also the case for variational databases, except that the components of the schema are variational. The variation in a variational schema states the condition under which its relations and attributes exist. For example, consider the *empbio* relation schema associated with variant V_3 of our motivating example shown in Table 1.1a. Table 3.1a shows

a corresponding relational table of this relation. Note that the relation *empbio* changes in variants that enable either V_4 or V_5 and Table 3.1b and Table 3.1c show their corresponding relational tables, respectively. The variational relation schema of *empbio* captures this variation in Table 3.1d by annotating the relation and each of its attributes with a feature expression indicating which configurations they exist in. The feature expressions written in blue above the attributes and the relation name are their presence conditions. For example, the feature expression $V_3 \vee V_4 \vee V_5$ indicates that the *empbio* table is present for variants that enable one of V_3 – V_5 . The three attributes *empno*, *sex*, and *birthdate* are present in all variants where the *empbio* relation exists, so their presence conditions are **true**. However, the *name* attribute is only present in variants that enable V_4 while attributes *firstname* and *lastname* are only present in variants that enable V_5 .

Furthermore, the existence of the variational relation *empbio* and its attributes relies on the existence of the entire variational database which is captured by the feature model of the database. Remember that the feature model is the presence condition of the variational database as a whole. The hierarchy of presence condition sometimes simplifies the presence conditions. For example, assuming that only one of the V_3 – V_5 can be enabled for a variant at a time, the *empbio* variational table shown in Table 3.1d can be simplified to the variational table shown in Table 3.2. Note that Table 3.2 and Table 3.1d focus only on the relation schema and does not include the variation at the content level.¹ We discuss the encoding of variation at the content level in Section 3.2.

¹Table 3.4 includes the variation at the content level.

Table 3.1: The relational tables of *empbio* for variants that enable one of the features V_3 , V_4 , or V_5 and the variational relation *empbio* that encompasses the three variants of the plain table *empbio* without accounting for variation at the content level. Note that data from earlier variants like $\{V_3\}$ is propagated to the later variants like $\{V_4\}$ and $\{V_5\}$.

(a) The relational table of *empbio* for variants that only enables the feature V_3 out of the features V_1 – V_5 . The relation schema is captured by the name of the relation and its attributes.

<i>empbio</i>	<i>empno</i>	<i>sex</i>	<i>birthdate</i>
	12001	F	1960-11-06
	12002	M	1961-04-15
	12003	M	1958-07-27

(b) The relational table of *empbio* for variants that only enables the feature V_4 out of the features V_1 – V_5 .

<i>empbio</i>	<i>empno</i>	<i>sex</i>	<i>birthdate</i>	<i>name</i>
	12001	F	1960-11-06	Ulf Hofstetter
	12002	M	1961-04-15	Luise McFarlan
	12003	M	1958-07-27	Shir DuCasse
	80001	M	1956-09-30	Nagui Merli
	80002	M	1963-04-25	Mayuko Meszaros
	80003	F	1960-10-26	Theirry Viele

(c) The relational table of *empbio* for variants that only enables the feature V_5 out of the features V_1 – V_5 .

<i>empbio</i>	<i>empno</i>	<i>sex</i>	<i>birthdate</i>	<i>firstname</i>	<i>lastname</i>
	12001	F	1960-11-06	Ulf	Hofstetter
	12002	M	1961-04-15	Luise	McFarlan
	12003	M	1958-07-27	Shir	DuCasse
	80001	M	1956-09-30	Nagui	Merli
	80002	M	1963-04-25	Mayuko	Mesaros
	80003	F	1960-10-26	Theirry	Viele
	200001	M	1960-01-11	Selwyn	Koshiba
	200002	M	1957-09-10	Bedrich	Markovitch
	200003	F	1961-02-07	Pascal	Benzmuller

(d) The variational relation of *empbio* without accounting for variation at the content level. The relation schema is captured by the name of the relation and attributes in addition to their presence conditions which are colored blue.

$\neg V_3 \vee \neg V_4 \vee \neg V_5$	true	true	true	$V_4 \wedge \neg V_3 \wedge \neg V_5$	$V_5 \wedge \neg V_3 \wedge \neg V_4$	$V_5 \wedge \neg V_3 \wedge \neg V_4$
<i>empbio</i>	<i>empno</i>	<i>sex</i>	<i>birthdate</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>
	12001	F	1960-11-06	Ulf Hofstetter	Ulf	Hofstetter
	12002	M	1961-04-15	Luise McFarlan	Luise	McFarlan
	12003	M	1958-07-27	Shir DuCasse	Shir	DuCasse
	80001	M	1956-09-30	Nagui Merli	Nagui	Merli
	80002	M	1963-04-25	Mayuko Meszaros	Mayuko	Mesaros
	80003	F	1960-10-26	Theirry Viele	Theirry	Viele
	200001	M	1960-01-11	Selwyn Koshiba	Selwyn	Koshiba
	200002	M	1957-09-10	Bedrich Markovitch	Bedrich	Markovitch
	200003	F	1961-02-07	Pascal Benzmuller	Pascal	Benzmuller

Table 3.2: The variational relation *empbio* without accounting for variation at the content level. This table is present under a presence condition e_{mot} that applies to the entire database of our motivating example. Example 3.1.2 provides the variational schema of our motivating example and explains e_{mot} .

$V_3 \vee V_4 \vee V_5$	true	true	true	V_4	V_5	V_5
<i>empbio</i>	<i>empno</i>	<i>sex</i>	<i>birthdate</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>
	12001	F	1960-11-06	Ulf Hofstetter	Ulf	Hofstetter
	12002	M	1961-04-15	Luise McFarlan	Luise	McFarlan
	12003	M	1958-07-27	Shir DuCasse	Shir	DuCasse
	80001	M	1956-09-30	Nagui Merli	Nagui	Merli
	80002	M	1963-04-25	Mayuko Meszaros	Mayuko	Meszaros
	80003	F	1960-10-26	Theirry Viele	Theirry	Viele
	200001	M	1960-01-11	Selwyn Koshiba	Selwyn	Koshiba
	200002	M	1957-09-10	Bedrich Markovitch	Bedrich	Markovitch
	200003	F	1961-02-07	Pascal Benzmueller	Pascal	Benzmueller

Figure 3.1 gives a formal definition of variational schemas. Variational schemas build on plain relational schemas defined in Section 2.1. A variational schema captures variation in the structure of a database by indicating which attributes and relations are included or excluded in which variants. To this end, we annotate attributes, relations, and the schema itself with feature expressions, which describe the conditions under which each is present. A *variational relation schema* (*v-relation schema*), s , is a relation name with an annotated variational set of attributes, $s \in \mathbf{RelSch} := r(A)^e$. The presence condition of the variational relation schema, e , determines in what variants of the database the relation itself is present. A *variational schema* (*v-schema*) is an annotated set of variational relation schemas, $S \in \mathbf{Sch} := \{s_1, \dots, s_n\}^e$. The presence condition of the entire variational schema, e , is the VDB's feature model, which provides a top-level constraint on the set of valid configurations, as described in Section 2.3, and can be extracted by $pc(S)$. Hence, the variational schema defines all valid schema

variants of a VDB. Example 3.1.1 defines a variational schema for only a part of our motivating example introduced in Section 1.1 and Example 3.1.2 provides the variational schema of our motivating example in its entirety.

Example 3.1.1. S_1 is the variational schema of a VDB that only includes relations *empacct* and *ecourse* in the last two rows of both Table 1.1a and Table 1.1b. It has the feature space $F = \{V_4, V_5, edu, T_4, T_5\}$. Note that attributes that exist conditionally are annotated with a feature expression to account for such a condition, e.g., the *salary* attribute only exists when $V_5 = \text{true}$.

$$S_1 = \{ \text{empacct}(\text{empno}, \text{hiredate}, \text{title}, \text{deptno}, \text{salary}^{V_5}, \text{std}^{edu}, \text{instr}^{edu})^{V_4 \vee V_5}, \\ \text{ecourse}(\text{courseno}, \text{coursename}, \text{deptno}^{T_5})^{T_4 \vee T_5} \}^{e_1}$$

$$e_1 = (\neg edu \wedge \text{oneof}(V_4, V_5) \wedge \neg (T_4 \vee T_5)) \vee (edu \wedge \text{oneof}(V_4, V_5) \wedge \text{oneof}(T_4, T_5))$$

where e_1 allows only one temporal feature for the basic schema to be enabled at a time, and either one temporal feature for the education extension, if *edu* is enabled, or else no temporal feature for the education extension.

The presence of an attribute follows the hierarchal layout of information in a database: an attribute's presence depends on the presence of its parent variational relation, which in turn depends on the presence of the variational schema. Thus, the complete presence condition of the attribute a^{e_a} in variational relation $r(\dots)^{e_r}$ defined in variational schema S is $pc(a, S) = e_a \wedge e_r \wedge pc(S)$.

Similarly, the presence condition of variational relation r is $pc(r, S) = e_r \wedge pc(S)$. For example, in Example 3.1.1 we have $pc(\text{empacct}, S_1) = (V_4 \vee V_5) \wedge e_1$. Further-

Variational schema objects:

$a \in \mathbf{AttrName}$	<i>Attribute Name</i>
$r \in \mathbf{RelName}$	<i>Relation Name</i>
$A \in \mathbf{Set}(\mathbf{Var} \mathbf{AttrName})$	$\{a_1^{e_1}, a_2^{e_2}, \dots, a_k^{e_k}\}$ <i>Variational Set of Attributes</i>
$s \in \mathbf{RelSch}$	$r(A)^e$ <i>Variational Relation Schema</i>
$S \in \mathbf{Sch}$	$\{s_1, \dots, s_n\}^e$ <i>Variational Schema</i>

Variational schema type synonyms:

$$\mathbf{Sch} = \mathbf{Var}(\mathbf{Set} \mathbf{RelSch})$$

Presence condition of attributes and relations:

$$\begin{aligned} pc(a, S) &= pc(a, r(\dots, a^{e_a}, \dots)^{e_r}) \wedge pc(r, S) = pc(a^{e_a}) \wedge pc(r, S) = e_a \wedge e_r \wedge pc(S) \\ pc(r, S) &= pc(r(A)^{e_r}) \wedge pc(S) = e_r \wedge pc(S) \end{aligned}$$

Variational set of attributes configuration:

$$\begin{aligned} \mathbb{A}[\cdot] &: \mathbf{Set}(\mathbf{Var} \mathbf{AttrName}) \rightarrow \mathbf{Config} \rightarrow \mathbf{AttrName} \\ \mathbb{A}[A]_c &= \mathbb{X}[A]_c \end{aligned}$$

Variational relation schema configuration:

$$\begin{aligned} \mathbb{R}[\cdot] &: \mathbf{RelSch} \rightarrow \mathbf{Config} \rightarrow \mathbf{RelSch}_\perp \\ \mathbb{R}[r(A)^{e_A}]_c &= \begin{cases} r(\mathbb{A}[\downarrow(A^{e_A})]_c), & \text{if } \mathbb{E}[e_A]_c = \mathbf{true} \\ \perp, & \text{otherwise} \end{cases} \end{aligned}$$

Variational schema configuration:

$$\begin{aligned} \mathbb{S}[\cdot] &: \mathbf{Sch} \rightarrow \mathbf{Config} \rightarrow \mathbf{Sch} \\ \mathbb{S}[\{r_1(A_1)^{e_1}, \dots, r_n(A_n)^{e_n}\}^e]_c &= \begin{cases} \{\mathbb{R}[r_1(A_1)^{e_1 \wedge e}]_c, \dots, \mathbb{R}[r_n(A_n)^{e_n \wedge e}]_c\}, & \text{if } \mathbb{E}[e]_c = \mathbf{true} \\ \{\}, & \text{otherwise} \end{cases} \end{aligned}$$

Figure 3.1: Variational schema definition, presence condition of attributes and relations, and variational schema configuration.

more, a database element is only present in variants for which its presence condition is satisfiable, e.g., in Example 3.1.1 the *std* attribute is present in the variant $\{edu, V_4, T_5\}$ since $\mathbb{E}[\llbracket pc(std, S_1) \rrbracket]_{\{edu, V_4, T_5\}} = \mathbb{E}[\llbracket edu \wedge (V_4 \vee V_5) \wedge e_1 \rrbracket]_{\{edu, V_4, T_5\}} = \text{true} \wedge (\text{true} \vee \text{false}) \wedge ((\neg \text{true} \wedge \text{oneof}(\text{true}, \text{false}) \wedge \neg(\text{false} \vee \text{true})) \vee (\text{true} \wedge \text{oneof}(\text{true}, \text{false}) \wedge \text{oneof}(\text{false}, \text{true}))) = \text{true}$ but it is not present in the variant $\{V_4, T_5\}$ since in this variant $edu = \text{false}$, thus, $\mathbb{E}[\llbracket pc(std, S_1) \rrbracket]_{\{edu, V_4, T_5\}} = \text{false}$.

Intuitively and similar to variational sets, a variational schema is a systematic compact representation of a set of plain schemas called variants. A schema variant can be obtained by *configuring* the variational schema with that variant's configuration. We define the configuration function for variational schemas and its elements in Figure 3.1. Example 3.1.2 illustrates configuring the variational schema of our motivating example for the variant $\{edu, V_2, T_3\}$.

Example 3.1.2. Table 3.3 illustrates the variational schema of the motivating example, denoted by S_{mot} . As a reminder the motivating example has the feature space $F = \{edu, V_1, V_2, V_3, V_4, V_5, T_1, T_2, T_3, T_4, T_5\}$. Additionally, all schema variants are illustrated in Table 1.1.

The feature model e_{mot} only allows one temporal feature to be true from a set of temporal features at the time.

$$e_{mot} = (\neg edu \wedge \text{oneof}(V_1, V_2, V_3, V_4, V_5) \wedge \neg(T_1 \vee T_2 \vee T_3 \vee T_4 \vee T_5)) \\ \vee (edu \wedge \text{oneof}(T_1, T_2, T_3, T_4, T_5) \wedge \text{oneof}(V_1, V_2, V_3, V_4, V_5))$$

make sure
encoding is
correct in
Table 3.3

Table 3.3: Variational schema S_{mot} with feature model e_{mot} . This variational schema encompasses 30 relational schemas: five schemas when $edu = \mathbf{false}$ and 25 schemas otherwise.

$engineerpersonnel(empno, name, hiredate, title, deptname)^{V_1}$
$otherpersonnel(empno, name, hiredate, title, deptname)^{V_1}$
$empacct(empno, name^{V_2 \vee V_3}, hiredate, title, deptname^{V_2}, deptno^{V_3 \vee V_4 \vee V_5}, salary^{V_5},$
$std^{V_4 \vee V_5}, instr^{V_4 \vee V_5})^{V_2 \vee V_3 \vee V_4 \vee V_5}$
$job(title, salary)^{V_1 \vee V_2 \vee V_3 \vee V_4}$
$dept(deptname, deptno, managerno, stdnum^{V_5}, instrnum^{V_5})^{V_3 \vee V_4 \vee V_5}$
$empbio(empno, sex, birthdate, name^{V_4}, firstname^{V_5}, lastname^{V_5})^{V_3 \vee V_4 \vee V_5}$
$course(courseno^{\neg T_1}, coursename, teacherno^{T_1 \vee T_2}, time^{T_4 \vee T_5}, class^{T_4 \vee T_5}, deptno^{T_5})^{edu}$
$student(studentno, coursename^{T_1}, courseno^{\neg T_1}, grade^{T_3 \vee T_4})^{edu \wedge \neg T_5}$
$teach(teacherno, courseno)^{edu \wedge (T_3 \vee T_4 \vee T_5)}$
$ecourse(courseno, coursename, deptno^{T_5})^{edu \wedge (T_4 \vee T_5)}$
$take(studentno, courseno, grade)^{edu \wedge T_5}$

However, the feature model can be encoded differently. For example, e'_{mot} restrict it such that it only allows the two sets of temporal features to change together.

$$e'_{mot} = oneof((V_1 \vee (V_1 \wedge edu \wedge T_1)), (V_2 \vee (V_2 \wedge edu \wedge T_2)), (V_3 \vee (V_3 \wedge edu \wedge T_3)), \\ , (V_4 \vee (V_4 \wedge edu \wedge T_4)), (V_5 \vee (V_5 \wedge edu \wedge T_5)))$$

Hence, the feature model of a VDB can vary based on the relationship between features and the restrictions that they must follow. Additionally, the encoding of presence condition can change since different feature expressions can be indicate the same set of variants. For example, the presence condition of the *job* relation can be changed to $\neg V_5$.

Configuring the variational schema S_{mot} for the variant that only enables features edu , V_2 , and T_3 (i.e., the variant $\{edu, V_2, T_3\}$) results in relations contained in the two yellow highlighted cells of tables in Table 1.1.

3.2 Variational Table

Thus far, we illustrated how variation can be incorporated into the schema of a database. However, it does not suffice to only have variation at the schema level. Consider the variants of the relation *empbio* shown in Table 3.1a–Table 3.1c. Table 3.2 illustrates the variational relation *empbio* but it does not include variation at the content level. To incorporate variation in the content of a variational relation we extend each relation with a new attribute *prescond* that stores the presence condition of tuples, as shown in Table 3.4. Thus, the value of this attribute for a tuple determines the set of variants that the tuple belongs to. For example, the first tuple in the Table 3.4 is present for all database variants that enable the feature V_3 . Note that the white spaces in Table 3.4 indicate the non-existing values for an attribute in a tuple. For example, consider the first three tuples of the variational table *empbio* shown in Table 3.4. Since none of the attributes *name*, *firstname*, and *lastname* exists for variants that enable V_3 they are left empty for tuples of variants that enable V_3 .

To account for content variability in the formal definition we tag tuples with presence conditions. Thus, a *variational tuple* (*v-tuple*) is an annotated tuple, $u \in \mathbf{Tuple} := (v_1, \dots, v_l)^e$. A variational tuple corresponds to a variational relation,

Table 3.4: The variational table of *empbio* encompassing the three variants of the plain relation *empbio* shown in Table 3.1a–Table 3.1c. This table accounts for both variation at the schema and content levels. Note that feature model e_{mot} of the entire VDB applies to it.

$V_3 \vee V_4 \vee V_5$	true	true	true	V_4	V_5	V_5	true
<i>empbio</i>	<i>empno</i>	<i>sex</i>	<i>birthdate</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>	<i>prescond</i>
	12001	F	1960-11-06	Ulf Hofstetter	Ulf	Hofstetter	$V_3 \vee V_4 \vee V_5$
	12002	M	1961-04-15	Luise McFarlan	Luise	McFarlan	$V_3 \vee V_4 \vee V_5$
	12003	M	1958-07-27	Shir DuCasse	Shir	DuCasse	$V_3 \vee V_4 \vee V_5$
	80001	M	1956-09-30	Nagui Merli	Nagui	Merli	$V_4 \vee V_5$
	80002	M	1963-04-25	Mayuko Meszaros	Mayuko	Meszaros	$V_4 \vee V_5$
	80003	F	1960-10-26	Theirry Viele	Theirry	Viele	$V_4 \vee V_5$
	200001	M	1960-01-11	Selwyn Koshiba	Selwyn	Koshiba	V_5
	200002	M	1957-09-10	Bedrich Markovitch	Bedrich	Markovitch	V_5
	200003	F	1961-02-07	Pascal Benzmueller	Pascal	Benzmueller	V_5

$r(a_1, \dots, a_l)^{e_r}$, where each element v_i is a value corresponding to attribute a_i (recall that attributes in a variational relation are ordered). For example, $(38, PL, 678)^{T_5}$ is a variational tuple that belongs to the *ecourse* relation from Example 3.1.1 and is only present when T_5 is enabled. The content of a variational relation is a set of variational tuples, $U \in \mathbf{RelCont} := \{u_1, \dots, u_k\}$ and a *variational table* (*v-table*) is the pair of its relation schema and content, $t = (s, U)$. A *variational database instance* is a set of variational tables, $\mathcal{I} \in \mathbf{DBInst} := \{t_1, \dots, t_n\}^e$. Figure 3.2 provides the formal definition of a VDB and its type synonyms. A VDB instance is *well-formed* if its encoded variation at the schema and content level are consistent and satisfiable [10]. Section 3.3 expands on this.

Similar to a variational schema, a user can configure a variational table or a VDB for a specific variant, formally defined in Figure 3.2. This allows users to deploy a VDB for a specific configuration and generate the corresponding VDB variant. For example, configuring the variational table *empbio*, shown in Table 3.4,

Variational database objects:

$$\begin{aligned}
u \in \mathbf{Var\ Tuple} &:= (v_1, \dots, v_l)^e && \text{Variational Tuple} \\
U \in \mathbf{RelCont} &:= \{u_1, \dots, u_k\} && \text{Variational Relation Content} \\
t \in \mathbf{Table} &:= (s, U) && \text{Variational Table} \\
\mathcal{I} \in \mathbf{DBInst} &:= \{t_1, \dots, t_n\}^e && \text{Variational Database Instance}
\end{aligned}$$

Variational database type synonyms:

$$\begin{aligned}
\mathbf{RelCont} &= \mathbf{Set\ (Var\ Tuple)} \\
\mathbf{Table} &= (\mathbf{RelSch}, \mathbf{RelCont}) \\
\mathbf{DBInst} &= \mathbf{Var\ (Set\ ((RelSch, RelCont)))}
\end{aligned}$$

Variational tuple configuration:

$$\begin{aligned}
&\mathbb{U}[\cdot] : \mathbf{Var\ Tuple} \rightarrow \mathbf{RelSch} \rightarrow \mathbf{Config} \rightarrow \mathbf{Tuple}_\perp \\
&\mathbb{U}[(v_1, \dots, v_l)^e]_{(s,c)} \\
&= \begin{cases} (v_i, \dots, v_j), & \text{if } \forall k. 1 \leq i \leq k \leq j \leq l, \mathbb{E}[pc(att(k), s) \wedge e]_c = \mathbf{true} \\ \perp, & \text{otherwise} \end{cases}
\end{aligned}$$

Variational relation content configuration:

$$\begin{aligned}
&\mathbb{T}[\cdot] : \mathbf{RelCont} \rightarrow \mathbf{RelSch} \rightarrow \mathbf{Config} \rightarrow \underline{\mathbf{RelCont}} \\
&\mathbb{T}[\{u_1, \dots, u_k\}]_{(s,c)} = \{\mathbb{U}[u_1]_{(s,c)}, \dots, \mathbb{U}[u_k]_{(s,c)}\}
\end{aligned}$$

VDB instance configuration:

$$\begin{aligned}
&\mathbb{I}[\cdot] : \mathbf{DBInst} \rightarrow \mathbf{Config} \rightarrow \underline{\mathbf{DBInst}} \\
&\mathbb{I}[\{t_1, \dots, t_n\}]_c = \mathbb{I}[\{(s_1, U_1), \dots, (s_n, U_n)\}^e]_c \\
&= \begin{cases} \{(\mathbb{R}[r_1(A_1)^{e_1 \wedge e}]_c, \mathbb{T}[\downarrow(U_1^{e_1 \wedge e})]_{(s_1, c)}), \dots\}, & \text{if } \mathbb{E}[e]_c = \mathbf{true} \\ \{\}, & \text{otherwise} \end{cases}
\end{aligned}$$

Figure 3.2: VDB instance syntax and configuration. Note that the schema of a relation must be passed to the configuration function for its content, however, the variational schema does not need to be passed to configuration functions of smaller parts of the variational schema such as $\mathbb{R}[\cdot]_c$ or $\mathbb{A}[\cdot]_c$ since all needed information for configuring a part of a variational schema is propagated.

for configuration $\{V_3, edu, T_1\}$ results in the relational table *empbio* in Table 3.1a, assuming the VDB has the variational schema S_{mot} given in Example 3.1.2. Additionally, our VDB framework puts all variants of a database into one VDB and it keep tracks of which variant a tuple belongs to by annotating them with presence conditions. For example, consider tuples $(38, PL, 678)^{T_5}$ and $(23, DB, \text{NULL})^{T_4}$ that belong to the *ecourse* table. The presence conditions T_5 and T_4 state that tuples belong to temporal variants four and five of this VDB, respectively. Hence, this framework tracks which variants a tuple belongs to.

Our VDB framework encodes variation at two levels: schema and content. In a variational database, while content-level variation can stand on its own, such as frameworks used for database versioning and experimental databases [31], the schema level cannot. For example, $ecourse(courseno, coursename, deptno)^{T_5}_{edu \wedge (T_4 \vee T_5)}$ encodes variation at the schema level for relation *ecourse*. Dropping the presence conditions of tuples leads to ambiguity, i.e., it is unclear which variant each of the tuples $(38, PL, 678)$ and $(23, DB, \text{NULL})$ belongs to. We can only guess that they belong to variants where T_4 or T_5 are enabled, but, we do not know for sure which one.

Note that we limit the granularity of variation in content to tuples, that is, the individual values within a tuple are not variational. This design decision causes some redundancy. For example, the two tuples $(38, PL, 678)^{T_5}$ and $(38, PL, \text{NULL})^{\neg T_5}$ cannot be represented as a single tuple with variation in the third element. However, this design decision does not prevent us from distinguishing between a **NULL** value that represents a missing value and a **NULL** value that

represents a cell that is not present. This distinction can be made by checking the satisfiability of the presence condition of the value v_i in tuple u with of relation r in schema S : If $\text{sat}(pc(att(i), S) \wedge pc(u, r) \wedge pc(r, S))$ then the **NULL** indicates a missing value and otherwise it indicates a non-present cell.

3.3 Properties of a Variational Database Framework

In this section, we describe a set of basic properties that a well-formed VDB should satisfy. These checks ensure that presence conditions are consistent and satisfiable, which ensures that each element is present in at least one variant. In the following, $\text{sat}(e)$ denotes a satisfiability check that returns **true** if the feature expression e is satisfiable and **false** otherwise.

A well-formed v-schema should have the following properties:

1. There is at least one valid configuration of the VDB feature model $pc(S)$:

$$\text{sat}(pc(S))$$

2. Every relation r is present in at least one configuration of the variational schema S :

$$\forall r \in S, \text{sat}(pc(r, S))$$

3. Every attribute a in every relation r is present in at least one configuration of the variational schema S :

$$\forall a \in r, \forall r \in S. \text{sat}(pc(r, S) \wedge pc(a, r))$$

4. If S_c denotes the expected plain relational schema for configuration c of the

variational schema S , then configuring the variational schema with that configuration, written $\llbracket S \rrbracket_c$, actually yields that variant:

$$\forall c \in \mathbf{Config}. \mathbb{S}[\llbracket S \rrbracket_c] = S_c$$

At the data level, a well-formed VDB should have these properties:

1. Every tuple u in relation r is present in at least one variant:

$$\forall u \in r, \forall r \in S. \text{sat}(pc(r, S) \wedge pc(u, r))$$

2. For every tuple u in relation r , if an attribute a in r is not present in any variants of the tuple, then the value of that attribute in the tuple, written $value_u(a)$, should be NULL:

$$\forall u \in r, a \in r, r \in S. \neg \text{sat}(pc(r, S) \wedge pc(a, r) \wedge pc(u, r)) \Rightarrow value_u(a) = \text{NULL}$$

Since a single VDB can supply data for many different database variants at the same time, encoding variation explicitly in a database allows the developers to check for different properties over all database variants. Thus, depending on the context of the VDB, more specialized properties can be checked. For example, if temporal variability in a database is accumulated over variants (i.e. old data is included in more recent variants in addition to newly added data), it is desirable to ensure that older variants are subsets of newer variants. This property should hold for our employee data set, introduced in Section 5.2. To check this, assume that configurations c_1, c_2, \dots represent time-ordered configurations, then check $\forall c_i, c_j \in \mathbf{Config}, i \leq j, \mathbb{I}[\mathcal{I}]_{c_i} \subseteq \mathbb{I}[\mathcal{I}]_{c_j}$, where $\mathbb{I}[\mathcal{I}]_c$ denotes configuring the VDB instance \mathcal{I} for configuration c , defined in Figure 3.2.

Chapter 4 Variational Queries

Now that we have introduced the variational database framework we need a query language to extract information from a VDB instance. Our approach will build on existing relational query languages (like SQL and relational algebra) but must also account for the new aspect of our database: variation.

remember
to ad-
just the
example
from type
system ac-
cording to
the deriva-
tion trees.

We formally define *variational relational algebra* (VRA) in Section 4.1 as our algebraic query language. A query written in VRA is called a *variational query* (*v-query*); we use query and variational query interchangeably when it is clear from context. Unlike relational queries that convey an intent over a single database, a variational query typically conveys the same intent over several relational database variants. However, a single variational query is also capable of capturing different intents over different database variants.

To understand the meaning of variational queries we define the semantics of variational queries via the semantics of relational queries in Section 4.2. We define how to configure a variational query to a relational query in Section 4.2.1. Then, we use the results of multiple relational queries to accumulate the result of the original variational query in Section 4.2.2.

Due to the expressiveness of variational queries, we define a type system for VRA that statically checks a variational query against the underlying variational schema in Section 4.3. To make variational queries more useable we relieve the

user from repeating the variational schema’s variation in their variational queries. This is achieved by explicitly annotating queries in Section 4.4. We then define the *variation-preservation* property for VRA at the type level in Section 4.6.2. Finally, we provide a set of syntactic rules that are semantic-preserving in Section 4.5 that enable factoring and distributing variation points within a variational query, which enables syntactic refactorings including maximizing sharing within a variational query.

4.1 Variational Relational Algebra

To account for variation, VRA combines relational algebra (RA) with *choices* [21, 32, 54]. Remember that a choice $e\langle x_1, x_2 \rangle$ consists of a feature expression e , called the *dimension* of the choice, and two *alternatives* x_1 and x_2 . For a given configuration c , the choice $e\langle x_1, x_2 \rangle$ can be replaced by x_1 if e evaluates to **true** under configuration c , (i.e., $\mathbb{E}[e]_c$), or x_2 otherwise.

The syntax of VRA is given in Figure 4.1. The selection operation is similar to standard RA selection except that the condition parameter is *variational* meaning that it may contain choices. For example, the query $\sigma_{e\langle a_1=a_2, a_1=a_3 \rangle}(r)$ selects a variational tuple u if it satisfies the condition $a_1 = a_2$ and $\text{sat}(e \wedge pc(u))$ or if $a_1 = a_3$ and $\text{sat}(\neg e \wedge pc(u))$. The projection operation is parameterized by a variational set of attributes, A . For example, the query $\pi_{a_1, a_2^e}(r)$ projects a_1 from relation r unconditionally, and a_2 when $\text{sat}(e)$. The choice operation enables combining two variational queries to be used in different variants based on the dimension. In

Operators:

$$\begin{aligned} \bullet &:= < \mid \leq \mid = \mid \neq \mid > \mid \geq \\ \circ &:= \cup \mid \cap \end{aligned}$$

Variational conditions:

$$\begin{aligned} \theta \in \mathbf{Condition} &:= b \mid a \bullet k \mid a \bullet a \mid \neg\theta \mid \theta \vee \theta \\ &\mid \theta \wedge \theta \mid e\langle\theta, \theta\rangle \end{aligned}$$

Variational queries:

$$\begin{aligned} q \in \mathbf{Q} &:= r && \textit{Relation} \\ &\mid \sigma_{\theta}q && \textit{Selection} \\ &\mid \pi_Aq && \textit{Projection} \\ &\mid e\langle q, q\rangle && \textit{Choice} \\ &\mid q \times q && \textit{Cartesian Product} \\ &\mid q \circ q && \textit{Set Operation} \\ &\mid \varepsilon && \textit{Empty Relation} \end{aligned}$$

Figure 4.1: Syntax of variational relational algebra.

practice, it is often useful to return information in some variants and nothing at all in others. We introduce an explicit *empty* query ε to facilitate this. Similar to our definition of the empty query for relational algebra, for VRA we also have: $\varepsilon = \pi_{\{\}}q$. The empty query is used, for example, in q_2 in Example 4.1.1. The rest of VRA's operations are similar to RA, where all set operations (union, intersection, and product) are changed to the corresponding variational set operations defined in Section 2.4.

Our implementation of VRA also provides mechanisms for renaming queries and qualifying attributes with relation/subquery names. These features are needed to support self joins and to project attributes with the same name in different relations. However, for simplicity, we omit these features from the formal definition

in this thesis.

The result of a variational query is a variational table with the reserved relation name *result*. For example, assume that variational tuples $(1, 2)^{f_1}$ and $(3, 4)^{\neg f_3}$ belong to a variational relation $r(a_1, a_2)$, which is the only relation in a VDB with the trivial feature model **true**. The query $f_3 \langle \pi_{a_1 f_2}(r), \varepsilon \rangle$ returns a variational table with relation schema $result(a_1^{f_2})^{f_3}$, which indicates that the result is only non-empty when f_3 is **true** and that the result includes attribute a_1 when f_2 is **true**. The content of the result relation for the example query is a single variational tuple $(1)^{f_1}$. The tuple $(3)^{\neg f_3}$ is not included since the projection occurs in the context of a choice in f_3 , which is incompatible with the presence condition of the tuple, i.e., $unsat(f_3 \wedge \neg f_3)$. This illustrates how choices can effectively filter the tuples in a VDB based on the dimension. Example 4.1.1 illustrates how a variational query can be used to express variational information needs.

Example 4.1.1. Assume a VDB with $F = \{V_3, V_4, V_5\}$, and the only variational table *empbio* shown in Table 3.4. The VDB has the feature model $e_2 = oneof(V_3, V_4, V_5)$ which states that the three V_3 – V_5 are mutually exclusive. Note that e_2 is different from the feature model e_{mot} of the *empbio* variational table shown in Table 3.4. The variational schema for this VDB is:

$$S_2 = \{empbio(empno, sex, birthdate, name^{V_4}, firstname^{V_5}, lastname^{V_5})\}^{e_2}.$$

Now, the user wants the employee ID numbers (*empno*) and their names for variants that enable either V_4 or V_5 but not V_3 . We show the steps to build up multiple queries that can extract this information. First, to extract the required attributes we write the query q_0 to project all the needed attributes without considering the

variational aspect of projection.

$$q_0 = \pi_{empno, name, firstname, lastname}(empbio)$$

Note that the presence condition attribute (*prescond*) does not need to be projected. In fact, the presence condition attribute is returned for every variational query since that is the only way to keep track of variation at the content level. Table 4.1 shows the result of query q_0 over the described VDB. Note that the presence condition of the result is $pc(empbio, S_2) = oneof(V_3, V_4, V_5) \wedge (V_3 \vee V_4 \vee V_5)$ which can be simplified to $oneof(V_3, V_4, V_5)$. We discuss how the presence conditions of the returned result and its attributes are generated in Section 4.3.

Table 4.1: Result of the v-query $q_0 = \pi_{empno, name, firstname, lastname}(empbio)$.

$oneof(V_3, V_4, V_5)$	true	V_4	V_5	V_5	true
<i>result</i>	<i>empno</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>	<i>prescond</i>
	12001	Ulf Hofstetter	Ulf	Hofstetter	$V_3 \vee V_4 \vee V_5$
	12002	Luise McFarlan	Luise	McFarlan	$V_3 \vee V_4 \vee V_5$
	12003	Shir DuCasse	Shir	DuCasse	$V_3 \vee V_4 \vee V_5$
	80001	Nagui Merli	Nagui	Merli	$V_4 \vee V_5$
	80002	Mayuko Meszaros	Mayuko	Meszaros	$V_4 \vee V_5$
	80003	Theirry Viele	Theirry	Viele	$V_4 \vee V_5$
	200001	Selwyn Koshiba	Selwyn	Koshiba	V_5
	200002	Bedrich Markovitch	Bedrich	Markovitch	V_5
	200003	Pascal Benzmueller	Pascal	Benzmueller	V_5

Now we pay attention to the variational aspect of the query. Knowing that the variation encoded in the VDB can be inferred (that is, the VDB exists if and only if exactly one of the features V_3 – V_5 is enabled, the *name* attribute only exists for variants that enable V_4 and the *firstname* and *lastname* attributes only exist for variants that enable V_5) and since we only want the projected attributes for variants that enable V_4 or V_5 we can write the query q_1 .

$$q_1 = \pi_{empno^{V_4 \vee V_5}, name, firstname, lastname}(empbio)$$

Table 4.2 shows the result of this query over the described VDB. Note that the first three tuples from Table 4.1 are not returned since the query does not project the *empno* attribute for variants that enable V_3 and attributes *name*, *firstname*, and *lastname* do not exist for these variants in the VDB. Thus, the tuple will just be empty and so is dropped.

Table 4.2: Result of the v-queries $q_1 = \pi_{empno^{V_4 \vee V_5}, name, firstname, lastname}(empbio)$ and $q'_1 = \pi_{empno^{(V_4 \vee V_5) \wedge \neg V_3}, name^{V_4 \wedge \neg V_3 \wedge \neg V_5}, firstname^{V_5 \wedge \neg V_3 \wedge \neg V_4}, lastname^{V_5 \wedge \neg V_3 \wedge \neg V_4}}(empbio)$.

$oneof(V_3, V_4, V_5)$	$V_4 \vee V_5$	V_4	V_5	V_5	true
<i>result</i>	<i>empno</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>	<i>prescond</i>
	12001	Ulf Hofstetter	Ulf	Hofstetter	$V_3 \vee V_4 \vee V_5$
	12002	Luise McFarlan	Luise	McFarlan	$V_3 \vee V_4 \vee V_5$
	12003	Shir DuCasse	Shir	DuCasse	$V_3 \vee V_4 \vee V_5$
	80001	Nagui Merli	Nagui	Merli	$V_4 \vee V_5$
	80002	Mayuko Meszaros	Mayuko	Meszaros	$V_4 \vee V_5$
	80003	Theirry Viele	Theirry	Viele	$V_4 \vee V_5$
	200001	Selwyn Koshiba	Selwyn	Koshiba	V_5
	200002	Bedrich Markovitch	Bedrich	Markovitch	V_5
	200003	Pascal Benzmueller	Pascal	Benzmueller	V_5

If desired, we can also make the inferred presence conditions explicit, as demonstrated in the following query q'_1 .

$$q'_1 = \pi_{empno^{(V_4 \vee V_5) \wedge \neg V_3}, name^{V_4 \wedge \neg V_3 \wedge \neg V_5}, firstname^{V_5 \wedge \neg V_3 \wedge \neg V_4}, lastname^{V_5 \wedge \neg V_3 \wedge \neg V_4}}(empbio)$$

The result of the query q'_1 is still Table 4.2. Note that all the variation encoded in the VDB is applied to the result of a query. Thus, the result of a variational query stands on its own, that is, it is not part of a bigger structure like the variational tables in a VDB.

In the example, note that the user does not need to repeat the variability

encoded in the variational schema in their query, that is, they do not need to annotate *name*, *firstname*, and *lastname* with V_4 , V_5 , and V_5 , respectively. We discuss this in more detail in Section 4.4. q_1 queries all three variants simultaneously although the returned results are only associated with variants V_4 and V_5 due to the annotation of the attribute *empno* in the query and the presence conditions of the rest of the projected attributes in the schema. Yet, the query can be further simplified with a choice. q_2 selects only two out of the three variants explicitly:

$$q_2 = \neg V_3 \langle \pi_{empno, name, firstname, lastname}(empbio), \varepsilon \rangle$$

Table 4.3 shows the result of this query over the VDB described in Example 4.1.1.

Table 4.3: Result of the v-query $q_2 = \neg V_3 \langle \pi_{empno, name, firstname, lastname}(empbio), \varepsilon \rangle$.

$oneof(V_3, V_4, V_5) \wedge \neg V_3$	true	V_4	V_5	V_5	true
<i>result</i>	<i>empno</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>	<i>prescond</i>
	12001	Ulf Hofstetter	Ulf	Hofstetter	$V_4 \vee V_5$
	12002	Luise McFarlan	Luise	McFarlan	$V_4 \vee V_5$
	12003	Shir DuCasse	Shir	DuCasse	$V_4 \vee V_5$
	80001	Nagui Merli	Nagui	Merli	$V_4 \vee V_5$
	80002	Mayuko Meszaros	Mayuko	Meszaros	$V_4 \vee V_5$
	80003	Theirry Viele	Theirry	Viele	$V_4 \vee V_5$
	200001	Selwyn Koshiba	Selwyn	Koshiba	V_5
	200002	Bedrich Markovitch	Bedrich	Markovitch	V_5
	200003	Pascal Benzmueller	Pascal	Benzmueller	V_5

Note that, as shown in Table 4.2 and Table 4.3, queries q_1 and q_2 return the same set of variational tuples. However, the first three tuples in Table 4.2 could belong to a variant that enables any of V_3 – V_5 whereas the first three tuples in Table 4.3 could only belong to variants that either enable V_4 or V_5 . This difference is due to the difference in their table’s presence conditions, that is, q_2 filters out tuples that belong to variant V_3 at the schema level while q_1 does not. We discuss

Eric, pls read this paragraph. I updated it after updating the tables.

this more in Example ???. More importantly, even though the first three tuples in Table 4.2 could belong to a variant that enables V_3 configuring Table 4.2 for such a variant drops the first three tuples since all their attributes would be `NULL`. We illustrate how configuring Table 4.2 for variant $\{V_3\}$ drops the first three tuples in Example 4.2.1.

Expressing the same intent over several database variants by a single query relieves the DBA from maintaining separate queries for different variants or configurations of the schema. Example 4.1.2 illustrates this point.

Example 4.1.2. Assume a VDB with $F = \{V_1, \dots, V_5\}$ and the corresponding basic schema variants in Table 1.1. The user wants to get all employee names across all variants. They express this intent by the query q_3 :

$$\begin{aligned} q_3 = & V_1 \langle (\pi_{name}(engineerpersonnel)) \cup (\pi_{name}(otherpersonnel)) \\ & , (V_2 \vee V_3) \langle \pi_{name}(empacct) \\ & , (V_4 \vee V_5) \langle \pi_{name,firstname,lastname}(empbio, \varepsilon) \rangle \rangle \rangle \end{aligned}$$

Since the variational schema enforces that exactly one of V_1 – V_5 be enabled, we can simplify the query by omitting the final choice.

$$\begin{aligned} q_4 = & V_1 \langle (\pi_{name}(engineerpersonnel)) \cup (\pi_{name}(otherpersonnel)) \\ & , (V_2 \vee V_3) \langle \pi_{name}(empacct), \pi_{name,firstname,lastname}(empbio) \rangle \rangle \end{aligned}$$

In principle, variational queries can also express arbitrarily different intents

over different database variants. However, we expect that variational queries are best used to capture single (or at least related) intents that vary in their realization since this is easier to understand and increases the potential for sharing in both the representation and execution of a variational query.

4.2 VRA Semantics

We use the semantics of relational queries to define the semantics of variational queries. We first define the configuration function for variational queries which takes a configuration and a variational query and returns a relational query, Section 4.2.1. We also define another version of the variational query configuration function that generates unique relational query variants, Section 4.2.1. Then, we define an accumulation function that accumulates multiple (annotated) relational tables into a variational table, Section 4.2.2. Finally, we define the denotational semantics of VRA using the defined configuration and accumulation functions, Section 4.2.3.

4.2.1 VRA Configuration

The *configuration* function maps a variational query under a configuration to a relational query, defined in Figure 4.2. Thus, a variational query can be understood as a set of relational queries that their results is gathered in a single table and tagged with the feature expression stating their variant. Users can deploy

Variational condition configuration:

$$\begin{aligned}
& \mathbb{C}[\cdot] : \text{Condition} \rightarrow \text{Config} \rightarrow \underline{\text{Condition}} \\
& \mathbb{C}[b]_c = b \\
& \mathbb{C}[a \bullet k]_c = a \bullet k \\
& \mathbb{C}[a_1 \bullet a_2]_c = a_1 \bullet a_2 \\
& \mathbb{C}[\neg\theta]_c = \neg\mathbb{C}[\theta]_c \\
& \mathbb{C}[\theta_1 \vee \theta_2]_c = \mathbb{C}[\theta_1]_c \vee \mathbb{C}[\theta_2]_c \\
& \mathbb{C}[\theta_1 \wedge \theta_2]_c = \mathbb{C}[\theta_1]_c \wedge \mathbb{C}[\theta_2]_c \\
& \mathbb{C}[e\langle\theta_1, \theta_2\rangle]_c = \begin{cases} \mathbb{C}[\theta_1]_c, & \text{if } \mathbb{E}[e]_c = \text{true} \\ \mathbb{C}[\theta_2]_c, & \text{otherwise} \end{cases}
\end{aligned}$$

Variational query configuration:

$$\begin{aligned}
& \mathbb{Q}[\cdot] : \mathbf{Q} \rightarrow \text{Config} \rightarrow \underline{\mathbf{Q}} \\
& \mathbb{Q}[r]_c = \mathbb{R}[r]_c = \underline{r} \\
& \mathbb{Q}[\sigma_\theta q]_c = \sigma_{\mathbb{C}[\theta]_c} \mathbb{Q}[q]_c \\
& \mathbb{Q}[\pi_A q]_c = \pi_{\mathbb{A}[A]_c} \mathbb{Q}[q]_c \\
& \mathbb{Q}[q_1 \times q_2]_c = \mathbb{Q}[q_1]_c \times \mathbb{Q}[q_2]_c \\
& \mathbb{Q}[e\langle q_1, q_2\rangle]_c = \begin{cases} \mathbb{Q}[q_1]_c, & \text{if } \mathbb{E}[e]_c = \text{true} \\ \mathbb{Q}[q_2]_c, & \text{otherwise} \end{cases} \\
& \mathbb{Q}[q_1 \circ q_2]_c = \mathbb{Q}[q_1]_c \circ \mathbb{Q}[q_2]_c \\
& \mathbb{Q}[\varepsilon]_c = \varepsilon
\end{aligned}$$

Figure 4.2: Configuration of variational queries and conditions. The configuration function assumes that the input, either the variational query or the variational condition, is well-typed.

queries for a specific variant by configuring them. Example 4.2.1 illustrates configuring a query and Example 4.2.2 illustrates the configuration of query q'_1 from Example 4.1.1 and their corresponding relational results table.

Example 4.2.1. Assume the underlying VDB has the variational schema $S_3 = \{r(a_1^{f_1}, a_2, a_3)^{f_1 \vee f_2}\}$ and the feature space $F = \{f_1, f_2\}$. For valid configurations of this VDB (i.e., $\{f_1, f_2\}$, $\{f_1\}$, $\{f_2\}$, and $\{\}$), the variational query $q_5 = \pi_{a_1, a_2, f_1 \wedge f_2, a_3, f_2}(r)$ is configured to the following relational queries:

$$\mathbb{Q}[q_5]_{\{f_1\}} = \pi_{a_1} \underline{r}$$

$$\mathbb{Q}[q_5]_{\{\}} = \pi_{a_1} \underline{r}$$

$$\mathbb{Q}[q_5]_{\{f_2\}} = \pi_{a_1, a_3} \underline{r}$$

$$\mathbb{Q}[q_5]_{\{f_1, f_2\}} = \pi_{a_1, a_2, a_3} \underline{r}$$

Example 4.2.2. Consider the query q'_1 given in Example 4.1.1:

$$q'_1 = \pi_{empno(V_4 \vee V_5) \wedge \neg V_3, name^{V_4 \wedge \neg V_3 \wedge \neg V_5}, firstname^{V_5 \wedge \neg V_3 \wedge \neg V_4}, lastname^{V_5 \wedge \neg V_3 \wedge \neg V_4}}(empbio).$$

Configuring q'_1 for all valid configurations ($\{V_3\}$, $\{V_4\}$, $\{V_5\}$) of the given VDB results in three relational queries:

$$\mathbb{Q}[q'_1]_{\{V_3\}} = \varepsilon$$

$$\mathbb{Q}[q'_1]_{\{V_4\}} = \pi_{empno, name}(empbio)$$

$$\mathbb{Q}[q'_1]_{\{V_5\}} = \pi_{empno, firstname, lastname}(empbio)$$

Table 4.4 shows the result of these relational queries.

Table 4.4: Results of relational queries from configuring the variational query q'_1 .

(a) Result of the query $\mathbb{Q}[[q'_1]]_{\{V_3\}} = \varepsilon$.

<i>result</i>	

(b) Result of the query $\mathbb{Q}[[q'_1]]_{\{V_4\}} = \pi_{empno, name}(empbio)$.

<i>result</i>	<i>empno</i>	<i>name</i>
	12001	Ulf Hofstetter
	12002	Luise McFarlan
	12003	Shir DuCasse
	80001	Nagui Merli
	80002	Mayuko Meszaros
	80003	Theirry Viele

(c) Result of the query $\mathbb{Q}[[q'_1]]_{\{V_5\}} = \pi_{empno, firstname, lastname}(empbio)$.

<i>result</i>	<i>empno</i>	<i>firstname</i>	<i>lastname</i>
	12001	Ulf	Hofstetter
	12002	Luise	McFarlan
	12003	Shir	DuCasse
	80001	Nagui	Merli
	80002	Mayuko	Meszaros
	80003	Theirry	Viele
	200001	Selwyn	Koshiba
	200002	Bedrich	Markovitch
	200003	Pascal	Benzmuller

Often a variational query will yield the same plain query for multiple configurations. For our semantics, it is useful to get the set of unique variants of a variational query. Thus, we define the *unique variants* function $\mathcal{Q}(.,.) : \mathbf{Q} \rightarrow \mathbf{Set\ FeatName} \rightarrow \mathbf{Set\ (Var\ Q)}$ that takes a variational query and VDB's set of features and returns a set of configured relational queries annotated with a presence condition. The presence condition is a feature expression generated from the set of

Eric, pls
re-read the
following
up to Fig-
ure 4.3

configurations that configured the variational query into the same relational query. To generate this presence condition from configurations we need to know the closed set of VDB's features. This is done by the $genFexp(c, F)$ that takes a configuration and a closed set of features and generates the feature expression e that is only satisfiable by the configuration c . For example, $genFexp(\{f_1\}, \{f_1, f_2\}) = f_1 \wedge \neg f_2$ and $genFexp(\{f_1, f_2\}, \{f_1, f_2\}) = f_1 \wedge f_2$. Remember that the set of enabled features of a configuration denote the said configuration, for example, $\{f_1\}$ denotes the configuration in which only feature f_1 has been enabled.

In essence, the unique variants function can be defined for all data types that encode variation. For example, the unique configuration function for variational queries can be defined by

$$\begin{aligned} \mathcal{Q}(q, F) = \{ \underline{q}^e \mid e = \bigvee_{e_i \in es} e_i, es = \{e_i \mid \forall c \in \mathbf{Config}. \mathbb{Q}[\![q]\!]_c = \underline{q}, e_i = genFexp(c, F)\} \\ , \exists c \in \mathbf{Config}. \mathbb{E}[\![e]\!]_c = \mathbf{true}, \mathbb{Q}[\![q]\!]_c = \underline{q} \} \end{aligned}$$

. Consequently, the unique configuration for variational sets of attributes (i.e., $\mathcal{A}(.,.) : \mathbf{Set}(\mathbf{Var} \mathbf{AttrName}) \rightarrow \mathbf{Set} \mathbf{FeatName} \rightarrow \mathbf{Var}(\mathbf{Set} \mathbf{AttrName})$) and variational conditions (i.e., $\mathcal{C}(.,.) : \mathbf{Condition} \rightarrow \mathbf{Set} \mathbf{FeatName} \rightarrow \mathbf{Var} \mathbf{Condition}$) are defined similarly. However, this definition is not efficient since it is still enumerating all possible configurations. Thus, we define the more efficient unique configuration function for variational queries in Figure 4.3.

Example 4.2.3. Consider the query $q_5 = \pi_{a_1, a_2 f_1 \wedge f_2, a_3 f_2}(r)$ given in Example 4.2.1.

$$\begin{aligned}
\mathcal{Q}(\cdot, \cdot) : \mathbf{Q} &\rightarrow \mathbf{Set} \text{ FeatName} \rightarrow \mathbf{Set} \text{ (Var } \underline{\mathbf{Q}}) \\
\mathcal{Q}(r, F) &= \{\underline{r}^{\mathbf{true}}\} \\
\mathcal{Q}(\sigma_\theta q, F) &= \{(\sigma_\theta \underline{q})^{e \wedge e_\theta} \mid \underline{q}^e \in \mathcal{Q}(q, F), \underline{\theta}^{e_\theta} \in \mathcal{C}(\theta, F)\} \\
\mathcal{Q}(\pi_A q, F) &= \{(\pi_A \underline{q})^{e \wedge e_A} \mid \underline{q}^e \in \mathcal{Q}(q, F), \underline{A}^{e_A} \in \mathcal{A}(A, F)\} \\
\mathcal{Q}(q_1 \times q_2, F) &= \{(\underline{q}_1 \times \underline{q}_2)^{e_1 \wedge e_2} \mid \underline{q}_1^{e_1} \in \mathcal{Q}(q_1, F), \underline{q}_2^{e_2} \in \mathcal{Q}(q_2, F)\} \\
\mathcal{Q}(q_1 \bowtie_\theta q_2, F) &= \{(\underline{q}_1 \bowtie_\theta \underline{q}_2)^{e_1 \wedge e_2 \wedge e_\theta} \mid \underline{q}_1^{e_1} \in \mathcal{Q}(q_1, F), \underline{q}_2^{e_2} \in \mathcal{Q}(q_2, F), \underline{\theta}^{e_\theta} \in \mathcal{C}(\theta, F)\} \\
\mathcal{Q}(e\langle q_1, q_2 \rangle, F) &= \{\underline{q}_1^{e \wedge e_1} \mid \underline{q}_1^{e_1} \in \mathcal{Q}(q_1, F)\} \cup \{\underline{q}_2^{e \wedge e_2} \mid \underline{q}_2^{e_2} \in \mathcal{Q}(q_2, F)\} \\
\mathcal{Q}(q_1 \circ q_2, F) &= \{(\underline{q}_1 \circ \underline{q}_2)^{e_1 \wedge e_2} \mid \underline{q}_1^{e_1} \in \mathcal{Q}(q_1, F), \underline{q}_2^{e_2} \in \mathcal{Q}(q_2, F)\} \\
\mathcal{Q}(\varepsilon, F) &= \varepsilon^{\mathbf{true}}
\end{aligned}$$

Figure 4.3: Unique configuration of variational queries. The unique configuration function assumes that the input variational query is well-typed.

The unique configuration of this query results in the following set of queries:

$$\mathcal{Q}(q_5, \{f_1, f_2\}) = \{(\pi_{a_1}(\underline{r}))^{(f_1 \wedge \neg f_2) \vee (\neg f_1 \wedge \neg f_2)}, (\pi_{a_1, a_3}(\underline{r}))^{\neg f_1 \wedge f_2}, (\pi_{a_1, a_2, a_3}(\underline{r}))^{f_1 \wedge f_2}\}.$$

Example 4.2.4. Consider the query q'_1 configured in Example 4.2.2:

$$q'_1 = \pi_{empno^{(V_4 \vee V_5) \wedge \neg V_3}, name^{V_4 \wedge \neg V_3 \wedge \neg V_5}, firstname^{V_5 \wedge \neg V_3 \wedge \neg V_4}, lastname^{V_5 \wedge \neg V_3 \wedge \neg V_4}}(empbio).$$

The unique configuration of it results in:

$$\begin{aligned}
\mathcal{Q}(q'_1, \{V_3, V_4, V_5\}) &= \{\varepsilon^{V_3 \wedge \neg V_4 \wedge \neg V_5}, (\pi_{empno, name}(empbio))^{\neg V_3 \wedge V_4 \wedge \neg V_5} \\
&\quad, (\pi_{empno, firstname, lastname}(empbio))^{\neg V_3 \wedge V_4 \wedge \neg V_5}\}.
\end{aligned}$$

4.2.2 Accumulation of Relational Tables to a Variational Table

After connecting variational queries to relational queries, to define the semantics of VRA we need to connect the results of multiple relational queries to the result of a single variational query. Since we have two approaches to connect a variational query to relational queries we define two *accumulation* functions that generate a variational table from a set of relational tables. The first accumulation function $accum : \text{Set FeatName} \rightarrow \text{Set (Config, Table)} \rightarrow \text{Table}$ takes the feature space of a database and a set of relational tables with their attached configurations and generates a variational table. Figure 4.4 defines this function in terms of some auxiliary functions. The *mkTable* function takes a variational relation schema and a set of variational relation contents and generates a variational table that has the given schema and the variational tuples in the input tables. The *addPresCondToConfTables* function maps the *addPresCondToConfContent* over a set of tables and their attached configuration and the *addPresCondToConfContent* function adds the *prescond* attribute to a relational table and its corresponding value which is a feature expression associated with the given configuration using the closed set of features. The *fitConfTablesToVsch* maps the function *fitTableToVsch* to tables of a set of relational tables and their attached configuration. The *fitTableToVsch* function adjusts a table, both its schema and content, to a variational relation schema. The *tablesToVsch* maps the function *schToVsch* to a set of relational tables and their attached configuration. The *schToVsch* generates a variational relation schema from a set of plain relation schema and their

pls read
this entire
section.
thx!

Table accumulation function:

$$\begin{aligned}
& accum : \text{Set FeatName} \rightarrow \text{Set (Config, \underline{Table})} \rightarrow \text{Table} \\
& accum \ F \ ts = mkTable \ vsch \ tables \\
& \text{where } vsch = tablesToVsch \ F \ ts \\
& \quad tables = addPresCondToConfTables \ F \ fitted \\
& \quad fitted = fitConfTablesToVsch \ ts \ vsch
\end{aligned}$$

Auxiliary functions for table accumulation:

$$\begin{aligned}
& schToVsch : \text{Set FeatName} \rightarrow \text{Set (Config, \underline{RelSch})} \rightarrow \text{RelSch} \\
& tablesToVsch : \text{Set FeatName} \rightarrow \text{Set (Config, \underline{Table})} \rightarrow \text{RelSch} \\
& fitTableToVsch : \underline{\text{Table}} \rightarrow \text{RelSch} \rightarrow \underline{\text{Table}} \\
& fitConfTablesToVsch : \text{Set (Config, \underline{Table})} \rightarrow \text{RelSch} \rightarrow \text{Set (Config, \underline{Table})} \\
& addPresCondToConfContent : \text{Set FeatName} \rightarrow (\text{Config, \underline{RelCont}}) \rightarrow \text{RelCont} \\
& addPresCondToConfTables : \text{Set FeatName} \rightarrow \text{Set (Config, \underline{Table})} \rightarrow \text{Set RelCont} \\
& mkTable : \text{RelSch} \rightarrow \text{Set RelCont} \rightarrow \text{Table}
\end{aligned}$$

Figure 4.4: Accumulation function of a set of relational tables with their attached configuration into a variational table and its auxiliary functions. The definition uses spaces to pass parameters. For example, $f \ x$ states that the parameter x is passed to the function x and $f \ x \ y$ states that parameters x and y are passed to f as the first and second arguments, respectively.

attached configuration given the closed set of features of the database’s feature space.¹ Note that to generate a feature expression from a configuration it is essential to pass the closed set of features. Example 4.2.5 illustrates the behavior of these auxiliary functions and the table accumulation function over the relational tables in Table 4.4.

Example 4.2.5. Consider the query q'_1 written over the VDB with variational

¹In implementation, for efficiency, we pass the type of the query from VRA’s type system as the variational relation schema that is generated by the *tablesToVsch* function.

schema S_2 and feature space $F = \{V_3, V_4, V_5\}$, all given in Example 4.1.1. All configured relational queries of q'_1 for VDB's valid configurations and their corresponding results in form of a relational table are given in Example 4.2.2 and Table 4.4, respectively. Now we show how the relational tables of the configured queries, shown in Table 4.4, are accumulated to the variational table, shown in Table 4.2, as the result of the variational query q'_1 by using the table accumulation function *accum*. As the first step of accumulation, we generate the variational relation schema by applying *tablesToVsch* to tables in Table 4.4. This results in the variational relation schema s_{accum}

$$s_{accum} = result(empno^{(\neg V_3 \wedge V_4 \wedge \neg V_5) \vee (\neg V_3 \wedge \neg V_4 \wedge V_5)}, name^{\neg V_3 \wedge V_4 \wedge \neg V_5}, \\ firstname^{\neg V_3 \wedge \neg V_4 \wedge V_5}, lastname^{\neg V_3 \wedge \neg V_4 \wedge V_5})_{oneof(V_3, V_4, V_5)}$$

Note that the presence conditions are generated based on the configurations attached to the tables. For example, the presence condition $(\neg V_3 \wedge V_4 \wedge \neg V_5) \vee (\neg V_3 \wedge \neg V_4 \wedge V_5)$ associated with the attribute *empno* is the disjunction of two feature expressions $(\neg V_3 \wedge V_4 \wedge \neg V_5)$ and $(\neg V_3 \wedge \neg V_4 \wedge V_5)$ where they represent the configuration $\{V_4\}$ (associated to Table 4.4b) and $\{V_5\}$ (associated to Table 4.4c), respectively. That is, the configuration $\{ \} V_4$ represents the variants that only enable the feature V_4 from V_3 – V_5 , thus, its corresponding feature expression is $(\neg V_3 \wedge V_4 \wedge \neg V_5)$. That is why we need to pass the closed set of features to the auxiliary functions (to generate feature expression corresponding to configurations).

In the next step, the tables in Table 4.4 are adjusted so that they all match a

certain relation schema. This is achieved by the *fitConfTablesToVsch* which gets all the tables in Table 4.4 with their associated configurations and the variational relation schema generated by passing them to the *tablesToVsch*. This is done by mapping the *fitTableToVsch* to all the tables in Table 4.4 with their associated configurations. This function simply adds attributes of the variational relation schema to the table that do not exists in the table and puts NULL as values (indicated by the white space) in the tuples for those attributes. Table 4.5–Table 4.7 illustrate the application of *fitTableToVsch* to Table 4.4a–Table 4.4c and variational relation schema s_{accum} .

Table 4.5: Result of the *fitTableToVsch* applied to Table 4.4a and variational relation schema s_{accum} .

<i>result</i>	<i>empno</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>
---------------	--------------	-------------	------------------	-----------------

Table 4.6: Result of the *fitTableToVsch* applied to Table 4.4b and variational relation schema s_{accum} .

<i>result</i>	<i>empno</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>
	12001	Ulf Hofstetter		
	12002	Luise McFarlan		
	12003	Shir DuCasse		
	80001	Nagui Merli		
	80002	Mayuko Meszaros		
	80003	Theirry Viele		

Then, the *addPresCondToConfContent* function adds the presence condition attribute and its values to relation contents of Table 4.5–Table 4.7, resulting in Table 4.8 which illustrates a set of relation contents that are separated by the red

Table 4.7: Result of the *fitTableToVsch* applied to Table 4.4c and variational relation schema s_{accum} .

<i>result</i>	<i>empno</i>	<i>name</i>	<i>firstname</i>	<i>lastname</i>
	12001		Ulf	Hofstetter
	12002		Luisse	McFarlan
	12003		Shir	DuCasse
	80001		Nagui	Merli
	80002		Mayuko	Meszaros
	80003		Theirry	Viele
	200001		Selwyn	Koshiba
	200002		Bedrich	Markovitch
	200003		Pascal	Benzmuller

bold line. Note that since Table 4.5 does not have any tuples Table 4.8 does not have any tuples associated with the variant $\{V_3\}$.

Finally, the *mkTable* function takes the variational relation schema s_{accum} and Table 4.8. Note that the values in tuples of Table 4.8 follow the order of the attributes in the variational relation schema. This results in Table 4.9 which is equivalent to the result of q'_1 given in Table 4.2.

The second accumulation function $accum' : \text{Set}(\text{Var } \underline{\text{Table}}) \rightarrow \text{Table}$ takes a set of relational tables that are annotated with a feature expression instead of their attached configuration. Figure 4.5 defines this function and its auxiliary functions. The auxiliary functions are similar to the ones defined in Figure 4.5 except that they do not need to generate a feature expression from a configuration and a set of closed features.

Table 4.8: Step three of table accumulation adds the presence condition values to relation contents. The table illustrates a set of relation contents that are separated by the red bold line between them. The tuples follow the order of attributes in the relation schema.

12001	Ulf Hofstetter			$\neg V_3 \wedge V_4 \wedge \neg V_5$
12002	Luisse McFarlan			$\neg V_3 \wedge V_4 \wedge \neg V_5$
12003	Shir DuCasse			$\neg V_3 \wedge V_4 \wedge \neg V_5$
80001	Nagui Merli			$\neg V_3 \wedge V_4 \wedge \neg V_5$
80002	Mayuko Meszaros			$\neg V_3 \wedge V_4 \wedge \neg V_5$
80003	Theirry Viele			$\neg V_3 \wedge V_4 \wedge \neg V_5$
...
12001	Ulf	Hofstetter		$\neg V_3 \wedge \neg V_4 \wedge V_5$
12002	Luisse	McFarlan		$\neg V_3 \wedge \neg V_4 \wedge V_5$
12003	Shir	DuCasse		$\neg V_3 \wedge \neg V_4 \wedge V_5$
80001	Nagui	Merli		$\neg V_3 \wedge \neg V_4 \wedge V_5$
80002	Mayuko	Meszaros		$\neg V_3 \wedge \neg V_4 \wedge V_5$
80003	Theirry	Viele		$\neg V_3 \wedge \neg V_4 \wedge V_5$
200001	Selwyn	Koshiba		$\neg V_3 \wedge \neg V_4 \wedge V_5$
200002	Bedrich	Markovitch		$\neg V_3 \wedge \neg V_4 \wedge V_5$
200003	Pascal	Benzmuller		$\neg V_3 \wedge \neg V_4 \wedge V_5$
...

Table 4.9: Final step of table accumulation passes the variational relation schema s_{accum} and relation contents in Table 4.8 to the *mkTable* function.

$oneof(V_3, V_4, V_5)$	$(\neg V_3 \wedge V_4 \wedge \neg V_5)$	$(\vee(\neg V_3 \wedge \neg V_4 \wedge V_5))$	$\neg V_3 \wedge V_4 \wedge \neg V_5$	$\neg V_3 \wedge \neg V_4 \wedge V_5$	$\neg V_3 \wedge \neg V_4 \wedge V_5$	true
result	empno	name	firstname	lastname	prescond	
	12001	Ulf Hofstetter			$\neg V_3 \wedge V_4 \wedge \neg V_5$	
	12002	Luisse McFarlan			$\neg V_3 \wedge V_4 \wedge \neg V_5$	
	12003	Shir DuCasse			$\neg V_3 \wedge V_4 \wedge \neg V_5$	
	80001	Nagui Merli			$\neg V_3 \wedge V_4 \wedge \neg V_5$	
	80002	Mayuko Meszaros			$\neg V_3 \wedge V_4 \wedge \neg V_5$	
	80003	Theirry Viele			$\neg V_3 \wedge V_4 \wedge \neg V_5$	
	12001		Ulf	Hofstetter	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	12002		Luisse	McFarlan	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	12003		Shir	DuCasse	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	80001		Nagui	Merli	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	80002		Mayuko	Meszaros	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	80003		Theirry	Viele	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	200001		Selwyn	Koshiba	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	200002		Bedrich	Markovitch	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	200003		Pascal	Benzmuller	$\neg V_3 \wedge \neg V_4 \wedge V_5$	
	

Table accumulation function:

$$\begin{aligned}
 accum' &: \text{Set } (\text{Var } \underline{\text{Table}}) \rightarrow \text{Table} \\
 accum' \ ts &= mkTable \ vsch \ tables \\
 \text{where } vsch &= annotTablesToVsch \ ts \\
 tables &= addPresCondToVarTables \ fitted \\
 fitted &= fitVarTablesToVsch \ ts \ vsch
 \end{aligned}$$

Auxiliary functions for table accumulation:

$$\begin{aligned}
 annotSchToVsch &: \text{Set } (\text{Var } \underline{\text{RelSch}}) \rightarrow \text{RelSch} \\
 annotTablesToVsch &: \text{Set } (\text{Var } \underline{\text{Table}}) \rightarrow \text{RelSch} \\
 fitVarTablesToVsch &: \text{Set } (\text{Var } \underline{\text{Table}}) \rightarrow \text{RelSch} \rightarrow \text{Set } (\text{Var } \underline{\text{Table}}) \\
 addPresCondToVarContent &: \text{Var } \underline{\text{RelCont}} \rightarrow \text{RelCont} \\
 addPresCondToVarTables &: \text{Set } (\text{Var } \underline{\text{Table}}) \rightarrow \text{Set } \text{RelCont}
 \end{aligned}$$

Figure 4.5: Accumulation function of a set of relational tables annotated with a feature expression into a variational table and its auxiliary functions. The definition uses spaces to pass parameters, e.g., $f \ x = f(x)$ and $f \ x \ y = f(x, y)$.

4.2.3 VRA Denotational Semantics

Now that we have all required parts we define the denotational semantics of variational relational algebra using the denotational semantics of relational algebra.

The denotational semantics of relational queries $rqSem : \underline{\mathbf{Q}} \rightarrow \underline{\mathbf{DBInst}} \rightarrow \underline{\mathbf{Table}}$ takes a plain query and a plain database and returns a table named *result*. We do not give a formal definition of $rqSem$, however, examples of the semantics of a query are given in Table 4.4. We then define the VRA denotational semantics $vgSem : \underline{\mathbf{Q}} \rightarrow \underline{\mathbf{DBInst}} \rightarrow \underline{\mathbf{Table}}$ as the accumulation of relational tables resulted from the semantics of its configured queries over their corresponding configured databases for all valid configurations of a variational database. The $mapRQSem$ takes a set

pls read
this entire
section.
thx!

VRA denotational semantics:

$$\begin{aligned}
 & \text{vqSem} : \mathbf{Q} \rightarrow \mathbf{DBInst} \rightarrow \mathbf{Table} \\
 & \text{vqSem } q \, \mathcal{I} = \text{accum } fs \, tabs \\
 & \text{where } fs = \text{features } \mathcal{I} \\
 & \quad rqs = qToConfRelQs \, q \, (\text{validConfigs } \mathcal{I}) \\
 & \quad tabs = \text{mapRQSem } rqs \, \mathcal{I}
 \end{aligned}$$

Auxiliary functions for VRA denotational semantics:

$$\begin{aligned}
 & \text{rqSem} : \underline{\mathbf{Q}} \rightarrow \underline{\mathbf{DBInst}} \rightarrow \underline{\mathbf{Table}} \\
 & \text{mapRQSem} : \mathbf{Set} \, (\mathbf{Config}, \underline{\mathbf{Q}}) \rightarrow \mathbf{DBInst} \rightarrow \mathbf{Set} \, (\mathbf{Config}, \underline{\mathbf{Table}}) \\
 & \text{features} : \mathbf{DBInst} \rightarrow \mathbf{Set} \, \mathbf{FeatName} \\
 & \text{validConfigs} : \mathbf{DBInst} \rightarrow \mathbf{Set} \, \mathbf{Config} \\
 & qToConfRelQs : \mathbf{Q} \rightarrow \mathbf{Set} \, \mathbf{Config} \rightarrow \mathbf{Set} \, (\mathbf{Config}, \underline{\mathbf{Q}})
 \end{aligned}$$

Figure 4.6: Denotational semantics of variational relational algebra.

of relational queries with their attached configurations and a variational database instance and returns the set of query semantics over their configured database with their attached configurations, that is, it maps rqSem on the relational queries over their corresponding relational database.²

4.3 VRA Type System

[type sys] [work on the derivation tree example separate from the text since youre

²In implementation, the closed set of features and valid configurations of a VDB are contained within, instead of extracting them from the database. However, we keep the formalization simple and assume that they can also be retrieved from the VDB.

waiting for eric on the text]

4.4 Explicitly Annotating Queries

Variational queries do not need to repeat information that can be inferred from the variational schema or the type of a query. For example, the query q_1 shown in Example 4.1.1 does not contradict the schema and thus is type correct. However, it does not include the presence conditions of attributes and the relation encoded in the schema while q_6 repeats this information:

$$q_6 = \pi_{empno(V_4 \vee V_5) \wedge \neg V_3, name \neg V_3 \wedge V_4 \wedge \neg V_5, firstname \neg V_3 \wedge \neg V_4 \wedge V_5, lastname \neg V_3 \wedge \neg V_4 \wedge V_5} (e_2 \langle empbio, \varepsilon \rangle).$$

3

I added the footnote to be more explicit about the example.

Similarly, the projection in the query $q_7 = \pi_{name,firstname}(subq_7)$ where $subq_7 = V_4 \langle \pi_{name}(q_6), \pi_{firstname}(q_6) \rangle$ is written over S_2 and it does not repeat the presence conditions of attributes from its $subq_7$'s type. The query $q_8 = \pi_{name^{V_4},firstname^{\neg V_4}}(subq_7)$ makes the annotations of projected attributes *explicit* with respect to both the variational schema S_2 and its subquery's type. Although relieving the user from explicitly repeating variation makes VRA easier to use, queries still have to state variation explicitly to avoid losing information when decoupled from the schema. We do this by defining the function $\lfloor q \rfloor_S : \mathbf{Q} \rightarrow \mathbf{Sch} \rightarrow \mathbf{Q}$, that *explicitly annotates a query q with the schema S* . The explicitly annotating query function, formally defined in Figure 4.10, conjoins attributes and relations presence condi-

³The query q_6 is the simplified version of
 $\lfloor q_1 \rfloor_{S_2} = \pi_{empno(V_4 \vee V_5) \wedge \neg V_3, name \neg V_3 \wedge V_4 \wedge \neg V_5, firstname \neg V_3 \wedge \neg V_4 \wedge V_5, lastname \neg V_3 \wedge \neg V_4 \wedge V_5} (\lfloor empbio \rfloor_{S_2})$
 where $\lfloor empbio \rfloor_{S_2} = e_2 \langle \pi_{empno, name^{V_4}, firstname^{V_5}, lastname^{V_5}}(empbio), \varepsilon \rangle$.

Variational queries typing rules:

$$\begin{array}{c}
\text{EMPTYRELATION-E} \\
\frac{}{e, S \vdash \varepsilon : \{\}^{\text{false}}}
\end{array}
\quad
\begin{array}{c}
\text{RELATION-E} \\
\frac{r(A)^{e'} \in S \quad \text{sat}(e \wedge pc(s, S))}{e, S \vdash r : A^{e \wedge e'}}
\end{array}$$

$$\begin{array}{c}
\text{PROJECT-E} \\
\frac{e, S \vdash q : A'^{e'} \quad |\downarrow(A^e)| = |A| \quad A \prec \downarrow(A'^{e'})}{e, S \vdash \pi_A q : (A \cap A')^{e'}}
\end{array}$$

$$\begin{array}{c}
\text{SELECT-E} \\
\frac{e, S \vdash q : A^{e'} \quad e, \downarrow(A^{e'}) \vdash \theta}{e, S \vdash \sigma_\theta q : A^{e'}}
\end{array}
\quad
\begin{array}{c}
\text{CHOICE-E} \\
\frac{e \wedge e', S \vdash q_1 : A_1^{e_1} \quad e \wedge \neg e', S \vdash q_2 : A_2^{e_2}}{e, S \vdash e' \langle q_1, q_2 \rangle : (\downarrow(A_1^{e_1}) \cup \downarrow(A_2^{e_2}))^{(e_1) \vee (e_2)}}
\end{array}$$

$$\begin{array}{c}
\text{PRODUCT-E} \\
\frac{e, S \vdash q_1 : A_1^{e_1} \quad e, S \vdash q_2 : A_2^{e_2} \quad \downarrow(A_1^{e_1}) \cap \downarrow(A_2^{e_2}) = \{\}}{e, S \vdash q_1 \times q_2 : (\downarrow(A_1^{e_1}) \cup \downarrow(A_2^{e_2}))^{e_1 \wedge e_2}}
\end{array}$$

$$\begin{array}{c}
\text{SETOP-E} \\
\frac{e, S \vdash q_1 : A_1^{e_1} \quad e, S \vdash q_2 : A_2^{e_2} \quad \downarrow(A_1^{e_1}) \equiv \downarrow(A_2^{e_2})}{e, S \vdash q_1 \circ q_2 : A_1^{e_1}}
\end{array}$$

Variational condition typing rules:

$$\begin{array}{c}
\text{BOOLEAN-C} \\
e, A \vdash b
\end{array}
\quad
\begin{array}{c}
\text{CONJUNCTION-C} \\
\frac{e, A \vdash \theta_1 \quad e, A \vdash \theta_2}{e, A \vdash \theta_1 \wedge \theta_2}
\end{array}
\quad
\begin{array}{c}
\text{DISJUNCTION-C} \\
\frac{e, A \vdash \theta_1 \quad e, A \vdash \theta_2}{e, A \vdash \theta_1 \vee \theta_2}
\end{array}$$

$$\begin{array}{c}
\text{CHOICE-C} \\
\frac{e \wedge e', A \vdash \theta_1 \quad e \wedge \neg e', A \vdash \theta_2}{e, A \vdash e' \langle \theta_1, \theta_2 \rangle}
\end{array}
\quad
\begin{array}{c}
\text{NEG-C} \\
\frac{e, A \vdash \theta}{e, A \vdash \neg \theta}
\end{array}$$

$$\begin{array}{c}
\text{ATTOPTVAL-C} \\
\frac{a^{e'} \in A \quad \text{sat}(e' \wedge e)}{e, A \vdash a \bullet k}
\end{array}
\quad
\begin{array}{c}
\text{ATTOPTATT-C} \\
\frac{a_1^{e_1} \in A \quad a_2^{e_2} \in A \quad \text{sat}(e_1 \wedge e_2 \wedge e)}{e, A \vdash a_1 \bullet a_2}
\end{array}$$

Figure 4.7: VRA and variational condition typing relation. The rules assume that the underlying VDB is well-formed. Remember that our theory assumes all attributes have the same type and all constants belong to attributes' domain.

Figure 4.8: Derivation tree for q_1 in Example ??.**Assumption 1:**

$$\frac{\text{empbio}(\text{empno}, \text{sex}, \text{birthdate}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5}) \in S_2 \quad \text{sat}(e_2 \wedge e_2)}{e_2, S_2 \vdash \text{empbio} : (\text{empno}, \text{sex}, \text{birthdate}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5})^{e_2}} \text{RELATION-E}$$

Assumption 2:

$$\begin{aligned} & \{\text{empno}^{V_4 \vee V_5}, \text{name}, \text{firstname}, \text{lastname}\} \\ & \prec \downarrow \left(\{\text{empno}, \text{sex}, \text{birthdate}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5}\}^{e_2} \right) \end{aligned}$$

Assumption 3:

$$|\downarrow(\{\text{empno}^{V_4 \vee V_5}, \text{name}, \text{firstname}, \text{lastname}\}^{e_2})| = |\{\text{empno}^{V_4 \vee V_5}, \text{name}, \text{firstname}, \text{lastname}\}|$$

Final derivation tree:

$$\frac{\text{Assumption 1} \quad \text{Assumption 2} \quad \text{Assumption 3}}{e_2, S_2 \vdash q_1 : (\text{empno}^{(V_4 \vee V_5)}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5})^{e_2}} \text{PROJECT-E}$$

tions with the corresponding annotations in the query and wraps subqueries in a choice when needed. Note that, q_8 and q_6 are the result of $[q_7]_{S_2}$ and $[q_1]_{S_2}$, respectively, after simplification ⁴.

Theorem 4.4.1. If the query q has the type A then its explicitly annotated counterpart has the same type A , i.e.:

$$S \vdash q : A \Rightarrow S \vdash [q]_S : A' \text{ and } A \equiv A'$$

This shows that the type system applies the schema to the type of a query although it does not apply it to the query. The *type equivalence* is variational set equivalence, defined in Figure 2.4, for normalized variational sets of attributes.

We encode and prove Theorem 4.4.1 in the Coq proof assistant [?]. We

⁴More specifically, they are simplified using rules defined in Figure 4.11

Figure 4.9: Derivation tree for q_2 in Example ??.**Assumption 1:**

$$\text{empbio}(\text{empno}, \text{sex}, \text{birthdate}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5})^{e_2} \in S_2$$

Assumption 2:

$$\frac{\text{Assumption 1} \quad \text{sat}((e_2 \wedge (\neg V_3)) \wedge e_2)}{e_2 \wedge (\neg V_3), S_2 \vdash \text{empbio} : (\text{empno}, \text{sex}, \text{birthdate}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5})^{e_2 \wedge (\neg V_3)}} \text{RELATION-E}$$

Assumption 3:

$$|\downarrow(\{\text{empno}, \text{name}, \text{firstname}, \text{lastname}\}^{e_2 \wedge \neg V_3})| = |\{\text{empno}, \text{name}, \text{firstname}, \text{lastname}\}|$$

Assumption 4:

$$\begin{aligned} & \{\text{empno}, \text{name}, \text{firstname}, \text{lastname}\} \\ & \prec \{\text{empno}^{e_2 \wedge (\neg V_3)}, \text{sex}^{e_2 \wedge (\neg V_3)}, \text{birthdate}^{e_2 \wedge (\neg V_3)}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5}\} \end{aligned}$$

Assumption 5 (derivation tree for $\text{left} = \pi_{\text{empno}, \text{name}, \text{firstname}, \text{lastname}}(\text{empbio})$):

$$\frac{\text{Assumption 2} \quad \text{Assumption 3} \quad \text{Assumption 4}}{e_2 \wedge (\neg V_3), S_2 \vdash \text{left} : (\text{empno}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5})^{e_2 \wedge (\neg V_3)}} \text{PROJECT-E}$$

Final derivation tree for q_2 :

$$\frac{\text{Assumption 5} \quad \frac{}{e_2 \wedge \neg(\neg V_3), S_2 \vdash \varepsilon : \{\}^{\text{false}}} \text{EMPTYRELATION-E}}{e_2, S_2 \vdash q_2 : (\text{empno}, \text{name}^{V_4}, \text{firstname}^{V_5}, \text{lastname}^{V_5})^{(e_2 \wedge (\neg V_3)) \vee \text{false}}} \text{CHOICE-E}$$

$$\begin{aligned}
[\cdot]_S &: \mathbf{Q} \rightarrow \mathbf{Sch} \rightarrow \mathbf{Q} \\
[r]_S &= pc(r, S) \langle \pi_A r, \varepsilon \rangle \text{ where } S \vdash r : A \\
[\sigma_\theta q]_S &= \sigma_\theta [q]_S \\
[\pi_A q]_S &= \pi_{A \cap A'} [q]_S \text{ where } S \vdash [q]_S : A' \\
[q_1 \times q_2]_S &= [q_1]_S \times [q_2]_S \\
[e \langle q_1, q_2 \rangle]_S &= e \langle [q_1]_{\downarrow(S^e)}, [q_2]_{\downarrow(S^{-e})} \rangle \\
[q_1 \circ q_2]_S &= [q_1]_S \circ [q_2]_S \\
[\varepsilon]_S &= \varepsilon
\end{aligned}$$

Figure 4.10: Explicitly annotating a well-typed query with a variational schema.

also illustrate the application of Theorem 4.4.1 to queries q_1 and q_6 . Example ?? explained how q_1 's type is generated step-by-step. The variation context and underlying schema are the same and the subquery *empbio* has the same type. The projected attribute set annotated with the variation context is:

$$A_2 = \{empno^{(V_4 \vee V_5) \wedge \neg V_3}, name^{\neg V_3 \wedge V_4 \wedge \neg V_5}, firstname^{\neg V_3 \wedge \neg V_4 \wedge V_5}, lastname^{\neg V_3 \wedge \neg V_4 \wedge V_5}\}_{e_2},$$

which is clearly subsumed by A_{empbio} , thus, its intersection with A_{empbio} annotated with the presence condition of A_{empbio} is itself, hence, $A_{q_1} \equiv A_{q_6}$.

Explicitly annotating variational queries not only relieves the user from repeating the database's variation in their queries but it is also necessary for the functions that take a query without taking the schema such as the query configuration function. This is as opposed to other functions that have to take both the query and the schema such as the type system. Example 4.4.2 illustrates why a query passed to the configuration function must be explicitly annotated.

Example 4.4.2. Consider the variational query $q_5 = \pi_{a_1, a_2 f_1 \wedge f_2, a_3 f_2}(r)$ given in

added this paragraph. pls review it

Example 4.2.1. This query is not explicitly annotated since attribute a_1 does not carry its variational encoding from the database, that is, it does not have the presence condition f_1 . Explicitly annotating this query gives us query $q'_5 = \pi_{a_1 f_1, a_2 f_1 \wedge f_2, a_3 f_2}(r)$. Configuring q'_5 results in the same query as configuring q_5 except for configuration $\{ \}$, that is, $\mathbb{Q}[[q'_5]]_{\{ \}} = \pi_{\{ \}} \mathcal{L} = \varepsilon$. The reason why $\mathbb{Q}[[q_5]]_{\{ \}}$ is incorrect is that q_5 is missing the variation attached to attribute a_1 and the configuration function does not consider the schema of a database while configuring variational queries written over that database.

4.5 Variation-Minimization Rules

VRA is flexible since an information need can be represented via multiple v-queries as demonstrated in Example 4.1.1 and Example 4.1.2. It allows users to incorporate their personal taste and task requirements into v-queries they write by having different levels of variation. For example, consider the explicitly annotated query q_6 in Section 4.4:

$q_6 = \pi_{empno^{V_4} \vee V_5, name^{V_4}, firstname^{V_5}, lastname^{V_5}}(m_2 \langle empbio, \varepsilon \rangle)$. To be explicit about the exact query that will be run for each variant the query q_6 's variation can be *lifted up* by using choices, resulting in the query q''_6

$q''_6 = V_4 \langle \pi_{empno, name} empbio, V_5 \langle \pi_{empno, firstname, lastname} empbio, \varepsilon \rangle \rangle$. While q_6 contains less redundancy q''_6 is more comprehensible since the variants are explicitly stated in the dimension of the choice. Thus, *supporting multiple levels of variation creates a tension between reducing redundancy and maintaining comprehensibility*.

add q_6 is simplified of q'_6 because of rule application blah blah.

add example + more rules + point out interesting ones

Choice Distributive Rules:

$$\begin{aligned}
e\langle \pi_{A_1} q_1, \pi_{A_2} q_2 \rangle &\equiv \pi_{\downarrow(A_1^e), \downarrow(A_2^e)} e\langle q_1, q_2 \rangle \\
e\langle \sigma_{\theta_1} q_1, \sigma_{\theta_2} q_2 \rangle &\equiv \sigma_{e\langle \theta_1, \theta_2 \rangle} e\langle q_1, q_2 \rangle \\
e\langle q_1 \times q_2, q_3 \times q_4 \rangle &\equiv e\langle q_1, q_3 \rangle \times e\langle q_2, q_4 \rangle \\
e\langle q_1 \bowtie_{\theta_1} q_2, q_3 \bowtie_{\theta_2} q_4 \rangle &\equiv e\langle q_1, q_3 \rangle \bowtie_{e\langle \theta_1, \theta_2 \rangle} e\langle q_2, q_4 \rangle \\
e\langle q_1 \circ q_2, q_3 \circ q_4 \rangle &\equiv e\langle q_1, q_3 \rangle \circ e\langle q_2, q_4 \rangle
\end{aligned}$$

CC and RA Optimization Rules:

$$\begin{aligned}
e\langle \sigma_{\theta_1 \wedge \theta_2} q_1, \sigma_{\theta_1 \wedge \theta_3} q_2 \rangle &\equiv \sigma_{\theta_1 \wedge e\langle \theta_2, \theta_3 \rangle} e\langle q_1, q_2 \rangle \\
\sigma_{\theta_1} e\langle \sigma_{\theta_2} q_1, \sigma_{\theta_3} q_2 \rangle &\equiv \sigma_{\theta_1 \wedge e\langle \theta_2, \theta_3 \rangle} e\langle q_1, q_2 \rangle \\
e\langle q_1 \bowtie_{\theta_1 \wedge \theta_2} q_2, q_3 \bowtie_{\theta_1 \wedge \theta_3} q_4 \rangle &\equiv \sigma_{e\langle \theta_2, \theta_3 \rangle} (e\langle q_1, q_3 \rangle \bowtie_{\theta_1} e\langle q_2, q_4 \rangle)
\end{aligned}$$

Figure 4.11: Selected variation minimization rules.

We define *variation minimization* rules in Figure 4.11 that are syntactic and preserve the semantics. Pushing in variation into a query, i.e., applying rules left-to-right, reduces redundancy while lifting them up, i.e., applying rules right-to-left, makes a query more understandable. When applied left-to-right, the rules are terminating since the scope of variation monotonically decreases in size.

4.6 Variational Relational Algebra Properties

In this section, we discuss important properties of VRA. We first discuss its expressiveness with regards to the relational algebra in Section 4.6.1. Then, we discuss VRA's type safety in Section 4.6.2 by taking advantage of the relational algebra's type safety and defining a property that connect VRA's type system to

pls read
the follow-
ing para-
graph

relational algebra's type system, called *variation-preserving property*.

4.6.1 Expressiveness

VRA enables querying multiple database variants encoded as a singled VDB simultaneously and selectively. More precisely, VRA is *maximally expressive* in the sense that it can express any set of plain RA queries over any subset of relational database variants encoded as a VDB. We prove this claim in Theorem 4.6.1.

Theorem 4.6.1. Given a set of plain RA queries q_1, \dots, q_n where each query q_i is to be executed over a disjoint subset \mathcal{I}_i of variants of the VDB instance \mathcal{I} , there exists a variational query q such that $\forall c \in \mathbf{Config}. \mathbb{I}[\mathcal{I}]_c = \mathcal{I}_i \implies \mathbb{Q}[q]_c = q_i$.

Proof. By construction. Let f_i be the feature expression that uniquely characterizes the variants in each \mathcal{I}_i . Then

$$q = (f_1 \wedge \neg f_2 \wedge \dots \wedge \neg f_n) \langle q_1, (f_2 \wedge \dots \wedge \neg f_n) \langle q_2, \dots f_n \langle q_n, \varepsilon \rangle \dots \rangle \rangle.$$

□

The above construction relies on the fact that every RA query is a valid VRA (sub)query in which every presence condition is **true**. Of course, in most realistic scenarios, we expect that variational queries can be encoded more efficiently by sharing commonalities and embedding relevant choices and presence conditions within the variational query.

4.6.2 Type Safety

To show that VRA is type safe we benefit from RA's type safety [42] by defining the *variation-preserving* property for VRA which connects VRA to RA. The *variation-preserving property with respect to variational schema* states that if a query q has type A then configuring the type of a valid explicitly annotated query is the same as the type of its configured corresponding query. Theorem 4.6.2 proves this property.

Theorem 4.6.2 is visualized in the diagram below, where the vertical arrows indicate corresponding configure functions, $type$ indicates VRA's type system, that is, $type(q, S) = A^e$ is $S \vdash q : A^e$, and $\underline{type}(\underline{q}, \underline{S})$ indicates RA's type system for the relational query \underline{q} over the relational database schema \underline{S} , that is, $\underline{S} \vdash \underline{q} : \underline{A}$. We assume that corresponding variation

$$\begin{array}{ccc} [q]_S & \xrightarrow{type} & A^e \\ \mathbb{Q}[\cdot]_c \downarrow & & \downarrow \mathbb{A}[\cdot]_c \\ \underline{q} & \xrightarrow{\underline{type}} & \underline{A} \end{array}$$

schema and schema is passed to type systems. Simply put, the relational type of the configured variational query q with configuration c , that is, $\underline{type}(\mathbb{Q}[q]_c, \mathbb{S}[S]_c)$, must be the same as the configured variational type of the variational query q with configuration c , that is, $\mathbb{A}[\underline{type}(q, S)]_c$. *Clearly the diagram commutes*: taking either path of 1) configuring $[q]_S$ first and then obtaining the relational type of it or 2) obtaining the variational type of $[q]_S$ first and then configuring it results in the same set of attributes. The variation-preserving property enforces the maintenance of variants that a tuple belongs to through running a query at the schema level.⁵ Example 4.6.3 illustrates why the query must be constrained by

⁵We define this property as a test at the semantics level and show that all our experimental queries passed it.

the variation schema in the variation-preserving diagram.

Theorem 4.6.2. For all configurations c , if a query q has type A then its configured query $\mathbb{Q}[\lfloor q \rfloor_S]_c$ has type $\mathbb{A}[A]_c$, i.e.,

$$\forall c \in \mathbf{Config}. S \vdash q : A \Rightarrow \mathbb{S}[S]_c \vdash \mathbb{Q}[\lfloor q \rfloor_S]_c : \mathbb{A}[A]_c \quad .$$

Proof. By structural induction. We proved this theorem in the Coq proof assistant [?]. □

Theorem 4.6.2 implies that for all valid configurations of a VDB, any variational query is correlated to a relational query and since RA is type safe its queries are type safe. Thus, variational queries are type safe.

Example 4.6.3. Consider the variational query $q_5 = \pi_{a_1, a_2^{f_1 \wedge f_2}, a_3^{f_2}} r$ given in Example 4.2.1. It is well-typed and it has the type $A = \{a_1^{f_1}, a_2^{f_1 \wedge f_2}, a_3^{f_2}\}$. Configuring A for the variant that both f_1 and f_2 are disabled results in an empty attribute set. However, the type of its configured query for this variant, i.e., $\mathbb{Q}[q_5]_{\{\}} = \pi_{a_1} \underline{r}$, is the attribute set $\{a_1\}$. This violates the variation-preserving property. A similar problem happens for the variant of $\{f_2\}$, i.e., $\underline{type}(\mathbb{Q}[q_5]_{\{f_2\}}) = \underline{type}(\pi_{a_1, a_3} \underline{r}) = \{a_1, a_3\} \neq \{a_3\} = \mathbb{A}[A]_{\{f_2\}} = \mathbb{A}[\underline{type}(q_5)]_{\{f_2\}}$. However, the variation-preserving property holds for the constrained query by variation schema, i.e., $\lfloor q_5 \rfloor_{S_3} = \pi_{a_1^{f_1}, a_2^{f_1 \wedge f_2}, a_3^{f_2}} r$. Thus, the input query to the configuration function $\mathbb{Q}[\cdot]_c$ *must* be explicitly annotated by the underlying variation schema for the configured query to match the underlying configured schema.


Eric, pls
read this
paragraph.

4.6.3 Variation-Preserving Property at the Semantics Level

Since VDB contains multiple database variants it is important running a variational query over a VDB does not lose the variation encoded in a variational query and the VDB, that is, VRA's semantics must also be variation-preserving. This is visualized in the diagram below, where the vertical arrows indicate corresponding configuration functions, sem indicates VRA's denotational semantics and \underline{sem} indicates RA's denotational semantics.

Eric, pls read this section.

Note that sem runs a variational query on a VDB and \underline{sem} runs a relational query variant over its corresponding configured relational database variant. Simply put, the configured



variational table resulted from running the variational query

q over the VDB \mathcal{I} and variational schema S with the configuration c , that is, $\mathbb{T}[\underline{sem}(q, \mathcal{I})]_{(type(q, S), c)}$, must be the same as the relational table resulting from

running the configured relational query with configuration c over its corresponding relational database, that is, $\underline{sem}(\mathbb{Q}[q]_c, \mathbb{I}[\mathcal{I}]_c)$. Clearly the diagram commutes:

taking either path of 1) obtaining the semantics of the variational query $[q]_S$ first and then configuring it or 2) configuring $[q]_S$ first and then getting its semantics results in the same plain relational table. The variation-preserving property enforces the maintenance of variants that a tuple belongs to through running a query at the semantics level. This property inherently follows from the denotational semantics of VRA since we define VRA's denotational semantics in terms of RA's denotational semantics by attaching either configurations of variants or

feature expressions that denote multiple configurations of variants to the relational queries.

Chapter 5 Variational Database Use Cases

Thus far we introduced the variational database framework and variational queries. However, the question becomes: “How useable is the variational database framework?”, “How hard is it to generate a VDB and write variational queries?”, “Can a VDB be generated automatically? And if so, what is required to make this process automated?”. In this chapter, we aim at answering these questions. Thus, the goal of this chapter is twofold: first, how generating a VDB can be made automatic; second, to guid an expert through both generating a VDB from a variation scenario when it cannot be done automatically and writing variational queries that express expert’s information need over multiple database variants in the variation scenario.

A VDB can be generated automatically when the main variational information and database variants are available, that is, when the closed set of features, the feature model, and closed set of database variants are provided. Unfortunately, in practice, these information and encodings are not available since existing work only focuses on studying a specific kind of variation in databases and does not encode variation inside the database, instead, it addresses the problem with tools that simulate the effect of the specific kind of variation. Consequently, we describe how we systematically generated two variational databases from real world scenarios where variation appears in databases. We take a scenario where variation over

pls read
from here

to here.

either time or space exists in the database, use the schema variants to generate the variational schema, and attach feature expressions to tables and tuples to populate the VDB with data for each use case.

Additionally, variation in software affects not only databases but also how developers and database administrators interact with databases. Since different software variants have different information needs, developers must often write and maintain different queries for different software variants. Moreover, even if a particular information need is similar across variants, different variants of a query may need to be created and maintained to account for structural differences in the schema for each variant. Creating and maintaining different queries for each variant is tedious and error-prone, and potentially even intractable for large and open-ended configuration spaces, such as most open-source projects [49].

Thus, for each use case we present a set of variational queries and we illustrate how VRA realizes the information needs of the different variants of the database and potentially the corresponding software systems. It achieves this level of expressiveness by accounting for variation explicitly and linking variation in software and databases to queries by using the same feature names and configuration space. We present only a sample of the queries, yet we provide the full query sets online.¹ The full query sets capture all of the information needs described in the papers that we base our variation scenarios on. It is important to note that this makes our query sets potentially biased toward queries containing more variation points since

¹Complete sets of queries in both formats are available at: <https://zenodo.org/record/4321921>.

the focus of the papers is on variational parts of the system. A complete query set, capturing *all* information needs for each scenario might contain more plain queries, that is, queries that perform the same way over all variants. However, we do not believe this bias is harmful for the role the case studies are intended to serve, namely, motivating and evaluating variational database systems. For this role, queries that contain variation are more useful than plain queries, and additional plain queries can likely be more easily generated if needed.

We distribute the v-queries in two formats: (1) VRA, encoded in the format used by our VDBMS tool, and (2) plain SQL queries with embedded `#ifdef` annotations to capture variation points. The SQL format provides queries for studying variational data independently of VDBMS tool and will be more immediately useful for other researchers studying variational data independently of our VDBMS tool, but we use VRA in this thesis for its brevity because it is much more concise.

also, pls
read from
here

We first focus on variation in databases over space, Section 5.1. Section 5.1.1 describes the variation scenario from Hall [28] that is the basis of this use case including the feature set and feature model. Then, Section 5.1.2 and Section 5.1.3 describe generating the variational schema for the described variation scenario and populating the email SPL VDB with Enron email data,² respectively. Finally, Section 5.1.4 describes how variational queries capture the information need adapted from feature interactions described by Hall [28]. We then switch focus to variation in databases over time, Section 5.2. Again, Section 5.2.1 describes the evolution

²<http://www.ahschulz.de/enron-email-data/>

of an employee database as the variation scenario from Moon et al. [41] that is the basis of this use case. Then, Section 5.2.2 and Section 5.2.3 describe generating the variational schema for the described variation scenario and populating the employee VDB with a well-known employee data set,³ respectively. Finally, Section 5.2.4 describes the adapted and adjusted queries from Moon et al. [41]. At the end of this chapter, Section 5.3, we discuss the trade offs of using variational databases and we answer the question: “Should variation be encoded explicitly in databases?”.

to here.

We distribute the VDBs, SQL scripts for generating them, and queries of our use cases.⁴ We distribute the VDBs in both MySQL and Postgres in two forms, one intended for use with our VDBMS tool, and one intended for more general-purpose research on variation in databases. We distribute the variational queries as simple `#ifdef`-annotated SQL files to promote their broad reuse in the design and evaluation of other systems for managing variational relational data.

5.1 Variation in Space: Email SPL Use Case

In our first case study, we focus on variation that occurs in “space”, that is, where multiple software variants are developed and maintained in parallel. In software, variation in space corresponds to a SPL, where many distinct variants (products) can be produced from a single shared code base by enabling or disabling features. A variety of representations and tools have been developed for indicating which

³https://github.com/datacharmer/test_db

⁴Available at: <https://zenodo.org/record/4321921>

code belongs to which feature(s) and supporting the process of configuring a SPL to obtain a particular variant.

Naturally, different variants of a SPL have different information needs. For example, an optional feature in the SPL may require a corresponding attribute or relation in the database that is not needed by the other features in the SPL. Currently, there is no good solution to managing the varying information needs of different variants at the level of the database. One possible solution is to manually maintain a separate database schema for each variant of the SPL. This works for some SPLs where the number of products is relatively small and the developer has control over the configuration process. However, it does not scale to open-source SPLs or other scenarios where the number of products is large and/or configuration is out of the developer's hands. Another possible solution is to use and maintain a single universal schema that includes all of the relations and attributes used by any feature in the SPL. In this solution, every product will use the same database schema regardless of the features that are enabled. This solves the problem of scaling to large numbers of products but is dangerous because it means that potentially several attributes and relations will be unused in any given product. Unused attributes will typically be populated by `NULL` values, which are a well-known source of errors in relational databases [1].

VDBs solve the problem by allowing the structure of a relational database to vary in a synchronous way with the SPL. Attributes and relations may be annotated by presence conditions to indicate in which feature(s) those attributes and relations are needed. An implementation of the VDB model might use a

universal schema under-the-hood to realize VDBs on top of a standard relational database management system (indeed, this is exactly how our prototype VDBMS implementation works), but by capturing the variation in the schema explicitly, we can validate (potentially variational) queries against the relevant variants of the variational schema to statically ensure that no `NULL` values will be referenced.

The email SPL use case shows the use of VDB to encode the variational information needs of a database-backed SPL. We consider an email SPL that has been used in several previous SPL research projects (e.g. [6, 3]). It develops a variational schema that captures the information needs of a SPL based on Hall’s decomposition of an email system into its component features [28]. The email SPL has been used in several previous SPL research projects (e.g. [4, 3]). The variational email database is populated using the Enron email dataset, adapted to fit our variational schema [46]. Our use case is formed by systematically combining two pre-existing works:

1. We use Hall’s decomposition of an email system into its component features [28] as high-level specification of a SPL.
2. We use the Enron email dataset⁵ as a source of a realistic email database.

In combining these works, we show how variation in space in an email SPL requires corresponding variation in a supporting database, how we can link the variation in the software to variation in the database, and how all of these variants can be encoded in a single VDB.

⁵<http://www.ahschulz.de/enron-email-data/>

5.1.1 Variation Scenario: An Email SPL

The email SPL consists of the following features from Hall [28]:

- *addressbook*, users can maintain lists of known email addresses with corresponding aliases, which may be used in place of recipient addresses;
- *signature*, messages may be digitally signed and verified using cryptographic keys;
- *encryption*, messages may be encrypted before sending and decrypted upon receipt using cryptographic keys;
- *autoresponder*, users can enable automatically generated email responses to incoming messages;
- *forwardmessages*, users can forward all incoming messages automatically to another address;
- *remailmessage*, users may send messages anonymously;
- *filtermessages*, incoming messages can be filtered according to a provided white list of known sender address suffixes; and
- *mailhost*, a list of known users is maintained and known users may retrieve messages on demand while messages sent to unknown users are rejected.

Note that Hall's decomposition separates *signature* and *encryption* into two features each (corresponding to signing and verifying, encrypting and decrypting).

Table 5.1: Original Enron email dataset schema.

employeelist(*eid*, *firstname*, *lastname*, *email_id*, *email2*, *email3*, *email4*, *folder*, *status*)
messages(*mid*, *sender*, *date*, *message_id*, *subject*, *body*, *folder*)
recipientinfo(*rid*, *mid*, *rtype*, *rvalue*)
referenceinfo(*rid*, *mid*, *reference*)

Since these pairs of features must always be enabled together and they are so closely conceptually related, we reduce them to one feature each for simplicity.

The listed features are used in presence conditions within the variational schema for the email VDB, linking the software variation to variation in the database. In the email SPL, each feature is optional and independent, resulting in the simple feature model $e_{en} = \text{true}$, given as a feature expression. The feature model e_{en} is used as the root presence condition of the variational schema for the email VDB, implicitly applying it to all relations, attributes, and tuples in the database.

5.1.2 Generating Variational Schema of the Email SPL VDB

To produce a variational schema for the email VDB, we start from plain schema of the Enron email dataset shown in Table 5.1, then systematically adjust its schema to align with the information needs of the email SPL described by Hall [28]. The *employeelist* table contains information about the employees of the company including the employee identification number (*eid*), their first name and last name (*firstname* and *lastname*), their primary email address (*email_id*), alternative email addresses (e.g. *email2*), a path to the folder that contains their data (*folder*), and their last status in the company (*status*). The *messages* table contains

Table 5.2: Variational schema of the email VDB with feature model e_{en} . Presence conditions are colored blue for clarity.

```

employeeelist(eid, firstname, lastname, email_id, folder, status, verification_keysignature,
              public_keyencryption)
messages(mid, sender, date, message_id, subject, body, folder, is_system_notification,
         is_encryptedencryption, is_autoresponseautoresponder, is_signedsignature,
         is_forward_msgforwardmessages)
recipientinfo(rid, mid, rtype, rvalue)
forward_msg(eid, forwardaddr)forwardmessages
mailhost(eid, username, mailhost)mailhost
filter_msg(eid, suffix)filtermessages
reemail_msg(eid, pseudonym)reemailmessage
auto_msg(eid, subject, body)autoresponder
alias(eid, email, nickname)addressbook

```

information about the email messages including the message ID (*mid*), the sender of the message (*sender*), the date (*date*), the internal message ID (*message_id*), the subject and body of the message (*subject* and *body*), and the exact folder of the email (*folder*). The *recipientinfo* table contains information about the recipient of a message including the recipient ID (*rid*), the message ID (*mid*), the type of the message (*rtype*), and the email address of the recipient (*rvalue*). The *referenceinfo* table contains messages that have been referenced in other email messages, for example, in a forwarded message; it contains a reference-info ID (*rid*), the message ID (*mid*), and the entire message (*reference*). This table simply backs up the emails.

From this starting point, we introduce new attributes and relations that are needed to implement the features in the email SPL. We attach presence conditions to new attributes and relations corresponding to the features they are needed to

support, which ensure they will *not* be present in configurations that do not include the relevant features. The resulting variational schema is given in Table 5.2.

For example, consider the *signature* feature. In the software, implementing this feature requires new operations for signing an email before sending it out and for verifying the signature of a received email. These new operations suggest new information needs: we need a way to indicate that a message has been signed, and we need access to each user’s public key to verify those signatures (private keys used to sign a message would not be stored in the database). These needs are reflected in the variational schema by the new attributes *verification_key* and *is_signed*, added to the relations *employeeelist* and *messages*, respectively. The new attributes are annotated by the *signature* presence condition, indicating that they correspond to the *signature* feature and are unused in configurations that exclude this feature. Additionally, several features require adding entirely new relations. For example, when the *forward_msg* feature is enabled, the system must keep track of which users have forwarding enabled and the address to forward the messages to. This need is reflected by the new *forward_msg* relation, which is correspondingly annotated by the *forward_msg* presence condition.

A main focus of Hall’s decomposition [28] is on the many feature interactions. Several of the features may interact in undesirable ways if special precautions are not taken. For example, any combination of the *forward_msg*, *reply_msg*, and *autoresponder* features can trigger an infinite messaging loop if users configure the features in the wrong way; preventing this creates an information need to identify auto-generated emails, which is realized in the variational schema by attributes like

is_forward_msg and *is_autoresponse*. As another example consider the interaction that occurs between the *signature* and *remail_msg* features: the *remail_msg* feature enables anonymously sending messages by replacing the sender with a pseudonym, but this prevents the recipient from being able to verify a signed email. Furthermore, consider the interaction that occurs between the *signature* and *forward_msg* features: if Sarah signs a message and sends it to Ina, and Ina forwards the message to Philippe, then the signature verification operation may incorrectly interpret Ina as the sender rather than Sarah and fail to verify the message.

For each feature, we (1) enumerated the operations that must be supported both to implement the feature itself and to resolve undesirable feature interactions, (2) identified the information needs to implement these operations, and (3) extended the variational schema to satisfy these information needs. We make similar changes made to accommodate all features and their interactions.

For brevity, we omit some attributes and relations from the original schema that are irrelevant to the email SPL described by Hall [28], such as the *referenceinfo* relation and alternative email addresses.

We distribute the variational schema for the email VDB in two formats. First, we provide the schema in the encoding used by our prototype VDBMS tool. Second, we provide the variational schema in plain SQL. The SQL encoding is given by a “universal” schema containing the relations and attributes of all variants, plus a relation *vdb_pcs* (*element_id*, *pres_cond*) that captures all of the relevant presence conditions: that of the variational schema itself (i.e. the feature model), and

those of each relation and attribute.⁶ The *element_id* of the feature model is *variational_schema*; the *element_id* of a relation *r* is its name *r*, and of attribute *a* in relation *r* is *r.a*. The plain SQL encoding of the variational schema supports the use of the use cases for research on the effective management of variation in databases independent of VDBMS.

5.1.3 Populating the Email SPL VDB

The final step to create the email VDB is to populate the database with data from the Enron email dataset, adapted to fit our variational schema [46]. For evaluation purposes, we want the data from the dataset to be distributed across multiple variants of the VDB. To simulate this, we identified five plausible configurations of the email SPL, which we divide the data among. The five configurations of the email SPL we considered are:

- *basic email*, which includes only basic email functionality and does not include any of the optional features from the SPL.
- *enhanced email*, which extends *basic email* by enabling two of the most commonly used email features, *forwardmessages* and *filtermessages*.
- *privacy-focused email*, which extends *basic email* with features that focus on privacy, specifically, the *signature*, *encryption*, and *remailmessage* features.
- *business email*, which extends *basic email* with features tailored to an en-

⁶All encodings are available at: <https://zenodo.org/record/4321921>.

vironment where most emails are expected to be among users within the same business network, specifically, *addressbook*, *signature*, *encryption*, *autoresponder*, and *mailhost*.

- *premium email*, in which all of the optional features in the SPL are enabled.

For all variants, any features that are not enabled are disabled.

The original Enron dataset has 150 employees with 252,759 email messages. We load this data into the *employeelist* and *messages* tables defined in Section 5.1.2, initializing all attributes that are not present in the original dataset to `NULL`.

For the *employeelist* table, we construct five views corresponding to the five variants of the email system described above. We allocate 30 employees to each view based on their employee ID, that is, the first 30 employees sorted by employee ID are associated with the basic email variant, the next 30 with the enhanced email variant, and so on. The presence condition for each tuple is set to the conjunction of features enabled in that view. We then modify each of the views of the *employeelist* table by adding randomly generated values for attributes associated with the enabled features; e.g., in the view for the privacy-focused variant, we populate the *verification_key* and *public_key* attributes. Any attribute that is not present in the given tuple due to a conflicting presence condition will remain `NULL`. For example, both the *verification_key* and *public_key* attributes remain `NULL` for employees in the enhanced variant view since the presence condition does not include the corresponding features.

For the *messages* table, we again create five views corresponding to each of

the variants. Each tuple is added to the view of the variant that contains the message’s sender, which updates the tuple’s presence condition accordingly. The *messages* table also contains several additional attributes corresponding to optional features, which we populate in a systematic way. We set *is_signed* to **true** if the message sender has the *signature* feature enabled, and we set *is_encrypted* to **true** if *both* the message sender and recipient have *encryption* enabled. We populate the *is_forward_msg*, *is_autoresponse*, and *is_system_notification* attributes by doing a lightweight analysis of message subjects to determine whether the email is any of these special kinds of messages; for example, if the subject begins with “FWD”, we set the *is_forward_msg* attribute to **true**. If a forward or auto-reply message was sent by a user that does not have the corresponding feature enabled, we filter it out of the dataset. After filtering, the *messages* relation contains 99,727 messages. For each forward or auto-reply message, we also add a tuple with the relevant information to the new *forward_msg* and *auto_msg* tables. For employees belonging to database variants that enable *remailmessage*, *autoresponder*, *addressbook*, or *mailhost* we randomly generate tuples in the tables that are specific to each of these features. Finally, the *recipientinfo* relation is imported directly from the dataset. We set each tuple’s presence condition to a conjunction of the presence conditions of the sender and recipient.

We provide SQL scripts to automate the creation of views for each variant and to automate the population of these views with tuples from the original dataset, which also sets each tuple’s presence condition. The resulting database is distributed in two forms, one with the embedded variational schema as described in Sec-

tion 5.1.2, and one without the embedded schema for use with our VDBMS tool in which the variational schema is provided separately.⁷ We have tested the email SPL VDB for the properties described in Section 3.3 and all of them hold.

5.1.4 Email Query Set

To produce a set of queries for the email SPL use case, we collected all of the information needs that we could identify in the description of the email SPL by Hall [28]. In order to make the information needs more concrete, we viewed the requirements of the email SPL mostly through the lens of constructing an email header. An email header includes all of the relevant information needed to send an email and is used by email systems and clients to ensure that an email is sent to the right place and interpreted correctly. More specifically, the email header includes the sender and receiver of the email, whether an email is signed and the location of a signature verification key, whether an email is encrypted and the location of the corresponding public key, the subject and body of the email, the mail host it belongs to, whether the email should be filtered, and so on. Although there is obviously other infrastructure involved, the fundamental information needs of an email system can be understood by considering how to construct email headers that ensures the email would get where it needs to go and be interpreted correctly on the other end.

Hall’s decomposition focuses on enumerating the features of the email SPL and

⁷Both the scripts and different encodings of the email SPL VDB are available at: <https://zenodo.org/record/4321921>.

enumerating the potential interactions of those features. We deduce the information need for each feature by asking: “what information is needed to modify the email header in a way that incorporates the new functionality?”. We deduce the information need for each interaction by asking: “what information is needed to modify the email header in a way that avoids the undesirable feature interaction?”. We can then translate these information needs into queries on the underlying variational database.

In total, we provide 27 queries for the email SPL. This consists of 1 query for constructing the basic email header, 8 queries for realizing the information needs corresponding to each feature, and 18 queries for realizing the information needs to correctly handle the feature interactions described by Hall.

We start by presenting the query to assemble the basic email header, Q_{basic} . This corresponds to the information need of a system with no features enabled. We use X to stand for the specific message ID (mid) of the email whose header we want to construct.

$$Q_{basic} = \pi_{sender, rvalue, subject, body} mes_rec$$

$$mes_rec \leftarrow (\sigma_{mid=X} messages) \bowtie recipientinfo$$

This query extracts the sender, recipient, subject, and body of the email to populate the header. The projection is applied to an intermediate result mes_rec constructed by joining the $messages$ table with the $recipientinfo$ table on recipient IDs; we reuse this intermediate result also in subsequent queries.

Taking Q_{basic} as our starting point, we next construct our set of 8 *single-feature queries* that capture the information needs specific to each feature. When a feature is enabled in the SPL, more information is needed to construct the header of email X . For example, if the feature *filtermessages* is enabled, then the query Q_{filter} extends Q_{basic} with the *suffix* attribute used in filtering. This additional information allows the system to filter a message if its address contains any of the suffixes set by the receiver.

$$\begin{aligned}
 Q_{filter} &= \pi_{sender, rvalue, suffix, subject, body} temp \\
 temp &\leftarrow mes_rec_emp \bowtie filter_msg \\
 mes_rec_emp &\leftarrow mes_rec \bowtie_{rvalue=email_id} employeelist
 \end{aligned}$$

We can construct a query that retrieves the required header information whether *filtermessages* is enabled or not by combining Q_{basic} and Q_{filter} in a choice, as $Q_{bf} = filtermessages \langle Q_{filter}, Q_{basic} \rangle$. Although we do not show the process in this thesis, we can use equivalence laws from the choice calculus [21, 32] to factor commonalities out of choices and reduce redundancy in queries like Q_{bf} . The other single-feature queries are written similarly.

As another example of a single-feature query, $Q_{forward}$ captures the information needs for implementing the *forwardmessages* feature. It is similar to the previous queries except that it extracts the *forwardaddr* from the *auto_msg* table, which is needed to construct the message header for the new email to be forwarded when

email X is received by a user with a *forwardaddr* set.

$$Q_{forward} = \pi_{rvalue, forwardaddr, subject, body} temp$$

$$temp \leftarrow mes_rec_emp \bowtie_{employeeid.eid=forward_msg.eid} auto_msg$$

The other single-feature queries are similar to those shown here.

Besides single-feature queries, we also provide queries that gather information needed to identify and address the undesirable feature interactions described by Hall [28]. Out of Hall’s 27 feature interactions, we determined 16 of them to have corresponding information needs related to the database; 2 of the interactions require 2 separate queries to resolve. Therefore, we define and provide 18 queries addressing all 16 of the relevant feature interactions. As before, we deduced the information needs through the lens of constructing an email header; in these cases, the header would correspond to an email produced after successfully resolving the interaction. However, some interactions can only be detected but not automatically resolved. In these cases, we constructed a query that would retrieve the relevant information to detect and report the issue.

One undesirable feature interaction occurs between the two features *signature* and *forwardmessages*: if Philippe signs a message and sends it to Sarah, and Sarah forwards the message to an alternate address Sarah-2, then signature verification may incorrectly interpret Sarah as the sender rather than Philippe and fail to verify the message (Hall’s interaction #4). A solution to this interaction is to embed the original sender’s verification information into the email header of the forwarded

message so that it can be used to verify the message, rather than relying solely on the message's "from" field.

Below, we show a variational query Q_{sf} that includes four variants corresponding to whether *signature* and *forwardmessages* are enabled or not independently. The information need for resolving the interaction is satisfied by the first alternative of the outermost choice with condition $signature \wedge forwardmessages$. The alternatives of the choices nested to the right satisfy the information needs for when only *signature* is enabled, only *forwardmessages* is enabled, or neither is enabled (Q_{basic}). We don't show the single-feature Q_{sig} query, but it is similar to other single-feature queries shown above.

$$\begin{aligned}
Q_{sf} = & \textit{signature} \wedge \textit{forwardmessages} \\
& \langle \pi_{rvalue, forwardaddr, emp1.is_signed, emp1.verification_key} temp \\
& , \textit{signature} \langle Q_{sig}, \textit{forwardmessages} \langle Q_{forward}, Q_{basic} \rangle \rangle \rangle \\
temp \leftarrow & (((\sigma_{mid=X} \textit{messages}) \bowtie \textit{recipientinfo}) \\
& \bowtie_{sender=emp1.email_id} (\rho_{emp1} \textit{employeelist})) \\
& \bowtie_{rvalue=emp2.email_id} (\rho_{emp2} \textit{employeelist})) \bowtie \textit{forward_msg}
\end{aligned}$$

The query Q_{sf} also resolves another consequence of the interaction between these two features. This time Sam successfully verifies message X and forwards it to Sam2 which changes the header in the system such that it states message X has been successfully verified, thus, the message could be altered by hackers while it is being forwarded (Hall's interaction #27). The system can use Q_{sf} to generate

the correct header in this scenario again.

Some feature interactions require more than one query to satisfy their information need. For example, assume both *encryption* and *forwardmessages* are enabled. Philippe sends an encrypted email X to Sarah; upon receiving it the message is decrypted and forwarded it to Sarah-2 (Hall's interaction #9). This violates the intention of encrypting the message and the system should warn the user. Queries Q_{ef} and Q'_{ef} satisfy the information need for this interaction when a message is encrypted or unencrypted, respectively.

$$\begin{aligned}
Q_{ef} &= \text{encryption} \wedge \text{forwardmessages} \\
&\quad \langle \pi_{rvalue}(\sigma_{mid=X \wedge is_encrypted} \text{messages}) \\
&\quad , \text{encryption} \langle Q_{encrypt}, \text{forwardmessages} \langle Q_{forward}, Q_{basic} \rangle \rangle \rangle \\
Q'_{ef} &= \text{encryption} \wedge \text{forwardmessages} \\
&\quad \langle \text{temp}, \text{encryption} \langle Q_{encrypt}, \text{forwardmessages} \langle Q_{forward}, Q_{basic} \rangle \rangle \rangle \\
\text{temp} &\leftarrow \pi_{rvalue, forwardaddr, subject, body}(\sigma_{mid=X \wedge \neg is_encrypted} \\
&\quad (\text{mes_rec_emp} \bowtie_{employeeid=forward_msg.eid} \text{forward_msg}))
\end{aligned}$$

However, managing feature interactions is not necessarily complicated. Some interactions simply require projecting more attributes from the corresponding single-feature queries. For example, assume both *filtermessages* and *mailhost* features are enabled. Philippe sends a message to a non-existent user in a mailhost that he has filtered. The mailhost generates a non-delivery notification and sends it to

Philippe, but he never receives it since it is filtered out (Hall’s interaction #26). The system can check the *is_system_notification* attribute for the Q_{filter} query and decide whether to filter a message or not. Therefore, we can resolve this interaction by extending the single-feature query for *filtermessages* to Q'_{filter} .

$$Q'_{filter} = \pi_{sender, rvalue, suffix, is_system_notification, subject, body} temp$$

$$temp \leftarrow mes_rec_emp \bowtie_{employeeelist.eid=filter_msg.eid} filter_msg$$

Overall, for the 18 interaction queries we provide, 12 have 4 variants, 3 have 3 variants, 2 have 2 variants, and 1 has 1 variant.

5.2 Variation in Time: Employee Use Case

In our second case study, we focus on variation that occurs in “time”, that is, where the software variants are produced sequentially by incrementally extending and modifying the previous variant in order to accommodate new features or changing business requirements. Although new variants conceptually replace older variants, in practice, older variants must often be maintained in parallel; external dependencies, requirements, and other issues may prevent clients from updating to the latest version. Variation in software over time directly affects the databases such software depends on [49], and dealing with such changes is a well-studied problem in the database community known as *database evolution* [44].

Although research on database evolution has produced a variety of solutions for

managing database variation over time, these solutions do not treat variation as an orthogonal property and so cannot also accommodate variation in space. The goal of our work on variational databases is not to directly compete with database evolution solutions for time-only variation scenarios, but rather to present a more general model of database variation that can accommodate variation in both time and space, and that integrates with related software via feature annotations.

We demonstrate variation in time by using a VDB to encode an employee database evolution scenario systematically adapted from Moon et al. [41] and populated by a dataset that is widely used in databases research.⁸

5.2.1 Variation Scenario: An Evolving Employee Database

Moon et al. [41] describe an evolution scenario in which the schema of a company’s employee management system changes over time, yielding the five versions of the schema shown in Table 5.3. In V_1 , employees are split into two separate relations for engineer and non-engineer personnel. In V_2 , these two tables are merged into one relation, *empacct*. In V_3 , departments are factored out of the *empacct* relation and into a new *dept* relation to reduce redundancy in the database. In V_4 , the company decides to start collecting more personal information about their employees and stores all personal information in the new relation *empbio*. Finally, in V_5 , the company decides to decouple salaries from job titles and instead base salaries on individual employee’s qualifications and performance; this leads to dropping the

⁸https://github.com/datacharmer/test_db

Table 5.3: Evolution of an employee database schema from Moon et al. [41].

Version	Schema
V_1	<i>engineerpersonnel</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>) <i>otherpersonnel</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>) <i>job</i> (<i>title</i> , <i>salary</i>)
V_2	<i>empacct</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptname</i>) <i>job</i> (<i>title</i> , <i>salary</i>)
V_3	<i>empacct</i> (<i>empno</i> , <i>name</i> , <i>hiredate</i> , <i>title</i> , <i>deptno</i>) <i>job</i> (<i>title</i> , <i>salary</i>) <i>dept</i> (<i>deptname</i> , <i>deptno</i> , <i>managerno</i>)
V_4	<i>empacct</i> (<i>empno</i> , <i>hiredate</i> , <i>title</i> , <i>deptno</i>) <i>job</i> (<i>title</i> , <i>salary</i>) <i>dept</i> (<i>deptname</i> , <i>deptno</i> , <i>managerno</i>) <i>empbio</i> (<i>empno</i> , <i>sex</i> , <i>birthdate</i> , <i>name</i>)
V_5	<i>empacct</i> (<i>empno</i> , <i>hiredate</i> , <i>title</i> , <i>deptno</i> , <i>salary</i>) <i>dept</i> (<i>deptname</i> , <i>deptno</i> , <i>managerno</i>) <i>empbio</i> (<i>empno</i> , <i>sex</i> , <i>birthdate</i> , <i>firstname</i> , <i>lastname</i>)

job relation and adding a new *salary* attribute to the *empacct* relation. This version also separates the *name* attribute in *empbio* into *firstname* and *lastname* attributes.

We associate a feature with each version of the schema, named $V_1 \dots V_5$. These features are mutually exclusive since only one version of the schema is valid at a time. This yields the feature model e_{emp} . Also, note that the feature model represent a restriction on the entire database.

$$e_{emp} = \text{oneof} (V_1, V_2, V_3, V_4, V_5)$$

Table 5.4: Employee variational schema with feature model. e_{emp} .

$engineerpersonnel(empno, name, hiredate, title, deptname)^{V_1}$
$otherpersonnel(empno, name, hiredate, title, deptname)^{V_1}$
$empacct(empno, name^{V_2 \vee V_3}, hiredate, title,$ $deptname^{V_2}, deptno^{V_3 \vee V_4 \vee V_5}, salary^{V_5})^{V_2 \vee V_3 \vee V_4 \vee V_5}$
$job(title, salary)^{V_2 \vee V_3 \vee V_4}$
$dept(deptname, deptno, managerno)^{V_3 \vee V_4 \vee V_5}$
$empbio(empno, sex, birthdate, name^{V_4}, firstname^{V_5}, lastname^{V_5})^{V_4 \vee V_5}$

5.2.2 Generating Variational Schema of the Employee VDB

The variational schema for this scenario is given in Table 5.4. It encodes all five of the schema versions in Table 5.3 and was systematically generated by the following process. First, generate a universal schema from all of the plain schema versions; the universal schema contains every relation and attribute appearing in any of the five versions. Then, annotate the attributes and relations in the universal schema according to the versions they are present in. For example, the *empacct* relation is present in versions V_2 – V_5 , so it will be annotated by the feature expression $V_2 \vee V_3 \vee V_4 \vee V_5$, while the *salary* attribute within the *empacct* relation is present only in version V_5 , so it will be annotated by simply V_5 . The overall variational schema will be annotated by the feature model e_{emp} , described in Section 5.2.1. Since the presence conditions of attributes are implicitly conjuncted with the presence condition of their relation that contains them, we can avoid redundant annotations when an attribute is present in all instances of its parent

relation. For example, the *empbio* relation is present in $V_4 \vee V_5$, and the *birthdate* attribute is present in the same versions, so we do not need to redundantly annotate *birthdate*.

Similar to the email SPL VDB, we distribute the variational schema for the employee VDB in two formats: First, we provide the schema in the encoding used by our prototype VDBMS tool. Second, we provide a direct encoding in SQL that generates the universal schema for the VDB in either MySQL or Postgres. The variability of the schema is embedded within the employee VDB using the same encoding as described at the end of Section 5.1.2.⁹

5.2.3 Populating the Employee VDB

Finally, we populate the employee VDB using data from the widely used employee database linked to in this subsection’s lede. This database contains information for 240,124 employees. To simulate the evolution of the database over time, we divide the employees into five roughly equal groups based on their hire date within the company. For example, the first group consists of employees hired before 1988-01-01, while the second group contains employees hired from 1988-01-01 to 1991-01-01. Each group is assumed to have been hired during the lifetime of a particular version of the database, and is therefore added to that version of the database and *also* to all subsequent versions of the database. This simulates the fact that as a database evolves, older records are typically forward propagated

⁹All encodings of the employee variational schema are available at: <https://zenodo.org/record/4321921>.

to the new schema [44]. Thus, V_5 contains the records for all 240,124 employees, while older versions will contain progressively fewer records. The final employee VDB has 954,762 employee due to this forward propagation, despite having the same number of employees as the original database.

The schema of the employee database used to populate the employee VDB is different from all versions of the variational schema, yet it includes all required information. Thus, we manually mapped data from the original schema onto each version of the variational schema.

We provide SQL scripts of required queries to automatically generate the employee VDB. We also provide SQL scripts to automate the separation of each group of employees into views according to their hire date and populating those views from data in the employee database.¹⁰

As for any VDB, if an attribute is not present in any of the variants covered by a tuple’s presence condition, that attribute will be set to NULL in the tuple. We do this even though the relevant information may be contained in the original employee database to ensure that we have a consistent VDB. For example, while inserting tuples into the V_4 view of the *empbio* table, we always insert NULL values attributes *firstname* and *lastname*. We also provide the final employee VDB in four flavors: both with and without the embedded schema, and in both cases, encoded in MySQL and PostgreSQL format.¹¹ We have tested the employee VDB for the properties described in Section 3.3 and all of them hold.

¹⁰All the scripts are available at: <https://zenodo.org/record/4321921>.

¹¹Both formats are available at: <https://zenodo.org/record/4321921>.

5.2.4 Employee Query Set

For this use case, we have a set of existing plain queries to start from. Moon et al. [41] provides 12 queries to evaluate the Prima schema evolution system. We adapt these queries to fit our encoding of the employee VDB described in Section 5.2. We provide the queries in both the VRA format usable by VDBMS and as `#ifdef`-annotated SQL.¹² We give an example of query written as `#ifdef`-annotated at the end of this section. 9 of these queries have one variant, 2 have two variants, and 1 has three variants.

Moon’s queries are of two types: 6 retrieve data valid on a particular date (corresponding to V_3 in our encoding), while 6 retrieve data valid on or after that date (V_3 – V_5 in our encoding). For example, one query expresses the intent “return the salary of employee number 10004” at a time corresponding to V_3 , which we encode:

$$empQ_1 = \pi_{salary^{V_3}} (\sigma_{empno=10004} empacct) \bowtie_{empacct.title=job.title} job.$$

Note that the presence condition of the only attribute *salary* determines the presence condition of the resulting table.

In general and for simplicity, the shared part of presence conditions of projected attributes is factored out and applied to the entire table. Assume the returned table as a result of query has the schema $(a_1^{e \wedge e_1}, a_2^{e \wedge e_2})$. The shared restriction can be factored out and applied to the entire table, i.e., $(a_1^{e_1}, a_2^{e_2})^e$.

¹²All queries are available at: <https://zenodo.org/record/4321921>.

We encode the same intent, but for all times at or after V_3 as follows:

$$\begin{aligned} empQ_2 = V_3 \vee V_4 \vee V_5 \langle \\ \pi_{salary}(V_3 \vee V_4 \langle ((\sigma_{empno=10004} empacct)) \bowtie job, \sigma_{empno=10004} empacct \rangle) \\ , \varepsilon \rangle \end{aligned}$$

There are a variety of ways we could encode both $empQ_1$ and $empQ_2$. For $empQ_1$ we could equivalently have embedded the projection in a choice, $V_3 \langle \pi_{salary}(\dots), \varepsilon \rangle$, however attaching the presence condition to the only projected attribute determines the presence condition of the resulting table and so achieves the same effect. In $empQ_2$ we use choices to structure the query since we have to project on a different intermediate result for V_5 than for V_3 and V_4 .

The feature expression $V_3 \vee V_4 \vee V_5$ determines the database variants to be inquired. Since the schema of *empacct* and *job* tables are the same in variants V_3 and V_4 they both have the same query. Note that one could move the condition $V_3 \vee V_4 \vee V_5$ to the projected attribute which results in $empQ'_2$, however, this query is wrong because the last alternative of the choice projects attribute *salary* from an empty relation which is incorrect. It is important to understand that the behavior of an empty relation is exactly the same as its behavior in relational algebra and one should be careful of using it in operations such as projection, selection, and join.

$$\begin{aligned}
empQ'_2 &= \pi_{salary}^{V_3 \vee V_4 \vee V_5} \\
&\quad (V_3 \vee V_4 \langle (\sigma_{empno=10004} empacct) \bowtie_{empacct.title=job.title} job \\
&\quad \quad , V_5 \langle \sigma_{empno=10004} empacct, \varepsilon \rangle \rangle)
\end{aligned}$$

As another example, the following query realizes the intent to “return the name of the manager of department d001” during the time frame of V_3 – V_5 :

$$\begin{aligned}
empQ_3 &= V_3 \vee V_4 \vee V_5 \langle \\
&\quad \pi_{name,firstname,lastname}(V_3 \langle empacct, empbio \rangle \bowtie_{empno=managerno} \\
&\quad \quad (\sigma_{deptno="d001"} dept)) \\
&\quad , \varepsilon \rangle
\end{aligned}$$

Note that even though the attributes *name*, *firstname*, and *lastname* are not present in all three of the variants corresponding to V_3 – V_5 , the VRA encoding permits omitting presence conditions that can be completely determined by the presence conditions of the corresponding relations or attributes in the variational schema. So, $empQ_3$ is equivalent to the following query in which the presence conditions of the attributes from the variational schema are listed explicitly in the

projection:

$$\begin{aligned} empQ'_3 = & V_3 \vee V_4 \vee V_5 \langle \pi_{name^{V_3 \vee V_4}, firstname^{V_5}, lastname^{V_5}} \\ & (V_3 \langle empacct, empbio \rangle \bowtie_{empno=managerno} (\sigma_{deptno="d001"} dept)), \varepsilon \rangle \end{aligned}$$

Allowing developers to encode variation in variational queries based on their preference makes VRA more flexible and easy to use. Also, variational queries are statically type-checked to ensure that the variation encoded in them does not conflict the variation encoded in the v-schema.

Finally, we want to briefly illustrate what queries look like in the `#ifdef`-annotated SQL format that we distribute as a potentially more portable and easy-to-use format for other researchers. Below is the query $empQ_3$ in this format.

```
#ifdef V3 || V4 || v5
  #ifdef V3 || V4
SELECT name
  #else
SELECT firstname, lastname
  #endif
FROM
  #ifdef V3
    empacct
  #else
    empbio
  #endif
JOIN (SELECT * FROM dept WHERE deptno="d001")
ON empno=managerno
```

5.3 Discussion: Should Variation Be Encoded Explicitly in Databases?

In this section we discuss the use cases and our encodings of VDB and variational queries in the context of the question: *Should variation be encoded explicitly in databases?*

Expressiveness of explicit variation. The use cases in Chapter 5 show that by treating variation as an orthogonal concern and embedding it directly in databases and queries (via presence conditions and choices), one can encode data variation scenarios in both time and space. In fact, VDBs and variational queries are *maximally expressive* in the sense that any set of plain relational databases can be encoded as a single VDB and any set of plain queries over the variants of a VDB can be encoded as a variational query.¹³

The expressiveness of our approach is its main advantage over other ways to manage database variation. When working with a form of variation that already has its own specialized solution (e.g. schema evolution, data integration), the expressiveness of explicit variation is probably not worth the additional complexity. The expressiveness of explicit variation is most useful when working with a form of variation that is not well supported (e.g. query-level variation in SPLs), or when combining multiple forms of variation in one database (e.g. during SPL evolution).

We expect that ill-supported forms of variation are common in industry and

¹³The expressiveness of VDBs and variational queries can be proved by construction. For VDBs, one can simply take the union of all relations, attributes, and tuples across all variants, then attach presence conditions corresponding to which variants each is present in. For variational queries, all variants can be organized under a tree of choices that similarly organizes the variants in the appropriate way.

justify the expressiveness of explicit variation. For example, the following is a scenario we recently discussed with an industry contact: A software company develops software for different networking companies and analyzes data from its clients to advise them accordingly. The company records information from each of its clients' networks in databases customized to the particular hardware, operating systems, etc. that each client uses. The company analysts need to query information from all clients who agreed to share their information, but the same information need will be represented differently for each client. This problem is essentially a combination of the SPL variation problem (the company develops and maintains many databases that vary in structure and content) and the data integration problem (querying over many databases that vary in structure and content). However, neither the existing solutions from the SPL community nor database integration address both sides of the problem. Currently the company manually maintains variant schemas and queries, but this does not take advantage of sharing and is a major maintenance challenge. With a database encoding that supports explicit variation in schemas, content, and queries, the company could maintain a single variational database that can be configured for each client, import shared data into a VDB, and write variational queries over the VDB to analyze the data, significantly reducing redundancy across clients.

Complexity of explicit variation. The generality of explicit variation comes at the cost of increased complexity. The complexity introduced by presence conditions and choices is similar to the complexity introduced by variation annota-

tions in annotative approaches to SPL implementation [35]. There is widespread acknowledgment that unrestricted use of variation annotations, such as the C Pre-processor’s `#ifdef`-notation [27], makes software difficult to understand [37] and is error prone [26]. However, so-called *disciplined* use of variation annotations, where annotations are used in a way that is consistent with the object language syntax of variants, may suffer less from such issues [38]. In VDBs, and in the VRA notation for variational queries, annotations are disciplined since presence conditions and choices are integrated into the existing syntax of relational database schemas and relational algebra. Note that annotation discipline is not enforced in the `#ifdef`-annotated SQL notation that we use to distribute the variational queries associated with our use cases.

Subjectively, the development of our use cases suggests that the impact of variation annotations on understandability is moderate for variational schemas and VDBs, and significant for variational queries written in VRA, despite the fact that such annotations are disciplined. That is, we believe that presence conditions make clear the structural and content variation in our example VDBs without significantly impacting the understandability of the overall structure and content of the variant databases. However, the understandability of variational queries do seem to be significantly impacted by the use of presence conditions and choices, despite the fact that their use is disciplined in the VRA notation.

It is possible that a more restrictive and/or coarse-grained form of variation in variational queries would make them easier to understand at the cost of increased redundancy and (potentially) reduced expressiveness. This tradeoff is one

we already made when considering how to encode variation in the *content* of a VDB. Specifically, we do not support cell-level variation in a VDB (e.g. choices within individual cells). This does not reduce the expressiveness of content variation in VDBs since cell-level variation can be simulated by row variation, but it does increase redundancy since all non-varied cells in the row must be duplicated. Similarly, variation in queries could be restricted to expression-level choices, with no choices or annotations in conditions or attribute lists. This would likely make understanding individual query variants easier at the cost of increasing redundancy among the alternatives of each choice.

Alternatively, the understandability of variational queries could be improved through tooling, for example, using background colors [25], virtual separation of concerns [34], or view-based editing [55, 50]. Future work should validate our subjective assessment of the understandability VDBs and variational queries, and explore techniques for improving this concern.

Analyzability of explicit variation. The relationship of our work to alternative approaches can be viewed through the lens of annotative vs. compositional variation, familiar to the SPL community [35]. VDBs and variational queries rely on generic annotations embedded directly in schemas and queries, respectively, while approaches from the databases community often express variation through separate artifacts, such as views [11]. Annotative vs. compositional representations often exhibit the same tradeoff between expressiveness and complexity described above: annotative variation tends to be general and expressive, while compositional

variation tends to be more restrictive but support modular reasoning [35]. Traditionally, another advantage of compositional approaches is that they are more analyzable thanks to the ability to analyze components separately (i.e. *feature-based* analysis [53]), a benefit shared by database views. However, in the last decade there has been a significant amount of work in the SPL community to improve the analyzability of annotative variation by analyzing whole variational artifacts directly (i.e. *family-based* analysis [53]). Although not presented here, we build directly on this body of work, especially work on variational typing [16, 17], to enable efficiently checking variational queries against all variants of a VDB, among other properties. Thus, the increased complexity of explicit variation annotations does not prevent us from verifying its correctness.

Chapter 6 Variational Database Management System (VDBMS)

We implement a prototype using the VDB and VRA frameworks as *Variational Database Management System (VDBMS)*. VDBMS is implemented in Haskell. VDBMS sits on top of any DBMS that the user used to store their data in form of variational tables, explained in Section 3.2, with one exception: we encode variation at the content level by storing tuples presence condition as a presence condition attribute to all tables since relational databases cannot represent annotations. Note that the rest of the presence conditions are stored in the Haskell side of the system. To support running VDBMS with multiple different plain relational DBMS backends, we provide a shared interface for communicating with the backend DBMS and instantiate it for different database engines such as PostgreSQL and MySQL. An expert can extend VDBMS to another database engine by writing methods for connecting to and querying from the database.

6.1 VDBMS Architecture

Figure 6.1 shows the architecture of VDBMS. We assume a VDB and its variational schema are generated by an expert and are stored in a DBMS. A VDB can be *configured* to its plain relational database variants by providing the configuration of the desired variant, Figure 3.2. For example, a SPL developer configures a VDB




Figure 6.1: VDBMS architecture and execution flow of a variational query. The dotted double-line from the input variational query indicates the dependency of passing the variational query to this module only if it is valid. The dashed gray arrows with diamond heads demonstrate an option for the flow of the variational query. The blue filled arrows track the data flow, the green hollow arrows indicate an input to a module.

to produce software and its database for a client.

To extract information from a VDB, a user inputs a variational query q to VDBMS. First, q is checked by the *type system*. If the query is ill-typed, the user gets an error explaining what part of the query violated the variational schema. Otherwise, q is explicitly annotated by the schema and is passed to the *variation minimization* module, to simplify q . The simplified query is then sent to the *gener-*

ator module where SQL queries are generated from variational queries by different approaches explained in Section 6.2. [Example ?? in Appendix ?? demonstrates the flow of a variational query through VDBMS.]

All generated SQL queries are then executed on the underlying VDB. The result could be either a variational table or multiple variational tables, depending on the approach chosen by the SQL generator. The variational table(s) is passed to the *variational table builder* to create one variational table that filters out duplicate and invalid tuples, shrinks presence conditions, and eventually, returns the final variational table to the user. Note that the variational table builder module uses the accumulation functions introduced in Section 4.2.2 in addition to filtering out tuples and cleaning a variational table.

have examples for each approaches. of mainly the final sql

6.2 SQL Generator

[if parallel running of queries make a difference add it.] Since VDBMS sits on top of a plain relational DBMS, in order to run variational queries we must translate them into (sets of) plain relational queries, that is, *SQL generator* module's task, and then synthesize the result into a variational table, that is, *variational table builder* module's task. Given an explicitly annotated well-typed variational query q , we provide three initial approaches to generate SQL query(ies) for q :

1. *Naive Brute Force (NBF)*: Configures a variational query q for all valid configurations, that is, $\forall c \in \mathbf{Config}$, translates them to RA queries, and finally generates SQL queries with renaming all subqueries. The SQL queries are

sent to underlying DBMS and the results are gathered and cleaned up in variational table builder module. Here is the flow of how results are generated by this approach:

$$q \xrightarrow{\mathbb{Q}[q]_c} [(c, \underline{q})] \xrightarrow[\text{to SQL}]{\text{translate}} [(c, \underline{sql})] \xrightarrow[\text{queries}]{\text{run}} v\text{-tables} \xrightarrow[\text{builder}]{v\text{-table}} v\text{-table}$$

Example 6.2.1.

write the
damn thing

2. *Unique Brute Force (UBF)*: This approach is just like NBF except that we only generate SQL queries for unique RA queries which are the result of configuring the variational query. That is, it uses the unique variants function $\mathcal{Q}(q, F)$ introduced in Section 4.2.1. The implementation of this function is more efficient than its definition. That is:

$$q \xrightarrow{\mathcal{Q}(q, F)} [\underline{q}^e] \xrightarrow[\text{to SQL}]{\text{translate}} [\underline{sql}^e] \xrightarrow[\text{queries}]{\text{run}} v\text{-tables} \xrightarrow[\text{builder}]{v\text{-table}} v\text{-table}$$

Example 6.2.2.

write the
damn thing

3. *Union-All-Variants (UAV)*: This approach takes the SQL queries generated by UBF and unions them to just run one SQL query. In order to do so it forces all the SQL queries to return the same relation schema. Additionally, it applies the presence condition of a SQL query to its tuples by concatenating it with the presence condition attribute in the projected attribute set. The query is sent to the underlying DBMS and the result is cleaned up by the variational table builder. Finally, it is returned to the user as a variational

table. Note that cleaning up the result is part of variational table builder tasks. That is:

$$q \xrightarrow{\mathcal{Q}(q,F)} [\underline{q}^e] \xrightarrow[SQL]{generate} [\underline{sql}^e] \xrightarrow{union} \underline{sql}' \xrightarrow[query]{run} v\text{-table} \xrightarrow{clean\ up} v\text{-table}$$

Example 6.2.3.

write the
damn thing

We use the first two methods to simulate existing approaches used to manage variation currently. In particular, NBF simulates how a naive DBA would conduct such a task. UBF simulates how an expert DBA would conduct such a task. UAV attempts to reuse as much of the already existing results as possible. The generated SQL queries need to be independent from the underlying DBMS that stores the VDB. Hence, the SQL generator module has a submodule that prints generated SQL queries for each DBMS engine.

To ensure that these methods are implemented correctly we conducted two sanity checks:

1. We check that the variation-preserving property at the semantics level holds for all the methods. That is, we check that configuring the result gotten from a method is the same as running the configured query over the corresponding configured database.
2. We check that the results from each two methods are equivalent based on the equivalency relation over variational sets defined in Section 2.4 (specifically, in Section 2.4).

Our set of queries for both the email VDB and employee VDB passed these sanity checks.

6.3 Experiments

write the
damn
thing.

Chapter 7 Related Work

[related work! have to work on this!]

7.1 Instances of Variation in Databases

[schema evolution. database versioning. data integration. data provenance.]

7.2 Instances of Database Variation Resulted from Software Development

[SPL. data model. query.]

7.3 Variational Research

[blah]

from vamos

We proposed encoding variation explicitly in database schemas and queries in [8] and proposed applying this idea to database-backed SPLs in [9]. Our previous work uses slightly different encodings; the one presented here is the basis of our VDBMS implementation. This is the first work that provides use cases for VDBs.

The SPL community has a tradition of developing and distributing use cases to support research on software variation. For example, SPL2go [52] catalogs

the source code and variability models of a large number of SPLs. Additionally, specific projects, such as Apel et al.’s [6] work on SPL verification, often distribute use cases along with study results. However, there are no existing datasets or use cases that include corresponding relational databases and queries, despite their ubiquity in modern software.

Many researchers have recognized the need to manage structural variation in the databases that SPLs rely on. Abo Zaid and De Troyer [2] argue for modeling data variability as part of a model-oriented SPL process. Their *variable data models* link features to concepts in a data model so that specialized data models can be generated for different products. Khedri and Khosravi [36] address data model variability in the context of delta-oriented programming. They define delta modules that can incrementally generate a relational database schema, and so can be used to generate different schemas for each variant of a SPL. Humblet et al. [33] present a tool to manage variation in the schema of a relational database used by a SPL. Their tool enables linking features to elements of a schema, then generating different variants of the schema for different products. Schäler et al. [45] generate a variable database schema from a given global schema and software configurations by mapping schema element to features. Siegmund et al. [47] emphasize the need for variable database schema in SPLs and propose two decomposition approaches: (1) *physical* where database sub-schemas associated with a feature are stored in physical files and (2) *virtual* where a global entity-relation model of a schema is annotated with features. All of these approaches address the issue of *structural* database variation in SPLs and provide a way to derive a schema per variant,

which is also achievable by configuring a VDB. The work of Humblet et al. [33] is most similar to our notion of a variational schema since it is an annotative approach [35] that directly associates schema elements with features. Abo Zaid and De Troyer [2] is also annotative, but operates at the higher level of a data model that may only later be realized as a relational database. Khedri and Khosravi [36] is a compositional approach [35] to generating database schemas. None of these approaches consider *content-level* variation, which is captured by VDBs and observable in our use cases, nor do they consider how to express queries over databases with structural variation, which is addressed by our *v-queries*.

While the previous approaches all address data variation in space, Herrmann et al. [29] emphasize that as an SPL evolves over time, so does its database. Their approach adapts work on database evolution to SPLs, enabling the safe evolution of all deployed products.

Database researchers have studied several kinds of variation in both time and space. There is a substantial body of work on *schema evolution* and *database migration* [19, 41, 30, 43], which corresponds to variation in time. Typically the goal of such work is to safely migrate existing databases forward to new versions of the schema as it evolves. Work on *database versioning* [13, 31] extends this idea to a database’s content. In a versioned database, content changes can be sent between different instances of a database, similar to a distributed revision control system. All of this work is different from variational databases because it encodes a less general notion of variation and does not support querying multiple versions of the database at once. Work on *data integration* can be viewed as managing variation in

space [20]. In data integration, the goal is to combine data from disparate sources and provide a unified interface for querying. This is different from VDBs, which make differences between variants explicit.

The representation of v-schemas and variational tables is based on previous work on variational sets [23], which is part of a larger effort toward developing safe and efficient variational data structures [56, 40]. The central motivation of work on variational data structures is that many applications can benefit from maintaining and computing with variation at runtime [22, 18]. The ability to maintain and query several variants of a database at once extends the idea of computing with variation to relational databases.

Chapter 8 Conclusion

from vamos

We provide two use cases that illustrate how software variation leads to corresponding variation in relational databases. These use cases demonstrate the feasibility of VDBs and v-queries to capture the data needs of variational software systems. We argue that effectively managing such variation is an open problem, and we believe that these use cases will form a useful basis for evaluating research that addresses it, such as our own VDBMS framework.

VDBs encode variation explicitly in the structure and content of databases. This is a source of complexity that may impact understandability, as can be observed in our use cases. However, it also has several advantages: it is general in the sense that any set of variant databases and queries can be encoded as a VDB and v-queries, and it enables directly associating variation in databases to variation in software. By applying variational typing to variational queries, this generality does not come at the cost of safety. Future work can explore how tooling can mitigate the usability concerns using techniques that have been developed in the SPL community.

vldb

We argued that there is need to consider variation as an orthogonal concern to databases for two reasons: 1) Context-specific solutions do not provide their users with all variational information needs they may have, e.g., in Section ?? we analyzed the lack of variational need support for database-back SPL. As another

example, imagine a user wants to know the data provenance of some data they got from an integrated database (i.e., what data source does the data belong to). This is a variational need that data integration systems cannot satisfy. 2) New variational scenarios could appear, often from combination of other data variation instances such as our motivating example in Section 1.1.

We studied variational information needs, i.e., needs that appear in a variational context independent from the specific use case and we defined a generic framework that incorporates variation into all parts of a database and we showed how our framework satisfies all variational information needs throughout the paper. Finally, we illustrated VDBMS: the implementation of our framework and compared its performance against simulated approaches that could be used to extract information from a database in a variational scenario. The most important contribution of this paper is the expressiveness of our framework (VDB and VRA) and our system (VDBMS).

Now we discuss limitations of our work in terms of possible improvements as future work. It is important to note that we consider closed-world variation where all the database variants are known. Currently, we represent presence conditions as strings, which is inefficient because we need to manipulate every tuple's presence condition while running a query. In future work, we plan to implement presence conditions as a user-defined data type inside the underlying DBMS engine, which limits the engines that VDBMS can sit on top of them, as well as defining user-defined functions over them that allow VDBMS to manipulate them. Another future work is to generalize feature expression so that it can be tailored toward a

specific instance (e.g., schema evolution) of variation in databases by experts to make VDBMS more efficient for that instance. Additionally, designing an error-tolerant type system that pinpoints where the user made a mistake in their query and allows the part of query that is well-typed to be run is beneficial when a query has lots of encoded variation within it. Having such a type system also helps implementing a visual assistance for writing queries gradually and with holes. Thus, a user can start writing part of their query and leave some parts blank and see what tables and attributes they have at their disposal for each left-out part. Although we have not implemented a system to generate a VDB for a variational scenario it is trivial to do so if we have the variant databases. The problem is that in most cases the variant databases do not exist since current variational scenarios only simulate the effect of variation and do not incorporate it directly into the database or queries. Thus, an expert needs to manually generate the variant databases.

8.1 Future Work

8.2 Summary of Contributions

Bibliography

- [1] Serge Abiteboul, Richard Hull, and Victor Vianu. *Foundations of Databases: The Logical Level*. Addison-Wesley, 1994.
- [2] Lamia Abo Zaid and Olga De Troyer. Towards modeling data variability in software product lines. In Terry Halpin, Selmin Nurcan, John Krogstie, Pnina Soffer, Erik Proper, Rainer Schmidt, and Ilia Bider, editors, *Enterprise, Business-Process and Information Systems Modeling*, pages 453–467, Berlin, Heidelberg, 2011. Springer. ISBN 978-3-642-21759-3.
- [3] Mustafa Al-Hajjaji, Thomas Thüm, Malte Lochau, Jens Meinicke, and Gunter Saake. Effective Product-Line Testing Using Similarity-Based Product Prioritization. *Software & Systems Modeling*, 18(1):499–521, 2019.
- [4] S. Apel, A. von Rhein, P. Wendler, A. Größlinger, and D. Beyer. Strategies for Product-Line Verification: Case Studies and Experiments. In *IEEE Int. Conf. on Software Engineering*, pages 482–491, 2013.
- [5] Sven Apel, Don Batory, Christian Kästner, and Gunter Saake. *Feature-Oriented Software Product Lines: Concepts and Implementation*. Springer-Verlag, Berlin/Heidelberg, 2013. ISBN 978-3-642-37520-0.
- [6] Sven Apel, Alexander von Rhein, Philipp Wendler, Armin Größlinger, and Dirk Beyer. Strategies for product-line verification: case studies and experiments. In *2013 35th International Conference on Software Engineering (ICSE)*, pages 482–491. IEEE, 2013.
- [7] Gad Ariav. Temporally oriented data definitions: Managing schema evolution in temporally oriented databases. *Data & Knowledge Engineering*, 6(6):451 – 467, 1991. ISSN 0169-023X. doi: [https://doi.org/10.1016/0169-023X\(91\)90023-Q](https://doi.org/10.1016/0169-023X(91)90023-Q). URL <http://www.sciencedirect.com/science/article/pii/0169023X9190023Q>.
- [8] Parisa Ataei, Arash Termehchy, and Eric Walkingshaw. Variational Databases. In *Int. Symp. on Database Programming Languages (DBPL)*, pages 11:1–11:4. ACM, 2017.

- [9] Parisa Ataei, Arash Termehchy, and Eric Walkingshaw. Managing Structurally Heterogeneous Databases in Software Product Lines. In *VLDB Workshop: Polystores and Other Systems for Heterogeneous Data (Poly)*, 2018.
- [10] Parisa Ataei, Qiaoran Li, and Eric Walkingshaw. Should variation be encoded explicitly in databases? In *15th International Working Conference on Variability Modelling of Software-Intensive Systems*, VaMoS'21, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450388245. doi: 10.1145/3442391.3442395. URL <https://doi.org/10.1145/3442391.3442395>.
- [11] François Bancilhon and Nicolas Spyrtos. Update Semantics of Relational Views. *ACM Transactions on Database Systems (TODS)*, 6(4):557–575, 1981.
- [12] Anant P. Bhardwaj, Souvik Bhattacharjee, Amit Chavan, Amol Deshpande, Aaron J. Elmore, Samuel Madden, and Aditya G. Parameswaran. Datahub: Collaborative data science & dataset version management at scale. In *CIDR 2015, Seventh Biennial Conference on Innovative Data Systems Research, Asilomar, CA, USA, January 4-7, 2015, Online Proceedings*. [www.cidrdb.org](http://cidrdb.org), 2015. URL http://cidrdb.org/cidr2015/Papers/CIDR15_Paper18.pdf.
- [13] Souvik Bhattacharjee, Amit Chavan, Silu Huang, Amol Deshpande, and Aditya Parameswaran. Principles of dataset versioning: Exploring the recreation/storage tradeoff. *Proc. VLDB Endow.*, 8(12):1346–1357, August 2015. ISSN 2150-8097. doi: 10.14778/2824032.2824035. URL <http://dx.doi.org/10.14778/2824032.2824035>.
- [14] Cristina De Castro, Fabio Grandi, and Maria Rita Scalas. Schema versioning for multitemporal relational databases. *Information Systems*, 22(5):249 – 290, 1997. ISSN 0306-4379. doi: [https://doi.org/10.1016/S0306-4379\(97\)00017-3](https://doi.org/10.1016/S0306-4379(97)00017-3). URL <http://www.sciencedirect.com/science/article/pii/S0306437997000173>.
- [15] Badrish Chandramouli, Johannes Gehrke, Jonathan Goldstein, Donald Kossmann, Justin J. Levandoski, Renato Marroquin, and Wenlei Xie. READY: completeness is in the eye of the beholder. In *CIDR 2017, 8th Biennial Conference on Innovative Data Systems Research, Chaminade, CA, USA, January 8-11, 2017, Online Proceedings*. [www.cidrdb.org](http://cidrdb.org), 2017. URL <http://cidrdb.org/cidr2017/papers/p18-chandramouli-cidr17.pdf>.

- [16] Sheng Chen, Martin Erwig, and Eric Walkingshaw. An Error-Tolerant Type System for Variational Lambda Calculus. In *ACM SIGPLAN Int. Conf. on Functional Programming (ICFP)*, pages 29–40, 2012.
- [17] Sheng Chen, Martin Erwig, and Eric Walkingshaw. Extending Type Inference to Variational Programs. *ACM Trans. on Programming Languages and Systems (TOPLAS)*, 36(1):1:1–1:54, 2014.
- [18] Sheng Chen, Martin Erwig, and Eric Walkingshaw. A Calculus for Variational Programming. In *European Conf. on Object-Oriented Programming (ECOOP)*, volume 56 of *LIPIcs*, pages 6:1–6:26, 2016.
- [19] Carlo A. Curino, Hyun J. Moon, and Carlo Zaniolo. Graceful database schema evolution: The prism workbench. *Proc. VLDB Endow.*, 1(1):761–772, August 2008. ISSN 2150-8097. doi: 10.14778/1453856.1453939. URL <http://dx.doi.org/10.14778/1453856.1453939>.
- [20] AnHai Doan, Alon Halevy, and Zachary Ives. *Principles of Data Integration*. Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 1st edition, 2012. ISBN 0124160441, 9780124160446.
- [21] Martin Erwig and Eric Walkingshaw. The Choice Calculus: A Representation for Software Variation. *ACM Trans. on Software Engineering and Methodology (TOSEM)*, 21(1):6:1–6:27, 2011.
- [22] Martin Erwig and Eric Walkingshaw. Variation Programming with the Choice Calculus. In *Generative and Transformational Techniques in Software Engineering IV (GTTSE 2011), Revised and Extended Papers*, volume 7680 of *LNCS*, pages 55–99, 2013.
- [23] Martin Erwig, Eric Walkingshaw, and Sheng Chen. An Abstract Representation of Variational Graphs. In *Int. Work. on Feature-Oriented Software Development (FOSD)*, pages 25–32. ACM, 2013.
- [24] Mina Farid, Alexandra Roatis, Ihab F. Ilyas, Hella-Franziska Hoffmann, and Xu Chu. Clams: Bringing quality to data lakes. In *Proceedings of the 2016 International Conference on Management of Data, SIGMOD '16*, page 2089–2092, New York, NY, USA, 2016. Association for Computing Machinery. ISBN 9781450335317. doi: 10.1145/2882903.2899391. URL <https://doi.org/10.1145/2882903.2899391>.

- [25] Janet Feigenspan, Christian Kästner, Sven Apel, Jörg Liebig, Michael Schulze, Raimund Dachzelt, Maria Papendieck, Thomas Leich, and Gunter Saake. Do Background Colors Improve Program Comprehension in the `#ifdef` Hell? *Empirical Software Engineering*, 18(4):699–745, 2013.
- [26] Gabriel Ferreira, Momin Malik, Christian Kästner, Juergen Pfeffer, and Sven Apel. Do `#ifdefs` Influence the Occurrence of Vulnerabilities? An Empirical Study of the Linux Kernel. In *Int. Software Product Line Conf.*, 2016.
- [27] GNU Project. *The C Preprocessor*. Free Software Foundation, 2009. <http://gcc.gnu.org/onlinedocs/cpp/>.
- [28] Robert J. Hall. Fundamental Nonmodularity in Electronic Mail. *Automated Software Engineering*, 12(1):41–79, 2005.
- [29] Kai Herrmann, Jan Reimann, Hannes Voigt, Birgit Demuth, Stefan Fromm, Robert Stelzmann, and Wolfgang Lehner. Database evolution for software product lines. In *DATA*, 2015.
- [30] Jean-Marc Hick and Jean-Luc Hainaut. Database application evolution: A transformational approach. *Data & Knowledge Engineering*, 59(3):534 – 558, 2006. ISSN 0169-023X. doi: <https://doi.org/10.1016/j.datak.2005.10.003>. URL <http://www.sciencedirect.com/science/article/pii/S0169023X05001631>. Including: ER 2003.
- [31] Silu Huang, Liqi Xu, Jialin Liu, Aaron J. Elmore, and Aditya Parameswaran. Orpheusdb: Bolt-on versioning for relational databases. *Proc. VLDB Endow.*, 10(10):1130–1141, June 2017. ISSN 2150-8097. URL <http://dl.acm.org/citation.cfm?id=3115404.3115417>.
- [32] Spencer Hubbard and Eric Walkingshaw. Formula Choice Calculus. In *Int. Work. on Feature-Oriented Software Development (FOSD)*, pages 49–57. ACM, 2016.
- [33] Mathieu Humblet, Dang Vinh Tran, Jens H. Weber, and Anthony Cleve. Variability management in database applications. In *Proceedings of the 1st International Workshop on Variability and Complexity in Software Design, VACE '16*, pages 21–27, New York, NY, USA, 2016. ACM. ISBN 978-1-4503-4176-9. doi: 10.1145/2897045.2897050. URL <http://doi.acm.org/10.1145/2897045.2897050>.

- [34] Christian Kästner and Sven Apel. Virtual Separation of Concerns—A Second Chance for Preprocessors. *Journal of Object Technology*, 8(6):59–78, 2009.
- [35] Christian Kästner, Sven Apel, and Martin Kuhlemann. Granularity in Software Product Lines. In *IEEE Int. Conf. on Software Engineering*, pages 311–320, 2008.
- [36] Niloofar Khedri and Ramtin Khosravi. Handling database schema variability in software product lines. In *Asia-Pacific Software Engineering Conference (APSEC)*, pages 331–338, 2013. doi: 10.1109/APSEC.2013.52. URL <https://doi.org/10.1109/APSEC.2013.52>.
- [37] Duc Le, Eric Walkingshaw, and Martin Erwig. #ifdef Confirmed Harmful: Promoting Understandable Software Variation. In *IEEE Int. Symp. on Visual Languages and Human-Centric Computing (VL/HCC)*, pages 143–150, 2011.
- [38] Jörg Liebig, Christian Kästner, and Sven Apel. Analyzing the discipline of preprocessor annotations in 30 million lines of c code. In *Int. Conf. on Aspect-Oriented Software Development*, pages 191–202, 3 2011.
- [39] Edwin McKenzie and Richard Thomas Snodgrass. Schema evolution and the relational algebra. *Inf. Syst.*, 15(2):207–232, May 1990. ISSN 0306-4379. doi: 10.1016/0306-4379(90)90036-O. URL [http://dx.doi.org/10.1016/0306-4379\(90\)90036-O](http://dx.doi.org/10.1016/0306-4379(90)90036-O).
- [40] Meng Meng, Jens Meinicke, Chu-Pan Wong, Eric Walkingshaw, and Christian Kästner. A Choice of Variational Stacks: Exploring Variational Data Structures. In *Int. Work. on Variability Modelling of Software-Intensive Systems (VaMoS)*, pages 28–35. ACM, 2017.
- [41] Hyun J. Moon, Carlo A. Curino, Alin Deutsch, Chien-Yi Hou, and Carlo Zaniolo. Managing and querying transaction-time databases under schema evolution. *Proc. VLDB Endow.*, 1(1):882–895, August 2008. ISSN 2150-8097. doi: 10.14778/1453856.1453952. URL <http://dx.doi.org/10.14778/1453856.1453952>.
- [42] Atsushi Ohori and Peter Buneman. Type inference in a database programming language. In *Proceedings of the 1988 ACM Conference on LISP and Functional Programming*, LFP ’88, page 174–183, New York, NY, USA, 1988. Association for Computing Machinery. ISBN 089791273X. doi: 10.1145/62678.62700. URL <https://doi.org/10.1145/62678.62700>.

- [43] Sudha Ram and Ganesan Shankaranarayanan. Research issues in database schema evolution: the road not taken. 2003.
- [44] John F Roddick. A survey of schema versioning issues for database systems. *Information and Software Technology*, 37(7):383 – 393, 1995. ISSN 0950-5849. doi: [https://doi.org/10.1016/0950-5849\(95\)91494-K](https://doi.org/10.1016/0950-5849(95)91494-K). URL <http://www.sciencedirect.com/science/article/pii/095058499591494K>.
- [45] Martin Schäler, Thomas Leich, Marko Rosenmüller, and Gunter Saake. Building information system variants with tailored database schemas using features. In Jolita Ralyté, Xavier Franch, Sjaak Brinkkemper, and Stanislaw Wrycza, editors, *Advanced Information Systems Engineering*, pages 597–612, Berlin, Heidelberg, 2012. Springer. ISBN 978-3-642-31095-9.
- [46] Jitesh Shetty and Jafar Adibi. The Enron Email Dataset: Database Schema and Brief Statistical Report. Technical report, Information Sciences Institute, University of Southern California, 2004.
- [47] Norbert Siegmund, Christian Kästner, Marko Rosenmüller, Florian Heidenreich, Sven Apel, and Gunter Saake. Bridging the Gap Between Variability in Client Application and Database Schema. In *13. GI-Fachtagung Datenbanksysteme für Business, Technologie und Web (BTW)*, pages 297–306. Gesellschaft für Informatik (GI), 2009.
- [48] Richard Thomas Snodgrass. *The TSQL2 Temporal Query Language*. Kluwer Academic Publishers, USA, 1995. ISBN 0792396146.
- [49] Micheal Stonebraker, Dong Deng, and Micheal L. Brodie. Database decay and how to avoid it. In *Big Data (Big Data), 2016 IEEE International Conference*. IEEE, 2016. doi: 10.1109/BigData.2016.7840584.
- [50] Ștefan Stănciulescu, Thorsten Berger, Eric Walkingshaw, and Andrzej Wasowski. Concepts, Operations, and Feasibility of a Projection-Based Variation Control System. In *IEEE Int. Conf. on Software Maintenance and Evolution (ICSME)*, pages 323–333, 2016.
- [51] U. Störl, D. Müller, A. Tekleab, S. Tolale, J. Stenzel, M. Klettke, and S. Scherzinger. Curating variational data in application development. In *2018 IEEE 34th International Conference on Data Engineering (ICDE)*, pages 1605–1608, 2018. doi: 10.1109/ICDE.2018.00187.

- [52] Thomas Thüm and Fabian Benduhn. SPL2go: An Online Repository for Open-Source Software Product Lines, 2011. <http://spl2go.cs.ovgu.de>.
- [53] Thomas Thüm, Sven Apel, Christian Kästner, Ina Schaefer, and Gunter Saake. A Classification and Survey of Analysis Strategies for Software Product Lines. *ACM Computing Surveys (CSUR)*, 47(1):6, 2014.
- [54] Eric Walkingshaw. *The Choice Calculus: A Formal Language of Variation*. PhD thesis, Oregon State University, 2013. <http://hdl.handle.net/1957/40652>.
- [55] Eric Walkingshaw and Klaus Ostermann. Projectional Editing of Variational Software. In *ACM SIGPLAN Int. Conf. on Generative Programming: Concepts and Experiences (GPCE)*, pages 29–38, 2014.
- [56] Eric Walkingshaw, Christian Kästner, Martin Erwig, Sven Apel, and Eric Bodden. Variational Data Structures: Exploring Trade-Offs in Computing with Variability. In *ACM SIGPLAN Symp. on New Ideas in Programming and Reflections on Software (Onward!)*, pages 213–226, 2014.

