CA-C30L: Mobile Application Development Lab

LAB PROGRAM-5 : Custom Designed Opening Screen

5.Create an application that displays custom designed Opening Screen.

Program description :

- The program displays a splash screen followed by the Welcome screen of the app

Steps :

Step 1 : Copy two background images in **res/drawable folder**

Step 2: Create a new activity Splash_screen.java (by right clicking on java->New->activity)

Step 3: Modify AndroidManifest.xml as follows (Swap the activity names and insert a **theme** attribute for SplashScreen to

```
Theme.AppCompat.DayNight.NoActionBar )
```

AndroidManifest.xml

```
<?xml version="1.0" encoding="utf-8"?>
<manifest
xmlns:android="http://schemas.android.com/apk/res/
android"
xmlns:tools="http://schemas.android.com/tools">
<application
        android:allowBackup="true"

android:dataExtractionRules="@xml/data_extraction_
rules"
android:fullBackupContent="@xml/backup_rules"
        android:icon="@mipmap/ic_launcher"
        android:label="@string/app_name"

android:roundIcon="@mipmap/ic_launcher_round"
        android:supportsRtl="true"
        android:theme="@style/Theme.SplashScreen"
        tools:targetApi="31">
```

```
<activity
            android:name=".MainActivity"
            android:exported="false" />
<activity
android:name=".SplashScreen"

android:theme="@style/Theme.AppCompat.DayNight.NoA
ctionBar"
android:exported="true">
<intent-filter>
        <action
android:name="android.intent.action.MAIN" />

        <category
android:name="android.intent.category.LAUNCHER" />
</intent-filter>
</activity>
</application>
```

Step 4 : Modify the code of Splash_screen.java file as follows

Splash_screen.java

```
package com.example.splashscreen;
import androidx.appcompat.app.AppCompatActivity;
import android.content.Intent;
import android.os.Bundle;
import android.os.Handler;

public class SplashScreen extends AppCompatActivity
{
    @Override

    protected void onCreate(Bundle
savedInstanceState) {
        super.onCreate(savedInstanceState);

setContentView(R.layout.activity_splash_screen);
        new  Handler().postDelayed(new Runnable() {
```

```
            public void run() {
                Intent intent = new
Intent(SplashScreen.this, MainActivity.class);
                startActivity(intent);
                finish();
            }
        },6000);

    }
}
```

Step 5 : Change the corresponding activity of splash_screen.xml as follows (Change to Relativelayout and insert background image inserted in drawable)

activity_splash_screen.xml

```
<?xml version="1.0" encoding="utf-8"?>
<RelativeLayout
xmlns:android="http://schemas.android.com/apk/res/
android"
    xmlns:app="http://schemas.android.com/apk/res-
auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    tools:context=".SplashScreen"
    android:background="@drawable/bg2">
</RelativeLayout>
```

Step 6 : MainActivity.java remains as it is

MainActivity.java

```
package com.example.splashscreen;
import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
```

```
public class MainActivity extends AppCompatActivity
{

    @Override
protected void onCreate(Bundle savedInstanceState)
{
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }
}
```

Step 7 : Modify activity_main.xml as follows (change to relative layout and insert a background image and a text view for Welcome message)

```
<?xml version="1.0" encoding="utf-8"?>
<RelativeLayout
xmlns:android="http://schemas.android.com/apk/res/
android"
xmlns:app="http://schemas.android.com/apk/res-
auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    tools:context=".MainActivity"
    android:background="@drawable/bg4">

 <TextView
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="@string/displaytext"
        android:textStyle="bold"
        android:textSize="50sp"/>
</RelativeLayout>
```

****

handler.postDelayed(runnable, delayInMillis);

interface

Is a class

method

new Handler(): This creates a new Handler instance, which allows you to schedule code execution after a certain delay.

postDelayed(Runnable r, long delayMillis): This method schedules the provided Runnable to execute after the specified delay (in milliseconds).