

Events Organizer on Social Networks



Julien Odent
Mar 28, 2013

Events Organizer: Overview

- Website
- New objective function
- Minimum capacity
- Aspiration criterion
- Ch 3 feedback

Website

- Events are public by default
- Owners can set their events private and invite participants

Objective function

Including event owners' preferences within objective function:

- Median age
$$\max_s \left\{ - \sum_j^m \left| \frac{\sum_i^n s_{ij} age_i}{\sum_i^n s_{ij}} - mage_j \right| \right\}$$
- Sex ratio
$$\max_s \left\{ - \sum_j^m \left| \frac{\sum_i^n s_{ij} male_i}{\sum_i^n s_{ij}} - sratio_j \right| \right\}$$

Compound objective function is now a weighted sum over all subobjectives, with $\sum_i w_i = 1$

We still have to set the weights

Minimum capacity

- Vector cmin of size m (one for each event)
- Constraint $\forall_j \sum_i^n s_{ij} < cmin_j \Rightarrow s_{ij} = 0$
- Problem: if incumbent has not included enough (i.e. at least cmin) participants to a given event, it will be definitely canceled; otherwise, the same problem will arise anyway whenever we fall below the cmin boundary.
- Other approach: relax constraints while below the cmin limit
- Whenever cmin is reached, we have to make s consistent
 - Keep the event and remove participations to conflicting events
 - Potentially cancel the event by going back under cmin
- This is a subproblem requiring a new definition of the neighborhood! (LNS)

Aspiration criterion

The $L(N, t)$ function filtering out illegal moves performs better when the aspiration criterion is applied, for the same computing time scale.