

# Lean Spring Boot


Applications for The Cloud

Patrick Baumgartner

42talents GmbH, Zürich, Switzerland

@patbaumgartner

patrick.baumgartner@42talents.com



TALENTS

# Abstract

## Lean Spring Boot Applications for The Cloud

With the starters, Spring-Boot offers a functionality that allows you to set up a new software project with little effort and start programming right away. You don't have to worry about the dependencies since the "right" ones are already pre-configured. But how can you, for example, optimize the start-up times and reduce the memory footprint and thus better prepare the application for the cloud?

In this talk, we will go into Spring-Boot features like "spring-context-indexer", classpath exclusions, lazy spring beans, actuator, JMX. In addition, we also look at switching to a different JVM and other tools.


Let's make Spring Boot great again!

# Lean Spring Boot

## Applications for The Cloud

Patrick Baumgartner  
42talents GmbH, Zürich, Switzerland

@patbaumgartner  
patrick.baumgartner@42talents.com



# **WARNING:**

**Numbers** shown in this talk are **not**  
based on **real data** but **only**  
**estimates** and **assumptions**  
made by the **author** for  
**educational purposes** only.

# Introduction



## Patrick Baumgartner

Technical Agile Coach @ 42talents

My focus is on the development of software solutions with humans.

Coaching, Architecture, Development, Reviews, and Training.

Lecturer @ Zürcher Fachhochschule für Angewandte Wissenschaften ZHAW

[@patbaumgartner](#)

**What is the problem?**

**Why this talk?**

**JAVA 🤔 & Spring Boot ❤️**







# Requirements

## When Choosing a Cloud

- How many vCPUs per server are required for my application?
- How much RAM do I need?
- How much storage is necessary?
- Which technology stack should I use?



# Considerations

## Resources

- CPU & RAM not linearly scalable
- Image Size & Network Bandwidth

## Scaleability

- Fast Startup
- Graceful Shutdown
- Throughput
- Latency



# Agenda


# Agenda


---

- Spring PetClinic & Baseline for Comparison
- Java Optimizations
- Spring Boot Optimizations
- Application Optimizations
- Other Runtimes
- Conclusions
- A Few Simple Optimizations Applied (OpenJDK Example)









# Spring Petclinic Community

---

- spring-framework-petclinic
- spring-petclinic-angular(js)
- spring-petclinic-rest
- spring-petclinic-graphql
- spring-petclinic-microservices
- spring-petclinic-data-jdbc
- spring-petclinic-cloud
- spring-petclinic-mustache
- spring-petclinic-kotlin
- spring-petclinic-reactive
- spring-petclinic-hilla
- spring-petclinic-angularjs
- spring-petclinic-vaadin-flow
- spring-petclinic-reactjs
- spring-petclinic-htmx
- spring-petclinic-istio
- ...

# NO!

The official **Spring PetClinic!** 🐾 🏥

Which is based on **Spring Boot**, Caffeine,  
Thymeleaf, **Spring Data JPA**, H2 and  
**Spring MVC** ...

# Optimizing Experiments



# Baseline


---

## Technology Stack

- OCI Container (Buildpacks)
- Java JDK 17 LTS
- Spring Boot 3.1.4
- DB Migration with SQL Scripts

## Examination

- Build Time
- Startup Time
- Resource Usage
- Container Image Size
- Throughput



**Buildpacks.io**



paketo  
buildpacks

**Your app,  
in your favorite language,  
ready to run in the cloud**



**GraalVM.**



**NGINX**

**node**



**python™**

```

Setting Active Processor Count to 4
Calculating JVM memory based on 16965780K available memory
For more information on this calculation, see https://paketo.io/docs/reference/java-reference/#memory-calculator
Calculated JVM Memory Configuration: -XX:MaxDirectMemorySize=10M -Xmx16335617K -XX:MaxMetaspaceSize=118162K -XX:ReservedCodeCacheSize=240M -Xss1M (Total Memory: 16965780K, Thread Count: 250, Loaded Class Count: 18448, Headroom: 0%)
Enabling Java Native Memory Tracking
Adding 137 container CA certificates to JVM truststore
Spring Cloud Bindings Enabled
Picked up JAVA_TOOL_OPTIONS: -Djava.security.properties=/layers/paketo-buildpacks_bellsoft-liberica/java-security-properties/java-security.properties -XX:+ExitOnOutOfMemoryError
-XX:ActiveProcessorCount=4 -XX:MaxDirectMemorySize=10M -Xmx16335617K -XX:MaxMetaspaceSize=118162K -XX:ReservedCodeCacheSize=240M -Xss1M
-XX:+UnlockDiagnosticVMOptions -XX:NativeMemoryTracking=summary -XX:+PrintNMTStatistics -Dorg.springframework.cloud.bindings.boot.enable=true

```



```
:: Built with Spring Boot :: 3.1.4
```

```

2023-08-23T17:17:37.209Z INFO 1 --- [main] o.s.s.petclinic.PetClinicApplication : Starting PetClinicApplication v3.1.4-SNAPSHOT using Java 17.0.8 with PID 1 (/workspace/BOOT-INF/classes started by cnb in /workspace)
2023-08-23T17:17:37.212Z INFO 1 --- [main] o.s.s.petclinic.PetClinicApplication : No active profile set, falling back to 1 default profile: "default"
2023-08-23T17:17:37.927Z INFO 1 --- [main] .s.d.r.c.RepositoryConfigurationDelegate : Bootstrapping Spring Data JPA repositories in DEFAULT mode.
2023-08-23T17:17:37.968Z INFO 1 --- [main] .s.d.r.c.RepositoryConfigurationDelegate : Finished Spring Data repository scanning in 36 ms. Found 2 JPA repository interfaces.
2023-08-23T17:17:38.379Z INFO 1 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port(s): 8080 (http)
2023-08-23T17:17:38.386Z INFO 1 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2023-08-23T17:17:38.386Z INFO 1 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.10]
2023-08-23T17:17:38.445Z INFO 1 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2023-08-23T17:17:38.447Z INFO 1 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 1202 ms
2023-08-23T17:17:38.613Z INFO 1 --- [main] com.zaxxer.hikari.HikariDataSource : HikariPool-1 - Starting...
2023-08-23T17:17:38.768Z INFO 1 --- [main] com.zaxxer.hikari.pool.HikariPool : HikariPool-1 - Added connection conn0: url=jdbc:h2:mem:62f6cba7-d5f4-4c9b-8d3b-f66ce0f168e1 user=SA
2023-08-23T17:17:38.770Z INFO 1 --- [main] com.zaxxer.hikari.HikariDataSource : HikariPool-1 - Start completed.
2023-08-23T17:17:38.899Z INFO 1 --- [main] o.hibernate.jpa.internal.util.LogHelper : HHH000204: Processing PersistenceUnitInfo [name: default]
2023-08-23T17:17:38.931Z INFO 1 --- [main] org.hibernate.Version : HHH000412: Hibernate ORM core version 6.2.5.Final
2023-08-23T17:17:38.933Z INFO 1 --- [main] org.hibernate.cfg.Environment : HHH000406: Using bytecode reflection optimizer
2023-08-23T17:17:39.017Z INFO 1 --- [main] o.h.b.i.BytecodeProviderInitiator : HHH000021: Bytecode provider name : bytebuddy
2023-08-23T17:17:39.107Z INFO 1 --- [main] o.s.o.j.p.SpringPersistenceUnitInfo : No LoadTimeWeaver setup: ignoring JPA class transformer
2023-08-23T17:17:39.330Z INFO 1 --- [main] o.h.b.i.BytecodeProviderInitiator : HHH000021: Bytecode provider name : bytebuddy
2023-08-23T17:17:39.915Z INFO 1 --- [main] o.h.e.t.j.p.i.JtaPlatformInitiator : HHH000490: Using JtaPlatform implementation: [org.hibernate.engine.transaction.jta.platform.internal.NoJtaPlatform]
2023-08-23T17:17:39.917Z INFO 1 --- [main] j.LocalContainerEntityManagerFactoryBean : Initialized JPA EntityManagerFactory for persistence unit 'default'
2023-08-23T17:17:40.090Z INFO 1 --- [main] o.s.d.j.r.query.QueryEnhancerFactory : Hibernate is in classpath; If applicable, HQL parser will be used.
2023-08-23T17:17:40.881Z INFO 1 --- [main] o.s.b.a.e.web.EndpointLinksResolver : Exposing 13 endpoint(s) beneath base path '/actuator'
2023-08-23T17:17:40.953Z INFO 1 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port(s): 8080 (http) with context path ''
2023-08-23T17:17:40.967Z INFO 1 --- [main] o.s.s.petclinic.PetClinicApplication : Started PetClinicApplication in 4.069 seconds (process running for 4.351)

```



**1000x Better** than your regular  
**Dockerfile**  ...

... more **Secure**  and maintained by the  
**Buildpacks community.**

See also: <https://buildpacks.io/> and <https://www.cncf.io/projects/buildpacks/>

# Startup Reporting

# Spring Boot Startup Report


By Maciej Walkowiak

---

- Startup report available in runtime as an interactive HTML page
- Generating startup reports in integration tests
- Flame chart for timings
- Search by class or an annotation

```
<dependency>  
  <groupId>com.maciejwalkowiak.spring</groupId>  
  <artifactId>spring-boot-startup-report</artifactId>  
  <version>0.2.0</version>  
  <optional>true</optional>  
</dependency>
```

Spring Boot Startup Analyzer				
made by @maciejwalkowiak				
Minimum duration <input type="text" value="0"/> Search <input type="text"/>				
	Name	Duration with children (ms)	Duration (ms)	Details
🔍	spring.context.refresh	3716	133	
⊕	spring.beans.instantiate	973	884	<b>class:</b> org.springframework.orm.jpa.LocalContainerEntityManagerFactoryBean <b>beanName:</b> entityManagerFactory
⊕	spring.context.beans.post-process	843	25	
⊕	spring.beans.instantiate	538	7	<b>class:</b> org.springframework.samples.petclinic.owner.OwnerController <b>annotations:</b> @Controller <b>beanName:</b> ownerController
⊕	spring.boot.webserver.create	448	172	<b>factory:</b> class org.springframework.boot.web.embedded.tomcat.TomcatServletWebServerFactory
⊕	spring.beans.instantiate	146	46	<b>class:</b> org.springframework.web.servlet.mvc.method.annotation.RequestMappingHandlerAdapter <b>beanName:</b> requestMappingHandlerAdapter





# Benchmarks

# Benchmarks

---

- Build
  - Maven build time
  - Artifact / Container Image size
- Startup
  - Startup time
  - Memory usage
- Throughput & Latency
  - `wrk2 -t4 -c200 -d60s -R2000 --latency`
  - 1 min warmup, 1min measurement
  - Docker container with 4 vCPU and 1 GB RAM




# No Optimizing - Baseline JDK 17

---

- Spring PetClinic (no adjustments)
- Bellsoft Liberica JDK 17.0.8
- Java Memory Calculator

```
sdk use java 17.0.8-librca  
mvn spring-boot:build-image  
docker run -p 8080:8080 -t spring-petclinic:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms

# No Optimizing - Baseline JDK 21


---

- Spring PetClinic (JDK 21 adjustments)
- Bellsoft Liberica JDK 21.0.0
- Java Memory Calculator

```
sdk use java 21-librca
```

```
mvn -Djava.version=21 spring-boot:build-image \  
    -Dspring-boot.build-image.imageName=spring-petclinic:3.1.4-SNAPSHOT-jdk20
```

```
docker run -p 8080:8080 -t spring-petclinic:3.1.4-SNAPSHOT-jdk20
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
62s	368MB	3.915s	277MB	1992/s	463MB	30ms	56ms	91ms



# -XX:TieredStopAtLevel=1


---

The tiered compilation is enabled by default since Java 8. Unless explicitly specified, the JVM decides which JIT compiler to use based on our CPU. For multi-core processors or 64-bit VMs, the JVM will select C2.

To disable C2 and only use the C1 compiler with no profiling overhead, we can apply the `-XX:TieredStopAtLevel=1` parameter.

```
docker run -p 8080:8080 -e "JAVA_TOOL_OPTIONS=-XX:TieredStopAtLevel=1" \
-t spring-petclinic:3.1.4-SNAPSHOT
```

*It will slow down the JIT later at the expense of the saved startup time!*

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
-	-	3.375s	203MB	1441/s	321MB	18340ms	19990ms	21353ms






# Lazy Spring Beans (1)

---

Configure lazy initialization across the whole application. A Spring Boot property makes all Beans lazy by default and only initializes them when they are needed. `@Lazy` can be used to override this behavior with e.g. `@Lazy(false)`.

```
docker run -p 8080:8080 \
  -e spring.main.lazy-initialization=true \
  -e spring.data.jpa.repositories.bootstrap-mode=lazy \
  -t spring-petclinic:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
-	-	2.182s	235MB	1996/s	441MB	35ms	75ms	130ms

# Lazy Spring Beans (2)

---

## Pros

- Faster startup useful in cloud environments
- Application startup is a CPU-intensive task. Spreading the load over time

## Cons

- The initial requests may take more time
- Class loading issues and misconfigurations unnoticed at startup
- Beans creation errors only be found at the time of loading the bean



# No Spring Boot Actuators

---

Don't use actuators if you can afford not to. 😊

- No. of Spring Beans
  - Spring Pet Clinic with Actuators: 415
  - Spring Pet Clinic no Actuators: 270 🔥

```
sdk use java 17.0.8-librca
```

```
mvn spring-boot:build-image
```

```
docker run -p 8080:8080 -t spring-petclinic-no-actuator:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
🕒 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
52.8s	313MB	3.445s	260MB	1996/s	431MB	36ms	62ms	94ms




# Fixing Spring Boot Config Location

Fix the location of the Spring Boot config file(s).  
Considered in the following order (`application.properties` and YAML variants):

- Application properties packaged inside your jar
- Profile-specific application properties packaged inside your jar
- Application properties outside of your packaged jar
- Profile-specific application properties outside of your packaged jar

```
docker run -p 8080:8080 -e spring.config.location=classpath:application.properties \
-t spring-petclinic:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
-	-	3.931s	292MB	1994/s	454MB	28ms	54ms	103ms



# Disabling JMX

---

JMX is `spring.jmx.enabled=false` by default in Spring Boot since 2.2.0 and later. Setting `BPL_JMX_ENABLED=true` and `BPL_JMX_PORT=9999` on the container will add the following arguments to the `java` command.

```
-Djava.rmi.server.hostname=127.0.0.1  
-Dcom.sun.management.jmxremote.authenticate=false  
-Dcom.sun.management.jmxremote.ssl=false  
-Dcom.sun.management.jmxremote.port=9999  
-Dcom.sun.management.jmxremote.rmi.port=9999
```

```
docker run -p 8080:8080 -p 9999:9999 \  
  -e BPL_JMX_ENABLED=false \  
  -e BPL_JMX_PORT=9999 \  
  -e spring.jmx.enabled=false \  
  -t spring-petclinic:3.1.4-SNAPSHOT
```





# **Spring Boot & Buildpacks**



# Dependency Cleanup (2)

---

DepClean detects and removes all the unused dependencies declared in the `pom.xml` file of a project or imported from its parent. It does not touch the original `pom.xml` file.

```
<plugin>
  <groupId>se.kth.castor</groupId>
  <artifactId>depclean-maven-plugin</artifactId>
  <version>2.0.6</version>
  <executions>
    <execution>
      <goals>
        <goal>depclean</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

```
mvn se.kth.castor:depclean-maven-plugin:2.0.6:depclean -DfailIfUnusedDirect=true -DignoreScopes=provided,test,runtime,system,import
```

```

[INFO] Starting DepClean dependency analysis
-----
D E P C L E A N   A N A L Y S I S   R E S U L T S
-----
USED DIRECT DEPENDENCIES [5]:
    jakarta.xml.bind:jakarta.xml.bind-api:4.0.0:compile (124 KB)
    org.springframework.boot:spring-boot-testcontainers:3.1.4:test (85 KB)
    javax.cache:cache-api:1.1.1:compile (50 KB)
    ...
USED TRANSITIVE DEPENDENCIES [22]:
    org.springframework:spring-core:6.0.10:compile (1 MB)
    org.springframework.boot:spring-boot-autoconfigure:3.1.4:compile (1 MB)
    org.springframework:spring-web:6.0.10:compile (1 MB)
    org.springframework.boot:spring-boot:3.1.4:compile (1 MB)
    org.springframework.data:spring-data-commons:3.1.4:compile (1 MB)
    org.assertj:assertj-core:3.24.2:test (1 MB)
    org.springframework:spring-context:6.0.10:compile (1 MB)
    org.springframework.data:spring-data-jpa:3.1.4:compile (1 MB)
    ...
USED INHERITED DIRECT DEPENDENCIES [0]:
USED INHERITED TRANSITIVE DEPENDENCIES [0]:
POTENTIALLY UNUSED DIRECT DEPENDENCIES [15]:
    com.h2database:h2:2.1.214:runtime (2 MB)
    com.mysql:mysql-connector-j:8.0.33:runtime (2 MB)
    org.webjars.npm:bootstrap:5.2.3:compile (1 MB)
    org.postgresql:postgresql:42.6.0:runtime (1 MB)
    com.github.ben-manes.caffeine:caffeine:3.1.6:compile (734 KB)
    org.webjars.npm:font-awesome:4.7.0:compile (665 KB)
    ...
POTENTIALLY UNUSED TRANSITIVE DEPENDENCIES [87]:
    org.testcontainers:testcontainers:1.18.3:test (11 MB)
    org.hibernate.orm:hibernate-core:6.2.5.Final:compile (10 MB)
    net.bytebuddy:byte-buddy:1.14.5:runtime (3 MB)
    org.apache.tomcat.embed:tomcat-embed-core:10.1.10:compile (3 MB)
    org.aspectj:aspectjweaver:1.9.19:compile (1 MB)
    com.github.docker-java:docker-java-transport-zero-dep:3.3.0:test (1 MB)
    net.java.dev.jna:jna:5.12.1:test (1 MB)
    com.fasterxml.jackson.core:jackson-databind:2.15.2:compile (1 MB)
    org.hibernate.validator:hibernate-validator:8.0.0.Final:compile (1 MB)
    org.apache.commons:commons-compress:1.23.0:test (1 MB)
    org.thymeleaf:thymeleaf:3.1.4.RELEASE:compile (915 KB)
    ...
POTENTIALLY UNUSED INHERITED DIRECT DEPENDENCIES [0]:
POTENTIALLY UNUSED INHERITED TRANSITIVE DEPENDENCIES [0]:
[INFO] Analysis done in 0min 8s


```

# Dependency Cleanup (2)

But there are some challenges:

- Spring uses reflection to load classes
- Spring Boot uses `META-INF/spring-boot/org.springframework.boot.autoconfigure.AutoConfiguration` to load classes
- Spring Context Indexer uses `META-INF/spring.components`
- Component & Entity Scanning through Classpath Scanning

```
sdk use java 17.0.8-librca
mvn spring-boot:build-image
docker run -p 8080:8080 -t spring-petclinic-depclean:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
65s	307MB	3.299s	244MB	1997/s	415MB	31ms	65ms	104ms



# Ahead-of-Time Processing (AOT) (1)

---

Spring AOT is a process that analyzes your application at build-time and generates an optimized version of it.

As the BeanFactory is fully prepared at build-time, conditions are also evaluated.


```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <executions>
    <execution>
      <id>process-aot</id>
      <goals>
        <goal>process-aot</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

# Ahead-of-Time Processing (AOT) (2)

---

We are creating a new container image with the AOT-processed application.

```
sdk use java 17.0.8-librca  
mvn spring-boot:build-image  
docker run -e spring.aot.enabled=true -p 8080:8080 -t spring-petclinic-aot:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
59.6s	317MB	3.916s	283MB	1996/s	447MB	33ms	57ms	82ms





# JLink (1)

---

Jlink assembles and optimizes a set of modules and their dependencies into a custom runtime image for your application.


```
$ jlink \  
  --add-modules java.base, ... \  
  --strip-debug \  
  --no-man-pages \  
  --no-header-files \  
  --compress=2 \  
  --output /javaruntime
```

```
$ /javaruntime/bin/java HelloWorld  
Hello, World!
```

## JLink (2)

---

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <env>
        <BP_JVM_JLINK_ENABLED>true</BP_JVM_JLINK_ENABLED>
      </env>
    </image>
  </configuration>
</plugin>
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
sdk use java 17.0.8-	68s	3.944s	281MB	1994/s	451MB	31ms	73ms	116ms


```
mvn spring-boot:build-image
```

```
docker run -p 8080:8080 -t spring-petclinic-jlink:3.1.4-SNAPSHOT
```

# JLink (3)

---

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <env>
        <BP_JVM_JLINK_ENABLED>true</BP_JVM_JLINK_ENABLED>
        <BP_JVM_JLINK_ARGS>--add-modules jdk.management.agent,java.base,java.logging,
java.xml,jdk.unsupported,java.sql,java.naming,java.desktop,java.management,
java.security.jgss,java.instrument --compress=2 --no-header-files --no-man-pages
--strip-debug</BP_JVM_JLINK_ARGS>
      </env>
    </image>
  </configuration>
</plugin>
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
65s	236MB	3.99s	301MB	1996/s	454MB	35ms	78ms	121ms



# **Spring Boot & Buildpacks**





## Unleash the power of Java

Optimized to run Java™ applications cost-effectively in the cloud, Eclipse OpenJ9™ is a fast and efficient JVM that delivers power and performance when you need it most.



**Optimized for the Cloud**  
for microservices and monoliths  
too!



**42% Faster Startup**  
over HotSpot




**28% Faster Ramp-up**  
when deployed to cloud vs HotSpot



**66% Smaller**  
when compared to HotSpot

# Eclipse OpenJ9

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <buildpacks>
        <buildpack>gcr.io/paketo-buildpacks/eclipse-openj9:latest</buildpack>
        <!-- Used to inherit all the other buildpacks -->
        <buildpack>gcr.io/paketo-buildpacks/java:latest</buildpack>
      </buildpacks>
    </image>
  </configuration>
</plugin>
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
73s	306MB	6.852s	163MB	1989/s	349MB	46ms	91ms	165ms

```
sdk use java 17.0.8
```

```
mvn spring-boot:build-image
```

```
docker run -p 8080:8080 -t spring-petclinic-custom-jvm-openj9:3.1.4-SNAPSHOT
```






# Eclipse OpenJ9 Optimized Quickstart

---

-Xquickstart causes the JIT compiler to run with a subset of optimizations, which can improve the performance of short-running applications.

Use the -Xshareclasses option to enable, disable, or modify class-sharing behavior. Class data sharing is enabled by default for bootstrap classes only, *unless your application is running in a container.*


```
docker run -p 8080:8080 -e "JAVA_TOOL_OPTIONS=-Xshareclasses -Xquickstart" \
-t spring-petclinic-custom-jvm:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
-	-	5.138s	161MB	1258/s	294MB	23510ms	25330ms	26530ms

# Eclipse OpenJ9 Optimized Virtualized

When `-Xtune:virtualized` is used in conjunction with the `-Xshareclasses` option, the JIT compiler is more aggressive with its use of AOT-compiled code compared to setting only `-Xshareclasses`. This action provides additional CPU savings during application start-up and ramp-up, but comes at the expense of an additional small loss in throughput.


```
docker run -p 8080:8080 -e "JAVA_TOOL_OPTIONS=-XX:+IgnoreUnrecognizedVMOptions -XX:+UseContainerSupport -XX:+IdleTuningCompactOnIdle -XX:+IdleTuningGcOnIdle -Xscmx50M -Xshareclasses -Xtune:virtualized" \
-t spring-petclinic-custom-jvm:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
-	-	8.632s	190MB	1989/s	342MB	71ms	142ms	235ms



# GraalVM

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <buildpacks>
        <buildpack>gcr.io/paketo-buildpacks/graalvm:latest</buildpack>
        <!-- Used to inherit all the other buildpacks -->
        <buildpack>gcr.io/paketo-buildpacks/java:latest</buildpack>
      </buildpacks>
    </image>
  </configuration>
</plugin>
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
77.5s	735MB	3.809s	239MB	1996/s	422MB	36ms	62ms	98ms

```
sdk use java 17.0.8-
```

```
mvn spring-boot:build-image
```


```
docker run -p 8080:8080 -t spring-petclinic-custom-jvm-graalvm:3.1.4-SNAPSHOT
```

# Other Buildpack Builders

# Bellsoft Buildpack Builder

Bellsoft provides an optimized builder for Spring Boot applications. It uses the Bellsoft Alpaquita, Liberica JDK and the musl C library. A glibc version is also available.

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <builder>bellsoft/buildpacks.builder:musl</builder>
    </image>
  </configuration>
</plugin>
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
57.3s	174MB	4.304s	249MB	1993/s	396MB	30ms	49ms	79ms

```
sdk use java 17.0.8-librca

mvn spring-boot:build-image

docker run -p 8080:8080 -t spring-petclinic-bellsoft-buildpack:3.1.4-SNAPSHOT
```






# GraalVM Native Image

---

A native image is a technology to build Java code to a standalone executable. This executable includes the application classes, classes from its dependencies, runtime library classes, and statically linked native code from JDK. The JVM is packaged into the native image, so there's no need for any Java Runtime Environment at the target system, but the build artifact is platform-dependent.

```
mvn -Pnative spring-boot:build-image
```

```
docker run -p 8080:8080 -t spring-petclinic-native:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
337s	219MB	0.277s	234MB	1994/s	466MB	114ms	207ms	307ms



# CRaC - OpenJDK (1)

---

CRaC (Checkpoint and Restart in Java) is a feature that allows to checkpoint the state of a Java application and restart it from the checkpointed state.

*The application starts within milliseconds!*

# CRaC - OpenJDK (2)

---

```
export JAVA_HOME=/opt/openjdk-17-crac+5_linux-x64/  
export PATH=$JAVA_HOME/bin:$PATH
```

```
mvn clean verify
```

```
java -XX:CRaCCheckpointTo=crac-files -jar target/spring-petclinic-crac-3.1.4.jar
```

```
jcmd target/spring-petclinic-crac-3.1.4.jar JDK.checkpoint
```

```
java -XX:CRaCRestoreFrom=crac-files
```

# CRaC - OpenJDK (3)

---

CRaC is currently in an experimental state and has the following limitations:

- Works with Spring Boot 3.0 & 3.1
  - Patched Tomcat 10.1.7 is available
- Support for Spring Boot 3.2 is in progress
  - Spring Framework 6.1.0-SNAPSHOT
- Does not work on Windows or on macOS
  - Does not work in Docker containers via WSL (yet)
- But works in VM with Ubuntu 22.04 LTS

Other JVM Vendors have similar features e.g. OpenJ9 with CRIU support.




# Virtual Threads

---

A thread is the smallest unit of processing that can be scheduled. It runs concurrently with — and largely independently of — other such units. It's an instance of `java.lang.Thread`. There are two kinds of threads, platform threads and virtual threads.

```
sdk use java 21-librca  
  
mvn spring-boot:build-image  
  
docker run -e spring.threads.virtual.enabled=true \  
-p 8080:8080 -t spring-petclinic-virtual-threads:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
62.6s	402MB	4.381s	296MB	1996/s	443MB	20ms	58ms	110ms

# Summary



# Summary

---

- No Optimizations with JDK 17 & JDK 20 & JDK 21
- JVM Tuning
- Lazy Spring Beans
- No Spring Boot Actuators
- Fix Spring Boot Config Location
- Disabling JMX
- Dependency Cleanup
- Ahead-of-Time Processing (AOT)
- JLink
- Other JVMs (Eclipse OpenJ9, GraalVM, OpenJDK with CRaC)
- GraalVM Native Image

# Conclusions

# Conclusions (1)

## CPUs

---

- Your application might not need a full CPU at runtime
- It will need multiple CPUs to start up as quickly as possible (at least 2, 4 are better)
- If you don't mind a slower startup you could throttle the CPUs down below 4

See: <https://spring.io/blog/2018/11/08/spring-boot-in-a-container>

# Conclusions (2)

## Throughput

---

- Every application is different and has different requirements
- Using proper load testing can help to find the optimal configuration for your application

# Conclusions (3)

## Other Runtimes

---

- CRIU Support for OpenJDK and OpenJ9 is promising
- GraalVM Native Image is a great option for Java applications
  - But build times are long
  - The result is different from what you run in your IDE
- Eclipse OpenJ9 is a great option for running apps with less memory
  - But startup times are longer than with HotSpot
- Depending on the distribution, you might get other interesting features
  - Oracle GraalVM Enterprise Edition, Azul Platform Prime, IBM Semeru Runtime, ...

# Conclusions (4)

## Other Ideas

---

- Using an Obfuscator like ProGuard
- App CDS (Class Data Sharing)
- Importing `AutoConfiguration` classes individually
- Using functional bean definitions
- Spring Context Indexer (removed from Spring Boot 3.2)
- More JVM tuning
- Project Leyden

See also: <https://spring.io/blog/2019/01/21/manual-bean-definitions-in-spring-boot>

# A Few Simple Optimizations Applied

1. **Constant Folding**

```
int x = 10;
int y = 20;
int z = x + y;
int w = z * 2;
```

2. **Dead Code Elimination**

```
int x = 10;
int y = 20;
if (x < 0) {
    int z = x + y;
    int w = z * 2;
}
```

3. **Common Subexpression Elimination**

```
int x = 10;
int y = 20;
int z = x + y;
int w = x + y;
```

4. **Loop Invariant Code Motion**

```
int x = 10;
int y = 20;
for (int i = 0; i < 10; i++) {
    int z = x + y;
    int w = z * 2;
}
```

5. **Basic Block Merging**

```
int x = 10;
int y = 20;
if (x < 0) {
    int z = x + y;
    int w = z * 2;
} else {
    int z = x + y;
    int w = z * 2;
}
```

# A Few Simple Optimizations Applied (1)

---


- Dependency Cleanup
  - DB Drivers, Spring Boot Actuator, Jackson, Tomcat Websocket, ...
- Bellsoft Buildpack
- JLink
- JVM Parameters (java-memory-calculator)
- Spring AOT
- Lazy Spring Beans
- Fix Spring Boot Config Location



# A Few Simple Optimizations Applied (2)

---

```
sdk use java 17.0.8-librca  
  
mvn spring-boot:build-image  
  
docker run -p 8080:8080 \  
-e spring.aot.enabled=true \  
-e spring.main.lazy-initialization=true \  
-e spring.data.jpa.repositories.bootstrap-mode=lazy \  
-e spring.config.location=classpath:application.properties \  
-t spring-petclinic-optimized:3.1.4-SNAPSHOT
```

Build	Image Size	Startup	Initial RAM	Requests	RAM	99%	99.9%	99.99%
 56.6s	316MB	3.915s	292MB	1992/s	455MB	34ms	64ms	101ms
63s	136MB	1.841s	189MB	1997/s	356MB	27ms	61ms	97ms

**Did I miss something?** 🧐

**Let me/us know!** 🙋

**... or not!** 🙊


# Lean Spring Boot

## Applications for The Cloud

Patrick Baumgartner  
42talents GmbH, Zürich, Switzerland


@patbaumgartner  
patrick.baumgartner@42talents.com

<https://github.com/patbaumgartner/lean-spring-boot-applications-for-the-cloud>



# Container start to application ready (milliseconds)

Webapp on Azure Container Apps with 1 CPU 2G memory



# Different tradeoffs

	Instant startup with peak performance	Require upfront deployment and checkpoint storage	Compatibility	Run on low resource devices	Compilation time	Compact packaging	Performance
GraalVM native image	Yes	No	Reachability Metadata	Yes	Slow	Yes	CE EE
CRaC JVM image	Yes	Yes for now <sup>1</sup>	Regular JVM <sup>2</sup>	No	Fast	JVM + checkpoint image	Regular JVM

<sup>1</sup> Build-time checkpoint could lift this requirement

<sup>2</sup> Can require custom checkpoint handling for specific use cases