Understanding Buildpacks

A Deep Dive Into Their Functionality

Patrick Baumgartner
42talents GmbH, Zürich, Switzerland

@patbaumgartner
patrick.baumgartner@42talents.com

Abstract

Understanding Buildpacks: Delving Deep into Their Functionality

Cloud Native Buildpacks make it easier for developers to create container images, offering a seamless experience with built-in features such as rebasing, reproducibility, and support for multiple entry points. In this talk, we begin by covering the basics of Buildpacks, looking at their architecture and the benefits they bring compared to traditional methods of building container images.

We'll then explore the lifecycle component, which is the central binary of Cloud Native Buildpacks. It shows how it manages the conversion of source code into OCI images and oversees the various stages of the build process, including detection, installation, and export.

We will also discuss the Paketo Buildpacks project, emphasizing its flexibility and community focus. This section will show how Paketo improves the developer experience by offering a curated selection of buildpacks that make configuration easier and enhance performance. Additionally, we'll share real-world examples of how organizations are using Buildpacks to streamline their CI/CD pipelines and speed up their deployment cycles. To wrap up, we'll go over some best practices for integrating Buildpacks into your workflows, providing tips on maximizing their features for better performance and security.

Understanding Buildpacks: Delving Deep into Their Functionality

Patrick Baumgartner
42talents GmbH, Zürich, Switzerland

@patbaumgartner
patrick.baumgartner@42talents.com

Who am I?

Patrick Baumgartner

Technical Agile Coach @ **42talents**

My focus is on the **development of software solutions *with* humans**.

Coaching, Architecture, Development, Reviews, and Training.

Lecturer @ **Zurich University of Applied Sciences ZHAW**

Co-Organizer of **Voxxed Days Zurich**, **JUG Switzerland**, Java Champion, Oracle ACE Pro Java ...

@patbaumgartner

Agenda

Agenda

1. What Are Containers, Really?
2. What Are Cloud Native Buildpacks?
3. Comparing Buildpacks to Dockerfiles
4. Buildpacks CLI and CA Certificate Integration
5. Software Supply Chain: SBOM and Observability
6. Advanced Java Buildpack Features
7. Customizing and Reusing Buildpacks
8. Paketo Buildpacks Overview
9. Integrating Buildpacks into CI/CD Pipelines

What Are Containers, Really?

What Are Containers, Really?

- Isolated processes using Linux primitives: `chroot`, `namespaces`, and `cgroups`
- Provide filesystem, resource, and process isolation
- Lightweight, fast to start, and portable
- Run on any host with a container runtime like Docker or containerd



What Are Cloud Native Buildpacks?



Buildpacks.io

What Are Cloud Native Buildpacks?

- Convert source code into OCI-compliant images
- Automatically detect app type and required dependencies
- No Dockerfile needed
- Originated at Heroku, now under CNCF
- Co-developed by Pivotal/VMware and Heroku



paketo

buildpacks

Your app,
in your favorite language,
ready to run in the cloud

Why Cloud Native Buildpacks Are Relevant Today

- Simplifies building container images without Dockerfiles
- Ensures consistent builds across teams and environments
- Enhances security via curated and updatable buildpacks
- Accelerates CI/CD with reproducible builds
- Integrates smoothly into modern DevOps workflows


PaaS
Platforms
CI/CD
Tools
Local Dev
Tools
Buildpacks
OCI Images
Container
Registries

Widespread Ecosystem Adoption

- **PaaS Platforms:** Heroku, Fly.io, Cloud Foundry, Google Cloud Run, DigitalOcean, Azure Container Apps, Epinio, etc.
- **CI/CD Tools:** GitHub Actions, CircleCI, GitLab, Jenkins, Tekton, etc.
- **Local Dev Tools:** Spring Boot, Quarkus, Pack CLI, Maven/Gradle, kpack, Skaffold, etc.
- **Container Registries:** Docker Hub, GCR, ECR, etc. (OCI-compliant images)

> From source code to production-ready container image, standardized and Dockerfile-free. Buildpacks automate and unify application delivery.

Cloud Native Buildpacks

475 followers https://buildpacks.io

Pinned

pack Public
CLI for building apps using Cloud Native Buildpacks
Go 2.7k 303

spec Public
Specification for Cloud Native Buildpacks
Shell 259 71

lifecycle Public
Reference implementation of the Cloud Native Buildpacks lifecycle
Go 194 115

rfcs Public
RFCs for Cloud Native Buildpacks
Shell 58 74

community Public
Community content for the Cloud Native Buildpacks (CNB) project
47 24

samples Public
Samples for Cloud Native Buildpacks
Shell 208 151

Why Choose Buildpacks Instead of Dockerfiles?

The Dockerfile Tax

- N teams × 2–4 services each = Dockerfile sprawl
- Every team picks a different base image, JDK vendor, and OS
- One critical CVE → rebuild, retest, redeploy **every single service**
- No consistency in memory settings, user, or signal handling
- Knowledge is locked in tribal lore, not in code

This is not a technical problem. It is an organisational one at scale.

> "Your Dockerfile might be fine. But do you trust the 47 other ones in your mono-repo?"

The Limitations of Dockerfiles

This is what a *senior* developer writes:

```
FROM eclipse-temurin:25-jdk-noble AS build
WORKDIR /app
COPY . .
RUN ./mvnw -q package -DskipTests

FROM eclipse-temurin:25-jre-noble
RUN addgroup --system app && adduser --system --ingroup app app
WORKDIR /app
COPY --from=build /app/target/*.jar app.jar
USER app
EXPOSE 8080
HEALTHCHECK CMD curl -f http://localhost:8080/actuator/health || exit 1
ENTRYPOINT ["java", "-jar", "app.jar"]
```

Still missing: memory calculator, CA certificate injection, SBOM, reproducible layers, signal handling (`tini`), JVM ergonomics for containers, automatic base-image patching.

See: https://snyk.io/blog/10-best-practices-to-containerize-nodejs-web-applications-with-docker/
Understanding Buildpacks

Reproducibility: Dockerfiles vs. Buildpacks

Dockerfiles are non-deterministic by design:

```
RUN apt-get install -y curl   # resolves differently on different days
FROM ubuntu:latest            # "latest" drifts silently
```

- Two builds from identical source → **different image digests**
- Breaks audit trails, supply chain attestations, and rollback guarantees

Buildpacks produce reproducible images:

- Same source + same builder = **identical OCI digest** every time
- Layers are content-addressed and cached precisely
- Builder version is explicit and pinnable:

```
pack build my-app \
  --builder paketobuildpacks/builder-noble-java-tiny:0.0.8
```

Image Size & CVE Reality Check

Approach	Compressed size	CVEs (Trivy)
`FROM openjdk` (naive)	~650 MB	200+
Multi-stage + `eclipse-temurin:jre`	~250 MB	40–80
Paketo `builder-noble-java-tiny`	~180 MB	< 10
Distroless + jlink (`distroless-buildpack-builder-java-tiny`)	~80–140 MB	0 (no shell, no pkgmgr)

- **Smaller = faster pull, faster start, smaller blast radius**
- Distroless: no shell means attackers can't `exec` in even if they break the app
- Paketo rebuilds the run image nightly and patches CVEs **without a code change**

```
# Scan yourself — no excuses
trivy image my-app
```

The Buildpacks CLI: Simplicity in Action

```
pack builder suggest
```

Google Cloud Buildpacks:

```
pack build my-app --builder gcr.io/buildpacks/builder
```

Paketo Buildpacks:

```
pack build my-app --builder paketobuildpacks/builder-jammy-base # Ubuntu 22.04 LTS

# Alternatively

pack build my-app --builder paketobuildpacks/builder-noble-java-tiny # Ubuntu 24.04 LTS
```

Spring Boot Maven Plugin:

```
./mvnw spring-boot:build-image
```

```
Calculating JVM memory based on 22818584K available memory
For more information on this calculation, see https://paketo.io/docs/reference/java-reference/#memory-calculator
Calculated JVM Memory Configuration: -XX:MaxDirectMemorySize=10M -Xmx22176385K -XX:MaxMetaspaceSize=130198K -XX:ReservedCodeCacheSize=240M -Xss1M
  (Total Memory: 22818584K, Thread Count: 250, Loaded Class Count: 20573, Headroom: 0%)
Enabling Java Native Memory Tracking
Adding 146 container CA certificates to JVM truststore
Spring Cloud Bindings Enabled
Picked up JAVA_TOOL_OPTIONS: -Djava.security.properties=/layers/paketo-buildpacks_bellsoft-liberica/java-security-properties/java-security.properties
 -XX:+ExitOnOutOfMemoryError -XX:AOTCache=/layers/patbaumgartner_aot-cache/aot-cache/app.aot
 -XX:MaxDirectMemorySize=10M -Xmx22176385K -XX:MaxMetaspaceSize=130198K -XX:ReservedCodeCacheSize=240M -Xss1M -XX:+UnlockDiagnosticVMOptions
 -XX:NativeMemoryTracking=summary -XX:+PrintNMTStatistics -Dorg.springframework.cloud.bindings.boot.enable=true


              |\      _,,,--,,_
             /,`.-'`'   ._  \-;;,_
  _______ __|,4-  ) )_   .;.(__`'-'__     ___ __    _ ___ _______
 |       | '---''(_/._)-'(_\_)   |   |   |   |  |  | |   |       |
 |    _  |    ___|_     _|       |   |   |   |  |_| |   |       | __ _ _
 |   |_| |   |___  |   | |       |   |   |   |       |   |       | \ \ \ \
 |    ___|    ___| |   | |      _|   |___|   |  _    |   |      _|  \ \ \ \
 |   |   |   |___  |   | |     |_|       |   | | |   |   |     |_    ) ) ) )
 |___|   |_______| |___| |_______|_______|___|_|  |__|___|_______|  / / / /
 ==========================================================================/_/_/_/

:: Built with Spring Boot :: 4.0.5


2026-04-23T18:50:45.429Z  INFO 1 --- [           main] o.s.s.petclinic.PetClinicApplication     : Starting PetClinicApplication v4.0.0-SNAPSHOT using Java 25.0.1 with PID 1
  (/workspace/BOOT-INF/classes started by cnb in /workspace)
2026-04-23T18:50:45.431Z  INFO 1 --- [           main] o.s.s.petclinic.PetClinicApplication     : No active profile set, falling back to 1 default profile: "default"
2026-04-23T18:50:46.163Z  INFO 1 --- [           main] .s.d.r.c.RepositoryConfigurationDelegate : Bootstrapping Spring Data JPA repositories in DEFAULT mode.
2026-04-23T18:50:46.213Z  INFO 1 --- [           main] .s.d.r.c.RepositoryConfigurationDelegate : Finished Spring Data repository scanning in 41 ms. Found 3 JPA repository interfaces.
2026-04-23T18:50:46.725Z  INFO 1 --- [           main] o.s.boot.tomcat.TomcatWebServer          : Tomcat initialized with port 8080 (http)
2026-04-23T18:50:46.735Z  INFO 1 --- [           main] o.apache.catalina.core.StandardService   : Starting service [Tomcat]
2026-04-23T18:50:46.735Z  INFO 1 --- [           main] o.apache.catalina.core.StandardEngine    : Starting Servlet engine: [Apache Tomcat/11.0.21]
2026-04-23T18:50:46.765Z  INFO 1 --- [           main] b.w.c.s.WebApplicationContextInitializer : Root WebApplicationContext: initialization completed in 1275 ms
2026-04-23T18:50:46.924Z  INFO 1 --- [           main] com.zaxxer.hikari.HikariDataSource       : HikariPool-1 - Starting...
2026-04-23T18:50:49.347Z  INFO 1 --- [           main] com.zaxxer.hikari.pool.HikariPool        : HikariPool-1 - Added connection conn0: url=jdbc:h2:mem:d5ad0118-b3ba-4ada-abfb-88acb20f9168 user=SA
2026-04-23T18:50:49.348Z  INFO 1 --- [           main] com.zaxxer.hikari.HikariDataSource       : HikariPool-1 - Start completed.
2026-04-23T18:50:49.470Z  INFO 1 --- [           main] org.hibernate.orm.jpa                    : HHH008540: Processing PersistenceUnitInfo [name: default]
2026-04-23T18:50:49.497Z  INFO 1 --- [           main] org.hibernate.orm.core                   : HHH000001: Hibernate ORM core version 7.2.12.Final
2026-04-23T18:50:49.751Z  INFO 1 --- [           main] o.s.o.j.p.SpringPersistenceUnitInfo      : No LoadTimeWeaver setup: ignoring JPA class transformer
2026-04-23T18:50:49.775Z  INFO 1 --- [           main] org.hibernate.orm.connections.pooling    : HHH10001005: Database info:
2026-04-23T18:50:50.272Z  INFO 1 --- [           main] org.hibernate.orm.core                   : HHH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA platform integration)
2026-04-23T18:50:50.276Z  INFO 1 --- [           main] j.LocalContainerEntityManagerFactoryBean : Initialized JPA EntityManagerFactory for persistence unit 'default'
2026-04-23T18:50:50.327Z  INFO 1 --- [           main] o.s.d.j.r.query.QueryEnhancerFactories   : Hibernate is in classpath; If applicable, HQL parser will be used.
2026-04-23T18:50:50.904Z  INFO 1 --- [           main] o.s.b.a.e.web.EndpointLinksResolver      : Exposing 13 endpoints beneath base path '/actuator'
2026-04-23T18:50:50.962Z  INFO 1 --- [           main] o.s.boot.tomcat.TomcatWebServer          : Tomcat started on port 8080 (http) with context path '/'
2026-04-23T18:50:50.970Z  INFO 1 --- [           main] o.s.s.petclinic.PetClinicApplication     : Started PetClinicApplication in 5.886 seconds (process running for 3.908)
```

Adding CA Certificates with Dockerfiles

```
FROM openjdk

COPY custom-ca.crt /app
RUN keytool -importcert -file /app/custom-ca.crt
COPY target/*.jar /app/app-runner.jar

WORKDIR /app

EXPOSE 8080

ENTRYPOINT [ "java","-jar" ]

CMD ["app-runner.jar" ]
```

Adding CA Certificates with Buildpacks

```
mkdir -p bindings/ca-certificates/certs
echo "ca-certificates" > bindings/ca-certificates/type
cp my-cert.crt bindings/ca-certificates/my-cert.crt
```

```
bindings/
└── ca-certificates/
    ├── type            # file contains: ca-certificates
    └── my-cert.crt
```

```
pack build my-app \
  --builder paketobuildpacks/builder-jammy-base \
  --volume "$(pwd)/bindings:/platform/bindings"
```

```
BellSoft Liberica JDK 25.0.1: Contributing to layer
  Downloading from https://github.com/bell-sw/Liberica/releases/download/25.0.1+13/bellsoft-jre25.0.1+13-linux-amd64.tar.gz
  Verifying checksum
  Expanding to /layers/paketo-buildpacks_bellsoft-liberica/jdk
  Adding 147 container CA certificates to JVM truststore
```

> Imagine if building your Go, Node.js, and Python apps with buildpacks were that simple.

The Basics of Cloud Native Buildpacks

Buildpacks Architecture

- **BuildImage and RunImage**: Base OS (e.g. Ubuntu) → Stack (deprecated)
- **Buildpacks:** Language/runtime logic (Node.js, Java, etc.)
- **Lifecycle:** Orchestrates the build
- **Builder:** All of the above in one image

How Buildpacks Work



- **buildpack.toml:** Provides metadata for buildpacks
- **Detect:** Identify the app type and required dependencies
- **Build:** Install dependencies and create the image

Anatomy of a Buildpack

- `bin/detect`
  - Runs against source to determine if the buildpack is applicable
  - Example:
    - A Java CNB might look for `.java` files or a `.jar`
    - A Node.js CNB might look for `package.json`
- `bin/build`
  - Downloads build-time and run-time dependencies
  - Example:
    - A Java CNB might download a JDK or JRE
    - Compiles sources (if needed)
    - Sets launch command and environment variables

Lifecycle Phases (Create)

The buildpack lifecycle is split into phases. Each plays a critical role in image creation.

- **Analyze:** Provides metadata from previous builds to buildpacks.
- **Detect:** Selects compatible buildpacks and creates a build plan.
- **Restore:** Retrieves cached data from earlier builds.
- **Build:** Rebuilds only the layers that need updating.
- **Export:** Replaces outdated layers with the newly built ones.


builder.toml
Builder
buildpack.toml
Buildpack A
Buildpack B
Buildpack C
Stack (deprecated)
Run Image
Build Image

Customizing and Reusing Buildpacks

- **Why customize?**
  - Select a specific JVM vendor or version (e.g. Adoptium, BellSoft)
  - Add CA certificates for internal services
  - Configure Maven or Gradle to use internal repositories or proxies
  - Extend functionality with custom environment variables or bindings
- **Keep your image updated:**
  - Rebase your image with the latest run image (no rebuild needed)
  - `pack rebase my-app`
- **Browse available buildpacks:** https://registry.buildpacks.io

CVE in the Base OS? Rebase, Don't Rebuild.

A critical vulnerability is patched in Ubuntu. With Dockerfiles:

1. Identify every affected service (good luck)
2. Trigger rebuilds across 50 repositories
3. Re-run full test suites
4. Redeploy everything

With buildpacks — seconds, no code change needed:

```
# Swap the run image layer. App layer is untouched.
pack rebase my-app \
  --run-image paketobuildpacks/run-noble-base:latest
```

- Only the OS layer is replaced — the app layer is **reused as-is**
- Image digest changes; provenance attestation is updated automatically
- Works at scale: one script, every image in your registry

paketo

buildpacks

Paketo Buildpacks Overview

- **Available in 3 variants:**
  - **Base** – Core buildpacks for major languages
  - **Tiny** – Minimal footprint, ideal for small apps or functions
  - **Static** – Static linked libraries
- **Broad language support:**
  - Java, Node.js, Python, Go, .NET, PHP, Ruby, Rust, and more
- **Rich feature set:**
  - Support for custom CA certificates
  - SBOM generation using Syft
  - OCI image annotations and additional labels
  - Arm64 and Red Hat UBI compatibility

Software Bill of Materials (SBOM) Support

```
pack sbom download my-app --output-dir ./my-app-sbom
```

```
cat ./my-app-sbom/layers/sbom/launch/paketo-buildpacks_executable-jar/sbom.cdx.json | \
  jq '.components[] | select(.name=="jackson-databind")'
```


```
{
  "bom-ref": "pkg:maven/tools.jackson.core/jackson-databind@3.0.3?package-id=a8ec16fa583e2012",
  "cpe": "cpe:2.3:a:jackson-databind:jackson-databind:3.0.3:*:*:*:*:*:*:*",
  "externalReferences": [
    {
      "hashes": [
        {
          "alg": "SHA-1",
          "content": "c024f05711e311341d4338cbb7905696e20921f8"
        }
      ],
      "type": "build-meta",
      "url": ""
    }
```

Observability Without Instrumentation Code

Paketo Java buildpacks inject observability tooling at **build time** — no library dependencies in your source code.

JMX — expose MBeans to any JMX-compatible tool:

```
docker run -p 8080:8080 -p 5000:5000 \
  -e BPL_JMX_ENABLED=true \
  -e BPL_JMX_PORT=5000 \
  my-app
```

Spring Boot Actuator — already wired in automatically when detected on the classpath:

```
curl http://localhost:8080/actuator/health
curl http://localhost:8080/actuator/metrics
```

OpenTelemetry — inject the agent via a binding, zero code change:

```
mkdir -p bindings/opentelemetry
echo "OpenTelemetry" > bindings/opentelemetry/type
echo "https://otel-collector:4317" > bindings/opentelemetry/endpoint

pack build my-app --volume "$(pwd)/bindings:/platform/bindings"
```

Advanced Features in Java Buildpacks

- Set JVM version using `BP_JVM_VERSION`
- Easy Java vendor selection using buildpack order

```
<buildpacks>
  <buildpack>gcr.io/paketo-buildpacks/adoptium</buildpack>
  <buildpack>urn:cnb:builder:paketo-buildpacks/java</buildpack>
</buildpacks>
```

- Optimizations for Spring Boot (AOT, CDS, Cloud Bindings) and memory management (memory calculator)
- jlink and JMX support
- Native image support with GraalVM

BP_* and BPL_* Environment Variables

- **`BP_*`** – **Build-time** variables; passed via `--env` or `<env>` in `pom.xml`; configure what the buildpack produces
- **`BPL_*`** – **Launch-time** variables; set at `docker run` or in Kubernetes; tune runtime behaviour without rebuilding

Variable	Phase	Purpose
`BP_JVM_VERSION`	Build	JDK version to install
`BP_JVM_JLINK_ENABLED`	Build	Create a custom JRE with jlink
`BP_SPRING_AOT_ENABLED`	Build	Enable Spring AOT processing
`BPL_JMX_ENABLED`	Launch	Enable JMX
`BPL_DEBUG_ENABLED`	Launch	Enable remote debugger (JDWP)
`BPL_DEBUG_PORT`	Launch	Debugger port (default `8000`)

```
# Remote debug a running container
docker run -p 8080:8080 -p 8000:8000 -e BPL_DEBUG_ENABLED=true -e BPL_DEBUG_PORT=8000   my-app
```

Demo

Challenges & Solutions

Patching the Base Image

- Base images do not contain fonts 😔

```
FROM paketobuildpacks/run-jammy-base:latest

USER root

## Idea from: https://blog.adoptopenjdk.net/2021/01/prerequisites-for-font-support-in-adoptopenjdk/
RUN apt-get update \
  && apt-get install -y --no-install-recommends \
  wget \
  fontconfig \
  && rm -rf /var/lib/apt/lists/*

# Install Noto Emoji Manually
RUN mkdir -p /usr/share/fonts/truetype/noto \
  && cd /usr/share/fonts/truetype/noto \
  && wget https://github.com/googlefonts/noto-emoji/raw/9a5261d871451f9b5183c93483cbd68ed916b1e9/fonts/NotoEmoji-Regular.ttf \
  && fc-cache -fv

USER cnb
```

When to Create a Custom Buildpack

- Custom JDK Version & JVM Tuning
- Application Configuration Injection
- Metrics/Monitoring Integration
- License Compliance
- Logging Configuration

```
pack buildpack new io.example/my-buildpack \
  --path ./my-buildpack

pack build my-app \
  --buildpack ./my-buildpack \
  --builder paketobuildpacks/builder-jammy-base
```

Custom Builder

- Using a custom builder for a custom base-image and run-image (stack)
- Allows a (pre-)selection of buildpacks to be used

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <builder>patbaumgartner/buildpack-builder:noble</builder>
    </image>
  </configuration>
</plugin>
```

Distroless Builder for Java

- Build stack: **Ubuntu 24.04** – full toolchain for compiling Java apps
- Run stack: **`gcr.io/distroless/cc:nonroot`** – no shell, no package manager, non-root
- Supports: **JVM** and **GraalVM Native Image**
- Images published to GHCR with **SLSA provenance** attestations

```
<!-- pom.xml – Spring Boot Maven Plugin -->
<image>
  <builder>ghcr.io/patbaumgartner/distroless-buildpack-builder-java-tiny:latest</builder>
  <env>
    <BP_JVM_JLINK_ENABLED>true</BP_JVM_JLINK_ENABLED>
  </env>
</image>
```

See: https://github.com/patbaumgartner/distroless-buildpack-builder-java-tiny

Custom Java Buildpacks

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <buildpacks>
        <!-- <buildpack>gcr.io/paketo-buildpacks/adoptium:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/alibaba-dragonwell:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/amazon-corretto:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/azul-zulu:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/bellsoft-liberica:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/eclipse-openj9:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/graalvm:latest</buildpack> -->
        <!-- <buildpack>gcr.io/paketo-buildpacks/sap-machine:latest</buildpack> -->
        <buildpack>gcr.io/paketo-buildpacks/oracle:latest</buildpack>
        <!-- Used to inherit all the other buildpacks -->
        <buildpack>urn:cnb:builder:paketo-buildpacks/java</buildpack>
      </buildpacks>
    </image>
  </configuration>
</plugin>
```

JLink

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <buildpacks>
        <buildpack>gcr.io/paketo-buildpacks/java:latest</buildpack>
      </buildpacks>
      <env>
        <BP_JVM_JLINK_ENABLED>true</BP_JVM_JLINK_ENABLED>
        <BP_JVM_JLINK_ARGS>--add-modules
          java.base,java.compiler,java.desktop,java.instrument,java.net.http,java.prefs,java.rmi,
          java.scripting,java.security.jgss,java.sql.rowset,jdk.jfr,jdk.management,jdk.net,jdk.unsupported
          --compress=zip-6 --no-header-files --no-man-pages --strip-debug</BP_JVM_JLINK_ARGS>
      </env>
    </image>
  </configuration>
</plugin>
```

AOT and App CDS (< Java 25)

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <buildpacks>
        <buildpack>gcr.io/paketo-buildpacks/java:latest</buildpack>
      </buildpacks>
      <env>
        <BP_JVM_CDS_ENABLED>true</BP_JVM_CDS_ENABLED>
        <BP_SPRING_AOT_ENABLED>true</BP_SPRING_AOT_ENABLED>
      </env>
    </image>
  </configuration>
  <executions>
    <execution>
      <id>process-aot</id>
      <goals>
        <goal>process-aot</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

AOT and AOT Caching (>= Java 25)

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <configuration>
    <image>
      <buildpacks>
        <buildpack>gcr.io/paketo-buildpacks/java:latest</buildpack>
      </buildpacks>
      <env>
        <BP_SPRING_AOT_ENABLED>true</BP_SPRING_AOT_ENABLED>
        <BP_JVM_AOTCACHE_ENABLED>true</BP_JVM_AOTCACHE_ENABLED>
        <TRAINING_RUN_JAVA_TOOL_OPTIONS>-Dtelegrambots.enabled=false</TRAINING_RUN_JAVA_TOOL_OPTIONS>
      </env>
    </image>
  </configuration>
  <executions>
    <execution>
      <id>process-aot</id>
      <goals>
        <goal>process-aot</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

Integrating Buildpacks into CI/CD Pipelines

- **Choose the Right Buildpacks**
  - Use only officially maintained and security-audited buildpacks.
- **Automate Security Scans**
  - Integrate static and dynamic security scans immediately after the build process.
- **Optimize Caching and Layer Reuse**
  - Enable buildpack-specific caching to avoid redundant steps.
- **Ensure Versioning and Traceability**
  - Explicitly document and version the buildpacks used in your CI configuration.
- **Integrate Observability and Metrics**
  - Continuously monitor build durations, error rates, and artifact sizes.

Summary and Key Takeaways

Why Use Cloud Native Buildpacks?

- No Dockerfile needed
- Focus on providing value to the end users
- Composable (Node.js, Bash, Java, Python, ...)
- Build any app with the same set of buildpacks
- Only rebuild layers that have changed
- Rebasing without rebuilding (put your app on a new base layer)

Q&A

I ❤ Feedback 🙏

Understanding Buildpacks:

Delving Deep into Their Functionality

Patrick Baumgartner
42talents GmbH, Zürich, Switzerland

@patbaumgartner
patrick.baumgartner@42talents.com

	Cloud Native Buildpacks	Dockerfile	source-to-image (s2i)	Jib	ko
Advanced Caching	Yes	No	Yes	No	Yes
Auto-detection	Yes	No	Yes	Yes	Yes
Bill-of-Materials	Yes	No	No	No	Yes
Modular / Pluggable	Yes	No	No	N/A †	N/A †
Multi-language	Yes	Yes	Yes	No	No
Multi-process	Yes	No	No	No	No
Minimal app image	Yes	Yes ♦	Yes ‡	Yes	Yes
Rebasing	Yes	No	No	No	No
Reproducibility	Yes	No	No	Yes	Yes
Reusability	Yes	No	Yes	N/A †	N/A †

Resources

Official Documentation and Tools

- Cloud Native Buildpacks (CNCF)
- Paketo Buildpacks
- Buildpacks Registry
- Spring Boot Buildpacks Integration
- Pack CLI Docs
- GraalVM Native Image Support
- Syft – SBOM Generation
- Snyk Docker Best Practices
- Datadog Java Integration
- What has changed on how we ship the Builders and the base images