



ROBOBIST P-SERIES · AUTONOMOUS PALLET TRUCK

P1000

High Compatibility. Fearless of Pallet Types.

- 1 Compatible with Various Pallets**
 Handles open pallets, closed pallets, and custom formats. No pallet left behind — worry-free handling across your entire fleet.
- 2 1,200 mm Slim Body, 1T Load Capacity**
 Ultra-slim 1,200 mm vehicle width with a rated load capacity of 1,000 kg. Minimum aisle width of just 1,300 mm for smooth passage in narrow aisles.
- 3 AI Deep Learning — Multi-Carrier Recognition**
 Recognizes pallets in various specifications, different colors, wrapped or damaged pallets, and racks. Adaptive multi-angle recognition with high-precision loading.
- 4 4 Navigation Options, ±10 mm Accuracy**
 Supports SLAM, reflector, NFL, and hybrid navigation. Repeat positioning accuracy up to ±10 mm — covering all warehouse navigation scenarios.
- 5 Flexible Customization — 4 Options**
 Fork width, vehicle height, color scheme, and co-branding. Fully adaptable to your warehouse standards and corporate identity.

BASIC PARAMETERS

Product Model	Robobist P1000
Product Series	P-Series — Autonomous Pallet Trucks
Operation Type	Automatic Navigation
Navigation Type	Laser SLAM
Pallet Type	Open Pallet / Closed Pallet
Rated Load Capacity	1,000 kg
Load Center Distance	100 mm
Weight (with battery)	450 kg
Standard Lifting Height	190 mm
Forklift Dimensions L×W×H	1,450 × 1,200 × 556 mm
Fork Dimensions L×W×H	1,220 × 168 × 60 mm
Fork Outer Width	610 mm
Minimum Turning Radius	900 mm
Ambient Temp / Humidity	0°C – 50°C / 10–90% RH

PERFORMANCE

Driving Speed (Full & No Load)	1.1 m/s
Passability (Slope / Step / Gap)	< 3% / 5 mm / 10 mm
Navigation Position Accuracy	±10 mm
Navigation Angle Accuracy	±1°

BATTERY


Battery Specifications	48V / 36Ah LiFePO4
Battery Life	8 hours
Charging Time (10% → 80%)	1.5 hours
Charging Method	Manual / Automatic

FUNCTION CONFIGURATIONS

Lidar	1× H1E0 / Mid-360 + 4× C213
Wi-Fi Roaming	● Standard
3D Obstacle Avoidance	○ Optional
Pallet Recognition AI	○ Optional
HMI Display	● Standard
E-Stop Button	● Standard
Sound & Light Indicator	● Standard

SAFETY

Braking Distance at 1.0 m/s	≤ 30 cm
Braking Distance at 1.5 m/s	≤ 50 cm
360° Laser Protection	● Standard
Bumper Strip	○ Optional
Fork Height Protection	● Standard



KEY DIMENSIONS

Overall L×W×H	1,450 × 1,200 × 556 mm
Fork Length	1,220 mm
Fork Width	610 mm
Fork Height	60 mm
Min. Aisle Width	1,300 mm
Turn Radius	900 mm